



**COMSATS University Islamabad (CUI), Lahore Campus**  
**Defence Road, Off Raiwind Road, Lahore**

CUI-LHR-TN-25-1883

## Invitation to Bid

### *For Procurement of*

**4456-Plumbing, Paint, Masonry, Carpentry, Welding, Telephone Exchange etc. and Poshish Items, CUI-Lahore Campus**

<b>Category of procurement</b>	Goods
<b>Procurement Method/ Procedure</b>	Open Competitive Bidding/ <b>Single Stage One Envelope Procedure</b>
<b>Submission Type</b>	By Uploading File on PPRA EPADS
<b>Tender Fee</b>	<b>Rs. 2,500/-</b> as per clause # 5 & 6 <i>also email the Scan Tender Fee Draft only on emails; asifullah@cuilahore.edu.pk, mshahid@cuilahore.edu.pk, pms@cuilahore.edu.pk</i>
<b>Bid Security Amount</b>	<b>Rs. 193,300/-</b> as per clause # 5 & 6 <i>also email the Scan CDR Draft only on emails; asifullah@cuilahore.edu.pk, mshahid@cuilahore.edu.pk, pms@cuilahore.edu.pk</i>
<b>Bid Closing date/ time</b>	<b>December 19, 2025, 1400 hrs</b> (Bids will be opened after 30 minutes)
<b>Bid Validity days/ Date</b>	<b>60 Days</b>
<b>Delivery days (after PO issuance)</b>	<b>30 Days</b>
<b>Decision Criteria for awarding of contract / PO</b>	<b>Item wise basis</b>
<b>COMSATS University Islamabad, Lahore Campus, Tax Free Number (TFN)</b>	9013701-9
<b>Retention Money against warranty items (applicable or not applicable)</b>	<b>Not applicable</b>

**Part: A GENERAL TERMS AND CONDITIONS**

1. *All pages of bidding documents are mandatory to be signed / stamped before uploading at EPADS, meaning thereby bidder agrees to our terms & conditions mentioned herein, failing which the bid may be rejected.*
2. *Any addition, deletion or modification of any clause of the procurement terms & conditions/BoQs of CUI-Lahore Campus by any vendor will not be acceptable and may lead to rejection of the bid.*
3. *Only registered Suppliers, who are on Active Taxpayers List (ATL) of FBR (GST & Income Tax), are eligible to participate in tender.*

Signature & Stamp of Bidder

4. The contract will be executed and handed over in satisfactory conditions up to the entire satisfaction of COMSATS University Islamabad, Lahore Campus.
5. *The bidder is required to furnish tender fee (non-refundable) and earnest money in form of Bank deposit/ CDR / Pay order crossed in favor of “COMSATS University Islamabad, Lahore Campus”.*
6. *Bidders are advised to upload scan copy of bank instruments (tender fee and earnest money) at PPRA EPADS along with their respective bid. However, original bank instruments must be submitted before closing time of the tender. Any bid not accompanied with earnest money or tender fee shall be rejected without any right of appeal.*
7. *CUI-Lahore Campus will retain the 5 % amount, at the time of release of payment, as security against items where warranty is required in our BoQs. The retention money will be released after the warranty period subject to a satisfactory report by the end user. The warranty period will be counted from the date of delivery/supply or installation (as the case may be).*
8. Part / Advance payments is not allowed.
9. Your bid proposal should be **on F.O.R (Pak Rupees) inclusive of all applicable taxes and freight** to be delivered at COMSATS University Islamabad, Lahore Campus’s premises.
10. In case of any holiday is announced by the Govt. OR any unforeseeable circumstances that prevent the tender from being opened on the date announced (Force Majure Situation), the tenders will be opened on the very next working day. Timing will remain as mentioned in the tender notice.
11. After opening of bids, COMSATS University Islamabad, Lahore Campus will examine the bids for completeness as per tender document.
12. Multiple rates of an item may also lead to the rejection of bid / item.
13. In case more than one bidder have quoted same rates for an item; the bidder securing more items (in terms of cost) will be awarded the specific item.
14. The bid form (BoQs) must be duly filled in, stamped and signed by the authorized representative of the bidder.
15. Payment will be made as per PPRA rule on submission of Invoice in the name of “COMSATS University Islamabad, Lahore Campus” with a copy of delivery challan (s) after the complete order has been supplied, inspected and accepted which includes delivery / installation, and COMSATS acceptance / inspection thereof.
16. Applicable Income tax and GST will be deducted at source/as per rules. In case of exemption, please mention and attach the proper documentation duly verified from the concerned tax authorities/FBR; however, CUI will be final authority to accept or reject the exemption certificate. In case of rejection, CUI will deduct all applicable taxes as per tax rate. CUI will provide a certificate of tax deduction and the vendor may claim refunds from Tax Authorities/FBR.
17. **If the vendor fails to deliver the goods / services to COMSATS University Islamabad (CUI), Lahore Campus within the given deadline, following action may be taken by CUI Lahore Campus**
  - a. A late delivery charge of **1% of the total amount of the undelivered item** will be imposed for each day the delivery is delayed after the Purchase Order (PO) deadline.

- b. Once the penalty reaches the 10% maximum, the **PO may be cancelled**, and the **Call Deposit Receipt (CDR) / Earnest Money** will be confiscated.
- 18. If the delivered goods / services are not according to the required quality standards / specifications, the same shall be liable to be rejected after inspection. The vendor would be required to supply as per requirements mentioned in our BoQs, otherwise the purchase / work order will be cancelled after due date with confiscation of earnest money.
- 19. Any defective / sub-standard item (s) will be replaced by the bidder in same quoted cost. In case of failure to supply the specific item, CUI-Lahore may issue PO to next lowest bidder to supply the item while the difference of amount will be deducted from the 1st lowest bidder’s earnest money.
- 20. Withdrawal or any modification of the original offer within the validity period shall entitle CUI- Lahore to forfeit the earnest money in favor of the CUI-Lahore and / or put a ban on such vendor participation in tenders / works.
- 21. It is the sole responsibility of the agent / supplier / manufacturer to comply with the applicable laws, be national or international.
- 22. In case of any dispute or grievance, the matter shall be addressed as per PPRA rules.
- 23. The CUI-Lahore Campus reserves the right to modify the quantities of goods / services at any time before the award of purchase / work order.
- 24. CUI-Lahore Campus shall disqualify any firm(s), if at any stage; it finds that the information submitted, or documents provided are inaccurate, fake, ambiguous or incomplete.
- 25. COMSATS University Islamabad, Lahore Campus reserves the right to reject the bid if;
  - i. Received without earnest money and tender fee,
  - ii. The tender is unsigned/ unstamped
  - iii. The offer is ambiguous
  - iv. The offer is conditional
  - v. **The offer is from a firm, either which is black listed OR the firm / company is involved in litigation with Procuring Agency**
  - vi. The offer is received by telephone/telex/fax/telegram.
  - vii. Any unsigned / ambiguous erasing, cutting / overwriting etc. is made.
- 26. **Please also submit the affidavit that the neither company/firm is blacklisted nor involved in the litigation with Procuring Agency.**
- 27. CUI Lahore can initiate blacklisting proceedings against the bidder for irregularities or violations committed during bidding and contract execution. The blacklisting proceedings will be initiated in line with the reasons and mechanism for blacklisting and debarment as mentioned in PPRA SRO 460 (I)/ 2024 dated 28<sup>th</sup> March 2024.
- 28. The undersigned affirm that the terms and conditions as contained in this document have been read and accepted and that in the event of selection of my/our rate the agreement in the prescribed form will be entered into:

- **Company / Vendor Name:**.....
- **Postal Address:**.....
- **Tel. / Mobile:**.....**Email:**.....

- **NTN#** :.....**GST#**:.....**PGST#**:.....
- **Signature**: .....

Please also attach the Certificate supporting being Active Taxpayer as per requirement of FBR.

**Part B: BoQs of required item (s):**

<p><b>Vendors must provide both the unit and total price of each item and calculations must be made carefully to avoid mistakes. However, in case, the total price does not match the unit price and quantity due to a calculation error or typo error, any of the following can be opted:</b></p> <ol style="list-style-type: none"> <li>1. The bid may be rejected on the reason of ambiguity (OR)</li> <li>2. Unit price will be considered as final, and the total price of the respective item will be calculated by multiplying it by the quantity required. Sub-totals and grand totals will also be corrected accordingly</li> </ol> <p><b>Note:</b>  <i>Bidders are required to quote the rates for the quantities / measurement unit mentioned in our BoQ. It is strictly advised that no change in quantity/ measurement unit due to different packing size may be made/ written by the vendor while quoting the price. In case, vendor has some different packing size, the same may be converted /calculated as per our required quantity unit/packing size failing which bid/ item may be rejected.</i></p>							
<p>No change in the BoQs (Specs &amp; Qty.) of CUI-Lahore Campus as detailed below, is allowed. Any additional information may be mentioned in the blank columns (i.e., model/brand or Price). Any modification in CUI-Lahore Campus BoQ may lead to the rejection of the bid (fully or partially).</p>					<p><b>Rates to be quoted inclusive of all (applicable) taxes</b></p>		
Sr. #	Item Name & Specifications		Qty.		Quoted Model / Brand	Unit Price (Rs.)	Total Amount (Rs.)
	<b>Carpentry Item</b>						
1	Supply of Plywood sheet with a thickness of 18mm , made from high-quality wood fibers. a smooth selector ultraviolet finish, high tensile strength and load bearing capacity, moisture resistance, strong and long lasting with resistance to bending and warping. typically density 800 kg/m3#2060	Al noor or equivalent	No's	30			
2	Supply of Plywood sheet with a thickness of 18mm , made from high-quality wood fibers. a smooth selector ultraviolet finish, high tensile strength and load bearing capacity, moisture resistance, strong and long lasting with resistance to bending and warping. typically, density 800 kg/m3#1900	Al noor or equivalent	No's	10			

3	supply of laminated chipboard sheet measures 4 feet x 8 feet with a thickness of 18mm, made from high-density chipboard with a decorative high glossy laminate surface, high density of 600-800 kg/m <sup>3</sup> , moisture resistance ultraviolet finish suitable for indoor use, weighing approximately 30-40 kg per sheet, and is ideal for furniture, office desks, cabinets, and durability, scratch resistance, color beige grains	Al noor or equivalent	No's	10			
4	Supply of MDF Wooden Press # 2 (No. 2060)	Kmi or equivalent	No's	30			
5	Supply of simple lasani MDF 3/4 inch	kmi or equivalent	No's	15			
6	Supply of formica sheet white 8ft x 4ft	SONY or equivalent	No's	12			
7	Supply of soft board sheet 8ft x4ft	China or equivalent	No's	6			
8	Supply of Clear Glass 6 mm thick 8ft x 4ft	Ghani or equivalent	Sheet	4			
9	4.5' wide soft board cloth, made from premium, durable fabric designed for use on bulletin boards and textured surface.	Pak polyster, interwood or equivalent	Yard	40			
10	Supply of PVC trim 3/4 inch (2060) made from high-quality Polyvinyl Chloride .smooth surface , and UV-resistant, scratch-resistant.	Local	Length	100			
11	Supply of kail wood strip ( 1.5 inch x 0.5 inch x 7 ft ),made from high-quality, select-grade wood with a smooth, sanded surface. properly dried to prevent warping or cracking. pressure-treated for enhanced weather resistance and are suitable for trim, molding,	wood n wood , pak timber or equivalent	No's	100			
12	Supply of kail wood strip ( 0.75 inch x 0.5 inch x 7ft) made from high-quality, select-grade wood with a smooth, sanded surface. properly dried to prevent warping or cracking. pressure-treated for enhanced weather resistance and are suitable for trim, molding,	wood n wood , pak timber or equivalent	No's	100			

13	Supply of kail wood semi molding 0.75 inch x 7ft) made from high-quality wood, such as Pine , with a smooth, sanded surface and an optional varnish finish. Designed for decorative trim, properly dried to prevent warping. pressure-treated for enhanced durability and weather resistance, ideal for interior trim, decorative molding,	Local	No's	120			
14	Supply of kail wood strip 2 inchx 3/4 inch x10ft AA grade. made from high-quality Pine, Cedar, or Teak wood, graded AA for minimal defects and consistent texture. smooth, sanded surface, ready for varnishing, and properly dried to prevent warping.	pak wood , awan timber or equivalent	Bundl e	10			
15	Supply of Glue german (1 Kg /pack)	ICI or equivalent	Pkt	20			
16	Supply of solution solvent-based adhesive containing synthetic polymers, resins, and organic solvents such as acetone and toluene. slightly yellowish liquid with low to medium viscosity, ensuring easy application. The adhesive sets quickly, typically bonding within 30 seconds to 5 minutes, 1liter/pack	Master, fevicol or equivalent	Box	10			
17	Supply of solution solvent-based adhesive containing synthetic polymers, resins, and organic solvents such as acetone and toluene. slightly yellowish liquid with low to medium viscosity, ensuring easy application. The adhesive sets quickly, typically bonding within 30 seconds to 5 minutes 4 lit/pack	Master, fevicol or equivalent	Gallon	12			
18	Supply of Elfy (50 grm/pack)	Gmsa or equivalent	No's	36			
19	one-component RTV silicone, 100 % pure, neutral-cure, weather- and UV-resistant sealant , flexible, and non-corrosive; light gray color; supplied in 310 mL cartridge with nozzle.	Gray rocks or equivalent	No's	6			
20	Supply of drawer lock , made from high-quality stainless steel , polished chromesatin finish and corrosion resistance. advanced locking mechanism with reinforced pins for	union lock , master lock or equivalent	No's	50			

	enhanced security. with three keys precision cut with anti bump feature.						
21	Supply of high quality mortise lock (Handle) standard size, durable brass body with a hardened steel cylinder, polished chrome, satin nickel finishes. operates with a single cylinder mortise locking system with a deadbolt, lock includes a smooth, ergonomic lever handle, a high-security keyway, and is rust-resistant. Easy installation is ensured with all necessary hardware included machine including (2 Handles, 1 Central machine, Brass spindle with 3 keys) complete.	pioneer, union brass or equivalent	No's	24			
22	Supply of high quality mortise lock (Handle type) 7', durable brass body with a hardened steel cylinder, polished chrome, satin nickel finishes. operates with a single cylinder mortise locking system with a deadbolt, lock includes a smooth, ergonomic lever handle, a high-security keyway, and is rust-resistant. Easy installation is ensured with all necessary hardware included machine including (2 Handles, 1 Central machine, Brass spindle with 3 keys) complete.	silver line, union lock or equivalent	No's	12			
23	Supply of round lock for wooden doors , made from high-quality brass satin finish for corrosion resistance. secure, key-operated locking mechanism with reinforced pins with all included hardware, available in keyed alike options, Inside: Turn button / push button locking. Outside: Key-operated locking cylinder. With 3 no's key complete.	union ,mughal lockor equivalent	No's	24			
24	Supply of high quality mortise lock (Handle) 4", durable brass body with a hardened steel cylinder, polished chrome, satin nickel finishes. operates with a single cylinder mortise locking system with a deadbolt, suitable for wooden, metal, and composite doors. The lock includes a smooth, ergonomic lever handle, a high-security keyway, and is rust-resistant. Easy installation is ensured with all	union , mughal lockor equivalent	No's	12			

	necessary hardware included machine including (2 Handles, 1 Central machine, Brass spindle with 3 keys) complete.						
25	Supply of Pedestal 3 In 1 Drawer Lock,made of high-quality stainless steel with a polished chrome finish. 3-in-1 key-operated locking system, with dimensions of 50mm x 60mm x 20mm for the lock body and a 100mm adjustable lock rod. The lock includes double steel keys, a round keyhole design, and an 80mm x 20mm strike plate.anti-drill and anti-pick security features. (strip type)	maeter lock ,godrej or equivalent	No's	24			
26	Supply of Pedestal 3 In 1 Drawer Lock,made of high-quality stainless steel with a polished chrome finish. 3-in-1 key-operated locking system, with dimensions of 50mm x 60mm x 20mm for the lock body and a 100mm adjustable lock rod. The lock includes double steel keys, a round keyhole design, and an 80mm x 20mm strike plate. anti-drill and anti-pick security features. (round bar type)	union , master lockor equivalent	No's	24			
27	Supply of Sliding Push Lock with 3 brass keys, made of steel or alloy body with a nickel-plated bolt .double-sided blade, a push-to-lock mechanism, and anti-tamper design. weather-resistant, corrosion-proof.	union ,master lock or equivalent	No's	24			
28	Supply of spindle lock with 3 keys for aluminum doors Made of high-quality zinc alloy body, chrome-plated matte finish, heavy-duty spindle system with a double-sided key with anti-tamper protection.	union ,master lock or equivalent	No's	12			
29	Supply of glass railing lock , made of high-quality stainless steel, polished chrome or matte black finish. with a high-security pin mechanism with 3 matching keys and anti-tamper design for added security. The lock is weather-resistant, corrosion-proof, and built for outdoor use with UV protection.	union ,master lock or equivalent	No's	24			

30	Supply door lock cylinder, high-quality brass body with steel pins. high-security pin mechanism with 3 matching double-sided keys, a turn/push-to-lock system, and anti-tamper design. weatherproof, impact-resistant, and ideal for indoor and outdoor use.	IHS or equivalent	No's	96			
31	Supply of door lock cylinder for Aluminum with 3 keys, door made of stainless steel . pin-tumbler system, with 2-3 matching keys and anti-picking security. corrosion-resistant, weatherproof, and designed for easy turn/push-to-lock operation. It is rekeyable for indoor and outdoor use, screw-mounted for standard aluminum window profiles.	IHS ,union or equivalent	No's	24			
32	Supply of glass railing aluminum	Khas or equivalent	Rft	100			
33	Supply of latch wheel for aluminum window	Khas or equivalent	No's	120			
34	Supply of latch lock for aluminum window	Khas or equivalent	No's	12			
35	Supply of 4-inch, heavy-duty latch Made from premium steel, ensures durability and rust resistance, with a smooth finish . The latch includes pre-drilled holes for quick, reliable closure.	Verona or equivalent	No's	100			
36	Supply of Door Closer ,surface-mounted hydraulic made of heavy-duty aluminum brass finish. accommodates doors weighing up to 100 kg and with widths ranging from 32" to 48. adjustable closing and latch speeds, a backcheck function to prevent forceful opening, and an optional hold-open arm.	Baldwin , keze or equivalent	No's	50			
37	Supply of high-quality EPDM rubberthis U-shape , UV, ozone, and weather-resistant, providing a tight seal to enhance insulation and prevent air and water leakage. effective soundproofing and weather resistance,	Dorma , rubber tech or equivalent	Bundl e	2			
38	Supply of Rubber Taper for Aluminum Windows made from durable, UV-resistant rubber, offering superior weatherproofing and	Dorma , rubber tech or equivalent	Bundl e	2			

	insulation. ensures a tight seal, preventing air and water leakage						
39	Supply of High quality Magnetic Catcher ,made with durable stainless steel housing with neodymium magnets, offering strong holding power for upto 20 kg. brushed nickel polished finishes, rust and corrosion-resistant,	rocky mountain, vingcard or equivalent	No's	90			
40	Supply of High-Quality 6-Inch Tower Bolt , made of durable stainless steel, offering excellent corrosion and rust resistance. 10 mm diameter and robust strength , sliding bolt mechanism for smooth locking and is surface-mounted and weather-resistant.	pakgate , al karam or equivalent	No's	30			
41	Supply of High-Quality 8-Inch Tower Bolt , made of durable stainless steel, offering excellent corrosion and rust resistance. 10 mm diameter and robust strength , sliding bolt mechanism for smooth locking and is surface-mounted and weather-resistant.	pakgate , al karam or equivalent	No's	50			
42	Supply of Hinged Strip (3/4 inch x 7 feet) , made of high-quality quality mild steel with a corrosion-resistant coating, and galvanized finishes. thickness of 2 mm, Suitable for doors weighing up to 150 kg, rust-resistant, weatherproof, and ideal for both indoor and outdoor use.	rocky mountain , mughal hardware equivalent	No's	24			
43	Supply of door Hinges 4 inch, made from high-quality solid bronze. precision pin for secure operation and a self-lubricating design, ensuring minimal wear over time. adjustable tension for optimal door alignment and can handle doors up to 100 kg.	rocky mountain , mughal hardware or equivalent	No's	60			
44	Supply of folding Door Latch ,made from high-quality stainless steel with excellent corrosion resistance and durability and smooth-operating latch, size 6 inches , and finishes as brushed nickel, weather-resistant rust free.	Pak gate , al karam or equivalent	Nos	100			
45	Supply of strip door handle 6 inch	Sitara or equivalent	No's	70			
46	Supply of handle Strip 4 inch	Sitara or equivalent	No's	60			

47	Supply of aluminum handle 5 inch (Drawer)	Khas or equivalent	No's	48			
48	Supply of steel nail 1 inch (#17) 500gm/box	China or equivalent	Box	24			
49	Supply of steel nail 1.5 inch (#17) 500gm/box	China or equivalent	Box	24			
50	Supply of steel nail 1 inch (thick) 500 gm/box	China or equivalent	Box	24			
51	Supply of steel nail 2.5 inch (thick)	China or equivalent	Box	24			
52	Supply of steel nail 1.5 inch (thick)	China or equivalent	Box	24			
53	Supply of steel nail 2 inch (thick)	China or equivalent	Box	24			
54	Supply of Iron nail 2 inch (#12) headed 1 kg/box	Local	Box	10			
55	Supply of Iron nail 3/4 inch (#20) Headless(T) 1 kg/box	Local	Box	5			
56	Supply of Iron nail 1.5 inch (#17) Headless (T) 1 kg/box	Local	Box	10			
57	Supply of Iron nail 1.25 inch (#17) Headless(T) 1 kg/box	Local	Box	10			
58	Supply of Iron nail 1 inch (#17) Headed	Local	Box	10			
59	Supply of Iron nail 3 inch (#12) Headed	Local	Box	6			
60	Supply of Iron nail 2 inch (#15) Headless (T) 1kg/pack	Local	Box	15			
61	Supply of Screw 2 inch (Black) (# 8) (100 Pcs/box)	Eagle or equivalent	Box	5			
62	Supply of Screw 1.5 inch (Black) (# 8) (100 Pcs/box)	Eagle or equivalent	Box	80			
63	Supply of Screw 1 inch (Black) (#6) (100 Pcs/box)	Eagle or equivalent	Box	80			
64	Supply of Screw 3/4 inch (Black) (#6) (100 Pcs/box)	Eagle or equivalent	Box	100			

65	Electric Staple Gun,230W power motor and operates on 220V - 240V AC. compatible with staples ranging from 6mm to 14mm in size, with a 100-staple capacity and maximum stapling force of 90N . Weighing 2.5 kg, dimensions of 350mm x 120mm x 270mm and with a 2-meter cord. The noise level is 75 dB. with rubber grip , while safety features and anti-jam mechanism.	Matika 6934 , dewalt or equivalent	No's	2			
66	10-inch diameter wood cutter blade, typically made from high-carbide-tipped with a bore size of 5/8 inch or 1 inch. 40 to 80 teeth with tungsten carbide-tipped high-speed steel teeth for precision. The kerf width ranges from 0.125 to 0.25 inches, with a thickness of 0.08 to 0.12 inches. Suitable for up to 5,000-8,000 RPM.	Dewalt ,lrwin or equivalent	No's	10			
67	4-inch wood cutter blade, made of high-carbon steel , with a thickness ranging from (0.8 to 1.5mm),24 to 60 teeth in either a toothed or continuous rim design. an arbor size of 3/8" or 1/2", a cutting angle of 10° to 15°, and operates at speeds between 5000 to 8000 RPM and coated with anti-corrosion protection	Dewalt ,lrwin or equivalent	No's	24			
68	supply of Circular Saw for 4 inch blade ,185 mm blade with a 1,200W motor, delivering a no-load speed of 5,800 RPM. cutting depth of 2-1/2 inches at 90° and 1-5/8 inches at 45°. The saw offers a bevel capacity of 0° to 45°., and has a magnesium body for durability. includes a soft-grip handle, blade brake,	Makita 500Mg, Dewalt E55sb or equivalent	No's	1			
69	supply of Jigsaw 650W motor with a variable no-load speed of 500-3,100 SPM and 3 orbital settings. cutting capacity of 65 mm in wood and 6 mm in steel, with an 18 mm stroke length. The bevel capacity is 45° left and right. soft-grip handle, tool-less blade change,	Makita 432 , bush pst 800 or equivalent	No's	1			
70	supply of 4-feet clamp bar , steel made clamping capacity of up to 3-4 inches and a clamping force of 1,000-1,500 pounds. It includes a quick-release adjustable sliding arm, non-marring pads to protect surfaces, and	black & dacker , stanly or equivalent	No's	1			

	an ergonomic handle for a secure grip with threaded screw mechanism.						
71	Supply of Triangle File for Saw Blades Made of hardened high-carbon with double cut precision ground teeth for smooth, efficient filing. Typically 6-8 inches in length, triangular shape with tapered edges for precise sharpening. Ergonomic non-slip handle fo, coated for anti-corrosion.	Proxxon, Irwin or equivalent	No's	30			
72	Supply of round file high-quality 12-inch, made from hardened alloy steel . precision-ground teeth for smooth, efficient filing and with a non-slip ergonomic handle coated with an anti-corrosion finish,	Lrwin , stanly or equivalent	No's	2			
73	Supply of round file high-quality 10-inch, made from hardened alloy steel . precision-ground teeth for smooth, efficient filing and with a non-slip ergonomic handle coated with an anti-corrosion finish,	Lrwin , stanly or equivalent	No's	2			
74	High-quality 4-piece/set glass steel clips, made from high-carbon steel, glass thicknesses of 6mm to 12mm, each clip provides a strong clamping force (up to 1000 lbs) with smooth, rounded edges to protect glass surfaces. polished brushed finish,	Bessey, Matika or equivalent	Set	30			
75	Supply of glass cutter pen, durable carbide-tipped wheel for precise scoring, designed to cut through glass with minimal effort. ergonomic handle made of lightweight and non-slip material with retractable mechanism .suitable for cutting various glass types, including tempered, laminated, and annealed glass, providing accurate and clean lines.	Diamond or equivalent	No's	6			
76	Supply of glass spacer 1.5 inch, made from durable material stainless steel, ,typical thickness 0.5 mm to 1 mm, with a smooth finish, Resistant to moisture, UV, and temperature changes,	stanly or equivalent	No's	36			

77	Supply of the grinding stone , manufactured from bonded aluminum-oxide abrasive with controlled grain size, vitrified matrix for high hardness and thermal stability. balanced round profile for low-vibration rotation, a precision-machined center bore for accurate spindle fit, and a uniform grit structure ensuring consistent cutting action. The stone offers high wear resistance, optimal heat dissipation, and reliable performance for metal grinding, edge shaping, and tool sharpening applications.	Good Quality	No's	3			
78	Supply of Iron circular saw blade double-sided design with precision-machined, sharp teeth, brushed metal finish with long-lasting wear resistance. consistent cuts with minimal vibration. The central hole is designed for compatibility with standard saw models, and its dual-edge design extends blade.	Diamond ,super star or equivalent	No's	36			
79	Supply of Iron saw frame, made from high-quality steel . 12-inch frame length and tool-free blade tension adjustment with ergonomic handle and the non-slip grip. compatible with 4 to 12-inch blades,	Wazir tools , master tools or equivalent	No's	2			
80	Supply of Hilti SDS Plus Drill Bit #2 x 6 inches, crafted from high-quality carbide, for heavy-duty drilling in concrete, masonry, and stone with reinforced cutting edges and a corrosion-resistant coating, Compatible with all SDS Plus hammer drills.	Kohinoor, master tools or equivalent	No.	18			
81	Supply of Hilti SDS Plus Drill Bit #2 x 4 inches , crafted from high-quality carbide, for heavy-duty drilling in concrete, masonry, and stone with reinforced cutting edges and a corrosion-resistant coating,. Compatible with all SDS Plus hammer drills.	Kohinoor, master tools or equivalent	No.	18			
82	Supply of glass breaking plier, made from high-quality steel with ergonomically designed, non-slip handles. precision-ground jaws ensure clean breaks without damaging surrounding areas. Typically measuring 160mm to 200mm in length lightweight and easy to handle	knipex ,stanly or equivalent	No's	2			

83	Supply of Electric wood plainer 500W motor smooth operation, planing width of 3 inches , no-load speed of 16,500 RPM for fast, precise work, adjustable depth up to 2mm , ergonomic handle for comfort and better control during extended use, lightweight design compatible precision-machined base plate ensures stability and smoothness during planing, and safety lock features	Makita , bosch or equivalent	No's	1			
84	5 meter measuring tape, fabricated from high-grade steel with corrosion-resistant coating, featuring precisely engraved dual-scale markings (inches and centimeters), durable retractable.	Total/China or equivalent	No's	3			
85	Supply of Anti-Termite Chemical A-Grade 1 lit/pack	Simba or equivalent	Lit	10			
86	Supply of Wooden writing pad for student chair acacia nilotia (Kikar wood) (size as per available chairs sample must see the sample before quoting)	Local	No's	50			
87	Supply of Electric Wood miter saw 1500W motor with a no-load speed of 3,800 RPM. 12-inch blade and offers a cutting capacity of 305mm (width) x 89mm (height) at 90°, and 215mm (width) x 89mm (height) at 45°. miter cut range of 60° left and 52° right and bevel angles of 47° both left and right. soft start for smooth design, ergonomic design, a sturdy table extension,	Bosch gcm12 ,Makita or equivalent	No's	1			
<b>Roof Treatment &amp; Boundary wall items</b>							
88	Styrene-Butadiene Rubber Water proofing Chemical milky white liquid with a solids content of 48-50%, a viscosity of 1500-2000 cps, and a pH value between 8.0 and 10.0. excellent water resistance and high bonding strength to concrete, mortar, and cementitious surfaces. durable, resistant to weather, UV, and wear, and can withstand temperatures from -20°C to 80°C.	Fosroc chemicals, Master solutions or equivalent	Kg/Lit	150			

89	Ementitious Seal Polymer Chemical 16 kg/kit for sealing concrete surfaces coverage of 1.5 to 2.0 kg/m <sup>2</sup> for two coats. with excellent water resistance, strong adhesion to concrete, and flexibility to bridge cracks up to 0.5 mm. UV and weather-resistant, with a temperature application range of 5°C to 35°C.	Sika , Imperial or equivalent	Kit	15			
90	one-component RTV silicone, 100 % pure, neutral-cure, weather- and UV-resistant sealant , flexible, and non-corrosive; slighty yellow color; supplied in 310 mL cartridge with nozzle.	Gray rocks or equivalent	No's	40			
91	Razor wire 2', made of galvanized steel, sharp arrow-shaped barbs, spaced evenly along the wire. Typically 0.8 to 1.2 mm thick, highly durable, corrosion-resistant, Rust free.	pak steel , universal steel or equivalent	Kg	530			
92	Barbed wire made of galvanized steel with a 2.77 mm diameter for the 12-gauge wire. The barbs are 38 mm in length, spaced 100 mm apart, and the wire has a tensile strength of 1000 MPa. coated with hot-dip galvanized zinc for corrosion resistance, and the wire strength is a minimum of 90-100 kgf per meter.	pak steel , universal steel or equivalent	Kg	200			
93	Supply of Galvanizes steel Powder coated profile shaped Corrugated sheet in (22 SWG) as per approved ridge and valley. Complete in all respects. size : Corrugated (22' x 4') = 68 Sheets Gola (12' x 2') = 08 Sheets	Local	Kg	3203			
94	Supply of self tapping metal screw @ # 1.5 diameter and 3 inch long with 1 metal and 1 bituminous washer complete in all respects.	Local	Kg	3			
95	Supply of self tapping metal screw @ # 1.5 diameter and 2 inch long with 1 metal and 1 bituminous washer complete in all respects. sample is available in works department	Local	Kg	5			
96	Polythene sheet with a thickness (0.3 mm), transparent, Smooth and glossy with UV protection.	Local	Kg	25			

97	30 meter measuring tape, fabricated from fiberglass with corrosion-resistant coating, featuring precisely engraved dual-scale markings (inches and centimeters), durable retractable.	Total/China or equivalent	No's	1			
98	5 meter measuring tape, fabricated from high-grade steel with corrosion-resistant coating, featuring precisely engraved dual-scale markings (inches and centimeters), durable retractable.	Total/China or equivalent	No's	2			
99	J-bolt with 2-inch diameter, 4-6 inches long, made of carbon steel , full threading, galvanized zinc-plated finish. Washer made of steel, stainless steel, with 4-inch outer diameter, 2.1-2.2 inches inner diameter, 0.1-0.2-inch thickness, and zinc-plated or stainless steel finish. Nut of 4-inch size, made of high-strength steel (Grade 8) or stainless steel, with zinc-plated or stainless steel finish.	Local	Kg	5			
	<b>Telephone Exchange Items</b>						
100	Supply of Telephone Cable 2- Pair	GM or equivalent	Coil	8			
101	Supply of DB Point (10-Pair with Box)	PTCL Standred or equivalent	Nos	10			
102	Supply of Telephone Set (With CLI) Model: {HCD399(126)P/TSDL}.	GAOXINQI or equivalent	Nos	30			
103	Supply of Punch Down Tool with Sensor Network Punch Tool.	China or equivalent	Nos	3			
104	Supply of Insulation Pvc Tape	Osaka or equivalent	Nos	50			
105	Supply of G Verma - Heilti 18" (1"-Dia)	Heilti or equivalent	Nos	01			
106	Supply of U.G Armoured Cables 10 Pair	GM or equivalent	Meter	60			
107	Supply of U.G Armoured Cables 20 Pair	GM or equivalent	Meter	75			
108	Supply of PVC Duct (16mm x 25mm)	Popular or equivalent	Length	30			
109	Supply of good quality Screw 1.5" (Black) (# 8) (100 Pcs/box)	Eagle or equivalent	Box	10			

110	Supply of good quality Screw 1" (#8) (Black) (100 Pcs/box)	Eagle or equivalent	Box	3			
111	Supply of Steel Nail 1.5" (14 No)	Taiwan or equivalent	1/2 KG Box	5			
112	Supply of rowel plug (Plastic Gutti, No. 12)- 100 PCS/pack	Local	Packet	24			
113	Supply of polythene CAUTION - TELECOMMUNICATIONS CABLE BELOW 30 microns x 150mm wide x 200 mtr/roll color orange.	Local	Role	3			
<b>Material for Welding</b>							
114	Galvanized Iron Inter-Crimped Wire Mesh, 12×24 mesh count*6feet, 0.8 mm wire thickness, epoxy-coated for anti-corrosion protection, bs 1052 standards tensile strenght 550 MPA,	JD, AIM Or equivalent	Bundl e	4			
115	Galvanized Iron Inter-Crimped Wire Mesh, 12×24 mesh count*5 feet, 0.8 mm wire thickness, epoxy-coated for anti-corrosion protection,bs 1052 standards tensile strenght 550 MPA ,	JD, AIM Or equivalent	bundle	4			
116	Welding lead 35mm <sup>2</sup> pure copper 1000-wire, rubber insulated, oil and heat resistant, 600/1000V rated, IEC 60245 compliant.	Longage , newage or equivalent	Rft	250			
117	Cutting Disk (14 Inch) (355mm × 3mm × 25.4mm) high-speed abrasive cutting disk made of resin-bonded aluminum oxide, maximum speed 4400 RPM,	Hitachi , bosch or equivalent	Nos	50			
118	Green Card Tower Bolt 4" (100 mm), stainless steel, satin finish, heavy-duty, rust-resistant, with all necessary screws and fitting.	union , dorma or equivalent	Nos	50			
119	ARL Tower Bolt 12" (300 mm), satin finish(S.S), heavy-duty, rust-resistant, complete with all required screws and fittings	union , dorma or equivalent	Nos	24			
120	High quality weldable gate hinges, 3-inch size, made of solid mild steel body with precision machined finish, fitted with built-in steel ball bearing for smooth rotation corrosion-resistant,	godrej , rox or equivalent	Nos	48			

121	9-inch cutting disk made of high-quality resin-bonded aluminum oxide, reinforced with double-layer fiberglass mesh ; 22.23 mm bore size; 1.9 mm thickness ensures fast, precise cutting with minimal material loss; maximum safe operating speed 6,600 RPM (80 m/s);	Permanent or equivalent	Nos	100			
122	Galvanized Iron Inter-Crimped Wire Mesh, 12×24 mesh count*7 feet, 0.8 mm wire thickness, epoxy-coated for anti-corrosion protection, bs 1052 standards tensile strength 550 MPA ,	JD, AIM Or equivalent	Bundl e	4			
123	No. 12 (4 mm) mild steel welding rod with rutile coating, ensures stable arc, strong joint, and smooth finish on structural; conforms to AWS A5.1 E6013 safety standards; supplied in 10 kg ; usable with both AC and DC supply.	jasic , boster or equivalent	Nos	5			
124	Rawl bolt No. 2.5 (8 mm × 70 mm) made of carbon steel with zinc coating, rust-resistant, expansion type for strong anchoring in concrete	fisher , Screwfix or equivalent	No	400			
125	Iron strip 1/2 inch, mild steel, hot-rolled, with smooth finis hand anti-rust/galvanized coating.	Local	kg	20			
126	Iron angle 1.5 inch × 1.5 inch, 1/4 inch thick, mild steel, L-shaped , with galvanized anti rust coating	Local	kg	30			
127	MS Square Pipe 1.125" (16 Gauge), 1.6mm thick mild steel IS-1239, 1.6 20 ft length, smooth finish with anti-rust coated.	Local	Nos	30			
128	MS Square Pipe 1" (16 Gauge), 1.6mm thick mild steel IS-1239, 1.6 20 ft length, smooth finish with anti-rust coated.	Local	Nos	12			
129	MS Sheet 16 Gauge, made from high-quality mild steel conforming to IS-2062 standards, thickness approx. 1.6 mm, smooth mill finish, supplied in standard sheet size 4'×8', free from scale and surface defects, provided with anti-rust coating.	Local	Nos	5			

130	MS Sheet 18 Gauge, made from high-quality mild steel conforming to IS-2062 standards, smooth mill finish, supplied in standard sheet size 4'×8', free from scale and surface defects, provided with anti-rust coating.	Local	Nos	5			
131	Ms Gola 16 Gauge, fabricated from high-quality mild steel conforming to IS-2062 standards, thickness approx. 1.6 mm, smooth and uniform finish, supplied in standard commercial lengths 20 feet, provided with anti-rust coating.	Local	Nos	12			
132	Heavy Duty Welding Holder, body made of heat-resistant and impact-proof insulated material, copper alloy jaws for superior current conductivity, rated capacity 800A to 1000A, suitable for electrode sizes up to 6 mm, strong spring grip for firm electrode holding, shockproof handle for operator safety,	INGCO , POL or equivalent	No	6			
133	High-quality Steel Putty (1liter box), two-component epoxy-based compound formulated for metal repair and surface restoration, resistant to heat, oil, and corrosion, cures to a hard, machinable finish.	Nexa , Devcon or equivalent	Nos	5			
134	One-piece moulded polypropylene shell seat (Elephsse type), moulded from virgin PP material, UV-stabilized to resist colour fading and cracking . Weather-resistant and corrosion-free, The seat shall have an ergonomic contour for back and thigh support, with a smooth, easy-to-clean surface and anti-slip sitting area. Load-bearing capacity: Designed to support more than 150 kg without deformation or structural failure. Colour and finish shall be the same as those fixed in our classrooms, and all materials and fabrication shall conform to relevant ISO/IS standards for seating durability, strength, and performance.	sioen, architex, toyo or equivalent	Nos	80			

135	High-quality industrial welding glasses, manufactured from impact-resistant, heat-resistant polycarbonate material with anti-scratch and anti-fog coating and EN166 safety standards; ergonomically designed lightweight frame with adjustable temples and soft nose bridge for prolonged use; provides complete protection against UV and IR radiation during welding operations; suitable for MIG, TIG, and arc welding works; durable, corrosion-resistant, and compliant with ISO 4850 standards.	Hakimi , Rahat or equivalent	Nos	3			
136	industrial-grade baby grinder, 4-inch (100 mm) wheel capacity, 1200 W copper-wound motor, 220–240 V, 50 Hz, 12,000 RPM; die-cast aluminum gear housing with reinforced heat-resistant body; side handle, safety guard, and spindle lock included; suitable for continuous metal cutting and fabrication works; conforms to ISO 11148-7 / CE / EN 60745 standards;	Ingco, or Hyundai Power (or equivalent).	No	1			
137	High-performance industrial rotary hammer drill, Hilti , 1700 W motor with 11.5 J impact energy and 0–360 RPM speed; robust SDS-Max system with depth gauge and anti-vibration (AVR) and torque-control (ATC) safety features.	Matika , Ingco or equivalent	No	1			
138	4-inch heavy-duty door hinges, manufactured from cold-rolled stainless steel with corrosion-resistant finish, featuring smooth ball-bearing pivot mechanism, electro-plated .	Sitara , Btc or equivalent	No	30			
139	5-inch heavy-duty door hinges, manufactured from cold-rolled stainless steel with corrosion-resistant finish, featuring smooth ball-bearing pivot mechanism, electro-plated .	Sitara , Btc or equivalent	No	36			
140	2.5-inch wrma length bit features a smooth shank, precision-ground HSS steel, compliant with DIN 338/340, for drilling holes	Ingco ,wise up or equivalent	No	5			

141	single-phase welding plant, 220 V $\pm 15\%$ input, employing IGBT technology industrial rectifier, output current range up to approximately 200-300 A , continuous duty rating at 60% or higher, multi-process capability (stick/MMA, optionally TIG, ), robust forced-air cooling, thermal overload and over-voltage protection	Edon ,Ingco or Equivalent	No	1			
142	welding kundy, fabricated from high-quality mild steel, smooth surface finish	local	Kg	5			
143	7-inch cutting disc for concrete-cutting, with a steel core and laser welded sintered diamond segment rim, bore 22.2 mm (7/8") arbor size, cutting width 2.4-3.0 mm, segment height 10 mm, maximum peripheral speed 80 m/s or maximum RPM 8,500, with stable.	Dewalt , Ingco or equivalent	No	12			
144	2.5 No flat washers, made of high-quality mild steel, corrosion-resistant, with precise inner diameter to fit 2.5 No bolts,	Local	Kg	13			
145	Metal window stay dabi type, fabricated from high-quality mild steel with corrosion-resistant coating, adjustable length, with locking pin mechanism for secure positioning, suitable and finished with smooth powder coating	Anwer , Btc or equivalent	No	24			
146	window stay, fabricated from Grade 304 stainless steel with anti-corrosion finish, , with friction halt mechanism allowing sash to open to 90°, suitable , with elongated fixing holes for adjustment.	Anwer , Btc or equivalent	No's	48			
147	5 meter measuring tape, fabricated from high-grade steel corrosion-resistant coating, featuring precisely engraved dual-scale markings (inches and centimeters), durable retractable.	China or equivalent	No,s	1			
148	black coated screws, size 3/4 inch, made of high-quality mild steel , sharp thread for secure fastening, packed in standard box quantity	China or equivalent	box	36			

149	mild steel (MS) door frame chokhat, fabricated from 16 SWG high-quality sheet, 7 Feet rectangular U-shaped profile with welded and reinforced corners, finished with corrosion-resistant	local	Nos	45			
150	Iron strip 1 inch, mild steel, hot-rolled, with smooth finish and anti-rust/galvanized coating.	Local	Kg	50			
<b>Paint, Mason &amp; Plumbing Item</b>							
151	high-quality Muslim shower, equipped with flexible PVC hose (minimum length 1.0 m), corrosion-resistant, leak-proof, and lightweight design, smooth water flow trigger, complete with wall-mount bracket,	Faisal, sonex or equivalent	Nos.	50			
152	Brass Bal Valve 3/4" size, leak-proof, and corrosion-resistant, with smooth quarter-turn operation and firm grip handle.	Faisal, Master or equivalent	Nos.	30			
153	Brass Bal Valve 1/2" size, leak-proof, and corrosion-resistant, with smooth quarter-turn operation and firm grip handle.	Faisal, Master or equivalent	Nos.	30			
154	Premium-grade Muslim shower body with precision control lever, high-pressure flow system, ceramic cartridge mechanism, anti-leak design, and long-life performance, complete with all required fittings and accessories,	Faisal, sonex or equivalent	Nos.	50			
155	Flexible rubber connection pipe, 1 meter length, high-pressure resistant, anti-kink, leak proof, corrosion- and temperature-resistant, fitted with heavy-duty brass nuts and washers,	Faco, Rehmat or equivalent	Nos.	100			
156	Anchor bolts made of galvanized steel, complete with nuts and washers; heavy-duty type.	Porta, Marachi or equivalent	Packet	10			
157	commode fixing kit comprising high-tensile galvanized bolts, neoprene washers, and sealing bushes	Qabil, lzyapi or equivalent	Nos.	10			

158	one-component RTV silicone, 100 % pure, neutral-cure, weather- and UV-resistant sealant , flexible, and non-corrosive; clear color; supplied in 310 mL cartridge with nozzle.	Gray rocks ,Gmsa or equivalent	Nos.	20			
159	Complete 8-piece bath/shower set Echo series including one basin mixer, one bath mixer with wall-shower/hand-shower, one double bib cock, three tee stop cocks, one basin waste and one toilet-(Muslim) shower, all in polished chrome finish, brass construction, modern design,	Faisal sentry or equivalent	Nos.	20			
160	wall-mounted bib cock, solid brass body finish, quarter-turn lever handle, ½" BSP male inlet, and threaded outlet; leak-proof.	Faisal, sonex or equivalent	Nos.	80			
161	Counter-mounted sink mixer of solid brass material with chrome-plated finish, fitted with quarter-turn ceramic disc cartridges, swivel spout, and dual control handles, complete with all necessary fittings;	Faisal, sonex or equivalent	Nos.	10			
162	counter-mounted double basin mixer of solid brass material with chrome-plated finish, fitted with dual lever handles , quarter-turn ceramic disc cartridges, and a swivel spout serving basins. The mixer shall include ½" BSP flexible connection hoses, rubber washers, and all necessary mounting accessories; heavy-duty type	Faisal, sonex or equivalent	Nos.	50			
163	Tee Coke brass tap with chrome finish for wall mounting, with a Head to turn water on and off, complete with all washers and fittings.	Faisal , sonex or equivalent	Nos.	36			
164	Teflon tape, pure PTFE, 12 mm × 12 m, 0.1 mm thick, white, resistant to chemicals, temperature -200°C to 260°C	Stallion , Mishoo or equivalent	Nos.	50			
165	High-neck side pillar cock basin mixer , high-strength corrosion-resistant steel,	Faisal , sonex or equivalent	Nos.	40			

166	Double bib cock wall-mounted, made of brass with chrome plating, featuring two independent taps. 3/4 inch inlet and outlet, with a polished chrome finish. designed to operate within a pressure range of 0.2 MPa to 0.75 MPa and a temperature range of 0°C to 80°C.	Sonex , Grohi or equivalent	Nos	50			
167	Flexible geyser pipe 2 feet in length, made from high-quality copper steel for optimal heat resistance. withstand high temperatures up to 90°C and water pressure ranging from 0.3 MPa to 1.0 MPa.	local	Nos	20			
168	One Piece Toilet floor-mounted, single-piece (Hd 113 A )ceramic commode with a glossy white finish with seat cover and efficient low-water consumption with a dual flush mechanism.	Porta or equivalent	Nos.	10			
169	Flush Tank ,made from high-quality ceramic vitreous china with a sleek white finish . 6-liter capacity with a dual flush system (3L/6L) and uses a gravity-fed flush mechanism with a push-button operation with a durable plastic flush valve designed to withstand high pressure. 1/2" inlet and 1.5" outlet . tank lid is made of ceramic and is stain-resistant. Leak-proof seals with rubber gaskets ,	sonex , Grohi or equivalent	Nos.	20			
170	4-inch concrete cutting disk made from high-quality diamond material, suitable for both dry and wet cutting applications. operates at a maximum RPM of 12,000 and is compatible with most angle grinders.	Stanly , Bush , Matika or equivalent	Nos.	20			
171	Kerosine oil	local	Liter	200			
172	pure Teflon sealing leak prevention, role size (36 feet *1') in high-temperature and chemically aggressive environments, superior resistance to corrosion, chemicals, and extreme temperatures,	local	Role	10			
173	cement bags OPC	Dg, maple or equivalent	Nos.	10			

174	cement bags White	Dg, maple or equivalent	No's	10			
175	sand ravi	ravi or equivalent	cft	800			
176	5-inch double paint brush with high-quality synthetic bristles, double-thick bristle head, a corrosion-resistant nickel-plated steel ferrule, and an ergonomic non-slip easy-grip handle about 7–9 inches long.	Captan, black cat or equivalent	Nos.	15			
177	4-inch double paint brush with high-quality synthetic bristles, double-thick bristle head, a corrosion-resistant nickel-plated steel ferrule, and an ergonomic non-slip easy-grip handle about 7–9 inches long.	Captan, black cat or equivalent	Nos.	15			
178	3-inch double paint brush with high-quality synthetic bristles, double-thick bristle head, a corrosion-resistant nickel-plated steel ferrule, and an ergonomic non-slip easy-grip handle about 7–9 inches long.	Captan, black cat or equivalent	Nos.	15			
179	Air compressor, single-stage, oil-lubricated piston type with a HP motor (230V, 50Hz, 2hp single-phase). maximum pressure of 135 PSI (9.3 bar), and delivers 10.2 CFM at 90 PSI. The pump runs at 1,725 RPM with a 75% duty cycle. splash lubrication system with an oil sight glass, built-in overload protection, and operates at a noise level of 75-80 dB. with air cooling, and the compressor is mounted on a stationary, vibration-free base. Included accessories, safety valve, pressure gauge, and drain valve.	INGERSOL L RAND , Faisal engineering or equivalent	No's	1			
180	high-end paint compressor gun made from durable stainless steel, adjustable spray patterns and multiple nozzle options. operates at 30-60 PSI, light weight design and adjustable paint flow with an efficient air cap.	sprytech, airmatic, bosch or equivalent	No's	2			
181	Paint thinner	Master , black horse or equivalent	Liter	50			

182	Heavy-duty aluminum ladder, height of 8 feet and a weight capacity of 150–180 kg. Made from high-quality anodized aluminum, double-riveted non-slip steps, reinforced side rails, and anti-skid rubber feet. The ladder includes a wide top platform for secure standing and is lightweight for easy portability.	Pak ladder , universal ladder or equivalent	No's	1			
183	12-foot aluminum ladder made from industrial-grade, corrosion-resistant aluminum. working height of 12 feet and supports a load capacity of up to 180 kg. The ladder features wide, anti-slip steps, The base is equipped with non-slip rubber feet for superior grip,	Pak ladder , universal ladder or equivalent	No's	1			
184	Aluminium ladder up to 20 feet made with High-grade fiber glass , reinforced for durability and lightweight performance. adjustable height of up to 20 feet, supports up to 250-300 kg, and includes a sliding mechanism for easy extension and compact storage. The ladder has wide, anti-slip steps, a heavy-duty locking system for stability, and rubber feet for secure placement. With weather and chemical resistance, light weight design ensures easy portability,	Pak ladder , universal ladder or equivalent	No's	1			
185	Plaster of Paris white powder made from gypsum, with a setting time of 10-15 minutes.	local	No's	100			
186	Sand paper 120# 150#	local	No's	150			
187	paint roller microfiber cover designed, The roller frame is made of sturdy steel, with a comfortable handle for extended use. typically ranging from 4 to 12 inches	Captan, black cat or equivalent	Nos.	15			
	<b>Material for Poshish Works</b>						
188	Cloth (Khasha) 54" Width black (thick)	Local	Yard	45			

189	Rexine black colour , premium synthetic leather made from high-quality PVC with fabric backing, durability and flexibility. smooth finish, is resistant to water, abrasion, and UV, combines strength and aesthetic appeal.	Texon ,intertext or equivalent	Mtr	30			
190	Rexine brown colour , premium synthetic leather made from high-quality PVC with fabric backing, durability and flexibility. smooth finish, is resistant to water, abrasion, and UV, combines strength and aesthetic appeal.	Local	Mtr	30			
191	High density foam (22" x 22" x 3" ) , made from high-density polyurethan, with a density of 2.0–3.0 lbs/ft <sup>3</sup> . high firm to firm support, excellent durability, and compression resistance (ILD 20-50). Weighing around 2.1 lbs (1 kg), hypoallergenic, odor-free, fire-retardant.	pak foam, Master foam or equivalent	Seat	24			
192	High density foam (22" x 22" x 2" ) , made from high-density polyurethan, with a density of 2.0–3.0 lbs/ft <sup>3</sup> . high firm to firm support, excellent durability, and compression resistance (ILD 20-50). Weighing around 2.1 lbs (1 kg), hypoallergenic, odor-free, fire-retardant.	pak foam, Master foam or equivalent	Seat	24			
193	High density foam (3 feet x 6" x 2" ) , made from high-density polyurethan, with a density of 2.0–3.0 lbs/ft <sup>3</sup> . high firm to firm support, excellent durability, and compression resistance (ILD 20-50). Weighing around 2.1 lbs (1 kg), hypoallergenic, odor-free, fire-retardant.	pak foam, Master foam or equivalent	Sheet	6			
194	Tyre Patti Large bundle	Local	Bundl e	2			
195	Bolt 1"(Small Threads) as per sample	Eagle or equivalent	Kg	1			
196	Bolt 1"(Big Threads) as per sample	Eagle or equivalent	KG	1			
197	Screw Black # 8, 3/4"	Eagle or equivalent	Box	5			

198	Screw Black # 8, 1"	Eagle or equivalent	Box	6			
199	Screw Black # 8, 1.5"	Eagle or equivalent	Box	6			
200	Screw Black # 8, 1.25"	Eagle or equivalent	Box	6			
201	Screw Black # 8, 2"	Eagle or equivalent	Box	5			
202	Staple pin # 10	Korea or equivalent	Box	12			
203	Chair Punja base (PVC)	Local	No's	12			
204	Chair Wheel Standard size (5 pics/set)	Local	Set	50			
205	Marking Chowk triangler (Kharya ) white 24 P/Box	Local	Box	2			
206	Electirc chargable screw driver	Makita, bosch or equivalent	No's	1			
207	Scissor for cloth cutting Medium	Wazirabad or equivalent	No's	1			
208	Nail Puller (Jamur)	Local	No's	1			
209	Tee spanner #10	Stanly or equivalent	No's	1			
210	Tee spanner #12	Stanly or equivalent	No's	1			
211	50 PSI Compressor with Staple Gunis a portable, oil-free compressor with a 1.5 HP motor and 6-8 liter tank capacity. delivers 120-140 L/min airflow and operates at < 75 dB for quieter performance. . Designed for 220-240V outlets, include 20 rft pipe	Bosch or equivalent	No's	1			

***Note: Bidders are required to must visit the CUI-Lahore Campus, Works Department and inspect the samples of all items before quoting rates to avoid quality and specification issues.***

**Part C: Bid Evaluation Criteria**

**Signature & Stamp of Bidder**

**All bids shall be evaluated in accordance with the following evaluation criteria and other terms & conditions set forth in this bidding document.**

- 1. Please submit the bid (rates) on our prescribed BoQs Form with complete terms and conditions signed & stamped, otherwise your bid (s) may be rejected.**
- 2. Brand name / model must be mentioned against items where required failing which the bid / item (s) may be rejected. Manufacturing origin can only be accepted against items where mentioned specifically in the BoQ form.**
- 3. To emphasize quality requirements of the items, the brand names / model are mentioned in the technical specifications (where applicable) in this document. Equivalent brand may be accepted subject to ensuring quality standards, compatibility / functionality and specification requirements otherwise may be rejected.**
- 4. Supporting literature of the quoted model must be attached (where available/required) for perusal of CUI Lahore to technically assess that the quoted item meets the required specifications and other conditions of our BoQs / tender document.**
- 5. The bids shall be evaluated to strictly ensure that the quoted brand/ model/ item meet all the BoQ/ specification requirements given in the tender document for each item.**
- 6. In addition to the BoQ requirements, vendors must meet the vendor qualification criteria /company profile requirements (if any), as set forth in this tender document.**
- 7. Bidders are required to quote genuine / quality products without compromising on quality. The supplied products shall be inspected by our technical experts with respect to BoQs requirements and quality standards. The bidder will be responsible to replace the items which are not found as per the required quality standard.**