

PAKISTAN NAVY

TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 24-12-2025

TERMS & CONDITION

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT".
2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.
3. LAB TESTING CHARGES IF ANY WILL BE BORN BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE894 68	QA263527	402099083318 4 / ROPE FIBROUS 8 STRAND, DIA 48MM,	-	440 / METER	NO DATA AVAILAB LE		UK	MARLOW ROPE LTD SOUTH ROAD HAILSHA M EAST SUSSEX UNITED KINGDO M		<p><u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 48-MM DIA, BERTHING HAWSER BLK CONT FILAMENT POLYESTER & SS POLYPROPYLENE, 3. MIN BREAKING LOAD: 36.5 TONNES, 4. SUPPLIED IN 220 MTR COIL 5. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 6. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK) RN/ RELATED COUNTRY. 7. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 8. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM, Phone: +44(0)1323 444 444 EMAIL: sales@marlowropes.com</p> <p><u>GENERAL SPECIFICATION -</u> SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											48-MM DIA, BERTHING HAWSER BLK CONT FILAMENT POLYESTER & SS POLYPROPYLENE, 3. MIN BREAKING LOAD: 36.5 TONNES, 4. SUPPLIED IN 220 MTR COIL 5. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 6. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 7. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 8. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM, Phone: +44(0)1323 444 444 EMAIL: sales@marlowropes.com	
2	DGE90136	RB10002 local	615070526408 5 / INSULATION RUBBER MAT		65 / FOOT	NA					TECHNICAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm.GENERAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm.	
3	DGE91401	-	035059571323 5 / ROPE SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH (ROUNDED IN 9-MM)		200 / FATHO M						TECHNICAL SPECIFICATION - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILBILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554. GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p><u>SPECIFICATION - 1.</u> MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554.</p>	
4	DGE928 28	NO DATA AVAILABL E	041359923875 5 / MAT FLOOR RUBBER LG. 18. WD.(LTR NO E-I/4927- A/1082 DT221096)		100 / METER						<p><u>TECHNICAL SPECIFICATION -</u> Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4- 6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black. <u>GENERAL SPECIFICATION -</u> Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4- 6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black.</p>	
5	DGE899 32		034059923620 3 / COT CANVAS COMPLETE FITTED SZ. 5.83X2.33X1. 25 FT		80 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - 1.</u> Frame Material: Steel, Aluminum, Powder-coated Iron (Rust-resistant) 2. Canvas Material: Heavy-Duty 600D or 1200D Oxford fabric, Polyester or Cotton Canvas 3. Load Capacity: 100-300kg (Average 120-</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>150kg) 4. Unfolded Dimensions √ LENGTH: 180-210CM √ Width: 60-80cm √ Height: 40-50cm 5. Folded Size Compact :-90x20x15cm (Approx) 6. Weight Of Cot: 06-12kg (Depends on Frame and Fabric) 7. Leg Design : X-shape, U-shape or Straight Legs with Anti-Slip Rubber feet 8. Setup Type: Manual Unfold/ fold; some have Tool- free assembly 9. Portability: Comes with a Carry Bag or Strap 10. Water Resistance: Waterproof Canvas Material 11. Ventilation: Breathable fabric for airflow (especially in Polyester/ mesh types) 12. Additional Features: √ Side pockets for storage √ Pillow attachment √ Adjustable Backrest √ Mosquito net compatibility √ Heavy duty zippers or Velcro for closure</p> <p>GENERAL SPECIFICATION</p> <p>- 1. Frame Material: Steel, Aluminum, Powder-coated Iron (Rust-resistant) 2. Canvas Material: Heavy-Duty 600D or 1200D Oxford fabric, Polyester or Cotton Canvas 3. Load Capacity: 100-300kg (Average 120-150kg) 4. Unfolded Dimensions √ LENGTH: 180-210CM √ Width: 60-80cm √ Height: 40-50cm 5. Folded Size Compact :-90x20x15cm (Approx) 6. Weight Of Cot: 06-12kg (Depends on Frame and Fabric) 7. Leg Design : X-shape, U-shape or Straight Legs with Anti-Slip Rubber feet 8. Setup Type: Manual Unfold/ fold; some have Tool- free assembly 9. Portability: Comes with a Carry Bag or Strap 10. Water Resistance: Waterproof Canvas Material 11. Ventilation: Breathable fabric for airflow (especially in Polyester/ mesh types) 12. Additional Features: √ Side pockets for storage √ Pillow attachment √ Adjustable Backrest √</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
6	DGE916 42	NIL	035059942506 2 / ROPE SISAL, 03- strands , HAWSERLAID, DIA: 5/8 INCH (16-MM)		150 / METER						<p>Mosquito net compatibility ; Heavy duty zippers or Velcro for closure</p> <p>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004 OR OF LATEST VERSION, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK/ RN/ RELATED COUNTRY), 8. LENGTH PER COIL: 120 FATHOM. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLYODS/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM: M/S COTESI GENERAL</p> <p>SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004 OR OF LATEST VERSION, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ROPE MUST BE APPROVED BY MOD (UK/ RN/ RELATED COUNTRY), 8. LENGTH PER COIL: 120 FATHOM. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM: M/S COTESI	
7	SGB92807	9104923 (5110-99-910-4923)	0274709104923 / FILE ENGINEER ROUND D-CUT BASTARD LG 6.00IN DIA 6MM.		110 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
8	DGE89937	NIL	0350599237126 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sTRAND, Z-LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	240 / FATHOM						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
9	DGB928 38		021459003565 1 / BOLT MACHINE STEEL BSW HEX HD SZ 1.000X0. 375 IN		21 / TEN						<u>TECHNICAL SPECIFICATION -</u> MATERIAL GRADE EN 4140 <u>GENERAL SPECIFICATION -</u> MATERIAL GRADE EN 4140	
10	DGB928 34		021459941001 9 / BOLT MACHINE STEEL UNC class 2a HEX HD SZ 0.625 X3.000X1.500 IN	BR-320 D/78	296 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - AISI</u> PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED <u>GENERAL</u> <u>SPECIFICATION - AISI PD 970:</u> 2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED	
11	DGE874 56		033059571326 6 / TWINE HEMP PACKING MEDIUM 3STRD POLISHE MIN BKG STRGTH 100LB		10 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - (1)</u> 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses. <u>GENERAL SPECIFICATION</u> - (1) 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses.	
12	SGB914 52		021459013080 9 / BOLT MACHINE STEEL BSF HEX HD SZ 0.500X2. 250X1.000 IN		30 / TEN						<u>TECHNICAL SPECIFICATION</u> - MATERIAL GRADE EN 4140 <u>GENERAL SPECIFICATION</u> - MATERIAL GRADE EN 4140	
13	SGB914 53		026259001689 7 / CLIP IRON O/A LG 6" DIA 3/8" BOTH ANGLE 90 BOTH ARM 2" (LOCAL)	USE MARINE RAILWAY	500 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - MILD STEEL BS 970 EN 3A superceded by PD 970 (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local) <u>GENERAL</u> <u>SPECIFICATION</u> - MILD STEEL BS 970 EN 3A superceded by PD 970 (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
14	SGB914 51		132572325000 1 / TIP DIAMOND CUTTING TOOL A25MM ATDIN4966		140 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - GRADES: TUNGSTEN CARBIDE ULTRA-MET GRADES:Z60 ISO CODE:P20/M15 GRAIN SIZE:FINE APPLICATION: GENERAL PURPOSE (MACHINING STEEL) HARDNESS (HRA):92.1 RA DENSITY:12.95 G/CC TRANSVERSE RUPTURE (TRS): 325 KSI325000 PSI</p> <p>GENERAL SPECIFICATION - GRADES: TUNGSTEN CARBIDE ULTRA-MET GRADES:Z60 ISO CODE:P20/M15 GRAIN SIZE:FINE APPLICATION: GENERAL PURPOSE (MACHINING STEEL) HARDNESS (HRA):92.1 RA DENSITY:12.95 G/CC TRANSVERSE RUPTURE (TRS): 325 KSI325000 PSI</p>	
15	DGE916 43	NIL	402099923712 1 / ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00", DIA 0.3125" (8MM)	NGTH 1.330 TONS UNIT OF AVAILABILITY	480 / FATHO M						<p>TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM.</p> <p>GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM.	
16	SGB92801	TPI 14	530571503899 6 / SCREW SELF TAPPING S/STEEL CSK HD 14 TPISZ 2.000X0.250" LOCAL	REPAIR FOR GRP BOATS	600 / TEN						<u>TECHNICAL SPECIFICATION</u> - material: stainless steel grade: 316 HD 14 Dimension: dimeter: 14mm Thread per inch: 2.000x0.250" <u>GENERAL SPECIFICATION</u> - material: stainless steel grade: 316 HD 14 Dimension: dimeter: 14mm Thread per inch: 2.000x0.250"	
17	DGE90152	NO DATA AVAILABL E	562050504233 5 / TILES CERAMIC GLAZED COLOUR WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")	DECK COVERING	400 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
18	DGB90883	NO DATA AVAILABL E	024850000001 5 / SAFE- STEEL-WITH- COMBINATION -LOCK FOR CBs SZ 28X20X16 5/8		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record <u>GENERAL SPECIFICATION</u> - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record	
19	DGE91641	NO DATA AVAILABLE	033050000018 / POPLIN CLOTH TARTAN GREEN WIDTH 36	GENERAL USE FOR BATTERIES OF S/MS	110 / YARD	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - material composition of 100% cotton WIDTH = 36" GENERAL SPECIFICATION - material composition of 100% cotton WIDTH = 36"	
20	DGE89925	NO DATA AVAILABLE	033050000018 / POPLIN CLOTH TARTAN GREEN WIDTH 36	GENERAL USE FOR BATTERIES OF S/MS	110 / YARD	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - material composition of 100% cotton WIDTH = 36" GENERAL SPECIFICATION - material composition of 100% cotton WIDTH = 36"	
21	DGE88905	NO DATA AVAILABLE	0330780000214 / CLOTH CLEANING 6X6 44-6729 133C		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DGE87588	NO DATA AVAILABLE	0474500000307 / FENDER COIR ROUND		19 / EACH/NUMBER	600MM 24" ROUND COIR BOAT FENDER					TECHNICAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE. BIODEGRADABLE- YES. WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION. STORAGE-WET AND DRY. GENERAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE. BIODEGRADABLE- YES. WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.	
23	DGD926 84	NO DATA AVAILABL E	00355000031 8 / Aluminium covers for utensil cooking (Large) O/D 25.50" TH 10 SWG.		53 / EACH/N UMBER	NO DATA AVILAB LE					<p>TECHNICAL SPECIFICATION - Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.GENERAL SPECIFICATION - Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.</p>	
24	DGE901 38	NO DATA AVAILABL E	100570513050 4 / STEEL WIRE BRUSH (DIA 8		7 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - Diameter 08 inch Thickness 01 inchGENERAL SPECIFICATION - Diameter 08 inch Thickness 01 inch</p>	
25	DGE894 51	B2315512	471070517796 0 / FLEXIBLE PIPE 1 INCH DIA	CNA LAN NETWORK	200 / METER			ADAMJEE PAKISTAN	ADAMJEE PAKISTA N		<p>TECHNICAL SPECIFICATION - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 MeterGENERAL SPECIFICATION -</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter	
26	DGE940 89	N/A	933070518127 9 / PLASTIC SHEET	GENERAL ITEM	15 / ROLL			LOCAL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
27	DGE940 66		933070530065 4 / telic sheet (TRANSPARENT sheet) THICKNESS: 0.35MM WIDTH:54 INCH LENGTH: 25-30 meter		166 / SQ FEET	sheet					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
28	DGT940 58	NO DATA AVAILAB LE	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTABLISHMENT	9 / SHEET	NO DATA AVAILAB LE		PK		SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETANI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-	TECHNICAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM GENERAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									2578654.			
29	DGE940 22		047450474012 6 / SHAMIANA COMPLETE, SIZE: 15X30- FEET		4 / EACH/ UMBER						<p>TECHNICAL SPECIFICATION - 1. SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES (GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03 KGS WITH WOODEN HANDLE 1.5 FEET LENGTH) GENERAL SPECIFICATION - 1. SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES (GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03 KGS WITH WOODEN HANDLE 1.5 FEET LENGTH)</p>	
30	DGE836 41	NO DATA AVAILABL E	046159000648 0 / PAINT ROLLER, LENGTH= 7- INCH, DIA= 2- INCH, C/W SHEEP SKIN	BLST PAINT UNDER WATER HULL	74 / EACH/ UMBER						<p>TECHNICAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip GENERAL SPECIFICATION - a.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			COVER AND HANDLE STEEL FRAME, WOODEN HANDLE								Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip	
31	DGT940 57	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD- II (CORE INNER & OUTER PLYS OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIV E		320 / SQ FEET						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) <u>GENERAL SPECIFICATION</u> - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
32	DGE910 70	NO DATA AVAILABL E	033059571326 0 / TWINE COTTON CHALK LINE G/PURPOSE MIN BKG STRG25 LB20YDS LG; DIA 1.5mm	GENERAL PURPOSE BS 2019	50 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - BS</u> 6125 of 1981 <u>GENERAL</u> SPECIFICATION - BS 6125 of 1981	
33	DGE913 41	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sSTRAND, Z- LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	600 / FATHO M						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED. 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.</u>	
34	SGB921 88		027470910484 0 / FILE ENGINEER FLAT D-CUT FACES single cut edges, length ROUGH 12.00IN		25 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - specs: def-1098(american pattern)</u> <u>GENERAL SPECIFICATION - specs: def-1098(american pattern)</u>	
35	DGB912 22	GLORIA 510T/172R T	024370243002 2 / SPRAYER- PNEU.INSECT-		3 / EACH/ NUMBER	PRIMA-5 (GLORIA GERMAN					<u>TECHNICAL SPECIFICATION - RANGE 20 LITER NAME ORANGE USED FOR SPRAYING CLEANING</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LIQUID(13.7 LTR W/P 6 BAR GERMANY OR SUITABLE			Y)					DERTEGENTS <u>GENERAL SPECIFICATION</u> - RANGE 20 LITER NAME ORANGE USED FOR SPRAYING CLEANING DERTEGENTS	
36	DGE940 15		209050503923 2 / SLEEPING BAG COMPLETE WITH COVER		87 / EACH/ UMBER						<u>TECHNICAL SPECIFICATION</u> - a. Size: Length: - 220 cm (Tolerance of 20 cm may be given) Width: - 75 cm (Tolerance of 20 cm may be given) b. Material: Outer: - Fine quality Parachute fabric with water resistance. Inner: - Fine quality double ply polyester. c. Finishing: High quality workmanship with attached pillow. d. Colour: Black / Green / Gray / Navy Blue / Camouflage. e. Make: Local / imported. f. Usage: Item is required to be used by personal assigned task at different operational areas. Accordingly, item is to be compatible for Military troop's standard i.e easy to pack / unpack, low weight, resilient and flexible in use. g. Misc requirements: Water proof, must include carry bag. <u>GENERAL SPECIFICATION</u> - a. Size: Length: - 220 cm (Tolerance of 20 cm may be given) Width: - 75 cm (Tolerance of 20 cm may be given) b. Material: Outer: - Fine quality Parachute fabric with water resistance. Inner: - Fine quality double ply polyester. c. Finishing: High quality workmanship with attached pillow. d. Colour: Black / Green / Gray / Navy Blue / Camouflage. e. Make: Local / imported. f. Usage: Item is required to be used by personal assigned task at different operational areas. Accordingly, item is to be compatible for Military troop's standard i.e easy to pack / unpack, low weight, resilient and flexible in use. g. Misc requirements: Water proof, must	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
37	DGE939 68		209050503923 2 / SLEEPING BAG COMPLETE WITH COVER		90 / EACH/N UMBER						include carry bag. TECHNICAL SPECIFICATION - a. Size: Length: - 220 cm (Tolerance of 20 cm may be given) Width: - 75 cm (Tolerance of 20 cm may be given) b. Material: Outer: - Fine quality Parachute fabric with water resistance. Inner: - Fine quality double ply polyester. c. Finishing: High quality workmanship with attached pillow. d. Colour: Black / Green / Gray / Navy Blue / Camouflage. e. Make: Local / imported. f. Usage: Item is required to be used by personal assigned task at different operational areas. Accordingly, item is to be compatible for Military troop's standard i.e easy to pack / unpack, low weight, resilient and flexible in use. g. Misc requirements: Water proof, must include carry bag. GENERAL SPECIFICATION - a. Size: Length: - 220 cm (Tolerance of 20 cm may be given) Width: - 75 cm (Tolerance of 20 cm may be given) b. Material: Outer: - Fine quality Parachute fabric with water resistance. Inner: - Fine quality double ply polyester. c. Finishing: High quality workmanship with attached pillow. d. Colour: Black / Green / Gray / Navy Blue / Camouflage. e. Make: Local / imported. f. Usage: Item is required to be used by personal assigned task at different operational areas. Accordingly, item is to be compatible for Military troop's standard i.e easy to pack / unpack, low weight, resilient and flexible in use. g. Misc requirements: Water proof, must include carry bag.	
38	DGE939 24	NO DATA AVAILABL E	047259523774 4 / Life Bouy Ring	FOR SHIPS/BOATS	6 / EACH/N UMBER						TECHNICAL SPECIFICATION - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(Orange) with SOLAS Reflective Tape								Reflective Tape. 30" Diameter External dia 74.5 CM – Internal dia 44.5 CM Thickness 11.5CM Buoyancy Rating:181N. <u>GENERAL SPECIFICATION - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM – Internal dia 44.5 CM Thickness 11.5 CM Buoyancy Rating:181N.</u>	
39	DGE94020		047450474001 9 / TENT MK 4 COMPLETE WITH ACCESSORIES W/O JHALER WT.180 LBS	CAPACITY 5 MAN,INNER PLY 5 OZ+9 OZ,UPPER	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF &WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03 <u>GENERAL SPECIFICATION -</u> Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03</p>	
40	DGE93972		047450474001 9 / TENT MK 4 COMPLETE WITH ACCESSORIES W/O JHALER WT.180 LBS	CAPACITY 5 MAN, INNER PLY 5 OZ+9 OZ, UPPER	7 / EACH NUMBER						<p>TECHNICAL SPECIFICATION - Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03</p> <p>GENERAL SPECIFICATION - Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>accessories are required with Tent Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001. ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF &WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03</p>	
41	DGB794 61	NO DATA AVAILABL E	512073100058 2 / SOCKET SPANNER STANDARD 10-32MM 26PCSSET		2 / SET						<p><u>TECHNICAL SPECIFICATION - a.</u> Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21, 22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16) Sliding bar (10 inches) Flip drive ratchet c. Drive type: ½" square drive d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chrome</p> <p><u>GENERAL SPECIFICATION - a.</u> Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21, 22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16) Sliding bar (10 inches) Flip drive ratchet c. Drive type: ½" square drive d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chrome</p>	
42	DGB819 57	NO DATA AVAILABL E	512073100058 2 / SOCKET SPANNER STANDARD 10-32MM 26PCSSET		3 / SET						<p><u>TECHNICAL SPECIFICATION - a.</u> Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21, 22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16) Sliding bar (10 inches) Flip drive ratchet c. Drive type: ½" square drive</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chrome GENERAL SPECIFICATION - a. Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21, 22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16) Sliding bar (10 inches) Flip drive ratchet c. Drive type: 1/2" square drive d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chrome	
43	DGE94088		535000235013 7 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE 2/0		160 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DGE94000	NO DATA AVAILABLE	562050504233 5 / TILES CERAMIC GLAZED COLOUR WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")	DECK COVERING	1130 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DGE88803	MIL-P-15280	564000237482 7 / INSULATION SLEEVING THERMAL		95 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
46	DGE94090	0413-2184	597099923966 4 / TAP INSULATION ELECT ADHESIVE PLASTIC RED W1	FOR RED PHASE	60 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing <u>GENERAL SPECIFICATION</u> _Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing	
47	DGE94091	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		60 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes <u>GENERAL SPECIFICATION</u> - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
48	DGE93918	NO DATA AVAILABL E	041350000013 4 / EAR DEFENDER LARGE SIZE		50 / PAIR	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
49	DGE94004		8340PK507382 7 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIE S		2 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - 1. DIMENSION/ SIZE: A. TENT SIZE= 20 X 16 FEET (± 0.6 INCH) B. WALL HEIGHT= 06 FEET (± 0.6 INCH) C. HEIGHT OF TENT= 12 FEET (± 0.6 INCH) 2. SPECIFICATION: A. CANVAS COTTON= 450/500 GSM (WITH WATER PROOFING, ROT PROOFING, DOUBLE FLY WITH SINGLE FOLD, DOSUTI FABRIC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>150 TO 180 GSM (GREEN/ YELLOW) B. COLOR OF TENT= OLIVE GREEN (COLOR CODE FOR MATCHING PURPOSE I.E RAL-6003) C. PACKING COMPLETE TENT AND ACCESSORIES IN TWO BAG. 3. LIST OF ACCESSORIES: A. IRON STANDING POLES= 02 IN NOS (LENGTH: 12 FEET & THICKNESS: 1.5 MM) (JOINTED WITH MALE/ FEMALE), B. IRON RICH POLE= 01 IN NO (LENGTH: 7 X FEET & THICKNESS: 1.5 MM) C. ROPE= 40 IN NOS (STANDARD SIZE & DIA: 12-14 MM) D. HAMMER= 01 IN NO (5 X KGS WEIGHT WITH WOODEN HANDLE) E. IRON PEGS= 40 IN NOS (LENGTH: 18 INCH & THICKNESS: 18 MM)</p> <p><u>GENERAL SPECIFICATION</u> <u>1. DIMENSION/ SIZE:</u> A. TENT SIZE= 20 X 16 FEET (± 0.6 INCH) B. WALL HEIGHT= 06 FEET (± 0.6 INCH) C. HEIGHT OF TENT= 12 FEET (± 0.6 INCH) 2. SPECIFICATION: A. CANVAS COTTON= 450/500 GSM (WITH WATER PROOFING, ROT PROOFING, DOUBLE FLY WITH SINGLE FOLD, DOSUTI FABRIC 150 TO 180 GSM (GREEN/ YELLOW) B. COLOR OF TENT= OLIVE GREEN (COLOR CODE FOR MATCHING PURPOSE I.E RAL-6003) C. PACKING COMPLETE TENT AND ACCESSORIES IN TWO BAG. 3. LIST OF ACCESSORIES: A. IRON STANDING POLES= 02 IN NOS (LENGTH: 12 FEET & THICKNESS: 1.5 MM) (JOINTED WITH MALE/ FEMALE), B. IRON RICH POLE= 01 IN NO (LENGTH: 7 X FEET & THICKNESS: 1.5 MM) C. ROPE= 40 IN NOS (STANDARD SIZE & DIA: 12-14 MM) D.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
50	DGE939 34		8340PK507382 7 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIE S		2 / EACH/N UMBER						<p>HAMMER= 01 IN NO (5 X KGS WEIGHT WITH WOODEN HANDLE) E. IRON PEGS= 40 IN NOS (LENGTH: 18 INCH & THICKNESS: 18 MM)</p> <p>TECHNICAL SPECIFICATION - 1. DIMENSION/ SIZE: A. TENT SIZE= 20 X 16 FEET (± 0.6 INCH) B. WALL HEIGHT= 06 FEET (± 0.6 INCH) C. HEIGHT OF TENT= 12 FEET (± 0.6 INCH) 2. SPECIFICATION: A. CANVAS COTTON= 450/500 GSM (WITH WATER PROOFING, ROT PROOFING, DOUBLE FLY WITH SINGLE FOLD. DOSUTI FABRIC 150 TO 180 GSM (GREEN/ YELLOW) B. COLOR OF TENT= OLIVE GREEN (COLOR CODE FOR MATCHING PURPOSE I.E RAL-6003) C. PACKING COMPLETE TENT AND ACCESSORIES IN TWO BAG. 3. LIST OF ACCESSORIES: A. IRON STANDING POLES= 02 IN NOS (LENGTH: 12 FEET & THICKNESS: 1.5 MM) (JOINED WITH MALE/ FEMALE), B. IRON RICH POLE= 01 IN NO (LENGTH: 7 X FEET & THICKNESS: 1.5 MM) C. ROPE= 40 IN NOS (STANDARD SIZE & DIA: 12-14 MM) D. HAMMER= 01 IN NO (5 X KGS WEIGHT WITH WOODEN HANDLE) E. IRON PEGS= 40 IN NOS (LENGTH: 18 INCH & THICKNESS: 18 MM)GENERAL SPECIFICATION - 1. DIMENSION/ SIZE: A. TENT SIZE= 20 X 16 FEET (± 0.6 INCH) B. WALL HEIGHT= 06 FEET (± 0.6 INCH) C. HEIGHT OF TENT= 12 FEET (± 0.6 INCH) 2. SPECIFICATION: A. CANVAS COTTON= 450/500 GSM (WITH WATER PROOFING, ROT PROOFING, DOUBLE FLY WITH SINGLE FOLD, DOSUTI FABRIC</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											150 TO 180 GSM (GREEN/YELLOW) B. COLOR OF TENT= OLIVE GREEN (COLOR CODE FOR MATCHING PURPOSE I.E RAL-6003) C. PACKING COMPLETE TENT AND ACCESSORIES IN TWO BAG. 3. LIST OF ACCESSORIES: A. IRON STANDING POLES= 02 IN NOS (LENGTH: 12 FEET & THICKNESS: 1.5 MM) (JOINTED WITH MALE/ FEMALE), B. IRON RICH POLE= 01 IN NO (LENGTH: 7 X FEET & THICKNESS: 1.5 MM) C. ROPE= 40 IN NOS (STANDARD SIZE & DIA: 12-14 MM) D. HAMMER= 01 IN NO (5 X KGS WEIGHT WITH WOODEN HANDLE) E. IRON PEGS= 40 IN NOS (LENGTH: 18 INCH & THICKNESS: 18 MM)	
51	DGE940 14		834070508791 3 / TENT 40 POUND, ARMY PATT, FLY & FOLD DOUBLE, (JUNGLE GREEN)	GENERAL PERPOSE	2/ EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. SIZE= 6X7 FEET 2. Tent 40 Pounds Army Pattern A. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 3. On inner fly with curtains on sides and walls fitted with pockets 4. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 5. ACCESSORIES: A. STANDING POLE QTY= 02 NO, B. RICH POLE, QTY= 01 NO, C. IRON PEGS QTY= 12, STANDARD SIZE, C. Rope QTY= 12, STANDARD SIZE, E. Hammer QTY= 01NO (3 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET), F. PACKING BAG QTY= 02 NO. 6. Testing/Acceptance Criteria: CINS/END USER</p> <p>GENERAL SPECIFICATION - 1. SIZE= 6X7 FEET 2. Tent 40 Pounds</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Army Pattern A. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 3. On inner fly with curtains on sides and walls fitted with pockets 4. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 5. ACCESSORIES: A. STANDING POLE QTY= 02 NO, B. RICH POLE, QTY= 01 NO, C. IRON PEGS QTY= 12, STANDARD SIZE, C. Rope QTY= 12, STANDARD SIZE, E. Hammer QTY= 01NO (3 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET), F. PACKING BAG QTY= 02 NO. 6. Testing/Acceptance Criteria: CINS/END USER</p>	
52	DGE939 45		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIE S)	OLIVE GREEN WATERPROO F INNER LINNING OF,	1/ EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. SPECIFICATIONS: PSG-600, 2. SIZE/ DIMENSION: A. LENGTH: 50 FEET (±0.5 FEET), B. WIDTH: 20 FEET (±0.2 FEET), C. RIDGE HEIGHT: 12 TO 14 FEET, D. SIDE WALL HEIGHT: 7 TO 8 FEET (DETACHABLE ALL ROUND WITH SUITABLE DOORS), 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. SPECIFICATION OF CANVAS COTTON: A. CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF FIRE PROOF. B. OUTER FOLDS: WATER PROOF, C. INNER FOLDS: SHEETING CLOTH & CANVAS DYED, D. NO OF DOORS: 02 E. NO OF WINDOW: 08 F. TAPE NEWAR: CANVAS COTTON, G. NO OF FOLDS: 02 5. LIST OF ACCESSORIES: A. UPRIGHT POLES: 04 QTY B. RIDGE POLES: 03 QTY C. ROPES:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>34 QTY (STANDARD SIZE) D. PEGS: 34 QTY (STANDARD SIZE) E. HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. DIAMETER OF POLES: 40 MM G. GAUGE OF POLES: 16 GAUGE H. LENGTH OF PINS: 12 INCH J. FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET K. PACKING: 02 QTY</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS: PSG-600, 2. SIZE/ DIMENSION: A. LENGTH: 50 FEET (±0.5 FEET), B. WIDTH: 20 FEET (±0.2 FEET), C. RIDGE HEIGHT: 12 TO 14 FEET, D. SIDE WALL HEIGHT: 7 TO 8 FEET (DETACHABLE ALL ROUND WITH SUITABLE DOORS), 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. SPECIFICATION OF CANVAS COTTON: A. CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF FIRE PROOF. B. OUTER FOLDS: WATER PROOF, C. INNER FOLDS: SHEETING CLOTH & CANVAS DYED, D. NO OF DOORS: 02 E. NO OF WINDOW: 08 F. TAPE NEWAR: CANVAS COTTON, G. NO OF FOLDS: 02 5. LIST OF ACCESSORIES: A. UPRIGHT POLES: 04 QTY B. RIDGE POLES: 03 QTY C. ROPES: 34 QTY (STANDARD SIZE) D. PEGS: 34 QTY (STANDARD SIZE) E. HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. DIAMETER OF POLES: 40 MM G. GAUGE OF POLES: 16 GAUGE H. LENGTH OF PINS: 12 INCH J. FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
53	DGE940 12		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIE S)	OLIVE GREEN WATERPROO F INNER LINNING OF,	1/ EACH/N UMBER						<p>SHEET K. PACKING: 02 QTY</p> <p><u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS: PSG-600, 2. SIZE/ DIMENSION: A. LENGTH: 50 FEET (±0.5 FEET), B. WIDTH: 20 FEET (±0.2 FEET), C. RIDGE HEIGHT: 12 TO 14 FEET, D. SIDE WALL HEIGHT: 7 TO 8 FEET (DETACHABLE ALL ROUND WITH SUITABLE DOORS), 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. SPECIFICATION OF CANVAS COTTON: A. CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF FIRE PROOF. B. OUTER FOLDS: WATER PROOF, C. INNER FOLDS: SHEETING CLOTH & CANVAS DYED, D. NO OF DOORS: 02 E. NO OF WINDOW: 08 F. TAPE NEWAR: CANVAS COTTON, G. NO OF FOLDS: 02 5. LIST OF ACCESSORIES: A. UPRIGHT POLES: 04 QTY B. RIDGE POLES: 03 QTY C. ROPES: 34 QTY (STANDARD SIZE) D. PEGS: 34 QTY (STANDARD SIZE) E. HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. DIAMETER OF POLES: 40 MM G. GAUGE OF POLES: 16 GAUGE H. LENGTH OF PINS: 12 INCH J. FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET K. PACKING: 02 QTY</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS: PSG-600, 2. SIZE/ DIMENSION: A. LENGTH: 50 FEET (±0.5 FEET), B. WIDTH: 20 FEET (±0.2 FEET), C. RIDGE HEIGHT: 12 TO 14 FEET, D. SIDE WALL HEIGHT: 7 TO 8 FEET (DETACHABLE ALL ROUND WITH SUITABLE DOORS), 3. COLOUR:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>JUNGLE GREEN (COLOUR CODE 3A5F31), 4. SPECIFICATION OF CANVAS COTTON: A. CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF FIRE PROOF. B. OUTER FOLDS: WATER PROOF, C. INNER FOLDS: SHEETING CLOTH & CANVAS DYED, D. NO OF DOORS: 02 E. NO OF WINDOW: 08 F. TAPE NEWAR: CANVAS COTTON, G. NO OF FOLDS: 02 5. LIST OF ACCESSORIES: A. UPRIGHT POLES: 04 QTY B. RIDGE POLES: 03 QTY C. ROPES: 34 QTY (STANDARD SIZE) D. PEGS: 34 QTY (STANDARD SIZE) E. HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. DIAMETER OF POLES: 40 MM G. GAUGE OF POLES: 16 GAUGE H. LENGTH OF PINS: 12 INCH J. FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET K. PACKING: 02 QTY</p>	
54	DGE940 11		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1/ EACH/ NUMBER						<p>TECHNICAL SPECIFICATION - SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>(WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150-180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3. ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY</p> <p><u>GENERAL SPECIFICATION</u> - SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF (WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150-</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3. ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY	
55	DGE939 36		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1/ EACH/ NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF (WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150- 180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3.</p> <p>ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY</p> <p><u>GENERAL SPECIFICATION</u> <u>- SPECIFICATION: 1. SIZES/ DIMENSION</u> • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%)</p> <p><u>2. SPECIFICATION:</u> • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF (WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150-180 G/M2 (5/8 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE :</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3. ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY	
56	DGE93362		834070508791 6 / TENT MARQUEE UNIVERSAL G. S (SIZE 27X19.6FT) FOLD & FLY TWO (J/GREEN)	GENERAL PURPOSE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE: • LENGTH: 27 FEET (±0.5 FEET), • WIDTH: 19.6 FEET (±0.2 FEET), • CENTER HEIGHT: 12.30 FEET, • WALL HEIGHT: 5.90 FEET, 2. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 3. SPECIFICATION: • 550/ 600 GSM (± 5%) 100 % WATER PROOF COTTON CANVAS, • WATER AND ROT RESISTANT, • GROUND SHEET AND MUD FLAP: 180 GSM (± 5%, 4. LIST OF ACCESSORIES= • STANDING POLES: 02 QTY, • RIDGE POLE: 01 QTY, • SIDE/ WALL POLES: 08-12 QTY • CORNER POLES: 04 X QTY • HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) • IRON PEGS: 24 QTY (45/45 CM LONG THICKNESS 18/19 MM • GUY ROPES: 48 QTY, THICKNESS: 14-MM, LENGTH: 3.60 MTR.) • WALL PIPE LATHI: 24 QTY • DIAMETER OF POLES: 54 MM • GAUGE OF POLES: 1.5 MM • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SHEET • PACKING: 02 QTY</p> <p>GENERAL SPECIFICATION - 1. SIZE: • LENGTH: 27 FEET (±0.5 FEET), • WIDTH: 19.6 FEET (±0.2 FEET), • CENTER HEIGHT: 12.30 FEET, • WALL HEIGHT: 5.90 FEET, 2. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 3. SPECIFICATION: • 550/ 600 GSM (± 5%) 100 % WATER PROOF COTTON CANVAS, • WATER AND ROT RESISTANT, • GROUND SHEET AND MUD FLAP: 180 GSM (± 5%, 4. LIST OF ACCESSORIES=</p> <p>• STANDING POLES: 02 QTY, • RIDGE POLE: 01 QTY, • SIDE/ WALL POLES: 08-12 QTY • CORNER POLES: 04 X QTY • HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) • IRON PEGS: 24 QTY (45/45 CM LONG THICKNESS 18/19 MM • GUY ROPES: 48 QTY, THICKNESS: 14-MM, LENGTH: 3.60 MTR,) • WALL PIPE LATHI: 24 QTY • DIAMETER OF POLES: 54 MM • GAUGE OF POLES: 1.5 MM • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET • PACKING: 02 QTY</p>	
57	DGE93288		834070508791 6 / TENT MARQUEE UNIVERSAL G. S (SIZE 27X19.6FT) FOLD & FLY TWO (J/GREEN)	GENERAL PURPOSE	1/ EACH/NUMBER						<p>TECHNICAL SPECIFICATION - 1. SIZE: • LENGTH: 27 FEET (±0.5 FEET), • WIDTH: 19.6 FEET (±0.2 FEET), • CENTER HEIGHT: 12.30 FEET, • WALL HEIGHT: 5.90 FEET, 2. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 3. SPECIFICATION: • 550/ 600 GSM (± 5%) 100 % WATER PROOF COTTON CANVAS, • WATER AND ROT RESISTANT, • GROUND SHEET AND MUD FLAP: 180 GSM (± 5%, 4. LIST OF ACCESSORIES=</p> <p>• STANDING POLES: 02 QTY, •</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>RIDGE POLE: 01 QTY, • SIDE/ WALL POLES: 08-12 QTY • CORNER POLES: 04 X QTY • HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) • IRON PEGS: 24 QTY (45/45 CM LONG THICKNESS 18/19 MM • GUY ROPES: 48 QTY, THICKNESS: 14- MM, LENGTH: 3.60 MTR,) • WALL PIPE LATHI: 24 QTY • DIAMETER OF POLES: 54 MM • GAUGE OF POLES: 1.5 MM • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET • PACKING: 02 QTY</p> <p><u>GENERAL SPECIFICATION - 1.</u> SIZE: • LENGTH: 27 FEET (±0.5 FEET), • WIDTH: 19.6 FEET (±0.2 FEET), • CENTER HEIGHT: 12.30 FEET, • WALL HEIGHT: 5.90 FEET, 2. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 3. SPECIFICATION: • 550/ 600 GSM (± 5%) 100 % WATER PROOF COTTON CANVAS, • WATER AND ROT RESISTANT, • GROUND SHEET AND MUD FLAP: 180 GSM (± 5%, 4. LIST OF ACCESSORIES= • STANDING POLES: 02 QTY, • RIDGE POLE: 01 QTY, • SIDE/ WALL POLES: 08-12 QTY • CORNER POLES: 04 X QTY • HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) • IRON PEGS: 24 QTY (45/45 CM LONG THICKNESS 18/19 MM • GUY ROPES: 48 QTY, THICKNESS: 14- MM, LENGTH: 3.60 MTR,) • WALL PIPE LATHI: 24 QTY • DIAMETER OF POLES: 54 MM • GAUGE OF POLES: 1.5 MM • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
58	DGE940 10		834070508791 6 / TENT MARQUEE UNIVERSAL G. S (SIZE 27X19. 6FT) FOLD & FLY TWO (J/GREEN)	GENERAL PURPOSE	1/ EACH/ UMBER						<p>SHEET • PACKING: 02 QTY</p> <p><u>TECHNICAL SPECIFICATION - 1.</u> SIZE: • LENGTH: 27 FEET (±0.5 FEET), • WIDTH: 19.6 FEET (±0.2 FEET), • CENTER HEIGHT: 12.30 FEET, • WALL HEIGHT: 5.90 FEET, 2. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 3. SPECIFICATION: • 550/ 600 GSM (± 5%) 100 % WATER PROOF COTTON CANVAS, • WATER AND ROT RESISTANT, • GROUND SHEET AND MUD FLAP: 180 GSM (± 5%, 4. LIST OF ACCESSORIES= • STANDING POLES: 02 QTY, • RIDGE POLE: 01 QTY, • SIDE/ WALL POLES: 08-12 QTY • CORNER POLES: 04 X QTY • HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) • IRON PEGS: 24 QTY (45/45 CM LONG THICKNESS 18/19 MM • GUY ROPES: 48 QTY, THICKNESS: 14-MM, LENGTH: 3.60 MTR,) • WALL PIPE LATHI: 24 QTY • DIAMETER OF POLES: 54 MM • GAUGE OF POLES: 1.5 MM • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET • PACKING: 02 QTY</p> <p><u>GENERAL SPECIFICATION - 1.</u> SIZE: • LENGTH: 27 FEET (±0.5 FEET), • WIDTH: 19.6 FEET (±0.2 FEET), • CENTER HEIGHT: 12.30 FEET, • WALL HEIGHT: 5.90 FEET, 2. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 3. SPECIFICATION: • 550/ 600 GSM (± 5%) 100 % WATER PROOF COTTON CANVAS, • WATER AND ROT RESISTANT, • GROUND SHEET AND MUD FLAP: 180 GSM (± 5%, 4. LIST OF ACCESSORIES= • STANDING POLES: 02 QTY, •</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>RIDGE POLE: 01 QTY, • SIDE/ WALL POLES: 08-12 QTY • CORNER POLES: 04 X QTY • HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) • IRON PEGS: 24 QTY (45/45 CM LONG THICKNESS 18/19 MM • GUY ROPES: 48 QTY, THICKNESS: 14-MM, LENGTH: 3.60 MTR.) • WALL PIPE LATHI: 24 QTY • DIAMETER OF POLES: 54 MM • GAUGE OF POLES: 1.5 MM • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET • PACKING: 02 QTY</p>	
59	DGE93287	NO DATA AVAILABL E	834070501408 4 / TENT FOR CPOS/SAILOR S, WT= 120 LBS, ALONGWITH COMPLETE ACCESSORIE S		4 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM : 1. SIZE/ DIMENSION A. LENGTH: 10 FEET, B. WIDTH: 10 FEET C. WALL HEIGHT: 07 FEET, D. TENT WALL: MADE OUT OF 400/G M2 2. OTHER SPECIFICATION: A. CANVAS COTTON: ROT PROOF, WATER PROOF, AND VAT DYED CANVAS, B. INNER LINING: MADE OUT OF 180-200/G M2, C. TENT PROOF: MADE OUT OF 450/G M2 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. LIST OF ACCESSORIES A. STANDARD POLE: 03 X QTY B. RICH POLE: 02 X QTY, C. PEGS IRON: 12 X QTY (STANDARD SIZE) D. ROPES: 12 X QTY QTY (STANDARD SIZE) E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. PACKING BAG: 02 QTY</p> <p>GENERAL SPECIFICATION - SPECIFICATION OF ITEM : 1. SIZE/ DIMENSION A. LENGTH: 10 FEET, B. WIDTH: 10 FEET C. WALL HEIGHT: 07 FEET, D. TENT WALL: MADE OUT OF 400/G M2 2. OTHER SPECIFICATION: A. CANVAS</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>COTTON: ROT PROOF, WATER PROOF, AND VAT DYED CANVAS, B. INNER LINING: MADE OUT OF 180-200/G M2, C. TENT PROOF: MADE OUT OF 450/G M2 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. LIST OF ACCESSORIES A. STANDARD POLE: 03 X QTY B. RICH POLE: 02 X QTY, C. PEGS IRON: 12 X QTY (STANDARD SIZE) D. ROPES: 12 X QTY QTY (STANDARD SIZE) E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. PACKING BAG: 02 QTY</p>	
60	DGE93780	NO DATA AVAILAB LE	834070501408 4 / TENT FOR CPOS/SAILOR S, WT= 120 LBS, ALONGWITH COMPLETE ACCESSORIE S		4 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM : 1. SIZE/ DIMENSION A. LENGTH: 10 FEET, B. WIDTH: 10 FEET C. WALL HEIGHT: 07 FEET, D. TENT WALL: MADE OUT OF 400/G M2 2. OTHER SPECIFICATION: A. CANVAS COTTON: ROT PROOF, WATER PROOF, AND VAT DYED CANVAS, B. INNER LINING: MADE OUT OF 180-200/G M2, C. TENT PROOF: MADE OUT OF 450/G M2 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. LIST OF ACCESSORIES A. STANDARD POLE: 03 X QTY B. RICH POLE: 02 X QTY, C. PEGS IRON: 12 X QTY (STANDARD SIZE) D. ROPES: 12 X QTY QTY (STANDARD SIZE) E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. PACKING BAG: 02 QTY</p> <p>GENERAL SPECIFICATION - SPECIFICATION OF ITEM : 1. SIZE/ DIMENSION A. LENGTH: 10 FEET, B. WIDTH: 10 FEET C. WALL HEIGHT: 07 FEET, D. TENT WALL: MADE OUT OF 400/G M2 2. OTHER SPECIFICATION: A. CANVAS</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>COTTON: ROT PROOF, WATER PROOF, AND VAT DYED CANVAS, B. INNER LINING: MADE OUT OF 180-200/G M2, C. TENT PROOF: MADE OUT OF 450/G M2 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. LIST OF ACCESSORIES A. STANDARD POLE: 03 X QTY B. RICH POLE: 02 X QTY, C. PEGS IRON: 12 X QTY (STANDARD SIZE) D. ROPES: 12 X QTY QTY (STANDARD SIZE) E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. PACKING BAG: 02 QTY</p>	
61	DGE93363	NO DATA AVAILABLE	834070501408 4 / TENT FOR CPOS/SAILORS, WT= 120 LBS, ALONGWITH COMPLETE ACCESSORIES		4 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM : 1. SIZE/ DIMENSION A. LENGTH: 10 FEET, B. WIDTH: 10 FEET C. WALL HEIGHT: 07 FEET, D. TENT WALL: MADE OUT OF 400/G M2 2. OTHER SPECIFICATION: A. CANVAS COTTON: ROT PROOF, WATER PROOF, AND VAT DYED CANVAS, B. INNER LINING: MADE OUT OF 180-200/G M2, C. TENT PROOF: MADE OUT OF 450/G M2 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. LIST OF ACCESSORIES A. STANDARD POLE: 03 X QTY B. RICH POLE: 02 X QTY, C. PEGS IRON: 12 X QTY (STANDARD SIZE) D. ROPES: 12 X QTY QTY (STANDARD SIZE) E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. PACKING BAG: 02 QTY</p> <p>GENERAL SPECIFICATION - SPECIFICATION OF ITEM : 1. SIZE/ DIMENSION A. LENGTH: 10 FEET, B. WIDTH: 10 FEET C. WALL HEIGHT: 07 FEET, D. TENT WALL: MADE OUT OF 400/G M2 2. OTHER SPECIFICATION: A. CANVAS</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>COTTON: ROT PROOF, WATER PROOF, AND VAT DYED CANVAS, B. INNER LINING: MADE OUT OF 180-200/G M2, C. TENT PROOF: MADE OUT OF 450/G M2 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. LIST OF ACCESSORIES A. STANDARD POLE: 03 X QTY B. RICH POLE: 02 X QTY, C. PEGS IRON: 12 X QTY (STANDARD SIZE) D. ROPES: 12 X QTY QTY (STANDARD SIZE) E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. PACKING BAG: 02 QTY</p>	
62	DGE94009	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	2 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAGE					<p>TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25- INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p>	
63	DGE939 31	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATIO N	2 / EACH/N UMBER	OPTICAL INFRARE D CAMOUF LAGE NET, ANTI RADAR CAMOUF LAG					<p>TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE=</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p> <p>TECHNICAL SPECIFICATION - P-SG/730 (B) SIZE: LENGTH=12-16 FT, WIDTH=09-18 INCH,</p>	
64	DGT844 20	NO DATA AVAILABL E	010050000004 9 / TEAK WOOD	SPECE/IM. 2763 (A)	10 / CUBIC FOOT	NO DATA AVAILAB LE						

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BURMESE GRADE-I SLEEPER								THICKNESS=8-10 INCH. Moisture Content= 12%±02% GENERAL SPECIFICATION - P-SG/730 (B) SIZE: LENGTH=12-16 FT, WIDTH=09-18 INCH, THICKNESS=8-10 INCH. Moisture Content= 12%±02%	
65	DGT863 34	NO DATA AVAILAB LE	04155000000 9 / FORMICA ENGRAVING WHITE FACE BLACK CORE (1220MMX1220MMX1.57MM		13 / SHEET						TECHNICAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness. GENERAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness.	
66	DGT941 70	NO DATA AVAILAB LE	01005000003 9 / TIMBER FIR HIMALAYA/ SPRUCE SLEEPER, WELL SEASONED LOCAL/ IMPORTED, SIZE: L=8'-15', W=8"-14", h=4"-10"	(3.05MTR X254 MM X127 MM) SPECE/PSG 69	33 / CUBIC FOOT						TECHNICAL SPECIFICATION - SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%, GENERAL SPECIFICATION - SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%,	
67	DGE888 08	N/A	933070518127 9 / PLASTIC SHEET	GENERAL ITEM	7 / ROLL			LOCAL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
68	DGE850 52	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	10 / EACH/NUMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4		GERMAN Y	TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω GENERAL SPECIFICATION - a.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
69	SGB93209		027679910583 2 / SCRAPER ENGINEER LG 6"		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	SGB93201	NO DATA AVAILABLE	026559423357 1 / NAIL-STEEL-WIRE-1.50	P/N. 0265-17041	200 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	SGB93212	0265-111	026559423319 5 / NAIL STEEL WIRE ROUND, CHEQUEReD HD, SWG 9 LG 3.0 IN (LOCAL)		130 / KILOGRAMME	local					TECHNICAL SPECIFICATION - nail steel wire round 3 inch GENERAL SPECIFICATION - nail steel wire round 3 inch	
72	DGE94164	NO DATA AVAILABLE	562050504233 5 / TILES CERAMIC GLAZED COLOUR WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")	DECK COVERING	1200 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DGE94240	NO DATA AVAILABLE	562050504233 5 / TILES CERAMIC GLAZED COLOUR WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")	DECK COVERING	1200 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DGH94330		614570505767 9 / CABLE ELEC 4COR O/D-52MM N/STRAND-36		250 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			S/D-2MM C/D-18MM 280AMP									
75	DGD94218	LG-MP-9482 SR	7310735118939 / MICROWAVE OVEN-LG SHARP WAVES/DAWLANCE & TOSHIBA	MICROWAVE OVEN LG	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - capacity: 36 LITTERs GENERAL SPECIFICATION - capacity: 36 LITTERs	
76	DGD94143	XG1910200103	7310705344787 / CHARCOAL GRILL		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - Color BLACK Grill Size MEDIUM MPN XG1910200103 Item Depth 44.88 IN (114 CM) (114 CM) Fuel Type CHARCOAL Brand UNBRANDED Type PORTABLE Griddle Material STEEL Manufacturer WARRANTY 2 YEARS Item Height 42.32 in (107.5 cm) (107.5 cm) Model XG1910200103 Country/Region of Manufacture i United States Item Width 26.38 in (67 cm) (67 cm) UPC 1 Does not apply / Item Weight 36 lbs (16.33 kg) GENERAL SPECIFICATION - Color BLACK Grill Size MEDIUM MPN XG1910200103 Item Depth 44.88 IN (114 CM) (114 CM) Fuel Type CHARCOAL Brand UNBRANDED Type PORTABLE Griddle Material STEEL Manufacturer WARRANTY 2 YEARS Item Height 42.32 in (107.5 cm) (107.5 cm) Model XG1910200103 Country/Region of Manufacture i United States Item Width 26.38 in (67 cm) (67 cm) UPC 1 Does not apply / Item Weight 36 lbs (16.33 kg)	
77	DGE72269	RB10002 local	6150705264085 / INSULATION RUBBER MAT		120 / FOOT	NA					TECHNICAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm. GENERAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm.	
78	DGD94148	10755-36	7310705344785 / 107SS RAYS		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - Weight 65 kgs Brands rays Top Cover METAL TOP COOKING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COOKING CABINET								CABINET 5 Burner Features: • 5 Burner Gas Burner • Panel & Top • Heavy Grates • Big Size Burners • Double Door • Metal Top Safely Packed <u>GENERAL SPECIFICATION</u> _Weight 65 kgs Brands rays Top Cover METAL TOP COOKING CABINET 5 Burner Features: • 5 Burner Gas Burner • Panel & Top • Heavy Grates • Big Size Burners • Double Door • Metal Top Safely Packed	
79	DGE679 22	010422003 1	454070524596 0 / grohe Baucosmo e infra red electronic basin mixture with mixing device chrome na		6 / EACH/ UMBER	01042200 31					<u>TECHNICAL SPECIFICATION -</u> GORHE BAUCOSMO e infra red electronic basin mixer with mixing device chrome. ITEM IS TO BE USED IN ALL WASH BASINS FOR economical PROVISION OF WATER <u>GENERAL SPECIFICATION</u> _GORHE BAUCOSMO e infra red electronic basin mixer with mixing device chrome. ITEM IS TO BE USED IN ALL WASH BASINS FOR economical PROVISION OF WATER	
80	DGD941 47		731070534478 6 / HOT/ COLD BAIN MARIE		1 / EACH/ UMBER	N/A					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
81	DGB813 54		026459001387 5 / WASH BASIN FOR ADMIRAL AND CAPTAN QUATERS SIZE 25X18"		8 / EACH/ UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
82	DGD910 91	T52254 / E-6228	732099759431 1 / VEGETABLE PEELING MACHINE, ELECTRIC	GALLEY	1 / EACH/ UMBER	NO DATA AVAILAB LE		UK		HOBART MANUFA CTURING UK, STREET BRAUNT ON ROAD CITY BARNST APLE, STATE	<u>TECHNICAL SPECIFICATION -</u> Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT. 440V <u>GENERAL SPECIFICATION -</u> Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT.440V	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									OR PROVINC E, DEVON, COUNTR Y UK POST-ZIP CODE. EX31 1GD, TELEPHO NE, 01271347 500, TELEFAX . 01271347 502			