PAKISTAN NAVY

TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 23-12-2025

TERMS & CONDITION

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT".

2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.

3. LAB TESTING CHARGES IF ANY WILL BE BORN BY FIRM.

5. BAD TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNQ90570	CEN1000063A	5510FT1019830 / Wooden Plug, 200 x 30 x 8 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
2	DPC91146	A020EEV2	8010705332825 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		450 / LITER	HIGHLY PERFUMED				.	TECHNICAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation. GENERAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.	
3	DNQ90571	CEN1000063C	5510FT1019832 / Wooden Plug 250 x 70 x 20 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
4	DNQ91234	CEN1000063D	5510FT1019833 / Wooden Plug 250 x 100 x 40 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
5	DNQ90572	CEN1000063D	5510FT1019833 / Wooden Plug 250 x 100 x 40 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
6	DNQ91233	CEN1000063E	5510FT1019834 / Wooden Plug 300 x 120 x 50 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
7	DNQ90573	CEN1000063E	5510FT1019834 / Wooden Plug 300 x 120 x 50 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
8	DNM90587	2652C112	4130795171901 / AIR FILTER	60 KVA PERKINS	7 / EACH/NUMBER	DK 51280	4ZK05396	PERKINS UK	PERKIN UK	.	TECHNICAL SPECIFICATION - a. OEM: Perkins Engines Ltd. Frank Perkins Way Peter Borough, PE1 5FQ United Kingdom c. Technical parameters of store: Width 190mm i. e Dimensions /sizes and etc: Height: 450mm (Packaged) d. Model Number : 02K18 (P) e. Country of origin: United KingdomGENERAL SPECIFICATION - a.OEM: Perkins Engines Ltd. Frank Perkins Way Peter Borough, PE1 5FQ United Kingdom c. Technical parameters of store: Width 190mm i.e Dimensions /sizes and etc: Height: 450mm (Packaged) d. Model Number : 02K18 (P) e. Country of origin: United Kingdom	
9	DPK89705	VP85108974	4320735157688 / SYNTHETIC COMPRESSOR OIL (Brand = VOLVO) ISO VG 80 (250 ML = Packing)	MAIN ENGINE VOLVO PENTA	80 / EACH/NUMBER		2006032390	AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN SE-405 08 GOTEBORG	VOLVO PANTA SWEDEN	.	TECHNICAL SPECIFICATION - OEM & SOURCE OF AVAILABILTY: AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN SE-405 08 GOTEBORG GENERAL SPECIFICATION - OEM & SOURCE OF AVAILABILTY:AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN SE-405 08 GOTEBORG	
10	DNQ90132	04834009/ LOCAL	6510795175760 / ADHESIVE TAPE WIDTH 2 INCHES	LIFE RAFT	10 / EACH/NUMBER	UK (RFD BEAUFORT)	04834009	RFD BEAUFORT LTD (UK)	RFD BEAUFORT LTD (UK)	.	TECHNICAL SPECIFICATION - ADHESIVE TAPE BLACK, RFD BEAUFORT LTD (UK)GENERAL SPECIFICATION - ADHESIVE TAPE BLACK, RFD BEAUFORT LTD (UK)	
11	DPC88507	NO DATA AVAILABLE	0443500443067 / Gas Nitrogen Technical (99.998% Pure	A/C NO 5 AND 6	55 / CUBIC METER					.	TECHNICAL SPECIFICATION - CGA G-10.1 OF 2008 QVLs GRADE 'L' Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Nitrogen Gas With Less Water Content (i.e. 4 PPM), In Buyer's/ Supplier's Returnable Cylinder of Water Capacity 45 to 55 Liters With Protection Cap.								seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder. GENERAL SPECIFICATION - CGA G-10.1 OF 2008 QVLs GRADE 'L' Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder.	
12	DPC92674	NO DATA AVAILABLE	0443500443067 / Gas Nitrogen Technical (99.998% Pure Nitrogen Gas With Less Water Content (i.e. 4 PPM), In Buyer's/	A/C NO 5 AND 6	10 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G-10.1 OF 2008 QVLs GRADE 'L' Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Supplier's Returnable Cylinder of Water Capacity 45 to 55 Liters With Protection Cap.								material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder. GENERAL SPECIFICATION - CGA G-10.1 OF 2008 QVLs GRADE 'L' Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder.	
13	DPC92673		0443705054896 / GAS HELIUM 99.995% PURE (CYLIDER 9.40 CUBIC M)		9.4 / CUBIC METER						TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	
14	DPC92672	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1634.4 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum):	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
15	DPC92642	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
16	DPC92591	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ft3, NIL, 1.GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
17	DPC85641	-	0474500474006 4 / SOAP HARD YELLOW 300 gram each (sufinirol soap or equivalent)		602 / KILOGRAMME					.	TECHNICAL SPECIFICATION - S. No Characteristics Range % Ref to Clause no in PS: 406-1964 01 Total Fatty Matter % 59 ± 1 15 02 Free Caustic Alkali as Sodium Hydroxide % 1 - 3 6 03 Chloride as Sodium Chloride % 0.1-0.2 10 04 Matter Insoluble in Alcohols % 5 ±0.5 5 05 Moisture Contents % 25-27 7 06 Titre of Fatty Acid (°C) 40-44°C 16 GENERAL SPECIFICATION - S. No Characteristics Range % Ref to Clause no in PS: 406-1964 01 Total Fatty Matter % 59 ± 1 15 02 Free Caustic Alkali as Sodium Hydroxide % 1 - 3 6 03 Chloride as Sodium Chloride % 0.1-0.2 10 04 Matter Insoluble in Alcohols % 5 ±0.5 5 05 Moisture Contents % 25-27 7 06 Titre of Fatty Acid (°C) 40-44°C 16	
18	DNM90368	4L-9852	2940000743584 / AIR FILTER ELEMENT	CATERPILLER D/G (USA)	7 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
19	DNH88719	700-800DEGREE-F(370-430) DEGREE-C	4540795050066 / OVEN BURN OFF 220/240V 50 HZ SINGLE PHASE METAL PARTS HEATED	USER PN DOCK YARD ELECT SHOP	1 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
20	DNM901	ALCO	412079501382	AIR	2 /					.	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	10	CONTROL D-48	5 / DRIER CORE LG 140MM O/D 96MM X I/D 44MM (ALCO CONTROL D-48)	CONDITIONING PLANT	EACH/NUMBER						MAKE: COOLPOINT, LG 140MM O/D 96MM X I/D 44MM (ALCO CONTROL D-48)GENERAL SPECIFICATION - MAKE: COOLPOINT, LG 140MM O/D 96MM X I/D 44MM (ALCO CONTROL D-48)	
21	DPC91142	NO DATA AVAILABLE	0474500000062 / POWDER CHALK, COMP CALCIUM CARBONATE 98% PURITY		150 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DPC91700	NO DATA AVAILABLE	0474500000062 / POWDER CHALK, COMP CALCIUM CARBONATE 98% PURITY		30 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DPC87800	NO DATA AVAILABLE	0474500000062 / POWDER CHALK, COMP CALCIUM CARBONATE 98% PURITY		25 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
24	DPK90060	AN002-200	6850143407653 / REALAY&CONT CLEANER100% TIRCHLOROETHANE (KF SITOSEC FPS) 200ML Packing OEM = CRC Industires France		8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
25	DPC89535	S. No. 19 jotun anti-skid	8010785292318 / paint JOTUN ANTI-SKID (Dark)		30 / LITER	JOTUN ANTI SKID					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
26	DNQ91235	CEN1000063C	5510FT1019832 / Wooden Plug 250 x 70 x	Portable Firefighting and Damage	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR	CENAK GIDA TUR.INS.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			20 mm	Control Equipment System				TÜRK YE	MUH. MAK. SAN.LTD. STI.			
27	DNM89838	AN55-0102-01700	4310705240366 / PRESSURE GUAGE (0-250 PSI)))		1 / EACH/NUMBER	nk 200					TECHNICAL SPECIFICATION - Valve Dia: 2.1 cm Position of connection: Back Length of connection Rod: 3.3 cmGENERAL SPECIFICATION - Valve Dia: 2.1 cm Position of connection: Back Length of connection Rod: 3.3 cm	
28	DSB90154	6315/C3VL0241/SKF 6315/C3VL0241 INSOCOAT	3110735172264 / DEEP GROOVE BALL BEARING		2 / EACH/NUMBER	SKF 6315/C3VL0241 INSOCOAT/SKF 6315/C3VL0241 INSOCOAT					TECHNICAL SPECIFICATION - a. Model No: SKF 6315/C3VL0241 INSOCOAT b. Technical parameter/ Specification. DIMENSIONS: Bore diameter : 175mm Outside diameter: 160mm Width: 37mm Shoulder diameter Inner ring: 101.4mm Recess diameter outer: 141mm C, COUNTRY OF ORIGIN MADE IN AUSTRIA 1 Reference speed 9000 r/min 2 Limiting speed 5600 r/min 3 Mass Bearing 3.04kg 4 Cage Sheet metal 5 Bore type Cylindrical 6 Bearing material Bearing steel 7 Sealing Without 8 Coating Insulating coating on outer ring GENERAL SPECIFICATION - a. Model No: SKF 6315/C3VL0241 INSOCOAT b. Technical parameter/ Specification. DIMENSIONS: Bore diameter : 175mm Outside diameter: 160mm Width: 37mm Shoulder diameter Inner ring: 101.4mm Recess diameter outer: 141mm C, COUNTRY OF ORIGIN MADE IN AUSTRIA 1 Reference speed 9000 r/min 2 Limiting speed 5600 r/min 3 Mass Bearing 3.04kg 4 Cage Sheet metal 5 Bore type Cylindrical 6 Bearing material Bearing steel 7 Sealing Without 8 Coating Insulating coating on outer ring	
29	DPK88768	B150SH (91511707	9150725312306 /		30 / LITER	B150SH (9151170					TECHNICAL SPECIFICATION - this refregration oil is type of synthytic	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		)	REFERIGERATION OIL FOR SCREW COMPRESSOR			7)					lubricant use in refregrant system. GENERAL SPECIFICATION - this refregration oil is type of synthytic lubricant use in refregrant system.	
30	DNH70950	244885	5330785283923 / GLAND, PACKING MALE (THROAT 4/ PACK)		2 / PACKET	70:1				.	TECHNICAL SPECIFICATION - gland packing maleGENERAL SPECIFICATION - gland packing male	
31	DPK89401	PYRATEX EP2	9150145784933 / FIRE PROOF GREASE / GREASE, HEAT DISSIPATION COMPOUND		2 / KILOGRAMME	EP2				.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
32	DPC90288	ARCANOL MULTITOP / ARCANOL L135V	9150124044878 / ARCANOL MULTITOP/ ARCANOL L135V ROLLING BEARING GREASE		3 / KILOGRAMME	76 mm gun				.	TECHNICAL SPECIFICATION - Universal application, moderate to high load, low starting temperatures, wide temperature range, very wide speed range, improved relubricatability, in special cases also for spherical roller thrust bearingsGENERAL SPECIFICATION - Universal application, moderate to high load, low starting temperatures, wide temperature range, very wide speed range, improved relubricatability, in special cases also for spherical roller thrust bearings	
33	DNH70952	244862	5330785283914 / PACKING VEE, TUFFSTACK (PISTON)		3 / PACKET	70:1				.	TECHNICAL SPECIFICATION - CARBON FILLED PTFE. VEE PACKING USED TO PREVENT/STOP LEACKAGE OF LUBRICANTSGENERAL SPECIFICATION - CARBON FILLED PTFE. VEE PACKING USED TO PREVENT/STOP LEACKAGE OF LUBRICANTS	
34	DPK92690	TW25B	6850015624164 / Synthetic		2 / OUNCE	76mm Gun				.	TECHNICAL SPECIFICATION - TW25B IS A SYNTHETIC LIGHT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Grease (INHIBITOR, CORROSION, LUBRICATING OIL)								GREASE ENGIREERED FOR LONG LASTING LUBRICATION PROTECTION AND EXTREME PRESSURE, HEAVY-LOAD APPLICATIONS. GENERAL SPECIFICATION - TW25B IS A SYNTHETIC LIGHT GREASE ENGIREERED FOR LONG LASTING LUBRICATION PROTECTION AND EXTREME PRESSURE, HEAVY-LOAD APPLICATIONS.	
35	DPC92822	008154Z03885	9350775274168 / REFRACTORY MORTAR READY MIX		25 / KILOGRAMME	FIBERSTICK 1600				.	TECHNICAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 cGENERAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 c	
36	DNM90415	AR11178	3120001320259 / MAIN BEARING SHELL STD.	CUMMINS DG VTA28-G5 USA	1 / SET	VTA28-G5	25354882	CUMMINS ENGINE COMPANY, INC. BOX 3005 COLUMBUS, INDIANA, USA 47202	CUMMINS ENGINE COMPANY, INC. USA	.	TECHNICAL SPECIFICATION - MAIN BEARING SET STANDARD 650 KVAGENERAL SPECIFICATION - MAIN BEARING SET STANDARD 650 KVA	
37	DNM90425	190128	2805715199913 / CONNECTING ROD	CUMMINS DG VTA28-G5 USA	12 / EACH/NUMBER	VTA28-G5	25354882	CUMMINS ENGINE COMPANY, INC. BOX 3005 COLUMBUS, INDIANA, USA 47202	CUMMINS ENGINE COMPANY, INC. USA	.	TECHNICAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA CONNECTING RODGENERAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA CONNECTING ROD	
38	DPK92848	PP 47-32 / P-903SW220-5TTL	4310FM0450001 / POLYESTER OIL CARRIER COMPRESSOR (5 LTRS PACKING)	CHILL WATER UNIT	15 / LITER	CARRIER		CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA, UNITED SATE	CARRIER CORP 1419 N MARKEET ST, SACRAMENTO, CA,UNIT	.	TECHNICAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA,UNITED SATEGENERAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA,UNITED SATE	
39	DPK91760	GB495-65	9150705139823 / CALCIUM BASE GREASE GREY (KUNLUN)	BOATBEARING OF ELECTRIC WINCH	75 / KILOGRAMME	NO DATA AVAILABLE		UK	UK	.	TECHNICAL SPECIFICATION - . GENERAL SPECIFICATION - .	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			15KG									
40	DNM88171	112017	433070517262 8 / INTAKE FILTER CARTRIDGE MOBILE LPAC (ALPINE)	LPAC	4 / EACH/NUMBER	NK200	L2010/4	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	ALPINE PAKISTAN (LAHORE)	.	TECHNICAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102GENERAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102	
41	DPK8969 9	SAE 75W-90	915001363119 2 / LUBRICANT OIL MOBIL 1 SHC (TRANSMISSION OIL) (Packing 20 Liters Drum)	ENGINE	80 / LITER	NO DATA AVAILABLE		US	M/S MOBILE OIL CORPORATION & GOVERNMENT SALES DIVSION 3225 GALLOWS RD FAIR FAX VA USA 22037-4090 TEL: 703-846-4090 IDNS: 00129483 4	.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
42	DPC91536	HDWR-1142	793079517458 7 / DETERGENT	Hul/Fittings/WC	10 / LITER	HOVERCRAFT 8100 TD		Griffon Hoverworks, Merlin Quay, Hazel Road Woolston, Southampton-SO19 7GB, Tel +4402380423450, Fax +4402380841489	Griffon Hoverworks, Merlin Quay, Hazel Road Woolst	.	TECHNICAL SPECIFICATION - used for cleaning purpose onboard craft GENERAL SPECIFICATION - used for cleaning purpose onboard craft	
43	DPK9271 2	KAP GRES 3	915027018217 5 / Grease, Utility	0	7 / KILOGRAMME	0	0	ESKI BUYUKDERE CADDESI. MASLAK ISTANBUL	PETROL OFISI GENEL MUDURLUGU	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
44	DPK8975 1	N 320	9150FP001000 5 / GREASE LUBRICANT (200 LITERS PACKING)	F-22P SHIPS	200 / LITER	NO DATA AVAILABLE		CH	CSTC-CHINA	.	TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINAGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SINOPEC									
45	DPK92830	N 320	9150FP0010005 / GREASE LUBRICANT (200 LITERS PACKING) SINOPEC	F-22P SHIPS	200 / LITER	NO DATA AVAILABLE		CH	CSTC-CHINA	.	TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINAGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINA	
46	DPC91538	HDWR-0887	7930795174554 / ANTI-CORROSIVE SPRAY WAX	H/CRAFT	20 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK	GRIFFON HOVER WORK	.	TECHNICAL SPECIFICATION - GRIFFON HOVER WORK UKGENERAL SPECIFICATION - GRIFFON HOVER WORK UK	
47	DPK90356		9150795158189 / MOBIL DTE 10 EXCEL 32 (208 LITERS DRUM)	STEERING SYSTEM	416 / LITER	MOBIL	05363	M/S MAL PAKISTAN LTD (FORMERLY MOBIL ASKARI LUBRICANTS LTD) D-46 BLOCK-5 SCHEME NO 5 CLIFTON KARACHI. TEL:021-111-840-840 E,MAIL: WWW. MOBIL.COM.PK		.	TECHNICAL SPECIFICATION - ISO VG32GENERAL SPECIFICATION - ISO VG32	
48	DNF76120	YAP 179	6630735178763 / FLORIDE (250 TESTS PER PAK	PHOTOMETER COLORIMETER	1 / EACH/NUMBER	YPT 9500		YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel:+1.937.767.7241 Fax: +1.937.767.9353	USA	.	TECHNICAL SPECIFICATION - M/s PENICON technology for life, Office # 504, 4th floor Resham Bazar & Tower , Gulshan-e-Iqbal, Main Unversity road Karachi Tele: 021-35479578 YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel:+1. 937.767.7241 Fax:+1.937.767.9353 GENERAL SPECIFICATION - M/s PENICON technology for life, Office # 504, 4th floor Resham Bazar & Tower , Gulshan-e-Iqbal, Main Unversity road Karachi Tele: 021-35479578 YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel:+1. 937.767.7241 Fax:+1.937.767.9353	
49	DNF76117	YAP 163	6630735178766 / NITRATE (200 TESTS PER PAK	PHOTOMETER COLORIMETER	1 / EACH/NUMBER	YPT 9500		YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel:+1.937.767.7241 Fax: +1.937.767.9353	USA	.	TECHNICAL SPECIFICATION - M/s PENICON technology for life, Office # 504, 4th floor Resham Bazar & Tower , Gulshan-e-Iqbal, Main Unversity road Karachi Tele: 021-35479578 YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel:+1. 937.767.7241 Fax:+1.937.767.9353 GENERAL SPECIFICATION - M/s PENICON technology for life, Office #	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											504, 4th floor Resham Bazar & Tower , Gulshan-e-Iqbal, Main Unversity road Karachi Tele: 021-35479578 YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel:+1. 937.767.7241 Fax:+1.937.767.9353	
50	DPC90828	CC 2748M (5 liters packing) CC2750M (20 liters packing)	6810715229857 / ES Complete EG premix coolant	MAIN ENGINE	240 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS/ FLEETGUARD	.	TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
51	DPC90561	CC 2748M (5 liters packing) CC2750M (20 liters packing)	6810715229857 / ES Complete EG premix coolant	MAIN ENGINE	280 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS/ FLEETGUARD	.	TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
52	DPK89849	SH0358-95	9150785164814 / HYDRAULIC OIL (NO 10 AVIATION OIL YH 10) (10 LITER PACKING)	RCG 35mm GUN (CS/AA3)	50 / LITER			M/S POLY TECHNOLOGIES INC CHINA	M/S POLY TECHNOLOGIES INC CHINA	.	TECHNICAL SPECIFICATION - M/S POLY TECHNOLOGIES INC CHINAGENERAL SPECIFICATION - M/S POLY TECHNOLOGIES INC CHINA	
53	DNQ90299	08279009	6210795175762 / LIFE RAFT INTERNAL LIGHT & BATTERY	UK RFD	2 / EACH/NUMBER	UK (RFD BEAUFORT)	08279009	RFD BEAUFORT LTD (UK)	RFD BEAUFORT LTD (UK)	.	TECHNICAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)GENERAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)	
54	DPK89647	90790BS810 (Local) or YMD-73011-20-02 (EU)	3020765180127 / YAMA LUBE Gear Oil SAE 90 GL-5 (20 LTR Packing)	ENGINE	200 / LITER	SAE90		JAPAN	JAPAN	.	TECHNICAL SPECIFICATION - GEAR OIL SAE 90 GL-5 (20 LTR PACKING)GENERAL SPECIFICATION - GEAR OIL SAE 90 GL-5 (20 LTR PACKING)	
55	DPK92844	TEXAMATIC 1888 SAE DEXRON-	9150014878530 / STEERING LUB OIL (PETROL/DIES	MT VEHICLE	30 / BOTTLE			GENERAL MOTORS CORP 3044 W GRAND BLVD DETROIT MI UNITED STATES	GENERAL MOTORS CORP	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		III	EL ENGINE MT VEHICLES) (01 ltrs packing)					PSC: 48202-3091 TEL: 248-857-2576				
56	DNQ893 06		046159129683 6 / STRETCHER NEIL ROBERTSON		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DPC927 53	BS 3981	047350942925 0 / PIGMENT POWDER BURNT SIENA (Packing 56 LB or 400 Gram) TIGER BRAND	USE DRY INGREDIENTS FOR PAINTS	12 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 3981 BRAND= TIGERGENERAL SPECIFICATION - BS 3981 BRAND= TIGER	
58	DPK8953 1		047550220358 7 / OIL OM 33 (LTR NO. NSSD/POL/GE N/Q.P/417 DT. 30 NOV 96)		209 / BOTTLE						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DPC918 80	NO DATA AVAILABL E	047350000537 0 / SILICA GEL (grain size 2-3mm)	Transformers Humidity Control	30 / KILOGR AMME						TECHNICAL SPECIFICATION - Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.GENERAL SPECIFICATION - Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.	
60	DPC928 24	NO DATA AVAILABL E	047350000537 0 / SILICA GEL (grain size 2-3mm)	Transformers Humidity Control	150 / KILOGR AMME						TECHNICAL SPECIFICATION - Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.GENERAL SPECIFICATION - Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											and release moisture when heated up.	
61	DPC92942	NO. NS/C01/GEN/566 DT 210902	0442509429120 / PAINT OIL FINISHING G. O.S.B. (GREEN)	FINISHING	20 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
62	DPC90403	NO DATA AVAILABLE	0442504420030 / DULAC HI-BUILD (Packing = 0.91 Liter)		20 / LITER	ICI					TECHNICAL SPECIFICATION - LACQURE MAKE: ICI OEM ICIGENERAL SPECIFICATION - LACQURE MAKE: ICI OEM ICI	
63	DPC92915	NO DATA AVAILABLE	0442504420039 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	24 / LITER						TECHNICAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
64	DPC89220	DEF-1145/1956	0442504420079 / THINNER (SPEC) DEF STAN 80-38/2 1985 (PACKING 20 LTRS DRUM)		20 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-38/2 of 1985 GENERAL SPECIFICATION - DEFSTAN 80-38/2 of 1985	
65	DPC92902		0442504420083 / THINNER (DECO) (04 LTR Packing) Flash point 16 C	BUTYL KETONE32+-3% 4METHYL PENTAN-2-ONE.	36 / LITER						TECHNICAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%GENERAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%	
66	DPC90654		0443504430001 / CYLINDER ACETYLENE		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TECHNICAL (EMPTY)WITH VALVE&PROTECTIVE(F8)								AVAILABLE	
67	DPC92670	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,	
68	DPC88506	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		45 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque.GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,	
69	DPC91581	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,	
70	DPC90653	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,	
71	DPC92756	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
72	DNQ91237	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			STEEL BS 4360 LG 403 WD190 H6O 6.5MM DIA								Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
73	DNM69563	1284J00970	1325794600056 / DIAPHRAGM PART/NO-1284J00970		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DPC91851		0474502242463 / SOAP SCRUBBING		108 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose.	
75	DPC79585		0474502242463 / SOAP SCRUBBING		320 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose.	
76	DPK90281	OM-33, DEFSTAN 91-39/3 of 2001	0475999440596 / Lub Oil OM-33 NATO H-576 With Q.C Petroleum ANTIWEAR HYDRALIC FLUID (200-210 ltr packing)	HYDRAULIC Fluid in M TOOL lubricating in Rada equipment ETC	208 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DPK92845	NO DATA AVAILABLE	0474509100504 / GREASE PUMPABLE CALCIUM BASE XG-380 (3KG TIN)		100 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
78	DPK91766	XG-264	0474509100516 / GREASE XG-264 (as per table 5A of Defstan 01-5/17)		10 / KILOGRAMME						TECHNICAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17GENERAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17	
79	DPK92825		0474509100524 / GREASE NAVAL GRAPHITE XG-460 3 KG PACK	XG-460	60 / KILOGRAMME						TECHNICAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460) GENERAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460)	
80	DNQ89454	en-1568 and imo 1312/med	4210992248369 / afff 6% foam concentrate (packing in 20 lt can)	FOR FIRE FIGHTING EQUIPMENT	12 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
81	SNQ33045	54.107.00	4210995413550 / INLINE INDUCTOR, 2.5" BSPF COUPLING, 445MM LG,	FIRE AND REPAIR PARTY POST UPPER DECK FO	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			160.5 MM DIA								Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8GENERAL SPECIFICATION - Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8	
82	SNQ33212	54.107.00	4210995413550 / INLINE INDUCTOR, 2.5" BSPF COUPLING, 445MM LG, 160.5 MM DIA	FIRE AND REPAIR PARTY POST UPPER DECK FO	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8GENERAL SPECIFICATION - Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8	
83	SNQ32998	54.107.00	4210995413550 / INLINE INDUCTOR, 2.5" BSPF COUPLING, 445MM LG, 160.5 MM DIA	FIRE AND REPAIR PARTY POST UPPER DECK FO	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8GENERAL SPECIFICATION - Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Coupling 445MM LG,160.5 M/M Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8	
84	DNH92528	NO DATA AVAILABLE	411070504164 1 / DEEP FREEZER 4.5 CUFT 220V AC 50HZ	DEEP FREEZER 4.5 CUFT 220V 50HZ	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DNQ90839	00779	473099533296 1 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DNQ90840	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
87	DNQ90578	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
88	DNQ89657	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
89	DPK93227	MIL-G-21164	915000223400 4 / GREASE MOLYBDENUM D (G-353)	25mm KBA B06 Automatic cannon	11 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
90	DPC92755	NO DATA AVAILABLE	683070504133 8 / GAS ARGON N56 HIGH PURITY 99.9996%	FOR MISTRAL AIR DEFENCE SYSTEM	61.2 / CUBIC METER						TECHNICAL SPECIFICATION - 1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes.GENERAL SPECIFICATION - 1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes.	
91	DPK92781	XG-279, G-403	915099220241 8 / GREASE		21 / KILOGR						TECHNICAL SPECIFICATION - Composition: low viscosity mineral	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		(DEFSTAN 91-27 ISSUE 2 OF 2011	AUTOMOTIVE & ARTILLERY XG-279 (G-403) (Packing 3KG TIN)		AMME						OI8L and water insoluble calcium soap DEFSTAN 91-27 Issue of 2003 03 LTR TINGENERAL SPECIFICATION - Composition: low viscosity mineral OI8L and water insoluble calcium soap DEFSTAN 91-27 Issue of 2003 03 LTR TIN	
92	DPK92826	1N70015/ NUTO H 32	9150795102743 / OIL NUTO H 32 Elevators skirt shift (MOBIL NUTO tm H 32) 20 liter Drum)	HOVERCRAFT ,GRIFFON HOVERCRAFT LTD,UK	380 / LITER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
93	DPK89703	1N70015/ NUTO H 32	9150795102743 / OIL NUTO H 32 Elevators skirt shift (MOBIL NUTO tm H 32) 20 liter Drum)	HOVERCRAFT ,GRIFFON HOVERCRAFT LTD,UK	100 / LITER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DPK92341	148-162 E 02 / anschutz gyro service kit	6810725037246 / GYRO COMPASS SUPPORTING LIQUID 148-162 E 02 (OEM = ANSCHUTZ) / complete kit including liquid 148-162 E 02	GYRO COMPASS STANDARD 22 ANCHUTZ NASR	1 / KIT					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DPC88328	2200200 , SPEC TT-I-735 GRADE A, TTI375GRADEB	6810007534993 / ISOPROPYL ALCOHOL TECHNICAL CLEAR COLORLESS FLAMMABLE	PHALANX	3 / BOTTLE					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
96	DPK90222	NT5610-0001STCM 77KGCIMENTENSEAU	5610143435958 / CIMENT PROMPT (NO MORE PROCUREMENT TILL		40 / KILOGRAMME	NO DATA AVAILABLE				.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			EXHAUSTION OF STOCK)									
97	DPK92770	10250	5970143407636 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	13 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DPK92741	PARKERO-LUBE	9150013505196 / GREASE PARKER O-LUBE		3 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
99	DNM89941	AN55-0102-01700	4310705240366 / PRESSURE GUAGE (0-250 PSI)))		3 / EACH/NUMBER	nk 200					TECHNICAL SPECIFICATION - Valve Dia: 2.1 cm Position of connection: Back Length of connection Rod: 3.3 cmGENERAL SPECIFICATION - Valve Dia: 2.1 cm Position of connection: Back Length of connection Rod: 3.3 cm	
100	DPC93818	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	12 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
101	DPC93591	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	9 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
102	DPC93748	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	20 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
103	DPC93696	100	5340715160688 / CHIPS WHITE (SIZE	DECK COVERING FOR	17 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200	ORIGNAL COLOR CHIPS,A		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	CONCRETE SURFACE				GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	DIVISION			
104	DNM92193	3955393	2815715193135 / SEAL VALVE STEM	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD USA	48 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s IMPEX NINE INC		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
105	DPK93588	DOD-L-24651 TY I	9150012377467 / LUBRICATING OIL FOOD PROCESSING	MEAT SLICING MACHINE	20 / EACH/NUMBER			MILITARY SPECIFICATION USA	MILITARY SPECIFICATION USA	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - VISCOSITY 28.00 MINIMUM AND 76.00 MAXIMUM AT 40 DEG CELCIUS MILITARY SPECIFICATION USAGENERAL SPECIFICATION - VISCOSITY 28.00 MINIMUM AND 76.00 MAXIMUM AT 40 DEG CELCIUS MILITARY SPECIFICATION USA	
106	DPC93817	WD40	8030014189008 / WD40 (PACKING 440ML SPRAY BOTTLE)	0	49 / EACH/NUMBER	0	0	1061 CUDAHY PL, SAN DIEGO, CA SAN DIEGO CA	WD-40 COMPANY		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
107	DPK92342	gb/t491-87/121/2#	9150FP0020007 / LOW TEMPERATURE GREASE	F-22P SHIPS	3 / KILOGRAMME	NO DATA AVAILABLE		CH	CSTC-CHINA	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINAGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINA	
108	DPK92348	GREASE 7016	9150FP0020020 / GREASE LUBRICATING 7016		4 / TUBE	NO DATA AVAILABLE		CH	M/S CHINA		TECHNICAL SPECIFICATION - OEM & SOURCE OF AVAILABILTY : M/S NEWTRANS INTERNATIONAL CO LTD MNJ 3159, RM1007,10F,HO KING CENTER NO 2-16 FA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											YUENTSTREET MONGKOK KOWLOON HONG KONG FAX: 0086-25-84050148GENERAL SPECIFICATION - OEM & SOURCE OF AVAILABILTY : M/S NEWTRANS INTERNATIONAL CO LTD MNJ 3159, RM1007,10F,HO KING CENTER NO 2-16 FA YUENTSTREET MONGKOK KOWLOON HONG KONG FAX: 0086-25-84050148	
109	DPK93741	gjb940-1990/7254/7254	9150FP0020013 / AVAITION LUBRICANT GREASE	F-22P SHIPS	3 / KILOGRAMME	NO DATA AVAILABLE		CH	CSTC-CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINAGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINA	
110	DPK93747	N 320	9150FP0010005 / GREASE LUBRICANT (200 LITERS PACKING) SINOPEC	F-22P SHIPS	200 / LITER	NO DATA AVAILABLE		CH	CSTC-CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINAGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINA	
111	DPC93750	NIL	6810FP0990017 / ALCOHOL ETHER MIXTURE	F-22P SHIPS	8 / LITER	NO DATA AVAILABLE		CH	CSTC-CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINAGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINA	
112	DPK93585		9150795158189 / MOBIL DTE 10 EXCEL 32 (208 LITERS DRUM)	STEERING SYSTEM	624 / LITER	MOBIL	05363	M/S MAL PAKISTAN LTD (FORMERLY MOBIL ASKARI LUBRICANTS LTD) D-46 BLOCK-5 SCHEME NO 5 CLIFTON KARACHI. TEL:021-111-840-840 E,MAIL: WWW. MOBIL.COM.PK			TECHNICAL SPECIFICATION - ISO VG32GENERAL SPECIFICATION - ISO VG32	
113	DNM92195	048500	2930715150440 / IMPELLER KIT	WESTERBEKE GENERATOR 5.7 EDT 50HZ	1 / EACH/NUMBER			OEM: WESTERBEKE CORP 150 JOHN HANCOCK RD TAUNTON MA UNITED STATES 02780 508-823-7677 508-884-9688 DUNS 001767706	WESTERBEKE CORP.		TECHNICAL SPECIFICATION - WESTERBEKE 048500 IMPELLER KIT WITH A COVER O-RING, IMPELLER DRIVE SCREW AND A COUPLE OF SPARE COVER SCREWS, 50.8MM, DIAMETER AND 22MM WIDE. FITS A 12MM SLOTTED SHAFT.GENERAL SPECIFICATION - WESTERBEKE 048500 IMPELLER KIT WITH A	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								SALES@WESTERBEKE.COM HTTP://WWW.WESTERBEKE			COVER O-RING, IMPELLER DRIVE SCREW AND A COUPLE OF SPARE COVER SCREWS, 50.8MM, DIAMETER AND 22MM WIDE. FITS A 12MM SLOTTED SHAFT.	
114	DPK93695	SH0358-95	9150785164814 / HYDRAULIC OIL (NO 10 AVIATION OIL YH 10) (10 LITER PACKING)	RCG 35mm GUN (CS/AA3)	40 / LITER			M/S POLY TECHNOLOGIES INC CHINA	M/S POLY TECHNOLOGIES INC CHINA		TECHNICAL SPECIFICATION - M/S POLY TECHNOLOGIES INC CHINAGENERAL SPECIFICATION - M/S POLY TECHNOLOGIES INC CHINA	
115	DPK93586	3809442	9150145297370 / SYNTHETIC TRANSMISSION OIL SAE 75W-90 (5L PACKING)	VOLVO PENTA ENGINES	20 / LITER	SAE75W-90	VOLVO PENTA ENGINES	AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	VOLVO PENTA		TECHNICAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669 GENERAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	
116	DNM92152	3969562	3120015815885 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA	CUMMINS		TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARDGENERAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD	
117	DNH92924	SPLIT TYPE A/C 01 TON MITSUBISHI / LG/GREE	5962735142474 / SPLIT TYPE A/C 01 TON MITSUBISHI / LG/GREE 12000 BTU (INVERTIBLE/	SPLIT TYPE A/C 01 TON	1 / EACH/NUMBER	12PITH		00	.	t-3 SERIES REQUIRED .	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			REVERSIBLE)									
118	DPC93390	NA	6508705231785 / HAND SANITIZER	SELF	100 / LITER	NIL	NIL	PAKISTAN	PAKISTAN	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - HAND SANITIZERGENERAL SPECIFICATION - HAND SANITIZER	
119	DPK91763	CS 836D	0475509100536 / LUB OIL GEAR COMPOUNDED OC-600 FOR TRANSMISSION(PAKING-25 LTR)	LUB OIL TRANSMISSION,GENERAL GEARS IN VEHICAL & CHASSIS LUBRICATION.	25 / LITER						TECHNICAL SPECIFICATION - DEF STAN 91-65/1 OF 1986.SUPPLIER,S IS TO BE PROVIDE FOLLOWING AT THE TIME OF SHIPMENT.OEM CONFORMITY CERTIFICATE & VALID TEST REPORT WITH BATCH NO AND FILLING DATE& EXPIRY DATE.IMPORT DOCUMENTS VALID QUALIFICATION CERTIFICATE FROM QIENTIQ UK. GENERAL SPECIFICATION - DEF STAN 91-65/1 OF 1986.SUPPLIER,S IS TO BE PROVIDE FOLLOWING AT THE TIME OF SHIPMENT.OEM CONFORMITY CERTIFICATE & VALID TEST REPORT WITH BATCH NO AND FILLING DATE& EXPIRY DATE.IMPORT DOCUMENTS VALID QUALIFICATION CERTIFICATE FROM QIENTIQ UK.	
120	DPK91764	XG-250	0474509424829 / XG-250 (Silicon Compound DM-3) (18KG Packing)		72 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
121	DPK89701	XG-250	0474509424829 / XG-250 (Silicon Compound DM-3) (18KG Packing)		18 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
122	DPC93503		0442500420051 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	140 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED .	TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg GENERAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
123	DPC93391	NO DATA AVAILABLE	0442500010644 / THINNER FOR VARNISH (Packing 04 liter)		30 / LITER						TECHNICAL SPECIFICATION - DEF STAN 80-38/2 195 1. FLASH POINT: 16°C 2. INGREDIENTS PROPERTIES BY VOLUME: - METHY ISO BUTYL KETONE: 32 ± 3% - ETHYLENE GLYCOL ACETATE: 7 ± 3% - ISO BUYYLE ALCOHAOL : 25 ± 3% OEM M/S FALAH TRADING AGENCY GENERAL SPECIFICATION - DEF STAN 80-38/2 195 1. FLASH POINT: 16°C 2. INGREDIENTS PROPERTIES BY VOLUME: - METHY ISO BUTYL KETONE: 32 ± 3% - ETHYLENE GLYCOL ACETATE: 7 ± 3% - ISO BUYYLE ALCOHAOL : 25 ± 3% OEM M/S FALAH TRADING AGENCY	
124	DPC93502		0442500420064 / PAINT WEATHER WORK (LIGHT GREY)NHQ LTR NS/G/1303/CDT 270199	WEATHER WORK	260 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
125	DPC93395		0442509423538 / PAINT MARKING BRUSH STENCILLING (BLACK) type: alky6ed, Flash Point: 32 Degreee C (Min) moethod of application brushing, Packing: 04 ltr tin gauge of drum 26 to 28 swg	N B C D MARKING ETC.	20 / LITER						TECHNICAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed GENERAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed	
126	DPC93882	NO DATA AVAILABLE	0442504420039 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	164 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
127	DPC93704	NO DATA AVAILABLE	0442504420039 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	48 / LITER						TECHNICAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
128	DPC93887		0442504420042 / PAINT FINISHING (MIDDLE BRUNSWICK GREEN), BRUSHING		300 / LITER						TECHNICAL SPECIFICATION - 1. DEFSTAN 80-54/4 OF 2019 2. stage inspection prescribed 3. flash point 32 c (MIN) 4. NS/P/008 OF APR 1976(revised) except for packing 5. COLOUR GREEN no 226 of BS-381-c 1996 Packing: 04 ltr tin Gauge of tin	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Flash point 32 C (min) (04LTR TIN)								26 to 28 swgGENERAL SPECIFICATION - 1. DEFSTAN 80-54/4 OF 2019 2. stage inspection prescribed 3. flash point 32 c (MIN) 4. NS/P/008 OF APR 1976(revised) except for packing 5. COLOUR GREEN no 226 of BS-381-c 1996 Packing: 04 ltr tin Gauge of tin 26 to 28 swg	
129	DPC93751		0442504420083 / THINNER (DECO) (04 LTR Packing) Flash point 16 C	BUTYL KETONE32+-3% 4METHYL PENTAN-2-ONE.	100 / LITER						TECHNICAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%GENERAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%	
130	DPC93594		0442504420083 / THINNER (DECO) (04 LTR Packing) Flash point 16 C	BUTYL KETONE32+-3% 4METHYL PENTAN-2-ONE.	92 / LITER						TECHNICAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%GENERAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%	
131	DPC93705		0442504420083 / THINNER (DECO) (04 LTR Packing) Flash point 16 C	BUTYL KETONE32+-3% 4METHYL PENTAN-2-ONE.	204 / LITER						TECHNICAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%GENERAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%	
132	DPC93884		044250442008 3 / THINNER (DECO) (04 LTR Packing) Flash point 16 C	BUTYL KETONE32+-3% 4METHYL PENTAN-2-ONE.	124 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%GENERAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%	
133	DPC93703	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		324 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABELGENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
134	DPC93458		044250942354 3 / PAINT MARKING (WHITE)		100 / LITER						TECHNICAL SPECIFICATION - a. Colour White b. Viscosity 100-200 cps (centipoise) c. Density 1.2-1.5 g/cm3 d. Fast Drying 15-30 minutes e. Thickness 50-100 microns (dry film) f. Adhesion Excellent on Metal, Wood, concrete g. Durability Resistant to weathering, UV and Chemicals h. Reflectivity High(85-90%)GENERAL SPECIFICATION - a. Colour White b. Viscosity 100-200 cps (centipoise) c. Density 1.2-1.5 g/cm3 d. Fast Drying 15-30 minutes e. Thickness 50-100 microns (dry film) f. Adhesion Excellent on Metal, Wood, concrete g. Durability Resistant to weathering, UV and Chemicals h. Reflectivity High(85-90%)	
135	DPC93460	NO DATA AVAILABL	041459924181 9 / SILICATE		30 / KILOGR					OEM/AUTHORIZED/DE	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	LIQUIED CEMENT		AMME					ALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	SPECIFICATION - NO DATA AVAILABLE	
136	DNQ91238	0254-254050	0254784203153 / CLAMP HOSE SZ 5.500 TO 6.250 BS 5315 71/226		35 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
137	DPC91535	NO DATA AVAILABLE	0473504730033 / DISTILLED WATER (10 ltr packing)		10 / GALLON					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
138	DNQ91116	00779	4730995332961 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	5 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
139	DNQ91564	00779	4730995332961 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	5 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
140	DPK92584	DOD-G-24508A	9150001491593 / GREASE BALL AND ROLLER BEARING (AEROSHELL GREASE 22) (XG-293)		16 / POUND						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
141	DPC934	BELZONA	803070504091	FOR	6 /						TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	66	9341	6 / BELZONA RE-INFORCEMENT TAPE (BELZONA 9341) (Packing 10 Meters roll)	BRIDGING CRACKS & FOR BELZONA METALS	ROLL						DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
142	DPC93399	BS 3591 of 1985	6810992201733 / METHYLATED SPIRIT INDUSTRIAL GEN/PURPOSE (Packing = 20 LTR), highly flammable	FOR GENERAL USE	20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
143	DPC93459	TS396A	6850992203062 / CLEANING & LUBRICATING COMPOUND ELEC CONTACT	MACHINERY CONTROL CONSOLE	2 / BOTTLE						TECHNICAL SPECIFICATION - DEFSTAN68-7/1 BR 320 D 0473/133 TABLE GENERAL SPECIFICATION - DEFSTAN68-7/1 BR 320 D 0473/133 TABLE	
144	SPC93686	S-10	6810705080419 / NEUTRALIZER -S-10	A/C PLANT CHILLER CONDENSER HEAT EXCHANG	450 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DPK93702	10250	5970143407636 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	8 / KILOGRAMME	NO DATA AVAILABLE				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
146	SPC93757	GB7820-1987	6850FP0990004 / DESICCANT		20 / KILOGRAMME	NO DATA AVAILABLE				OEM/AUTHORIZED/DEALER COC WITH TECHNICA	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										L DATA FOR ACCEPTANCE OF END USER IS REQUIRED		
147	DPK88638	GB7324-1994 LB3	9150FP0020010 / LITHIUM BASE GREASE NO.3		8 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
148	DPK93740	LG280	9150FP0020014 / GREASE LG280		3 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
149	DPK93742	SH0358-95	9150FP0010307 / MECHANICAL LUBRICATION # 10 (10 LITRE PACKING)		30 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
150	DSB74376	FORELECTRICAL HACK SAW MACHINE	3455TY6719726 / FLEXIBLE HACK SAW BLADE		22 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Material : Carbon Steel b. Teeth size : 6 x teeth per c. Width of blade : 1 Inch d. Thickness of blade : 1.5 mm e. Roll length : 250 ft f. Packing requirement: Wooden or plastic box and teeth suitably protected by coverGENERAL SPECIFICATION - a. Material : Carbon Steel b. Teeth size : 6 x teeth per c. Width of blade : 1 Inch d. Thickness of blade : 1.5 mm e. Roll length : 250 ft f. Packing requirement: Wooden or plastic box and teeth suitably protected by cover	
151	DPK92451	815	6810142855639 / EPON RESINE 815C WITH HARDNER		300 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
152	DRG88625		1730ZO6549721 / TRESTLE AFT		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. HEIGHT: 9.5FT 2. WIDTH: 4FT 3. LENGTH: 8FT 4. Aluminium Section: 40x40 5. Aluminium Checker Plate: 4mm Thick (Stairs) 6. Aluminium	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Checker Plate 4mm Thick Platform (900x900) 7. Section Fitting (Customize) 8. MS PIPE 30X30X2MM FOR STAIRS (900MM LENGTH) 8. MS Railing Pipe 50mm round 2mm thick 9. Side Rigger (Screw and Floding Type) 10. Wheel 8inch (2revolving 2 fix) alongwith brake Hardware 11. Paint Powder Coating (Only MS Material Yellow color) GENERAL SPECIFICATION - 1. HEIGHT: 9.5FT 2. WIDTH: 4FT 3. LENGTH: 8FT 4. Aluminium Section: 40x40 5. Aluminium Checker Plate: 4mm Thick (Stairs) 6. Aluminium Checker Plate 4mm Thick Platform (900x900) 7. Section Fitting (Customize) 8. MS PIPE 30X30X2MM FOR STAIRS (900MM LENGTH) 8. MS Railing Pipe 50mm round 2mm thick 9. Side Rigger (Screw and Floding Type) 10. Wheel 8inch (2revolving 2 fix) alongwith brake Hardware 11. Paint Powder Coating (Only MS Material Yellow color)	
153	DPC926 92	ALTEMP Q NB 50	915012196162 4 / GREASE, GENERAL PURPOSE (CAN = 750 GRAM)		14 / CAN	Antenna Base					TECHNICAL SPECIFICATION - ALTEMP Q NB 50 IS A WHITE/ BEIGE LUBRICATING PASTE CONTAINING A MINERAL BASE OIL, A BARIUM COMPLEX SOAP AND INORGANIC SOLID LUBRICANTS. BESIDES ITS APPLICATION AS A UNIVERSAL ASSEMBLY PASTE, THIS PRODUCT OFFERS BENEFITS ESPECIALLY IN FRICTION POINTS WITH SMALL TO MINIMUM MOTION UNDER HIGH STATIC AND DYNAMIC LOADS.GENERAL SPECIFICATION - ALTEMP Q NB 50 IS A WHITE/ BEIGE LUBRICATING PASTE CONTAINING A MINERAL BASE OIL, A BARIUM COMPLEX SOAP	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AND INORGANIC SOLID LUBRICANTS. BESIDES ITS APPLICATION AS A UNIVERSAL ASSEMBLY PASTE, THIS PRODUCT OFFERS BENEFITS ESPECIALLY IN FRICTION POINTS WITH SMALL TO MINIMUM MOTION UNDER HIGH STATIC AND DYNAMIC LOADS.	
154	DPK88792	B150SH (91511707)	9150725312306 / REFERIGERATION OIL FOR SCREW COMPRESSOR		30 / LITER	B150SH (91511707)					TECHNICAL SPECIFICATION - this refregration oil is type of synthytic lubricant use in refregrant system. GENERAL SPECIFICATION - this refregration oil is type of synthytic lubricant use in refregrant system.	
155	DPK88018	B150SH (91511707)	9150725312306 / REFERIGERATION OIL FOR SCREW COMPRESSOR		60 / LITER	B150SH (91511707)					TECHNICAL SPECIFICATION - this refregration oil is type of synthytic lubricant use in refregrant system. GENERAL SPECIFICATION - this refregration oil is type of synthytic lubricant use in refregrant system.	
156	DPC91145	RELAY+on	8010705332823 / VIRKON SURFACE DISINFECTANT POWDER		40 / LITER	ZEEPER-114					TECHNICAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal GENERAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal	
157	DSB93805	ORB-ETM/0-120/V1/F332	6685545327042 / Expansion Thermometer guage (0-120°C) with temp prob		1 / EACH/NUMBER	ORB-ETM/0-120/V1/F332					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
158	SRP93202	SURISO 3GS	9150ZO6511641 / OIL COMPRESSOR		40 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - FOR LUBRICATION OF COMPRESSORS TYPE &BRAND TO BE QUOTED.OIL IS AVAILABLE AT AIRCONDITIONS MARKET. GENERAL SPECIFICATION - FOR LUBRICATION OF COMPRESSORS TYPE &BRAND TO BE QUOTED. OIL IS AVAILABLE AT AIRCONDITIONS MARKET.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
159	DSB93758	ORB-BTPG/0-100/V1/F333	6685545327040 / Pressure Gauge (0-100 Bar)		1 / EACH/NUMBER	ORB-BTPG/0-100/V1/F333					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
160	DPC93398	008154Z03885	9350775274168 / REFRACTORY MORTAR READY MIX		25 / KILOGRAMME	FIBERSTICK 1600					TECHNICAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 cGENERAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 c	
161	DSB73724	tet02033	3439785301718 / ELECTRODE (plasama consumable)		100 / EACH/NUMBER	PLASMA CUTTER P80 ELECTRODE				Recommended source: OEM Black Wolf (Changzhou Golden Globe Welding & Cutting Equipment Co. Ltd) No 7 Renmin East Road, Changzhou Jiangsu, China	TECHNICAL SPECIFICATION - P 80 ELECTRODE LENGHT 26MM P 80 ELECTRODE WidTH 18MM HOLE 1.5MM OUTER SIDE diameter PLASMA CUTTER P80 ELECTRODE CUTTING PLATE THICKNESS 10-18 MM PLATEGENERAL SPECIFICATION - P 80 ELECTRODE LENGHT 26MM P 80 ELECTRODE WidTH 18MM HOLE 1.5MM OUTER SIDE diameter PLASMA CUTTER P80 ELECTRODE CUTTING PLATE THICKNESS 10-18 MM PLATE	
162	DSM93294	LOCAL	4010TY6740722 / GUARD RAIL		200 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - DIAMETER: 10MM MATERIAL:steel wire rope SS (PVC COATED) non magnatic TESTING: 200 KG ACCEPTANCE CRITERIA: LOAD TESTINGGENERAL SPECIFICATION - DIAMETER: 10MM MATERIAL:steel wire rope SS (PVC COATED) non magnatic TESTING: 200 KG ACCEPTANCE CRITERIA: LOAD TESTING	
163	DSM93364	LOCAL	4010TY6740722 / GUARD RAIL		200 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - DIAMETER: 10MM MATERIAL:steel wire rope SS (PVC COATED) non magnatic TESTING: 200 KG ACCEPTANCE CRITERIA: LOAD TESTINGGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - DIAMETER: 10MM MATERIAL:steel wire rope SS (PVC COATED) non magnatic TESTING: 200 KG ACCEPTANCE CRITERIA: LOAD TESTING	
164	DSM93966	LOCAL	4010TY6740722 / GUARD RAIL		200 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - DIAMETER: 10MM MATERIAL:steel wire rope SS (PVC COATED) non magnatic TESTING: 200 KG ACCEPTANCE CRITERIA: LOAD TESTINGGENERAL SPECIFICATION - DIAMETER: 10MM MATERIAL:steel wire rope SS (PVC COATED) non magnatic TESTING: 200 KG ACCEPTANCE CRITERIA: LOAD TESTING	
165	DPK92705	NOSOL GBY2	9150123226527 / GREASE NOSOL GBY2		6 / KILOGRAMME	NO DATA AVAILABLE				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
166	DNQ92993	IACD42106 or CITEX H-1140	4240995275985 / SAFETY HARNESS (100% POLYSTER WITH BUCKLES & D-RING	PPE	5 / EACH/NUMBER	NO DATA AVAILABLE				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - MATERIAL: 100% POLYSTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH:>=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Email: Info@abdullahfireprotection.com.pk b. Last Procurement data through registered supplier M/S ASHI Enterprises in Sep 18. Spefication may be endorsed to avoid complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max impact force of 6 KN. GENERAL SPECIFICATION - MATERIAL: 100% POLYSTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH:>=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: Info@abdullahfireprotection.com.pk b. Last Procurement data through registered supplier M/S ASHI Enterprises in Sep 18. Spefication may be endorsed to avoid complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max impact force of 6 KN.	
167	DPC94068	ZEEPER114	8010705332849 / ZEEPER 114 CLEANER		1000 / KILOGRAMME	ZEEPER. 114					TECHNICAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years GENERAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
168	DPC93969	ZEEPER114	8010705332849 / ZEEPER 114 CLEANER		1000 / KILOGRAMME	ZEEPER. 114					TECHNICAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years GENERAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
169	DPC94320	ZEEPER114	8010705332849 / ZEEPER 114 CLEANER		1000 / KILOGRAMME	ZEEPER. 114				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years GENERAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
170	DPC92700	INDUSTRIAL SEALANT 800	8030000802171 / INDUSTRIAL SEALANT (SEALING COMPOUND) (Each Tube contains 147.9 ml)		1 / EACH/NUMBER	EC800				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - 3M Scotch-Seal Industrial Sealant 800 is a reddish brown, brushable sealant that air dries to a flexible seal that resists water, oils and fuel and adheres to many metallic surfaces. useful temperature range: -65° to 200°F (-54 to 93°C).GENERAL SPECIFICATION - 3M Scotch-Seal Industrial Sealant 800 is a reddish brown, brushable sealant that air	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											dries to a flexible seal that resists water, oils and fuel and adheres to many metallic surfaces. useful temperature range: -65° to 200°F (-54 to 93°C).	
171	DPC92730	Q3-1566	8040015990596 / ADHESIVE (SEALANT SILICON) (310 ML CARTRIDGE) DOWSIL BRAND		1 / CARTRIDGE	NA				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
172	DPK93980	B150SH (91511707)	9150725312306 / REFERIGERATION OIL FOR SCREW COMPRESSOR		35 / LITER	B150SH (91511707)				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - this refregration oil is type of synthytic lubricant use in refregrant system. GENERAL SPECIFICATION - this refregration oil is type of synthytic lubricant use in refregrant system.	
173	DNM93057	7351079	4730735245367 / 1/2"x1150 SAE 100 R9 hose		2 / EACH/NUMBER	CLASSIC V				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
174	DNM93056	7350730	4730735245321 / 3/4"x2150 SAE 100 R15 hose		2 / EACH/NUMBER	CLASSIC V				OEM/AUTHORIZED/DEALER COC WITH TECHNICA	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										L DATA FOR ACCEPTANCE OF END USER IS REQUIRED		
175	DPC94321	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		1000 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans $ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. GENERAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans $ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
176	DPC94067	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		1000 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans $ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Daily mopping purpose concentrated Zeeper Pinax which Cleans $ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
177	DPC93970	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		1000 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans $ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. GENERAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans $ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
178	DPC92702	TECTYL 300G BLACK E MATT	9150775311764 / Premium waterborne matt black corrosion preventive coating		5 / LITER	TE079/01				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTAN	TECHNICAL SPECIFICATION - tectyl 300g black e matt premium waterborne matt black corrosion preventive coating. The cured film is hard and flexible and has a matt black appearance. TECTYL 300G Black E Matt provides an effective barrier against corrosive	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										CE OF END USER IS REQUIRED .	environments for ferrous and non-ferrous fabrications and industrial components.GENERAL SPECIFICATION - tectyl 300g black e matt premium waterborne matt black corrosion preventive coating. The cured film is hard and flexible and has a matt black appearance. TECTYL 300G Black E Matt provides an effective barrier against corrosive environments for ferrous and non-ferrous fabrications and industrial components.	
179	DPC92701	DOWCAL 100	6850992161665 / HEAT TRANSTER FLUID		30 / LITER	3d radar				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED .	TECHNICAL SPECIFICATION - DOWCAL™ 100 IS AN ETHYLENE GLYCOL-BASED HEAT TRANSFER FLUID FOR USE IN A WIDE RANGE OF INDUSTRIAL, CONSTRUCTION AND INFRASTRUCTURE APPLICATIONS. IT IS HIGHLY RECOMMENDED FOR HEATING APPLICATIONS. recommended operating temperature of this fluid ranges from -50°C TO 175°C. GENERAL SPECIFICATION - DOWCAL™ 100 IS AN ETHYLENE GLYCOL-BASED HEAT TRANSFER FLUID FOR USE IN A WIDE RANGE OF INDUSTRIAL, CONSTRUCTION AND INFRASTRUCTURE APPLICATIONS. IT IS HIGHLY RECOMMENDED FOR HEATING APPLICATIONS. recommended operating temperature of this fluid ranges from -50°C TO 175°C.	
180	DSA93759	VRLHP101595VTX / SM163-02DETNG	4730142243898 / VIROLE-A-BRASER-NG		310 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Material = Copper Inner Dia = 10mm Outer Dia = 15 mm Height = 09 mm GENERAL SPECIFICATION - Material = Copper Inner Dia = 10mm Outer Dia = 15 mm Height = 09 mm	
181	DPC93962	008154Z03885	9350775274168 / REFRACTORY MORTAR		50 / KILOGRAMME	FIBERSTICK 1600				OEM/AUTHORIZED/DEALER COC WITH	TECHNICAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			READY MIX							TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	cGENERAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 c	
182	DPC94230	008154Z03885	935077527416 8 / REFRACTORY MORTAR READY MIX		25 / KILOGRAMME	FIBERSTICK 1600				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 cGENERAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 c	
183	DPK93968	MOBIL RARUS SHC 1025	915070519700 1 / SYNTHETIC OIL MOBIL RARUS SHC 1025 (20 LITER PACKING)	AIR COMPRESSOR	80 / LITER	NA	NA	M/S MOBIL	M/S MOBIL	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - MOBIL RARUS SHC 1025GENERAL SPECIFICATION - MOBIL RARUS SHC 1025	
184	DNM93943	SA9-27019PF	626001195975 3 / LIGHT CHEMICAL 6INCH ORANG/CYALUME CHEMLIGH ORANGE		50 / EACH/NUMBER			CYALUME TECHNOLOGIES SA 295 R MAYOR DE MONTRICHER AIX EN PROVENCE FRANCE AIX EN PROVENCE CEDEX 3 13591 04 42 37 17 80 04 42 37 17 99 XFARCY@CYALUME.COM MWWW.CYALUME.COM	CYALUME TECHNOLOGIES SA 295 R MAYOR DE MONTRICHER	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - Make/ Model / Brand Equivalent : Cyalume TechnologiesGENERAL SPECIFICATION - Make/ Model / Brand Equivalent : Cyalume Technologies	
185	DNQ93261	SPL-1	623099991050 4 / FLOOD	FLOOD LIGHT LIGHT	2 / EACH/N			UNIT 4-6, HIGHFIELD BUSINESS PARK	UK	OEM/AUTHORIZED/DE	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: UNIT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LIGHT ELECTRICAL (NITECH UK)	ELECTRICAL	UMBER			ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK		ALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED .	4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM TN38 9UB 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK GENERAL SPECIFICATION - SOURCE OF AVAILABILITY; UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM TN38 9UB 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK	
186	DNQ92994	SPL-1	6230999910504 / FLOOD LIGHT ELECTRICAL (NITECH UK)	FLOOD LIGHT LIGHT ELECTRICAL	4 / EACH/NUMBER			UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK	UK	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED .	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY; UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM TN38 9UB 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK GENERAL SPECIFICATION - SOURCE OF AVAILABILITY; UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM TN38 9UB 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK	
187	DPC93963	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	15 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
188	DPC94069	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	14 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION	.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
189	DPC94231	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	14 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
190	DNH93121	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENCER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENCER PAKISTAN	ORIENT	model pwd-315 required	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENCER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENCER	
191	DNH93712	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENCER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENCER PAKISTAN	ORIENT	model pwd-315 required.	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENCER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENCER	
192	DNH93940	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENCER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENCER PAKISTAN	ORIENT	model pwd-315 required	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENCER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENCER	
193	DPC92980	CUMMINS VALVOLINE DIESEL ENGINE SPECIAL COOLANT (G)	6850SV5231612 / COOLANT CUMMINS VALVOLINE DIESEL ENGINE SPECIAL	MAIN AND EMERGENCY GENSET	20 / LITER	CCUMMINS VALVOLINE DIESEL ENGINE SPECIAL COOLANT(G	KH180429 BV01, BV02, BV03, BV04	VALVOLINE INC,USA AND SHANGHAI VC LUBRICATING OIL CO, LTD CHINA	DREW MARINE CO LTD	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - COOLANT CWT-PDS-AP-MAXIGARD-R1GENERAL SPECIFICATION - COOLANT CWT-PDS-AP-MAXIGARD-R1	
194	DPC93973	H-300 HUX	8040735140710 / HARDNER (SET OF 2X1KG	AC COMPRESSOR KALMAT GWADER	10 / SET	NO DATA AVAILABLE		00	.	OEM/AUTHORIZED/DEALER COC WITH	TECHNICAL SPECIFICATION - A.V 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown , Flash point, 200f>GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BOTTLE)							TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	SPECIFICATION - A.V 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown , Flash point, 200f>	
195	DNM93448	390-1557	2815715224203 / PUMP AS FUEL TRANSFER	DGCAT7.1USA	2 / UNIT	CAT7.1	NA	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPILLAR USA	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGsGENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs	
196	DPK92906	SAE 90 (80W90)	9150251145135 / ENGINE GEAR OIL SAE 90 (80W90) (03 Ltr to 18 Ltr PACKING)	YAMAHA OUTBOARD ENGINE	6 / LITER	NO DATA AVAILABLE		US	SOCIETY OF AUTOMOTIVE ENGINEERS INC, COMMANWEALTH DRIVE, WARRENDALE, USA., PSC: 15096, TEL#724-776-4841	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - SAE 90 (80W90)GENERAL SPECIFICATION - SAE 90 (80W90)	
197	DNQ93359	8930	9390999808079 / TAPE LUMINOUS / LUMINOUS SHEETING ROLL 150MM WIDE 45M LONG FLAME RETARDANT	SMOKE CURTAIN(FF)	11 / EACH/NUMBER	NO DATA AVAILABLE		UK	UK ENGLAND	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										REQUIRED		
198	DNM93001	HBC 139/HBC 52	5130735227950 / BRUSH CUTTER	Bush Cutter	2 / EACH/NUMBER	HBC 139/HBC 52	NIL	Hyundai Power products, Korea	Hyundai		TECHNICAL SPECIFICATION - BBC 139/HBC 52 Engine Cylinder Displacement 31cm3 Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of carburettor Diaphragm typeGENERAL SPECIFICATION - BBC 139/HBC 52 Engine Cylinder Displacement 31cm3 Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of carburettor Diaphragm type	
199	DPK93982	SUNISO SL32	9150123680726 / LUBRICATING OIL FOR REFRIGERANT COMPRESSOR (SUNISO SL32) (04 LTR Packing)	BITZER COMPRESSOR	12 / LITER			SUN OIL COMPANY BELGIUM NV INGBERTHOEVEWEG, 4 AARTSELAAR BELGIUM TEL:3234581230 FAX:3234581478 INFO@SUNOCO.BE HTTP://WWW.SUNOCO.BE	SUN OIL	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - PATT VIDE:RASDGAR LETTER RDR/300/191 DT 16-5-11GENERAL SPECIFICATION - PATT VIDE: RASDGAR LETTER RDR/300/191 DT 16-5-11	
200	DNM94042	3584427	4820270382248 / PRESSURE RETAINING V (FUEL SYSTEM)	(FUEL SYSTEM)	2 / EACH/NUMBER	D6-370D-E		AB VALVO PENTA SE 405 08 GOTHENBURG SWEDEN	VALVO PENTA SWEDEN	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - PRESSURE RETAINING V (FUEL SYSTEM)GENERAL SPECIFICATION - PRESSURE RETAINING V (FUEL SYSTEM)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
201	DPK93979	3809442	9150145297370 / SYNTHETIC TRANSMISSION OIL SAE 75W-90 (5L PACKING)	VOLVO PENTA ENGINES	10 / LITER	SAE75W-90	VOLVO PENTA ENGINES	AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	VOLVO PENTA	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669 GENERAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	
202	DPK92846	CASTROL TRANSMAX ATF DEX-MERCMULTIVEHICLE	9150705197314 / CASTROL transmax atf dex-mercmultivehicle	RHIB BOAT INBOARD DIESEL ENGINE	10 / LITER	-	-	CASTROL	CASTROL	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - CASTROL ATF MULTIVEHICLEGENERAL SPECIFICATION - CASTROL ATF MULTIVEHICLE	
203	DPK93978	N28355-1	9150123772290 / OIL SYNTHETIC/LUBRICATING OIL HYDRAULIC (VDL100) OEM = BAUER	HPAC	40 / LITER	NO DATA AVAILABLE		GR	SMITHS DETECTION-WATFORD LIMITED 459 PARK AVENUE BUSHEY, WATFORD HERTFORDSHIRE UNITED KINGDOM WD23 2BW 01923 658185 01923 221361C	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - SMITHS DETECTION-WATFORD LIMITED 459 PARK AVENUE BUSHEY, WATFORDHERTFORDSHIRE UNITED KINGDOM WD23 2BW 01923 658185 01923 221361COMMENTS@GRASEBYDYNAMICS.COM WWW.SMITHSDETECTION.COMGENERAL SPECIFICATION - SMITHS DETECTION-WATFORD LIMITED 459 PARK AVENUE BUSHEY, WATFORDHERTFORDSHIRE UNITED KINGDOM WD23 2BW 01923 658185 01923 221361COMMENTS@GRASEBYDYNAMICS.COM WWW.SMITHSDETECTION.COM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									OMMENTS@GRASEBYDYNAMICS.COM WWW.SMITHSDETECTION.COM			
204	DNH93707	-	4940735132133 / WASHING MACHINE WITH AUTOMATIC CAPACITY DRY WEIGHT UPTO 21/25 KG	WASHING MACHINE	1 / EACH/NUMBER	th2721ds2b1		OC	M/S ELECTROLUX WASCATOR SWEDEN		TECHNICAL SPECIFICATION - make : lg thailandGENERAL SPECIFICATION - make : lg thailand	
205	DPC92968		0473502202307 / PAINT REMOVER ORGANIC SOLVENT TYPE WATER RINSABLE (04 LTR TIN)		300 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - 1. DEFSTAN80-14/1 OF 1970. type brushingGENERAL SPECIFICATION - 1. DEFSTAN80-14/1 OF 1970. type brushing	
206	DPC92513	DEFSTAN 68-30/1 OF 1974	0474502204834 / CHLORINATED LIME, TECHNICAL 30% MIN available CHLORINE (25 KG Packing)		900 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - DEFSTAN 68-30/1 OF 1974 OEM COC DATE OF MANUFACTURING & EXPIRY OEM TEST CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE GENERAL SPECIFICATION - DEFSTAN 68-30/1 OF 1974 OEM COC DATE OF MANUFACTURING & EXPIRY OEM TEST CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE	
207	DPC93971	NO DATA AVAILABL	0473500005370 / SILICA GEL	Transformers Humidity	50 / KILOGR					OEM/AUTHORIZED/DE	TECHNICAL SPECIFICATION - Silica Gel (Desiccaant) in grain form	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	(grain size 2-3mm)	Control	AMME					ALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.GENERAL SPECIFICATION - Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.	
208	DPC92914	SAME AS S NO 9 EXECPT SHADE.	0442502201637 / PAINT FINISHING (GREEN)	USES FOR STEEL ALUMINUM OR WOOD ON GLASS	8 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
209	DPC93881		0442504420051 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	60 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg GENERAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
210	DPC94206		0442509434483 / PAINT FINISHING	FINISHING	424 / LITER					OEM/AUTHORIZED/DEALER COC	TECHNICAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg							WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	STAGE INSPECTION PRESCRIBED COLoUR SHADE NO 537 TO BS: 381-C Of 1996GENERAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLoUR SHADE NO 537 TO BS: 381-C Of 1996	
211	DPC94326		0442504420075 / THINNER		12 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
212	DPC94200	NO DATA AVAILABLE	0442504420039 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	336 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
213	DPC94178		0442504420083 / THINNER (DECO) (04 LTR Packing) Flash point 16 C	BUTYL KETONE32+-3% 4METHYL PENTAN-2-ONE.	450 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END	TECHNICAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%GENERAL SPECIFICATION - defstan 80-38/2 of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										USER IS REQUIRED .	2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%	
214	DPC92911	SPEC,DEF 1052 COLOURS TO BS 381C	0442509107035 / PAINT FNSHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/566DT210902		20 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED .	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
215	DPC94217	SPEC,DEF 1052 COLOURS TO BS 381C	0442509107035 / PAINT FNSHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/566DT210902		400 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED .	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
216	DNQ93468	A4	0273599104486 / axe fireman head	FIRE FIGHTING PURPOSE	2 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED .	TECHNICAL SPECIFICATION - length of head: 8 1/4" cutting edge: 2 3/4" length of handle:12 1/2" 8.250" in/out edge 2 -3/4" length of handle 12-1/2 " and handle insulated specs 3054 drawing picture illustration br 320 d of 1967 t-1 catalouge of naval store attahed acctg status: c unit of issue: oGENERAL SPECIFICATION - length of head: 8 1/4" cutting edge: 2 3/4" length of handle:12 1/2" 8.250" in/out edge 2 -3/4" length of handle 12-1/2 " and handle insulated specs 3054 drawing picture illustration br 320 d of 1967 t-1 catalouge of naval store attahed acctg status: c unit of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											issue: o	
217	DNQ92989	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H6O 6.5MM DIA		4 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
218	DNH93446	NO DATA AVAILABLE	1308500530116 / AIR CONDITIONER 1.5 TON WINDOW TYPE		1 / EACH/NUMBER					t3 series required.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
219	DNH93543	MODEL NO SS-30P (STEEL)	1308500530129 / COOLER W/DRINKING20-25 LTR. 1/2TON AMPS 2.5 220V SING PHASE		1 / EACH/NUMBER					cannon brand required.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
220	DNM93725	3930942/FS1280	2815715109966 / FUEL/WATER SEPERATOR FILTER	PROPULSION CUMMINS ENGINE FORSPDB-II 173HP.	2 / EACH/NUMBER	6CT8 3-P				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - ENGINE S NO.45225188. RATED HPAT2200 RPMM 173HP. GENERAL SPECIFICATION - ENGINE S NO.45225188. RATED HPAT2200 RPMM 173HP.	
221	DNM93681	QP407PAA	4310765021898 / COMPRESSOR 2 TON BTU 24000 ROTARY 220V	A/C 02 TON WINDOW TYPE	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			50 HZT									
222	DNH93549	9178 chrome	4110PK5067366 / REFRIGERATOR 14CUFT	REFRIGEERATOR 14CUFT (PAKISTAN)	1 / EACH/NUMBER	9178 CHROME					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
223	DNH93048	NO DATA AVAILABLE	3431705048748 / WELDING RECTIFIER, W/CART, WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT	USER WELDING SHOP DOCKYARD	1 / SET					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - WELDING RECTIFIER W/CART I/P 380/440V 3P 50/60HZ O/P600A WITH500A30/50M STICK WELDING ACESSARIES KITGENERAL SPECIFICATION - WELDING RECTIFIER W/CART I/P 380/440V 3P 50/60HZ O/P600A WITH500A30/50M STICK WELDING ACESSARIES KIT	
224	DNH93266	NO DATA AVAILABLE	3431705048748 / WELDING RECTIFIER, W/CART, WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT	USER WELDING SHOP DOCKYARD	1 / SET					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - WELDING RECTIFIER W/CART I/P 380/440V 3P 50/60HZ O/P600A WITH500A30/50M STICK WELDING ACESSARIES KITGENERAL SPECIFICATION - WELDING RECTIFIER W/CART I/P 380/440V 3P 50/60HZ O/P600A WITH500A30/50M STICK WELDING ACESSARIES KIT	
225	DNH93552	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1 / EACH/NUMBER	GREE/PEL, MITSBUSHI/ DAKEN/ GENERAL, GENERAL, LG,				t-3 series required.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
226	DNH93443	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/	SELF	1 / EACH/NUMBER	GREE/PEL, MITSBUS				t-3 series required.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MITSBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY			HI/ DAKEN/ GENERAL, GENERAL, LG,						
227	DNH93719	NO DATA AVAILABLE	413070504652 9 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1 / EACH/NUMBER	GREE/PEL, MITSBUSHI/ DAKEN/ GENERAL, GENERAL, LG,				t-3 series required.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
228	DNM93003	qxs-h80sn345 (t1)	413076509189 6 / COMPRESSOR 380-400V, 3PHASE,50HZ ,04TONS	DAIKIN AIR CONDITION 04TONS JAPAN	1 / EACH/NUMBER	QXS-H80SN345 (T1)					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
229	DNH93806	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
230	DNH93605	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
231	DNH93986		411073506082 8 / REFRIGERATOR 18-CUFT DOUBLE		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DOOR PEL/DAWLANCE									
232	DNH93167		4110735060828 / REFRIGERATOR 18-CUFT DOUBLE DOOR PEL/DAWLANCE		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
233	DNQ92991	00779	4730995332961 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	3 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
234	DNQ93548	00779	4730995332961 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	4 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
235	DNQ92996	515 / TIR8828	6605735099701 / 515 TEMPERATURE GUN,-50-1000 CENTIGRADE	MOTOR CURRENT ANALYSIS EQUIPMENT	4 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
236	DNH93551	NO DATA AVAILABLE	4110500530126 / DEEP FREEZER 12/13 CUFT 220V 50HZ	DEEPFREEZER 12CUFT (PEL) OR WAVES PAK	1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
237	DPC94329	NO DATA AVAILABLE	6830705059992 / GAS MIXTURE HYDROGEN 2% 98% NITROGEN (PACKING 6.8 CM)	GALIBERATION OF GAS METERS SUBMARINES	6 / CUBIC METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
238	DPK94016	OMALA S2 GX150	9150170328851 / LUBRICATING OIL GEAR , SHELL OMALA S2 GX150	NIL	418 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - Typical Physical Characteristics Kinematic Viscosity @ 40C mm2/s ISO 3104 150 Kinematic Viscosity @100C mm2/s ISO 3104 14.8 Viscosity index ISO 2909 98 Flash point COC 0C ISO 2592 >240 Pour point 0C ISO 3016 -24 Density @ 15C Kg/m3 ISO 12185 897 @ 40C CST:150 Packing: 209 ltr drum original seeled packing non returnableGENERAL SPECIFICATION - Typical Physical Characteristics Kinematic Viscosity @ 40C mm2/s ISO 3104 150 Kinematic Viscosity @100C mm2/s ISO 3104 14.8 Viscosity index ISO 2909 98 Flash point COC 0C ISO 2592 >240 Pour point 0C ISO 3016 -24 Density @ 15C Kg/m3 ISO 12185 897 @ 40C CST:150 Packing: 209 ltr drum original seeled packing non returnable	
239	DPK93977	OMALA S2 GX150	9150170328851 / LUBRICATING OIL GEAR , SHELL OMALA S2 GX150	NIL	209 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTAN	TECHNICAL SPECIFICATION - Typical Physical Characteristics Kinematic Viscosity @ 40C mm2/s ISO 3104 150 Kinematic Viscosity @100C mm2/s ISO 3104 14.8 Viscosity index ISO 2909 98 Flash point COC 0C ISO 2592 >240 Pour	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										CE OF END USER IS REQUIRED .	point 0C ISO 3016 -24 Density @ 15C Kg/m3 ISO 12185 897 @ 40C CST:150 Packing: 209 ltr drum original seeled packing non returnableGENERAL SPECIFICATION - Typical Physical Characteristics Kinematic Viscosity @ 40C mm2/s ISO 3104 150 Kinematic Viscosity @100C mm2/s ISO 3104 14.8 Viscosity index ISO 2909 98 Flash point COC 0C ISO 2592 >240 Pour point 0C ISO 3016 -24 Density @ 15C Kg/m3 ISO 12185 897 @ 40C CST:150 Packing: 209 ltr drum original seeled packing non returnable	
240	DPK93981	XG-460	9150999100524 / GREASE LUBRICATING XG-460 (Packing = 03 KG Tin)	MAINTENANCE, OILS, GREASES AND APPLICATO	60 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED .	TECHNICAL SPECIFICATION - Technical Data (Typical Values) Appearance = Fibrous Grease Colour = Black NLGI Classification = 00 Unworked Penetration(IP50) = 400-430 Worked Penetration (IP50) = 400-430 Base oil Viscosity (IP71) @ 400C cSt = 600 @ 1000C cSt = 34 Four Ball (IP 239) Weld Load kgs = 315 Timken Ok Load IBS = 45 Operating Temperature Range = -25 to + 1000C GENERAL SPECIFICATION - Technical Data (Typical Values) Appearance = Fibrous Grease Colour = Black NLGI Classification = 00 Unworked Penetration(IP50) = 400-430 Worked Penetration (IP50) = 400-430 Base oil Viscosity (IP71) @ 400C cSt = 600 @ 1000C cSt = 34 Four Ball (IP 239) Weld Load kgs = 315 Timken Ok Load IBS = 45 Operating Temperature Range = -25 to + 1000C	
241	DNM92369	MURPHY LTD PDS 100-007	6685715048527 / OIL PRESSURE GAUGE 0-TO-100 PSI& 0-7	CUMMINS DIESEL ENGINE 34.5 KVA (USA/UK)	5 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICA	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BAR MURPHY SWITCH GAUGE							L DATA FOR ACCEPTANCE OF END USER IS REQUIRED.		
242	DPC93961	205-6611 (05 Ltr) / 205-6612 (20 Ltr)	6810705084532 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (05 Liter Can)	CP AIR COMP	300 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTRGENERAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTR	
243	DNM93807		6685US5080847 / GAS CHARGING SETLOW SIDE O TO 250PSI HIGH SIDE O TO 500PSI		2 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
244	DNM93262	HD 6/15 m	7910725118904 / KARCHER COLD WATER HIGH PRESSURE CLEANER WITH		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 220-440V/ 60HzGENERAL SPECIFICATION - 220-440V/ 60Hz	
245	DNM93058	3805782	6620735126507 / VALVE PLATE ASSY	COMPRESSOR D6SHI-350X AWM/D	3 / EACH/NUMBER	D6SHI-350X AWM/D BELGIUM				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTAN	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										CE OF END USER IS REQUIRED		
246	DPK92518	F60	801014279973 1 / PEINTURE FIN ALK VERT FONL F60		80 / KILOGRAMME	NO DATA AVAILABLE				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA FOR ACCEPTANCE OF END USER IS REQUIRED	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	