PAKISTAN NAVY

TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 09-12-2025

TERMS & CONDITION

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT".

2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.

3. LAB TESTING CHARGES IF ANY WILL BE BORN BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	SGE78727	NIL	4230705181268 / BAG PAPER FOR CONTAMINATED CLOTHING	NIL	400 / EACH/NUMBER		NIL	PLASTIC MARKET	NIL	.	TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) Dimensions: Height: = 40 cm Width: = 32 cm Depth: = 11 cm Paper specifications: (1) Paper sack: Multi-layered, 3-ply (2) GSM: 100 – 150 (3) Paper bag should be printed with phrase "Contaminated Material". (4) Each bag should have double padding at its bottom. PACKING: STANDARDGENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) Dimensions: Height: = 40 cm Width: = 32 cm Depth: = 11 cm Paper specifications: (1) Paper sack: Multi-layered, 3-ply (2) GSM: 100 – 150 (3) Paper bag should be printed with phrase "Contaminated Material". (4) Each bag should have double padding at its bottom. PACKING: STANDARD	
2	DPK83992	CORENA S2 P150	9150705196699 / SHELL CORENA S2 P150 (PACKING = 20 LITERS)	HPAC PNFT	209 / LITER	NA	NA	M/S SHELL	M/S SHELL	.	TECHNICAL SPECIFICATION - SHELL CORENA S2 P150GENERAL SPECIFICATION - SHELL CORENA S2 P150	
3	DPC930	008154Z03	935077527416		50 /	FIBERSTI					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	87	885	8 / REFRACTORY MORTAR READY MIX		KILOGRAMME	CK 1600					FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 cGENERAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 c	
4	DPK91923	HA5440	9150735164285 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	30 / GALLON	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	TELEFLEX MARINE CANADA		TECHNICAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW.seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858GENERAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	
5	DPK92344	HA5440	9150735164285 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	100 / GALLON	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	TELEFLEX MARINE CANADA		TECHNICAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW.seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858GENERAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	
6	DPC92280	P-D-1747	7930009265280 / DETERGENT GENERAL PURPOSE (CLEAN ALL PURPOSE CLEANSER) OEM = SKILLCRAFT (BOTTLE)	GENERAL PURPOSE CLEANER	50 / BOX			3530 W DALLAS ST HOUSTON 77019 USA	LIGHTHOUSE OF HOUSTON		TECHNICAL SPECIFICATION - BIODEGRADABE GENERAL PURPOSE CLEANER NONMEDICATED, SUITABLE FOR USE ON GREASE, DIRT, SOAP SCUM, FOOD STAINS AND FINGERPRINTSGENERAL SPECIFICATION - BIODEGRADABE GENERAL PURPOSE CLEANER NONMEDICATED, SUITABLE FOR USE ON GREASE, DIRT, SOAP SCUM, FOOD STAINS AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FINGERPRINTS	
7	DNM83713	3804713	3120715161336 / SET, MAIN BEARING	ENGINE CRANK SHAFT	1 / EACH/NUMBER	QST 30 G2	37178798	CUMMINS INC. 500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 812-377-3920 812-377-1715 DUNS 006415160 STEVE.A. HEWITT@CUMMINS.COM	CUMMINS INC.	.	TECHNICAL SPECIFICATION - CUMMINS INC. 500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 812-377-3920 812-377-1715 DUNS 006415160 STEVE.A. HEWITT@CUMMINS.COM GENERAL SPECIFICATION - CUMMINS INC. 500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 812-377-3920 812-377-1715 DUNS 006415160 STEVE.A. HEWITT@CUMMINS.COM	
8	DPC92441	NIL	6810FP0990017 / ALCOHOL ETHER MIXTURE	F-22P SHIPS	1.5 / LITER	NO DATA AVAILABLE		CH	CSTC-CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINAGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINA	
9	DPC87583	CLK724	8010992355263 / PAINT INTERLAC 665 STORM GREY	Switchboard PNFT	50 / LITER	INTERLAC 665 INTERNATIONAL PAINT UK		AKZO NOBEL International Paint (Suzhou) Co.Ltd. No.129 Hongxi Road New District Suzhou, Jiangsu, 215151 China Telephone No. 86(512) 66167888 Fax No. 86(512)66163911	AKZO NOBEL International Paint (Suzhou) Co.Ltd.	.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
10	DPK91919	VALVOLINE PREMIUM BLUE 7800 15W40	9150715229858 / 15W40 VALVOLINE PREMIUM BLUE 7800	MAIN ENGINE	140 / LITER	QSB6.7 CM2250 MARINE	22376716	valvoline distributors	VALVOLINE		TECHNICAL SPECIFICATION - 15W40 VALVOLINE PREMIUM BLUE 7800 ENGINE OIL. FOR PERIODIC MAINTAINENCE ROUTINES GENERAL SPECIFICATION - 15W40 VALVOLINE PREMIUM BLUE 7800 ENGINE OIL. FOR PERIODIC MAINTAINENCE ROUTINES	
11	DPK91924	92-8m0133951/92-8M0133949	9150715229211 / POWER STEERING FLUID SAE0W-30 FULL SYNTHETIC	300 HP OBM	50 / QUART	1300V24LD	2B550466	MERCURY MARINE W6250 PIONEER ROAD FOND DU LAC, WI 54936-1939 TEL NO 920-929-5000	USA		TECHNICAL SPECIFICATION - POWER STEERING FLUID SAE0W-30 FULL SYNTHETIC HYDRAULIC FLUID USED IN MERCRUY OBMs 300,. IPC OF THE SAME AND SPECIFICATION ENCLSOED. GENERAL SPECIFICATION - POWER STEERING FLUID SAE0W-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											30 FULL SYNTHETIC HYDRAULIC FLUID USED IN MERCRUY OBMs 300,. IPC OF THE SAME AND SPECIFICATION ENCLSOED.	
12	DPC87583	CLK724	8010992355263 / PAINT INTERLAC 665 STORM GREY	Switchboard PNFT	50 / LITER	INTERLAC 665 INTERNATIONAL PAINT UK		"International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD, UK. Ph:0191 4696111	International Paint Pvt Ltd, uk	.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
13	DPK92325	OMALA 68	9150270001857 / SHELL OMALA OIL 68 (PACKING 209 LTR DRUM)	MTP 750DD HUB OIL	209 / LITER	NO DATA AVAILABLE		OC	TURKEY		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
14	DPK91913	15W40 (API CF-4/SG) /870234	9150SV1210006 / LUBE OIL CUMMINS VALVOLINE PREMIUM BLUE 7800 15W40	MAINE AND EMERGENCY GENSET	200 / LITER	CUMMINS VALVOLINE VI TOPFLITE	KH180429(BVO1, BVO2, BVO3, BVO4)	SHANGHAI VCLUBRICATING OIL CO, LTD.CHINA	CHEVRON MARINE		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
15	DPC92057	NO DATA AVAILABLE	0473502247695 / REFINED SODIUM BICARBONATE (OEM = ICI PAKISTAN) Packing = 25kg Bag		50 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
16	DPC71953		0474502201711 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	846 / KILOGRAMME					.	TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSEGENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
17	DPK91908		0475509100550 / OIL OM 150 SPEC. DTD417B		40 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
18	DPC92164		0473995314641 / AMEROYAL	EVAPORATORS	25 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
19	DPK90223	XG-250	0474509424829 / XG-250 (Silicon Compound DM-3) (18KG Packing)		54 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
20	DPC92112	MAINLY SPECIFIED AS A PRE-WELD	0442502201209 / PAINT ALUMINEUM DUCO (NSSD/C01/0442/GEN/173DT060393)		60 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
21	DPC92998	NO DATA AVAILABLE	0442504420039 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	60 / LITER						TECHNICAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
22	DPC93000		0442504420083 / THINNER (DECO) (04 LTR Packing) Flash point 16 C	BUTYL KETONE32+-3% 4METHYL PENTAN-2-ONE.	16 / LITER						TECHNICAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%GENERAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingridient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_ 3% c. ethylene 7+_3% d. iso butyl alcohal: 26+_3%	
23	DPC93045	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		200 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABELGENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
24	DPC92981	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		313 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABELGENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
25	DPC92880	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
26	DPC92820	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CU strip corrosion @ 100 oF. UNIT: -, psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
27	DNM76100	ITSHFD4-SEW / 692170658	3040725094058 / INTERMEDIATE DRIVE SHAFT	DOCK BILGE PP.ZVZ 400/300 FD-IV OEM:	1 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 2987 mm Material = C35K (High Carbon Steel) Shaft size = 2987 mm Outer Dia = 100 mm Model: ZVZ 400/300 TECHNICAL DATA , Drawing No. D004 MARTERIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar GENERAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 2987 mm Material = C35K (High Carbon Steel) Shaft size = 2987 mm Outer Dia = 100 mm Model: ZVZ 400/300 TECHNICAL DATA , Drawing No. D004 MARTERIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar	
28	DNQ82563	en-1568 and imo 1312/med	4210992248369 / afff 6% foam concentrate (packing in 20 lt can)	FOR FIRE FIGHTING EQUIPMENT	10 / CAN					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DNQ91676	00779	4730995332961 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	3 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
30	DPC93041	NO DATA AVAILABLE	0474500000062 / POWDER CHALK, COMP CALCIUM CARBONATE		100 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			98% PURITY									
31	DPC68134	R-5002	8010705111037 / PIGMENT (BRILIANT WHITE)	GRP WORK, M/S ZAIN SONS. KARCHI.PH; 7731541	5 / KILOGRAMME					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
32	DPC68133	R-5021	8010705111038 / PIGMENT (PANTHER BLACK)	GRP WORK, M/S ZAIN SONS KARCHI, PH7731541	5 / KILOGRAMME					.	TECHNICAL SPECIFICATION - 05 Kg packingGENERAL SPECIFICATION - 05 Kg packing	
33	DPC92166	NO DATA AVAILABLE	8030785033979 / MOLYKOTE G-Rapid Plus TYPE 605 Paste (PACKING 01 KG CAN)	MAIN ENGINE 8RLB 66 FOR PNS NASR	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - Test Property Unit Result Color - Black Consistency, Density Unworked penetration Mm/10 255-275 Density @ 20 C g/ml 1.40 Temperature - - - Service Temperature C F -35 - +450 -31 - +842 Load Carrying Capacity Four ball Tester - - Weld Load N 5300 Almen Wieland machine OK load N >20000 Coefficient of friction μ thread μ head - 0.10 0.06 Resistance Water resistance, static, evaluation - 1-90GENERAL SPECIFICATION - Test Property Unit Result Color - Black Consistency, Density Unworked penetration Mm/10 255-275 Density @ 20 C g/ml 1.40 Temperature - - - Service Temperature C F -35 - +450 -31 - +842 Load Carrying Capacity Four ball Tester - - Weld Load N 5300 Almen Wieland machine OK load N >20000 Coefficient of friction μ thread μ head - 0.10 0.06 Resistance Water resistance, static, evaluation - 1-90	
34	DPC92982	BS 3591 of 1985	6810992201733 / METHYLATED SPIRIT INDUSTRIAL GEN/PURPOSE (Packing = 20 LTR), highly flammable	FOR GENERAL USE	20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
35	DPK91916	MIL-L-2105/80W90 or J2360-3-80W90W	9150010355393 / LUBRICATING OIL GEAR (01 CAN = 20 LITERS) brand (Shell or Mobil)	IT SELF	20 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
36	DPK92326	MIL-L 63460	9150010546453 / CLEANER LUBRICANT & PRESERVATIVE	VALCUAN PHALANX	16 / PINT						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DPK92186	TELLUS S2 M-32	9150701003319 / Lub Oil TELLUS S2 MX 32 HIGH PREMIUM HYDRAULIC OIL	HYDRAULIC SYSTEM	150 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DPC92967	205-6611 (05 Ltr) / 205-6612 (20 Ltr)	6810705084532 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (05 Liter Can)	CP AIR COMP	220 / LITER						TECHNICAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTRGENERAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTR	
39	DPC93044	205-6611 (05 Ltr) / 205-6612 (20 Ltr)	6810705084532 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (05 Liter Can)	CP AIR COMP	400 / LITER						TECHNICAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTRGENERAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTR	
40	SPK74562	ALBA ABP-8	6850TY6720908 / ETCHING		50 / KILOGR	NO DATA AVAILAB					TECHNICAL SPECIFICATION - (PACKING 30 KG PLASTIC CAN)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SOLUTION (PCBA ABP-8) 6850TY6/20908		AMME	LE					GENERAL SPECIFICATION - (PACKING 30 KG PLASTIC CAN)	
41	DPK90429	10250	5970143407636 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	20 / KILOGRAMME	NO DATA AVAILABLE				.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DPK91677	PATEARO DERGRAIN240	5350143407964 / LAPPING AND GRINDING COMPOUND		2 / KILOGRAMME	NO DATA AVAILABLE				.	TECHNICAL SPECIFICATION - ABRASIVE MATERIAL; SILICON CARBIDE. SCREEN GRIT SIZE DESIGNATOR: P240. ABRASIVE LUBRICANT TYPE: OIL WT: 05 KG. UNIT PAKAGE TYPE; BOXGENERAL SPECIFICATION - ABRASIVE MATERIAL; SILICON CARBIDE. SCREEN GRIT SIZE DESIGNATOR: P240. ABRASIVE LUBRICANT TYPE: OIL WT: 05 KG. UNIT PAKAGE TYPE; BOX	
43	DPK92909	GB7324-1994 LB3	9150FP0020010 / LITHIUM BASE GREASE NO.3		15 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DPK92346	SH0358-95	9150FP0010307 / MECHANICAL LUBRICATION # 10 (10 LITRE PACKING)		40 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DPC68132	BS 627 (F-8) (R 5123)	8010705128764 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOU	10 / KILOGRAMME					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DNH86700		1308546011081 / REFRIGERATOR 10.CU FT-220V AC (NO FROST)		1 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DPC92010	INDUSTRIAL SEALANT	8030000802171 / INDUSTRIAL		50 / EACH/NUMBER	EC800					TECHNICAL SPECIFICATION - 3M Scotch-Seal Industrial Sealant 800 is a reddish brown, brushable sealant	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		800	SEALANT (SEALING COMPOUND) (Each Tube contains 147.9 ml)								that air dries to a flexible seal that resists water, oils and fuel and adheres to many metallic surfaces. useful temperature range: -65° to 200°F (-54 to 93°C).GENERAL SPECIFICATION - 3M Scotch-Seal Industrial Sealant 800 is a reddish brown, brushable sealant that air dries to a flexible seal that resists water, oils and fuel and adheres to many metallic surfaces. useful temperature range: -65° to 200°F (-54 to 93°C).	
48	DPK92324	ROBUST man 3277 10W40	9150725316314 / MAN GENUINE OIL (10W-40 MAN 3277 PACKING 20L FOR DIESEL ENGINE)		100 / LITER	10w-40 m3277					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
49	DPC49051	BLK01	6810705279759 / ADVANCE COAT Polyethylene COATING POWDER BLACK SHADE		40 / KILOGRAMME	POLYETHYLENE					TECHNICAL SPECIFICATION - Polyethylene CoatiNG PowDER) GENERAL SPECIFICATION - Polyethylene CoatiNG PowDER)	
50	DPK93088	bvc32	9150725344812 / synthetic ether pve refrigeration OIL bitzer bvc32		10 / LITER	BVC32					TECHNICAL SPECIFICATION - SYNTHETIC POLYVINYL ETHER PVE REFRIGERATION OIL BVC32 1 litter packing viscosity @ 40c 32cst VISCOSITY @ 100c 5.7 cst VISCOSITY index 120 pour point -42 c mosture content less then 50ppm campatibility hfc refrigerant r-410a,r-32,r407c,r134a application scroll compressors oem bitzer original oil bvc32 flash point 250c density @20c 1.03g/cm3 GENERAL SPECIFICATION - SYNTHETIC POLYVINYL ETHER PVE REFRIGERATION OIL BVC32 1 litter	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											packing viscosity @ 40c 32cst VISCOSITY @ 100c 5.7 cst VISCOSITY index 120 pour point -42 c mosture content less then 50ppm campatibility hfc refrigerant r-410a,r-32,r407c,r134a application scroll compressors oem bitzer original oil bvc32 flash point 250c density @20c 1.03g/cm3	
51	DPK6142 4	LOCTITE4 95-50G	804099224850 3 / LOCTITE 495		23 / EACH/N UMBER	NO DATA AVAILAB LE				.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
52	DNM753 93	289-2349	294071524012 1 / FILTER ELEMENT-AIR (SECONDARY)		1 / EACH/N UMBER	C7.1				.	TECHNICAL SPECIFICATION - MAKE: CATTERPILLAR GENERAL SPECIFICATION - MAKE: CATTERPILLAR	
53	DNM904 22	AR11330	432000132023 7 / PUMP, LUBE OIL	CUMMINS DG VTA28-G5 USA	1 / EACH/N UMBER	VTA28-G5	25354882	CUMMINS ENGINE COMPANY, INC. BOX 3005 COLUMBUS, INDIANA, USA 47202	CUMMIN S ENGINE COMPAN Y, INC. USA	.	TECHNICAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA OIL PUMPGENERAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA OIL PUMP	
54	SGE828 53	N/A	933070518127 9 / PLASTIC SHEET	GENERAL ITEM	10 / ROLL			LOCAL MARKET	GENERA L ITEM	.	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
55	SRP9284 9	TEXAMATI C 1888	9150ZO653196 7 / FLUID AUTOMATIC TRANSMISSIO N (PACK 01LI)		85 / LITER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - CALTEX TEXAMATIC 1888, MAKE: CALTEX, CHEVRON, COLOUR: RED, POUR POINT, OC: -51, VISCOSITY BROOK FIELD, MPA.S @ 40 OC: 15000, VISCOSITY KINEMATIC, MM2/S@ 40OC: 35.8, MM2/S @ 10OC: 7.2, VISCOSITY INDEX: 168, FLASH: >190 (CLEVELAND OPEN-CUP). GENERAL SPECIFICATION - CALTEX TEXAMATIC 1888, MAKE: CALTEX, CHEVRON, COLOUR: RED, POUR POINT, OC: -51, VISCOSITY BROOK FIELD, MPA.S	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											@ 40 OC: 15000, VISCOSITY KINEMATIC, MM2/S@ 40OC: 35.8, MM2/S @ 10OC: 7.2, VISCOSITY INDEX: 168, FLASH: >190 (CLEVELAND OPEN-CUP).	
56	DNF7407 2	YAP 179	663073517876 3 / FLORIDE (250 TESTS PER PAK	PHOTOMETER COLORIMETE R	1 / EACH/N UMBER	YPT 9500		YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel:+1.937.767.7241 Fax: +1.937.767.9353	USA	.	TECHNICAL SPECIFICATION - M/s PENICON technology for life, Office # 504, 4th floor Resham Bazar & Tower , Gulshan-e-Iqbal, Main Unversity road Karachi Tele: 021-35479578 YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel:+1. 937.767.7241 Fax:+1.937.767.9353 GENERAL SPECIFICATION - M/s PENICON technology for life, Office # 504, 4th floor Resham Bazar & Tower , Gulshan-e-Iqbal, Main Unversity road Karachi Tele: 021-35479578 YSI 1725 Brannum Lane, Yellow Springs, OH 45387 Tel:+1. 937.767.7241 Fax:+1.937.767.9353	
57	SGE828 56	Ic-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	600 / EACH/N UMBER	SSP-01-LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTA N	.	TECHNICAL SPECIFICATION - AS PER LETTER ATTACHGENERAL SPECIFICATION - AS PER LETTER ATTACH	
58	SGE829 65	P1000C	535070516064 5 / WATER PROOF PAPER 166 SIZE 1000MM	WTER PROOF PAPER	120 / SHEET			LOCAL SOURCE:PRIME BUSINESS SYNDICATE SHOP#2.GROUND FLOOR ABID CHAMBER SHAH0E-LIAQUAT KARACHI (TEL: 32213969,32624690)FAX: 32623828	PRIME BUSINES S SYNDICA TE	.	TECHNICAL SPECIFICATION - LOCAL SOURCE:PRIME BUSINESS SYNDICATE SHOP#2.GROUND FLOOR ABID CHAMBER SHAH0E-LIAQUAT KARACHI (TEL: 32213969,32624690)FAX: 32623828GENERAL SPECIFICATION - LOCAL SOURCE:PRIME BUSINESS SYNDICATE SHOP#2.GROUND FLOOR ABID CHAMBER SHAH0E-LIAQUAT KARACHI (TEL: 32213969,32624690)FAX:32623828	
59	SGH701 25	MUREX 1281201 (L1281201/ 1EL)	028159923368 4 / REGULATOR oxygen with	SPECIF REDUCE GAS WELDING TYPE GH191,	15 / EACH/N UMBER	murex SAFFIRE SERIES 1 +				.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			guage of range 0-16 bar and 0-400 bar	194								
60	SGB73430		0283595711448 / ROD NAVAL BRASS RD DIA 1-1/8,	SERVICE PUMP	10 / METER					.	TECHNICAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft:3.70 lb authority: br320d BS EN/2163 OF1998 GRADE CW719R (M)GENERAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft:3.70 lb authority: br320d BS EN/2163 OF1998 GRADE CW719R (M)	
61	SGB70111		0214580001004 / NUT (Dia 10mm) WITH BOLT STEEL (Dia 10.00MM) 480TD	S/M	500 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - HEXAGON BOLT DIMENSION: OUT SIDE DIA: 10 MM PITCH THREAD: 1.5 MM LENGTH: 40 MM LENGTH WITHOUT HEAD: 35 MM HEAD WIDTH: 20 MM HEXAGON NUT DIMENSION: INSIDE DIA: 10 MM PITCH THREAD: 1.5 MM HEIGHT: 7 MM WIDTH: 20 MM MATERAL GRADE EN 4140GENERAL SPECIFICATION - HEXAGON BOLT DIMENSION: OUT SIDE DIA: 10 MM PITCH THREAD: 1.5 MM LENGTH: 40 MM LENGTH WITHOUT HEAD: 35 MM HEAD WIDTH: 20 MM HEXAGON NUT DIMENSION: INSIDE DIA: 10 MM PITCH THREAD: 1.5 MM HEIGHT: 7 MM WIDTH: 20 MM MATERAL GRADE EN 4140	
62	SGB68662		0267599235338 / Tee pipe (three sides equal) black		30 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - BS 1740/71 nominal bore size 1.00 inch (dimension 25 mm), corrosion resisting steel/ferrous alloy, thread type BSP (TPI 11) oem coc: requiredGENERAL SPECIFICATION - BS 1740/71 nominal bore size 1.00 inch (dimension 25 mm), corrosion resisting steel/ferrous alloy, thread type BSP (TPI 11) oem coc: required	
63	SGH63392		0212595710913 / CHANNEL MILD STEEL		24 / METER					.	TECHNICAL SPECIFICATION - DIMENSIONS: 8 INCH (WIDTH) X 3 1/2 INCH X 3 1/2 INCH (GAP OF U	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SZ 8X3 1/2X3 1/2, WEIGHT 20LBS/FT								CHANNEL) X 8MM (TH), RUNNING LENGTH 6 RM SPECS BSEN 10025-2/2004, MATERIAL GRADE S-275JRGENERAL SPECIFICATION - DIMENSIONS: 8 INCH (WIDTH) X 3 1/2 INCH X 3 1/2 INCH (GAP OF U CHANNEL) X 8MM (TH), RUNNING LENGTH 6 RM SPECS BSEN 10025-2/2004, MATERIAL GRADE S-275JR	
64	SGH61476	DNC/S23	0212595710921 / CHANNEL STEEL CARBON STEEL BLACK 102X51 MM WEIGHT PER FT 7LB		50 / METER						TECHNICAL SPECIFICATION - bsen 10025 of 2004 grade s275JR MATERIAL TEST CERTIFICATE REQUIREDGENERAL SPECIFICATION - bsen 10025 of 2004 grade s275JR MATERIAL TEST CERTIFICATE REQUIRED	
65	SGB80273		0267599235092 / ELBOW ROUND BLACK 0.50IN		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - material: black steel grade: bs1740 nominal dia: 1/2 inch treads: bsp pressure: 150 psi degree: 90 requirement of galvanization or heat treatment: n.aGENERAL SPECIFICATION - material: black steel grade: bs1740 nominal dia: 1/2 inch treads: bsp pressure: 150 psi degree: 90 requirement of galvanization or heat treatment: n.a	
66	SGB73427		0214502140586 / Bolt and Nut Steel Head Hexagonal		350 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL: BS 1210 Length: 8.750 inch Dia: 0.625 inch Full threaded TPI 11 GENERAL SPECIFICATION - MATERIAL: BS 1210 Length: 8.750 inch Dia: 0.625 inch Full threaded TPI 11	
67	SGB56865	SPECIFICATION BS 887	0274599100077 / CALIPER VERNIER ENG&MM COMB IN&EXT W/CASE 0-TO9"(0-TO-225MM)	MEASURING TOOL	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION BS 887GENERAL SPECIFICATION - SPECIFICATION BS 887	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
68	SGH61513		0212595275272 / ANGLE STEEL CARBON 02"X02"X1/4" LG 6 METER		4 / METER					.	TECHNICAL SPECIFICATION - DIMENSIONS: ANGLE STEEL CARBON 02"X02"X1/4" LG 6 METER MATERIAL GRADE : S275JR TOLERANCES LENGTH +-1/8 INCH THICKNESS: 6MM THICKNESS +-0.01 INCH STRAIGHTNESS 1/8 INCH PER 5 FEET LENGTH GENERAL SPECIFICATION - DIMENSIONS: ANGLE STEEL CARBON 02"X02" X1/4" LG 6 METER MATERIAL GRADE : S275JR TOLERANCES LENGTH +-1/8 INCH THICKNESS: 6MM THICKNESS +-0.01 INCH STRAIGHTNESS 1/8 INCH PER 5 FEET LENGTH	
69	SGB61478		0214790131424 / BOLT MACHINE STEEL BSF HEX HD SZ 0.875X6.000X1.750 IN	BS 1083 THREAD SIZE 22.225MM	100 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - DIA: 7/8" LENGTH: 6" sPEC: PD 970: 2005 MATERIAL GRADE 708M40/42 CRMO4GENERAL SPECIFICATION - DIA: 7/8" LENGTH: 6" sPEC: PD 970:2005 MATERIAL GRADE 708M40/42 CRMO4	
70	SGB56738		0214590035655 / BOLT MACHINE ST. BSW HEX HD THREAD LG3/4"SZ 2.0 X0.375IN TPI16		50 / TEN					.	TECHNICAL SPECIFICATION - Material GRADE bs-970 en 4140 GENERAL SPECIFICATION - Material GRADE bs-970 en 4140	
71	SGB81789		0283705711634 / BRAZING ALLOY, SILVER,STRIP WIDTH 0.1875 TH 0.048 IN LG22-24 inch MATERIAL AG-103		200 / GRAM					.	TECHNICAL SPECIFICATION - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%GENERAL SPECIFICATION - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
72	SGB56631	A0188	0273599104246 / WOODEN CHISEL PARING WIDTH OF CUT 0.375 LG BOISTER TO POINT 8.500IN		12 / EACH/NUMBER	A0188				.	TECHNICAL SPECIFICATION - SIZE: 3/4 INCHGENERAL SPECIFICATION - SIZE: 3/4 INCH	
73	SGB61937		0214599410137 / NUT-PLAIN-HEX-UNC-0.75-INCH X 1.250 X0758 INCH SPEC. 1769		50 / TEN					.	TECHNICAL SPECIFICATION - material: ms matrial steel BS 970 EN 3a,COLOUR BLACK,specs bs 1769 (heavy sieries): uncclass 2b oem coc/mtc requiredGENERAL SPECIFICATION - material: ms matrial steel BS 970 EN 3a,COLOUR BLACK,specs bs 1769(heavy sieries): uncclass 2b oem coc/mtc required	
74	SGB66987	MATERIAL GRADE EN 4140	0214599416388 / BOLT MACHINE STEEL UNC HEX HD 0.75 X12X2 INCH TPI 10 (LOCAL)		100 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIREDGENERAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
75	SGB51720		0214590130818 / BOLT MACHINE STEEL BSF HEX HD SZ 0.500X4.500X1.000 IN		10 / TEN					.	TECHNICAL SPECIFICATION - Material: ferrous Grade: EN4140, DGS 8060 class 1(a) (as per BR-320d) GENERAL SPECIFICATION - Material: ferrous Grade: EN4140, DGS 8060 class 1(a) (as per BR-320d)	
76	SGB68083	NO DATA AVAILABLE	0257702570025 / POP-RIVET-ALUMINUM-ALLOY 50% MAG NOM SELF TAPIN TYPE DIA4.00	HANGER DOOR	400 / KILOGRAMME					.	TECHNICAL SPECIFICATION - Grade: Aluminum Length: 11mm Dia: 4mm GENERAL SPECIFICATION - Grade: Aluminum Length: 11mm Dia: 4mm	
77	SGB56621		0266591363310 / SCREW MACHINE B STEEL BSW	DRIVE FIT FREE SPEC=BS 450	400 / TEN					.	TECHNICAL SPECIFICATION - a. Size: 1.500X0.500 Inch b. Material Grade: Steel (SPEC=BS 450) c. Acceptance Criteria: As per specs &	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OVAL CSK HD SZ 1.500X0. 500IN								standard mentioned in S. No. b GENERAL SPECIFICATION - a. Size: 1.500X0.500 Inch b. Material Grade: Steel (SPEC=BS 450) c. Acceptance Criteria: As per specs & standard mentioned in S. No. b	
78	SGH62691	SPEC DG SHIPS 212 TABLE 9	0561595218441 / CABLE ELECT BUTYL CSP 4CORE COND 7/.670 440V 33AMP 500LG		65 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
79	SGE68775	621100/3068.184	4220795229562 / FINS SWIM RUBBER BLACK	FOR DIVING	4 / PAIR						TECHNICAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95LBs(2.25Kg,MADE USA. GENERAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95LBs(2.25Kg,MADE USA.	
80	SGB52796	CATLOG-NO.(USA) 42-059-008WHITE	3439715066892 / ELECTRODE (WHITE)TUFF COTE CUTTING U/WATER DIA 5/16X18	FOR GENERAL USE	300 / PACKET						TECHNICAL SPECIFICATION - Size: 3/8" x 18" Polarity: DC Electrode Negative (DCEN) Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration Material: Low Carbon Steels Technique: Use short Arc length with electrode angle 30o +15o, to the line of weld. UTILIZED DURING UNDERWATER WELDING OPERATION. MUST BE AS PER ISO 9000 STANDARD. MUST HAVE WATER PROOF COATING.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilit y	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL SPECIFICATION - Size: 3/8" x 18" Polarity: DC Electrode Negative (DCEN) Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration Material: Low Carbon Steels Technique: Use short Arc length with electrode angle 30o +15o, to the line of weld. UTILIZED DURING UNDERWATER WELDING OPERATION. MUST BE AS PER ISO 9000 STANDARD. MUST HAVE WATER PROOF COATING.	
81	SGB66988	10N47 (WELDCRAFT (USA) or equivalent)	3439701004654 / CERAMIC SHEILD HI-AMP CUPS SIZE-7, O/A LG 47.4 I/D 9,10 MM		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - Ceramic Shield (Cup) Size No. 7, Part No 10N47, Make: WELDCRAFT (USA) or equivalent, Packing: 10 Pieces/ Packet.GENERAL SPECIFICATION - Ceramic Shield (Cup) Size No. 7, Part No 10N47, Make: WELDCRAFT (USA) or equivalent, Packing: 10 Pieces/ Packet.	
82	SGB61477		5306PK5065916 / BOLT 8X35MM (STEEL) NOMINAL LENGTH: 35MM, OUTER DIA 8MM, THREAD LENGTH 24X11MM, TPI 20		200 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Bolt, overall length 35 mm b. Outer dia: 8 mm c. Nominal Length: 35mm d. Length of Thread: 24mm TPI 20 e. material grade: AISI 4140 or (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) OEM COC/MTC required GENERAL SPECIFICATION - a. Bolt, overall length 35 mm b. Outer dia: 8 mm c. Nominal Length: 35mm d. Length of Thread: 24mm TPI 20 e. material grade: AISI 4140 or (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) OEM COC/MTC required	
83	SGB51525		4730995311398 / FLANGE PIPE STEEL ROUND SIZE 4.0X8.50X0.50 INCH	GERNAL USE	100 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION : BS10 AS PER BR-320D NOMINAL SIZE: 100 MM, NOMINAL BORE: 4 INCH, FLANGE OD: 8-1/2 INCH, FLANGE THICKNESS: 1/2 INCH, BOLT HOLES SIZE: 11/16 INCH, NO. OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BOLT HOLES: 4 (DATA SHEET FROM CATALOG OF NAVAL STORES IS ENCLOSED)GENERAL SPECIFICATION - SPECIFICATION : BS10 AS PER BR-320D NOMINAL SIZE: 100 MM, NOMINAL BORE: 4 INCH, FLANGE OD: 8-1/2 INCH, FLANGE THICKNESS: 1/2 INCH, BOLT HOLES SIZE: 11/16 INCH, NO. OF BOLT HOLES: 4 (DATA SHEET FROM CATALOG OF NAVAL STORES IS ENCLOSED)	
84	SGB81787		4730995311376 / FLANGE, PIPE STEEL, ROUND Nominal BORE1.00 inch	FOR PIPE FITTING/AS&AS P-6 KHAIBER, TARIQ	300 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL GRADE: MILD STEEL MILD STEEL, STANDARD: BS-10 OF 2009, GRADE S235-JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3-1/4 INCH, OUTER DIA: 4-1/2 INCH, BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH GENERAL SPECIFICATION - MATERIAL GRADE: MILD STEEL MILD STEEL, STANDARD: BS-10 OF 2009, GRADE S235-JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3-1/4 INCH, OUTER DIA: 4-1/2 INCH, BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH	
85	SGB81788		4730705038534 / ELBOW BAND PIPE 90 deg with out threads (welding purpose)	DUMP BARGE CONSTRUCTION	140 / EACH/NUMBER						TECHNICAL SPECIFICATION - Mild Steel ASTM-106 Grade B Inner dia. 76mm, Outer dia. 88mm, Wall thickness 6mm Application Fuel and sea water systemGENERAL SPECIFICATION - Mild Steel ASTM-106 Grade B Inner dia. 76mm, Outer dia. 88mm, Wall thickness 6mm Application Fuel and sea water system	
86	SGB714		530699124362	FASTENINGS,	160 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	56		8 / BOLT MACHINE ISO STEEL HEX HD SIZE 16X5X38 MM	BOLTS AND STUDS.	EACH/NUMBER						SIZE: 16X5X38 MM, MATERIAL: MS, Grade AISI 4140, BOLT HEAD HEXAGONGENERAL SPECIFICATION - SIZE: 16X5X38 MM, MATERIAL: MS, Grade AISI 4140, BOLT HEAD HEXAGON	
87	SGE83277		5350731002897 / PAPER GARNET SANDING DISC DIA 30" P-80 BONNIN MACHINE	FOR COMBINED DISE & BOBBIN MACHINE	36 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
88	SGE83278	nil	5350001619715 / PAPER ABRASIVE 9" X11" ALUMI. OXIDE MATERIAL EMERY GRADE 240-J	GENERAL USE	35 / PACKET					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
89	SGE8285	nil	5350001619715 / PAPER ABRASIVE 9" X11" ALUMI. OXIDE MATERIAL EMERY GRADE 240-J	GENERAL USE	20 / PACKET					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
90	SGE68778	BA111131/5931052	8465725022150 / BAG CARRYING FOR DIVING EQUIPMENT		7 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - (1) Volume : 130 Liters (2) Dimension : 85 cm x35 cm x 45 cm (3) Made from : Bag made with Tarpolin (4) Shape : U shape for opening (5) Appearance : 2 handles and shoulder strips/ 2 screwed valves GENERAL SPECIFICATION - (1) Volume : 130 Liters (2) Dimension : 85 cm x35 cm x 45 cm (3) Made from : Bag made with Tarpolin (4) Shape : U shape for opening (5) Appearance : 2 handles and shoulder strips/ 2 screwed valves	
91	SGE38542	NO DATA AVAILABLE	9320705056984 / RUBBER STRIP (FOAM	GENERAL USE	340 / METER					.	TECHNICAL SPECIFICATION - Rubber Type: Ethylene-Propylene Rubber (EPDM).GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TYPE), SIZE, WIDTH= 30MM, THICKNESS= 20-MM, (LENGTH PER ROLL= 15-MTR)								SPECIFICATION - Rubber Type: Ethylene-Propylene Rubber (EPDM).	
92	SGE78726	NOT KNOWN	7920705181271 / BROOM SCRUBBING DECK (FOR DECONTAIMINATION)	NIL	100 / EACH/NUMBER		NIL	LOCAL MARKET	NIL	.	TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21	
93	DNM92940	SA9-27019PF	6260011959753 / LIGHT CHEMICAL 6INCH ORANG/CYALUME CHEMLIGH ORANGE		50 / EACH/NUMBER			CYALUME TECHNOLOGIES SA 295 R MAYOR DE MONTRICHER AIX EN PROVENCE FRANCE AIX EN PROVENCE CEDEX 3 13591 04 42 37 17 80 04 42 37 17 99 XFARCY@CYALUME.COM MWWW.CYALUME.COM	CYALUME TECHNOLOGIES SA 295 R MAYOR DE MONTRICHER		TECHNICAL SPECIFICATION - Make/ Model / Brand Equivalent : Cyalume TechnologiesGENERAL SPECIFICATION - Make/ Model / Brand Equivalent : Cyalume Technologies	
94	DNQ92941	SPL-1	6230999910504 / FLOOD LIGHT ELECTRICAL (NITECH UK)	FLOOD LIGHT LIGHT ELECTRICAL	2 / EACH/NUMBER			UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM 01424 852788	UK		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY; UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM TN38	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK			9UB 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK GENERAL SPECIFICATION - SOURCE OF AVAILABILITY; UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM TN38 9UB 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK	
95	DNM90417	181211	5305001320267 / SCREW, HEXAGON HEAD CAP	CUMMINS DG VTA28-G5 USA	6 / EACH/NUMBER	VTA28-G5	25354882	CUMMINS ENGINE COMPANY, INC. BOX 3005 COLUMBUS, INDIANA, USA 47202	CUMMINS ENGINE COMPANY, INC. USA	.	TECHNICAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA CYL HEAD BOLTSGENERAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA CYL HEAD BOLTS	
96	DPC93215	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	14 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
97	DPC93311	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	10 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
98	DPK93229	PP 47-32 / P-903SW220-5TTL	4310FM0450001 / POLYESTER OIL CARRIER COMPRESSOR (5 LTRS PACKING)	CHILL WATER UNIT	50 / LITER	CARRIER		CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA, UNITED SATE	CARRIER CORP 1419 N MARKEET ST, SACRAMENTO, CA,UNIT		TECHNICAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA,UNITED SATEGENERAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA,UNITED SATE	
99	DNM89448	112-4033/1061706	2930715156565 / TANK GP EXPANSION	DG	1 / EACH/NUMBER	3306 B AND S. N0. 85Z3764-UP	3306 B	CATER PILLER DIESEL CO USA.	USA	.	TECHNICAL SPECIFICATION - .list of accessories enclosedGENERAL SPECIFICATION - .list of accessories enclosed	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
						CATER PILLER D/G						
100	DNM91669	5N5692	6115015352699 / GENERATING, ALTERNATING CURRENT (ALTERNATOR GP 24 VOLT 45 AMPERE)	CATERPILLAR ENGINE 3306	1 / EACH/NUMBER	3306	64Z28249	CATTER PILLAR UK	CATTER PILLAR UK		TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
101	DPC91539	COOL-0026	1420795174457 / Anti freeze & Coolant Xstream G48 (Brand Comma) packing (02 LTRS OR 20 LITERS)	Engine Cooling System	160 / LITER	Hovercraft 8100 TD	N/A	Griffon Hoverworks, Merlin Quay Hazel Road, Woolston, Southampton, SO19 7GB, UK	Griffon Hoverworks, Merlin Quay Hazel Road, Woolst	.	TECHNICAL SPECIFICATION - Used in Turbo Cooling System of engine as coolant. It maintains Engine Temperature within permissible limits and acts as anti corrosion element.GENERAL SPECIFICATION - Used in Turbo Cooling System of engine as coolant. It maintains Engine Temperature within permissible limits and acts as anti corrosion element.	
102	DPK91918	ATF DEXRON II	9150218708820 / HYDRAULIC FLUID AUTO TRANSMISSION (OIL GRADE: DEXRON II (MINERAL OIL)) (PACKING 16 LITER CAN)		64 / LITER	NO DATA AVAILABLE		IT	PETRO-CANADA INC 150 6TH AVE SW CALGARY AB CANADA T2P 3E3 2844	.	TECHNICAL SPECIFICATION - oil grade: Dexron II (mineral oil) Test Method Typical Properties Kinematic viscosity (100oc), {c St} ASTM D445 6,4 – 8,9 Viscosity index ASTM D2270 Min. 150 Flash Point, O C ASTM D92 Min. 200 Pour Point, O C ASTM D97 Max. -40 GENERAL SPECIFICATION - oil grade: Dexron II (mineral oil) Test Method Typical Properties Kinematic viscosity (100oc), {c St} ASTM D445 6,4 – 8,9 Viscosity index ASTM D2270 Min. 150 Flash Point, O C ASTM D92 Min. 200 Pour Point, O C ASTM D97 Max. -40	
103	DPC89741	-	6750705139827 / SODIUM HYPOCHIORITE (Normal Household Bleach) 5% Concentration	EVAC SYSTEM	20 / LITER	NO DATA AVAILABLE		UK	UK	.	TECHNICAL SPECIFICATION - . GENERAL SPECIFICATION - .	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(20-25 ltr can)									
104	DPK91917	3809441	9150735169761 / SYNTHETIC TRANSMISSION OIL SAE75W-90 (Packing 20 LITRE)	VOLVO PENTA ENGINES	80 / LITER	SAE75W-90		AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	VOLVO PENTA	.	TECHNICAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669 AB VOLVO PENTA PAKISTAN VPL PLOT 6 SECT 24 KORANGI INDUSTRIAL AREA KARACHI 2811+4669GENERAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669 AB VOLVO PENTA PAKISTAN VPL PLOT 6 SECT 24 KORANGI INDUSTRIAL AREA KARACHI 2811+4669	
105	DPC89571	BS381C	8010991689269 / PAINT BRUSHING GREY	F-22P FRIGATES	6 / LITER	NO DATA AVAILABLE		UK	INTERNATIONAL PAINTSLTD.P.O. BOX: 20980, ORIEL HOUSE 16 CANNAUGHT PLACE, LONDON, W22 2ZB, UNITED KINGDOM.	.	TECHNICAL SPECIFICATION - OEM ADD:INTERNATIONAL PAINTS LTD. P.O.BOX 20980, ORIEL HOUSE 16,CANNAUGHT PLACE,LONDON,W22 2ZB,UK. GENERAL SPECIFICATION - OEM ADD:INTERNATIONAL PAINTS LTD. P.O.BOX 20980,ORIEL HOUSE 16,CANNAUGHT PLACE, LONDON,W22 2ZB,UK.	
106	DNM91024	BRA10312H	2530715140377 / AIR COMPRESSOR 10HP 380V, 3PHASE,MAX. 175PSI	AIR COMPRESSOR	1 / EACH/NUMBER	FTK100300		US	SNAP ON LOGISTICS COMPANY COSTOMER	.	TECHNICAL SPECIFICATION - a. OEM & Make: Fountain b. Model: FTK100300 b. Origin: Taiwan 30AMP,460V,MAG STARTER,HOUR METER AUTO DRAIN,AIR DELIVERY SCFM@PS 36.00175 GENERAL SPECIFICATION - a.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									WARANTY INFORMATION CENTER KENOSHA WISCONSIN 53141-1410.262-656-5200		OEM & Make: Fountain b. Model: FTK100300 b. Origin: Taiwan 30AMP,460V,MAG STARTER,HOUR METER AUTO DRAIN,AIR DELIVERY SCFM@PS 36.00175	
107	DPC89997	TT-L-58	8010011390328 / LACQUER	CIWS ILM BLK 1B USA	1 / PACKAGE	BLK 1B	N/A	FEDERAL SPECIFICATIONS PROMULGATED BY GENERAL SERVICES ADMINISTRATION WASHINGTON DC, ST1:100 BUREAU DR, CIT:NATL INSTITUTE STDS & TECH, USA PSC:20899	FEDERAL SPECIFICATIONS	.	TECHNICAL SPECIFICATION - AS PER UPLOADED IPCGENERAL SPECIFICATION - AS PER UPLOADED IPC	
108	DNQ91236	CEN1000063A	5510FT1019830 / Wooden Plug, 200 x 30 x 8 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
109	DPC93224	WD40	8030014189008 / WD40 (PACKING 440ML SPRAY BOTTLE)	0	56 / EACH/NUMBER	0	0	1061 CUDAHY PL, SAN DIEGO, CA SAN DIEGO CA	WD-40 COMPANY		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
110	DNM90720	380-1882	6625715228830 / SENSOR GP-PRESSURE (ENGINE OIL)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
111	DNM90617	344-5894	2895715228403 / MOUNT	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	4 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE	ALLIED CAT	.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA				
112	DPK90155	90790-74066/90890-69911	9150765168798 / YAMAHA GREASE (200g/TUBE)	SFB (ENGINE)	12 / TUBE	F350A	102563X35	YAMAHA CORPORATION USA /JAPAN	YAMAHA	.	TECHNICAL SPECIFICATION - YAMAHA CORPORATION USA /JAPANGENERAL SPECIFICATION - YAMAHA CORPORATION USA /JAPAN	
113	DPK93226	N 320	9150FP0010005 / GREASE LUBRICANT (200 LITERS PACKING) SINOPEC	F-22P SHIPS	200 / LITER	NO DATA AVAILABLE		CH	CSTC-CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINAGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINA	
114	DPC91903	GB/T/678-2002 (99.5)	6810FP0010002 / ALCOHOL 99.5%	F-22P SHIPS	5 / CAN	NO DATA AVAILABLE		CH	CSTC-CHINA	.	TECHNICAL SPECIFICATION - MODEL: 32061 OEM ADDRES: ZHONGYUAN RESEARCH INSTITUTE OF ELECTRONIC TECHNOLOGY NO-71 HANGHAI MID ROAD ZHENGZHOU CITY HANON PROVINCE CHINA VIDE PNS SAIF LETTER 400/GEN/164 DT 13 JAN 14.GENERAL SPECIFICATION - MODEL: 32061 OEM ADDRES: ZHONGYUAN RESEARCH INSTITUTE OF ELECTRONIC TECHNOLOGY NO-71 HANGHAI MID ROAD ZHENGZHOU CITY HANON PROVINCE CHINA VIDE PNS SAIF LETTER 400/GEN/164 DT 13 JAN 14.	
115	DPK93370	sh/t0371-1992/SH/T0378-1992	9150FP0020004 / ALUMINIUM BASED GREASE	F-22P SHIPS	32 / KILOGRAMME	NO DATA AVAILABLE		CH	CSTC-CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINAGENERAL SPECIFICATION - SOURCE OF AVAILIBILITY: CSTC, CHINA	
116	DNH89653	7611005	6105705168378 / FOLDABLE W/SHOP CRANE	FOLDABLE CRANE	2 / EACH/NUMBER	1.5T-SPR-L&E		MESSER INTERNATIONAL MARKETING SERVICES KARACHI C/O IBRAHIM CELL:0345-8435152	-		TECHNICAL SPECIFICATION - Capacity: 02 Tons OEM: China Control/ Equipment: Remote Control (Lifting , Extension & Rotation) RELEVANT LITERATURE: AVAILABLE ON INTERNETGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - Capacity: 02 Tons OEM: China Control/ Equipment: Remote Control (Lifting , Extension & Rotation) RELEVANT LITERATURE: AVAILABLE ON INTERNET	
117	DNM90685	423-8521	2910715223059 / FILTER GP- WATER SEP AND FUEL	caterpillar C-13 USA	1 / EACH/NUMBER	NA	NA	CATER PILLAR DIESEL GENERATOR SET Electric power North America Attn: Product support Manager AC 6109 Mossville, LLLinois 61552	CATTER PILLER	.	TECHNICAL SPECIFICATION - OEM: CATERPILLAR GENERAL SPECIFICATION - OEM: CATERPILLAR	
118	DPK92340	GB/T 7631.8-1990/CB3.	9150FP0020016 / CALCIUM BASE GREASE 3# (OEM = SHEN YANG TRI PETROC CO . LTD) 15 KG PACKING	F-22P SHIPS	45 / KILOGRAMME	NO DATA AVAILABLE		CH	CSTC, CHINA		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
119	DPC88146	A-1	6810005987316 / SODIUM HYPOCHLORITE SOLUTION (A-1 BLEACH)	SELF CONTAINED BREATHING APPRATUS	10 / BOX			1901 S BELL ST ARLINGTON 22202 USA	GENERAL SERVICE ADMINISTRATION	.	TECHNICAL SPECIFICATION - PCT BY WT SODIUM HYPOCHLORITE 5.25-6.6 PCT GENERAL SERVICE ADMINISTRATION 1901 S BELL ST ARLINGTON 22202 USAGENERAL SPECIFICATION - PCT BY WT SODIUM HYPOCHLORITE 5.25-6.6 PCT GENERAL SERVICE ADMINISTRATION 1901 S BELL ST ARLINGTON 22202 USA	
120	DNM92664	4938598	4130715194380 / FILTER AIR	CUMMINS D/G4BTA3.9-G2 USA	12 / EACH/NUMBER		87351753	CUMMINS ENGINE USA	CUMMINS ENGINE CO. LTD.		TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
121	DPC91420	CC2750M	2930015941180 / ES COMPLEAT PRE MIX 50/50 (COOLANT)	DG	25 / LITER	C350 D5	A13K447525	MANSTON COLUMBUS AVENUE RAMSGATE KENT ENGLAND CT125BS	MANSTON COLUMBUS UK	.	TECHNICAL SPECIFICATION - FLEETGUARD CC2750M 20 LTRS PACKING PREMIX 50/50 ES COMPLEAT DO NOT ADD WATER EXTENDED LIFE ANTIFREEZE / COOLANTGENERAL SPECIFICATION - FLEETGUARD CC2750M 20 LTRS PACKING PREMIX 50/50 ES COMPLEAT DO NOT ADD WATER EXTENDED LIFE ANTIFREEZE / COOLANT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
122	DPC89843	CC 2748M (5 liters packing) CC2750M (20 liters packing)	6810715229857 / ES Complete EG premix coolant	MAIN ENGINE	260 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS/ FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
123	DPC91543	CC 2748M (5 liters packing) CC2750M (20 liters packing)	6810715229857 / ES Complete EG premix coolant	MAIN ENGINE	220 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS/ FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
124	DPC93217	CC 2748M (5 liters packing) CC2750M (20 liters packing)	6810715229857 / ES Complete EG premix coolant	MAIN ENGINE	260 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS/ FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
125	DPC91150	CC 2748M (5 liters packing) CC2750M (20 liters packing)	6810715229857 / ES Complete EG premix coolant	MAIN ENGINE	240 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS/ FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
126	DPC89570	CC 2748M (5 liters packing) CC2750M (20 liters packing)	6810715229857 / ES Complete EG premix coolant	MAIN ENGINE	100 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS/ FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
127	DPC92167	CC 2748M (5 liters packing) CC2750M (20 liters packing)	6810715229857 / ES Complete EG premix coolant	MAIN ENGINE	100 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS/ FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
128	DPK93228	R 141b	6810715225084 / OIL FLUSHING	MAIN AC	70 / KILOGRAMME	R 141b	NA	COMSTAR INTERNATIONAL INC 20-45 128TH STREET	COMSTAR INTERNA		TECHNICAL SPECIFICATION - Transport package: Disposable cylinder RS-141b oil flushing	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			AGENT R 141B					COLLEGE POINT, NY 11356 +1 (800) 328-0142 USA www.comstarproducts.com	TIONAL INC		agentGENERAL SPECIFICATION - Transport package: Disposable cylinder RS-141b oil flushing agent	
129	DPK93230	828250	9150270374373 / GREASE, GENERAL PURPOSE	VOLVO PENTA MAIN ENGINE	40 / TUBE	NO DATA AVAILABLE		OC	VOLVO AB, GOETEBORG, SWEDEN		TECHNICAL SPECIFICATION - OEM ADD/SOURCE OF AVAILIBILITY:VOLVO AB, GOETEBORG,SWEDENGENERAL SPECIFICATION - OEM ADD/SOURCE OF AVAILIBILITY: VOLVO AB,GOETEBORG,SWEDEN	
130	DPC89606	YBB 727	8010795140410 / ULTRA 300 YBB 727-GREY (Antifouling Paint)	MRTP 33 &MABS	30 / LITER	NO DATA AVAILABLE		UK	INTERNATIONAL PAINT LTD PO BOX 20980 ORIAL HOUSE 16 CONNAUGHT PLACE LONDON W2 2ZB UK	.	TECHNICAL SPECIFICATION - . GENERAL SPECIFICATION - .	
131	DPK93234	0239686941 42	9150FT1018832 / Grease, High temparature, high speed, Nlgi2,14 Oz	-	5 / PACKET	-	null	6001 BOLLINGER, SAN RAMON	CHEVRON U S A INC		TECHNICAL SPECIFICATION - AS PER TPGENERAL SPECIFICATION - AS PER TP	
132	DNM90579	9510227/85148526	5999735161488 / CORROSION PROTECTION	IPS 500 (PROPULSION & STEERING SYSTEM)	4 / EACH/NUMBER			M/S VOLVO PENTA, GOTEBORG SWEDEN	M/S VOLVO PENTA	.	TECHNICAL SPECIFICATION - CORROSION PROTECTIONGENERAL SPECIFICATION - CORROSION PROTECTION	
133	DPC92056	BOSTIK M501	8010795208200 / BOSTIK THINNERS / CLEANER M501	RHIB BOAT	20 / LITER	BOSTIK M501	NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX,TEL"01963 33237, FAX 01963 34578,	HENSHAW INFLATABLES LTD	.	TECHNICAL SPECIFICATION - M501 IS USED TO CLEAN, DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 2402ADHESIVE.THINNING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								EMAIL karen@henshaw.co.uk, www.henshaw.co.uk			BOSTIK NE486,CLEANING GLUE BRUSHES.SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW TOP.HIGHLY FLAMMABLE PRODUCT AND MUST BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA.GENERAL SPECIFICATION - M501 IS USED TO CLEAN,DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 2402ADHESIVE.THINNING BOSTIK NE486,CLEANING GLUE BRUSHES.SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW TOP.HIGHLY FLAMMABLE PRODUCT AND MUST BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA.	
134	DPC92055	BOSTIK 2402	6510795208197 / BOSTIK 2402 ADHESIVE + HARDENER	RHIB BOAT	25 / LITER	BOSTIK2402		HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX,TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHAW INFLATABLES LTD	.	TECHNICAL SPECIFICATION - BOSTIK 2402 CREATES A STRONG BOND WHICH IS RESISTANT TO HEAT -40 DEG C -90 DEG C,UV, SALTWATER AND HUMIDITY COVERAGE IS APPROX 4 SQUARE METER PER LITRE(VARIES WITH SURFACE).SUPPLIED AS 1 L TIN OF ADHESIVE AND A 40 ML BOTTLE OF BOSTIKURE D HARDENER.STORE B/W 5 DEG AND 25 DEG IN A DRY FLAMPROOF AREA.GENERAL SPECIFICATION - BOSTIK 2402 CREATES A STRONG BOND WHICH IS RESISTANT TO HEAT -40 DEG C -90 DEG C,UV, SALTWATER AND HUMIDITY COVERAGE IS APPROX 4 SQUARE METER PER LITRE(VARIES WITH SURFACE).SUPPLIED AS 1 L TIN OF ADHESIVE AND A 40 ML BOTTLE OF BOSTIKURE D HARDENER.STORE B/W 5 DEG AND 25 DEG IN A DRY FLAMPROOF AREA.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
135	DNM92663	HBC 139/HBC 52	5130735227950 / BRUSH CUTTER	Bush Cutter	2 / EACH/NUMBER	HBC 139/HBC 52	NIL	Hyundai Power products, Korea	Hyundai		TECHNICAL SPECIFICATION - BBC 139/HBC 52 Engine Cylinder Displacement 31cm3 Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of carburettor Diaphragm typeGENERAL SPECIFICATION - BBC 139/HBC 52 Engine Cylinder Displacement 31cm3 Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of carburettor Diaphragm type	
136	DNQ92777	ITD/0274-7587	5110994375839 / KNIFE SEATH 100MM (4 INCH)	KNIFE(FIRE FIGHTING)	1 / EACH/NUMBER	NO DATA AVAILABLE		UK	UK ENGLAND		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
137	DNQ90687	ITD/0274-7587	5110994375839 / KNIFE SEATH 100MM (4 INCH)	KNIFE(FIRE FIGHTING)	1 / EACH/NUMBER	NO DATA AVAILABLE		UK	UK ENGLAND	.	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
138	DPK91920	MOBIL RARUS 427	9150011582881 / LUBRICATING OIL FOR AIR COMPRESSOR (PACKING = 3.80 LTRS)	HATLAPA LP AIR COMPRESSOR L-20 GERMANY	5 / LITER			MOBIL OIL CORP AVIATION & GOVERNMENT SALES DIV 3225 GALLOWS RD FAIRFAX UNITED STATES 22037-4872 703-846-4090	MOBIL	.	TECHNICAL SPECIFICATION - PATT VIDE:RASDGAR LETTER RDR/300/191 DT 16-5-11GENERAL SPECIFICATION - PATT VIDE: RASDGAR LETTER RDR/300/191 DT 16-5-11	
139	DNQ90592	08279009	6210795175762 / LIFE RAFT INTERNAL LIGHT & BATTERY	UK RFD	2 / EACH/NUMBER	UK (RFD BEAUFORT)	08279009	RFD BEAUFORT LTD (UK)	RFD BEAUFORT LTD (UK)	.	TECHNICAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)GENERAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)	
140	DPC896	YBA067-	801071520864	HULL	40 /	TRILUX	JU110016	AKZONOBEL	INTERLU	.	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	05	Black	4 / Trilux 33 Antifouling Paint (Black)		LITER	33	-B1-H	INTERNATIONAL PAINT OFFICE 536JF SMITH AVE, SLIDELL, LOUISIANA, 70460 UNITED STATES OF AMERICA TEL: 9857183358 EMAIL: PCMARKETING. AMERICAS@AKZONOBEL .COM	X AKZONOBEL GROUP OF COMPANIES USA		COLOR: BLACK FINISH: MATTE SPECIFIC GRAVITY: 1.6 VOLUME SOLID: 52% TYPICAL SHELF LIFE : 02 YRARS VOC(AS SUPPLIED): 390 gram/LITER UNIT SIZE : 20 LtrsGENERAL SPECIFICATION - COLOR: BLACK FINISH: MATTE SPECIFIC GRAVITY: 1.6 VOLUME SOLID: 52% TYPICAL SHELF LIFE : 02 YRARS VOC(AS SUPPLIED): 390 gram/LITER UNIT SIZE : 20 Ltrs	
141	DPK90431	15W40 (API CF-4/SG) /870234	91500V1210006 / LUBE OIL CUMMINS VALVOLINE PREMIUM BLUE 7800 15W40	MAINE AND EMERGENCY GENSET	440 / LITER	CUMMINS VALVOLINE VI TOPFLITE	KH180429(BVO1, BVO2, BVO3, BVO4)	SHANGHAI VCLUBRICATING OIL CO, LTD.CHINA	CHEVRON MARINE	.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
142	DPC91167	NO DATA AVAILABLE	0443500443067 / Gas Nitrogen Technical (99.998% Pure Nitrogen Gas With Less Water Content (i.e. 4 PPM), In Buyer's/ Supplier's Returnable Cylinder of Water Capacity 45 to 55 Liters With Protection Cap.	A/C NO 5 AND 6	55 / CUBIC METER					.	TECHNICAL SPECIFICATION - CGA G-10.1 OF 2008 QVLs GRADE 'L' Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder. GENERAL SPECIFICATION - CGA G-10.1 OF 2008 QVLs GRADE 'L' Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder.	
143	DPC89964		0473502247701 / GUM ACACIA TECHNICAL		20 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
144	DPC93216	NO DATA AVAILABLE	0473500005372 / SILICA GEL		50 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DPC76416		0474502201711 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	1080 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSEGENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
146	DPC87727	BS 3981	0473509429250 / PIGMENT POWDER BURNT SIENA (Packing 56 LB or 400 Gram) TIGER BRAND	USE DRY INGREDIENTS FOR PAINTS	2 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 3981 BRAND= TIGERGENERAL SPECIFICATION - BS 3981 BRAND= TIGER	
147	DPK90855		0475502203587 / OIL OM 33 (LTR NO. NSSD/POL/GEN/Q.P/417 DT. 30 NOV 96)		209 / BOTTLE						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
148	DPC92094	NO DATA AVAILABLE	0442502201164 / PAINT FINISHING GLOSS BLACK	PRIMED STEEL ALUMINUM OR WOOD	50 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			DLT LTR NS/G/1303/C DT 270199									
149	DPC921 04	NO DATA AVAILABL E	044250001064 4 / THINNER FOR VARNISH (Packing 04 liter)		100 / LITER						TECHNICAL SPECIFICATION - DEF STAN 80-38/2 195 1. FLASH POINT: 16ºC 2. INGREDIENTS PROPERTIES BY VOLUME: - METHY ISO BUTYL KETONE: 32 ± 3% - ETHYLENE GLYCOL ACETATE: 7 ± 3% - ISO BUYYLE ALCOHAOL : 25 ± 3% OEM M/S FALAH TRADING AGENCY GENERAL SPECIFICATION - DEF STAN 80-38/2 195 1. FLASH POINT: 16ºC 2. INGREDIENTS PROPERTIES BY VOLUME: - METHY ISO BUTYL KETONE: 32 ± 3% - ETHYLENE GLYCOL ACETATE: 7 ± 3% - ISO BUYYLE ALCOHAOL : 25 ± 3% OEM M/S FALAH TRADING AGENCY	
150	DPC899 16		044250442006 4 / PAINT WEATHER WORK (LIGHT GREY)NHQ LTR NS/G/1303/C DT 270199	WEATHER WORK	100 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
151	DPC874 95		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
152	SPC8896 7		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		300 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
153	DPC896 42		044250442006 9 / RUST		20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)								SPECIFICATION - NO DATA AVAILABLE	
154	DPC89347		0442504420069 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		100 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
155	DPC89646		0442509423538 / PAINT MARKING BRUSH STENCILLING (BLACK) type: alky6ed, Flash Point: 32 Degreee C (Min) moethod of application brushing, Packing: 04 ltr tin gauge of drum 26 to 28 swg	N B C D MARKING ETC.	20 / LITER						TECHNICAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed GENERAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed	
156	DPC92095	NO DATA AVAILABLE	0442504420039 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	200 / LITER						TECHNICAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
157	DPC93388	NO DATA AVAILABLE	0442504420039 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	220 / LITER						TECHNICAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
158	DPC92103	DEF-1145/1956	0442504420079 / THINNER (SPEC) DEF STAN 80-38/2 1985 (PACKING 20 LTRS DRUM)		40 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-38/2 of 1985 GENERAL SPECIFICATION - DEFSTAN 80-38/2 of 1985	
159	DPC93219	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		868 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABELGENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
160	DPC91153	WHO/SIF/14 R-5 (6TH EDITION OF85)	0442504420136 / Insecticide Malathian 60		110 / LITER						TECHNICAL SPECIFICATION - Insecticide Malathion 57 to 60% EC, SPECIFICATION: Active Ingredience (A.1) Malathion 57 to 60% EC W/W PACKING: 01 Ltr Plastic Packing with registered labelGENERAL SPECIFICATION - Insecticide Malathion 57 to 60% EC, SPECIFICATION: Active Ingredience (A.1) Malathion 57 to 60% EC W/W PACKING: 01 Ltr Plastic Packing with registered label	
161	DPC91931	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer DIa=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,	
162	DPC91033	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilit y	Tender Remarks	TECH / GEN SPECS	Dimension
											type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,	
163	DPC91158	NO DATA AVAILABLE	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilit y	Tender Remarks	TECH / GEN SPECS	Dimension
											SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2. 1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOt ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,	
164	DPC90353	NO DATA AVAILABLE	0414599241819 / SILICATE LIQUIED		30 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			CEMENT								AVAILABLE	
165	DNQ918 23		026599419526 4 / 6" STAPLE CLAMP		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
166	DNQ918 77	DEVELOP ED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H6O 6.5MM DIA		4 / EACH/N UMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
167	DNQ918 24	DEVELOP ED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H6O 6.5MM DIA		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
168	DNH926 68	MODEL NO SS-30P (STEEL)	130850053012 9 / COOLER W/DRINKING2 0-25 LTR. 1/2TON AMPS 2.5 220V SING PHASE		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
169	DPC911 56		047350473005 3 / SALT ZOZAX PASSIVTING		35 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
170	DPC932 23		047450474001 2 /		9 / EACH/N						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DEOXIDISING TUBE (1 TUBE =25 GRAMS)		UMBER						SPECIFICATION - NO DATA AVAILABLE	
171	DPK91065	OM-33, DEFSTAN 91-39/3 of 2001	0475999440596 / Lub Oil OM-33 NATO H-576 With Q.C Petroleum ANTIWEAR HYDRALIC FLUID (200-210 ltr packing)	HYDRAULIC Fluid in M TOOL lubricating in Rada equipment ETC	208 / LITER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
172	DPK91911	NO DATA AVAILABLE	0474509100504 / GREASE PUMPABLE CALCIUM BASE XG-380 (3KG TIN)		36 / KILOGRAMME					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
173	DPK89970	XG-264	0474509100516 / GREASE XG-264 (as per table 5A of Defstan 01-5/17)		10 / KILOGRAMME					.	TECHNICAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17GENERAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17	
174	DPK91914	XG-264	0474509100516 / GREASE XG-264 (as per table 5A of Defstan 01-5/17)		10 / KILOGRAMME					.	TECHNICAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17GENERAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17	
175	DPC91155	NO DATA AVAILABLE	0473504730033 / DISTILLED WATER (10 ltr packing)		130 / GALLON					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
176	DPK91921	DEFSTAN 91-25	0721509100578 / LUB OIL GEAR OM-100 (OEM ORIGINAL SEALED PACKING 200 TO 210 LTR) NATO CODE: 0-240.	USE IN MAIN AUX.SYSTEM TURBINE	210 / LITER					.	TECHNICAL SPECIFICATION - OEM ADDRESS ; AS PER NMCRL FROM QIENTIQ UKGENERAL SPECIFICATION - OEM ADDRESS ; AS PER NMCRL FROM QIENTIQ UK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
177	DNM90985	6N9312	2930711003767 / SEAL GROUP PART NO 6N312 D/E CATERPELLER	3304PC, CATERPILLER D/GEN.USA	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
178	DNM91601	20405837-4	2940735110173 / AIR FILTER	AIR SYSTEM (SWEEDEN)	1 / EACH/NUMBER	VOLVO PENTA/ 20405837-4					TECHNICAL SPECIFICATION - Filter type: Air Filter, Primary radial seal Diameter: 221 mm Length: 375.5 mm Weight: 1.76 kgGENERAL SPECIFICATION - Filter type: Air Filter, Primary radial seal Diameter: 221 mm Length: 375.5 mm Weight: 1.76 kg	
179	DNM90940	7L7504/2592550	2930US5080823 / BODY SEA WATER PUMP	CATTER PILLER D/G (U S A)	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
180	DNM90983	7N5899 (3040-01-122-6149)	2930711003768 / SHAFT F/W/PP DIE CATERPELLER P/N 7N5899	3304PC, CATERPILLER D/GEN.USA	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
181	DNM90913	5N9359 (3040-01-203-0160)	3040715035130 / SHAFT, SHOULDERED OA-LG168MM-COLLAR-DIA34.8MM SPLINED ENDED	INDUSTRIEL MARINE CATTER PILLER D/G	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Spline EndedGENERAL SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Spline Ended	
182	DNM90960	7N5910	2930711003773 / IMPELLER P/N 7N5910 D/E CATERPELLER USA	CATTER PILLER DIESEL ENGINE 50KW	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
183	DNQ92920	TF50	4210705051591 / AFFF 50 LTR TROLLY MOUNTED MOBILE FIRE EXTINGUISHER	FIRE FIGHTING	6 / EACH/NUMBER	TF50					TECHNICAL SPECIFICATION - AFFF Foam 3% Volume : 50 Ltr Discharge Time: > 120 Sec Discharge Range: > 10 Mtr for 30 Sec Working Pressure: > 13 bar Hose Length: 10 mtr Valve: Quarter Turn Ball Type Cylinder: Stainless Steel Polyster Resin Powder Coated	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilit y	Tender Remarks	TECH / GEN SPECS	Dimension
											Trolley: Welded tubular mild steel, polyester powder coat , STEEL HUB, ROLLER BEARING pneumatic tyres UL/FM , BSI / KITE Mark approved BS EN 1866-1:2007 and BS EN 3-7 & 8 1-MODEL TF50 2-CAPACITY 50 LTRGLORIA 3-TOTAL WEIGHT 82 KG 4-TOTAL HEIGHT 1010MM 5-TOTAL WIDTH 555 MM 6- TOTAL DEPTH 695 MM 7- HOSE LENGTH 5000MM 8-MAXIMUM EFFCTIVE RANGE 8 M 9-DURATION OF DISCHARGE 38-42 (SEC) 10-WORKING PRESSURE 12-15 BAR 11- PROPELLING AGENT N2 EXTINGUISHER AGENT AFFF 12-TESTING PRESSURE 30 BAR 13-STORAGE TEMPERATURE 5 DEGREE C 14-COATING ELECTROSTIC POLYESTER POWDER SAUDI FIRE EQUIPMENT CO (SFFECO) Likely Supplier/OEM Prime Business Syndicate Abid Chamber, Shop # G-2, Sharah-e-Liaquat Karachi Contact No: 0333-2195970 Meraj Ltd. Cdr (R) Mehdi 021-35050145 03008216714 Abdullah Anti Fire Corp. Ghulam Nabi 042-36813131 0321-9403211GENERAL SPECIFICATION - AFFF Foam 3% Volume : 50 Ltr Discharge Time: > 120 Sec Discharge Range: > 10 Mtr for 30 Sec Working Pressure: > 13 bar Hose Length: 10 mtr Valve: Quarter Turn Ball Type Cylinder: Stainless Steel Polyster Resin Powder Coated Trolley: Welded tubular mild steel, polyester powder coat , STEEL HUB, ROLLER BEARING pneumatic tyres UL/FM , BSI / KITE Mark approved BS EN 1866-1:2007 and BS EN 3-7 & 8 1-MODEL TF50 2-CAPACITY 50 LTRGLORIA 3-TOTAL WEIGHT 82	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											KG 4-TOTAL HEIGHT 1010MM 5-TOTAL WIDTH 555 MM 6- TOTAL DEPTH 695 MM 7- HOSE LENGTH 5000MM 8-MAXIMUM EFFCTIVE RANGE 8 M 9-DURATION OF DISCHARGE 38-42 (SEC) 10-WORKING PRESSURE 12-15 BAR 11- PROPELLING AGENT N2 EXTINGUISHER AGENT AFFF 12-TESTING PRESSURE 30 BAR 13-STORAGE TEMPERATURE 5 DEGREE C 14-COATING ELECTROSTIC POLYESTER POWDER SAUDI FIRE EQUIPMENT CO (SFFECO) Likely Supplier/OEM Prime Business Syndicate Abid Chamber, Shop # G-2, Sharah-e-Liaquat Karachi Contact No: 0333-2195970 Meraj Ltd. Cdr (R) Mehdi 021-35050145 03008216714 Abdullah Anti Fire Corp. Ghulam Nabi 042-36813131 0321-9403211	
184	DNQ92921	BS EN-3	4210705036007 / CO2 CYLINDER TROLLY MOUNTED 50KG WITH VALVE &HP HOSE DIA.75"	FIRE FIGHTING EQIPMENT	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - DES:CO2 CYLINDER TRALLY MOUNTED 50KGGENERAL SPECIFICATION - DES:CO2 CYLINDER TRALLY MOUNTED 50KG	
185	DNQ91830	MS149111/5033-50	4220013272120 / DIVING GOGGLES WITH SAFETY GLASS DOUBLE SEALING FRAME	FOR DIVING USE.	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - * Double lends, 3mm tempered glass. new twin buttons seeger release system, it make glass locking rings removal quick, safe and easy. * Pure silicon mask skirt it fits like the micromask skirt. * cardanc joint buckles (double joint buckles) rotate both up-and-down and in-and-out. * quick counterposed push button activation is easy to use even when wearing gloves. * wide headpiece on silicone strap provides stability and comfort. GENERAL SPECIFICATION - * Double lends,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilit y	Tender Remarks	TECH / GEN SPECS	Dimension
											3mm tempered glass. new twin buttons seeger release system, it make glass locking rings removal quick, safe and easy. * Pure silicon mask skirt it fits like the micromask skirt. * cardanc joint buckles (double joint buckles) rotate both up-and-down and in-and-out. * quick counterposed push button activation is easy to use even when wearing gloves. * wide headpiece on silicone strap provides stability and comfort.	
186	DNQ92925	MS149111/5033-50	4220013272120 / DIVING GOGGLES WITH SAFETY GLASS DOUBLE SEALING FRAME	FOR DIVING USE.	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - * Double lends, 3mm tempered glass. new twin buttons seeger release system, it make glass locking rings removal quick, safe and easy. * Pure silicon mask skirt it fits like the micromask skirt. * cardanc joint buckles (double joint buckles) rotate both up-and-down and in-and-out. * quick counterposed push button activation is easy to use even when wearing gloves. * wide headpiece on silicone strap provides stability and comfort. GENERAL SPECIFICATION - * Double lends, 3mm tempered glass. new twin buttons seeger release system, it make glass locking rings removal quick, safe and easy. * Pure silicon mask skirt it fits like the micromask skirt. * cardanc joint buckles (double joint buckles) rotate both up-and-down and in-and-out. * quick counterposed push button activation is easy to use even when wearing gloves. * wide headpiece on silicone strap provides stability and comfort.	
187	DNH92774		4120705051919 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	1 / EACH/NUMBER					t3-seres in arry	TECHNICAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION -	

S. No	I.PR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
188	DNH92936	NO DATA AVAILABLE	3431705048748 / WELDING RECTIFIER, W/CART, WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT	USER WELDING SHOP DOCKYARD	1 / SET						TECHNICAL SPECIFICATION - WELDING RECTIFIER W/CART I/P 380/440V 3P 50/60HZ O/P600A WITH500A30/50M STICK WELDING ACESSARIES KITGENERAL SPECIFICATION - WELDING RECTIFIER W/CART I/P 380/440V 3P 50/60HZ O/P600A WITH500A30/50M STICK WELDING ACESSARIES KIT	
189	DNM91878	ALCO CONTROL D-48	4120795013825 / DRIER CORE LG 140MM O/D 96MM X I/D 44MM (ALCO CONTROL D-48)	AIR CONDITIONING PLANT	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - MAKE: COOLPOINT, LG 140MM O/D 96MM X I/D 44MM (ALCO CONTROL D-48)GENERAL SPECIFICATION - MAKE: COOLPOINT, LG 140MM O/D 96MM X I/D 44MM (ALCO CONTROL D-48)	
190	DNH92857	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
191	DNH92084		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	1 / EACH/NUMBER	WA60000514					TECHNICAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 WGENERAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W	
192	DNH92930	NO DATA AVAILABLE	4110731001910 / WATER COOLER	WATER COOLER	1 / EACH/NUMBER					water cooler 50l canon	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			40/45 LITER ELECT220 AKS 40PW/FRONT STEELBODY								AVAILABLE	
193	DNQ91826	00779	4730995332961 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	15 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
194	DNQ90580	00779	4730995332961 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	4 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
195	DNQ91827	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	16 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
196	DNQ92780	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
197	DNQ91883	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	10 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
198	DNM90907	70HF120	5961755067776 / DIODE 70HF120 (BLACK LEAD) (9602 ITALY	DORMAN D/G 500KVA	3 / EACH/NUMBER					.	TECHNICAL SPECIFICATION - MAKE: ITALYGENERAL SPECIFICATION - MAKE: ITALY	
199	DPK93227	MIL-G-21164	9150002234004 / GREASE MOLYBDENUM D (G-353)	25mm KBA B06 Automatic cannon	11 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
200	DPC91900	NO DATA AVAILABLE	0474500000062 / POWDER CHALK, COMP		25 / KILOGRAMME	NO DATA AVAILABLE				.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CALCIUM CARBONATE 98% PURITY								AVAILABLE	
201	DPC92050	NO DATA AVAILABLE	0474500000062 / POWDER CHALK, COMP CALCIUM CARBONATE 98% PURITY		25 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
202	DPC89917	RESIN 60 TO 70% (DRIER 01.5)	8010705061107 / PAINT WEATHER WORK FINISHING DLT LTR NS/G/1303/CDT 270199		200 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
203	DPC92163	NO DATA AVAILABLE	8010705112537 / SOLIGNUM WOOD LACQUER	FOR WOOD WORK	10 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
204	DPC91898	D5015/MIL-PRF-81309E	8030009381947 / CORROSION PREVENTIVE COMPOUND OF 16 OUNCE CAN MIL-C-81309	PHALANX	12 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
205	DPC91152	CITRIKLEEN ECO	6850997009698 / CLEANING COMPOUND SOLVENT DEGREASING AND CLEANING AGENT	DOME EXTERNAL	15 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
206	DPC90406	M101021	91350K5085413 / ALCOHOL FOR CLEANING	C-3 SYSTEM	5 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
207	DPC93218	M101021	91350K5085413 / ALCOHOL FOR CLEANING	C-3 SYSTEM	9 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
208	DPK92182	ROYCO756	9150002234134 / HYDRAULIC FLUID PETROEUM BASE (ROYCO 756)	C I W S	5 / QUART					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
209	DPK89443	ROYCO756	9150002234134 / HYDRAULIC FLUID PETROEUM BASE (ROYCO 756)	C I W S	10 / QUART					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
210	DPK91221	ROYCO756	9150002234134 / HYDRAULIC FLUID PETROEUM BASE (ROYCO 756)	C I W S	15 / QUART					.	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
211	DPK93233	MIL-L-2105/80W90 or J2360-3-80W90W	9150010355393 / LUBRICATING OIL GEAR (01 CAN = 20 LITERS) brand (Shell or Mobil)	IT SELF	100 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
212	DPC93367		6840705055633 / INSECTICIDE DELTAMETHRIN-EC-15	FOR INSECT KILLING	200 / LITER						TECHNICAL SPECIFICATION - 01 ltr plastic packing with registerd lable composition: 100ml of k-15 ec othrine containing 1.5g (1.7%, 15G/LTR) DELTAMETHRINE AND CO-FORMULAS TO 100ML FORMULATION EMULSHION CONCENTRATE(EC) 01 LTR LIQUID PACKING WITH REGISTERED LABELGENERAL SPECIFICATION - 01 ltr plastic packing with registerd lable composition: 100ml of k-15 ec othrine containing 1.5g (1.7%, 15G/LTR) DELTAMETHRINE AND CO-FORMULAS TO 100ML FORMULATION EMULSHION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											CONCENTRATE(EC) 01 LTR LIQUID PACKING WITH REGISTERED LABEL	
213	DPK89362	CALIBRATION OIL GRADE C CASTROL	9160795049554 / CALIBRATION OIL GRADE 'C' USED IN DIESEL ENGINE FUEL PUMP (Packing = 200 Liters Drum)	FOR ZULFIQAR SHAMSHER	210 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
214	DPK91645	TYPE DEXRON II	9150705052442 / TORQUE CONVERTOR OIL		210 / LITER						TECHNICAL SPECIFICATION - SIZE: (01 LTR,04 LTRS,20 LTRS, 208 LTR PACKING)GENERAL SPECIFICATION - SIZE: (01 LTR,04 LTRS,20 LTRS,208 LTR PACKING)	
215	DPK90354	GADUS S2 V220 2	9150705091174 / GADUS S2 V220 2 (OLD NAME ALVANIA EP 2) OEM = MS SHELL (PACKING 18 KG)		18 / KILOGRAMME						TECHNICAL SPECIFICATION - KINEMATIC VISCOSITY (ASTMD445)@GENERAL SPECIFICATION - KINEMATIC VISCOSITY(ASTMD445)@	
216	DPC90352	829382	6810006826867 / DISTILLED WATER REAGENT (04 ITR OR 01 gALLON pACKING)	PHALANX	25 / GALLON						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
217	DPC93214	ARCOBURAG-P21	6810705080418 / SCALE REMOVER packing 25 ltr	A/C PLANT CHILLER CONDENSER HEAT EXCHANG	200 / LITER						TECHNICAL SPECIFICATION - DETAILED SPECIFICATION / TECHNICAL DATA: greenish blue granular powder; converts to gold when solution is made. colour variations of ARCOburag-p21 has no effect on performance odour: irritating. solubility in water: 10% at 75 degree f b. Brands: ARCOCHEMICALS c. OEM: M/S Arcochemicals Suite 103 Fortune	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Centre, 45A Block 6 P.E.C.H.S Sharah-e Faisal Karachi- 75400. Ph : 3438992623-25 GENERAL SPECIFICATION - DETAILED SPECIFICATION / TECHNICAL DATA: greenish blue granular powder; converts to gold when solution is made. colour variations of ARCOburag-p21 has no effect on performance odour: irritating. solubility in water: 10% at 75 degree f b. Brands: ARCOCHEMICALS c. OEM: M/S Arcochemicals Suite 103 Fortune Centre, 45A Block 6 P.E.C. H.S Sharah-e Faisal Karachi- 75400. Ph : 3438992623-25	
218	DPC89845	205-6611 (05 Ltr) / 205-6612 (20 Ltr)	6810705084532 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (05 Liter Can)	CP AIR COMP	100 / LITER						TECHNICAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTRGENERAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTR	
219	DPC93220	NO DATA AVAILABLE	6810731000999 / CRYSTIC 406E NON ACCELERATED VERSION LOW EXOTHERM MARINE GRADE POLYESTER RESIN OR EQUIVALENT LLOYDS APPROVED PRODUCT	FOR GRP BOAT	450 / KILOGRAMME						TECHNICAL SPECIFICATION - General purpose unsaturated, polyester resin un promoted thixotropic, laminating type orthophatalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lioyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 "C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time,30oC with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max)GENERAL SPECIFICATION - General purpose unsaturated, polyester resin un promoted thixotropic, laminating type orthophatalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lioyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 "C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time,30oC with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max)	
220	DPC91534	NO DATA AVAILABLE	6810731000999 / CRYSTIC 406E NON ACCELERATED VERSION	FOR GRP BOAT	225 / KILOGRAMME						TECHNICAL SPECIFICATION - General purpose unsaturated, polyester resin un promoted thixotropic, laminating type orthophatalic, suitable for hand and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LOW EXOTHERM MARINE GRADE POLYESTER RESIN OR EQUIVALENT LLOYDS APPROVED PRODUCT								spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lioyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 "C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time,30oC with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max)GENERAL SPECIFICATION - General purpose unsaturated, polyester resin un promoted thixotropic, laminating type orthophatalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lioyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 "C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilit y	Tender Remarks	TECH / GEN SPECS	Dimension
											175 (Min) k. Typical gel time,30oC with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max)	
221	DPC93221		6810731001001 / CRYTIC GELCOAT 65 E (BRUSH) NON-ACCELERATED UNSATURATED OR EQUIVALANT LLOYDS APPROVED PRODUCT	USE BY BOAT SHOP FOR ANTICORROSION	225 / KILOGRAMME						TECHNICAL SPECIFICATION - Gel coat polyester resin unsaturated unprompted thixotropic suitable for hand and spray lay up in tropical conditions Material should be preferable of USA West Europe, Japan make. Material should have valid Type Approval certificate of Lioyds's Register. EPOVIATH-350T OR EQUIVALANT LIOYDS APPROVEDPRODUCT The material specifications are given below: a. Governing Reference/ Specifications NES -167 b. Viscosity, 20 "C Poise 30-35 - c. Appearance - pale - d. Tensile strength (unfilled resin) MPa 60 (Min) e. Flexural strength (unfilled resin) MPa 110 (Min) f. Typical gel time,30oC with accelerator & MEKP Minutes 25 (Min) g. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) h. Stability in dark at 25oC without initiator Months 6-8 - J. Water absorption (24 hours) mg 30 (Max) GENERAL SPECIFICATION - Gel coat polyester resin unsaturated unprompted thixotropic suitable for hand and spray lay up in tropical conditions Material should be preferable of USA West Europe, Japan make. Material should have valid Type Approval certificate of Lioyds's Register. EPOVIATH-350T OR EQUIVALANT LIOYDS APPROVEDPRODUCT The material specifications are given below: a. Governing Reference/ Specifications NES -167 b. Viscosity, 20 "C Poise	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											30-35 - c. Appearance - pale - d. Tensile strength (unfilled resin) MPa 60 (Min) e. Flexural strength (unfilled resin) MPa 110 (Min) f. Typical gel time,30oC with accelerator & MEKP Minutes 25 (Min) g. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) h. Stability in dark at 25oC without initiator Months 6-8 - J. Water absorption (24 hours) mg 30 (Max)	
222	DPC91542	ASTM E1119	6810000064205 / ETHYLENE GLYCOL TECHNICAL (Brand K-Chemicals, Inc.)	PHALANX	10 / GALLON						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
223	DPC90218	A A895	6810002708177 / SODIUM HYDRO OXIDE TECHNICL		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
224	DNM91668	SP-45-6N/SW1P1 PART NO /MC 40/50	6105705054382 / SUBMERSIBLE PUMP 380V 18.8A-7.5KW HP 10 3PH	DISTILL WATER PLANT (FRANCE)	1 / EACH/NUMBER	MC 40/50 (MAKE LOCAL)					TECHNICAL SPECIFICATION - FAZAL SONS PLOT NO SR 3/26, SHOP N. 26, OPP: CHAMBER OF COMMERCE, SHARAH-E-LIAQUAT, KJARACHI TEL: 32428613-32428614 FAX: (9221) 32428629 E-MAIL: fazalsons@fountainpk.comGENERAL SPECIFICATION - FAZAL SONS PLOT NO SR 3/26, SHOP N. 26, OPP: CHAMBER OF COMMERCE, SHARAH-E-LIAQUAT, KJARACHI TEL: 32428613-32428614 FAX: (9221) 32428629 E-MAIL: fazalsons@fountainpk.com	
225	DNM89346	CPMU-18	4920705126467 / AIR INTAKE FILTER	AIR COND SYS CWM-2C70-PN	57 / EACH/NUMBER	CWM-2C70-PN					TECHNICAL SPECIFICATION - M/S COOL POINT ADDA PLOT SHARIZ JATTI UMRAH ROAD LAHORE TEL: 9242 35322612-7GENERAL SPECIFICATION - M/S COOL POINT ADDA PLOT SHARIZ JATTI UMRAH ROAD LAHORE TEL: 9242 35322612-7	
226	DNM91022	3805782	6620735126507 / VALVE	COMPRESSOR D6SHI-350X	5 / EACH/N	D6SHI-350X					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PLATE ASSY	AWM/D	UMBER	AWM/D BELGIUM					SPECIFICATION - NO DATA AVAILABLE	
227	DPK91388	AN002-200	685014340765 3 / REALAY&CONT CLEANER100 % TIRCHLOROETHANE (KF SITOSEC FPS) 200ML Packing OEM = CRC Industires France		12 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
228	DPK90409	TK6850-057 00082	685012311736 2 / CHEMICAL 'B'		5 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
229	DPK90387	RH0D0RSILPATES428	915014278959 0 / SILICON GREASE (PKG OF 100 GRAMS TUBE) PASTE 70 428 OEM = Bluestar Silicones	HP AIR SYSTEM ONBOARD AGOSTA 90B	10 / TUBE	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
230	DPK91389	RH0D0RSILPATES428	915014278959 0 / SILICON GREASE (PKG OF 100 GRAMS TUBE) PASTE 70 428 OEM = Bluestar Silicones	HP AIR SYSTEM ONBOARD AGOSTA 90B	4 / TUBE	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
231	DPK90290	STM7272CF1T25L	915014400665 2 / BETULA OIL S32 (25LTR PACKING) OIL AS REPLACE WITH CF-1 OIL NATO CODE 0-290	A) FC-AIR CONDITIONING PLANT (AGOSTA 70 ONLY) B) RM-OLEO PNEUMATIC MASTS. C) AG-BULK HEAD	325 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				OPERATING								
232	DPK91387	NT5610-0001STCM77KGCIMENTENSEAU	5610143435958 / CIMENT PROMPT (NO MORE PROCUREMENT TILL EXHAUSTION OF STOCK)		10 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
233	DPK91329	10250	5970143407636 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	22 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
234	DPK93225	10250	5970143407636 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	25 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
235	DPK91915	GB7324-1994 LB3	9150FP0020010 / LITHIUM BASE GREASE NO.3		13 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
236	DPK92260	GB7324-1994 LB3	9150FP0020010 / LITHIUM BASE GREASE NO.3		45 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
237	DPK93232	L-HM 46	9150FP0010210 / HYDRAULIC OIL L-HM 46 (200 LITERS PACKING) SINOPEC		200 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
238	DPK93231	L-HM 32	9150FP0010215 / L- HM32 OIL MARINE HYDRAULIC OIL (16 Liters Packing)		80 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
239	DNM89938	IACD42106 or CITEX H-1140	4240995275985 / SAFETY HARNESS (100%	PPE	5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - MATERIAL: 100% POLYSTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilit y	Tender Remarks	TECH / GEN SPECS	Dimension
			POLYSTER WITH BUCKLES & D-RING								APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH:>=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: Info@abdullahfireprotection. com.pk b. Last Procurement data through registered supplier M/S ASHI Enterprises in Sep 18. Spefication may be endorsed to avoid complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max impact force of 6 KN. GENERAL SPECIFICATION - MATERIAL: 100% POLYSTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH:>=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: Info@abdullahfireprotection. com.pk b. Last Procurement data through registered supplier M/S ASHI Enterprises in Sep 18. Spefication may be endorsed to avoid complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max impact force of 6 KN.	
240	DNM89982	IACD42106 or CITEX H-1140	4240995275985 / SAFETY HARNESS (100% POLYSTER WITH BUCKLES & D-RING	PPE	40 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - MATERIAL: 100% POLYSTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH:>=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: Info@abdullahfireprotection. com.pk b. Last Procurement data through registered supplier M/S ASHI Enterprises in Sep 18. Spefication may be endorsed to avoid complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max impact force of 6 KN. GENERAL SPECIFICATION - MATERIAL: 100% POLYSTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH:>=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: info@abdullahfireprotection.com.pk b. Last Procurement data through registered supplier M/S ASHI Enterprises in Sep 18. Spefication may be endorsed to avoid complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max impact force of 6 KN.	
241	DNM90986	DDR-2000	7320705332673 / dough divider &		1 / EACH/NUMBER	Latest					TECHNICAL SPECIFICATION - CAPACITY 1500-2500 DOUGH BALL PER HOUSR BASED AT 80-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			rounder								100 GMS MS ANGLE IRON STRUCTURE COVERED WITH STAINLESS STEEL SHEET MOTOR 1HP, 220V, 50HZ SENSOR OPERATING KNIFE PORTABLE ON WHEELSGENERAL SPECIFICATION - CAPACITY 1500-2500 DOUGH BALL PER HOUSR BASED AT 80-100 GMS MS ANGLE IRON STRUCTURE COVERED WITH STAINLESS STEEL SHEET MOTOR 1HP, 220V, 50HZ SENSOR OPERATING KNIFE PORTABLE ON WHEELS	
242	DPK73669	050005	9150124224520 / KLUBER SUMMIT SH46 Synthetic air compressor oil		1 / LITER	Drive Motor assembly					TECHNICAL SPECIFICATION - Klüber Summit SH oils are air compressor oils based on synthetic hydrocarbon and additives. They can be mixed with mineral oils and synthetic hydrocarbon oils, however are not miscible with polyglycol oils. GENERAL SPECIFICATION - Klüber Summit SH oils are air compressor oils based on synthetic hydrocarbon and additives. They can be mixed with mineral oils and synthetic hydrocarbon oils, however are not miscible with polyglycol oils.	
243	DPK89419	RL 32-3MAF	9150998417753 / Lubricating Oil, Refrigerant Compressor		40 / LITER	ECO SNM 32-125					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
244	DPC91929	code s 205	6850725279744 / ALCA SOLUTION (LUB OIL TEST KIT) PACKING 500 ML		4 / BOTTLE	CODE S 205					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
245	DPK92745	SHELL OMALA S4 GX 220	9150705312134 / advanced synthetic industerial gear oil		8 / LITER	HIZIR TCMS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
246	DPK92743	SHELL GADUS S3 A1000XD 2	9150715312357 / PREMIUM GREASES WITH EXTRA SOLIDS		6 / KILOGRAMME	NA					TECHNICAL SPECIFICATION - SHELL GADUS S3 A1000XD 2 IS A HEAVY DUTY CALCIUM GREASE FORMULATED WITH A HIGH LEVEL OF SOLID ADDITIVES FOR ENHANCED LOAD CARRYING CAPABILITY. THE HIGH SOLIDS CONTENT AND HEAVY BASE OIL UTILIZED IN THIS PRODUCT ARE DESIGNED TO PROVIDE AN EFFECTIVE LUBRICANT FILM UNDER THE HIGH LOADS AND CONSTANT SLIDING CONTACT. A lubricating grease containing highly-refined mineral oils and additives. The highly refined mineral oil contains 3% (w/w) DMSO extract, according to IP346.GENERAL SPECIFICATION - SHELL GADUS S3 A1000XD 2 IS A HEAVY DUTY CALCIUM GREASE FORMULATED WITH A HIGH LEVEL OF SOLID ADDITIVES FOR ENHANCED LOAD CARRYING CAPABILITY. THE HIGH SOLIDS CONTENT AND HEAVY BASE OIL UTILIZED IN THIS PRODUCT ARE DESIGNED TO PROVIDE AN EFFECTIVE LUBRICANT FILM UNDER THE HIGH LOADS AND CONSTANT SLIDING CONTACT. A lubricating grease containing highly-refined mineral oils and additives. The highly refined mineral oil contains 3% (w/w) DMSO extract, according to IP346.	
247	DPC77035	A020EEV2	8010705332825 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		600 / LITER	HIGHLY PERFUMED					TECHNICAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilit y	Tender Remarks	TECH / GEN SPECS	Dimension
											COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation. GENERAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.	
248	DNQ905 94	30-2062	422078528943 3 / FLARE SET (06 RED HAND FLARE MK8+04 PARA RED ROCKET MK8A +02 LIFE SMOKE MK9) FOR SURVIVAL PACK OF 25 X MEN LIFE RAFT		7 / PACKE T	life raft				.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
249	DNQ92648	30-2062	4220785289433 / FLARE SET (06 RED HAND FLARE MK8+04 PARA RED ROCKET MK8A +02 LIFE SMOKE MK9) FOR SURVIVAL PACK OF 25 X MEN LIFE RAFT		2 / PACKET	life raft					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
250	DPK93369	s4 p 100	9150705270734 / compressor oil shell corena s4 p 100		20 / LITER	s4 p 100					TECHNICAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURESGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES	
251	DPC91540	ARCANOL MULTITOP / ARCANOL L135V	9150124044878 / ARCANOL MULTITOP/ ARCANOL L135V ROLLING BEARING GREASE		3 / KILOGRAMME	76 mm gun					TECHNICAL SPECIFICATION - Universal application, moderate to high load, low starting temperatures, wide temperature range, very wide speed range, improved relubricatability, in special cases also for spherical roller thrust bearingsGENERAL SPECIFICATION - Universal application, moderate to high load, low starting temperatures, wide temperature range, very wide speed range, improved relubricatability, in	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											special cases also for spherical roller thrust bearings	
252	DPC91541	ASTM D1193	6810003564936 / Distilled-deionized water		40 / LITER	N/A				.	TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A	
253	DPC91926	code s154	6850725279747 / SALTESMO (LUB OIL TEST KIT AGENT) PACKING 100 PIECES		4 / BOTTLE	CODE S154				.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
254	DPC89996	INTERTHERM 50 ALUMINIUM	8010999690549 / PAINT, HEAT RESISTING		20 / LITER	INTERTHERM50 ALUMINIUM					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
255	DNM89589	2898288	5340705237592 / zinc anode 25		2 / EACH/NUMBER	CLASSIC V				.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
256	DPC93222	008154Z03885	9350775274168 / REFRACTORY MORTAR READY MIX		225 / KILOGRAMME	FIBERSTICK 1600					TECHNICAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 cGENERAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 c	
257	DNQ90503	zxs9984-401-07sm	8120785344719 / co2 bottle 45 kgs		4 / BOTTLE	ZXS9984-401-07SM				.	TECHNICAL SPECIFICATION - CO2 BOTTLE 45 KGS height 5 feets radius 2.10 feets pressure 250GENERAL SPECIFICATION - CO2 BOTTLE 45 KGS height 5 feets radius 2.10 feets pressure 250	
258	DPK90430	nyvac fr 200d	9150755270805 / mobil nyvac FR 200D		5 / LITER	NYVAC FR 200D				.	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
259	DRG88762	SINIG	2925ZO5238488 / SINGLE IGNITION		4 / EACH/NUMBER	GREAT POWER				.	TECHNICAL SPECIFICATION - SINGLE IGNITION GENERAL SPECIFICATION - SINGLE IGNITION	
260	DRG85357	315/70 R 15 TL (300 R 15)	2610124002724 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL				.	TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
261	DSB92944	4011890052334	5130725155229 / FLAP GRINDING DISK (SIZE 125 X 22.23 MM)		5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Size: 125 X 22.23MM 3 YEARS FROM DATE OF MANUFACTURE oem/made: RHODIUS GERMANY Acceptance Criteria: Concerned rep will inspect and practically test in workshop. GENERAL SPECIFICATION - Size: 125 X 22.23 MM 3 YEARS FROM DATE OF MANUFACTURE oem/made: RHODIUS GERMANY Acceptance Criteria: Concerned rep will inspect and practically test in workshop.	
262	SRV41893	ELITE-2/3A1500	6160ZO5207534 / SEALED RECHARGEABLE NI-MH CELL		90 / EACH/NUMBER	0					TECHNICAL SPECIFICATION - SIZE 2/3A,VOLT1.2, CAPACITY 1500 MAH, TYPE SEALED RECHARGABLE NI-MH. GENERAL SPECIFICATION - SIZE 2/3A, VOLT1.2, CAPACITY 1500 MAH, TYPE SEALED RECHARGABLE NI-MH.	
263	DSM80759	82.JL10	5120142761964 / ALLEN KEY KIT		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
264	DRG86554	UP-RW1220P1	6140ZO5229752 / UPS BATTERY FOR MOOG CABINET		2 / EACH/NUMBER	MOOG					TECHNICAL SPECIFICATION - AS MENTIONED IN LETTER OF EU: PN/NATS/MAINTENANCE/3289115 DT 01 JULY 2025 GENERAL SPECIFICATION - AS MENTIONED IN LETTER OF EU: PN/NATS/MAINTENANCE/3289115 DT 01 JULY 2025	
265	DSB92003	MAT 424-0463	5331745233263 / Seal for Regulation Tank		8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Make/ Model (Local Source): Amir Enterprises (Ph # 0321-2030898 & 0333-3860521) SPECIFICATION: THE RUBBER SEAL USED IN REGULATING TANK COVERS. CHEMICAL COMPOSITION REPORT IS ATTACHED. STOCK SAMPLE: SAMPLE AVAILABLE (IF REQUIRED) Material: Polychloroprene Pressure Tested: Upto 100bar Dimension As per	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											drawing (enclosed) Acceptance Criteria Physically inspection of rubber quality/ hardness by concerned rep. GENERAL SPECIFICATION - Make/ Model (Local Source): Amir Enterprises (Ph # 0321-2030898 & 0333-3860521) SPECIFICATION: THE RUBBER SEAL USED IN REGULATING TANK COVERS. CHEMICAL COMPOSITION REPORT IS ATTACHED. STOCK SAMPLE: SAMPLE AVAILABLE (IF REQUIRED) Material: Polychloroprene Pressure Tested: Upto 100bar Dimension As per drawing (enclosed) Acceptance Criteria Physically inspection of rubber quality/ hardness by concerned rep.	
266	DSB90915	LOCAL TR230S-SEW	5330705268870 / Teflon, S/Steel & O-Ring		50 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - D1: 42,5 MM D2: 22,5MM C: 4 MM hydraulic piping sealing ring de-30 hp. SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG)GENERAL SPECIFICATION - D1: 42,5 MM D2: 22,5MM C: 4 MM hydraulic piping sealing ring de-30 hp. SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG)	
267	DRG88966	ZO6570838	4710ZO6570838 / PVC PIPE DIA 1"		5000 / FOOT	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - PVC(HARD PLASTIC) WITH JOINTS,AVAILABLE IN 2O FEETLENGHTH,ONE JOINT REQD FOR EACH 2 PIECES,FOR 4 PIECES 3 JOINTS REQD a. PVC PIPE DIA 1", b. MATERIAL HARD, ALONGWITH JOINT (SOCKET), c. PIPE LENTH 20 FEET, c. BRAND PAK ARAB OR STEELEX, d. CLOUR WHITE OR GREY. GENERAL SPECIFICATION - PVC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(HARD PLASTIC) WITH JOINTS, AVAILABLE IN 2O FEETLENGHTH, ONE JOINT REQD FOR EACH 2 PIECES,FOR 4 PIECES 3 JOINTS REQD a. PVC PIPE DIA 1", b. MATERIAL HARD, ALONGWITH JOINT (SOCKET), c. PIPE LENTH 20 FEET, c. BRAND PAK ARAB OR STEELEX, d. CLOUR WHITE OR GREY.	
268	DSB92947	RS-480 / RS-2	5130144018461 / GRINDING DISC 7 INCH		12 / EACH/NUMBER	RS2					TECHNICAL SPECIFICATION - Dimensions: 180x7,0x22, 23GENERAL SPECIFICATION - Dimensions: 180x7,0x22,23	
269	DSB93043	RS-480 / RS-2	5130144018461 / GRINDING DISC 7 INCH		3 / EACH/NUMBER	RS2					TECHNICAL SPECIFICATION - Dimensions: 180x7,0x22, 23GENERAL SPECIFICATION - Dimensions: 180x7,0x22,23	
270	DRG86171	315/70 R 15 TL (300 R 15)	2610124002724 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL				.	TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
271	DRG85374	315/70 R 15 TL (300 R 15)	2610124002724 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL				.	TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
272	DRG86337	315/70 R 15 TL (300 R 15)	2610124002724 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL				.	TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
273	DSB90909	LOCAL TR250S-SEW	5330705268088 / TEFLON, BRASS & O-RING		15 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - D1: 53 MM D2: 25 MM C: 3 MM OEM: Star engineering works ITEM IS USED IN HP AIR SYSTEM (WITH 250 BAR PRESSURE) AND COMPLETE ITEM IS COMBINATION OF 03 PARTS: METALLIC RING, RUBBERIZED O-RING & TEFLON RING.GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilit y	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - D1: 53 MM D2: 25 MM C: 3 MM OEM: Star engineering works ITEM IS USED IN HP AIR SYSTEM (WITH 250 BAR PRESSURE) AND COMPLETE ITEM IS COMBINATION OF 03 PARTS: METALLIC RING, RUBBERIZED O-RING & TEFLON RING.	