

PAKISTAN NAVY

TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 29-12-2025

TERMS & CONDITION

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT".
2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.
3. LAB TESTING CHARGES IF ANY WILL BE BORN BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF94111	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	0562795620006 / BATTERY LEAD ACID 12V 200AH	DG USED	8 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					<u>TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u> <u>GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u>	
2	DNJ94113	17400-98J01-000 & 17400-98J05-000	5180765222548 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI	JAPAN	<u>TECHNICAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416-93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER</u> <u>GENERAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416-93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER</u>	
3	DNF94107	06070301	2590999100334 / HORN ELECTRICAL 24V AC/DC 3AMP C/W BRACKET (SOGO CHINA		3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - OEM, M/S SOGO GROUP COMPNIES CHINA. WWW. SOGOLIGHTINGWORLD. COM</u> <u>GENERAL SPECIFICATION - OEM, M/S SOGO GROUP COMPNIES CHINA. WWW.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			BRAND)								SOGOLIGHTINGWORLD.COM	
4	DNF94049	PAK / GFC/MILL AT/ EQUIVALE N	0565700000048 / FAN PADESTAL-230VAC-24INCH 50CYCLES (PAK FAN)	END USE SELF	10 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
5	DNF93987	PAK / GFC/MILL AT/ EQUIVALE N	05657000000048 / FAN PADESTAL-230VAC-24INCH 50CYCLES (PAK FAN)	END USE SELF	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
6	DNF94027	Winner pro1K	6150TA5249659 / UPS 1KVA		10 / EACH/N UMBER	Winner pro1K					TECHNICAL SPECIFICATION - Complete Details regarding 2KVA & 1KVA UPS are available in the attached Brochure named "WinnerPro" GENERAL SPECIFICATION - Complete Details regarding 2KVA & 1KVA UPS are available in the attached Brochure named "WinnerPro"	
7	DNF94054	S5750E-28F-SI-D	6650735293090 / 28 Ports Layer 3 All OptIcal Switch with Uplink 10Gx04 Ports		1 / EACH/N UMBER	S5750E-28F-SI-D					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
8	DNF94038	J9776A / J9772A+j4 859c	5895785207833 / NETWORK SWITCH HP 2530 24G/48G WITH 2/4 SFP MODULES	NETWORK SWITCH J9772A CHINA	2 / EACH/N UMBER	RG-NBS5200-48GT4xS/ R8N88A-HP/J9776A/J9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA		TECHNICAL SPECIFICATION - ATTACHED GENERAL SPECIFICATION - ATTACHED	
9	DNF90260	APC BRAND SMC2000I / GX9-2000	6130785166752 / UPS 2KVA 2H O/P 220V 2000VA	PSS (CCTV SYS)	1 / EACH/N UMBER	APC BRAND/G X9-2000		M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC Internatio nal CO., LTD		TECHNICAL SPECIFICATION - OEM & SOA:M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China . GENERAL SPECIFICATION - OEM & SOA:M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China .	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
10	DNF91445	DGS-3000-28XS	593070524633 2 / MANAGED L2 GIGABIT SWITCHES		1 / EACH/NUMBER	DGS-3000-28XS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
11	DNF76594	AS(U) M332M500 DF1	591075531634 5 / CAPACITOR 3300 uf 500V DC AYX-HR (M)		9 / EACH/NUMBER	AYX-HR (M)					TECHNICAL SPECIFICATION - Capacitor 3300MF 500V BATTERY CHARGING SYSTEM INDICATION MONITORING SYSTEM ANTI CONDENSATION HEATER AUDIBLE ALARM SYSTEM LIGHT INDICATOR FOR POWER ON/OFF SEPARATE CONTROL AND BATTERY BANK CABINET WITH WHEEL MOUNTING FOR EASE OF MOVEMENT. GENERAL SPECIFICATION - Capacitor 3300MF 500V BATTERY CHARGING SYSTEM INDICATION MONITORING SYSTEM ANTI CONDENSATION HEATER AUDIBLE ALARM SYSTEM LIGHT INDICATOR FOR POWER ON/OFF SEPARATE CONTROL AND BATTERY BANK CABINET WITH WHEEL MOUNTING FOR EASE OF MOVEMENT.	
12	DNC90823	WBCL002 320/cn-btu-60000	413074513315 3 / CHILLER 60000 BTU	A/C SYSTEM PNS KARRAR	1 / EACH/NUMBER	NO DATA AVAILABLE		FR		WEBAST O MARINE COMFORT FRANCE	TECHNICAL SPECIFICATION - CHILLER 60000 BTU GENERAL SPECIFICATION - CHILLER 60000 BTU	
13	DNF92678	38109-829 rev D/ GS-55	591073512072 1 / pro Dynamic CARDIOD VOCAL MICROPHONE Electro-voice	PA SYSTEM	2 / EACH/NUMBER	ELECTRO VOICE					TECHNICAL SPECIFICATION - OEM, ELECTRO-VOICE USA. TECH-SPECS, Wired handheld microphones. DYNAMIC N/DYM MAGNET 45HZ-15000 HZ CARDIOD Non reflecting black finish. On/Off switch. 3-pin XLR connector. Weight 238gm GENERAL SPECIFICATION - OEM, ELECTRO-VOICE USA. TECH-SPECS, Wired handheld microphones. DYNAMIC N/DYM MAGNET 45HZ-15000 HZ CARDIOD Non reflecting black finish. On/Off	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											switch. 3-pin XLR connector. Weight 238gm	
14	DNF94219	12C48	6140995132645 / BATTERY SEC/RECHARGEABLE12V 48/55AH M/FREE SZ 27.2X16.4X20CM	RICE COMM SYSTEM	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
15	DNF91165	6X120 EXIDE/ 6X15/ exide n-140 plus	6140705023607 / BATTERY SECONDARY 105AH 12V SZ 367X173X228 MM EXIDE		2 / EACH/NUMBER	6X120EXIDE/ EXIDE N-140 PLUS local					TECHNICAL SPECIFICATION - 12 V, Volt 12 V DC Amp 105 AH OEM Exide/ AGS GENERAL SPECIFICATION - 12 V, Volt 12 V DC Amp 105 AH OEM Exide/ AGS	
16	DNF94097	CW-770	5995715118130 / POWER CABLE 3 CORE FOR CCTV SYSTEM		60 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
17	DNF94112	PP3 , 6F22, (6135-00-900-2139)	6135701004118 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25.75X017MM	AVO METER	60 / EACH/NUMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
18	DNF94176	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	0562795620006 / BATTERY LEAD ACID 12V 200AH	DG USED	2 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
19	DNF94098	CMS-118	5998705219304 / POWER EXTENSION BOARD CAMELLION MODEL CMS-118	SM RACK	8 / EACH/NUMBER	CMS-118 (CAMELLION)	NA	Commercially Of The Shelf (COTS)/Local Market	COTS		TECHNICAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan GENERAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
20	DNF94102	TL-SG1024	7025290001813 / NETWORK SWITCH TP LINK (PROCESSOR, GATEWAY)	SCADA	1 / SET	TL-SG1024	NOT KNOWN	145 SOUTH STATE COLLEGE BLVD SOUT 400, BREA CA 92821 TP LINK RESEARCH AMERICA CROPORATION.	USA		TECHNICAL SPECIFICATION - 100 V TO 220 V AC MAX POWER 13.6 WM, OPERATING TEMPERATURE 0 TO 40 C, STORAGE TEMP. 40 TO 70 C. MAC ADDRESS TABLE 8K SWITCHING CAPABILITY 48 GBPS. ACKED FORWARDING RATE 35.7 MBPS GENERAL SPECIFICATION - 100 V TO 220 V AC MAX POWER 13.6 WM, OPERATING TEMPERATURE 0 TO 40 C, STORAGE TEMP. 40 TO 70 C. MAC ADDRESS TABLE 8K SWITCHING CAPABILITY 48 GBPS. ACKED FORWARDING RATE 35.7 MBPS	
21	DNF94100		6070705229821 / 24 JOINT BOX	PSS SYSTEM	5 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		TECHNICAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type GENERAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
22	DNF94101	DHI-NVR 4216-16P-4KS3/ DHI-NVR4216-16P-4KS2/I	6760785207846 / 16 CHANNEL PRO NETWORK VIDEO RECORDER	CCTV System NVR5216-4KS2 CHINA	2 / EACH/NUMBER	DHI-NVR4216-16P-4KS2/L/D HI-NVR4216-16P-4KS2	NA	NO.1199 bin'an road , binjiang district hangzhou , china, 310053 tel: +86-571-87688883	MS NETWORK		TECHNICAL SPECIFICATION - Main Processor Quad-core embedded processor Operating System Embedded LINUX Display Interface 1 HDMI, 1 VGA Resolution 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 Multi-screen Display 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording GENERAL SPECIFICATION - Main Processor Quad-core embedded processor Operating System Embedded LINUX Display Interface 1 HDMI, 1 VGA Resolution 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 Multi-screen Display 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
23	DNF94323	3549.8550.00	5995725138624 / DATA CABLE SCREENED 8	XK-2900L 1KW TX BERQV	60 / METER	NO DATA AVAILABLE		GR	GERMAN YROHDE & SCHWAR		TECHNICAL SPECIFICATION - . GENERAL SPECIFICATION - .	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
CORE									Z			
24	DNF94292	S4600-28P-SI /J9776A	7025145837789 / SWITCH UNIT 24 PORT WITH 4SFP & Accessories	Local Area Network (LAN) (Intranet)	1 / EACH/NUMBER	S4600-28P-SI /CSS326-24G-2SRM	0	1 AV DU CANADA LES ULIS LES ULIS	HEWLETT-PACKARD CENTRE COMPETENCE FRANCE		TECHNICAL SPECIFICATION - DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFP GENERAL SPECIFICATION - DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFP	
25	DNF94223	J9776A / J9772A+j4859c	5895785207833 / NETWORK SWITCH HP 2530 24G/48G WITH 2/4 SFP MODULES	NETWORK SWITCH J9772A CHINA	1 / EACH/NUMBER	RG-NBS5200-48GT4xS/R8N88A-HP/J9776A/J9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA		TECHNICAL SPECIFICATION - ATTACHED GENERAL SPECIFICATION - ATTACHED	
26	DNF94099	ML-1102S-A & B(2 RJ-45 PORTS)/ 4V1D	6030705215937 / FIBER OPTIC MEDIA CONVERTER FOR IP CAMERAS	CCTV SYSTEM 4V1D PAKISTAN	7 / PAIR	ml-1102s-a & ml-1102s-b		Al-Sa'ee business Solutions Suit 30, 3rd Floor, Crown Centre Plot SB-1, Opp Bait-ul-Mukarram Masjid, Gulshan-e-Iqbal Karachi Tel & Fax (9221)3483-7233	Al-Sa'ee/Pro Secure		TECHNICAL SPECIFICATION - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission. GENERAL SPECIFICATION - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission.	
27	DNF94096	MCTX-NTLNK	5915705248706 / ODF 8 PORTS		8 / EACH/NUMBER	MCTX-NTLNK					TECHNICAL SPECIFICATION - BRAND: NETLINK MODEL: MCTX-NTLNK GENERAL SPECIFICATION - BRAND: NETLINK MODEL: MCTX-NTLNK	
28	DNS94173	21707132/ 477556-5	4330331080376 / OIL FILTER	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	1 / EACH/NUMBER	NO DATA AVAILABLE		FR	SIEMEN PAKISTAN ENGINEERING CO LTD AUTOMATION&DRIVE DIVISION BU SMALL&L		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									ARGE B-72ESTAT E AVNEUE SITE PO BOX 7158PH# 92(021) 2574910-19 KARACHI 75700			
29	DNF94290	NIL	4920705141287 / NETWORK CABLE TESTER WITH TOOL	BASIC ELECTRONIC WARFARE TRAIN	2 / EACH/NUMBER	NO DATA AVAILAB LE		PK	M/S DATA CUMMUN ICATION & CONTRO L(PVT) LTD.409 CLIFTON CENTER DC-1, BLOCK-5, KARACHI .75600.		<u>TECHNICAL SPECIFICATION -</u> OEM ADD/SOURCE OF AVAILABILITY:M/S DATA COMMUNICATION&CONTROL (PVT)LTD.409 CLIFTON CENTER DC-1,BLOCK-5,KARACHI. <u>GENERAL SPECIFICATION -</u> OEM ADD/SOURCE OF AVAILABILITY:M/S DATA COMMUNICATION&CONTROL (PVT)LTD.409 CLIFTON CENTER DC-1,BLOCK-5,KARACHI.75600	
30	DNF94175	ub500 / ZA3000E	6350785246359 / WALK THROUGH GATE WITH MONITOR & FACE CAPTURE CAMERA		1 / EACH/NUMBER	ub500 /ZA3000E					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
31	DNF94103	DCN S4600-28P-SI /J9776A/r8n88a	7035715248832 / HP ARUBA 2530 24G network switch		1 / EACH/NUMBER	ARUBA 2530 24G (J9776A)					<u>TECHNICAL SPECIFICATION - HP</u> ARUBA 24 PORT NETWORK SWITCH <u>GENERAL SPECIFICATION - HP</u> ARUBA 24 PORT NETWORK SWITCH	
32	DNF94110	WP7-12-LONG	5935705249028 / Dry Battery 12V 7AH		16 / EACH/NUMBER	China					<u>TECHNICAL SPECIFICATION -</u> M/FREE BATTERY 12V 7AH FOR UPS OEM, kung long battries industrial co., ltd. <u>GENERAL SPECIFICATION - M/FREE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BATTERY 12V 7AH FOR UPS OEM, kung long batteries industrial co., ltd.	
33	DNF94029	toten 6u	593070524631 1 / networking switch rack toten 6u 600 x 600 single section 1 fixed tray, 2 fan.		10 / UNIT	TOTEN 6U					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
34	DNF94109	51289	599970528442 8 / VACUUM CLEANER WET AND DRY MOD 4200L		1 / EACH/NUMBER	42I					TECHNICAL SPECIFICATION - 2 stable castor wheels 2 rubber rear wheels built in detergent tank detergent socket tough, sturdy plastic tank two stage motor plastic body flow rate of 0.8l/min at a pressure of 2 bar GENERAL SPECIFICATION - 2 stable castor wheels 2 rubber rear wheels built in detergent tank detergent socket tough, sturdy plastic tank two stage motor plastic body flow rate of 0.8l/min at a pressure of 2 bar	
35	DN093007	RK 50/65-SEW	281578528496 8 / REDUCER COUPLING (DN 50 TO DN 65 - 2 INCH TO 3 INCH) FOR FF HOSE		4 / EACH/NUMBER	RK 50/65-SEW					TECHNICAL SPECIFICATION - ALUMINIUM ALLOY COUPLING WITH RUBBER SEALS GENERAL SPECIFICATION - ALUMINIUM ALLOY COUPLING WITH RUBBER SEALS	
36	DNF93144	RTAC-01	702558000296 9 / DIGITIZER, DATA ENTRY	PORTAL CRANE M-4 TURKEY	2 / EACH/NUMBER	M-4	21338-100	Nisantepi Mh. Fabrikalar Sk. No:8 Alemdag Umraniye 34794 Istanbul TURKEY Phone: +90(216) 585 1818 Fax +90(216) 585 1819 Website: esitscale.com	ISTANBUL EURO CRANE (IEC) TURKEY		TECHNICAL SPECIFICATION - OUTPUT VOLTAGE 1: +24VDC OUTPUT VOLTAGE 2: +15VDC MAX POWER CONSUMPTION : 140mA(5v)+55mA(24v) GENERAL SPECIFICATION - OUTPUT VOLTAGE 1: +24VDC OUTPUT VOLTAGE 2: +15VDC MAX POWER CONSUMPTION : 140mA(5v)+55mA (24v)	
37	DNF94296	51289	599970528442 8 / VACUUM CLEANER WET AND DRY MOD 4200L		1 / EACH/NUMBER	42I					TECHNICAL SPECIFICATION - 2 stable castor wheels 2 rubber rear wheels built in detergent tank detergent socket tough, sturdy plastic tank two stage motor plastic body flow rate of 0.8l/min at a pressure of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2 barGENERAL SPECIFICATION - 2 stable castor wheels 2 rubber rear wheels built in detergent tank detergent socket tough, sturdy plastic tank two stage motor plastic body flow rate of 0.8l/min at a pressure of 2 bar	
38	DNF92089	GY 6.35	624015218393 1 / MARINE ENGINE ROOM LIGHT	PORTAL CRANE FD-IV	1 / EACH/NUMBER	GY 6.35	N/A	M/S DRSA		M/S DRSA	TECHNICAL SPECIFICATION - METALIC CAGE LIGHT WITH GLASS RATED VOOLTAGE 220 V FREQUENCY 50/60 HZGENERAL SPECIFICATION - METALIC CAGE LIGHT WITH GLASS RATED VOOLTAGE 220 V FREQUENCY 50/60 HZ	
39	DNZ93271	98660/1153	533001415554 7 / WASHER	MAIN AIR COMPRESSOR	1 / EACH/NUMBER	NO DATA AVAILABLE		UK		COMPAIR UK LTD ENGLAND	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
40	DNF92364	10-145 /1679-0011-01 (LOCAL PAKISTAN)	6145RC508459 2 / RADIATOR WIRE FLEXIBLE MULTI STRANDS COPPER FOR ANTENA	SPIRACONE ANTENA MODEL 3002A 36S	600 / METER	RX 895 LOCAL PAKISTAN					TECHNICAL SPECIFICATION - a. Make: British Aero Space Australia Limited. b. Parent Equipment: Spiracon Antenna (HF DF System). C.ALTERNATE AS PER PART NO RX 895 LOCALLY AVAILABLE/ MANUFACTURED IN PAKISTAN. GENERAL SPECIFICATION - a. Make: British Aero Space Australia Limited. b. Parent Equipment: Spiracon Antenna (HF DF System). C.ALTERNATE AS PER PART NO RX 895 LOCALLY AVAILABLE/ MANUFACTURED IN PAKISTAN.	
41	DNF92651	380V/ 2500W LOCAL	7310PK507571 8 / COOKING PLATE 380V 2500W LG 11.5" W 11.5"	COOCKING SYS.	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DNF91449	A6301-02	614071521961 7 / 12- VOLT BATTERY (LI-ION)	ANALYZER 6320 PA/VA USA	50 / EACH/NUMBER	A6320/PA	1408630658	1832 MIDPARK ROAD, SUIT 102, KNOXVILLE, TN (USA)37921 TEL: 9546485528		M/s WINDROCK USA	TECHNICAL SPECIFICATION - 12VOLT BATTERY GENERAL SPECIFICATION - 12VOLT BATTERY	
43	DNF89024	FXTM2 32 / ONYX-32	599671514367 4 / MIXER PRE AMPLIFIER	PA SYSTEM	1 / EACH/NUMBER	FXTM2 32		US		M/S:KYAF CORPORATION,24	TECHNICAL SPECIFICATION - b. Specification: 32 channels Dual effect processors Digital audio ports	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			(PEAVY)						NATIONA L T.V. MARKET SOHRAB KHATRA K ROAD SADDAR KARACHI ,TEL: 0092-21-5685654&5680739		interface 600 Ohm Mics supported c. Power Supply 220 V AC single Phase & 24 V DC d. Acceptance criteria 32 Mic should be ON at a time. High gain with no noise and distortion for crystal clear signal reproduction onboard e. Dimensions Height 92 cm approx. Width 64 cm approx. Depth 30 cm approx. Weight 21 kg approx. SOURCE OF AVALIBILITY:KYAF CORPORATION,24 NATIONAL T.V. MARKET SOHRAB KHATRAK ROAD KARACHI.TEL:0092-21-5685654&5680739.GENERAL SPECIFICATION - b. Specification: 32 channels Dual effect processors Digital audio ports interface 600 Ohm Mics supported c. Power Supply 220 V AC single Phase & 24 V DC d. Acceptance criteria 32 Mic should be ON at a time. High gain with no noise and distortion for crystal clear signal reproduction onboard e. Dimensions Height 92 cm approx. Width 64 cm approx. Depth 30 cm approx. Weight 21 kg approx. SOURCE OF AVALIBILITY:KYAF CORPORATION,24 NATIONAL T.V. MARKET SOHRAB KHATRAK ROAD KARACHI.TEL:0092-21-5685654&5680739.	
44	DNF91963	Q101848	6130TY5200873 / POWER SUPPLY Q4	METAL ANALYZER	1 / EACH/N UMBER	Q4 TASMAN	Q0195	Braker AXS GmbH Karlsruhe Germany Phone +49(0)721-50997-0 Fax +49(0)721-50997 E.mail: info@braker-axs.de www.braker.com	BRUKER GERMAN Y		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
45	DNF89256	05-00-0515-00	6350715194472 / EMERGENCY STOP KIT, LIGHTED	Luggage Scanning Machine size (40	1 / EACH/N UMBER	XIS-100X	ASTVC180LL740	ASTROPHYSICS INC. UNITED STATES psc91789-5233 tel 9095985488 fax 9095985546 nai 334511+334517+334519+335999+488119	Astrophysi cs Manufactu red		TECHNICAL SPECIFICATION - Security EquipmentGENERAL SPECIFICATION - Security Equipment	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
46	DNC914 43	ELEC-2650 / IN 63047/ 2650	623079511027 2 / SEARCH LIGHT HAND HELD (24V DC&230 WATT)	GRIFFON HOVER CRAFT LTD UK	2 / EACH/NUMBER	GEEPAS®					TECHNICAL SPECIFICATION - 1. Make/ Brand: GEEPAS @ 2. Model: GSL5706 - 30Watt GENERAL SPECIFICATION - 1. Make/ Brand: GEEPAS @ 2. Model: GSL5706 - 30Watt	
47	DNF9189 1	210883-1	665500162247 9 / EXPENDABLE BATHY PROBE T7	LEANDER CLASS DEPOT PACKAGE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DNF9058 2	210883-1	665500162247 9 / EXPENDABLE BATHY PROBE T7	LEANDER CLASS DEPOT PACKAGE	19 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DNF9182 9	210883-1	665500162247 9 / EXPENDABLE BATHY PROBE T7	LEANDER CLASS DEPOT PACKAGE	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
50	DNF9157 1	210883-1	665500162247 9 / EXPENDABLE BATHY PROBE T7	LEANDER CLASS DEPOT PACKAGE	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
51	DNF9137 4	210883-1	665500162247 9 / EXPENDABLE BATHY PROBE T7	LEANDER CLASS DEPOT PACKAGE	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
52	DNF9285 8	33010319	414099260927 2 / FAN SPEED TRANSDUCER		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - FAN SPEED TRANSDUCER GENERAL SPECIFICATION - FAN SPEED TRANSDUCER	
53	DN09068 6	DL-473WDL02 4-02-07-02 / 473WDL02 4-02-07-02/ZACR-061-SEW	4110FP305006 1 / Anti-corrosion zinc bar (Fresh keeping device)		4 / EACH/NUMBER	473WDL0 24-02-07-02					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
54	SCP9418 1		841550250155 0 / BLANKET		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - Color: Blue, Weight: 2250g (+)(-)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			OFFICER		UMBER						100g Material: 90% Imported Wool and 10% Soft Fabric Size: 60"x96" Side Cloth Piping <u>GENERAL SPECIFICATION</u> - Color: Blue, Weight: 2250g (+)(-) 100g Material: 90% Imported Wool and 10% Soft Fabric Size: 60"x96" Side Cloth Piping	
55	DN090690	CSA-150-SEW / FFF1	534078527963 2 / ISOMETRIC COMPOSITE SACRI FICIAL ANODE (150 OD = 190 Ømm, ID = 153 Ømm)		3 / EACH/N UMBER	215ZF907-12-0					<u>TECHNICAL SPECIFICATION</u> - NSX-FHYJ-HZ3 1.0 MPa DN 150 OD = 190 (Ømm), ID = 153 (Ømm), Length of sleeve = 50 (mm) <u>GENERAL SPECIFICATION</u> - NSX-FHYJ-HZ3 1.0 MPa DN 150 OD = 190 (Ømm), ID = 153 (Ømm), Length of sleeve = 50 (mm)	
56	DNF89567	d701-537	613573527071 2 / LUMINAL CELL (PACK OF 6 CELLS)		2 / EACH/N UMBER	NA					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
57	SNC93371	X00003420	293012386012 0 / ELBOW TO PLATE-CORE COOLE		1 / EACH/N UMBER	8V 2000 M84					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
58	DCP93165		653250040006 3 / BLANKET SCARLET RED HOSPITAL		36 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - BLANKET SCARLET RED HOSPITAL <u>GENERAL SPECIFICATION</u> - BLANKET SCARLET RED HOSPITAL	
59	DNJ91666	16510-61a31	294070526787 5 / filter assy oil		1 / EACH/N UMBER	dfa 150 suzuki					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
60	SNC93372	X59414500018/87	281572530067 1 / EXHAUST PIPE BELOWS		1 / EACH/N UMBER	N/A					<u>TECHNICAL SPECIFICATION</u> - WEIGHT: 13.500KG <u>GENERAL SPECIFICATION</u> - WEIGHT: 13.500 KG	
61	DNJ91667	09482-00446	593576525887 0 / SPARK PLUG (DCPR6E)		4 / EACH/N UMBER	N/A					<u>TECHNICAL SPECIFICATION</u> - OEM & MAKE: PAK SUZUKI CO LTD <u>GENERAL SPECIFICATION</u> - OEM & MAKE: PAK SUZUKI CO LTD	
62	DNF90377	zkx8s	581515171795 8 / zk-teco zk-8s/ZKTECO G3 PLUS biometric		1 / EACH/N UMBER	zkx8s/ZK Teco G3 Plus					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			finger print reader									
63	DNO91574	ST2SAAE HENAE310	5998505314290 / AZIMUTH HOLLOW ENCODER		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
64	DNF92368	R-41056367	6140785289142 / lithium polymar rechargeable battery for MAVIC AIR 2		5 / EACH/NUMBER	pb2-3500mah-11.55v					TECHNICAL SPECIFICATION - INTELLIGENT FLIGHT BATTERY 3500 MAH TYPE LIPO 3S VOLTAGE 11.55 GENERAL SPECIFICATION - INTELLIGENT FLIGHT BATTERY 3500 MAH TYPE LIPO 3S VOLTAGE 11.55	
65	DNO91240	526-3696	6620775259155 / SENSOR GP- OIL LEVEL		2 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
66	DCP94374		6532500601092 / SHEET HOSPITAL WHITE COTTON SIZE 100"X68" (254X170CM)		450 / EACH/NUMBER						TECHNICAL SPECIFICATION - SHEET HOSPITAL WHITE COTTON SIZE 100"X68" (254X170CM) GENERAL SPECIFICATION - SHEET HOSPITAL WHITE COTTON SIZE 100"X68" (254X170CM)	
67	DNO92027	319-6217.	5340715268517 / CONNECTOR AS		2 / EACH/NUMBER	C9.3					TECHNICAL SPECIFICATION - CONNECTOR AS GENERAL SPECIFICATION - CONNECTOR AS	
68	DNF91442	HID RP40	5810715279711 / HID ICLASS R40 SE reader		1 / EACH/NUMBER	hid					TECHNICAL SPECIFICATION - $\angle$ RFID card reader $\angle$ HID iClass SE reader $\angle$ R40/ U90 GENERAL SPECIFICATION - $\angle$ RFID card reader $\angle$ HID iClass SE reader $\angle$ R40/ U90	