

**PAKISTAN NAVY**  
**TENDER BULLETIN**

**INVITATION TO TENDER TO BE OPENED ON 06-01-2026**

**TERMS & CONDITION**

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT".
  
2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.
  
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPC94666	SPEC,DEF 1052 COLOURS TO BS 381C	044250910703 5 / PAINT FNSHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/5 66DT210902		20 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
2	DPC94667		044250942119 3 / PAINT FINISHING INTERIOR WHITE FIRE RETARDANT flash point 32C (20 LTR drum)	BILGES, CABINS	540 / LITER					oem/authorized/dealer coc is required with technical data sheet	TECHNICAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG) GENERAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG)	
3	DPC94670		044250442008 3 / THINNER (DECO) (04 LTR Packing) Flash point 16 C	BUTYL KETONE32+-3% 4METHYL PENTAN-2-ONE.	44 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED	TECHNICAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingredient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_3% c. ethylene 7+_3% d. iso butyl alcohol: 26+_3% GENERAL SPECIFICATION - defstan 80-38/2 of 2009 2. ingredient production by volume is under: a. methyl iso butyl ketone 32 +_3% (04 methylpentan-2-one) b. solesso 32 +_3% c. ethylene	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											7+_3% d. iso butyl alcohol: 26+_3%	
4	DPC94669	DEF-1145/1956	0442504420079 / THINNER (SPEC) DEF STAN 80-38/2 1985 (PACKING 20 LTRS DRUM)		60 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED	TECHNICAL SPECIFICATION - DEFSTAN 80-38/2 of 1985 GENERAL SPECIFICATION - DEFSTAN 80-38/2 of 1985	
5	DPC94664	NO DATA AVAILABLE	0442504420039 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	240 / LITER					oem/authorized/dealer coc with technical data sheet is required	TECHNICAL SPECIFICATION - Flash point 32C( Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR GENERAL SPECIFICATION - Flash point 32C( Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
6	DPC94668		0442504420049 / PAINT FOR INTERIOR FIRE RETARDING (PALE CREAM) (04 LTR Packing) (Flash point 32.22)	FINISHING INTERIOR	40 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED	TECHNICAL SPECIFICATION - DEFSTAN 80-78/2 OF 1995, SHADE NO 352 OF BS 381-C Flash point 32.22 C 04 LTR TIN Method of application: Brushing stage inspection prescribed NS/P/002 OF 2013(revised)except for packing Colour shade no 352 OF bs: 381-c of 1996 defstan 80-78/2 of 1995 GENERAL SPECIFICATION - DEFSTAN 80-78/2 OF 1995, SHADE NO 352 OF BS 381-C Flash point 32.22 C 04 LTR TIN Method of application: Brushing stage inspection prescribed NS/P/002 OF 2013(revised)except for packing Colour shade no 352 OF bs: 381-c of 1996 defstan 80-78/2 of 1995	
7	DPC94662	NIL	6810FP0990017 / ALCOHOL ETHER MIXTURE	F-22P SHIPS	1 / LITER	NO DATA AVAILABLE		CH		CSTC-CHINA	oem/authorized/dealer coc is required with technical data sheet TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: CSTC, CHINA GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: CSTC, CHINA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
8	DPK94663	815C/3282	6810142855639 / EPON RESIN 815C WITH Epikure Curing Agent 3282		70 / KILOGRAMME	NO DATA AVAILABLE				oem/authorized/coc with technical data sheet is required	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DPC94651	WD40	8030014189008 / WD40 ( PACKING 440ML SPRAY BOTTLE)	0	8 / EACH/NUMBER	0	0	1061 CUDAHY PL, SAN DIEGO, CA SAN DIEGO CA	WD-40 COMPANY	OEM/AUTHORIZED/DEALER COC IS REQUIRED WITH TECHNICAL DATA SHEET	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
10	DPC94760	NO DATA AVAILABLE	0443500443067 / Gas Nitrogen Technical (99.998% Pure Nitrogen Gas With Less Water Content (i.e. 4 PPM), In Buyer's/ Supplier's Returnable Cylinder of Water Capacity 45 to 55 Liters With Protection Cap.	A/C NO 5 AND 6	6.23 / CUBIC METER					oem/authorized/dealer coc is required	TECHNICAL SPECIFICATION - CGA G-10.1 OF 2008 QVLs GRADE 'L' Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder. GENERAL SPECIFICATION - CGA G-10.1 OF 2008 QVLs GRADE 'L' Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder.	
11	DPC94650	NO DATA AVAILABL E	0473500005370 / SILICA GEL (grain size 2-3mm)	Transformers Humidity Control	50 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC IS REQUIRED WITH TECHNICAL DATA SHEET	<u>TECHNICAL SPECIFICATION -</u> Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up. <u>GENERAL SPECIFICATION -</u> Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.	
12	DPC94711		0442509434483 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	100 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED	<u>TECHNICAL SPECIFICATION -</u> DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996 <u>GENERAL SPECIFICATION -</u> DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996	
13	DPK94800	828250	9150270374373 / GREASE, GENERAL PURPOSE	VOLVO PENTA MAIN ENGINE	12 / TUBE	NO DATA AVAILAB LE		OC	VOLVO AB, GOETEB ORG, SWEDEN	OEM/AUTHORIZED/DEALER COC IS REQUIRED WITH	<u>TECHNICAL SPECIFICATION -</u> OEM ADD/SOURCE OF AVAILABILITY:VOLVO AB, GOETEBORG,SWEDEN <u>GENERAL SPECIFICATION -</u> OEM ADD/SOURCE OF AVAILABILITY:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										TECHINCA L DATA SHEET	VOLVO AB,GOETEBORG,SWEDEN	
14	DNM94631	2366057	433071518666 9 / FILTER ELEMENT FUEL	D/G CATTER PILLAR C2.2	8 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED TECHNICAL SPECIFICATION - oem : caterpillar GENERAL SPECIFICATION - oem : caterpillar	
15	DNM94524	2366057	433071518666 9 / FILTER ELEMENT FUEL	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED TECHNICAL SPECIFICATION - oem : caterpillar GENERAL SPECIFICATION - oem : caterpillar	
16	DNM94388	3863373	304073517558 4 / DRIVES SHAFT	IPS 500	1 / EACH/NUMBER	IPS 500	IPS-F3940012979	VOLVO PENTA		VPL SWEDEN VOLVO PENTA	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED TECHNICAL SPECIFICATION - VOLVO PENTAGENERAL SPECIFICATION - VOLVO PENTA	
17	DNM94617	CWCU-230-26	413070521436 1 / F-6 BAG FILTER (65% EFFICIENCY) SIZE 24	HVAC PLANT 1 CWAHU-32 PAKISTAN	5 / EACH/NUMBER	CP-F6-65-3	NIL	GUARD FILTERS PAKISTAN www. quardfilters.com COOL POINT PVT LMTD LAHORE PAKISTAN		GUARD FILTERS PAKISTAN www. quardfilters.com	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED TECHNICAL SPECIFICATION - FILTER USED HVAC PLAIT F-6 BAG FILTER (65 % EFFICIENCY) SIZE 24X24X20 GENERAL SPECIFICATION - FILTER USED HVAC PLAIT F-6 BAG FILTER (65 % EFFICIENCY) SIZE 24X24X20	
18	DNH94562	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENCER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENCER PAKISTAN		ORIENT	pwd-315 TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENCER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENCER	
19	DNM94391	4919951	312071519312 5 / SLEEVE, SALVAGE	MAIN ENGINE CUMMINS MODEL QSB6.77305MD	6 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA		M/s IMPEX NINE INC	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
20	DPC94842	A020EEV2	8010705332825 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		600 / LITER	HIGHLY PERFUMED				TECHNICAL DATA SHEET IS REQUIRED  OEM/AUTHORIZED/DEALER COC IS REQUIRED WITH TECHNICAL DATA SHEET	<p><u>TECHNICAL SPECIFICATION - PRODUCT INFORMATION:</u>  APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.</p> <p><u>GENERAL SPECIFICATION - PRODUCT INFORMATION:</u>  APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
21	DNM94614	TEC-7676	4120735332907 / air conditioner (PORTABLE) 5050 BTU (0.42 TON) 220-240 volt 1480 watt		2 / EACH/NUMBER	tec-7676					TECHNICAL SPECIFICATION - RATED POWER(EN60335) COOLING: 1480W HEATING: 1300W COOLING CAPACITY: 3500W HEATING CAPACITY: 3500W <u>GENERAL SPECIFICATION - RATED POWER(EN60335) COOLING: 1480W HEATING: 1300W COOLING CAPACITY: 3500W HEATING CAPACITY: 3500W</u>	
22	DNH94494	NO DATA AVAILABLE	1308500530125 / REFRIG 12CUFT DOUBLE DR 220V(DLT. NSSD/HMPAT T/467 DT. 121093)	12 CUF	1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
23	DPC94843		0473546004703 / SODA CAUSTIC (PACKING 25 KG)		250 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC IS REQUIRED WITH TECHNICAL DATA SHEET	TECHNICAL SPECIFICATION - Soda Caustic (chemical nomenclature SODIUM HYDROXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments <u>GENERAL SPECIFICATION - Soda Caustic (chemical nomenclature SODIUM HYDROXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments</u>	
24	DPC94844	NO DATA AVAILABLE	0442500000107 / SPIRIT METHYLATED		40 / LITER	NO DATA AVAILABLE				OEM/AUTHORIZED/DEALER COC IS REQUIRED	TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										WITH TECHNICAL DATA SHEET		
25	DNQ94389	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. <u>GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.</u>	
26	DPK94802	NO DATA AVAILABE	0474509100504 / GREASE PUMPABLE CALCIUM BASE XG-380 (3KG TIN)		48 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC IS REQUIRED WITH TECHNICAL DATA SHEET	TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
27	DPK94803		0474509100524 / GREASE NAVAL GRAPHITE XG-460 3 KG PACK	XG-460	24 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC IS REQUIRED WITH TECHNICAL DATA SHEET	TECHNICAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460) <u>GENERAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460)	
28	DPK9432 5		047450910052 4 / GREASE NAVAL GRAPHITE XG-460 3 KG PACK	XG-460	18 / KILOGR AMME					OEM/AUTH ORIZED/ ALER CO IS REQUIRED WITH TECHINCA L DATA SHEET	TECHNICAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460) GENERAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460)	
29	DPK9480 1	LG 280	047450910050 2 / GREASE LG-280 (XG- 286)	FIVE /G SERVICE PUMP NO.3	100 / KILOGR AMME					OEM/AUTH ORIZED/ ALER CO IS REQUIRED WITH TECHINCA L DATA	TECHNICAL SPECIFICATION - SUPERCEDED VIDE CICIP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128GENERAL SPECIFICATION - SUPERCEDED VIDE CICIP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										SHEET	128	
30	DNM94384	NR-20550/96	2920725089587 / FOG GENERATOR TF-35 FOR CONTROL OF MOSQUITOES	FOR GENERATOR TF35FOR CONTROL (GERMANY)	1 / EACH/NUMBER	TF-35				oem/authorized/dealer coc with technical data sheet is required	<u>TECHNICAL SPECIFICATION - IGEBAGENERAL SPECIFICATION - IGEBGA</u>	
31	DNM92322	540400	4220505059626 / PRO WEIGHT BELT (6 POUCH BELT)	AQUALUNG DIVING EQUIPMENT	3 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED	<u>TECHNICAL SPECIFICATION - Size: S (23"-31") M (32"-40") L (41"-49") Material: Nylon Colour: As available Capacity: w.r.t weight holding Enhanced width: 4 inch wide maximum Buckle: Heave duty (Buckle Metallic) Test Certificate: Will be REQUIRED on physical inspection</u> <u>GENERAL SPECIFICATION - Size: S (23"-31") M (32"-40") L (41"-49") Material: Nylon Colour: As available Capacity: w.r.t weight holding Enhanced width: 4 inch wide maximum Buckle: Heave duty (Buckle Metallic) Test Certificate: Will be REQUIRED on physical inspection</u>	
32	DNH94379		4120705051919 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	1 / EACH/NUMBER					t3 series required	<u>TECHNICAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)</u> <u>GENERAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)</u>	
33	DNM94521	BMCU-60	4120PK5073944 / CONDENSING UNIT (05 TONS)440V 3PH WITH ALL ACCESSORIES	A/C UNIT SPLIT TYPE	1 / EACH/NUMBER	BMCU-60					<u>TECHNICAL SPECIFICATION - ZR61KCE-TFD-522 Refrigerant R-22 Sea Water Cooled Condenser (Cu-Ni) (BT-60-CTT-20) Suction Accumulator Size 7/8" (Design Pressure 450PSIG) Liquid Receiver (Design Pressure 500PSIG) Solenoid Valve Size 3/8" Solenoid Coil 220V Dual Pressure Switch (Danfoss) KP-15 Low Pressure Switch (Danfoss)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											KP-01 Drier Shell Service Valve 3/4" Service Valve 3/8" Stainless Steel Drain Tray Complete Copper Piping Imported Foam Insulation <u>GENERAL SPECIFICATION - ZR61KCE-TFD-522 Refrigerant R-22 Sea Water Cooled Condenser (Cu-Ni) (BT-60-CTT-20) Suction Accumulator Size 7/8" (Design Pressure 450PSIG) Liquid Receiver (Design Pressure 500PSIG) Solenoid Valve Size 3/8" Solenoid Coil 220V Dual Pressure Switch (Danfoss) KP-15 Low Pressure Switch (Danfoss) KP-01 Drier Shell Service Valve 3/4" Service Valve 3/8" Stainless Steel Drain Tray Complete Copper Piping Imported Foam Insulation</u>	
34	DNM93713	ALCO CONTROL D-48	4120795013825 / DRIER CORE LG 140MM O/D 96MM X I/D 44MM (ALCO CONTROL D-48)	AIR CONDITIONING PLANT	2 / EACH/NUMBER					oem/authorized/dealer coc with technical data sheet is required	<u>TECHNICAL SPECIFICATION - MAKE: COOLPOINT, LG 140MM O/D 96MM X I/D 44MM (ALCO CONTROL D-48)</u> <u>GENERAL SPECIFICATION - MAKE: COOLPOINT, LG 140MM O/D 96MM X I/D 44MM (ALCO CONTROL D-48)</u>	
35	DNH94488	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	2 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, GENERAL, LG,				T3 SERIES REQUIRED	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
36	DNH94378	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
37	DNM94566	1W3900	5330011554283 / GASKET	CATTER PILLAR DIESEL GENERATOR (USA)	2 / EACH/NUMBER	3304 SSDG				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED	TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG	
38	SPC95063	R-5021	8010705111038 / PIGMENT (PANTHER BLACK)	GRP WORK, M/S ZAIN SONS KARCHI, PH7731541	40 / KILOGRAMME						TECHNICAL SPECIFICATION - 05 Kg packing GENERAL SPECIFICATION - 05 Kg packing	
39	DRG85357	315/70 R 15 TL (300 R 15)	2610124002724 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL					TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
40	DRG86171	315/70 R 15 TL (300 R 15)	2610124002724 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL					TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
41	DRG85374	315/70 R 15 TL (300 R 15)	2610124002724 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL					TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
42	DRG86337	315/70 R 15 TL (300 R 15)	2610124002724 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL					TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
43	DPC84167	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1589 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - . psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
44	DPC95068	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	6 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
45	DPK94891	HA5430H	9150735164284 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	20 / QUART	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	TELEFLEX MARINE CANADA	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858GENERAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	
46	DNM94055	3583440-VOLVO	4720270375416 / FUEL HOSE	VOLVO PENTA ENGINE	2 / EACH/NUMBER	NO DATA AVAILAB LE	27		M/S AB VOLVO PENTA CITY: GOTEBO RG SWEDEN GOTEBO	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED	TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									RG	FOR FINALIZATION OF LPO.		
47	DPK93584	ALVANIA2	9150010864163 / Grease, general purpose	0	5 / KILOGRAMME	0	0	1 SHELL PLZ, HOUSTON, TX HOUSTON TX	SHELL OIL CO	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
48	SPC95062	WD40	8030014189008 / WD40 (PACKING 440ML SPRAY BOTTLE)	0	140 / EACH/NUMBER	0	0	1061 CUDAHY PL, SAN DIEGO, CA SAN DIEGO CA	WD-40 COMPANY Y	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
49	DPK93744	sh/t0466-1992/7023	9150FP0020024 / LOW TEMPERATURE GREASE	F-22P SHIPS	3 / KILOGRAMME	NO DATA AVAILABLE		CH	CSTC-CHINA	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: CSTC, CHINA</u> <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: CSTC, CHINA</u>	
50	DPK93743	SPEC#7	9150FP0020021 / PRECISION INSTRUMENT GREASE (30 KG PACK)	F-22P SHIPS	30 / EACH/NUMBER	NO DATA AVAILABLE		CH	CSTC-CHINA	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: CSTC, CHINA</u> <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: CSTC, CHINA</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										SHEET IS REQUIRED FOR FINALIZATION OF LPO.		
51	DPK94607	VALVOLINE PREMIUM BLUE 7800 15W40	9150715229858 / 15W40 VALVOLINE PREMIUM BLUE 7800	MAIN ENGINE	208 / LITER	QSB6.7 CM2250 MARINE	22376716	valvoline distributors	VALVOLINE	oem/authorized/dealer coc with technical data sheet is required for finalization of lpo.	TECHNICAL SPECIFICATION - 15W40 VALVOLINE PREMIUM BLUE 7800 ENGINE OIL. FOR PERIODIC MAINTAINENCE ROUTINES GENERAL SPECIFICATION - 15W40 VALVOLINE PREMIUM BLUE 7800 ENGINE OIL. FOR PERIODIC MAINTAINENCE ROUTINES	
52	DNQ92995	ITEM INDINEGOS DEVELOP	8415595160246 / SURCOAT BLUE	FIRE FIGHTING EQUIPMENT	14 / EACH/NUMBER			LOCALLY AVAIL ABLE/IND DEVELOP.	LOCALLY AVAIL ABLE/IND DEVELOP.	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - LOCALLY AVAIL ABLE/IND DEVELOP. GENERAL SPECIFICATION - LOCALLY AVAIL ABLE/IND DEVELOP.	
53	DNM92682	3920679/5 293586	2920123688237 / ALTERNATOR	CUMMINS STANDBY EMERGENCY GENERATOR 4BT3-9D UK	1 / SET	4BT3-9D	MAD 46950895 RSD 46954407	CUMMINS LTD T/A CUMMINS UK RUTHERFORD DRIVE, PARK FARM INDUSTRIAL ESTATE, WELLINGBOROUGH, NORTHAMTONSHIRE, UK Tel : 01933 672 200 Fax : 01933 403 200 Email/URL : www.cummins.com	CUMMINS LTD UK	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - IPC GENERAL SPECIFICATION - IPC	
54	DNM94055	3583440-VOLVO	4720270375416 / FUEL HOSE	VOLVO PENTA ENGINE	2 / EACH/NUMBER	NO DATA AVAILAB LE		AB VALVO PENTA SE 405 08 GOTHENBURG SWEDEN	VALVO PENTA	OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS	TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										REQUIRED FOR FINALIZATION OF LPO.		
55	SPC94840		047450474008 2 / CUPREX 1 BLOCK (PACKING 1 KG)	4FI SSDG SEA WATER PUMP	35 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - packing 1 kg GENERAL SPECIFICATION - packing 1 kg	
56	DPC95106		047350220230 7 / PAINT REMOVER ORGANIC SOLVENT TYPE WATER RINSABLE (04 LTR TIN)		20 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - 1. DEFSTAN80-14/1 OF 1970. type brushing GENERAL SPECIFICATION - 1. DEFSTAN80-14/1 OF 1970. type brushing	
57	SPC94841	NO DATA AVAILABLE	047450474009 5 / MOLASSES (PACKING 25 KG CAN)	PORT MAIN FIRE PUMP	1000 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - MOLASSES COMPOSITION: BRIX SPINDLE: 86.0LBS WEIGHT/GALLON: 11.8-12.0 LBS NITROGEN: 1.01% CRUDE PROTEIN: 6.30% TOTAL SUGARS: 48.3% DENSITY: 11.8% DRY MATTER: 76.5% MOISTURE: 23.5% ASH; 16.0% ORGANIC MATTER: 62.5% REDUCING SUBSTANCE AS DEXTRROSE: 11.5% SUCROSE: 35.9% FRUCTOSE: 5.6% GLUCOSE: 2.6% PH: 4.9-5. GENERAL SPECIFICATION - MOLASSES COMPOSITION: BRIX SPINDLE: 86.0LBS WEIGHT/GALLON: 11.8-12.0 LBS NITROGEN: 1.01% CRUDE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PROTEIN: 6.30% TOTAL SUGARS: 48.3% DENSITY: 11.8% DRY MATTER: 76.5% MOISTURE: 23.5% ASH; 16.0% ORGANIC MATTER: 62.5% REDUCING SUBSTANCE AS DEXTROSE: 11.5% SUCROSE: 35.9% FRUCTOSE:5.6% GLUCOSE: 2.6% PH:4.9-5.	
58	SPK94839	ZX13-500 GRAMME	0474509100528 / ANTISEIZE COMPOUND ZX13-500 GRAMME (NSN8030999100528)		10 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DPC95101	NO DATA AVAILABLE	0442502201164 / PAINT FINISHING GLOSS BLACK DLT LTR NS/G/1303/C DT 270199	PRIMED STEEL ALUMINUM OR WOOD	40 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DPC94878		0442799423542 / Paint Marking, Stenciling (Signal Red) flash point: 32 degree C (Min) method of application: brushing & stenciling type: Alkyed Packing: 04 liter tin gauge		60 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - 1. DEFSTAN 80-68/4 2. NS/P/012 OF 2013 (REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996 GENERAL SPECIFICATION - 1. DEFSTAN 80-68/4 2. NS/P/012 OF 2013 (REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			of tin 26 to 28 SWG									
61	DPC951 12		044250942937 4 / VARNISH MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	USE ONWOOD UNDER CONDITIONS OF MARINE EX	60 / LITER					OEM/AUTH ORIZED/DE ALER COC WITH TECHNICA L DATA SHEET IS REQUIRED FOR FINALIZATI ON OF LPO.	TECHNICAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED GENERAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED	
62	DPC951 02	NO DATA AVAILABL E	044250442003 9 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	260 / LITER					OEM/AUTH ORIZED/DE ALER COC WITH TECHNICA L DATA SHEET IS REQUIRED FOR FINALIZATI ON OF LPO.	TECHNICAL SPECIFICATION - Flash point 32C( Min) DEFSTAN 80- 59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C( Min) DEFSTAN 80- 59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
63	DPC933 92		044250442013 9 / PAINT GLOSS ALKIDE RESIN, THINNER: WHITE SPIRIT NAPTH COL 361		16 / TIN					OEM/AUTH ORIZED/DE ALER COC WITH TECHNICA L DATA SHEET IS REQUIRED FOR FINALIZATI ON OF LPO.	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DPC951 04	NO DATA AVAILABL E	044250220213 7 / PAINT FINISHING FOR GENERAL SERVICE (RED)	IDENTIFICATI ON OF PIPES ETC.	20 / LITER					OEM/AUTH ORIZED/DE ALER COC WITH TECHNICA L DATA SHEET IS REQUIRED	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
65	DPC95123	NO DATA AVAILABL E	0443504430005 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/N UMBER					FOR FINALIZATI ON OF LPO.  OEM/AUTH ORIZED/DE ALER COC WITH TECHNICA L DATA SHEET IS REQUIRED FOR FINALIZATI ON OF LPO.	<b>TECHNICAL SPECIFICATION - 1.</b> grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque. GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4"</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120-150 Torque.	
66	DPC95107	SUPERSEDED BY DGS 1035	044250220200 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	120 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed <u>GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed</u>	
67	DPC95099		0442799107001 / Paint Finishing General Service Black	IDENTIFICATION OF PIPES ETC	320 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - 1. FLASH POINT: 32 DEGREE C 2. SPECIFIC GRAVITY: 0.90+0.03 3. NS/P/008 OF 2013(REVISED) 4. DEFSTAN: 80-54/4 Of 2005 5. STAGE INSPECTION PRESCRIBED 6. PACKING:20 LITER DRUM) 7. GAUGE OF DRUM 24 TO 26 SWG <u>GENERAL SPECIFICATION - 1. FLASH POINT: 32 DEGREE C 2. SPECIFIC GRAVITY: 0.90+0.03 3. NS/P/008 OF 2013(REVISED) 4. DEFSTAN: 80-54/4 Of 2005 5. STAGE INSPECTION PRESCRIBED 6. PACKING:20 LITER DRUM) 7. GAUGE OF DRUM 24 TO 26 SWG</u>	
68	DPC94874	SPEC,DEF 1052 COLOURS TO BS 381C	0442509107035 / PAINT FINISHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/5 66DT210902		300 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR	TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										FINALIZATION OF LPO.		
69	DPK94905	NO DATA AVAILABLE	0474509100504 / GREASE PUMPABLE CALCIUM BASE XG-380 (3KG TIN)		60 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
70	DNM94075	3802130 / 380239700	2815795045875 / KIT ENGINE PISTON	DIESEL GENERATOR 100KW (COUMMIUS)	6 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	<u>TECHNICAL SPECIFICATION - LG 12MM BROG 111MM</u> <u>GENERAL SPECIFICATION - LG 12MM BROG 111MM</u>	
71	DPC93457	551G	7930997379940 / PENETRANT CLEANER N/FLAM AEROSOL TYPES 400MLS COLOURLES	CHEMICAL	10 / EACH/NUMBER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	<u>TECHNICAL SPECIFICATION - ITEM MAY BE PROCURED FROM LOCAL SOURCE M/S ZH &amp; COMPANY OFFICE, 510, 5TH FLOOR ANUM BLESSING SHAHRA-E-FAISAL KARACHI TEL: 021-34390313 CELL NO: 03012611327 NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - ITEM MAY BE PROCURED FROM LOCAL SOURCE M/S ZH &amp; COMPANY OFFICE, 510, 5TH FLOOR ANUM BLESSING SHAHRA-E-FAISAL KARACHI TEL: 021-34390313 CELL NO:03012611327 NO DATA AVAILABLE</u>	
72	DPC95000	BS 3591 of 1985	6810992201733 /	FOR GENERAL	80 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			METHYLATED SPIRIT INDUSTRIAL GEN/PURPOSE (Packing = 20 LTR), highly flammable	USE							SPECIFICATION - NO DATA AVAILABLE	
73	DPC94152	BS 3591 of 1985	6810992201733 / METHYLATED SPIRIT INDUSTRIAL GEN/PURPOSE (Packing = 20 LTR), highly flammable	FOR GENERAL USE	20 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	SPC95061	AEROSIL® 200	6810705009686 / POWDER AEROSIL 200 (packing 10/15/20 kg)	EXPOSED DECKS	40 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - REQUIREMENT....FUMED SILICA AEROSIL® GRADES = AEROSIL® 200 BET SURFACE AREA [m2/g] = 175-225 LSS ON DRYING [wt.%] ==1.5 ph VALUE = 3.7-4.5* GENERAL SPECIFICATION - REQUIREMENT....FUMED SILICA AEROSIL® GRADES = AEROSIL® 200 BET SURFACE AREA [m2/g] = 175-225 LSS ON DRYING [wt.%] ==1.5 ph VALUE = 3.7-4.5*	
75	DPC93463	S-10	6810705080419 / NEUTRALIZER -S-10	A/C PLANT CHILLER CONDENSER HEAT EXCHANG	250 / KILOGRAMME					oem/authorized/dealer coc with technical data sheet is required for finalization of lpo.	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
76	DPC93213	S-10	6810705080419 / NEUTRALIZER -S-10	A/C PLANT CHILLER CONDENSER HEAT EXCHANG	500 / KILOGRAMME					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										SHEET IS REQUIRED FOR FINALIZATION OF LPO.		
77	DPC95060	205-6611 (05 Ltr) / 205-6612 (20 Ltr)	6810705084532 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (05 Liter Can)	CP AIR COMP	80 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTR GENERAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTR	
78	DPC93593	G9005	8010715119369 / GLOBALDUGN101 EPOXY PRIMER (EURO BASIC-BLACK) (Packing = 20 LTRS)	INSIDE BOTTOM AND WING TANK OF FD-1	120 / LITER					OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DNM93083	A055M148	5330715267661 / JOINT-PDC- WATER INTET CONNECTION		1 / EACH/NUMBER	C22 D5				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
80	DPC95067	MP4-2020TX	6850705281909 / MARINE ORTHOPHTHALIC		225 / KILOGRAMME	matpol				OEM/AUTHORIZED/DEALER COC WITH	TECHNICAL SPECIFICATION - Appearance:clear slightly pale, styrene content:30-35%, acid value: 35-40 mg KOH/g, solid content:60-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			UNSATURATED POLYESTER RESIN 225 KG Drum for underwater repairs							TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	65%, mass density:1.12-1.19g/cm3, viscosity@300 in Din cup-4:80-90 seconds Gel time @300:10-12 Min, exothermic temperature:165-1700 C, Exothermic time: 13-20 Min, storage: 250, shelf life:03 months (reduces shelf life above 250)GENERAL SPECIFICATION - Appearance:clear slightly pale, styrene content:30-35%, acid value:35-40 mg KOH/g, solid content:60-65%, mass density:1.12-1.19g/cm3, viscosity@300 in Din cup-4:80-90 seconds Gel time @300:10-12 Min, exothermic temperature: 165-1700 C, Exothermic time: 13-20 Min, storage: 250, shelf life:03 months (reduces shelf life above 250)	
81	DNM93073	0502-1630	530679526430 1 / BOLT BANJO		3 / EACH/NUMBER	C110D5				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
82	DNM93449	362 201 02	433072534508 3 / oil filter (insert)		2 / EACH/NUMBER	36220102-000				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - OIL FILTER (INSERT) material tencel + carbon steel filtration ratio 25 micron weight aprox 1.5kgs use un hvac and refrigeration systems not washable filter it is used with chs,csw,hsk, oskaand bitzer 6g/4g series compressors GENERAL SPECIFICATION - OIL FILTER (INSERT) material tencel + carbon steel filtration ratio 25 micron weight aprox 1.5kgs use un hvac and refrigeration systems not washable filter it is used with chs,csw,hsk, oskaand bitzer 6g/4g series compressors	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
83	DNM94056	362 201 02	433072534508 3 / oil filter (insert)		4 / EACH/N UMBER	36220102 -000				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - OIL FILTER (INSERT) material tencel + carbon steel filtration ratio 25 micron weight aprox 1.5kgs use un hvac and refrigeration systems not washable filter it is used with chs,csw,hsk, oskaand bitzer 6g/4g series compressors GENERAL SPECIFICATION - OIL FILTER (INSERT) material tencel + carbon steel filtration ratio 25 micron weight aprox 1.5kgs use un hvac and refrigeration systems not washable filter it is used with chs,csw,hsk, oskaand bitzer 6g/4g series compressors	
84	DNM93084	0104-2116	534079523736 0 / COVER FLYWHEEL HSG		1 / EACH/N UMBER	C110D5				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
85	DNM93074	0406-1247	531071526756 7 / WASHER TAB- FAN TO WATER PUMP PULLEY SETSCREW		2 / EACH/N UMBER	C22 D5				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATION OF LPO.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
86	DNM93086	0503-2922 / 3280822	534071526757 6 / CLAMP		5 / EACH/N UMBER	C22 D5				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										SHEET IS REQUIRED FOR FINALIZATI ON OF LPO.		
87	DNM93076	A043A632	533071526762 2 / JOINT-LUBRICATION OIL SUCTION PIPE FLANGE TO LUBRICATION OIL PUMP		1 / EACH/N UMBER	C22 D5				OEM/AUTHORIZED/DEALER COC WITH TECHNICAL DATA SHEET IS REQUIRED FOR FINALIZATI ON OF LPO.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
88	DNM93075	0518-0789	531571526752 6 / CIRCLIP-GUDGEON PIN RETAINING		4 / EACH/N UMBER	C22 D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
89	DSB90028	cp307-sa-120-1-8r-e2-cr-5v	702572528920 5 / CORE DUO U2500, 12GHZ, 2MBL2, 1GB SOLDERED, BHP REAR I/O, EXTENDED TEMP, RANGE EZ, WITH CONFORMAL COATING AND RUGGEDIZATI ON SERVICE, 5V VI/O		2 / EACH/N UMBER	cp 307 3u					TECHNICAL SPECIFICATION - MEMORY: 1- SYSTEM MEMORY; UPTO 4GBYTE DUAL CHANNEL DDR2 667 MHZ MEMORY VIA MAX 2GBYTE SOLDERED MEMORY AND SOOIMM - SOCKET FOR MAX 2GBYTE MEMORY MODULE. 2- FLASH (BIOS); 1MB FIRM WARE HUB (FWH) 3- EPROM; SERIAL EEPROM (24LC64) 64KBIT FOR CMOS DATA SOTRING (NO BATTERY OPERATION) 4- COMPACT FLASH; TYPE I & II MOUNTING WITH IN 4HP VIA MEZZANINE MODEL OR ALTERNATIVLY TYPE I & II WITH IN 8HP VIA SOCKET ON MAZZANINE CARRIER 5- HDD; ONBOARD 2.5SATA HDD MOUNTING WITH IN 8HP MAZZANINE VIA CARRIER GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>MEMORY: 1- SYSTEM MEMORY; UPTO 4GBYTE DUAL CHANNEL DDR2 667 MHZ MEMORY VIA MAX 2GBYTE SOLDERED MEMORY AND SOOIMM - SOCKET FOR MAX 2GBYTE MEMORY MODULE. 2- FLASH (BIOS); 1MB FIRM WARE HUB (FWH) 3- EPROM; SERIAL EEPROM (24LC64) 64KBIT FOR CMOS DATA SOTRING (NO BATTERY OPERATION) 4- COMPACT FLASH; TYPE I &amp; II MOUNTING WITH IN 4HP VIA MEZZANINE MODEL OR ALTERNATIVLY TYPE I &amp; II WITH IN 8HP VIA SOCKET ON MAZZANINE CARRIER 5- HDD; ONBOARD 2.5SATA HDD MOUNTING WITH IN 8HP MAZZNINE VIA CARRIER</p>	
90	DRG937 17	SMTCS08- 02	7210ZO656201 1 / PVC MAT (VENYL FLOORING) WIDTH : 2 MTR, THICK 2MM		75 / METER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> W=2M,TH=2MM,LENGTH AS REQUIRED,COLOUR DARK GREY WITH 25MM CIRCLES DESIGN NO. SMTCS08-02) MAKE: LOCAL/IMPORTED SAMPLE HELD IN LIB. <u>GENERAL SPECIFICATION</u> - W=2M,TH=2MM,LENGTH AS REQUIRED,COLOUR DARK GREY WITH 25MM CIRCLES DESIGN NO. SMTCS08-02) MAKE: LOCAL/IMPORTED SAMPLE HELD IN LIB.</p>	
91	DRQ901 51	DUSTMAS K	5340ZO653000 6 / ROUND DUST MASK		500 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> DISPOSABLE NON-TOXIC DUST &amp; FILTER MASK(MOQ:50), WT:1/7 OF AN OUNCE,MAKE LOCAL/IMPORTED(QUALITY CERTIFIED MARK CE) <u>GENERAL</u> <u>SPECIFICATION - DISPOSABLE</u> NON-TOXIC DUST &amp; FILTER MASK (MOQ:50), WT:1/7 OF AN OUNCE, MAKE LOCAL/IMPORTED(QUALITY CERTIFIED MARK CE)</p>	
92	SRP9320	ETHYLEN	6850ZO654747		100 /	NO DATA					<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	4	E GLYCOL (OSAKA COOLENT PK	6 / ETHYLENE GLYCOL COOLENT (ANTI FREEZE)		LITER	AVAILAB LE					NASA ANTI FREEZ COOLANT (MAKE:KOREA),2.5LTR PACKINGMEET GM 1899M & 1825M ASTM D-3306 & D-4340 CUMMINS& CATERPILLER D/E CONTAINS ETHYLENE GLYCOL, RUST INHIBITOR IN PURIFIED WATER+BITTERIING AGENT3. 5PPM GENERAL SPECIFICATION - NASA ANTI FREEZ COOLANT (MAKE:KOREA),2.5LTR PACKINGMEET GM 1899M & 1825M ASTM D-3306 & D-4340 CUMMINS& CATERPILLER D/E CONTAINS ETHYLENE GLYCOL, RUST INHIBITOR IN PURIFIED WATER+BITTERIING AGENT3. 5PPM	
93	DRG942 88	950-50-0113	5340ZO517736 7 / WINDSOCK COMPLETE		6 / EACH/NUMBER	MSAT-500NG					TECHNICAL SPECIFICATION - MSAT-500NG GENERAL SPECIFICATION - MSAT-500NG	
94	DRG904 61	TRI CYCLE	2340ZO656952 9 / TRI CYCLE		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. Overall dimensions of tricycle to be as per drawing. 2. Steel frame of welded tubing. 3. Wooden frame mounted on rear axle behind seat for loading of items. 4. Rear axle to be supported on shock absorbers (coil or leaf springs). 5. Internal side of Wooden frame to be lined with 1 inch soft rubber padding. 6. Chain length of approximately 9 ft 2 inches 7. Tricycle to be delivered in yellow paint scheme (minimum 2 coats). 8. Rear tires to be heavy duty used on motorcycles (CG125) Part No 42701-KCS- 65K or equivalent. 9. Tricycle to be provided with following set of standard spares: a. 1 x seat b. 1 x chain c. 1 x set of Brake pads d. 2 x brake wires e. 1 x set of pedals f. 3 x air charging nozzles PHOTO COPY OF DRAWING HELD WITH TECH LIB MADE IN PAKISTAN GENERAL SPECIFICATION - 1. Overall	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>dimensions of tricycle to be as per drawing. 2. Steel frame of welded tubing. 3. Wooden frame mounted on rear axle behind seat for loading of items. 4. Rear axle to be supported on shock absorbers (coil or leaf springs). 5. Internal side of Wooden frame to be lined with 1 inch soft rubber padding. 6. Chain length of approximately 9 ft 2 inches 7. Tricycle to be delivered in yellow paint scheme (minimum 2 coats). 8. Rear tires to be heavy duty used on motorcycles (CG125) Part No 42701-KCS- 65K or equivalent. 9. Tricycle to be provided with following set of standard spares: a. 1 x seat b. 1 x chain c. 1 x set of Brake pads d. 2 x brake wires e. 1 x set of pedals f. 3 x air charging nozzles PHOTO COPY OF DRAWING HELD WITH TECH LIB MADE IN PAKISTAN</p>	
95	DSB92002	008a103	6850TY6715340 / MAGNETIC PARTICLE INSPECTION INK		70 / EACH/NUMBER	NO DATA AVAILAB LE					<p><b>TECHNICAL SPECIFICATION -</b> packing detail: 10 x 400ml tin-can in each box brand: Magnaflux  <b>GENERAL SPECIFICATION -</b> packing detail: 10 x 400ml tin-can in each box brand: Magnaflux</p>	
96	DRG94289	ZO6547220	5995ZO6547220 / EARTHING CABLE		5 / METER	NO DATA AVAILAB LE					<p><b>TECHNICAL SPECIFICATION -</b> Conductor : Copper Insulation: PVC Insulation Color: Yellow, Green, Black Temp Range: -20°C to 70°C Nominal Voltage: 450 V Test Voltage: 1000 V Standard: IEC (International Electromechanical Commission)  <b>GENERAL SPECIFICATION -</b> Conductor : Copper Insulation: PVC Insulation Color: Yellow, Green, Black Temp Range: -20°C to 70°C Nominal Voltage: 450 V Test Voltage: 1000 V Standard: IEC (International Electromechanical Commission)</p>	
97	DSB94222	NRC-PN-108-	5340143059306 / SUPPORT-		50 / EACH/NUMBER	NO DATA AVAILAB					<p><b>TECHNICAL SPECIFICATION -</b> NO DATA AVAILABLE  <b>GENERAL</b></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		9306/N532 300- 19303-45- 51	ELA-532300- 19303A		UMBER	LE					SPECIFICATION - NO DATA AVAILABLE	
98	SSM172 93	APMC- 01BR	599970523193 1 / BRAKE IGBT		3 / EACH/ UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	34