

PAKISTAN NAVY
TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 07-01-2026

TERMS & CONDITION

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT".

2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.

3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGD92750	NO DATA AVAILABLE	0035500000273 / BOARD CHOPPING		8 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - make/brand ken wood size ; 12" x 6" x 1/2" material; fiber/nylon ref haibat/03/7765652 <u>GENERAL SPECIFICATION</u> - make/brand ken wood size ; 12" x 6" x 1/2" material; fiber/nylon ref haibat/03/7765652	
2	DGB94040		0214590035661 / BOLT MACHINE STEEL BSW HEX HD SZ 4.000X0.375 IN		20 / TEN						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
3	DGB94039		0214590131010 / BOLT MACHINE STEEL BSF MEDIUM CLASS	BR 320 D/78	80 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Thread Size 5/8 Inch Nominal Length 2 1/2 Inch Length of Thread 1 1/4 Inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) METARIAL: STEEL 45 TON/SQ.IN.NTS TENSILE STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC REQUIRED <u>GENERAL SPECIFICATION</u> - Thread Size 5/8 Inch Nominal Length 2 1/2 Inch Length of Thread 1 1/4 Inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) METARIAL: STEEL 45 TON/SQ.IN.NTS TENSILE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
4	DGE946 16	NO DATA AVAILABL E	04765000006 1 / GLOVES LEATHER FOR WELDING, treated with presservative, standard quality		80 / PAIR	NO DATA AVAILAB LE					<p>STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC REQUIRED</p> <p>TECHNICAL SPECIFICATION - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL detials: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex GENERAL SPECIFICATION - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex	
5	DGT90479	NO DATA AVAILAB LE	010050000002 8 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLIES OF SHESHAM WOOD) 5-PLY	2.440X1. 220MTRX6. 35MM) SPECE/BS- 1088	512 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM TO 07 MM, 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM) AS PER INTERNATIONAL STANDARD. 5. DENSITY OF TIMBER SHESHAM: 100% 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, GENERAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM TO 07 MM, 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM) AS PER INTERNATIONAL STANDARD. 5. DENSITY OF TIMBER SHESHAM: 100% 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,	
6	DGB74638	10504 or A-A-2344	512000240532 8 / WRENCH ADJ STEEL LG 7.500	CIWS TOOL	3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
7	DGE74407	NO DATA AVAILAB LE	035059923357 5 / FENDER		14 / EACH/N						TECHNICAL SPECIFICATION - 2 MEDIUM SIZE: 2 1000 MM LENGHT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		E	MARINE ROUND SISAL WT.32 LBS. OVERALL DIA 2",INTERNAL DIA 8" FOR HARBOUR LAUNCHES		UMBER						<p>¿ 500 MM DIAMETER ¿ 1550 MM CIRCUMFERENCE ¿ MATERIAL EVA FOAM AND NATURAL RUBBER ¿ TYPE: FLANGE TYPE AND ROPE TYPE ¿ ISO 9001 COMPLIANCE ¿ ENERGY ABSORPTION 08 K NM ¿ FORCE RECTION 71 KN <u>GENERAL SPECIFICATION - ¿ MEDIUM SIZE:</u></p> <p>¿ 1000 MM LENGHT ¿ 500 MM DIAMETER ¿ 1550 MM CIRCUMFERENCE ¿ MATERIAL EVA FOAM AND NATURAL RUBBER ¿ TYPE: FLANGE TYPE AND ROPE TYPE ¿ ISO 9001 COMPLIANCE ¿ ENERGY ABSORPTION 08 K NM ¿ FORCE RECTION 71 KN</p>	
8	SGB914 56	NO DATA AVAILAB E	021479013101 2 / BOLT MACHINE STEEL BSF HEX HD SZ 0.625X3. 000X1.250 IN	TURBO DRIVEN FL PUMP	750 / EACH/N UMBER	NO DATA AVILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> DGS ;8060-A CLASS-1 MATERIAL GRADE . EN-4140 <u>GENERAL</u> <u>SPECIFICATION - DGS ;8060-A</u> CLASS-1 MATERIAL GRADE . EN- 4140</p>	
9	DGD940 36	MS-3443- A/DW- 136G	731070512190 4 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	1 / EACH/N UMBER	DW- 136G					<p><u>TECHNICAL SPECIFICATION -</u> brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E- IQBAL KARACHI<u>GENERAL</u> <u>SPECIFICATION - brand name: (i.e.</u> WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI</p>	
10	DGE940 87	A-A-1201, P-P-121, ANSIB74- 18	535000186882 0 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL		110 / SHEET						<p><u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE<u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GLASS GRADE 110-A									
11	DGD92686	NO DATA AVAILABLE	0035500000274 / BOARD KNIFE		15 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952 GENERAL SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952	
12	DGD92687	NO DATA AVAILABLE	0035500000379 / LADLE S/S HANDLE (L-13") WITH WOODEN GRIP,POT WD 3.5".		20 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
13	SGB91547		0266590016032 / WASHER FLAT ROUND MILD STEEL 0.875X0.937X1.875X0.160"(LOCAL)	THK 0.160" APPROX WT PER 100 9 LB 6 OZ	350 / KILOGRAMME						TECHNICAL SPECIFICATION - Size: 0.875 x 0.937 x 1.875 x 0.16" Shape: Round Thickness: 3mm Usage: Used to distribute the load of a threaded fastener GENERAL SPECIFICATION - Size: 0.875 x 0.937 x 1.875 x 0.16" Shape: Round Thickness: 3mm Usage: Used to distribute the load of a threaded fastener	
14	SGB91455	NO DATA AVAILABLE	0214502140608 / BOLT AND NUTS STEEL FOUNDATION TYPE HEX HD SZ 12.000X0.500 INCH		850 / EACH/NUMBER						TECHNICAL SPECIFICATION - length 12 inch thickness ½ inch threaded area 3 inch head HEX PND/Timber Craft Shop (C No 107) specs: DGS 8060 - A, Class - I Material Grade: EN 16 (605 M36) GENERAL SPECIFICATION - length 12 inch thickness ½ inch threaded area 3 inch head HEX PND/Timber Craft Shop (C No 107) specs: DGS 8060 - A, Class - I Material Grade: EN 16 (605 M36)	
15	DGE90367	3000	4510705226414 / SINGLE LEVER SINK MIXER	SINK MIXER	11 / EACH/NUMBER	ARTICLE 3000		FAISAL SANITARY FITTING INDUSTRY G.T ROAD GUJRANWALA.	FASIAL SANITARY FITTING INDUSTR		TECHNICAL SPECIFICATION - ITEM IS USED IN PAINTRY, GALLEY AND SCULLERY WASHING BASIN/SINK. GENERAL SPECIFICATION - ITEM IS USED IN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									Y		PAINTRY, GALLEY AND SCULLERY WASHING BASIN/SINK.	
16	DGE903 23	honey/mk/ 22	597070526728 8 / Honey Comb Hole matt rubber 20"x36"x1/2"		40 / EACH/ NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
17	DGE784 94	large 94.2 ltrs 300 plus	811570525959 7 / coleman ice boxes or EQUIVALENT (LARGE) 94.2 LTRS 300 (PLUS)		6 / EACH/ NUMBER						TECHNICAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM) GENERAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)	
18	DGE911 83	NO DATA AVAILABL E	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	3 / EACH/ NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p>	
19	DGE915 45	NO DATA AVAILABL E	424050508870 5/ CAMOUFLAGE	TO COVER/CAMO FLAGE THE 14.5MM GUNS	3/ EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NETS, SIZE 26 X 26 FT								<p>FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
20	DGE721 73	0472-99- 425-8913	0472UK511799 8 / HYDROSTATI C RELEASE		8 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
21	DGE724 67		041559923140 8 / PLASTIC SHEET METHYL METHACRYLA TE TRANSPAREN T 48"X36"X0. 0625		16 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DGD949 74	S NO 32 MODEL 2018	003550000038 6 / MINCING MACHINE MEDIUM		1 / EACH/N UMBER	2018					TECHNICAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450 GENERAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450	
23	DGE949 73		045159451009 4 / MATTRESS		20 / EACH/N						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FOAM RUBBER WITH COVER 82" X36"X4" (WARRANTY 10 YEARS)		UMBER						null	
24	DGE94709	NO DATA AVAILAB LE	0421500000008 / PERSONAL LOCKER CUM STEEL ALMIRAH		10 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZES: hieght: 6 FEET, 2 INCH width: 3 FEET ,11 INCH depth: 1 FEET, 8 INCH gauge of almira: 22 coating: silver colour lock type : handle lock APRENT EQUIPMENT: ACCOMODATION SPACE <u>GENERAL SPECIFICATION</u> _SIZES: hieght: 6 FEET, 2 INCH width: 3 FEET ,11 INCH depth: 1 FEET, 8 INCH gauge of almira: 22 coating: silver colour lock type : handle lock APRENT EQUIPMENT: ACCOMODATION SPACE	
25	DGE94940		0451594510094 / MATTRESS FOAM RUBBER WITH COVER 82" X36"X4" (WARRANTY 10 YEARS)		20 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
26	DGT94992	NO DATA AVAILAB LE	0100500000018 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM)	SPECEFCATI ON.IM-2581 (E)	800 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 <u>GENERAL SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											: 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
27	DGT949 91	NO DATA AVAILABL E	010000000004 8 / TIMBER SHESHAM SLEEPER WELL SEASONED LOCAL		52 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH IM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL USEGENERAL SPECIFICATION - SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH IM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL USE	
28	DGT950 82	NIL	723070513291 0 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"		15000 / FOOT	NO DATA AVAILAB LE		PK		TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI	TECHNICAL SPECIFICATION -A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required GENERAL SPECIFICATION -A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
29	DGT949 90	NO DATA AVAILABL E	041550000000 9 / FORMICA ENGRAVING WHITE FACE BLACK CORE (1220MMX122 0MMX1.57MM		7 / SHEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness.GENERAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness.	
30	DGD948 51	HS CODE 29161900	156073519303 9 / HEXAMINE	N/A	300 / PACK	N/A	N/A	HOT MEAL TECH CO LTD, 42-54 SINHUNG,	HOT MEAL		TECHNICAL SPECIFICATION - ITEM IS ESSENTIAL FOR MEAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SOLID FUEL TABLETS					SINPYEENG, DANGJI, CHUNGNAM# 343-816 KOREA TELE NO 008241 3632020	TECH		READY TO EAT GENERAL SPECIFICATION - ITEM IS ESSENTIAL FOR MEAL READY TO EAT	
31	DGE947 10	NO DATA AVAILABLE	045150000005 / CLOTH FOR CURTAIN WIDTH 46 INCHES.		142 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
32	DGT949 93	NO DATA AVAILABLE	9330705079704 / PLASTIC FORMICA DULL COLOUR OFF WHITE SIZE 8'X4', THICKNESS 1.50mm		52 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
33	DGE948 21		7110705114888 / master AURA LOW BACK REVOLVING CHAIR	MASTER OFFICE CHAIR	7 / EACH/NUMBER						TECHNICAL SPECIFICATION - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240 GENERAL SPECIFICATION - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240</p>	
34	DGD933 42		003550000045 7 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS		4 / EACH/NUMBER	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			10 SWG								(CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
35	DGD94578		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		7 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
36	DGB76665		0274599104889 / FILE ENGINEER FLAT D-CUT SECOND 12.00 IN		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DGE94925	ASTM D 6413	7210505155171 / FIRE RETARDANT SPRING MATTRESS (L6. 5"XW2"XH6)	MATRESSES FOR BED	10 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.		AL-KHAIR HOUSE-43-T	TECHNICAL SPECIFICATION - MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500-1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL) GENERAL SPECIFICATION - MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500-1800N/MM2 COVERING FABRIC:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL)	
38	DGE946 98		721050515517 2 / FIRE RETARDANT SPRING MATRESS (L6'XW2'XH6)	MATRESSES FOR BED	25 / EACH/ UMBER			LOCAL ADDRESS:AL- KHAIR HOUSE-43-T,AL- KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL- KHAIR HOUSE- 43-T		<u>TECHNICAL SPECIFICATION</u> - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 <u>GENERAL SPECIFICATION</u> - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
39	DGE948 20		721050515517 2 / FIRE RETARDANT SPRING MATRESS (L6'XW2'XH6)	MATRESSES FOR BED	30 / EACH/ UMBER			LOCAL ADDRESS:AL- KHAIR HOUSE-43-T,AL- KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL- KHAIR HOUSE- 43-T		<u>TECHNICAL SPECIFICATION</u> - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 <u>GENERAL SPECIFICATION</u> - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
40	DGE947 02	NO DATA AVAILABL E	593572507749 3 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 35/12, LG 01 METER		50 / METER						<u>TECHNICAL SPECIFICATION - A.</u> Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW- 3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714, Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion. <u>GENERAL SPECIFICATION - A.</u> Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW-3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714, Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion.	
41	DGB943 61	39X131	599978514009 1 / WIRE MESH 11X4FEET	HOOPER DECK	200 / EACH/NUMBER	NO DATA AVAILAB LE		CH		CHINA	TECHNICAL SPECIFICATION - MS, 11X4 FEET GENERAL SPECIFICATION - MS, 11X4 FEET	
42	DGH946 26	GDHBMK4 092040	4010FT100791 8 / STEEL WIRE ROPE (20MM/40M/N ON-ROTATING/GALVANIZED)	9M COMBINED BOAT CRANE	6.75 / EACH/NUMBER	GD.HBM. K.S-40/6-PG&40/9	N/A	GURDESAN GEMI MAK. SAN.TIC.A.S, DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM, KOCAELI, TURKEY TEL # 9.02627E+11 FAX # 9.02627E+11 INFO@GURDESAN.COM. TR		GURDES AN GEMI MAK. SAN.TIC. A.S	TECHNICAL SPECIFICATION - A. Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual GENERAL SPECIFICATION - A. Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual	
43	DGB943 52		028259571209 8 / PIPING COPPER INT DIA 0.50 TH 0.110" SPEC: DG SHIPS 8556		97.84 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DGB943 40		028370571123 0 / ALUMINIUM ALLOY ANGLE EQUAL SIDED	BR 320 D/1976 UNIT OF AVAIL 12-30 FT LG	296 / METER						TECHNICAL SPECIFICATION - SPECIFICATION: FOR CHEMICAL COMPOSITION BS EN 573-3 OF 2019 + A2: 2022 FOR MECHANICAL PROPERTIES BS 755-2 OF 2025 GRADE: ENAW 5083 SIZE:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>LENGTH OF LEG: 2X2 INCHES. THICKNESS: 1/4 INCHES. WEIGHT PER FEET (POUNDS): 1.02 POUNDS. RUNNING LENGTH: 12 TO 30 FEET. GENERAL SPECIFICATION - SPECIFICATION: FOR CHEMICAL COMPOSITION BS EN 573-3 OF 2019 + A2: 2022 FOR MECHANICAL PROPERTIES BS 755-2 OF 2025 GRADE: ENAW 5083 SIZE: LENGTH OF LEG: 2X2 INCHES. THICKNESS: 1/4 INCHES. WEIGHT PER FEET (POUNDS): 1.02 POUNDS. RUNNING LENGTH: 12 TO 30 FEET.</p>	
45	DGB943 58		028370923350 4 / ZINC INGOT 99.995% PURITY LG 16", BREADTH 8", HT 1.75"		231 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005%</u> <u>GENERAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005%</u></p>	
46	DGB943 60		028370923508 7 / GUN METAL INGOT MIN:15KG MAX:20KG CuSn7Pb3Zn3	FOR FOUNDRY SHOP USE	150 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - BS EN 1982 OF 2008 MIN:15 KG MAX: 20 KG CUSN7ZN2pb3-B (CB492K)</u> <u>GENERAL SPECIFICATION - BS EN 1982 OF 2008 MIN:15 KG MAX: 20 KG CUSN7ZN2pb3-B (CB492K)</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(CB492K)									
47	DGB943 55		028350283152 1 / CADMIUM ANODE ROLLED LG 12 WTH 8 TH 3/8		8.6 / EACH/ UMBER						TECHNICAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm GENERAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm	
48	DGB943 67		028359571146 7 / ROD NAVAL BRASS RD DIA 5.12 INCH WT PER FT 76.98 LB		3.3 / METER						TECHNICAL SPECIFICATION - BS EN-12163 OF 1998 DESIGNATION : CW-712R CONDITION: M GENERAL SPECIFICATION - BS EN-12163 OF 1998 DESIGNATION : CW-712R CONDITION: M	
49	DGB943 45		026759521328 0 / PIPING STEEL GALVANIZED SEAMLESS (EXT DIA 1.906		100 / METER						TECHNICAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P-265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0.128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr GENERAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P-265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0.128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr	
50	DGB940 94		026759521328 0 / PIPING STEEL GALVANIZED SEAMLESS (EXT DIA 1.906		110 / METER						TECHNICAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P-265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0.128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr GENERAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P-265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0.128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr	
51	DGB940 95		026759521328 1 / PIPING STEEL GALV SEAMLESS, EXT DIA: 60.3 mm,WALL THKNSS: 3.6 mm,N/BORE: 50.8mm, running length 6 meter	GENERAL USE	60 / METER						TECHNICAL SPECIFICATION - 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships.GENERAL SPECIFICATION - 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships.	
52	DGB943 42		026759521328 1 / PIPING STEEL GALV SEAMLESS, EXT DIA: 60.3 mm,WALL THKNSS: 3.6 mm,N/BORE: 50.8mm, running length 6 meter	GENERAL USE	60 / METER						TECHNICAL SPECIFICATION - 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships.GENERAL SPECIFICATION - 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships.	
53	DGB943 46		026759521328 2 / PIPING STEEL GALVANIZED SEAMLESS	LENGHT BULK SUPPLY EXT DIA 76.1MM(3	100 / METER						TECHNICAL SPECIFICATION - SIZES: EXT DIA 03 INCH, WALL THICKNESS; 0.144" AND NOMINAL BORE: 2.5" (AS PER BR 320 D) RUNNING LENGTH: 06 METERS STANDARD SPECIFICATION 1- BS EN 10216-2 of 2019 2. BS EN ISO 10240 Thickness of 55 um on inside and outside of pipe is recommended	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											FOR GALVANIZATION. <u>GENERAL SPECIFICATION</u> - SIZES: EXT DIA 03 INCH, WALL THICKNESS: 0.144" AND NOMINAL BORE: 2.5" (AS PER BR 320 D) RUNNING LENGTH: 06 METERS STANDARD SPECIFICATION 1- BS EN 10216-2 of 2019 2. BS EN ISO 10240 Thickness of 55 um on inside and outside of pipe is recommended FOR GALVANIZATION.	
54	DGH945 81		021159204455 3 / SHEET STEEL STAINLESS SIZE 3050X1220X3 MM	DEEP FRYER 2PAN	4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MM <u>GENERAL</u> <u>SPECIFICATION</u> - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0. 25MM	
55	DGH946 47		021159204455 3 / SHEET STEEL STAINLESS SIZE 3050X1220X3 MM	DEEP FRYER 2PAN	3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MM <u>GENERAL</u> <u>SPECIFICATION</u> - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0. 25MM	
56	DGH945 60		021159923017 3 / STAINLESS STEEL SHEET SIZE 2500X1250X1 MM	COLD ROLLED TENSILE TESTED ZINC COATED	15 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC) <u>GENERAL SPECIFICATION</u> - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC)	
57	DGH946 45		021159923017 3 / STAINLESS STEEL SHEET SIZE 2500X1250X1 MM	COLD ROLLED TENSILE TESTED ZINC COATED	15 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC) <u>GENERAL SPECIFICATION</u> - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC)	
58	DGB949 34		021450214058 9 / BOLT AND		135 / EACH/N						<u>TECHNICAL SPECIFICATION</u> - material: ms bsw Length of bolt: 38	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NUTS STEEL HEX HD SZ 2.500X0. 875 IN		UMBER						mm length of thread: full thread diameter: 06 mm shape: hex MATERIAL GRADE EN4140GENERAL SPECIFICATION _material: ms bsw Length of bolt: 38 mm length of thread: full thread diameter: 06 mm shape: hex MATERIAL GRADE EN4140	
59	DGB949 39		021450214059 8 / BOLT AND NUTS STEEL HEX HD SZ 3.500X0. 750 IN		315 / EACH/ UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DGB943 65		021259571025 9 / BAR STEEL CARBON HOT ROLLED FLAT 2-1/2"X3/8"WT PER FT3. 19LBS		300 / METER						TECHNICAL SPECIFICATION - Specs: BS970, Grade EN3A/070M20 , Running Length: 06 meterGENERAL SPECIFICATION - Specs: BS970, Grade EN3A/070M20 , Running Length: 06 meter	
61	DGB943 66		021859571185 2 / PIPING STEEL SEAMLESS DIA 5.998" (152.150 MM) TH 0.249"		10 / METER						TECHNICAL SPECIFICATION - STANDARD/SPECIFICATION-ISO- 9329-1 OF 1989 MATERIAL GRADE-TS-430GENERAL SPECIFICATION - STANDARD/SPECIFICATION-ISO- 9329-1 OF 1989 MATERIAL GRADE-TS-430	
62	DGB943 50		028259571203 7 / PIPING COPPER RD. SEAMLESS EXT.DIA.1.732" THK.0.116" SWG11.		42.4 / METER						TECHNICAL SPECIFICATION - Inner Dia: 1.5 inch Outer Dia: 1.732 inch Wall thickness: 0.116 inch Material Copper Grade: ASTM B280 GENERAL SPECIFICATION - Inner Dia: 1.5 inch Outer Dia: 1.732 inch Wall thickness: 0.116 inch Material Copper Grade: ASTM B280	
63	DGB943 51	NO DATA AVAILABL E	028259571204 3 / PIPING COPPER ROUND SEAML EXT DIA 2.232" INT. DIA 2" T= 0.116" WPT	WDG 116	42.4 / METER						TECHNICAL SPECIFICATION - DEFSTAN 02-878 ISSUE 1 OF 2011 Material Designation: CW024A, Condition: R290 RUNING LENGHT OF ITEM IS 12 TO 15 FT AS PER BR 320 D.GENERAL SPECIFICATION - DEFSTAN 02-878 ISSUE 1 OF 2011 Material	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			1000 PSI (LB PER SQ INCH)								Designation: CW024A; Condition: R290 RUNING LENGHT OF ITEM IS 12 TO 15 FT AS PER BR 320 D.	
64	DGB949 36		021459003285 2 / WASHER FLAT ROUND M.S. HARDENED 0.625X1. 125X0.125IN		144 / TEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DGB949 37		021450214065 0 / BOLT AND NUT M S HEX HD SZ 1 X 2.50IN		400 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
66	DGB949 38		021450214062 3 / BOLT AND NUTS STEEL HEX HD SZ 8.000X1. 000 IN		24 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
67	DGB943 44		021259571007 6 / BAR STEEL ALLOY HOT ROLLED	WOODEN LADDER	230 / METER						TECHNICAL SPECIFICATION - Dia: 0.75 inch or 3/4 inch LENGTH 10FT - 15FT as per br-320d SHAPE ROUND PD 970: 2005 Grade 605M36 WEIGHT PER FOOT 1.500 LB GENERAL SPECIFICATION - Dia: 0.75 inch or 3/4 inch LENGTH 10FT - 15FT as per br-320d SHAPE ROUND PD 970: 2005 Grade 605M36 WEIGHT PER FOOT 1.500 LB	
68	DGB943 41		021259571007 8 / BAR STEEL CARBON ALLOY HOT ROLLED RD DIA 1 INCH, WT/FT 2.670 LBS	SPEC.BS 970EN 16 (R)	380 / METER						TECHNICAL SPECIFICATION - PD 970 DIA 1 INCH, WT/FT 2.670 LBS MATERIAL GRADE: 605M36 RUNNING LENGTH: 10 TO 15 FT GENERAL SPECIFICATION - PD 970 DIA 1 INCH, WT/FT 2.670 LBS MATERIAL GRADE: 605M36 RUNNING LENGTH: 10 TO 15 FT	
69	DGH945 77		951550501787 9 / PLATE STEEL HT SZ 7300X2470X01 2MM		4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
70	DGH94653		951570503121 7 / PLATE STEEL FLOOR ROLLED	FOR GENERAL USED	10 / EACH/ UMBER						<p>TECHNICAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTGRAPH ATTACHED</p> <p>GENERAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTGRAPH ATTACHED</p>	
71	DGH94623		951570503121 7 / PLATE STEEL FLOOR ROLLED	FOR GENERAL USED	15 / EACH/ UMBER						<p>TECHNICAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTGRAPH ATTACHED</p> <p>GENERAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTGRAPH ATTACHED</p>	
72	DGH94622		712599129769 4 / ANGLE POSTS STORAGE SHELVING 123		23 / EACH/ UMBER						<p>TECHNICAL SPECIFICATION - Material : Steel/ Aluminum Length: 6 feet to 24 feet Width: 02" to 6" Angle : 90 Degrees (standard) Thickness: ¼" to 1" Size: 2x2x ¼" (50.8 x50.8x6.35mm) 2x4x ¼" (50.8 x101.6.8 x 6.35 mm) 3x3x ½" (76.2 x76.2 x 12.7mm) MATERIAL GRADE SS 400</p> <p>GENERAL SPECIFICATION - Material : Steel/ Aluminum Length: 6 feet to 24 feet Width: 02" to 6" Angle : 90 Degrees (standard) Thickness: ¼" to 1" Size: 2x2x ¼" (50.8 x50.8x6.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											35mm) 2x4x 1/4" (50.8 x101.6.8 x 6.35 mm) 3x3x 1/2" (76.2 x76.2 x 12.7mm) MATERIAL GRADE SS 400	
73	DGB943 64		953599571140 1 / PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 3600 mm X WIDTH 910 mM X 6.4 MM BASE THICKNESS CROSS - SECTION THICKNESS: 8.8MM base thickness 6.4 MM	MATERIAL SPEC.BS 1477HP 30SPEC. ADSP1098A	30 / EACH/N UMBER						TECHNICAL SPECIFICATION - PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 3600 MM X WIDTH 910 MM X 6.4 MM BASE THICKNESS CROSS - SECTION THICKNESS: 8.8MM British Specification 1474 along with Material Grade 6082 and heat treatment condition T6. Embossed pattern height: 2.4 mm ± 0.5 mm above the base metal. basic shape style: b2 pattern no 10 density: 18.95 KG/M2 DEFSTAN 02-840 (NES- 840) GENERAL SPECIFICATION - PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 3600 MM X WIDTH 910 MM X 6.4 MM BASE THICKNESS CROSS - SECTION THICKNESS: 8.8MM British Specification 1474 along with Material Grade 6082 and heat treatment condition T6. Embossed pattern height: 2.4 mm ± 0.5 mm above the base metal. basic shape style: b2 pattern no 10 density: 18.95 KG/M2 DEFSTAN 02-840 (NES- 840)	
74	DGD951 28		734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTME NT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 354 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL. BRAND: INFULLGENERAL SPECIFICATION -280 X 220X40MM WEIGHT: 354 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL. BRAND: INFULL	
75	DGD951 11		734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTME	MESS UTENSILS, OFFICER WARD PNS SHIFA	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 354 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL. BRAND: INFULLGENERAL SPECIFICATION -280 X 220X40MM WEIGHT: 354	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NT PLATES DINNER MESS PLATES								GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL. BRAND: INFULL	
76	DGH943 43		399070533116 3 / MULTI- PURPOSE TROLLEY		3 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
77	DGE951 00	2040	533070513180 6 / RUBBER STRIP	DOOR&HATC HES SEAL	370 / METER	NO DATA AVAILAB LE		PK		ABBASI TRADER S RUBBER STORE PH#2416 152	TECHNICAL SPECIFICATION - 1 GENERAL SPECIFICATION - 1	
78	DGE950 88		834570511986 2 / SATTON CLOTH WHITE	PRESENTATIO N VIP ITEM	140 / METER						TECHNICAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches GENERAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches	
79	DGD948 49	MS-563XD LG	734070511750 1 / MICROWAVE OVEN LG 56 LTRS		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
80	DGE949 10	NO DATA AVAILABL E	8415PK506744 2 / CLOTH PARASHUTE GRAY		450 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
81	DGE913 62		834070508924 9 / CAMOUFLAGE NET, SIZE: 30X25FT FOR COVER 12.7- MM GUNS	TO COVER COMOUFLAG E TE 12.7MM GUNS	5 / EACH/N UMBER						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM : 1. 100% POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH G1 COATED 300 G/SQ METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438 <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM : 1. 100% POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH G1 COATED 300 G/SQ METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438	
82	DGE950 65	R	834570504262 9 / Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter)	ITEM REQUIRED FOR MAKING OF GIFT BOXES	285 / METER						<u>TECHNICAL SPECIFICATION -</u> Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes <u>GENERAL SPECIFICATION -</u> Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes	
83	DGE949 22	SL-130A	534070521963 4 / DEADBOLT LOCK SOCA SL-130A	SNIDS SECURITY SYSTEM	3 / EACH/N UMBER	SL-130A		MECHATRONICS PLOT NO 169 ST-9 SECTOR I 10/3 INDUSTRIAL AREA ISLAMAABAD, PAKISTAN PHONE: 051-4430370 MOBILE: 0333-5513377		MECHAT RONICS PAKISTA N	<u>TECHNICAL SPECIFICATION -</u> Power supply DC 12V Operation current 880 Ma Holding current 250mA Door position detecting points N.C. Bolt position points X Re lock function X Application All type of 90-180 door Delay time 0,3,5,9,Sec (available to set) Mechanic life More then 500,000 time Door open contact Photo coupler contact Overloaded current protection Available Operation temperature Usual:0c/ Long unlocked:500c±50c Range of the door crack Maximum of 10mm Length of bolt 16mm Weight 750g (included wrapping). <u>GENERAL SPECIFICATION -</u> Power supply DC 12V Operation current 880 Ma Holding current 250mA Door position detecting points N.C. Bolt position points X Re lock function X Application All type of 90-180 door Delay time 0,3,5,9,Sec (available to set) Mechanic life More then 500,000	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											time Door open contact Photo coupler contact Overloaded current protection Available Operation temperature Usual:0c/ Long unlocked:500c±50c Range of the door crack Maximum of 10mm Length of bolt 16mm Weight 750g (included wrapping).	
84	DGE948 83		047659000006 2 / GLOVES LEATHER LEFT HAND.		30 / EACH/ UMBER						<u>TECHNICAL SPECIFICATION -</u> Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable <u>GENERAL SPECIFICATION</u> _ Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable	
85	DGE627 35		047450474012 6 / SHAMIANA COMPLETE, SIZE: 15X30- FEET		4 / EACH/ UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES (GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03 KGS WITH WOODEN HANDLE 1.5 FEET LENGTH) <u>GENERAL SPECIFICATION - 1.</u> SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES (GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03 KGS WITH WOODEN HANDLE 1.5 FEET LENGTH)	
86	DGE948 89	0415-2502	041559923145 0 / CORK AND RUBBER SHEET, LG.01 MTR WIDTH 01 MTR THICK 3.175MM. SYNTHETIC RUBBER DEF 22		2 / SHEET						TECHNICAL SPECIFICATION - CORK AND RUBBER SHEET,Item Specification: DEF-22,THIC=3. 175mm,LG=01 MTR WIDTH 01 MTR Synthetic Rubber.GENERAL SPECIFICATION - CORK AND RUBBER SHEET,Item Specification: DEF-22,THIC=3.175mm,LG=01 MTR WIDTH 01 MTR Synthetic Rubber.	
87	DGE948 90	NO DATA AVAILABL E	041559923141 0 / SHEET PLASTIC TRASPARENT LG.48 WD 36TH 0.125 MATERIAL METHYL METHACRYLA TE PLAIN REF DTD 5592		4 / SHEET						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
88	DGE951 03		045159129298 9 / CLOTH COATED PVC FOR FURNITURE UPHOLSTERY COLOUR BLUE WD,50 INCH	FOR SPECS SEE CMD 8	300 / METER						TECHNICAL SPECIFICATION - ISO7617-2 OF 1994 colour blue wd . 50 INCHGENERAL SPECIFICATION - ISO7617-2 OF 1994 colour blue wd .50 INCH	
89	SGB487 33	SKF RMS 12 (31109995 01305)	026959950130 5 / BEARING BALL DEEP GROVE SKF RMS 12 SZ		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			1-1/2X3-3/4X15/16"									
90	DGD78274	NO DATA AVAILAB LE	003154600077 1 / DISH VEGETABLE (DONGA) GOLDEN CRESTED		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - (Ceranic) with (lid) cover GENERAL SPECIFICATION - (Ceranic) with (lid) cover	
91	DGB79214		025159411964 8 / HINGE-BUTT-BRASS-SINGLE		116 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DGE95174		2040PK510105 2 / RUBBER SHEET SIZE WEIGHT: 10-KG, LENGTH: 7-ft, WIDTH: 1-FT, THICKNESS: 3/8-INCH	FENDER	196 / KILOGRAMME						TECHNICAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552 GENERAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552	
93	DGE89542	DEF STAN 59-15/1 BS3858 TYPE 2	0559999011139 / INSULATION SLEEVING ELECTRICAL	GENERAL USE FOR TYPE 21 SHIPS	58 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DGE94885	NO DATA AVAILABLE	4220795055193 / WHISTLE PLASTIC FOR GENERAL SERVICE LIFE JACKET	LIFE JACKET MK-1,ORALLY INFLATED	60 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	SGB57072	SKF 6232	3110009673004 / BALL BEARING 6232MC3 SIZE. 160X290X48 MM		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
96	DGE95105	MIL-P-15280	5640002374828 / INSULATION SLEEVING THERMAL		50 / EACH/NUMBER						TECHNICAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
97	DGE950 91	NO DATA AVAILABL E	593572507749 3 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 35/12, LG 01 METER		180 / METER						UNICELLULAR PLASTIC FOAM. <u>TECHNICAL SPECIFICATION - A.</u> Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW- 3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714, Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion. <u>GENERAL SPECIFICATION - A.</u> Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW- 3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714, Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion.	
98	DGD922 00		773070504888 3 / HALF PLATE 21 CM FOR CAKE PUDDING ETC GOLDEN CRESTED		8 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
99	DGE939 48		834070508791 3 / TENT 40 POUND, ARMY PATT, FLY & FOLD DOUBLE, (JUNGLE GREEN)	GENERAL PERPOSE	8 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE= 6X7 FEET 2. Tent 40 Pounds Army Pattern A. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 3. On inner fly with curtains on sides and walls fitted with pockets 4. The inner fly wall and curtains are made of two	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 5. ACCESSORIES: A. STANDING POLE QTY= 02 NO, B. RICH POLE, QTY= 01 NO, C. IRON PEGS QTY= 12, STANDARD SIZE, C. Rope QTY= 12, STANDARD SIZE, E. Hammer QTY= 01NO (3 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET), F. PACKING BAG QTY= 02 NO. 6. Testing/Acceptance Criteria: CINS/END USER</p> <p><u>GENERAL SPECIFICATION - 1.</u> SIZE= 6X7 FEET 2. Tent 40 Pounds Army Pattern A. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 3. On inner fly with curtains on sides and walls fitted with pockets 4. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 5. ACCESSORIES: A. STANDING POLE QTY= 02 NO, B. RICH POLE, QTY= 01 NO, C. IRON PEGS QTY= 12, STANDARD SIZE, C. Rope QTY= 12, STANDARD SIZE, E. Hammer QTY= 01NO (3 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET), F. PACKING BAG QTY= 02 NO. 6. Testing/Acceptance Criteria: CINS/END USER</p>	
100	DGE950 86	R	834570504262 9 / Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter)	ITEM REQUIRED FOR MAKING OF GIFT BOXES	85 / METER						<p><u>TECHNICAL SPECIFICATION -</u> Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes <u>GENERAL SPECIFICATION -</u> Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes	
101	DGD92160		773070504806 1 / SAUCER TEA GOLDEN CRESTED		24 / EACH/ UMBER						<u>TECHNICAL SPECIFICATION -</u> MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) <u>GENERAL SPECIFICATION -</u> MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
102	DGD78272		734070506044 8 / DESERT SPOON		12 / EACH/ UMBER						<u>TECHNICAL SPECIFICATION -</u> Material S/S 304 FOOD GRADE NON Magnetic (LOCAL) <u>GENERAL SPECIFICATION -</u> Material S/S 304 FOOD GRADE NON Magnetic (LOCAL)	
103	DGE74694	NO DATA AVAILABL E	834050503926 2 / QANAT COMPLETE SIZE 18.X 7. OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		20 / EACH/ UMBER						<u>TECHNICAL SPECIFICATION -</u> Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON,BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED. <u>GENERAL SPECIFICATION -</u> Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH) 100% COTTON NIWAR, BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
104	DGD781 51		734070506081 3 / PASTRY FORK		12 / EACH/ UMBER						<u>TECHNICAL SPECIFICATION -</u> Material S/S 304 FOOD GRADE NON Magnetic (LOCAL) <u>GENERAL</u> <u>SPECIFICATION -</u> Material S/S 304 FOOD GRADE NON Magnetic (LOCAL)	
105	DGD927 46	pp-01	732070526966 6 / POTATO PEELER		1 / EACH/ UMBER	pp-01					<u>TECHNICAL SPECIFICATION -</u> capacity: 15kg, power: 1500w, voltage: 220v/50hz, net weight: 62kg, dimension: 18x30x26 inch, heavy duty full load 1.5hp motor <u>GENERAL</u> <u>SPECIFICATION -</u> capacity: 15kg, power: 1500w, voltage: 220v/50hz, net weight: 62kg, dimension: 18x30x26 inch, heavy duty full load 1.5hp motor	
106	DGE830 85	N/A	933070518127 9 / PLASTIC SHEET	GENERAL ITEM	5 / ROLL			LOCAL MARKET		GENERA L ITEM	<u>TECHNICAL SPECIFICATION -</u> PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm <u>GENERAL</u> <u>SPECIFICATION -</u> PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	