

PAKISTAN NAVY
TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 14-01-2026

TERMS & CONDITION

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT".

2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.

3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

TENDER BULLETIN

DATE & TIME 12/31/25 1:21 PM INVITATION TO TENDER TO BE OPENED ON 1/14/2 10:00 AM AND ITEM REQ BY

CONDITIONS

NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.

FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.

LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGT94058	NO DATA AVAILABL E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTABLISHMENT	9 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		TECHNICAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM GENERAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	
2	DGD94148	10755-36	731070534478 5 / 107SS RAYS COOKING CABINET		1 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - Weight 65 kgs Brands rays Top Cover METAL TOP COOKING CABINET 5 Burner Features: • 5 Burner Gas Burner • Panel & Top • Heavy Grates • Big Size Burners • Double Door • Metal Top Safely Packed GENERAL SPECIFICATION - Weight 65 kgs Brands rays Top	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Cover METAL TOP COOKING CABINET 5 Burner Features: • 5 Burner Gas Burner • Panel & Top • Heavy Grates • Big Size Burners • Double Door • Metal Top Safely Packed	
3	DGE92828	NO DATA AVAILABLE	041359923875 5 / MAT FLOOR RUBBER LG. 18. WD.(LTR NO E-I/4927-A/1082 DT221096)		100 / METER						<u>TECHNICAL SPECIFICATION -</u> Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4-6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black. <u>GENERAL SPECIFICATION -</u> Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4-6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black.	
4	DGE84783	04769430557, BS2992TA BLE8ITEM 8/5	047659943055 7 / BRUSH VARNISH TYNEX FIBER FLAT SQUIRE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	101 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 2.</u> Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable <u>GENERAL SPECIFICATION -2.</u> Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
5	DGB75957		028359571143 7 / ROD NAVAL BRASS HEX A F 1.67 INCH		6 / METER						<u>TECHNICAL SPECIFICATION -</u> BSEN-12163, MATERIAL GRADE CW712R, MATERIAL CONDITION: M WEIGHT: 9.010 LB/FT AS PER BR-320D. RUNNING LENGTH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Minimum 8 foot. <u>GENERAL SPECIFICATION</u> - BSEN-12163, MATERIAL GRADE CW712R, MATERIAL CONDITION: M WEIGHT: 9.010 LB/FT AS PER BR-320D. RUNNING LENGTH: Minimum 8 foot.	
6	DGT94057	NO DATA AVAILABLE	0100501000118 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE		320 / SQ FEET						<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) <u>GENERAL SPECIFICATION</u> - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
7	DGE91642	NIL	0350599425062 / ROPE SISAL, 03-strands , HAWSERLAID, DIA: 5/8 INCH (16-MM)		150 / METER						<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004 OR OF LATEST VERSION, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK/ RN/ RELATED COUNTRY), 8. LENGTH PER COIL: 120 FATHOM. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLYODS/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM: M/S COTESI <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004 OR OF LATEST VERSION, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK/ RN/ RELATED COUNTRY), 8. LENGTH PER COIL: 120 FATHOM. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYDS/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM: M/S COTESI	
8	SGB92807	9104923 (5110-99-910-4923)	0274709104923 / FILE ENGINEER ROUND D-CUT BASTARD LG 6.00IN DIA 6MM.		110 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
9	DGB91396		0214590131414 / BOLT MACHINE, THREAD SERIES: BSF, MEDIUM CLASS, HEXAGON, SIZE (0.875X3.500X1.750		165 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - HEAD: HEXAGON, THREAD SIZE: 7/8 INCH, NOMINAL LENGTH: 3 1/2 INCH, LENGTH OF THREAD: 1 3/4 INCH. SPECIFICATION: DEF STAN 02-862 Part 2, Issue 3 Class III, MATERIAL GRADE: BS EN 10269 42CrMo5-6 (OR) BS EN 10269 40CrMoV4-6 <u>GENERAL SPECIFICATION</u> - HEAD:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH)								HEXAGON, THREAD SIZE: 7/8 INCH, NOMINAL LENGTH: 3 1/2 INCH, LENGTH OF THREAD: 1 3/4 INCH. SPECIFICATION: DEF STAN 02-862 Part 2, Issue 3 Class III, MATERIAL GRADE: BS EN 10269 42CrMo5-6 (OR) BS EN 10269 40CrMoV4-6	
10	DGE91070	NO DATA AVAILABLE	0330595713260 / TWINE COTTON CHALK LINE G/PURPOSE MIN BKG STRG25 LB20YDS LG; DIA 1.5mm	GENERAL PURPOSE BS 2019	50 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 6125 of 1981 GENERAL SPECIFICATION - BS 6125 of 1981	
11	DGB92838		0214590035651 / BOLT MACHINE STEEL BSW HEX HD SZ 1.000X0.375 IN		21 / TEN						TECHNICAL SPECIFICATION - MATERIAL GRADE EN 4140 GENERAL SPECIFICATION - MATERIAL GRADE EN 4140	
12	SGB93209		0276799105832 / SCRAPER ENGINEER LG 6"		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
13	DGE87456		0330595713266 / TWINE HEMP PACKING MEDIUM 3STRD POLISHE MIN BKG STRGTH 100LB		10 / KILOGRAMME						TECHNICAL SPECIFICATION - (1) 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											harmful substances & making it safe for various uses. <u>GENERAL SPECIFICATION</u> - (1) 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses.	
14	DGD69268	NO DATA AVAILABLE	003154600077 1 / DISH VEGETABLE (DONGA) GOLDEN CRESTED		40 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - (Ceranic) with (lid) cover <u>GENERAL SPECIFICATION</u> - (Ceranic) with (lid) cover	
15	SGB92801	TPI 14	530571503899 6 / SCREW SELF TAPPING S/STEEL CSK HD 14 TPISZ 2.000X0.250" LOCAL	REPAIR FOR GRP BOATS	600 / TEN						<u>TECHNICAL SPECIFICATION</u> - material: stainless steel grade: 316 HD 14 Diamension: diameter: 14mm Thread per inch: 2.000x0.250" <u>GENERAL SPECIFICATION</u> - material: stainless steel grade: 316 HD 14 Diamension: diameter: 14mm Thread per inch: 2.000x0.250"	
16	DGB91163		530699124362 8 / BOLT MACHINE ISO STEEL HEX HD SIZE 16X5X38 MM	FASTENINGS, BOLTS AND STUDS.	120 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - SIZE: 16X5X38 MM, MATERIAL: MS, Grade AISI 4140, BOLT HEAD HEXAGON <u>GENERAL SPECIFICATION</u> - SIZE: 16X5X38 MM, MATERIAL: MS, Grade AISI 4140, BOLT HEAD HEXAGON	
17	DGE94088		535000235013 7 / PAPER ABRASIVE 9"		160 / SHEET						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			X11" WATER PROOF MATERIAL GLASS GRADE 2/0								AVAILABLE	
18	DGH94330		6145705057679 / CABLE ELEC 4COR O/D-52MM N/STRAND-36 S/D-2MM C/D-18MM 280AMP		250 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
19	DGE94090	0413-2184	5970999239664 / TAP INSULATION ELECT ADHESIVE PLASTIC RED W1	FOR RED PHASE	60 / EACH/NUMBER						TECHNICAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing GENERAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing	
20	DGE94091	CM6538-000	5970705044352 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		60 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
21	DGE91641	NO DATA AVAILABLE	0330500000018 / POPLIN CLOTH TARTAN GREEN WIDTH 36	GENERAL USE FOR BATTERIES OF S/MS	110 / YARD	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - material composition of 100% cotton WIDTH = 36" GENERAL SPECIFICATION - material composition of 100% cotton WIDTH = 36"	
22	DGE93918	NO DATA AVAILABLE	0413500000134 / EAR		50 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	DEFENDER LARGE SIZE			LE					<u>SPECIFICATION - NO DATA AVAILABLE</u>	
23	DGE93945		8340705087914 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIES)	OLIVE GREEN WATERPROOF INNER LINNING OF,	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS: PSG-600, 2. SIZE/ DIMENSION: A. LENGTH: 50 FEET (±0.5 FEET), B. WIDTH: 20 FEET (±0.2 FEET), C. RIDGE HEIGHT: 12 TO 14 FEET, D. SIDE WALL HEIGHT: 7 TO 8 FEET (DETACHABLE ALL ROUND WITH SUITABLE DOORS), 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. SPECIFICATION OF CANVAS COTTON: A. CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF FIRE PROOF. B. OUTER FOLDS: WATER PROOF, C. INNER FOLDS: SHEETING CLOTH & CANVAS DYED, D. NO OF DOORS: 02 E. NO OF WINDOW: 08 F. TAPE NEWAR: CANVAS COTTON, G. NO OF FOLDS: 02 5. LIST OF ACCESSORIES: A. UPRIGHT POLES: 04 QTY B. RIDGE POLES: 03 QTY C. ROPES: 34 QTY (STANDARD SIZE) D. PEGS: 34 QTY (STANDARD SIZE) E. HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. DIAMETER OF POLES: 40 MM G. GAUGE OF POLES: 16 GAUGE H. LENGTH OF PINS: 12 INCH J. FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET K. PACKING: 02 QTY <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS: PSG-600, 2. SIZE/ DIMENSION: A. LENGTH: 50 FEET (±0.5 FEET), B. WIDTH: 20 FEET (±0.2 FEET), C. RIDGE HEIGHT: 12 TO 14 FEET, D. SIDE WALL HEIGHT: 7 TO 8 FEET (DETACHABLE ALL ROUND WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SUITABLE DOORS), 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. SPECIFICATION OF CANVAS COTTON: A. CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF FIRE PROOF. B. OUTER FOLDS: WATER PROOF, C. INNER FOLDS: SHEETING CLOTH & CANVAS DYED, D. NO OF DOORS: 02 E. NO OF WINDOW: 08 F. TAPE NEWAR: CANVAS COTTON, G. NO OF FOLDS: 02 5. LIST OF ACCESSORIES: A. UPRIGHT POLES: 04 QTY B. RIDGE POLES: 03 QTY C. ROPES: 34 QTY (STANDARD SIZE) D. PEGS: 34 QTY (STANDARD SIZE) E. HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. DIAMETER OF POLES: 40 MM G. GAUGE OF POLES: 16 GAUGE H. LENGTH OF PINS: 12 INCH J. FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET K. PACKING: 02 QTY	
24	DGT94170	NO DATA AVAILABLE	0100500000039 / TIMBER FIR HIMALAYA/ SPRUCE SLEEPER, WELL SEASONED LOCAL/ IMPORTED, SIZE: L=8'-15', W=8"-14", h=4"-10"	(3.05MTR X254 MM X127 MM) SPECE/PSG 69	33 / CUBIC FOOT	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - SPECS=</u> PSG/69 well-seasoned wood, moisture content = 12% ± 02%, <u>GENERAL SPECIFICATION - SPECS=</u> PSG/69 well-seasoned wood, moisture content = 12% ± 02%,	
25	DGD92684	NO DATA AVAILABLE	00355000000318 / Aluminium covers for utensil cooking (Large) O/D 25.50" TH 10		53 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SWG.								and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers. <u>GENERAL SPECIFICATION</u> - Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.	
26	DGE83640		9330PK5124258 / PLASTIC COVER TRANSPARENT FOR MODLLES OF 12' (SEE COMD F8)		20 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
27	DGD94143	XG1910200103	7310705344787 / CHARCOAL GRILL		1 / EACH/NUMBER	N/A					<u>TECHNICAL SPECIFICATION</u> - Color BLACK Grill Size MEDIUM MPN XG1910200103 Item Depth 44.88 IN (114 CM) (114 CM) Fuel Type CHARCOAL Brand UNBRANDED Type PORTABLE Griddle Material STEEL Manufacturer WARRANTY 2 YEARS Item Height 42.32 in (107.5 cm) (107.5 cm) Model XG1910200103 Country/Region of Manufacture i United States Item Width 26.38 in (67 cm) (67 cm) UPC 1 Does not apply / Item Weight 36 lbs (16.33 kg) <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - Color BLACK Grill Size MEDIUM MPN XG1910200103 Item Depth 44.88 IN (114 CM) (114 CM) Fuel Type CHARCOAL Brand UNBRANDED Type PORTABLE Griddle Material STEEL Manufacturer WARRANTY 2 YEARS Item Height 42.32 in (107.5 cm (107.5 cm) Model XG1910200103 Country/Region of Manufacture i United States Item Width 26.38 in (67 cm) (67 cm) UPC 1 Does not apply / Item Weight 36 lbs (16.33 kg)	
28	DGE94066		9330705300654 / telic sheet (TRANSPARENT sheet) THICKNESS: 0.35MM WIDTH:54 INCH LENGTH: 25-30 meter		166 / SQ FEET	sheet					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
29	DGD94147		7310705344786 / HOT/ COLD BAIN MARIE		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
30	DGE88603	ALM7140A	8415735139736 / DIVING GLOVES	DIVING	15 / PAIR	ISF PROLINE		OC		TIWAN	TECHNICAL SPECIFICATION - SOFT,THICK RUBBER, SIZE: NORMAL SIZEGENERAL SPECIFICATION - SOFT,THICK RUBBER, SIZE: NORMAL SIZE	
31	DGE65915	SA9-27020	6260011960136 / LIGHT, CHEMILUMINESCENT 6INCH YELLOW	REPLENISHMENT LIGHT	286 / EACH/NUMBER			CYALUME TECHNOLOGIES SA 295 R MAYOR DE MONTRICHER AIX EN PROVENCE FRANCE AIX EN PROVENCE CEDEX 04 42 37 17 80 04 42 37 17 99 XFARCY@CYALUME.COM WWW.CYALUME.COM		CYALUME TECHNOLOGIES	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
32	DGB78617	VE-SB-1168	5450505332781 / SIDE BRACKET 3 10		105 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
33	DGE89093	611-055	402079515314 3 / ROPE NYLON 16MM WHITE MULTIPLAIT (FLEXABLE AND HIGH	TAL SHIP SAILING RIG	100 / METER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT.	UK		<u>TECHNICAL SPECIFICATION - 1.</u> 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG <u>GENERAL SPECIFICATION - 1.</u> 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG	
34	DGE85052	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	10 / EACH/N UMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021- 34302153-4	GERMAN Y		<u>TECHNICAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
35	DGH946	GDHBMK4	4010FT100791	9M COMBINED	6.75 /	GD.HBM.	N/A	GURDESAN GEMI MAK.	GURDES		<u>TECHNICAL SPECIFICATION - A.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	26	092040	8 / STEEL WIRE ROPE (20MM/40M/N ON-ROTATING/GALVANIZED)	BOAT CRANE	EACH/NUMBER	K.S-40/6-PG&40/9		SAN.TIC.A.S, DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM, KOCAELI, TURKEY TEL # 9.02627E+11 FAX # 9.02627E+11 INFO@GURDESAN.COM.TR	AN GEMI MAK. SAN.TIC.A.S		Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual <u>GENERAL SPECIFICATION - A.</u> Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual	
36	DGT88974	NO DATA AVAILABLE	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTABLISHMENT	25 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETANI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		<u>TECHNICAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM <u>GENERAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	
37	DGE89407	B2315512	4710705177960 / FLEXIBLE PIPE 1 INCH DIA	CNA LAN NETWORK	400 / METER			ADAMJEE PAKISTAN	ADAMJEE PAKISTAN		<u>TECHNICAL SPECIFICATION -</u> ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter <u>GENERAL SPECIFICATION - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE</u> Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter	
38	DGB73958	IC3553, BS3594PT1	0276789106635 / WRENCH PIPE CAPACITY 1/8" TO 1" LG OVERALL 10"		22 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
39	DGB74731		0277502771506 / SPANNER D.E D.J BSW 0.25X0.3125"		12 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
40	DGE89409	NO DATA AVAILABLE	0413599238755 / MAT FLOOR RUBBER LG. 18. WD.(LTR NO E-I/4927-A/1082 DT221096)		10 / METER						<u>TECHNICAL SPECIFICATION - Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4-6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black.</u> <u>GENERAL SPECIFICATION - Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4-6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
41	DGE894 12		047659943041 4 / BRUSH PAINT SQ EDGE S/TOOL 8 STCL MRKG EXP DIA 1.125" LG 2.8"		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DGE836 41	NO DATA AVAILABL E	046159000648 0 / PAINT ROLLER, LENGTH= 7- INCH, DIA= 2- INCH, C/W SHEEP SKIN COVER AND HANDLE STEEL FRAME, WOODEN HANDLE	BLST PAINT UNDER WATER HULL	74 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip GENERAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip	
43	DGB827 43	NO DATA AVAILABL E	026759923510 0 / ELBOW ROUND BLACK 1.50 INCH		80 / EACH/N UMBER						TECHNICAL SPECIFICATION - ID: 1.5 INCH OD: 48.3 MM WALL THICKNESS: 3.7 MM GRADE. ASTM 106 GRADE B. SCHEDULE: 40 Material: mild steel Specs: (galvanized) BS 1740/71,1387, grade: corrosion resisting ferrous alloy Nominal bore= 40mm/ 1.50" without internal thread, wall thickness: 6mm, external dia: 52mm Running length: 5.5 inch Origin: Pakistan / China GENERAL SPECIFICATION - ID: 1.5 INCH OD: 48.3 MM WALL THICKNESS: 3.7 MM GRADE. ASTM 106 GRADE B. SCHEDULE:40 Material: mild steel Specs:(galvanized) BS 1740/71, 1387, grade: corrosion resisting ferrous alloy Nominal bore= 40mm/ 1.50" without internal thread, wall thickness: 6mm, external dia: 52mm Running length: 5.5 inch Origin: Pakistan / China	
44	DGB838 74	BS 1421	027570910547 4 / PICK HEAD		12 / EACH/N						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DIGGING TYPE CHISEL AND POINT 07LBS EYE 3" X3"		UMBER						SPECIFICATION - NO DATA AVAILABLE	
45	DGB739 47	(FLUTE LG 2.250 INCH)	027279923788 4 / DRILL-TWIST-MORSE TAPER SK-1 (H/S/STEEL) DIA 15/64"-O/LG-5.438		15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DGB739 55	NO DATA AVAILABLE	027378000942 6 / BLADE HACKSAW SIZE 12IN TP1-32		25 / DOZEN	Eclipse Plus, Griffon, (or any other brand)					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
47	DGB847 31	NO DATA AVAILABLE	027259272007 2 / DRILL-TWIST-TAPER-SHANK-HSS-9MM		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - size: 9 mm material: hss Hardness HRC65-66. hss jobber drill-general purpose a100, 9.00mm GENERAL SPECIFICATION - size: 9 mm material: hss Hardness HRC65-66. hss jobber drill-general purpose a100, 9.00mm	
48	DGE813 52		033059571325 2 / TWINE NYLON MACKEREL LINE 3 STRD MIN BKG STRENGTH 140 LBS.		49 / EACH/NUMBER						TECHNICAL SPECIFICATION - Dimensions: 3 STRD 2mm x 218 yard BS 6125 OF 1981 TABLE 12 GENERAL SPECIFICATION - Dimensions: 3 STRD 2mm x 218 yard BS 6125 OF 1981 TABLE 12	
49	DGB771 96	SKF 6322	026979950132 9 / BEARING, BALL, JOURNAL, S/ROW, C/MEDIUM SERIES SZ 110X240X50MM	DEF SPEC.4A & BS292 REF. BRM MEDIUM FIT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
50	DGB75833	OUT/BODY 1/8" PLATE. INNER 16 GAUG	0248591296147 / SAFE STEEL FITTED WITH COMB 6 LEVER EXT DIM SZ 28X21X16 5/8"	SZ 710X535X425 MM(27-3/4X21-1/16X16-3/4"	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required GENERAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required	
51	DGB73561	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE,DOOR NOT LESS THAN3/8"THK-	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03 GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03	
52	DGB73045	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE,DOOR NOT LESS THAN3/8"THK-	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03 GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03	
53	DGB73924	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE,DOOR NOT LESS THAN3/8"THK-	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03 GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03	
54	DGB77812	BS1780 / EN 837-1 NS 100	0242599420447 / GAUGE-PRESSURE INDICATING DIAL (0-100PSI)		5 / EACH/NUMBER	111.10					TECHNICAL SPECIFICATION - NOMINAL SIZE (NS): 100 MM (4 INCH) CONNECTION LOCATION: LOWER MOUNT (RADIAL) MATERIAL: STEEL BLACK MEASURING ELEMENT: BOURDON TUBE, C-TYPE OR HELICAL GENERAL SPECIFICATION - NOMINAL SIZE (NS): 100 MM (4 INCH) CONNECTION LOCATION: LOWER MOUNT (RADIAL) MATERIAL:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											STEEL BLACK MEASURING ELEMENT: BOURDON TUBE, C-TYPE OR HELICAL	
55	DGD70664		0032500032009 / KNIVES FISH EATING FOR OCNS		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL S/S 304 /316 FOOD GRADE NON MAGNETIC (LOCAL) PN CREST ENGRAVED ON KNIFE STAINLESS STEEL M/GRADE SS 304/316 (FOOD GRADE) LENGTH 21 TO 23 CM GENERAL SPECIFICATION - MATERIAL S/S 304 /316 FOOD GRADE NON MAGNETIC (LOCAL) PN CREST ENGRAVED ON KNIFE STAINLESS STEEL M/GRADE SS 304/316 (FOOD GRADE) LENGTH 21 TO 23 CM	
56	DGE72300	C-134	0851580000076 / DEFENCER EAR C-134 62TD		57 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DGE79829	DEF STAN 59-15/1 BS3858 TYPE 2	0559999011139 / INSULATION SLEEVING ELECTRICAL	GENERAL USE FOR TYPE 21 SHIPS	358 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DGE78220		4220505101929 / LIFE JACKETS (Orange/Camo uflage)	FOR PERSONNAL SAFETY,PNS QASIM,PRIZE ENT	65 / EACH/NUMBER						TECHNICAL SPECIFICATION - (1) Buoyancy: 7.5kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003 GENERAL SPECIFICATION - (1) Buoyancy: 7.5 kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003	
59	DGB85595	skf-3308/A122	3110002273276 / BEARING		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		6-1-9	BALL ANNULAR SZ 40.00X90.00MMX1.4375 IN		UMBER						null	
60	DGB734 35	NSK 6313ZZ	311078503351 5 / BEARING BALL DEEP GROVE NSK 6313ZZ 065X140X33MM O-083	CARGO JP-5 OIL PUMP	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DGB794 61	NO DATA AVAILABLE	512073100058 2 / SOCKET SPANNER STANDARD 10-32MM 26PCSSET		2 / SET						TECHNICAL SPECIFICATION - a. Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21, 22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16) Sliding bar (10 inches) Flip drive ratchet c. Drive type: 1/2" square drive d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chrome GENERAL SPECIFICATION - a. Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21, 22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16) Sliding bar (10 inches) Flip drive ratchet c. Drive type: 1/2" square drive d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chrome	
62	DGE875 77	NO DATA AVAILABLE	562050504233 5 / TILES CERAMIC GLAZED COLOUR WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")	DECK COVERING	400 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
63	DGE723	NO DATA	594070508869	GENERAL	5 /						TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	17	AVAILABLE	4 / RAYCHEM HEAT SHRINK TUBE MWTM 140/42 1000MM LENGTH	PURPOSE ITEM ELECTRIC CABLES	EACH/NUMBER						DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DGD95297	MS-3443-A/DW-136G	7310705121904 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	1 / EACH/NUMBER	DW-136G					TECHNICAL SPECIFICATION - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI GENERAL SPECIFICATION - brand name: (i.e. WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI	
65	DGE88905	NO DATA AVAILABLE	0330780000214 / CLOTH CLEANING 6X6 44-6729 133C		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
66	DGE85289	NO DATA AVAILABLE	0421500000008 / PERSONAL LOCKER CUM STEEL ALMIRAH		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SIZES: hieght: 6 FEET, 2 INCH width: 3 FEET ,11 INCH depth: 1 FEET, 8 INCH gauge of almira: 22 coating: silver colour lock type : handle lock APRENT EQUIPMENT: ACCOMODATION SPACE GENERAL SPECIFICATION - SIZES: hieght: 6 FEET, 2 INCH width: 3 FEET ,11 INCH depth: 1 FEET, 8 INCH gauge of almira: 22 coating: silver colour lock type : handle lock APRENT EQUIPMENT: ACCOMODATION SPACE	
67	DGE89087	NO DATA AVAILABLE	04325000000026 / HELMET PROTECTIVE DESPATCH RIDER SIZE 6 5/8"		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
68	DGE95346	NO DATA AVAILABLE	031050000000 7 / CANVAS COTTON WHITE (WD: 36 INCH)	SPEC.NO:PS-319	190 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - a.</u> SIZE: (1). WIDTH 36 INCH (2) WEIGHT 18 OZ PER SQ YARD, (3) ROT PROOFED & WATER PROOF (4) PS- 319 OF 1986 TABLE-1 VARIETY NO-5 (5) ADVANCE SAMPLE TO BE APPROVED BY CINS <u>GENERAL SPECIFICATION - a.</u> SIZE: (1). WIDTH 36 INCH (2) WEIGHT 18 OZ PER SQ YARD, (3) ROT PROOFED & WATER PROOF (4) PS- 319 OF 1986 TABLE-1 VARIETY NO-5 (5) ADVANCE SAMPLE TO BE APPROVED BY CINS	
69	DGE65115	NO DATA AVAILABLE	834050503926 2 / QANAT COMPLETE SIZE 18.X 7. OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		21 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON,BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED. <u>GENERAL SPECIFICATION -</u> Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH) 100% COTTON NIWAR, BRASS EYELET WITH STRENGTHENING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
70	DGE95345	NO DATA AVAILABLE	8340705014084 / TENT FOR CPOS/SAILORS, WT= 120 LBS, ALONG WITH COMPLETE ACCESSORIES		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM : 1. SIZE/ DIMENSION A. LENGTH: 10 FEET, B. WIDTH: 10 FEET C. WALL HEIGHT: 07 FEET, D. TENT WALL: MADE OUT OF 400/G M2 2. OTHER SPECIFICATION: A. CANVAS COTTON: ROT PROOF, WATER PROOF, AND VAT DYED CANVAS, B. INNER LINING: MADE OUT OF 180-200/G M2, C. TENT PROOF: MADE OUT OF 450/G M2 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. LIST OF ACCESSORIES A. STANDARD POLE: 03 X QTY B. RICH POLE: 02 X QTY, C. PEGS IRON: 12 X QTY (STANDARD SIZE) D. ROPES: 12 X QTY (STANDARD SIZE) E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. PACKING BAG: 02 QTY GENERAL SPECIFICATION - SPECIFICATION OF ITEM : 1. SIZE/ DIMENSION A. LENGTH: 10 FEET, B. WIDTH: 10 FEET C. WALL HEIGHT: 07 FEET, D. TENT WALL: MADE OUT OF 400/G M2 2. OTHER SPECIFICATION: A. CANVAS COTTON: ROT PROOF, WATER PROOF, AND VAT DYED CANVAS, B. INNER LINING: MADE OUT OF 180-200/G M2, C. TENT PROOF: MADE OUT OF 450/G M2 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. LIST	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OF ACCESSORIES A. STANDARD POLE: 03 X QTY B. RICH POLE: 02 X QTY, C. PEGS IRON: 12 X QTY (STANDARD SIZE) D. ROPES: 12 X QTY QTY (STANDARD SIZE) E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. PACKING BAG: 02 QTY	
71	DGE89076	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	25 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					<u>TECHNICAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. <u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
72	DGT844 18	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	992 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											w/shop GENERAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop	
73	DGD724 87	NO DATA AVAILABL E	024750000001 9 / GAS BURNER WITH HANDLE VALVE FITTED IN A ROUND STEEL FRAME TH 6mm,H 8" WITH 20FT RUBBER TUBE		3 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - ROUND STEEL FRAME Thickness: 6MM, Hieght: 8" WITH 20FT RUBBER TUBE GENERAL SPECIFICATION - ROUND STEEL FRAME Thickness: 6MM, Hieght: 8" WITH 20FT RUBBER TUBE	
74	DGT863 34	NO DATA AVAILABL E	041550000000 9 / FORMICA ENGRAVING WHITE FACE BLACK CORE (1220MMX122 0MMX1.57MM		13 / SHEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness. GENERAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness.	
75	DGE854 56	NO DATA AVAILABL E	933070505435 4 / PLASTIC SHEET BLACK	FOR PN CREST	5 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH 1220MM WIDTH 610MM THICKNESS 12MM								AVAILABLE	
76	DGE836 37		933099224609 0 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4. X0.60 to 0.70 MM	GENERAL USE	16 / SHEET						<u>TECHNICAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 <u>GENERAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
77	DGE832 01		933099224609 0 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4. X0.60 to 0.70 MM	GENERAL USE	33 / SHEET						<u>TECHNICAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 <u>GENERAL SPECIFICATION -</u> Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
78	DGD821 91		003554600061 7 / Pot Aluminum 6/5" With Cover ALUMINUM FOOD GRADE (LEAD FREE) OD: 40 TO 45 CM H:18 TO 18.5 CM THICKNESS: 10 GUAGE		4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> 10 Gauge Aluminum Aluminum Food Grade(Lead Free) od: 40 to 45 cm h: 18 to 18.5 cm thickness: 10 guage <u>GENERAL SPECIFICATION -</u> 10 Gauge Aluminum Aluminum Food Grade(Lead Free) od: 40 to 45 cm h: 18 to 18.5 cm thickness: 10 guage	
79	DGD898 31		003554600047 5 / BUCKET PLASTIC (MEDIUM) WITH COVER FOR DISPOSAL OF PANTRY GARBAGE		30 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
80	DGE890 88	MIL-I- 46852	597000177162 7 / TAPE INSULATION		180 / ROLL	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> PVC TAPE OSAKA Tape insulation electrical ADHES plastic BLK WD 19	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ELECTRICAL NOMINAL WD 1.5								mm thickness 0.2mm <u>GENERAL SPECIFICATION</u> - PVC TAPE OSAKA Tape insulation electrical ADHES plastic BLK WD 19 mm thickness 0.2mm	
81	DGE722 69	RB10002 local	615070526408 5 / INSULATION RUBBER MAT		120 / FOOT	NA					<u>TECHNICAL SPECIFICATION</u> - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm. <u>GENERAL SPECIFICATION</u> - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm.	
82	DGB812 04	4992	402079515312 0 / DOUBLE SIDED TAPE (SIZE 12MMX50M)	TALL SHIP SAILING RIG	50 / EACH/N UMBER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT. COM WWW. BASELINEHARDWARE. CO.UK	BASELIN E MARINE PRODUC TS LTD 10 APPLE INDUSTRI AL E		<u>TECHNICAL SPECIFICATION</u> - LIGHT,NON YELLOWING ACRLIC TAPE WITH VERY HIGH ADHESION,SIZE: 12mmx50m <u>GENERAL SPECIFICATION</u> - LIGHT,NON YELLOWING ACRLIC TAPE WITH VERY HIGH ADHESION,SIZE: 12mmx50m	
83	DGB746 13	0140	403079515388 7 / SPLIT THIMBLES (316 STAINLESS STEEL)10MM	TAL SHIP SAILING RIG	14 / EACH/N UMBER			BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST,HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE. MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE. CO.UK	UK		<u>TECHNICAL SPECIFICATION</u> - SOURCE OF AVAILABILITY ; BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE. SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX;+44(0) 1489578835. <u>GENERAL</u> <u>SPECIFICATION</u> - SOURCE OF AVAILABILITY ;BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB;WWW.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX;+44(0) 1489578835.	
84	DGE821 08	SA9-27020	626001196013 6 / LIGHT, CHEMILUMINE SCENT 6INCH YELLOW	REPLENISHM ENT LIGHT	30 / EACH/N UMBER			CYALUME TECHNOLOGIES SA 295 R MAYOR DE MONTRICHER AIX EN PROVENCE FRANCE AIX EN PROVENCE CEDEX 04 42 37 17 80 04 42 37 17 99 XFARCY@CYALUME.COM WWW.CYALUME.COM	CYALUM E TECHNO LOGIES		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
85	DGT887 81	NIL	723070513291 0 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"		4000 / FOOT	NO DATA AVAILAB LE		PK	TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		<u>TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required</u> <u>GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required</u>	
86	DGE769 14		047659943044 1 / BRUSH ARTISTS QUILL FERRULE;RED SABLE HAIR EXPOSED LG. 0.500"		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
87	DGE768 30	SPEC-HMSO TG27	047659943045 2 / BRUSH ARTISTS QUILL FERRULE RED SABLE HAIR WRITING CROW 3/4"		7 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - Size: 33-37 mm Length: 185-224 mm Weight: 12gm</u> <u>GENERAL SPECIFICATION - Size: 33-37 mm Length: 185-224 mm Weight: 12gm</u>	
88	DGE769		047659943045		20 /						<u>TECHNICAL SPECIFICATION - NO</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	12		3 / BRUSH ARTISTS CAMEL HAIR SWAN SMALL EXPOSED LG 1 3/16 INCH		EACH/NUMBER						DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
89	DGE80668	NO DATA AVAILABLE	0461590006480 / PAINT ROLLER, LENGTH= 7-INCH, DIA= 2-INCH, C/W SHEEP SKIN COVER AND HANDLE STEEL FRAME, WOODEN HANDLE	BLST PAINT UNDER WATER HULL	323 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip GENERAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip	
90	DGB95445		0283595711456 / ROD NAVAL BRASS RD DIA 2.12 INCH WT.13.14 PER FOOT(LB)	SP.BS 2874,CZ 112M	1 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
91	DGE78049	NO DATA AVAILABLE	0451594510013 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	100 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS GENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	
92	DGB74640		0273709104476 / DIVIDERS SPRING LG OF LEG 06IN		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
93	DGE90753	NO DATA AVAILABLE	0330595713260 / TWINE COTTON CHALK LINE G/PURPOSE MIN BKG STRG25 LB20YDS LG; DIA 1.5mm	GENERAL PURPOSE BS 2019	50 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 6125 of 1981 GENERAL SPECIFICATION - BS 6125 of 1981	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
94	DGB74619		0274599104856 / FILE ENGINEER HALF ROUND D-CUT FACES BASTARD 14.00IN		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DGB92834		0214599410019 / BOLT MACHINE STEEL UNC class 2a HEX HD SZ 0.625 X3.000X1.500 IN	BR-320 D/78	296 / EACH/NUMBER						TECHNICAL SPECIFICATION - AISI PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED GENERAL SPECIFICATION - AISI PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED	
96	DGB74581		0273789238078 / BLADE POWER HACKSAW HIGH SPEED STEEL LG 14" WDT 01" TEETH		18 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Make: ECLIPSE 2. OEM/Country of origin: England 3. OEM COC/authorized dealer certificate: N/A GENERAL SPECIFICATION - 1. Make: ECLIPSE 2. OEM/Country of origin: England 3. OEM COC/authorized dealer certificate: N/A	
97	DGE63458	NO DATA AVAILABLE	0413546004803 / PVC PIPE DIA 1.50"		150 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a) Material: Poly Vinyl Chloride b) Diameter 1.5 inch c) Environmental friendly material. d) Heat resistant. e) Fire resistant. f) Reputable company. GENERAL SPECIFICATION - a) Material: Poly Vinyl Chloride b) Diameter 1.5 inch c) Environmental friendly material. d) Heat resistant. e) Fire resistant. f) Reputable company.	
98	DGE58385		0474504740019 / TENT MK 4 COMPLETE WITH ACCESSORIES W/O JHALER WT.180 LBS	CAPACITY 5 MAN, INNER PLY 5 OZ+9 OZ, UPPER	7 / EACH/NUMBER						TECHNICAL SPECIFICATION - Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03 <u>GENERAL SPECIFICATION -</u> Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03	
99	DGB58065	NOR-3	5110765016376 / BLADE JIG SAW THICKNESS 3 MM24 TEETH STEEL	JIG SAW	50 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - a.</u> Specification Nor-3 Blade Jig Saw Thickness 3mm & 24 Teeth Steel used for cutting of wood and GRP material b. Material grade High carbon steel c. Accepted Criteria Concerned rep. to check physically d. Thickness 3mm e. OEM/ Country of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Origin: England/ Germany f. Length 3 ½ inch <u>GENERAL SPECIFICATION</u> - a. Specification Nor-3 Blade Jig Saw Thickness 3mm & 24 Teeth Steel used for cutting of wood and GRP material b. Material grade High carbon steel c. Accepted Criteria Concerned rep. to check physically d. Thickness 3mm e. OEM/ Country of Origin: England/ Germany f. Length 3 ½ inch	
100	DGB73653	NO DATA AVAILABLE	5345765016385 / DISC CUTTING SIZE 300MM X 3.0 MM X 22.23MM		24 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Make:Rhodius Model: Alphaline ST21 Made:EU Dimensions: 300mm x 3.0mm x 22.23mm Diameter : 300 mm Thickness: 3.0 mm Hole: 22.23 mm <u>GENERAL SPECIFICATION</u> - Make:Rhodius Model: Alphaline ST21 Made:EU Dimensions: 300mm x 3.0mm x 22.23mm Diameter : 300 mm Thickness: 3.0 mm Hole: 22.23 mm	
101	DGE76915	NO DATA AVAILABLE	0476599432853 / BRUSH W C		62 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
102	DGE74379	NO DATA AVAILABLE	0432500000028 / HELMET PROTECTIVE WITH VISER COLOUR WHITE (FULL HEAD)		20 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
103	DGT84420	NO DATA AVAILABLE	01005000000049 / TEAK WOOD BURMESE GRADE-I SLEEPER	SPECE/IM. 2763 (A)	10 / CUBIC FOOT	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - P-SG/730 (B) SIZE: LENGTH=12-16 FT, WIDTH=09-18 INCH, THICKNESS=8-10 INCH. Moisture Content= 12%±02% <u>GENERAL SPECIFICATION</u> - P-SG/730 (B) SIZE: LENGTH=12-16 FT, WIDTH=09-18 INCH, THICKNESS=8-10 INCH. Moisture Content= 12%±02%	
104	DGT84601	NO DATA AVAILABLE	01005000000030 / PLY WOOD	2.44X1.22MTRX19.	320 / SQ	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION: bs-1088 part-1&II.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	NATURAL TEAK FINISH BOTH SIDE (NOT ARTIFICIAL) GRADE-1, 9-PLY, LENGTH= 8- FEET, WIDTH= 4- FEET, THICKNESS= 16mm ±2	05MM) SPECE/BS656 6 OF1985	FEET	LE					density of PLY WOOD TEAK= 500 TO 850 KG/M3, thickness of face back veneer should be 0.6 mm (min) <u>GENERAL SPECIFICATION - SPECIFICATION: bs-1088 part-1&II, density of PLY WOOD TEAK= 500 TO 850 KG/M3, thickness of face back veneer should be 0.6 mm (min)</u>	
105	DGE721 98	E-AE10000	047650000006 8 / LEATHER CHROME BLACK 24X24X1/16 INCH		56 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - SIZE:24X24X1/16 INCH NATO Code: F3013</u> <u>GENERAL SPECIFICATION - SIZE:24X24X1/16 INCH NATO Code: F3013</u>	
106	DGT842 95	NO DATA AVAILABLE	933070507970 4 / PLASTIC FORMICA DULL COLOUR OFF WHITE SIZE 8'X4', THICKNESS 1.50mm		14 / SHEET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
107	DGD954 17	NO DATA	732070501242 6 / MACHINE ATTA KNEADING100 TO120KG CAPACITY 440V 50HZ 3PHS 5AMP		1 / EACH/NUMBER	GSA/23/A KM					<u>TECHNICAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)</u> <u>GENERAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)</u>	
108	DGE793 16	NO DATA AVAILABLE	830570512795 0 / RUBBER FABRIC (PVC COATED) CLOTH IN SHIP SIDE GREY COLOUR	FOR PNS SHIFA	400 / METER						<u>TECHNICAL SPECIFICATION - 1. APPLICATION= COVERAGE FOR SHIPS, ETC 2. TOTAL WEIGHT (DIN EN ISO 2286-2)= 500 g/m2 3. SUPPORT CLOTH (DIN 6000)= POLYESTER 4. TYPE OF COATING = PVC COATED ON BOTH SIDES 5. YARN (DIN EN ISO 2060)= 1000 X 1000D 6. SPECIFICATION (DIN EN</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											1049-2)= 18 X 18 PER INCH (PLAIN WEAVE) 7. DIMENSION (DIN EN ISO 2286-1)= WIDTH: 01 METER & ROLL 50 METER 8. TENSILE STRENGTH (DIN 53354)= 2500/2400 N/ 5CM 9. TEAR STRENGTH (DIN 53363)= 270/250 N 10. ADHESION STRENGTH (DIN 53357)= 100 N /5CM 11. TEMPERATURE RESISTANCE= -30 C° TO +70 C° 12. FEATURE= HIGH TENACITY POLYESTER YARN ENSURES SUPERIOR DURABILITY UV PROTECTION TREATED 13. PACKING= CRAFT PAPER OR PE 14. RUBBER FABRIC BASE MATERIAL= POLYESTER, 15. CHEMICAL RESISTANCE= 98% SULFURIC ACID, 38% HYDROCHLORIC ACID AND 40% SODIUM HYDROXIDE, 16. ABRASION RESISTANCE= >1000 ZYKLEN, 17. WATER RESISTANCE= >0.8 BAR, 18. COATING THICKNESS= 0.5 MM, 19. FLAME RETARDANCY AND CERTIFICATION= M2GENERAL SPECIFICATION - 1. APPLICATION= COVERAGE FOR SHIPS, ETC 2. TOTAL WEIGHT (DIN EN ISO 2286-2)= 500 g/m2 3. SUPPORT CLOTH (DIN 6000)= POLYESTER 4. TYPE OF COATING = PVC COATED ON BOTH SIDES 5. YARN (DIN EN ISO 2060)= 1000 X 1000D 6. SPECIFICATION (DIN EN 1049-2)= 18 X 18 PER INCH (PLAIN WEAVE) 7. DIMENSION (DIN EN ISO 2286-1)= WIDTH: 01 METER & ROLL 50 METER 8. TENSILE STRENGTH (DIN 53354)= 2500/2400 N/ 5CM 9. TEAR STRENGTH (DIN 53363)= 270/250 N 10. ADHESION STRENGTH (DIN 53357)= 100 N /5CM 11.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TEMPERATURE RESISTANCE= -30 C° TO +70 C° 12. FEATURE= HIGH TENACITY POLYESTER YARN ENSURES SUPERIOR DURABILITY UV PROTECTION TREATED 13. PACKING= CRAFT PAPER OR PE 14. RUBBER FABRIC BASE MATERIAL= POLYESTER, 15. CHEMICAL RESISTANCE= 98% SULFURIC ACID, 38% HYDROCHLORIC ACID AND 40% SODIUM HYDROXIDE, 16. ABRASION RESISTANCE= >1000 ZYKLEN, 17. WATER RESISTANCE= >0.8 BAR, 18. COATING THICKNESS= 0.5 MM, 19. FLAME RETARDANCY AND CERTIFICATION= M2	
109	DGT776 22		041554600431 2 / SHEET FORMICA WHITE 4.X4. X1/16"		4 / SHEET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
110	DGB742 49	FTK38/ 201082	345572528080 7 / CUTTING DISC RHODIUS FTK38 SIZE 100x2x16		20 / EACH/ NUMBER	RHODIUS TOPLINE					<u>TECHNICAL SPECIFICATION -</u> Product Dimension: 100x2x16mm Shape long version: Depressed Cutting Disc Shape Short version: Shape 42 Working Speed: 80 m/s Max revolution: 15300 U/min Material Suitability: Stain less steel steel Machine Suitability: Free Hand angle grinder Safety and application IDENTIFICATION: Iron and sulphur free = 0.1% Abrasive marking according to EN12413: A24U9BF1338 A NUMBER OF RHODIUS FREEHAND CUTTING DISCS WHICH ARE ONLY 2MM WIDE. THIS ACHIEVES A FASTER AND COOLER CUT <u>GENERAL SPECIFICATION - Product</u> Dimension: 100x2x16mm Shape long version: Depressed Cutting Disc Shape Short version: Shape 42 Working Speed: 80 m/s Max	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											revolution: 15300 U/min Material Suitability: Stain less steel steel Machine Suitability: Free Hand angle grinder Safety and application IDENTIFICATION: Iron and sulphur free = 0.1% Abrasive marking according to EN12413: A24U9BF1338 A NUMBER OF RHODIUS FREEHAND CUTTING DISCS WHICH ARE ONLY 2MM WIDE. THIS ACHIEVES A FASTER AND COOLER CUT	
111	DGH95530	NO DATA AVAILAB E	5305ZO6568045 / LAWN MOVER MACHINE		1 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
112	SGB65953	DEVS7866	4730995253348 / FLANGE		8 / EACH/N UMBER	NO DATA AVAILAB LE		UK	MOD (NAVY) SHIP SUPPORT AGENCY DME MC253 ROOM 19 BLOCK B FRAHILL BATH UK		<u>TECHNICAL SPECIFICATION - BS 1400</u> Inner dia: 1 ½ inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: ½ inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing <u>GENERAL SPECIFICATION - BS 1400</u> Inner dia: 1 ½ inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: ½ inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing	