

PAKISTAN NAVY
TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 21-01-2026

TERMS & CONDITION

- 1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT”.**
- 2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.**
- 3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.**

CONDITIONS

- NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
- FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
- LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGT68020	NO DATA AVAILAB LE	0100500000039 / TIMBER FIR HIMALAYA/ SPRUCE SLEEPER, WELL SEASONED LOCAL/ IMPORTED, SIZE: L=8'-15', W=8"-14", h=4"-10"	(3.05MTR X254 MM X127 MM) SPECE/PSG 69	92 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%, GENERAL SPECIFICATION - SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%,</u>	
2	DGT78422	NO DATA AVAILAB LE	0100500000039 / TIMBER FIR HIMALAYA/ SPRUCE SLEEPER, WELL SEASONED LOCAL/ IMPORTED, SIZE: L=8'-15', W=8"-14", h=4"-10"	(3.05MTR X254 MM X127 MM) SPECE/PSG 69	50 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%, GENERAL SPECIFICATION - SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%,</u>	
3	SGB17560		1325723350003 / BAND SAW SIZE 1-1"/4- FOR WOOD NPN		500 / FOOT						<u>TECHNICAL SPECIFICATION - MATERIAL GRADE: FUNER, GHAGE: 20 MADE: GERMANY/ENGLAND WIDTH: 1 1/4 INCH LENGTH: 200 FT ROLLGENERAL SPECIFICATION - MATERIAL GRADE: FUNER, GHAGE: 20 MADE:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GERMANY/ENGLAND WIDTH: 1 1/4 INCH LENGTH: 200 FT ROLL	
4	DGE77587		0462502201803 / TUBING PLASTIC POLYETHYLENE LAY FLAT WD.48	DC/FF	60 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION</u> - 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317</p> <p><u>GENERAL SPECIFICATION</u> - 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317</p>	
5	DGB65291	XT10/209822	3455725280806 / CUTTING DISC RHODIUS XT10 SIZE 105x1x16		85 / EACH/NUMBER	RHODIUS TOPLINE					<p><u>TECHNICAL SPECIFICATION</u> - MATERIAL SPECIFICATIONS: STAINLESS STEEL, RUST AND ACID PROOFED STEELS, HIGH TENSILE, HIGH ALLOYED STEELS, TOOL STEELS, HARDENED STEELS, HARDOX, HIGH TENSILE METAL SHEETS</p> <p><u>GENERAL SPECIFICATION</u> - MATERIAL SPECIFICATIONS: STAINLESS STEEL, RUST AND ACID PROOFED STEELS, HIGH TENSILE, HIGH ALLOYED STEELS, TOOL STEELS, HARDENED STEELS, HARDOX, HIGH TENSILE METAL SHEETS</p>	
6	DGE85332	k817-r	5340705278734 / rubber wheel (under carriage)		12 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - A) 6" RED PP WHEEL NYLON MATERIAL WITH REUOLING BRACKET COMPLETE (MADE BY LOCAL) B) 6" RED PP WHEEL NYLON MATERIAL WHEEL ONLY (MADE BY LOCAL)</p> <p><u>GENERAL SPECIFICATION</u> - A) 6" RED PP WHEEL NYLON MATERIAL WITH REUOLING BRACKET COMPLETE (MADE BY LOCAL) B) 6" RED PP WHEEL NYLON MATERIAL WHEEL ONLY (MADE BY LOCAL)</p>	
7	DGB75230	NO DATA AVAILABLE	5120731000593 / WRENCH PIPE CHAIN CAPICTY		6 / EACH/NUMBER	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6INCH									
8	DGD51838	NO DATA	7320705012426 / MACHINE ATTA KNEADING100 TO120KG CAPACITY 440V 50HZ 3PHS 5AMP		2 / EACH/NUMBER	GSA/23/AKM					<p><u>TECHNICAL SPECIFICATION -</u> Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade) <u>GENERAL SPECIFICATION</u> - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)</p>	
9	DGH53652		7125991297694 / ANGLE POSTS STORAGE SHELVING 123		50 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> Material : Steel/ Aluminum Length: 6 feet to 24 feet Width: 02" to 6" Angle : 90 Degrees (standard) Thickness: ¼" to 1" Size: 2x2x ¼" (50.8 x50.8x6.35mm) 2x4x ¼" (50.8 x101.6.8 x 6.35mm) 3x3x ½" (76.2 x76.2 x 12.7mm) MATERIAL GRADE SS 400 <u>GENERAL SPECIFICATION -</u> Material : Steel/ Aluminum Length: 6 feet to 24 feet Width: 02" to 6" Angle : 90 Degrees (standard) Thickness: ¼" to 1" Size: 2x2x ¼" (50.8 x50.8x6.35mm) 2x4x ¼" (50.8 x101.6.8 x 6.35mm) 3x3x ½" (76.2 x76.2 x 12.7mm) MATERIAL GRADE SS 400</p>	
10	DGE69651	NO DATA AVAILABLE	8340505039261 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		3 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - 1.</u> Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE)</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos <u>GENERAL SPECIFICATION - 1.</u>Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p>	
11	DGE939 36		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1/ EACH/ NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF (WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150-180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3.</p> <p>ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY</p> <p><u>GENERAL SPECIFICATION</u> - SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF</p>	

PR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										(WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150-180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3. ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY	
GE940 1		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF (WEIGHT: 04 OZS PER M2), •	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>OF COLOURED SHEETING OF 150-180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3.</p> <p>ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY</p> <p><u>GENERAL SPECIFICATION</u> - SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF (WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150-180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3. ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY	
13	DGB59857	NO DATA AVAILAB LE	024650000106 6 / BLOCK CHAIN 5 TON 10METER (ORIGINAL MANUFACTUR E LENGTH}		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Make: Elephant Chain Block Co. Ltd. Japan. Model: Manually operated chain Hoist Model C21. <u>GENERAL SPECIFICATION -</u> Make: Elephant Chain Block Co. Ltd. Japan. Model: Manually operated chain Hoist Model C21.	
14	DGB70880	NO DATA AVAILAB LE	024850000001 5 / SAFE- STEEL-WITH- COMBINATION -LOCK FOR CBs SZ 28X20X16 5/8		1 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - A.</u> BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record <u>GENERAL SPECIFICATION - A.</u> BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
15	DGE714 34		653050502490 8 / OVER BED TABLE ADJUSTABLE 805X405MM STAND 4 WHEEL S/S ROUND		17 / EACH/N UMBER						TECHNICAL SPECIFICATION - Item Specification: Height-30 Cm,Length-28 Cm, Width-15 Cm, Steel brand Standard 16" Gauge, Adjustable Stand Handle, 04 Wheel plastic GENERAL SPECIFICATION - Item Specification: Height-30 Cm,Length-28 Cm, Width-15 Cm, Steel brand Standard 16" Gauge, Adjustable Stand Handle, 04 Wheel plastic	
16	SGB114 33	BRANDS: TOKA, FLEXOVIT AND BLACK & DECKER	534570506021 8 / GRINDING DISC SIZE: 125X7X22.23 MM	GENERAL PURPOSE	150 / EACH/N UMBER						TECHNICAL SPECIFICATION - GRINDING OF METAL SHEETS/ PIPES DIMENSION: 125X7X22.23 MM BRAND: RHODIUS/ ANY OTHER CERTIFIED BRAND Date of manufacturing and expiry should be mentioned on item. Shelf life: 03 Years GENERAL SPECIFICATION - GRINDING OF METAL SHEETS/ PIPES DIMENSION: 125X7X22.23 MM BRAND: RHODIUS/ ANY OTHER CERTIFIED BRAND Date of manufacturing and expiry should be mentioned on item. Shelf life: 03 Years	
17	SGB350 79	NO DATA AVAILABL E	473070503853 1 / BAND PIPE M/S 1.50IN	DUMP BARGE CONSTRUCTI ON	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material specification/ Grade: Steel/ Ferrous Alloy BS 1740/71, Corrosion Resisting Ferrous Alloy Complete dimensions, internal dia 1.50 inch, External dia 54mm, thickness 6mm, Running length 5.5 inch. GENERAL SPECIFICATION - Material specification/ Grade: Steel/ Ferrous Alloy BS 1740/71, Corrosion Resisting Ferrous Alloy Complete dimensions, internal dia 1.50 inch, External dia 54mm, thickness 6mm, Running length 5.5 inch.	
18	SGB298 41		473099531137 6 / FLANGE, PIPE STEEL, ROUND Nominal BORE1.00 inch	FOR PIPE FITTING/AS&A S P-6 KHAIBER, TARIQ	25 / EACH/N UMBER						TECHNICAL SPECIFICATION - MATERIAL GRADE: MILD STEEL MILD STEEL, STANDARD: BS-10 OF 2009, GRADE S235-JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											1/4 INCH, OUTER DIA: 4-1/2 INCH, BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH <u>GENERAL SPECIFICATION - MATERIAL GRADE: MILD STEEL MILD STEEL, STANDARD: BS-10 OF 2009, GRADE S235-JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3-1/4 INCH, OUTER DIA: 4-1/2 INCH, BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH</u>	
19	DGB79238	TWO JOINT CUTTER, 0.188 IN W	512099910552 4 / PLIER SIDE CUTTING LINESMAN TYPE SINGLE JOINT, 8" NOM SZ		9 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
20	DGB73531	6308ZZ	311000158816 1 / BEARING BALL ANNUAL SIZE . 40X90X23.		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - OEM: SKF Model: AB SKF 6308ZZ, Origin USA/ Sweden, Locally available.</u> <u>GENERAL SPECIFICATION - OEM: SKF Model: AB SKF 6308ZZ, Origin USA/ Sweden, Locally available.</u>	
21	SGB57075	SKF 6311ZZ	311099950202 9 / BEARING BALL JOURNAL SINGLE SKF 6311ZZ 055X120X29MM	GENERAL USE ITEM	15 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Brand: SKF Model: 6311 ZZ Seal Type: Double End Cage Type: Steel Inside Diameter: 55mm Outside Diameter: 120mm Width: 29mm Weight: 1.37kg Limiting Speed: 5600 RPM</u> <u>GENERAL SPECIFICATION - Brand: SKF Model: 6311 ZZ Seal Type: Double End Cage Type: Steel Inside Diameter: 55mm Outside Diameter: 120mm Width: 29mm Weight: 1.37kg Limiting Speed: 5600 RPM</u>	
22	DGE73971	MD231 (CROWN)	444079510254 4 / PREMI-AIR	DEHUMIDIFIERS	4 / EACH/NUMBER	MD231 (CROWN)					<u>TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V - Rated</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		/EH1504 /EH1418	DEHUMIDIFIE RS,300W, 220/240V SIZE: 350X452X275 MM		UMBER	/EH1504/ EH1418					Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <u>GENERAL SPECIFICATION</u> _Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG	
23	DGE740 06	MD231 (CROWN) /EH1504 /EH1418	444079510254 4 / PREMI-AIR DEHUMIDIFIE RS,300W, 220/240V SIZE: 350X452X275 MM	DEHUMIDIFIE RS	4 / EACH/N UMBER	MD231 (CROWN) /EH1504/ EH1418					<u>TECHNICAL SPECIFICATION -</u> Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <u>GENERAL SPECIFICATION</u> _Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG	
24	SGB733 5		132572325000 2 / WIDIA DIAMOND CUTTING TIP TOOL B-25MM AT DIN 4966		30 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
25	DGE876 71		209050503923 3 / GROUND SHEET- CANVAS LG- 2M 35CM WITH85CM THK 0.75MM		50 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Specifications: √ Material: Polyester- cotton canvas with PU/ PVC coating. √ Weight: 450-550 GSM √ Size: 5m x 8m (standard) √ Coating: Waterproof, anti-fungal, UV-resistant √ Color: Olive green/ khaki/ brown √ Edges:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Reinforced with rust proof eyelets. ζ Finish: Mildew resistant Technical Data: ζ Waterproofing: 2000 mm hydrostatic head ζ Tensile Strength: 350 N/ cm (warp), 300 N/ cm (weft). ζ Tear Strength: 50N ζ UV Resistance: 500 hrs exposure without degradation ζ Abrasion: 30,000 rubs ζ Shrinkage: 3% ζ Temp Range: -100 C to + 550 ζ Flame Retardant: NFPA 701/ BS 5852 compliant Testing Criteria : ζ Hydrostatic pressure (ISO 811) ζ Tensile & tear strength (ISO 13934-1, ISO 13937-2) ζ UV resistance ζ Mildew test ζ Abrasion (ISO Standard) ζ Shrinkage (ISO Standard) ζ Fire resistance Accepting Criteria: ζ Waterproof 2000 mm ζ Tensile 350/300 N/cm ζ Tear Strength > 50N ζ No mildew growth (7 days) ζ UV degradation 15% ζ Abrasion > 30,000 rubs ζ Shrinkage 3% ζ Must pass flame test dimension: Width = 4 feet Height = 3 feet</p> <p>GENERAL SPECIFICATION - Specifications: ζ Material: Polyester- cotton canvas with PU/ PVC coating. ζ Weight: 450-550 GSM ζ Size: 5m x 8m (standard) ζ Coating: Waterproof, anti-fungal, UV-resistant ζ Color: Olive green/ khaki/ brown ζ Edges: Reinforced with rust proof eyelets. ζ Finish: Mildew resistant Technical Data: ζ Waterproofing: 2000 mm hydrostatic head ζ Tensile Strength: 350 N/ cm (warp), 300 N/ cm (weft). ζ Tear Strength: 50N ζ UV Resistance: 500 hrs exposure without degradation ζ Abrasion: 30,000 rubs ζ Shrinkage: 3% ζ Temp Range: -100 C to + 550 ζ Flame Retardant: NFPA 701/ BS 5852 compliant Testing Criteria : ζ Hydrostatic pressure (ISO 811) ζ Tensile & tear strength (ISO 13934-1, ISO 13937-2)</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>¿ UV resistance ¿ Mildew test ¿ Abrasion (ISO Standard) ¿ Shrinkage (ISO Standard) ¿ Fire resistance</p> <p>Accepting Criteria: ¿ Waterproof 2000 mm ¿ Tensile 350/300 N/cm ¿ Tear Strength > 50N ¿ No mildew growth (7 days) ¿ UV degradation 15% ¿ Abrasion > 30,000 rubs ¿ Shrinkage 3% ¿ Must pass flame test dimension: Width = 4 feet Height = 3 feet</p>	
26	SGH514 15	SAFFIRE MODEL NM250, PART NO. 116324	028150281166 6 / NOZZLE INNER GAS CUTTING TORCH SIZE 1/16 INCH	REF NO 529-4 SHEET U	120 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.</u></p> <p><u>GENERAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.</u></p>	
27	DGB501 51	NO DATA AVAILABL E	024670523143 5 / HOIST- CHAIN- RATCHET- SWL1. 5PROOF- LOAD2.25 TON.		2 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - a. Load Capacity: 2.25 Ton b. Test Load (Kg): 3800 c. Standard Lift (m): 1.5 - 2 d. Mass (Net Weight) Approx KG: 10 -14</u></p> <p><u>GENERAL SPECIFICATION - a. Load Capacity: 2.25 Ton b. Test Load (Kg): 3800 c. Standard Lift (m): 1.5 - 2 d. Mass (Net Weight) Approx KG: 10 -14</u></p>	
28	SGB487 36	19-00072	025478420320 5 / CLAMP HOSE TERRY BRAND SZ 0.500 TO 0.625 X0.505X0. 038IN	BALLAST TANK	1500 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
29	SGB517 19	0254-5672	025478420320 3 / CLAMP HOSE TERRY BRAND SZ 0.875 TO 1.125 X0.505X0. 038IN	FUEL TANK	250 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - Code Number: 442-035, Adjustment: 25-35mm (1" -1 3/8"), Acceptance Criteria: BS 5315 Standard, BS Code 35</u></p> <p><u>GENERAL SPECIFICATION - Code Number: 442-035, Adjustment: 25-35mm (1" -1 3/8"), Acceptance Criteria: BS 5315 Standard, BS Code 35</u></p>	
30	DGB695 18	OUT/BOD Y 1/8"	024859129614 7 / SAFE	SZ 710X535X425	1 / EACH/N						<p><u>TECHNICAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8"</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		PLATE. INNER 16 GAUG	STEEL FITTED WITH COMB 6 LEVER EXT DIM SZ 28X21X16 5/8"	MM(27-3/4X21- 1/16X16-3/4"	UMBER						plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required GENERAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required	
31	DGB669 51	OUT/BOD Y 1/8" PLATE. INNER 16 GAUG	024859129614 7 / SAFE STEEL FITTED WITH COMB 6 LEVER EXT DIM SZ 28X21X16 5/8"	SZ 710X535X425 MM(27-3/4X21- 1/16X16-3/4"	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required GENERAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required	
32	DGB733 99	OUT/BOD Y 1/8" PLATE. INNER 16 GAUG	024859129614 7 / SAFE STEEL FITTED WITH COMB 6 LEVER EXT DIM SZ 28X21X16 5/8"	SZ 710X535X425 MM(27-3/4X21- 1/16X16-3/4"	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required GENERAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required	
33	DGB738 59	OUT/BOD Y 1/8" PLATE. INNER 16 GAUG	024859129614 7 / SAFE STEEL FITTED WITH COMB 6 LEVER EXT DIM SZ 28X21X16 5/8"	SZ 710X535X425 MM(27-3/4X21- 1/16X16-3/4"	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required GENERAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required	
34	DGB540 60	HH5010A (Nitchi Japan)	024679463385 4 / HOIST CHAIN STEEL GEARED HAND OPERATED SWIVEL HOOKS, CAPACITY 01 TON	SHIP 76,LOAD CHAIN 1,MAX. DIST.HOOK TO	2 / EACH/N UMBER	HE-50A					TECHNICAL SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 75 LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up) Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, DEFSTAN02-113 (LATIEST EDITION) (PROVISION OF LOAD TEST CERTIFICATE) GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 75 LOAD CHAIN 1, MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up) Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, DEFSTAN02-113 (LATIEST EDITION) (PROVISION OF LOAD TEST CERTIFICATE)	
35	SGB316 18		021459941001 9 / BOLT MACHINE STEEL UNC class 2a HEX HD SZ 0.625 X3.000X1.500 IN	BR-320 D/78	300 / EACH/N UMBER						TECHNICAL SPECIFICATION - AISI PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED GENERAL SPECIFICATION - AISI PD 970: 2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED	
36	SGB313 88		021459033081 4 / STUD- PLAIN-BSW- THRED-0.50- INCH-LH-3.50 LH OF THK 1/2" NUT&1"		50 / EACH/N UMBER						TECHNICAL SPECIFICATION - STEELL material GRADE AISI 4140 (PD 970:2005 GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED GENERAL SPECIFICATION - STEELL material GRADE AISI 4140(PD 970:2005 GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
37	DGB431 66		021459013101 3 / BOLT MACHINE STEEL BSFmedium class.		480 / EACH/N UMBER						TECHNICAL SPECIFICATION - metarial: steel 45 tons/sq in nts head: hexagon specs: dgs 8060 class 1(b) for general purpose and in steam system for temprature upto 400 deg c bs-1083 SIZE 5/8 X 3 ¼ INCH LENGTH 3 ¼ INCH BSF THREAD SIZE 5/8 INCH BSF THREAD PER INCH 14 GENERAL SPECIFICATION - metarial: steel 45 tons/sq in nts head: hexagon specs: dgs 8060 class 1(b) for general purpose and in steam system for temprature upto 400 deg c bs-1083 SIZE 5/8 X 3 ¼ INCH LENGTH 3 ¼ INCH BSF THREAD SIZE 5/8 INCH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
38	DGB8234		0214590131013 / BOLT MACHINE STEEL BSFmedium class.		40 / EACH/NUMBER						BSF THREAD PER INCH 14 <u>TECHNICAL SPECIFICATION</u> - metarial: steel 45 tons/sq in nts head: hexagon specs: dgs 8060 class 1(b) for general purpose and in steam system for temprature upto 400 deg c bs-1083 SIZE 5/8 X 3 1/4 INCH LENGTH 3 1/4 INCH BSF THREAD SIZE 5/8 INCH BSF THREAD PER INCH 14 <u>GENERAL SPECIFICATION</u> - metarial: steel 45 tons/sq in nts head: hexagon specs: dgs 8060 class 1(b) for general purpose and in steam system for temprature upto 400 deg c bs-1083 SIZE 5/8 X 3 1/4 INCH LENGTH 3 1/4 INCH BSF THREAD SIZE 5/8 INCH BSF THREAD PER INCH 14	
39	SGB31623		0214590131010 / BOLT MACHINE STEEL BSF MEDIUM CLASS	BR 320 D/78	280 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Thread Size 5/8 Inch Nominal Length 2 1/2 Inch Length of Thread 1 1/4 Inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) METARIAL: STEEL 45 TON/SQ.IN.NTS TENSILE STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC REQUIRED <u>GENERAL SPECIFICATION</u> - Thread Size 5/8 Inch Nominal Length 2 1/2 Inch Length of Thread 1 1/4 Inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) METARIAL: STEEL 45 TON/SQ.IN.NTS TENSILE STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC REQUIRED	
40	DGB75786	NO DATA AVAILABE	0274700001191 / HAMMER HAND WIGHT OF HEAD 1.75 LB		3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABE <u>GENERAL SPECIFICATION</u> -NO DATA AVAILABE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
41	SGB57078	SKF 7310	0269599500028 / BEARING BALL ANGULAR CONTACT SKF 7310 B 050X110X27MM		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DGE86883	C-268	0476599430559 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		121 / EACH/NUMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
43	DGE86636	NIL	0476599430558 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		318 / EACH/NUMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
44	DGE79697	NIL	0476599430558 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		275 / EACH/NUMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
45	DGE768	9-27061	047350473015	LIGHT STICK	200 /						TECHNICAL SPECIFICATION - NO	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	01	(NSN 6260-01-074-4230)	9 / LIGHT, CHEMILUMINE SCENT YELLOW	(SAFETY LIGHT)-YELLOW	EACH/NUMBER						DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DGE83651		04765900006 2 / GLOVES LEATHER LEFT HAND.		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable GENERAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable	
47	DGB84158		027678910587 6 / SCREWDRIVE R F/POINT BLADE LG 6" TIP WIDTH 0.156 O/A LG 9.25"		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DGE64183	2890S	4240TY520256 0 / 3M COMFORT LINE SAFETY GOGGLES 2890S SEALED VERSION	BV	10 / EACH/NUMBER	NA		VHKMHMN			TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
49	DGE77243	2895S	4240TY520256 2 / 3M COMFORT LINE SAFETY GOGGLES 2890 SERIES	BV	62 / EACH/NUMBER	NA		VHKMHMN			TECHNICAL SPECIFICATION - a. Goggle Type Sealed b. Lens Color Clear c. Lens Coating Anti fog & Anti-scratch d. Lens Material Polycarbonate e. Product Series 2890s f. Size Universal g. Venting None GENERAL SPECIFICATION - a. Goggle Type Sealed b. Lens Color Clear c. Lens Coating Anti fog & Anti-scratch d. Lens Material Polycarbonate e. Product Series 2890s f. Size Universal g. Venting None	
50	SGB40964	NA	473074521661 4 / UNION 1/2	HPAC WP5000	20 / EACH/NUMBER	union 1/2	NIL	GIRODIN SAUR COMPRESSOR	PARKER USA		TECHNICAL SPECIFICATION - COUNTRY OF ORIGIN: USA MAKE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH threaded		UMBER			URBAN VALLEY-BATC-16, CHEMIN DU BASDES INDES 95240 CORMELLES-EN-PARIS FRANCE TELE +33 (0)134117610 FAX: +33(0)130100079 EMAIL INFO@GIRODIN- SAUER.FR WWW.GIRODIN-SAUER. COM			: PARKER USA BRAND: HY LOK KOREA HP UNION 1/2" , THREADED material: SS316L Pressure rating: 4500 psi <u>GENERAL</u> SPECIFICATION - COUNTRY OF ORIGIN: USA MAKE : PARKER USA BRAND: HY LOK KOREA HP UNION 1/2" ,THREADED material: SS316L Pressure rating: 4500 psi	
51	DGE786 65	NIL	046170514204 1 / REFILE PAINT ROLLER WITHOUT HANDLE, LENGTH= 4- INCH, DIA= 1- INCH	HULL PAINT SCHEME	57 / EACH/N UMBER	NO DATA AVAILAB LE		PK		M/S AJAZ PAINT HOUSE MARRIOT ROAD KARACHI PHON NO.021 32412531	<u>TECHNICAL SPECIFICATION -</u> Refile Paint Roller WithOUT Handle Length 4 Inch Dia 1 Inch Make: local OEM: pakistan SOURCE OF AVAILABILITY: M/S AJAZ PAINT HOUSE MARRIOT ROAD KARACHI PHON NO.021 32412531 Parent equipment be indicated : Hypox Work <u>GENERAL SPECIFICATION -</u> Refile Paint Roller WithOUT Handle Length 4 Inch Dia 1 Inch Make: local OEM: pakistan SOURCE OF AVAILABILITY: M/S AJAZ PAINT HOUSE MARRIOT ROAD KARACHI PHON NO.021 32412531 Parent equipment be indicated : Hypox Work	
52	DGE860 59	CY720- 7003	562078522115 5 / FIRE RETARDANT TILES (SEA GREY COLOR)	SHIP DECK	60 / EACH/N UMBER	CY720- 7003	NIL	ASIA & LATIN AMERICA DEPT. CHINA SHIPBUILDING TRADING COMPANY LTD. (CSTC)	CSTC CHINA		<u>TECHNICAL SPECIFICATION -</u> FIRE RETARDANT TILES <u>GENERAL</u> SPECIFICATION - FIRE RETARDANT TILES	
53	DGE786 64	NIL	047659000775 8 / GLOVES SEAMLESS DIPPED RUBBER		210 / PAIR	202- GNFG					<u>TECHNICAL SPECIFICATION - a.</u> Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc <u>GENERAL</u> SPECIFICATION - a. Product Code:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc	
54	DGE83202	N/A	9330705181279 / PLASTIC SHEET	GENERAL ITEM	3 / ROLL			LOCAL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
55	DGB72886		5120731000585 / SPANNER RING DOUBLE END 6-TO-22MM 8 PIECES SET		14 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DGB79518		0276795057080 / BOX SPANNER SET FROM 10MM TO 27MM(9 PIECES)+3 TOMMY BARS	FOR GENERAL USE	3 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DGE76652		5330705050663 / CARD BOARD SHEET SIZE 31"X50 1/2" THICKNESS 05MM.	FOR PACKING PURPOSE FOR PP CENTRE	100 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DGT70243	NO DATA AVAILABLE	0100501000118 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM		512 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) GENERAL SPECIFICATION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE								- SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
59	SGB49249	BS9522F0014	0214590130606 / BOLT MACHINE STEEL BSF HEX HD 20TPI-SZ 0.375 X1.500X0.750 IN	GENERAL USE	80 / TEN						<u>TECHNICAL SPECIFICATION</u> - material specs i.e aisi 4140(pd 970: 2005 material grade 708m40 or 42crm04) <u>GENERAL SPECIFICATION</u> - material specs i.e aisi 4140(pd 970:2005 material grade 708m40 or 42crm04)	
60	SGB33369	Material Grade EN 4140	0214590330512 / STUD-PLAIN-BSW-THRED-0.31-INCH-LH-3-INCH		50 / TEN						<u>TECHNICAL SPECIFICATION</u> - MATERIAL GRADE EN 4140 *. material specification i.e aisi 4140(pd 970: 2005 material grade 708m40 or 43crm04) <u>GENERAL SPECIFICATION</u> - MATERIAL GRADE EN 4140 *. material specification i.e aisi 4140(pd 970: 2005 material grade 708m40 or 43crm04)	
61	SGB38481		0214590035651 / BOLT MACHINE STEEL BSW HEX HD SZ 1.000X0.375 IN		100 / TEN						<u>TECHNICAL SPECIFICATION</u> - MATERIAL GRADE EN 4140 <u>GENERAL SPECIFICATION</u> - MATERIAL GRADE EN 4140	
62	DGH16557	423100	4030795088966 / HOIST STEEL WIRE ROPE OUTER DIA (22MM X 301.6 MTR LONG DYFORM 34LR BREAKING LOAD 415 KN 42.3 TON)	UK MADE	60 / METER						<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
63	DGH10493	DEFSTAN-02-215 /	0561595218342 / CABLE	SONAR 184P TRANSDUCER	400 / METER						<u>TECHNICAL SPECIFICATION</u> - OUTSIDE DIAMETER 7.2MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		def stan 02-526	ELECTEP, EP RUBBER INSULATED, CSP SH 2CORE COND32/200 440V 17AMP								CROSSECTIONAL AREA OF ONE CORE 1.0 SQMM POWER SOURCE 440V, 17AMPR NO OF CORE 2 DEFENCE STANDARD 02-215 (GUIDE TO CABLE ELECTRICAL PART 1-13 <u>GENERAL SPECIFICATION</u> - OUTSIDE DIAMETER 7.2MM CROSSECTIONAL AREA OF ONE CORE 1.0 SQMM POWER SOURCE 440V, 17AMPR NO OF CORE 2 DEFENCE STANDARD 02-215 (GUIDE TO CABLE ELECTRICAL PART 1-13	
64	DGH858 71	10830- 1600	4010795160140 / STAINLESS STEEL WIRE ROPE (6X19+SE) 16MM	FORE & MAIN LOWER/UPPERS FOOF ROPES /STIRRUPS/FLAM	50 / METER	10830/16 00		MANUFACTURE ADDRESS: JACOB UK MMA ARCHITECHUARL SYS BROADWAY HOUSE, UNIT 5.SECOND AVENUE WESTFIED INDUSTRIAL ESTATE MIDSOMER NORTON SOMERSET.BA3 4BH	JACOB UK MMA ARCHITECHUARL		<u>TECHNICAL SPECIFICATION</u> - MANUFACTURE ADDRESS: JACOB UK MMA ARCHITECHUARL SYS BROADWAY HOUSE,UNIT 5. SECOND AVENUE WESTFIED INDUSTRIAL ESTATE MIDSOMER NORTON SOMERSET.BA3 4BH TEL:0845 1300 185 FAX:0845 1300 136 E-MAUJL:sales@jacob.co.uk <u>GENERAL SPECIFICATION</u> - MANUFACTURE ADDRESS: JACOB UK MMA ARCHITECHUARL SYS BROADWAY HOUSE,UNIT 5. SECOND AVENUE WESTFIED INDUSTRIAL ESTATE MIDSOMER NORTON SOMERSET.BA3 4BH TEL:0845 1300 185 FAX:0845 1300 136 E-MAUJL:sales@jacob.co.uk	
65	DGE948 24	NIL	0350599237126 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sSTRAND, Z-LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	240 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	---------------	----------------	------------------	-----------

MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.

66	DGE946 15	NO DATA AVAILABL E	593572507749 3 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 35/12, LG 01 METER		150 / METER						<u>TECHNICAL SPECIFICATION - A.</u> Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW- 3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714,	
----	--------------	--------------------------	--	--	----------------	--	--	--	--	--	--	--

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion.<u>GENERAL SPECIFICATION - A. Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW-3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714, Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion.</u></p>	
67	DGE799 71	0413-8553	041359923892 6 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		59 / KILOGR AMME						<p><u>TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYES=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"</u><u>GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYES=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"</u></p>	
68	DGE939 23		046259000598 9 / TUBING PLASTIC POLYTHYINE LAY FLAT 0.005"TH.WD. 27"WEIGHT PER		35 / KILOGR AMME						<p><u>TECHNICAL SPECIFICATION - TUBING PLASTIC POLYTHYINE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches thickness: 0.005 inches (DOUBLE SIDE)</u> <u>GENERAL SPECIFICATION - TUBING PLASTIC POLYTHYINE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											thickness: 0.005 inches (DOUBLE SIDE)	
69	DGE94376	SMALL 56.8 LTRS 150 PLUS	811570525959 6 / coleman ice boxes (SMALL) 56.8 LTRS 150 (PLUS)		2 / EACH/NUMBER	N/A					<p><u>TECHNICAL SPECIFICATION</u> - trolley hook with wheel, both side handles CAPACITY 56.8 LTRS size (LENGTH 24" WIDTH 16" HEIGHT 24" WALL THICKNESS 3 CM)</p> <p><u>GENERAL SPECIFICATION</u> - trolley hook with wheel, both side handles CAPACITY 56.8 LTRS size (LENGTH 24" WIDTH 16" HEIGHT 24" WALL THICKNESS 3 CM)</p>	
70	DGE94282		722050503979 6 / VINYL TILE NON PVC BAGE SIZE 304X304X3MM	FLOOR COVERING	800 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
71	DGE94580		722050503979 6 / VINYL TILE NON PVC BAGE SIZE 304X304X3MM	FLOOR COVERING	800 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
72	DGB94070	NO DATA AVAILABLE	026550000130 2 / HINGES-PYANO-STEEL- LG 6 FT 0.750-INCH WIDTH		109 / EACH/NUMBER	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
73	DGE94132	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	2 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAGE					<p><u>TECHNICAL SPECIFICATION</u> - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p> <p>TECHNICAL SPECIFICATION - SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF</p>	
74	DGE948 37		834070508791 5 / HIGH QUALITY KUWAITI	GENERAL PURPOSE	1 / EACH/N UMBER							

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DELUXE TENT 23 X 15 FT								<p>TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF (WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150-180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3.</p> <p>ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY</p> <p><u>GENERAL SPECIFICATION</u> - SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF (WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150-180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3. ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY</p>	

75	DGE943 75	NO DATA AVAILABL E	046150000008 6 / GOGGLE CHIPPING		60 / EACH/N UMBER	NO DATA AVILAB LE					<p>TECHNICAL SPECIFICATION - Concurrence to CSA Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large</p>	
----	--------------	--------------------------	--	--	-------------------------	-------------------------	--	--	--	--	--	--

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.<u>GENERAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.</p>	
76	DGB94658	NO DATA AVAILAB LE	026850000004 7 / WEIGHING MACHINE 50 KG - 300 kg		2 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - a.</u> Make Model: OMEGA TAIWA/KINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g <u>GENERAL SPECIFICATION - a.</u> Make Model: OMEGA TAIWA/KINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g</p>	
77	DGT94179		551050507742 5 / WOODEN BEEDING DESIGNED SIZE WIDTH 2" THICK 1/2"		100 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
78	DGE65892		422050510192 9 / LIFE JACKETS (Orange/Camo	FOR PERSONNAL SAFETY,PNS QASIM,PRIZE	130 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - (1)</u> Buoyancy: 7.5kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 -- 4.33" bust) (3) Material: 240D</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ufflage)	ENT							<p>Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003 <u>GENERAL SPECIFICATION</u> - (1) Buoyancy: 7.5 kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003</p>	
79	DGB63614	NO DATA AVAILABLE	0248591296149 / STEEL SAFE FITTED WITH COMBINATION LOCK	NAL DIMENSIONS: 23-1/2	1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - a. Complete Item/ Store DESCRIPTION: Steel Safe fitted with Combination LOCK b. Gauge : Outer 16 SWG Inner 16 SWG c. Size/ dimension: Length/ Height 22 Inch Width 20 Inch Depth 18 Inch d. Door: Single e. No. of shelves: 02 f. No. of Levers: 01 g. Lock Type: Combination + Key/ Digital Lock h. Fire Retardant: Yes</u><u>GENERAL SPECIFICATION - a. Complete Item/ Store DESCRIPTION: Steel Safe fitted with Combination LOCK b. Gauge : Outer 16 SWG Inner 16 SWG c. Size/ dimension: Length/ Height 22 Inch Width 20 Inch Depth 18 Inch d. Door: Single e. No. of shelves: 02 f. No. of Levers: 01 g. Lock Type: Combination + Key/ Digital Lock h. Fire Retardant: Yes</u></p>	
80	DGB93385		0262594195065 / CLEAT-ROPE-3-8.25-HEIGHT-5.125-INCH		6 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
81	DGB78593		0273599104461 / CALIPER INSIDE 8IN		2 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
82	SGB92185		0272502720040 / DRILL-		18 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - Material HSS, Hardness HRC65-66.</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PARALELL-SHANK-3MM CARBON STEEL		UMBER						GENERAL SPECIFICATION - Material HSS, Hardness HRC65-66.	
83	DGB941 71	NO DATA AVAILABL E	026359923698 7 / THIMBLE, ROPE STEEL BS 970-EN 3A GALVANISED PEAR SHAPED OPEN TYPE WT 1.75LBS SIZE 1.25	SPEC NO DGS 5031NO.40	350 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
84	SGB933 73		021459013122 4 / BOLT MACHINE STEEL BSF HEX HD SZ 0.750X6.000X1.500 IN		140 / EACH/N UMBER						TECHNICAL SPECIFICATION - size: BOLT MACHINE STEEL BSF HEX HD SZ 0.750X6.000X1.500 IN STEELL GRADE AISI 4140 (PD 970: 2005 GRADE 708M40/42CRM40 Material Grade EN 4140 (OEM CoC Required). GENERAL SPECIFICATION - size: BOLT MACHINE STEEL BSF HEX HD SZ 0.750X6.000X1.500 IN STEELL GRADE AISI 4140 (PD 970:2005 GRADE 708M40/42CRM40 Material Grade EN 4140 (OEM CoC Required).	
85	DGB929 86		021479013142 4 / BOLT MACHINE STEEL BSF HEX HD SZ 0.875X6.000X1.750 IN	BS 1083 THREAD SIZE 22.225MM	15 / EACH/N UMBER						TECHNICAL SPECIFICATION - DIA: 7/8" LENGTH: 6" sPEC: PD 970: 2005 MATERIAL GRADE 708M40/42 CRMO4 GENERAL SPECIFICATION - DIA: 7/8" LENGTH: 6" sPEC: PD 970:2005 MATERIAL GRADE 708M40/42 CRMO4	
86	DGB935 79		021459013101 0 / BOLT MACHINE STEEL BSF MEDIUM CLASS	BR 320 D/78	90 / EACH/N UMBER						TECHNICAL SPECIFICATION - Thread Size 5/8 Inch Nominal Length 2 1/2 Inch Length of Thread 1 1/4 Inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) METARIAL: STEEL 45 TON/SQ.IN.NTS TENSILE STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<u>REQUIRED GENERAL SPECIFICATION</u> - Thread Size 5/8 Inch Nominal Length 2 1/2 Inch Length of Thread 1 1/4 Inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) METARIAL: STEEL 45 TON/SQ.IN.NTS TENSILE STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC REQUIRED	
87	DGB93553	1A2672	0275799105473 / PICK HEAD, DIGGING TYPE, CHISEL&POINT SZ,4.50LBS EYE, UNIVERSAL NO2		27 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - STANDARD/SPECIFICATION=BS1421TABLE-2(AS PER BR320D) <u>GENERAL SPECIFICATION</u> - STANDARD/SPECIFICATION=BS1421TABLE-2(AS PER BR320D)	
88	DGB93580		0214502140586 / Bolt and Nut Steel Head Hexagonal		300 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - MATERIAL: BS 1210 Length: 8.750 inch Dia: 0.625 inch Full threaded TPI 11 <u>GENERAL SPECIFICATION</u> - MATERIAL: BS 1210 Length: 8.750 inch Dia: 0.625 inch Full threaded TPI 11	
89	DGB94399		0266590000390 / HAND CUFFS BRIGHT STEEL LARGE SIZE WITH KEY		27 / PAIR						<u>TECHNICAL SPECIFICATION</u> - made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg <u>GENERAL SPECIFICATION</u> - made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg	
90	DGT94528	BELFONT TRUWOOD TEAK	9330992246097 / PLASTIC SHEET, LAMINATED,		27 / SHEET						<u>TECHNICAL SPECIFICATION</u> - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 <u>GENERAL SPECIFICATION</u> - SIZE:8'X 4' X	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			DECORATIVE (SIZE:8'X 4' X 1MM,SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)								1/25" resistant tested to bs 476pt 1class 1	
91	DGT94585	NO DATA AVAILAB L E	9330705079704 / PLASTIC FORMICA DULL COLOUR OFF WHITE SIZE 8'X4' , THICKNESS 1.50mm		30 / SHEET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
92	DGT93912	NO DATA AVAILAB L E	0100000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	78 / SQ FEET	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
93	DGB93606		0214599410137 / NUT-PLAIN-HEX-UNC-0.75-INCH X 1.250 X0758 INCH SPEC. 1769		118 / TEN						<u>TECHNICAL SPECIFICATION - material: ms matrial steel BS 970 EN 3a,COLOUR BLACK,specs bs 1769 (heavy sieries): uncclass 2b oem coc/mtc required</u> <u>GENERAL SPECIFICATION - material: ms matrial steel BS 970 EN 3a,COLOUR BLACK,specs bs 1769(heavy sieries): uncclass 2b oem coc/mtc required</u>	
94	SGB93206		0214599410137 / NUT-PLAIN-HEX-UNC-0.75-INCH X 1.250 X0758 INCH SPEC. 1769		100 / TEN						<u>TECHNICAL SPECIFICATION - material: ms matrial steel BS 970 EN 3a,COLOUR BLACK,specs bs 1769 (heavy sieries): uncclass 2b oem coc/mtc required</u> <u>GENERAL SPECIFICATION - material: ms matrial steel BS 970 EN 3a,COLOUR BLACK,specs bs 1769(heavy sieries): uncclass 2b oem coc/mtc required</u>	
95	DGB93598		0214590430206 / NUT-PLAIN-HEXAGON-BSW-0.56INCH		100 / TEN						<u>TECHNICAL SPECIFICATION - AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) Spec: BS-970 material grade:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Rêmarks	TECH / GEN SPECS	Dimension
			THREAD SIZE 9/16"THICK 0.500								EN4140 THICKNESS: 1/4" INNER DIA: 1/2" OUTER DIA: 7/8" THREAD SIZE: 9/16" Material Grade EN4140 coc/mtc requiredGENERAL SPECIFICATION - AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) Spec: BS- 970 material grade: EN4140 THICKNESS: 1/4" INNER DIA: 1/2" OUTER DIA: 7/8" THREAD SIZE: 9/16" Material Grade EN4140 coc/mtc required	
96	DGH946 71	TSGU-400 , MIL-C- 24643/16	614500110634 1 / CABLE ELECT 3- COND/0.742" SI &GLASS INSUL PVC JKT 1000V 400A		250 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DGB940 64		026659001603 0 / WASHER FLAT ROUND MILD STEEL 0.625X0. 687X1.375X0. 128IN	O/D 34.925 INCH THK 0.128 INCH SPEC=BS 1769	146 / KILOGR AMME						TECHNICAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER REQUIREMENT IS REQUIREDGENERAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925 MM), THICKNESS 0.128" INCH (3.25 MM), NO TEMPER REQUIREMENT IS REQUIRED	