

PAKISTAN NAVY
TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 26-01-2026

TERMS & CONDITION

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT".
2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF95582	A-2120	5835765013358 / AMPLIFIER 100/120W, TOA JAPAN	PA SYSTEM	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
2	DCD95473		8440504100398 / CAP BARRET BLACK FOR CPOs/SAILOR S/FIRE BRIGADE AND PNP STAFF SIZE 7.25 INCH		700 / EACH/NUMBER						TECHNICAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE GENERAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE	item required as per tender sample
3	DCD95469		8440504100397 / CAP BARRET BLACK FOR CPOs/SAILOR S/FIRE BRIGADE AND PNP STAFF SIZE 7 INCH		800 / EACH/NUMBER						TECHNICAL SPECIFICATION - Color Pantone Shade BLACK: 19-4006 TCX Body: 100% Pure Merino Wool Lining: Artificial Silk Thread of Stitching: Polyester Dimension Stability (Wool Shrinkage): 2% Max Binding: Tape Textile Silk Corded 25 mm wide GENERAL SPECIFICATION - Color Pantone	item required as per tender sample

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Shade BLACK: 19-4006 TCX Body: 100% Pure Merino Wool Lining: Artificial Silk Thread of Stitching: Polyester Dimension Stability (Wool Shrinkage): 2% Max Binding: Tape Textile Silk Corded 25 mm wide	
4	DCW95602		8430500759140 / BATH ROOM CHAPPLE FOR SURGEON		350 / PAIR						TECHNICAL SPECIFICATION - BATH ROOM CHAPPLE FOR SURGEON GENERAL SPECIFICATION - BATH ROOM CHAPPLE FOR SURGEON	items on required as per specification s
5	DCD95471		8440504100425 / CAP BARRET BLACK FOR CPO/SAILOR SIZE 7.5 INCH		700 / EACH/N UMBER						TECHNICAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDEGENERAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE	item required as per tender sample
6	DNF95583	WT-5810 TOA	5830725207331 / SOUND AND PA SYSTEM WIRELESS TUNER WT-5810 TOA	UFFAQ W/5810c076R TOA, Germany	1 / EACH/N UMBER	Wt/5810c076R		"TOA Electronic Europe Gmbti, Suderstrabe 282, 20537 Hamburg, Germany Tel: +49 / (0) 40 / 25 17 19-0 Fax: +49 / (0) 40 / 25 17 19-98 Web: www.toa.com"	TOA Electronic sCoporati on		TECHNICAL SPECIFICATION - OEM MS TOA CORPORATION. Video Wall Matrix controllerGENERAL SPECIFICATION - OEM MS TOA CORPORATION. Video Wall Matrix controller	
7	DCD95472		8440504100395 / CAP BARRET BLACK FOR CPOs/SAILOR S/FIRE		700 / EACH/N UMBER						TECHNICAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER	item required as per tender sample

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BRIGADE AND PNP STAFF SIZE 6.50 INCH								DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDEGENERAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE	
8	DNF95585	6105.5639.10	615012364863 8 / POWER SUPPLY CABLE		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DCD95470		844050410039 6 / CAP BARRET BLACK FOR CPOs/SAILOR S/FIRE BRIGADE AND PNP STAFF SIZE 6.75 INCH		800 / EACH/NUMBER						TECHNICAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDEGENERAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE	item required as per tender sample
10	DNJ95511	6CE-12411-00	668576520249 9 / THERMOSTAT	OBM YAMAHA ENGINE FL300BETX JAPAN	9 / EACH/NUMBER	FL300BETX	6CF-1009814	YAMAHA MOTO CO LTD. 2500 SHINGAI IWATA SHIZUOKA JAPAN		YAMAHA JAPAN	TECHNICAL SPECIFICATION - OBM YAMAHA ENGINE FL300BETX JAPAN GENERAL SPECIFICATION - OBM YAMAHA ENGINE FL300BETX JAPAN	
11	DNF95507	EDG-MRS16-PRG	599573532702 6 / DG CONTROLLER INTELI LITE		2 / EACH/NUMBER	mrs16 (new model)					TECHNICAL SPECIFICATION - COMAPGENERAL SPECIFICATION - COMAP	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			MRS16									
12	DNF94383	5000VA STABIMAT IC UK	6130715068169 / UPS-MATRIX 5000VA O/P 220V 50/60 HZ (APC)	SELF END USE	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Minimum: 30 min b. Preferred: upto 60 min or above GENERAL SPECIFICATION - a. Minimum: 30 min b. Preferred: upto 60 min or above	
13	DNJ91365	RM1100B/ RM1100A	4320015707346 / RULE MATE AUTOMATIC BILGE PUMP 12VDC WITH ALL ACCE	OUTFITTING ITEM-RHIB	1 / EACH/N UMBER	RM1100B /RM1100A		RULEMATE, Maxico, www. rule-industries.com		RULEMA TE, Maxico	TECHNICAL SPECIFICATION - RULEMATE, Maxico, www.rule-industries.com Capacity: 1100GPH, with Skin fitting, One NRV, 5m flexible hose & hose clamp, 12V @ 3.4 Amp, Height: 4 1/4?, Width: 6?, Depth:3.25?, Footprint:2.75?x4.5?, Hose Size: 1 1/8?, Fuse size: 5 GENERAL SPECIFICATION - RULEMATE, Maxico, www.rule-industries.com Capacity: 1100GPH, with Skin fitting, One NRV, 5m flexible hose & hose clamp, 12V @ 3.4 Amp, Height: 4 1/4?, Width: 6?, Depth:3.25?, Footprint:2.75?x4.5?, Hose Size: 1 1/8?, Fuse size:5	
14	DNF91572	DCC/HFB M/HW/120	6730705213201 / HDMI CABLE 30M DVI TO HDMI	OPERATOR CONSOLE DCC-2012016 PAKISTAN	4 / EACH/N UMBER	DCC-2012016	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212		DATA COMM	TECHNICAL SPECIFICATION - Make: Dell or HP DISPLAY GENERAL SPECIFICATION - Make: Dell or HP DISPLAY CABLE	
15	DNF94497	ML-1102S-A & B(2 RJ-45 PORTS)/ 4V1D	6030705215937 / FIBER OPTIC MEDIA CONVERTER FOR IP CAMERAS	CCTV SYSTEM 4V1D PAKISTAN	1 / PAIR	ml-1102s-a & ml-1102s-b		Al-Sa'ee business Solutions Suit 30, 3rd Floor, Crown Centre Plot SB-1, Opp Bait-ul-Mukarram Masjid, Gulshan-e-Iqbal Karachi Tel & Fax (9221)3483-7233		Al-Sa'ee/Pro Secure	TECHNICAL SPECIFICATION - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission. GENERAL SPECIFICATION - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission.	
16	DNF95584	sc-615/ sc-630m/ TC15ML/T C10ML	9512700030004 / LOUD-SPEAKER HORN TYPE	PA SYSTEM/SRE SYSTEM	2 / EACH/N UMBER	TC15ML/ TC10ML TOA sc-615					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		TOA										
17	DNF95318	KFAE-55C	610570504423 6 / BLOWER EXHAUST 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3PHASE	EXHAUST BLOWER STEERING COMPART	18 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE GENERAL SPECIFICATION - 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE	
18	DNF95410	SMT3000I C/SURTD3 000XLI/30 00VA APC	613071506382 3 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/N UMBER	MODEL ESP-808 (E) /SYSTEK PVT.					TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART- UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
19	DNF95267	16X50 ACULON A211/DPSI 8-16X40	055278000024 5 / BINOCULAR WITH CASE	SELF & USE	4 / EACH/N UMBER	16X50 ACULON A211/DPS I AND MAKE OLYMPU S					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
20	DNF95579	Winner pro1K	6150TA524965 9 / UPS 1KVA		4 / EACH/N UMBER	Winner pro1K					TECHNICAL SPECIFICATION - Complete Details regarding 2KVA & 1KVA UPS are available in the attached Brochure named "WinnerPro" GENERAL SPECIFICATION - Complete Details regarding 2KVA & 1KVA UPS are	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											avialable in the attached Brochure named "WinnerPro"	
21	DNF95850	CC-01-00017	5935785232786 / CAT6A STP RJ45 CONNECTOR FOR ETHERNET CABLE		80 / EACH/NUMBER	RJ45					TECHNICAL SPECIFICATION - AS PER BROUCHER ENCLOSED a. Schneider Electric/Actassi Cat-6 RJ45 connectors/China/Rs 2700/50 Pcs . b. 3M Micro link /Cat-6 RJ45 Connectors/China/Rs 1999/100 Pcs. c. Black copper/Cat-6 RJ45 connectors/China/Rs 1350/100 Pcs. GENERAL SPECIFICATION - AS PER BROUCHER ENCLOSED a. Schneider Electric/Actassi Cat-6 RJ45 connectors/China/Rs 2700/50 Pcs . b. 3M Micro link /Cat-6 RJ45 Connectors/China/Rs 1999/100 Pcs. c. Black copper/Cat-6 RJ45 connectors/China/Rs 1350/100 Pcs.	
22	DNF9580	toten 6u	5930705246311 / networking switch rack toten 6u 600 x 600 single section 1 fixed tray, 2 fan.		4 / UNIT	TOTEN 6U					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
23	DNF95533	SBS- MF 673-22 / WINXP (SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		12 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLE GENERAL SPECIFICATION - 4G DATA WINGLE	
24	DNF95323	SBS- MF 673-22 / WINXP (SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLE GENERAL SPECIFICATION - 4G DATA WINGLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
25	DNF9541 1	KNOX / INFINISOL AR/YUKO N II	613071530065 5 / HYBIRD SOLAR INVERTER 6KW / 5.5 KW MPPT CHARGER		1 / EACH/N UMBER	INFINISO LAR E 5.5 KW					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
26	DNO952 69	hr1234w f2/ WP 1236W- LONG	614001618242 1 / BATTERY, RECHARGABL E (12V, 34W)		75 / EACH/N UMBER	8GSYBTU					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
27	DNF9564 2	AA2500ma h	614071528191 0 / battery pack rechargeable NIMH (pack of 4) DURACELL AA 2500MAH		30 / PACKE T	AA2500M AH					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
28	DNG958 44	MIL-I- 24391	597000419429 1 / TAPE INSULATION ELECT ADHES PLASTIC BLK LG1296"W.75" TH.0085"	CIWS consumble	30 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DNF9540 8	STAVOL/S TABIMATI C	611070505492 2 / STABILIZER 5KVA I/P 160- 240V O/P220V 50HZ S/CONT	GENERAL ELECTRICAL USE.	3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
30	DNF9584 7	E91 LR6 / E91 IEC LR6	613579505849 2 / BATTERY ALKALINE (ENERGIZER) (Non Rechargeable) 1.5V AA SIZE NO.E91 IEC LR6	GENERAL USE	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
31	DNF9534 4	7-427-510	392050505695 8 / TROLLY ELECT FOOD WARMING SYSTEM S/STEEL 220V 1PH	PNS SHIFA	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - (a)- Main frame (top/body)in SS201 material, machine pressed and international standard finishing. (b)- Four iron synthetic Plastic covered tires castors 6" with 2 casters with breaks. (c)- Two top doors opening	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			44X30X41/48 Inch.								along with side rest for door support. <u>GENERAL SPECIFICATION</u> - (a)- Main frame (top/body)in SS201 material, machine pressed and international standard finishing. (b)- Four iron synthetic Plastic covered tires castors 6" with 2 casters with breaks. (c)- Two top doors opening along with side rest for door support.	
32	DNF95395	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	0562795620006 / BATTERY LEAD ACID 12V 200AH	DG USED	4 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					<u>TECHNICAL SPECIFICATION</u> - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA <u>GENERAL SPECIFICATION</u> - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
33	DNF95321	06070301	2590999100334 / HORN ELECTRICAL 24V AC/DC 3AMP C/W BRACKET (SOGO CHINA BRAND)		3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - OEM, M/S SOGO GROUP COMPNIES CHINA. WWW. SOGOLIGHTINGWORLD. <u>GENERAL SPECIFICATION</u> - OEM, M/S SOGO GROUP COMPNIES CHINA. WWW. SOGOLIGHTINGWORLD.COM	
34	DNZ95407	FCS035C / CV - 165	5975705227475 / CABLE TIES 144mm 1PC	37MM UPGRADED GUN	652 / EACH/NUMBER	N/A		KRL / PAK		KRL / PAK	<u>TECHNICAL SPECIFICATION</u> - Cable Ties Nylon 144mm <u>GENERAL SPECIFICATION</u> - Cable Ties Nylon 144mm	
35	DNF95398	683-576	3413795137753 / DRILLING MACHINE	DRILILING MACHINE	1 / EACH/NUMBER	NO DATA AVAILAB LE		UK		AIR SYSTEM UK LTD	<u>TECHNICAL SPECIFICATION</u> - a. Product: Tiger 600W drill with accessories. b. Input: 600W. c. Capacity: 20mm. SPEED 0 TO 1500 CHUCK 3 JAW 10MM POWER 240V 50HZ <u>GENERAL SPECIFICATION</u> - a. Product: Tiger 600W drill with accessories. b. Input: 600W. c. Capacity: 20mm. SPEED 0 TO 1500 CHUCK 3 JAW 10MM POWER 240V 50HZ	
36	DNF95846	E93 (C)	6135715179433 / 1.5 V +C SIZE ENERGIZER PILE ALKALINE	CTD.SV PROBE	50 / EACH/NUMBER	SNI 04-205-2-2004	SNI 04-205-2-2004	Energizer Holding Inc st Louis MO 63141 UNITED STATES OF AMERICA		ENERGIZER . USA	<u>TECHNICAL SPECIFICATION</u> - 1.5 VOLT PILE ALKALINE BATTERY. USEFUL FOR SURVEY OPERATION. GOOD CURRENT RATE. C SIZE CELL CLASSIFICATION: ALKALINE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BATTERY								CHEMICAL SYSTEMS: ZINC-MANGANESE DIOXIDE. NO ADDED MERCURY OR CADMIUM DESIGNATION: IEC-LR14 NOMINAL VOLTAGE: 1.5 VOLTS, NOMINAL IR: 150 TO 300 MILLIOHMS OPERATING TEMP: -18C TO 55C TYPICAL WEIGHT: 66 GMS TYPICAL VOLUME: 27 CUBIC CENTIMETERS JACKET: PLASTIC LABEL SHELF LIFE: 7 YRS AT 21C TERMINAL: FLAT CONTACT oem: m/s Energizer <u>GENERAL SPECIFICATION</u> - 1.5 VOLT PILE ALKALINE BATTERY. USEFUL FOR SURVEY OPERATION. GOOD CURRENT RATE. C SIZE CELL CLASSIFICATION: ALKALINE CHEMICAL SYSTEMS: ZINC-MANGANESE DIOXIDE. NO ADDED MERCURY OR CADMIUM DESIGNATION: IEC-LR14 NOMINAL VOLTAGE: 1.5 VOLTS, NOMINAL IR: 150 TO 300 MILLIOHMS OPERATING TEMP: -18C TO 55C TYPICAL WEIGHT: 66 GMS TYPICAL VOLUME: 27 CUBIC CENTIMETERS JACKET: PLASTIC LABEL SHELF LIFE: 7 YRS AT 21C TERMINAL: FLAT CONTACT oem: m/s Energizer	
37	DNF95320	SC-630M/SC-615M TOA	596525151194 6 / SPEAKER 3-15 WATT (HORN TYPE) WITH MATCHING TRANSFORMER & ACCESSORIES.	PRESENT COFIGURATION SRE SYST	25 / EACH/NUMBER	SC-615M TOA		JP		SOURCE: M/S KYAF CORPORATION, 24 NATIONAL TV. MARKET SOHRAB KHATRAK ROAD SADDR KARACHI .TEL: 0092-21-	TECHNICAL SPECIFICATION - SOURCE: M/S KYAF CORPORATION, 24 NATIONAL TV. MARKET SOHRAB KHATRAK ROAD SADDR KARACHI. TEL: 0092-21-5685654 & 5680739. SPECS: SPEAKER 3-15 WATT (HORN TYPE) MATCHING TRANSFORMER & ACCESSORIES. PRICE RS: 3000 EACH. <u>GENERAL SPECIFICATION</u> - SOURCE: M/S KYAF CORPORATION, 24 NATIONAL TV. MARKET SOHRAB KHATRAK ROAD SADDR KARACHI.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									5685654&5680739.		TEL:0092-21-5685654&5680739. SPECS:SPEAKER 3-15 WATT (HORN TYPE)MATCHING TRANSFORMER&ACCESSORIES. PRICE RS:3000 EACH.	
38	DNJ95270	17471-98J01-000	2920765222099 / PANEL, PUMP CASE UNDER	SUZUKI DF300AP 300 HP OBM	3 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION</u> - OEM: SUZUKI MOTOR JAPAN <u>GENERAL SPECIFICATION</u> - OEM: SUZUKI MOTOR JAPAN	
39	DNF95459	N-120 / 6-QA-120, N-150 / n-150 12v 120 ah	6130785173196 / 12V 120 A/H BATTERY EXIDE	D/G KABOTA 20KVA	2 / EACH/NUMBER	N-120 VOLTA		SAIL FENG FAN BATTERY CO LTD CHINA	M/S SAIL		<u>TECHNICAL SPECIFICATION</u> - SAIL FENG FAN BATTERY CO LTD CHINA H=200 mm W=180 mm L=490 mm <u>GENERAL SPECIFICATION</u> - SAIL FENG FAN BATTERY CO LTD CHINA H=200 mm W=180 mm L=490 mm	
40	DNF95543	NP2.1-12	6515795172394 / VALVE REGULATED LEAD ACID BATTERY LENGTH (12V 2.3 AH)	MIDAS	4 / EACH/NUMBER			YUASA CORPORATION UK	YUASA CORPORATION UK		<u>TECHNICAL SPECIFICATION</u> - YUASA CORPORATION <u>GENERAL SPECIFICATION</u> - YUASA CORPORATION UK	
41	DNF94038	RG-NBS3100-24GT4SFP /J9776A / J9772A+j4 859c	5895785207833 / NETWORK SWITCH HP 2530 24G/48G WITH 2/4 SFP MODULES	NETWORK SWITCH J9772A CHINA	2 / EACH/NUMBER	RG-NBS5200-48GT4xS/ R8N88A-HP/J9776A/J9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA		<u>TECHNICAL SPECIFICATION</u> - ATTACHED <u>GENERAL SPECIFICATION</u> - ATTACHED	
42	DNN94567	3888555	3110735180594 / BEARING	engine gearbox	1 / EACH/NUMBER			AB volvo penta, Gropegardsgatan, 405 08 Gote borg, Sweden	AB volvo penta, gote borg, sweden		<u>TECHNICAL SPECIFICATION</u> - item required for the rectification of OPDEF of MST boat gear box <u>GENERAL SPECIFICATION</u> - item required for the rectification of OPDEF of MST boat gear box	
43	DNF94563	TH12-42AH/6FM 45-X/ LC-P1242/ LC-X1242	6130765163092 / BATTERY M/FREE LEAD ACID 12V 42-45 AH.	FOR UPS 15 KVA 03 PHASE	1 / EACH/NUMBER	6FM45-X/ LC-P1242/ LC-X1242		PANASONIC SADDAR KARACI.TECHNO POWER SYSTEM	PANASONIC SADDAR KARACI.TECHNO POWER SYSTEM		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
44	DNF94290	NIL	4920705141287 / NETWORK CABLE	BASIC ELECTRONIC WARFARE	2 / EACH/NUMBER	NO DATA AVAILAB LE		PK	M/S DATA CUMMUN		<u>TECHNICAL SPECIFICATION</u> - OEM ADD/SOURCE OF AVAILABILITY:M/S DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			TESTER WITH TOOL	TRAIN					ICATION & CONTROL (PVT) LTD.409 CLIFTON CENTER DC-1, BLOCK-5, KARACHI .75600.		COMMUNICATION&CONTROL (PVT)LTD.409 CLIFTON CENTER DC-1,BLOCK-5,KARACHI. 75600GENERAL SPECIFICATION - OEM ADD/SOURCE OF AVAILABILITY:M/S DATA COMMUNICATION&CONTROL (PVT)LTD.409 CLIFTON CENTER DC-1,BLOCK-5,KARACHI.75600	
45	DNF93264	3BA23265	711070520497 1 / ANALOGUE EXTENSION BOARD (EZ 32-2)/ EZ 32	Navcomm Switches OXE FRANCE	12 / EACH/N UMBER	EZ 32-2	-	Immeuble Cyteo, 147, Avenue Paul Doumer 92500, Rueil-MALMAISON France.	M/s Alcatel Lucent France		TECHNICAL SPECIFICATION - This board is used to provide 32 Analogue Numbers.GENERAL SPECIFICATION - This board is used to provide 32 Analogue Numbers.	
46	DNF92089	GY 6.35	624015218393 1 / MARINE ENGINE ROOM LIGHT	PORTAL CRANE FD-IV	1 / EACH/N UMBER	GY 6.35	N/A	M/S DRSA	M/S DRSA		TECHNICAL SPECIFICATION - METALIC CAGE LIGHT WITH GLASS RATED VOOLTAGE 220 V FREQUENCY 50/60 HZGENERAL SPECIFICATION - METALIC CAGE LIGHT WITH GLASS RATED VOOLTAGE 220 V FREQUENCY 50/60 HZ	
47	DNF89024	FXTM2 32 / ONYX-32	599671514367 4 / MIXER PRE AMPLIFIER (PEAVY)	PA SYSTEM	1 / EACH/N UMBER	FXTM2 32		US	M/S:KYAF CORPORATION,24 NATIONAL T.V. MARKET SOHRAB KHATRA K ROAD SADDAR KARACHI ,TEL: 0092-21-5685654&5680739		TECHNICAL SPECIFICATION - b. Specification: 32 channels Dual effect processors Digital audio ports interface 600 Ohm Mics supported c. Power Supply 220 V AC single Phase & 24 V DC d. Acceptance criteria 32 Mic should be ON at a time. High gain with no noise and distortion for crystal clear signal reproduction onboard e. Dimensions Height 92 cm approx. Width 64 cm approx. Depth 30 cm approx. Weight 21 kg approx. SOURCE OF AVAILABILITY:KYAF CORPORATION,24 NATIONAL T.V. MARKET SOHRAB KHATRAK ROAD KARACHI.TEL:0092-21-5685654&5680739.GENERAL SPECIFICATION - b. Specification: 32 channels Dual effect processors	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Digital audio ports interface 600 Ohm Mics supported c. Power Supply 220 V AC single Phase & 24 V DC d. Acceptance criteria 32 Mic should be ON at a time. High gain with no noise and distortion for crystal clear signal reproduction onboard e. Dimensions Height 92 cm approx. Width 64 cm approx. Depth 30 cm approx. Weight 21 kg approx. SOURCE OF AVAILABILITY: KYAF CORPORATION, 24 NATIONAL T.V. MARKET SOHRAB KHATRAK ROAD KARACHI. TEL: 0092-21-5685654 & 5680739.	
48	DNZ93271	98660/1153	5330014155547 / WASHER	MAIN AIR COMPRESSOR	1 / EACH/NUMBER	NO DATA AVAILABLE		UK	COMPAIR UK LTD ENGLAND		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
49	DNF94323	3549.8550.00	5995725138624 / DATA CABLE SCREENED 8 CORE	XK-2900L 1KW TX BERQV	60 / METER	NO DATA AVAILABLE		GR	GERMAN YROHDE & SCHWARZ		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
50	DNF88180	EN60 898 TDC TIM DIN	5925765160799 / MCB 2 POLE 220V 10AMPS	CONVERSION OF BOATSWAIN INTO MRO/BEHR KUSHA	10 / EACH/NUMBER	EN60 898 TDC TIM DIN		M/S DIGI TECH SHOP NO2 NEW MEMON CHAMMBER ALTAH HUSSAIN ROAD DENSO HALL KARACHI-7400 ,TEL: 2639514&2638482	M/S DIGI TECH SHOP NO2 NEW MEMON		<u>TECHNICAL SPECIFICATION - M/S DIGI TECH SHOP NO2 NEW MEMON CHAMMBER ALTAH HUSSAIN ROAD DENSO HALL KARACHI-7400 ,TEL: 2639514&2638482</u> <u>GENERAL SPECIFICATION - M/S DIGI TECH SHOP NO2 NEW MEMON CHAMMBER ALTAH HUSSAIN ROAD DENSO HALL KARACHI-7400 ,TEL: 2639514&2638482</u>	
51	DNC90823	WBCL002 320/cn-btu-60000	4130745133153 / CHILLER 60000 BTU	A/C SYSTEM PNS KARRAR	1 / EACH/NUMBER	NO DATA AVAILABLE		FR	WEBAST O MARINE COMFORT FRANCE		<u>TECHNICAL SPECIFICATION - CHILLER 60000 BTU</u> <u>GENERAL SPECIFICATION - CHILLER 60000 BTU</u>	
52	DNF95131	CMS-118	5998705219304 / POWER EXTENSION BOARD	SM RACK	2 / EACH/NUMBER	CMS-118 (CAMELLION)	NA	Commercially Of The Shelf (COTS)/Local Market	COTS		<u>TECHNICAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan</u> <u>GENERAL SPECIFICATION - 220V</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CAMELLION MODEL CMS-118								Power Connection Board. Used in mounting racks.pakistan	
53	SNF51754	ACC2425BB-3	5925725129139 / CIRCUIT BREAKER 24VDC, 25AMPS(F8)	CUMMUNICAT ION SYSTEM	2 / EACH/NUMBER			GR		DIGI TECH DENSO HALL KARACHI	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
54	DNJ92238	6CE-81975-00	5340765203987 / PLATE, RECTIFIER FITTING	YAMAHA OBM	1 / EACH/NUMBER	NO DATA AVAILAB LE	6CE-1029885, 6CF-1009814	YAMAHA MOTOR CO. LTD JAPAN		JAPAN	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
55	DNG73970	5228785	2910008486764 / FUEL INJECTOR		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DNF94868	1106	5825705118323 / BATTERY CHARGER I/P220V 50HZ 1PH O/P 48V (12X4) 20A WITH ACCE		1 / EACH/NUMBER	GZL30A-6/48V					TECHNICAL SPECIFICATION - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC: OEM: Nanchang Shuguang Eledricd Equipment Factory GENERAL SPECIFICATION - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC: OEM: Nanchang Shuguang Eledricd Equipment Factory	
57	DNF94985	6 242 01	6130997427670 / CHARGER PANEL LIGHT, TYPE 10-MODIFIED 110/130V AND 200/250V 50/60HZ	PANNEL LIGHT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - country of origin uk GENERAL SPECIFICATION - country of origin uk	
58	DNF92678	38109-829 rev D/ GS-55	5910735120721 / pro Dynamic CARDIOD VOCAL MICROPHONE Electro-voice	PA SYSTEM	2 / EACH/NUMBER	ELECTR O VOICE					TECHNICAL SPECIFICATION - OEM, ELECTRO-VOICE USA. TECH-SPECS, Wired handheld microphones. DYNAMIC N/DYM MAGNET 45HZ-15000 HZ CARDIOD Non reflecting black finish. On/Off switch. 3-pin XLR connector. Weight	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											238gm GENERAL SPECIFICATION - OEM, ELECTRO-VOICE USA. TECH-SPECS, Wired handheld microphones. DYNAMIC N/DYM MAGNET 45HZ-15000 HZ CARDIOD Non reflecting black finish. On/Off switch. 3-pin XLR connector. Weight 238gm	
59	DNF92858	33010319	414099260927 2 / FAN SPEED TRANSDUCER		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - FAN SPEED TRANSDUCER GENERAL SPECIFICATION - FAN SPEED TRANSDUCER	
60	DNF76594	AS(U) M332M500 DF1	591075531634 5 / CAPACITOR 3300 uf 500V DC AYX-HR (M)		9 / EACH/NUMBER	AYX-HR (M)					TECHNICAL SPECIFICATION - Capacitor 3300MF 500V BATTERY CHARGING SYSTEM INDICATION MONITORING SYSTEM ANTI CONDENSATION HEATER AUDIBLE ALARM SYSTEM LIGHT INDICATOR FOR POWER ON/OFF SEPARATE CONTROL AND BATTERY BANK CABINET WITH WHEEL MOUNTING FOR EASE OF MOVEMENT. GENERAL SPECIFICATION - Capacitor 3300MF 500V BATTERY CHARGING SYSTEM INDICATION MONITORING SYSTEM ANTI CONDENSATION HEATER AUDIBLE ALARM SYSTEM LIGHT INDICATOR FOR POWER ON/OFF SEPARATE CONTROL AND BATTERY BANK CABINET WITH WHEEL MOUNTING FOR EASE OF MOVEMENT.	
61	DCW94674		843050000002 9 / BOOT DMS SIZE 7		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7 GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7	ITEMS AS PER SPECIFICATION
62	DCW94680		843050000003 5 / BOOT DMS SIZE 9 MEDIUM		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9 MEDIUM GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE	ITEMS AS PER SPECIFICATION

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											9 MEDIUM	
63	DN090686	DL-473WDL02 4-02-07-02 / 473WDL02 4-02-07-02/ZACR-061-SEW	4110FP305006 1 / Anti-corrosion zinc bar (Fresh keeping device)		4 / EACH/NUMBER	473WDL024-02-07-02					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
64	DCW94686		843050000157 7 / BOOT DMS SIZE 14 MEDIUM		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 MEDIUM GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 MEDIUM	ITEMS AS PER SPECIFICATION
65	DCW94679		843050000003 6 / BOOT DMS SIZE 9L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L	ITEMS AS PER SPECIFICATION
66	DNF94694	134-88-01	599879528498 9 / KEYPAD		1 / EACH/NUMBER	134-88-01					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
67	DCW94682		843050000003 4 / BOOT DMS SIZE 9S		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S	ITEMS AS PER SPECIFICATION
68	SNC93371	X00003420	293012386012 0 / ELBOW TO PLATE-CORE COOLE		1 / EACH/NUMBER	8V 2000 M84					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
69	DNJ91674	65770-90J02	299076531025 8 / PUMP, SQUEEZE		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
70	DCW94685		843050000157 8 / BOOT DMS SIZE 14 LARGE		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE	ITEMS AS PER SPECIFICATION
71	DNO952	US050361	543075535016		1 /	varem-					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
66		CS000000	5 / PRESSURE TANK 50 litre 10 bar		EACH/NUMBER	maxivare m ls					PRESSURE MEMBRANE TANK 50 LITRE 10 BAR DIMM= 793X393X403 MM WEIGHT 12.9KG CAPACITY 50LITERS MAX PRESSURE 10BAR TEST PRESSURE 15 BARGENERAL SPECIFICATION - PRESSURE MEMBRANE TANK 50 LITRE 10 BAR DIMM= 793X393X403 MM WEIGHT 12.9KG CAPACITY 50LITERS MAX PRESSURE 10BAR TEST PRESSURE 15 BAR	
72	DCW94676		8430500000033 / BOOT DMS SIZE 8L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8L	ITEMS AS PER SPECIFICATION
73	DCP93165		6532500400063 / BLANKET SCARLET RED HOSPITAL		36 / EACH/NUMBER						TECHNICAL SPECIFICATION - BLANKET SCARLET RED HOSPITAL GENERAL SPECIFICATION - BLANKET SCARLET RED HOSPITAL	
74	DNF94696	134-88-25	5998795284991 / LCD ASSEMBLY		1 / EACH/NUMBER	134-88-25					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
75	SNC93372	X59414500018/87	2815725300671 / EXHAUST PIPE BELOWS		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - WEIGHT: 13.500KGGENERAL SPECIFICATION - WEIGHT: 13.500 KG	
76	DNO91574	ST2SAAEHENAE310	5998505314290 / AZIMUTH HOLLOW ENCODER		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
77	DCW94683		84305000000045 / BOOT DMS SIZE 12L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L	ITEMS AS PER SPECIFICATION
78	DN093007	RK 50/65-SEW	2815785284968 / rEDUCER COUPLING (DN 50 TO DN 65 - 2 INCH TO 3		4 / EACH/NUMBER	RK 50/65-SEW					TECHNICAL SPECIFICATION - ALUMINIUM ALLOY COUPLING WITH RUBBER SEALSGENERAL SPECIFICATION - ALUMINIUM ALLOY COUPLING WITH RUBBER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH) FOR FF HOSE								SEALS	
79	DCW94673		8430500000025 / BOOT DMS SIZE 6S		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 6S GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 6S	items as per specification
80	DNO91240	526-3696	6620775259155 / SENSOR GP- OIL LEVEL		2 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
81	DNF94695	A074A900	5998795284988 / system control board scb1		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - OEM:M/S HARTRIDGE NETWORK RADCLIVE ROAD ,BUCKINGHAM,MK 18,4FD,UK LOCAL SOURCE:M/S COUNTRY WIDE TRADE LINKERS 9-D,1ST FLOOR,CANTT BAZAR AREA MALIR CANTT KARACHI-75070. GENERAL SPECIFICATION - OEM:M/S HARTRIDGE NETWORK RADCLIVE ROAD ,BUCKINGHAM,MK 18,4FD,UK LOCAL SOURCE:M/S COUNTRY WIDE TRADE LINKERS 9-D,1ST FLOOR,CANTT BAZAR AREA MALIR CANTT KARACHI-75070.	
82	DCP94374		6532500601092 / SHEET HOSPITAL WHITE COTTON SIZE 100"X68" (254X170CM)		450 / EACH/NUMBER						TECHNICAL SPECIFICATION - SHEET HOSPITAL WHITE COTTON SIZE 100"X68" (254X170CM) GENERAL SPECIFICATION - SHEET HOSPITAL WHITE COTTON SIZE 100"X68" (254X170CM)	
83	DCW94678		84305000000031 / BOOT DMS SIZE 8S		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8S GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8S	ITEMS AS PER SPECIFICATION
84	DNJ91673	15642-88L10	2940765308432 / FILTER		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
85	DCW94684		8430500001576 / BOOT DMS SIZE 13		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 13 GENERAL	ITEMS AS PER SPECIFICATION

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LARGE								SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 13 LARGE	TION
86	DCW94677		843050000003 2 / BOOT DMS SIZE 8 M		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8 M <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8 M	ITEMS AS PER SPECIFICATION