

**PAKISTAN NAVY**  
**TENDER BULLETIN**

**INVITATION TO TENDER TO BE OPENED ON 04-02-2026**

**TERMS & CONDITION**

- 1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT".**
  
- 2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.**
  
- 3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.**

## TENDER BULLETIN

ATE & TIME 1/21/26 12:28 PM INVITATION TO TENDER TO BE OPENED ON 2/4/26 10:00 AM AND ITEM REQ BY

**CONDITIONS**

NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.

FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.

LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE954 60		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/N UMBER						<b>TECHNICAL SPECIFICATION -</b> SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS & WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS & WATER PROOF (WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150- 180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3. ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES:	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY</p> <p><u>GENERAL SPECIFICATION</u>  - SPECIFICATION: 1. SIZES/ DIMENSION • LENGTH: 8 METER • WIDTH: 5 METER • HEIGHT OF TENT: 3.00 METER • HEIGHT OF WALLS: 1.80 METER (DETACHABLE ALL ROUND WITH SUITABLE DOORS &amp; WINDOWS), • (DIMENSION TOLERANCE: ± 2%) 2. SPECIFICATION: • OUTER FOLD CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF, FUNGUS PROOF AND FIRE PROOF (WEIGHT: 20 OZS PER M2), • MIDDLE FOLD: FOLD MADE OF BLACK DYED COTTON SHEETING FOR PREVENTION OF SUN RAYS &amp; WATER PROOF (WEIGHT: 04 OZS PER M2), • INNER FOLD: INNER FOLD MADE OF COLOURED SHEETING OF 150-180 G/M2 (5/6 OZS PER M2), • DOOR: 02 X DOORS, • WINDOW: 06 X WINDOWS, • TAPE NEWAR: CANVAS COTTON, • COLOUR: JUNGLE GREEN (COLOUR CODE : 3A5F31), • MATERIAL: DOUBLE COTTON CANVAS 3. ACCESSORIES REQUIRED: • STANDING POLES: 03 X QTY, • RICH POLES: 02 X QTY, • ROPES: 20 X QTY STANDARD SIZE, • PEGS: 20 X QTY STANDARD SIZE, • HAMMER: 01 X QTY (03 KG</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WEIGHT WITH WOODEN HANDLE 1.5 FT) • DIAMETER OF POLE: 40 MM, • GAUGE OF POLE: 16 GAUGE • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND: POLYETHYLENE SHEET (FIRE PROOF 200 GSM) • PACKING BAG: 01 QTY	
2	DGE95971		834070508791 6 / TENT MARQUEE UNIVERSAL G. S (SIZE 27X19.6FT) FOLD & FLY TWO (J/GREEN)	GENERAL PURPOSE	2 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - 1. SIZE: • LENGTH: 27 FEET (±0.5 FEET), • WIDTH: 19.6 FEET (±0.2 FEET), • CENTER HEIGHT: 12.30 FEET, • WALL HEIGHT: 5.90 FEET, 2. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 3. SPECIFICATION: • 550/ 600 GSM (± 5%) 100 % WATER PROOF COTTON CANVAS, • WATER AND ROT RESISTANT, • GROUND SHEET AND MUD FLAP: 180 GSM (± 5%, 4. LIST OF ACCESSORIES= • STANDING POLES: 02 QTY, • RIDGE POLE: 01 QTY, • SIDE/ WALL POLES: 08-12 QTY • CORNER POLES: 04 X QTY • HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) • IRON PEGS: 24 QTY (45/45 CM LONG THICKNESS 18/19 MM • GUY ROPES: 48 QTY, THICKNESS: 14-MM, LENGTH: 3.60 MTR.) • WALL PIPE LATHI: 24 QTY • DIAMETER OF POLES: 54 MM • GAUGE OF POLES: 1.5 MM • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET • PACKING: 02 QTY</p> <p>GENERAL SPECIFICATION - 1. SIZE: • LENGTH: 27 FEET (±0.5 FEET), • WIDTH: 19.6 FEET (±0.2 FEET), • CENTER HEIGHT: 12.30 FEET, • WALL HEIGHT: 5.90 FEET, 2. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 3.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SPECIFICATION: • 550/ 600 GSM (± 5%) 100 % WATER PROOF COTTON CANVAS, • WATER AND ROT RESISTANT, • GROUND SHEET AND MUD FLAP: 180 GSM (± 5%, 4. LIST OF ACCESSORIES=</p> <ul style="list-style-type: none"> <li>• STANDING POLES: 02 QTY, • RIDGE POLE: 01 QTY, • SIDE/ WALL POLES: 08-12 QTY • CORNER POLES: 04 X QTY • HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET)</li> <li>• IRON PEGS: 24 QTY (45/45 CM LONG THICKNESS 18/19 MM • GUY ROPES: 48 QTY, THICKNESS: 14-MM, LENGTH: 3.80 MTR,) • WALL PIPE LATHI: 24 QTY • DIAMETER OF POLES: 54 MM • GAUGE OF POLES: 1.5 MM • LENGTH OF PINS: 12 INCH • FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET • PACKING: 02 QTY</li> </ul>	
3	DGE960 21	R	834570504262 9 / Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter)	ITEM REQUIRED FOR MAKING OF GIFT BOXES	22 / METER						<p><u>TECHNICAL SPECIFICATION -</u> Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes</p> <p><u>GENERAL SPECIFICATION -</u> Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes</p>	
4	DGE955 20	NO DATA AVAILAB LE	834050503926 0 / TENT 180 LBS MILITARY PATTERN MK-4 WITH ALL ACCESSORIES (COMPLETE SET)		5 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: 1. SIZES/ DIMENSION A. LENGTH: 4.25 MTR (±2%), B. WIDTH: 4.25 MTR (±2%), C. CENTRAL HEIGHT: 2.40 MTR (±2%), D. WALL HEIGHT: 0.90 MTR, E. THICKNESS: 2 MM, F. DIA: 52-56 MM, G. FILES: 02, H. FOLDS: 02, J. POLE: 05 MS POLE 2. COLOUR: JUNGLE GREEN (COLOR CODE: 3A5F31). 3. TENT ROOF: A. MADE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>OUT OF 450/G M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF AND VAT DYED CANVAS. B. TENT WALL: MADE OUT OF 400G / M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF AND VAT DYED CANVAS. C. INNER LINING: MADE OUT OF 180G / M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF. D. PACKING COMPLETE TENT AND ACCESSORIES IN ONE BAG WITH RAW MATERIAL. 4. ADVANCE SAMPLE TO BE APPROVED BY CINS. 5. LIST OF ACCESSORIES: A. IRON PIN: 22 B. ROPES: 22 X QTY QTY (STANDARD SIZE) C. BAMBOO (STAND POLE): 03 D. PIG POLE: 02 X QTY STANDARD SIZE E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET)GENERAL SPECIFICATION - SPECIFICATION: 1. SIZES/ DIMENSION A. LENGTH: 4.25 MTR (±2%), B. WIDTH: 4.25 MTR (±2%), C. CENTRAL HEIGHT: 2.40 MTR (±2%), D. WALL HEIGHT: 0.90 MTR, E. THICKNESS: 2 MM, F. DIA: 52-56 MM, G. FILES: 02, H. FOLDS: 02, J. POLE: 05 MS POLE 2. COLOUR: JUNGLE GREEN (COLOR CODE: 3A5F31). 3. TENT ROOF: A. MADE OUT OF 450/G M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF AND VAT DYED CANVAS. B. TENT WALL: MADE OUT OF 400G / M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF AND VAT DYED CANVAS. C. INNER LINING: MADE OUT OF 180G / M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF. D. PACKING COMPLETE TENT AND</p>	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ACCESSORIES IN ONE BAG WITH RAW MATERIAL. 4. ADVANCE SAMPLE TO BE APPROVED BY CINS. 5. LIST OF ACCESSORIES: A. IRON PIN: 22 B. ROPES: 22 X QTY QTY (STANDARD SIZE) C. BAMBOO (STAND POLE): 03 D. PIG POLE: 02 X QTY STANDARD SIZE E. HAMMER: 01 X QTY (03 KGS WEIGHT WITH WOODEN HANDLE 1.5 FEET)	
5	DGE95577	NO DATA AVAILABLE	834050503926 2 / QANAT COMPLETE SIZE 18.X 7. OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		10 / EACH/NUMBER						<p><b>TECHNICAL SPECIFICATION -</b>  Length: 18 feet. Width: 7 feet.  COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 &amp; 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON,BAMBO MATURED &amp;TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.<b>GENERAL SPECIFICATION -</b> Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 &amp; 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED &amp;TREATED WITH PRESERVATIVE (INSERTED</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
6	DGE96046	NO DATA AVAILABLE	8415705045705 / CLOTH PARASHUTE WHITE	CEREMONAL ACCOMODATION ON SCREEN	130 / METER						TECHNICAL SPECIFICATION - a. Nylon 1680D, PU Coating, Water Proof (Packing 50 yard per Roll, Width 5 Ft) b. $\pm 2\%$ tolerance is acceptable GENERAL SPECIFICATION - a. Nylon 1680D, PU Coating, Water Proof (Packing 50 yard per Roll, Width 5 Ft) b. $\pm 2\%$ tolerance is acceptable	
7	DGD96291	NO DATA AVAILABLE	024750000019 / GAS BURNER WITH HANDLE VALVE FITTED IN A ROUND STEEL FRAME TH 6mm,H 8" WITH 20FT RUBBER TUBE		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - ROUND STEEL FRAME Thickness: 6MM, Height: 8" WITH 20FT RUBBER TUBE GENERAL SPECIFICATION - ROUND STEEL FRAME Thickness: 6MM, Height: 8" WITH 20FT RUBBER TUBE	
8	DGB96251	NO DATA AVAILABLE	0265500001496 / NAIL STEEL SZ LG 41MM DIA 4MM		22 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DGE95863	NO DATA AVAILABLE	9330705052043 / PLASTIC SHEET BLACK SIZE 4.X 4.X 1/8	FOR CNS STATE BOARD	5 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
10	DGE96042	NIL	9340731000995 / E-GLASS FIBER (POWDER) CHOPPED STRAND MAT	GRP BOATS	127 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2 GENERAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CHINA e. TYPE 450 G/M2	
11	DGE960 30	BS 419/156	055954600536 2 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		40 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
12	DGE957 99		045154600446 4 / TAPE, COTTON WIDTH 3/4 INCH 50 MTR ROLL QUALITY HEAVY.		60 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
13	DGE960 22		834570511986 2 / SATTON CLOTH WHITE	PRESENTATIO N VIP ITEM	15 / METER						TECHNICAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches GENERAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches	
14	DGE961 23	N/A	933070518127 9 / PLASTIC SHEET	GENERAL ITEM	15 / ROLL			LOCAL MARKET		GENERA L ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
15	DGD961 67	T52254 / E-6228	732099759431 1 / VEGETABLE PEELING MACHINE, ELECTRIC	GALLEY	1 / EACH/N UMBER	NO DATA AVAILAB LE		UK		HOBART MANUFA CTURING UK, STREET BRAUNT ON ROAD CITY BARNST APLE, STATE OR PROVINC E, DEVON, COUNTR	TECHNICAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT. 440V GENERAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT.440V	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									Y UK POST-ZIP CODE. EX31 1GD, TELEPHO NE, 01271347 500, TELEFAX  01271347 502			
16	DGH963 40	LCKHB108 1182B	302070520258 0 / BEAM PR 2740X240	RACKS	35 / EACH/N UMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021- 5388726		HABIB & SONS	<b>TECHNICAL SPECIFICATION -</b> Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l- type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5 <b>GENERAL SPECIFICATION</b> _Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l- type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
17	DGE957 98		033050942726 7 / FLANNELETTE CLOTH WHITE GROUND WITH RED STRIPT 4*X50 YARDS	SMALL ARMS CLEANING	2200 / METER						<b>TECHNICAL SPECIFICATION -</b> BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural. <b>GENERAL SPECIFICATION</b> _BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural.	
18	DGB962 36		027779923816 4 / TOOL BOX PORTABLE		44 / EACH/N UMBER						<b>TECHNICAL SPECIFICATION - A.</b> multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											d. size: 29x3x8 cm <b>GENERAL SPECIFICATION</b> - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm	
19	DGB951 96	SPEC: NES837 , DG SHIPS 8556B	028259571216 3 / PIPING COPPER RD SEAMLESS EXT.DIA 0.625" THK.0.036" SWG 20		30 / METER						<b>TECHNICAL SPECIFICATION</b> - a. External Diameter : 0.625 inch b. External Thickness : 0.036 inch SWG 20 c. Parent Equipment: Air Conditioning & Refrigeration system d. Specifications: BS EN 12735/2 (relevant to Tubes for equipment) e. Material Designation: Copper & Copper Alloys Seamless, round tubes for Air Conditioning & Refrigeration f. Temper Condition: Soft fully annealed copper coils g. Length of Item: In shape of Coil/ Roll of 50 feet length h. MTC: Not known/ Not available Material: Copper Pipe Shape: Round (RD) Manufacturing Type: Seamless External DIA: 0.625 inches Wall Thickness: 0.036 inches Standard Wire Gauge (SWG): 20 SWG Grade: Type <b>GENERAL SPECIFICATION</b> - a. External Diameter : 0.625 inch b. External Thickness : 0.036 inch SWG 20 c. Parent Equipment: Air Conditioning & Refrigeration system d. Specifications: BS EN 12735/2 (relevant to Tubes for equipment) e. Material Designation: Copper & Copper Alloys Seamless, round tubes for Air Conditioning & Refrigeration f. Temper Condition: Soft fully annealed copper coils g. Length of Item: In shape of Coil/ Roll of 50 feet length h. MTC: Not known/ Not available Material: Copper Pipe Shape: Round (RD) Manufacturing Type: Seamless External DIA: 0.625 inches Wall Thickness: 0.036 inches Standard Wire Gauge (SWG): 20	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SWG Grade: Type L	
20	DGE960 48	NO DATA AVAILABL E	047659943474 3 / TUFF GRADE 1" PAINT BRUSH	HANGAR DOOR	62 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch GENERAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch	
21	DGE960 29	0.75X0. 007INCH- 50MTR-	055979001524 4 / INSULATION- TAPE- VARNISHED WOVEN GLASS-FIBRE- (STRAIGHT CUT)		15 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DGE958 14		046250220180 3 / TUBING PLASTIC POLYETHLEN E LAY FLAT WD.48	DC/FF	535 / KILOGR AMME						TECHNICAL SPECIFICATION - 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317 GENERAL SPECIFICATION - 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317	
23	DGE958 18	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED		76 / EACH/N UMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH 3 INCH.								SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
24	DGE958 19	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		54 / EACH/NUMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
25	DGE958 16		047659924451 9 / STRAPS LEATHER HYDRAULIC 4.-3"X4.-3" WEIGHT 5LB THICK 0.0625"		5 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DGB963 87		028359571150 7 / ROD COPPER RD ANNEALED DIA 2.00 INCH WT PER FT 12.180(LB)		5 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
27	DGB962 59	NO DATA AVAILABLE	027770000347 7 / SPANNER OPEN JAW ADJ 0.50" X 0.57"		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - Brand: Bahco Overall Length: 257 mm Wrench type: Adjustable Spanner Jaw Capacity: 33 mm Handle Type : Plastic/ Steel Material: Alloy Steel GENERAL SPECIFICATION - Brand: Bahco Overall Length: 257 mm Wrench type: Adjustable Spanner Jaw Capacity: 33 mm Handle Type : Plastic/ Steel Material: Alloy Steel	
28	DGB963 68		028359571143 3 / ROD NAVAL BRASS HEX SIZE A/F 1.10"WT PER FT 3.910(LB)		3 / METER						TECHNICAL SPECIFICATION - SPECS BSEN 12163, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet GENERAL SPECIFICATION - SPECS BSEN 12163, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
29	DGB963 71		028359571144 7 / ROD NAVAL BRASS RD DIA 01 INCH	GENERAL USE	4 / METER						TECHNICAL SPECIFICATION - BS EN 12163 OF 1998, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT : (LBS), R-LENGTH-03 METERS (EACH)GENERAL SPECIFICATION - BS EN 12163 OF 1998, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT : (LBS), R-LENGTH-03 METERS (EACH)	
30	DGB963 90	CW712R, MATERIAL COND: R- 400	028359571145 1 / ROD NAVAL BRASS RD DIA 1.50 INCH(38MM), L: 4 MTR, WT/FT: 6.05 LBS		8 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2011, CW712R, MATERIAL CONDITION: R-400. GENERAL SPECIFICATION - BSEN 12163 OF 2011, CW712R, MATERIAL CONDITION: R-400.	
31	DGB963 70		028359571145 5 / ROD NAVAL BRASS DIA 2 INCH (WT PER FT 11.72 LB)		7 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.GENERAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.	
32	DGB951 93		028359571145 5 / ROD NAVAL BRASS DIA 2 INCH (WT PER FT 11.72 LB)		6.6 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.GENERAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.	
33	DGB962 47		027670910583 1 / SCRAPER ENGINEER TRINGLE LG OF SERAPING		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			3IN									
34	DGB962 12		027770277015 1 / METRIC SOCKET SET 10 TO 32MM CONSIST 24 PIECES WITH BOX		14 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
35	DGB964 78	BS EN 573-3 OF 95 (CHEM COMPOSI TION)	028359571115 0 / ALUMINIUM ALLOY SHEET QUARTER HARD L=240	LOCKING &STOWAGE	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - a) bs; en 573-3 of 1995 b) BS; EN 485- 2 c) SIZE: L 2520"X W 1270" 6 MM d) GRADE: 5083 lab testing charges rs; 9100/ - will be borne by the supplying firm Complete dimensions Length -240" Width-60" Thickness 0.252 Material grade of Aluminium Alloy Complete dimension Length 240" Width 60" Thickness 0.252" and WT/sq H-3.480 Lbs Material/Grade 5083 May be endorsed in WIMS.. GENERAL SPECIFICATION - a) bs; en 573-3 of 1995 b) BS; EN 485- 2 c) SIZE: L 2520"X W 1270" 6 MM d) GRADE: 5083 lab testing charges rs; 9100/ - will be borne by the supplying firm Complete dimensions Length -240" Width-60" Thickness 0.252 Material grade of Aluminium Alloy Complete dimension Length 240" Width 60" Thickness 0.252" and WT/sq H-3.480 Lbs Material/Grade 5083 May be endorsed in WIMS..	
36	DGE960 32	0461-931- 8996	046059931899 6 / TAPE COTTON ADHASIVE COMPOUND WIDTH 3" THICK 0.038" LG.10 MTR.	30 MM GUN.	20 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DGB963 72		028359571145 9 / ROD NAVAL BRASS RD DIA.2.50		16 / METER						TECHNICAL SPECIFICATION - BS EN-12163 DESIGNATION: CW- 719R, R-340 SYMBOL: CU zN 39 SN 1 GENERAL SPECIFICATION - BS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH WT PER MTR 27.49 KG								EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU zN 39 SN 1	
38	DGB962 42	FA14774/ EC2002M	027670910527 0 / SOLDERING IRON NON ELECT.ST. TYPE.WT.12 OZ.BIT SZ. 3/4SQIN.D.T		26 / EACH/NUMBER	T0053298 399					TECHNICAL SPECIFICATION - Make: Germany Brand: WELLER WE1010 GENERAL SPECIFICATION - Make: Germany Brand: WELLER WE1010	
39	DGE960 36	NO DATA AVAILAB LE	045159451001 3 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	75 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS GENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	
40	DGE958 11	NO DATA AVAILAB LE	041559923141 1 / PERPEX-SHEET TRANSPAREN T 5MM 4FT X 5FT		5 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
41	DGE960 40		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN TRANSPAREN T L X W X THIC 48"X48"X0. 250"		11 / SHEET						TECHNICAL SPECIFICATION - Manfr/Tech.Sponcer Code reference: DTD 5592 GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference:DTD 5592	
42	DGB963 69	BS 970 OF 1996 Part 1 Grade 316531	021259571056 5 / BAR-STEEL-CORROSION-WIDTH-A-F-1.25-INCH		4 / METER						TECHNICAL SPECIFICATION - grade:316531 GENERAL SPECIFICATION - grade:316531	
43	DGB963 86		021259571069 9 / BAR STEEL CORROSION RESISTING		4 / METER						TECHNICAL SPECIFICATION - material grade: SS316L GENERAL SPECIFICATION - material grade: SS316L	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			H/R RD 0.50									
44	DGB951 94		021259571070 2 / BAR STEEL CORROSION RESISTING H/R 1.00"WT PER FT 2.670 SLB	MAT IDEND SYMB.L42H35	1 / METER						TECHNICAL SPECIFICATION - MAT. IDENTIFICATION SYMB. L42H35, BS 970/EN58J GENERAL SPECIFICATION - MAT. IDENTIFICATION SYMB.L42H35, BS 970/EN58J	
45	DGB963 84		026759521328 0 / PIPING STEEL GALVANIZED SEAMLESS (EXT DIA 1.906		72 / METER						TECHNICAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P- 265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0.128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr GENERAL SPECIFICATION - BSEN:10216-2 OF 2019 , GRADE:P-265GH BSEN ISO 1461: 2022 FOR GALVANIZING dimension: external dia: 48.3 mm= 1.906 inch wall thickness: 3.2 mm=0. 128 inch nom bore: 38.1 mm=1.50 inch length : 3.6 to 6.1 mtr	
46	DGB963 85		021259923280 2 / BAR STEEL CORROSION RESISTING H/R RD 1.25" WT PER FT 4.209LBS		4 / METER						TECHNICAL SPECIFICATION - minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D) GENERAL SPECIFICATION - minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D)	
47	DGB963 73		021259923280 5 / BAR STEEL CORROSION RESISTING H/R RD 2.50" WT PER FT16. 700LBS		7.8 / METER						TECHNICAL SPECIFICATION - BS- 970, Stainless Steel Grade 316L, Running Length: 6 meter (OLD GRADE EN-58J) GENERAL SPECIFICATION - BS-970, Stainless Steel Grade 316L, Running Length: 6 meter (OLD GRADE EN-58J)	
48	DGB963 74		021870000001 8 / PIPE STEEL		25 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DGB962 16		027459910470 0 / HAMMER		5 / EACH/N						TECHNICAL SPECIFICATION - Material: Mild Steel Length of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			HAND SLEDGE 10.00 LBS LG 36.00 IN STRAIGHT PEIN		UMBER						wooden handle: 3 feet Diameter of wooden handle: 1.5 Inch <u>GENERAL SPECIFICATION</u> - Material: Mild Steel Length of wooden handle: 3 feet Diameter of wooden handle: 1.5 Inch	
50	DGE958 03		033059571325 2 / TWINE NYLON MACKEREL LINE 3 STRD MIN BKG STRENGTH 140 LBS.		17 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Dimensions: 3 STRD 2mm x 218 yard BS 6125 OF 1981 TABLE 12 <u>GENERAL SPECIFICATION</u> - Dimensions: 3 STRD 2mm x 218 yard BS 6125 OF 1981 TABLE 12	
51	DGB962 40		027179910188 7 / TAP THREAD CUTTING HS BSW P/S16. 0TPI0.375X1. 240X0.294X2. 937"		17 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
52	DGE963 35	NO DATA AVAILAB LE	033059571326 0 / TWINE COTTON CHALK LINE G/PURPOSE MIN BKG STRG25 LB20YDS LG; DIA 1.5mm	GENERAL PURPOSE BS 2019	50 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - BS 6125 of 1981 <u>GENERAL SPECIFICATION</u> - BS 6125 of 1981	
53	DGE958 02	NO DATA AVAILAB LE	033059571326 0 / TWINE COTTON CHALK LINE G/PURPOSE MIN BKG STRG25 LB20YDS LG; DIA 1.5mm	GENERAL PURPOSE BS 2019	50 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - BS 6125 of 1981 <u>GENERAL SPECIFICATION</u> - BS 6125 of 1981	
54	DGE958 05		033059571326 2 / TWINE NYLON ROPING 3		16 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5	

Jo	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			STRD NATURAL FINISH MIN BKG STRGT 50 LB								mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed. <u>GENERAL SPECIFICATION - a.</u> Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed.	
55	DGB961 32		026659001603 2 / WASHER FLAT ROUND MILD STEEL 0.875X0. 937X1.875X0. 160"(LOCAL)	THK 0.160" APPROX WT PER 100 9 LB 6 OZ	158.5 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - i</u> Size: 0.875 x 0.937 x 1.875 x 0.16" i Shape: Round i Thickness: 3mm i Usage: Used to distribute the load of a threaded fastener <u>GENERAL SPECIFICATION - i</u> Size: 0.875 x 0.937 x 1.875 x 0.16" i Shape: Round i Thickness: 3mm i Usage: Used to distribute the load of a threaded fastener	
56	DGB962 56	NO DATA AVAILABL E	026359923698 7 / THIMBLE, ROPE STEEL BS 970-EN 3A GALVANISED PEAR SHAPED OPEN TYPE WT 1.75LBS SIZE 1.25	SPEC NO DGS 5031NO.40	220 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
57	DGB961 28	SPEC. BS57 LG. OF THREAD FULL(SIM)	026659128262 4 / SCREW MACHINE STEEL FLAT FILLISTER HD THRED 6 BA LOCAL LG 1"	SPEC= BS 57 LENTH OF THREAD FULL	99 / TEN						<u>TECHNICAL SPECIFICATION - Material Grade EN 4140</u> <u>GENERAL SPECIFICATION - Material Grade EN 4140</u>	
58	DGB962 43		027179910172 7 / TAP THREAD CUTTING HS BSF T/S20. 0TPI0.373X1. 250X0.293X2. 937"		17 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
59	DGB96070	0257-13023	0257704195010 / NUT PLAIN HEXAGON BRASS BSW THD-SZ 0.500 IN HEIGHT. 437 IN		52 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DGB96245		0257704195013 / NUT PLAIN HEX BSW BRASS THD 0.250 O/A LG 0.200 (FULL BEARING)	0.250", O/A HEIGHT: 0.200", STYLE: FULL BEA.	45 / DOZEN						TECHNICAL SPECIFICATION - MATERIAL GRADE: MILD STEEL INNER DIA: 6.5MM OUTER DIA: 11MM WIDTH: 7MM BR 320-D/69 GENERAL SPECIFICATION - MATERIAL GRADE: MILD STEEL INNER DIA: 6.5MM OUTER DIA: 11MM WIDTH: 7MM BR 320-D/69	
61	DGB96248	NO DATA AVAILABLE	0264594481524 / FUNNEL-OIL-FILLING	DUST BIN PASTIC 3.250 CU FT	18 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
62	DGD96168	S NO 32 MODEL 2018	0035500000386 / MINCING MACHINE MEDIUM		3 / EACH/NUMBER	2018					TECHNICAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450 GENERAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450	
63	DGB96220	16Q5076	0253794419755 / HYDROMETER	TESTER BATTERY P/NO. (016Q5076)	87 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DGB96388		0212595711003 / STEEL-ROUND-CARBON-REFORGING-DIA-178MM		10 / KILOGRAMME						TECHNICAL SPECIFICATION - Dia: 178mm (7 inch) Length: 1 meter (at least) GENERAL SPECIFICATION - Dia: 178mm (7 inch) Length: 1 meter (at least)	
65	DGB95110	NIL	0267595213279 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia: 1.688" wALL/thckness:	NIL	120 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE: P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS: 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 :	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			0.128" N/BORE:1.25" LENGHT: 06 MTR								2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
66	DGE958 15	NO DATA AVAILABL E	047659923891 9 / RUBBER SHEET (SIZE: L 2250 x W 2250 x THKNESS 12MM)		5 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
67	DGB961 27	C60	047450448149 7 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	FOUNDRY USE OEM MORGANITE UK FAX NO	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
68	DGE958 23		422070504642 4 / AIRCRAFT MARSHALLER S IDENTIFICATI ON JACKET	TO USED BY GROUND PERSONEL DEPLOYED	39 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
69	DGB961 24	MODEL P- 40	513076501639 4 / ELECTRIC PORTABLE PLANNER AND GROOVERS (C/W/D 136 MAX-C/D 3MM)	GENERAL USE	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
70	DGB961 25		512073100118 6 / WRENCH ALLEN KEY SET 1.5-19MM ELOR4159/6		3 / SET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
71	DGH965 02	NO DATA AVAILABL E	561070506109 9 / PORTA CABIN 40X8FT FULL REFURBISHE D TO SUIT		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PURPOSE									
72	DGE958 26	MWTM 95/29-1200	593572507749 1 / HEAT SHRINK SLEEVE		5 / METER						TECHNICAL SPECIFICATION - Dimensions: Size: 95/29 Expanded Diameter: 95mm Recovered Diameter: 29mm Cable Range Diameter:32-86 mm Length: 1m GENERAL SPECIFICATION - Dimensions: Size: 95/29 Expanded Diameter: 95mm Recovered Diameter: 29mm Cable Range Diameter:32-86 mm Length: 1m	
73	DGE958 27	NO DATA AVAILABL E	593572507749 3 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 35/12, LG 01 METER		3 / METER						TECHNICAL SPECIFICATION - A. Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW- 3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714, Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion. GENERAL SPECIFICATION - A. Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW- 3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714, Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion.	
74	DGE960 24	CM6538- 000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		13 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch)	

3. Jo	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes <u>GENERAL SPECIFICATION - Material System:</u> Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
75	DGE958 12	NO DATA AVAILABL E	04615000008 6 / GOGGLE CHIPPING		24 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire-resistant head band. <u>GENERAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
76	DGE95466		8340PK507382 7 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIES		1 / EACH/ NUMBER						<p>most along with fire- resistant head band.</p> <p><b>TECHNICAL SPECIFICATION - 1.</b>  DIMENSION/ SIZE: A. TENT SIZE= 20 X 16 FEET (± 0.6 INCH) B. WALL HEIGHT= 06 FEET (± 0.6 INCH) C. HEIGHT OF TENT= 12 FEET (± 0.6 INCH) 2. SPECIFICATION: A. CANVAS COTTON= 450/500 GSM (WITH WATER PROOFING, ROT PROOFING, DOUBLE FLY WITH SINGLE FOLD, DOSUTI FABRIC 150 TO 180 GSM (GREEN/ YELLOW) B. COLOR OF TENT= OLIVE GREEN (COLOR CODE FOR MATCHING PURPOSE I.E RAL-6003) C. PACKING COMPLETE TENT AND ACCESSORIES IN TWO BAG. 3. LIST OF ACCESSORIES: A. IRON STANDING POLES= 02 IN NOS (LENGTH: 12 FEET &amp; THICKNESS: 1.5 MM) (JOINTED WITH MALE/ FEMALE), B. IRON RICH POLE= 01 IN NO (LENGTH: 7 X FEET &amp; THICKNESS: 1.5 MM) C. ROPE= 40 IN NOS (STANDARD SIZE &amp; DIA: 12-14 MM) D. HAMMER= 01 IN NO (5 X KGS WEIGHT WITH WOODEN HANDLE) E. IRON PEGS= 40 IN NOS (LENGTH: 18 INCH &amp; THICKNESS: 18 MM)<b>GENERAL SPECIFICATION</b>  -1. DIMENSION/ SIZE: A. TENT SIZE= 20 X 16 FEET (± 0.6 INCH) B. WALL HEIGHT= 06 FEET (± 0.6 INCH) C. HEIGHT OF TENT= 12 FEET (± 0.6 INCH) 2. SPECIFICATION: A. CANVAS COTTON= 450/500 GSM (WITH WATER PROOFING, ROT PROOFING, DOUBLE FLY WITH SINGLE FOLD, DOSUTI FABRIC 150 TO 180 GSM (GREEN/ YELLOW) B. COLOR OF TENT= OLIVE GREEN (COLOR CODE FOR</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>MATCHING PURPOSE I.E RAL-6003) C. PACKING COMPLETE TENT AND ACCESSORIES IN TWO BAG. 3. LIST OF ACCESSORIES: A. IRON STANDING POLES= 02 IN NOS (LENGTH: 12 FEET &amp; THICKNESS: 1.5 MM) (JOINED WITH MALE/ FEMALE), B. IRON RICH POLE= 01 IN NO (LENGTH: 7 X FEET &amp; THICKNESS: 1.5 MM) C. ROPE= 40 IN NOS (STANDARD SIZE &amp; DIA: 12-14 MM) D. HAMMER= 01 IN NO (5 X KGS WEIGHT WITH WOODEN HANDLE) E. IRON PEGS= 40 IN NOS (LENGTH: 18 INCH &amp; THICKNESS: 18 MM)</p>	
77	DGE95461		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIE S)	OLIVE GREEN WATERPROO F INNER LINNING OF,	1 / EACH/N UMBER						<p><b>TECHNICAL SPECIFICATION - 1.</b> SPECIFICATIONS: PSG-600, 2. SIZE/ DIMENSION: A. LENGTH: 50 FEET (±0.5 FEET), B. WIDTH: 20 FEET (±0.2 FEET), C. RIDGE HEIGHT: 12 TO 14 FEET, D. SIDE WALL HEIGHT: 7 TO 8 FEET (DETACHABLE ALL ROUND WITH SUITABLE DOORS), 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. SPECIFICATION OF CANVAS COTTON: A. CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF FIRE PROOF. B. OUTER FOLDS: WATER PROOF, C. INNER FOLDS: SHEETING CLOTH &amp; CANVAS DYED, D. NO OF DOORS: 02 E. NO OF WINDOW: 08 F. TAPE NEWAR: CANVAS COTTON, G. NO OF FOLDS: 02 5. LIST OF ACCESSORIES: A. UPRIGHT POLES: 04 QTY B. RIDGE POLES: 03 QTY C. ROPES: 34 QTY (STANDARD SIZE) D. PEGS: 34 QTY (STANDARD SIZE) E. HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>1.5 FEET) F. DIAMETER OF POLES: 40 MM G. GAUGE OF POLES: 16 GAUGE H. LENGTH OF PINS: 12 INCH J. FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET K. PACKING: 02 QTY</p> <p><u>GENERAL SPECIFICATION - 1.</u>  SPECIFICATIONS: PSG-600, 2. SIZE/ DIMENSION: A. LENGTH: 50 FEET (±0.5 FEET), B. WIDTH: 20 FEET (±0.2 FEET), C. RIDGE HEIGHT: 12 TO 14 FEET, D. SIDE WALL HEIGHT: 7 TO 8 FEET (DETACHABLE ALL ROUND WITH SUITABLE DOORS), 3. COLOUR: JUNGLE GREEN (COLOUR CODE 3A5F31), 4. SPECIFICATION OF CANVAS COTTON: A. CANVAS: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF FIRE PROOF. B. OUTER FOLDS: WATER PROOF, C. INNER FOLDS: SHEETING CLOTH &amp; CANVAS DYED, D. NO OF DOORS: 02 E. NO OF WINDOW: 08 F. TAPE NEWAR: CANVAS COTTON, G. NO OF FOLDS: 02 5. LIST OF ACCESSORIES: A. UPRIGHT POLES: 04 QTY B. RIDGE POLES: 03 QTY C. ROPES: 34 QTY (STANDARD SIZE) D. PEGS: 34 QTY (STANDARD SIZE) E. HAMMER: 02 QTY (03 KG WEIGHT WITH WOODEN HANDLE 1.5 FEET) F. DIAMETER OF POLES: 40 MM G. GAUGE OF POLES: 16 GAUGE H. LENGTH OF PINS: 12 INCH J. FLAPPER FOR GROUND SHEET: POLYETHYLENE SHEET IS BEST FOR GROUND SHEET K. PACKING: 02 QTY</p>	
78	DGT961 30	707	5530FM036007 6 / 5 LAYERS PLYWOOD	WEAPON AND AMMUNITION STORAGE SYSTEM	20 / EACH/N UMBER	NIL		FENGTAI DISTRICT YUNGANG NORTH WEST BEIJING CHINA Tel : 86-13911121951 Fax :	BEIJING ELECTR OMECHA NICAL		<p><u>TECHNICAL SPECIFICATION - AVAILABLE IN TPI</u>  <u>GENERAL SPECIFICATION - AVAILABLE IN</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								86-010-68191140 Email : lujirui@live.cn	ENGINEERING INSTITUTE, CHINA		TPI	
79	DGE96241	1900gsr-2usb	7025015913120 / honey well 1900 bar code scanner		2 / EACH/NUMBER	xeon 1900					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
80	DGE96229	100-65F	7920993008997 / CLEANING LINT FREE CLOTH (GUC ITEM)	CLEANING CLOTH	120 / EACH/NUMBER	NO DATA AVAILABLE		UK	MEMO HCG/MS D/03/336 DT 2/7/08		<u>TECHNICAL SPECIFICATION -</u> Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy). <u>GENERAL SPECIFICATION -</u> Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy).	
81	DGT96503	NO DATA AVAILABLE	9340705149922 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE	WOOD WORKS SHIPS&ESTABLISHMENT	8 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA		<u>TECHNICAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM <u>GENERAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM						NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92- 21- 32776064 .MOBILE 0322- 2578654.			
82	DGE962 37	NIL	047659000775 8 / GLOVES SEAMLESS DIPPED RUBBER		13 / PAIR	202- GNFG					<p><b>TECHNICAL SPECIFICATION - a.</b> Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester &amp; nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester &amp; nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc <b>GENERAL SPECIFICATION - a.</b> Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester &amp; nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester &amp; nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc</p>	
83	DGE962 39		045159129298 9 / CLOTH COATED PVC FOR FURNITURE UPHOLSTERY COLOUR BLUE WD.50	FOR SPECS SEE CMD 8	340 / METER						<p><b>TECHNICAL SPECIFICATION -</b> ISO7617-2 OF 1994 colour blue wd . 50 INCH<b>GENERAL SPECIFICATION - ISO7617-2 OF</b> 1994 colour blue wd .50 INCH</p>	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH									
84	DGT96505	NO DATA AVAILAB LE	553070504293 3 / PLY WOOD NATURAL TEAK FINISH ONE SIDE (NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W= 4' TH=03mm to 04mm	PRESENTATIO N BOXES FOR VVIPS	160 / SQ FEET						TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm GENERAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm	
85	DGE96235	NO DATA AVAILAB LE	593572507749 4 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 31/8 LG, 01 METER		7 / METER						TECHNICAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B. PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224 G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT AND ABRASION. GENERAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B. PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224 G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT AND ABRASION.	
86	DGE962 23	NO DATA AVAILABL E	04135000013 3 / EAR DEFENDER		106 / PAIR	PELTOR H10A/ OPTIME 105					<p><u>TECHNICAL SPECIFICATION -</u>  acceptance on delivery or at the time of inspection may be obtained  Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB.  a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar &amp; Industrial Safety Equip) <u>GENERAL SPECIFICATION -</u>  acceptance on delivery or at the time of inspection may be obtained  Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB.  a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar &amp; Industrial Safety Equip)</p>	
87	DGE962 46	NO DATA AVAILABL E	04615000008 6 / GOGGLE CHIPPING		90 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u>  Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at &gt;5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head</p>	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											band. <u>GENERAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.	
88	DGT965 04	NO DATA AVAILABLE	010050000001 4 / PLYWOOD GRAD-1, (WBP) 5-PLY, SIZE: 6X4FT X 1/4-INCH (1.83 MTR X 1.22 MTR X 6.35 MM)		30 / SHEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - BS6566OF 1985 1 TO 8</u> <u>GENERAL SPECIFICATION - BS6566OF 1985 1 TO 8</u>	
89	DGT965 06	NO DATA AVAILABLE	010050000002 8 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLYS OF SHESHAM WOOD) 5-PLY	2.440X1.220MTRX6.35MM) SPECE/BS-1088	160 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I &amp; II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M<sup>3</sup>. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, <u>GENERAL SPECIFICATION -</u> 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M <sup>3</sup> . 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM.	
90	DGE960 26	60-501-001	615076502401 1 / TIE WRPA (CABLE TIE) P/N 60-501-001	GRADIOMETE R SYSTEM	160 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - a.</u> Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held <u>GENERAL SPECIFICATION - a.</u> Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held	
91	DGE962 38		046154600451 5 / PAPER ABRASIVE 9" X11" WATERPROO F MATERIAL EMERY GRADE P- 400C		100 / SHEET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
92	DGE962 44	NO DATA AVAILABL E	055979000198 5 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR	GENERAL ELECTRIC USE	16 / ROLL	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
93	DGE960 51	ASTM D 6413	721050515517 1 / FIRE RETARDANT SPRING MATTRESS (L6. 5"XW2'XH6)	MATRESSES FOR BED	10 / EACH/N UMBER			LOCAL ADDRESS:AL- KHAIR HOUSE-43-T,AL- KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL- KHAIR HOUSE- 43-T		<u>TECHNICAL SPECIFICATION - MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500- 1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL) <u>GENERAL SPECIFICATION -</u> MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500-1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL)	
94	DGE966 92	GRS010-HPLP	422075521668 5 / OXYGEN COMPATIBLE GREASE KIT WITH ORING TOOL	CAIMANO MK4	20 / EACH/NUMBER	NA	CAIMANO MK4	SIEL VIA VINCINELLA 19037 S.STEFANO MAGRA LA SPEZIA ITALY	SIEL VIA VINCINELLA 19037 S. STEFANO MAGRA ITALY		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
95	DGH961 20	LUKUF901 052100M	712570520625 7 / FRAME 10' X 3.5'	Racking	15 / EACH/NUMBER	NA		M/s Habib & Sons 3rd Floor, 83-C, Phase II Extension, Main National Highway, Defense Housing Society Karachi-Pakistan	M/s Habib & Sons		<u>TECHNICAL SPECIFICATION -</u> Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated <u>GENERAL SPECIFICATION -</u> Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated	
96	DGH961 22	LCKHB108 1182B	302070520258 0 / BEAM PR	RACKS	35 / EACH/NUMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN	HABIB & SONS		<u>TECHNICAL SPECIFICATION -</u> Profile: Step Beam Size: 118mm x	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			2740X240		UMBER			NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726			50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5 <u>GENERAL SPECIFICATION</u> _Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
97	DGE965 86	04769430557, BS2992TABLE8ITEM 8/5	0476599430557 / BRUSH VARNISH TYNEX FIBER FLAT SQUIRE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	21 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 2.</u> Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable <u>GENERAL SPECIFICATION</u> -2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
98	DGE965 64	C-268	0476599430559 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		12 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 <u>GENERAL SPECIFICATION -</u> stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
99	DGE965 99	NIL	0413599238923 / RUBBER SHEET SOLID NATURAL (CLOTH INSERT)		30 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION OF ITEM AS PER NMCRL: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER	

Jo	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.</p> <p><u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCR:</u> 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.</p>	
100	DGE965 92	0413-8553	041359923892 6 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		40 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992</u> LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"<u>GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992</u> LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"</p>	
101	DGE965 90	BS-1145 HARDNES S 42-50	041359923890 0 / SHEET RUBBER SOLID NATURAL OFF WHITE SQ 05	TENSILE STRENGTH 2500PSI	30 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	

Jo	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LBS 0.625 X48X72IN									
102	DGB963 63	SPEC BS 2874 C 107-0	028359961098 2 / ROD COPPER RD ANNEALED DIA 0.75 INCH (WEIGHT/ FOOT 1.710 LB		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
103	DGB963 61	BS 2870	028359961098 3 / ROD COPPER RD DIA 1 INCH WT PER FT 3.040 LB	SPEC. BS 2874 C107-0	10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
104	DGB965 94	OUT/BOD Y 1/8" PLATE. INNER 16 GAUG	024859129614 7 / SAFE STEEL FITTED WITH COMB 6 LEVER EXT DIM SZ 28X21X16 5/8"	SZ 710X535X425 MM(27-3/4X21- 1/16X16-3/4"	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required GENERAL SPECIFICATION - Size: 28X21X16 5/8" out body: 1/8" plate: inner gauge: 16 local/ indigenous Steel crs s400 Fire Proof Required	
105	DGE969 18	NO DATA AVAILABL E	562050504233 5 / TILES CERAMIC GLAZED COLOUR WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")	DECK COVERING	300 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DGB965 91	NO DATA AVAILABL E	024850000001 5 / SAFE- STEEL-WITH- COMBINATION -LOCK FOR CBs SZ 28X20X16 5/8		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record	
107	DGE96598	NO DATA AVAILAB LE	04515000002 1 / CLOTH TICKEN BLUE STRIPS WIDTH 58 INCHES		240 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - a.</u> WIDTH:58 INCH(1,473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT;40 d.COUNT OF YARN WARP;2/206 WEFT2/206 e. SHRINKAGE- WARP; 2%(MAX) WEFT;2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS) <u>GENERAL SPECIFICATION - a.</u> WIDTH:58 INCH(1,473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT;40 d.COUNT OF YARN WARP;2/206 WEFT2/206 e. SHRINKAGE- WARP; 2%(MAX) WEFT;2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS)	
108	DGE96680	MEDIUM 66.2 LTRS 2000 PLUS	811570525959 8 / COLEMAN or EQUIVALENT ICE BOXES (MEDIUM) 66.2 LTRS 2000 (PLUS)		2 / EACH/N UMBER	N/A					<u>TECHNICAL SPECIFICATION -</u> BOTH SIDE HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200 (plus) approx. <u>GENERAL</u> <u>SPECIFICATION - BOTH SIDE</u> HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200 (plus) approx.	
109	DGH96807	LNKCB151 520S	3020PK520265 0 / CROSS BRACING 20' X 20"	RACK	15 / UNIT	NIL	NIL	3RD FLOOR 83C,PHASE 2, EXTENSION,MAIN NATIONAL HIGHWADEFENCE KARACHIY,,021538726		HABIB & SONS	<u>TECHNICAL SPECIFICATION -</u> Profile: Type-Square Size: 15mm x 15mm Surface Finish:RAL 5010/ Powder Coated Material: SS400 Yeild Strength: 245 16mm Tensile Strenght: 400-510 mpa Shim plate:1 Anchor bolts:M12x110x2 <u>GENERAL</u> <u>SPECIFICATION - Profile: Type-</u> Square Size: 15mm x 15mm Surface Finish:RAL 5010/ Powder Coated Material: SS400 Yeild Strength: 245	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											16mm Tensile Strenght: 400-510 mpa Shim plate:1 Anchor bolts: M12x110x2	
110	DGH952 46	GDHBMK4 092040	4010FT100791 8 / STEEL WIRE ROPE (20MM/40M/N ON- ROTATING/GA LVANIZED)	9M COMBINED BOAT CRANE	6.75 / EACH/N UMBER	GD.HBM. K.S-40/6- PG&40/9	N/A	GURDESAN GEMI MAK. SAN.TIC.A.S, DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM, KOCAELI, TURKEY TEL # 9.02627E+11 FAX # 9.02627E+11 INFO@GURDESAN.COM. TR		GURDES AN GEMI MAK. SAN.TIC. A.S	<p><b>TECHNICAL SPECIFICATION - A.</b> Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual</p> <p><b>GENERAL SPECIFICATION - A.</b> Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual</p>	
111	DGB951 95		028259571216 2 / PIPING COPPER ROUND SEAMLESS (External dia 0.50 INCH)		60 / METER						<p><b>TECHNICAL SPECIFICATION -</b> material grade: acr (astm B280), C- 10200 or C-12200. EXTERNAL DIAMETER: 0.50 INCH WALL THICKNESS: 0.032"(MULLAR USA MAKE) Specifications:BS 2871 AND DESIGNATION C-106 (Relevant to Tubes for equipment) METARIAL DESIGNATION: Copper &amp; Copper Alloys Seamless, Round Tubes for Air Conditioning &amp; Refrigeration Temper Condition: soft fully anealled coils Conditioning &amp; Refrigeration system Running Length: In shape of Coil/Roll of 50 feet length (equivalent 15.24 meters) <b>GENERAL</b> <b>SPECIFICATION -</b> material grade: acr (astm B280), C-10200 or C- 12200. EXTERNAL DIAMETER: 0.50 INCH WALL THICKNESS: 0.032" (MULLAR USA MAKE) Specifications:BS 2871 AND DESIGNATION C-106 (Relevant to Tubes for equipment) METARIAL</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DESIGNATION: Copper & Copper Alloys Seamless, Round Tubes for Air Conditioning & Refrigeration Temper Condition: soft fully anealed coils Conditioning & Refrigeration system Running Length: In shape of Coil/Roll of 50 feet length (equivalent 15.24 meters)	
112	DGH95273	HD-EP05	0222590903610 / SWIVEL PIECE (MATERIAL: STEEL, SIZE 19mm - 132 mm") (MAKE & ORIGIN: QINGDAO POWERFUL MACHINERY LTD)	ANCHOR CHAIN	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
113	DGH96394	SPEC:BS826	0281594559636 / Panel storage & Display Shelving		54 / EACH/NUMBER						TECHNICAL SPECIFICATION - GREY 63"H X 18.25" W 3XSIDES SHEET METALIC. SIZE 3,63"H X 18 1/4"NOMINAL BAY DEPTH GENERAL SPECIFICATION - GREY 63"H X 18.25" W 3XSIDES SHEET METALIC. SIZE 3,63"H X 18 1/4"NOMINAL BAY DEPTH	
114	DGH96916		3990705331163 / MULTI-PURPOSE TROLLEY		3 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
115	DGB94652	NIL	0267595213279 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	130 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MTR	
116	DGE94540	NO DATA AVAILAB LE	8415PK506744 2 / CLOTH PARASHUTE GRAY		300 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
117	DGE94675	NO DATA AVAILAB LE	8415PK506744 2 / CLOTH PARASHUTE GRAY		450 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
118	DGD70441		003550000052 0 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		13 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER GENERAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
119	DGH96392	NO DATA AVAILAB LE	026259419526 1 / GRAPNEL- HEIGHT- 20INCH- WIDTH-18 3/4 Material Steel Galvanized		30 / EACH/N UMBER						TECHNICAL SPECIFICATION - HEIGHT-20INCH-WIDTH-18 3/4 Material Steel Galvanized, Drawing# CHC328 as endorsed by CINSGENERAL SPECIFICATION - HEIGHT-20INCH-WIDTH-18 3/4 Material Steel Galvanized, Drawing# CHC328 as endorsed by CINS	