

PAKISTAN NAVY
TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 09-02-2026

TERMS & CONDITION

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT".

2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.

3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

1. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF95070	RG-NBS3100-24GT4SFP / J9776A / J9772A+j4 859c/RG-NBS3100-24GT4SFP	589578520783 3 / NETWORK SWITCH HP 2530 24G/48G WITH 2/4 SFP MODULES	NETWORK SWITCH J9772A CHINA	1 / EACH/NUMBER	RG-NBS5200-48GT4xS/R8N88A-HP/J9776A/J9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA		TECHNICAL SPECIFICATION - ATTACHED GENERAL SPECIFICATION - ATTACHED	
2	DNF94024	NCB-FS09D-LCLC-10	599570524635 7 / D-LINK LC-LC SINGLEMODE OS2 DUPLEX PATCH CORD 10M		5 / EACH/NUMBER	NCB-FS09D-LCLC-10					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
3	DNF96472	HTDZ HT-2000A/YX 1620	599671514371 9 / MIXER(PRE AMPLIFIER FOR MIC)	CONNING INTERCOM SYSTEM	2 / EACH/NUMBER	NO DATA AVAILABLE		US	M/S:KYAF CORPORATION,24 NATIONAL T.V. MARKET SOHRAB KHATRA K ROAD SADDAR KARACHI ,TEL: 0092-21-5685654&5680739		TECHNICAL SPECIFICATION - M/S:KYAF CORPORATION,24 NATIONAL T.V.MARKET SOHRAB KHATRAK ROAD SADDAR KARACHI,TEL:0092-21-5685654&5680739 12 Ports of Mike GENERAL SPECIFICATION - M/S:KYAF CORPORATION,24 NATIONAL T.V.MARKET SOHRAB KHATRAK ROAD SADDAR KARACHI,TEL:0092-21-5685654&5680739 12 Ports of Mike	
4	DNF96294	ML-1102S-A/ML-1102S-B	609978516657 5 / FIBER	CCTV SYSTEM (PSS)	1 / PAIR	ML-1102S-A RJ45/4V1		CETC Mansion No 5 walatong north street, Xicheng District, Beijing	M/S CETC international		TECHNICAL SPECIFICATION - Optical Transceiver model number:	

LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	(RJ-45 PORTS) /4V1D	MEDIA CONVERTER FOR IP CAMERAS			D		China 100120		al Co.Ltd	ML-1102S-A ML-1102S-B (2 RJ-45 Ports sPEC: transceivers HAVING 100/1000 MBPS (GB) oem: MICROLINKGENERAL SPECIFICATION - Optical Transceiver model number: ML-1102S-A ML-1102S-B (2 RJ-45 Ports sPEC: transceivers HAVING 100/1000 MBPS (GB) oem: MICROLINK	
DNZ96582	A12150	2530785158980 / BRAKE LINING MATERIAL SIZE. 5/8	PORT DRAG HEAD WINCH	80 / FOOT			M/S CSTC CHINA/ABBASI TRADERS LTD		M/S CSTC CHINA..	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
DNF96577	MD3003B1 / BS-HH-D7	6665705208217 / HAND HELD METAL DETECTOR	METAL DETECTOR DESTO PAK	2 / EACH/NUMBER	MD3003B1/BS-HH-D7	NA	DESTO (HQ)CHAKLALA cant, Rawalpindi-46200, Pakistan		DESTO	TECHNICAL SPECIFICATION - a. Operating Frequency :25/27/93 KHz b.Length c.Weight d.Tuning e.Battery f.Maximum Detection Depth at 70 KHZ Paper Pin: 2-3 cm Razor Blade/Knife: 9-15 cm Pistol: 15-18 cm g. Normal Operation duration: 12 hrsGENERAL SPECIFICATION - a. Operating Frequency :25/27/93 KHz b.Length c.Weight d.Tuning e.Battery f.Maximum Detection Depth at 70 KHZ Paper Pin: 2-3 cm Razor Blade/Knife: 9-15 cm Pistol: 15-18 cm g. Normal Operation duration: 12 hrs	
DNF96295	DH-IPC-HFW2231 TP-ZS-S2/DH-HAC-HFW3231 E-ZT/DH-HAC-HFW2231 RP-Z-IRE6	6710785220312 / FIX IR CAMERA DAHUA	CCTV SURVELLANC E	6 / EACH/NUMBER	DH-HAC-HFW3231 E-ZT		Dahua Technology Co., Ltd. 1199 BinAn Road, Binjiang District, Hangzhou, China Tel: +86-571-87688883 Fax: +86-571-87688815 Email: overseas@dahuatech.com www.dahuatech.com		Dahua Technolog y Co., Ltd.	TECHNICAL SPECIFICATION - 1/2. 8" 2.1Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P High speed, long distance real-time transmission HDCVI, SDI and SD output, SD Tester out OSD Menu, control over coaxial cable 120dB True WDR, Day/Night(ICR), AWB, AGC, BLC, 3DNR IP67, IK10, AC24V/DC12VGENERAL SPECIFICATION - 1/2.8" 2.1 Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P High speed, long distance real-time transmission	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											HDCVI, SDI and SD output, SD Tester out OSD Menu, control over coaxial cable 120dB True WDR, Day/Night(ICR), AWB, AGC, BLC, 3DNR IP67, IK10, AC24V/DC12V	
8	DNF96655	MT-6500 (1310-1550,32 /30dB/MT-7300 PLUS	662578520903 0 / OTDR WOSHIDA MT 7300 REFLECTOMETER	VIGIL-II	1 / BOX	MT-7300 PLUS	NA	2nd Floor Block C Det Building no 2,Ruitai Road Kaitai Street Huangpu District Guangzhou CHINA Email:- cctvtester@wanglu.com.cn		WANGLU TECHNOLOGY	<p>TECHNICAL SPECIFICATION - oem, WANGLU technology ltd. Plus Wavelength (nm) 850/1300 1310/1550 1310/1490/1550 1625 Loss threshold (dB) 0.0 distance + sampling interval) Distance scope (km) 0.3 to180 Typical real-time refreshing duration (s) 0.2 Memory capacity of trace SD Card (2G), > 10000 pieces Make FIBERGATE, KELUSHI SYRETECH, FEIBTECH Parent equipment Fault diagnostic tool for optical fiber</p> <p>GENERAL SPECIFICATION - oem, WANGLU technology ltd. Plus Wavelength (nm) 850/1300 1310/1550 1310/1490/1550 1625 Loss threshold (dB) 0.0 distance + sampling interval) Distance scope (km) 0.3 to180 Typical real-time refreshing duration (s) 0.2 Memory capacity of trace SD Card (2G), > 10000 pieces Make FIBERGATE, KELUSHI SYRETECH, FEIBTECH Parent equipment Fault diagnostic tool for optical fiber</p>	
9	DNF96578	ED-786D/Ed-D787	666570522104 0 / HAND HELD EXPLOSIVE DETECTOR	DESTO EXPLOSIVE DETECTOR PAKISTAN	1 / EACH/NUMBER	ED-786D/d787		DESTO (HQ) CHAKLALA CANTT, RAWALPINDI-46200, PAKISTAN PHONE NO +92-51-9280507, FAX +92-51-92-9280502 EMAIL desto@isbpaknet.com.pk		DESTO (DEFENCE & SCIENCE TECHNOLOGY ORGANIZATION)	<p>TECHNICAL SPECIFICATION - 1.</p> <p>Principle: Ions concentration 2. Respective Time: Immediate 3. Operating Voltage: 14.5VDC + Volts 4. Battery Type: Li-ion recharged 5. Battery life: 04 Hours 6. Max Charging Time: 02 hrs 30 minutes 7. Low Voltage Alarms: 09 Volts + 1 Volt 8. Audio Indicators: Beep 9. Visual Indicators: LED 10. Operating Temp Range: +5 C to +55 C 11. Storage Temp Range: +5 C to 80 C</p> <p>Range of ED-D787 has been designed to detect the presence Explosives of various from the</p>	

LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										following explosive substances: Detector 1. TNT (Tri Nitro Toluene) 2. NG (Nitro Gtyceone) 3. Dynamite 4. ANFO (Ammonium Nitrate Fuel Oil) 5. Tetryl MANUAL ZERO 10 SEC FROM SWITCH ON RESPONSE TIME IMMEDIATE BATTERY VOLTAGE TYPE +12V, AA SIZE CELL INDICATOR PEIZO BUZZER VISUAL INDICATOR LED TEMP 0-60C <u>GENERAL SPECIFICATION -</u> 1. Principle: Ions concentration 2. Respective Time: Immediate 3. Operating Voltage: 14.5VDC + Volts 4. Battery Type: Li-ion recharged 5. Battery life: 04 Hours 6. Max Charging Time: 02 hrs 30 minutes 7. Low Voltage Alarms: 09 Volts + 1 Volt 8. Audio Indicators: Beep 9. Visual Indicators: LED 10. Operating Temp Range: +5 C to +55 C 11. Storage Temp Range: +5 C to 80 C Range of ED-D787 has been designed to detect the presence Explosives of various from the following explosive substances: Detector 1. TNT (Tri Nitro Toluene) 2. NG (Nitro Gtyceone) 3. Dynamite 4. ANFO (Ammonium Nitrate Fuel Oil) 5. Tetryl MANUAL ZERO 10 SEC FROM SWITCH ON RESPONSE TIME IMMEDIATE BATTERY VOLTAGE TYPE +12V, AA SIZE CELL INDICATOR PEIZO BUZZER VISUAL INDICATOR LED TEMP 0-60C	
10	DNF96473	N1537	6110705155260 / ENERGY SAVER 220V-240V ,11W. (screw type)	SELF, FOR DISTRIBUTION SYS.	24 / EACH/NUMBER		SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI.		PHILIPS CO LTD.	<u>TECHNICAL SPECIFICATION -</u> SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN' SPECS	Dimension
											Origin: China. 2. Philips Pakistan Address: K-2/I,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi 'GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address: K-2/I,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi '	
11	DNF96479	TG-24/50 / RE4020	056479222657 3 / CHARGER BATTERY 30A/50A 230V50HZ	BATTERY CHARGERS	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
12	DNF96304	TG-24/50 / RE4020	056479222657 3 / CHARGER BATTERY 30A/50A 230V50HZ	BATTERY CHARGERS	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
13	DNF96720	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	056279562000 6 / BATTERY LEAD ACID 12V 200AH	DG USED	6 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					<u>TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA SIZE: 511X280X246MM EXIDE PAKISTAN.</u> <u>GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA SIZE:511X280X246MM EXIDE PAKISTAN.</u>	
14	DNF96469		599576501671 3 / CABLE MICROPHONE	MICROPHONE /SRE SYSTEM.	300 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
15	DNF96580	SERVO CONTROL STAC JAPAN	611070504503 7 / STABILIZER 3KVA I/P50-130V/160-240VAC50/60HZ O/P110/220V STAC	ELECTRICAL GENERAL USE	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
DNF96296	PP3 . 6F22. (6135-00-900-2139)	613570100411 8 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25.75X017MM	AVO METER	30 / EACH/NUMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
DNF96302	GXE-3-1000M/GX T1000LMT PLUS230	611070509568 1 / UNINTRUPPT ED POWER SUPPLY (UPS) 1.0KVA (without batteries)	RESCO/PM-100 UPS OEM: RELIABLE SECURITY	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
DNF96475	SMT3000I C/SURTD3 000XLI/30 00VA APC	613071506382 3 / UPS 3KVA APC/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/NUMBER	MODEL ESP-808 (E) /SYSTEK PVT.					TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
DNF96653	SMT3000I C/SURTD3 000XLI/30 00VA APC	613071506382 3 / UPS 3KVA APC/P220V O/P220V W/BATTERY BACKUP 25	SELF	1 / EACH/NUMBER	MODEL ESP-808 (E) /SYSTEK PVT.					TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MINUTES.								WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE. SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL <u>GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE. SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL</u>	
20	DNF96730	STEEL/METAL LOCAL	492073512072 4 / PEINCE TABLE STAND	PA SYSTEM	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Heavy duty speaker stand. Light weight aluminum construction. Adjustable up to 6 feet in height. 65 Kg handling capacity. Samson, USA <u>GENERAL SPECIFICATION -</u> Heavy duty speaker stand. Light weight aluminum construction. Adjustable up to 6 feet in height. 65 Kg handling capacity. Samson, USA	
21	DNF96466	DM-1100/403	591076512072 7 / pro Goosenek Desktop MIC Electro-voice pc-12 & 18,48v phantom power	PA SYSTEM	17 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Multi-pattern gooseneck desk microphones. Dual condenser, back electric element. High pass/ normal response option. PTT/PTM option, MIC audio always On option Noise 26 dB. 50 HZ-20 KHz Freq Response. Nonreflecting black color, gooseneck length 470mm. <u>GENERAL SPECIFICATION -</u> Multi-pattern gooseneck desk microphones. Dual condenser, back electric element. High pass/ normal response option. PTT/PTM option, MIC audio always On option Noise 26 dB. 50 HZ-20 KHz Freq Response. Nonreflecting black color, gooseneck length 470mm.	

LFR No	PART NO	NSN / Description	Pr/Equipment	QTY / UENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
DNF95322	XR-800 FT/DC-CMS2200-3-MIG	142071512071 1 / PRO AUDIO MIXER DYNACORD CMS-1600/2200-3 16/22-CHANNEL	PA SYSTEM	2 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> Main voltage 100 to 240VAC, 50/60 Hz, battery power supply 48 V DC, 12 Mic/Line +4 Mic/Stereo inputs. 15 Hz-70KHz Freq response. master EQ 11 Band. XR-800 FT/DC-CMS2200-3-MIG OEM: DYNACORD ORIGIN: USAGENERAL SPECIFICATION - Main voltage 100 to 240VAC, 50/60 Hz, battery power supply 48 V DC, 12 Mic/Line +4 Mic/Stereo inputs. 15 Hz-70KHz Freq response. master EQ 11 Band. XR-800 FT/DC-CMS2200-3-MIG OEM: DYNACORD ORIGIN: USA</p>	
DNF95230	MINI-GBIC-LX-SM1310	534078528936 4 / OPTICAL TRANCEIVER MODULE (SFP 1310nm 1000Base-LxSM 1GbB, LC single mode 10Km)		6 / NUMBERS	MINI-GBIC-LX-SM1310					<p><u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null</p>	
DCP93911		653250040006 3 / BLANKET SCARLET RED HOSPITAL		200 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> BLANKET SCARLET RED HOSPITAL <u>GENERAL SPECIFICATION -</u> BLANKET SCARLET RED HOSPITAL</p>	
DNF96731	zkx8s	581515171795 8 / zk-teco zk-8s/ZKTECO G3 PLUS biometric finger print reader		1 / EACH/NUMBER	zkx8s/ZKTECO G3 Plus					<p><u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null</p>	
DNF96579	YSAPL22-DL24RHG / 153060718	621073520465 5 / INDICATION LIGHT (R-GREEN)	MONITORING & ALARM SYSTEM YSAPL22-DL24RHG KOREA	6 / EACH/NUMBER	YSAPL22-DL24RHG	NIL	87, HWANGMUL-RO, DONGDAEMUN-GU, SEOUL, KOREA	YONGSUNG KOREA		<p><u>TECHNICAL SPECIFICATION -</u> PANNEL INDICATION LIGHT IT'S A NORMAL INDICATION LIGHT THAT IS USED IN ELECTRICAL SWITCH BOARD. <u>GENERAL SPECIFICATION -</u> PANNEL INDICATION LIGHT IT'S A NORMAL INDICATION LIGHT THAT IS USED IN ELECTRICAL SWITCH BOARD.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabi ty	Tender Remarks	TECH / GEN SPECS	Dimension
27	DNF96575	ub500 / ZA3000E	6350785246359 / WALK THROUGH GATE WITH MONITOR & FACE CAPTURE CAMERA		1 / EACH/NUMBER	ub500 /ZA3000E					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
28	DCD96711		8455702802529 / SHOULDER BADGES BRASS FIRE BRIGADE		2000 / PAIR						TECHNICAL SPECIFICATION - SHOULDER BADGES BRASS FIRE BRIGADE Material Composition IRON NICKLE ZINC PEWTER GOLD PLATING POWDER COATING GENERAL SPECIFICATION - SHOULDER BADGES BRASS FIRE BRIGADE Material Composition IRON NICKLE ZINC PEWTER GOLD PLATING POWDER COATING	item required as per tender sample
29	DNF94290	NIL	4920705141287 / NETWORK CABLE TESTER WITH TOOL	BASIC ELECTRONIC WARFARE TRAIN	2 / EACH/NUMBER	NO DATA AVAILAB LE		PK	M/S DATA CUMMUN ICAION & CONTRO L(PVT) LTD.409 CLIFTON CENTER DC-1, BLOCK-5, KARACHI .75600.		TECHNICAL SPECIFICATION - OEM ADD/SOURCE OF AVAILABILITY:M/S DATA COMMUNICATION&CONTROL (PVT)LTD.409 CLIFTON CENTER DC-1,BLOCK-5,KARACHI.75600 GENERAL SPECIFICATION - OEM ADD/SOURCE OF AVAILABILITY:M/S DATA COMMUNICATION&CONTROL (PVT)LTD.409 CLIFTON CENTER DC-1,BLOCK-5,KARACHI.75600	
30	DNJ93706	94702-00400	1325765165142 / PLUG SPARKING (NGK LFR6A-11)	ENGINE F350A CYLINDER & CRANK CASE 2	32 / EACH/NUMBER	F350A	6AW-1004474	M/S YAMAHA MOTOR CO LTD 2500 SHINGAI IWATA SHIZUOKA JAPAN	YAMAHA JAPAN		TECHNICAL SPECIFICATION - OEM:M/S YAMAHA MOTOR CO LTD 2500 SHINGAI IWATA SHIZUOKA JAPAN. SOA:M/S CIROS ENTERPRISE 42 HAIDER ROAD RAWALPINDI 48000 PAKISTAN TEL: 051-5562202, 5567254. GENERAL SPECIFICATION - OEM:M/S YAMAHA MOTOR CO LTD 2500 SHINGAI IWATA SHIZUOKA JAPAN. SOA:M/S CIROS	

LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										ENTERPRISE 42 HAIDER ROAD RAWALPINDI 46000 PAKISTAN TEL: 051-5562202. 5567254.	
DNF93264	3BA23265	711070520497 1 / ANALOGUE EXTENSION BOARD (EZ 32-2)/ EZ 32	Navcomm Switches OXE FRANCE	12 / EACH/NUMBER	EZ 32-2		Immeuble Cyteo, 147, Avenue Paul Doumer 92500, Rueil-MALMAISON France.	M/s Alcatel Lucent France		TECHNICAL SPECIFICATION - This board is used to provide 32 Analogue Numbers. GENERAL SPECIFICATION - This board is used to provide 32 Analogue Numbers.	
DNF92089	GY 6.35	624015218393 1 / MARINE ENGINE ROOM LIGHT	PORTAL CRANE FD-IV	1 / EACH/NUMBER	GY 6.35	N/A	M/S DRSA	M/S DRSA		TECHNICAL SPECIFICATION - METALIC CAGE LIGHT WITH GLASS RATED VOOLTAGE 220 V FREQUENCY 50/60 HZ GENERAL SPECIFICATION - METALIC CAGE LIGHT WITH GLASS RATED VOOLTAGE 220 V FREQUENCY 50/60 HZ	
DNF94497	ML-1102S-A & B(2 RJ-45 PORTS)/ 4V1D	603070521593 7 / FIBER OPTIC MEDIA CONVERTER FOR IP CAMERAS	CCTV SYSTEM 4V1D PAKISTAN	1 / PAIR	ml-1102s-a & ml-1102s-b		Al-Sa'ee business Solutions Suit 30, 3rd Floor, Crown Centre Plot SB-1, Opp Bait-ul-Mukarram Masjid, Gulshan-e-Iqbal Karachi Tel & Fax (9221)3483-7233	Al-Sa'ee/Pro Secure		TECHNICAL SPECIFICATION - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission. GENERAL SPECIFICATION - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission.	
34 DNF91572	DCC/HFB M/HW/120	673070521320 1 / HDMI CABLE 30M DVI TO HDMI	OPERATOR CONSOLE DCC-2012016 PAKISTAN	4 / EACH/NUMBER	DCC-2012016	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212	DATA COMM		TECHNICAL SPECIFICATION - Make: Dell or HP DISPLAY CABLE GENERAL SPECIFICATION - Make: Dell or HP DISPLAY CABLE	
35 DNZ93271	98660/1153	533001415554 7 / WASHER	MAIN AIR COMPRESSOR	1 / EACH/NUMBER	NO DATA AVAILAB LE		UK	COMPAIR UK LTD ENGLAN D		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
36 DNF94323	3549.8550.00	599572513862 4 / DATA CABLE SCREENED 8 CORE	XK-2900L 1KW TX BERQV	60 / METER	NO DATA AVAILAB LE		GR	GERMAN YROHDE & SCHWAR Z		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
37 DNF8818	EN60 898	592576516079	CONVERSION	10 /	EN60 898		M/S DIGI TECH SHOP	M/S DIGI		TECHNICAL SPECIFICATION - M/S	

http://www.wims.mil/MSPage/L/BidAndCS/Print/View=497535569757747507

1/20/26, 3:24 PM

PDF.js viewer

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	0	TDC TIM DIN	9 / MCB 2 POLE 220V 10AMPS	OF BOATSWAIN INTO MRO/BEHR KUSHA	EACH/N UMBER	TDC TIM DIN		NO2 NEW MEMON CHAMMBER ALTAF HUSSAIN ROAD DENSO HALL KARACHI-7400 ,TEL: 2639514&2638482	TECH SHOP NO2 NEW MEMON		DIGI TECH SHOP NO2 NEW MEMON CHAMMBER ALTAF HUSSAIN ROAD DENSO HALL KARACHI-7400 ,TEL: 2639514&2638482 <u>GENERAL SPECIFICATION - M/S DIGI TECH SHOP NO2 NEW MEMON CHAMMBER ALTAF HUSSAIN ROAD DENSO HALL KARACHI-7400 ,TEL:2639514&2638482</u>	
38	DNJ91365	RM1100B/RM1100A	432001570734 6 / RULE MATE AUTOMATIC BILGE PUMP 12VDC WITH ALL ACCE	OUTFITTING ITEM-RHIB	1 / EACH/N UMBER	RM1100B /RM1100 A		RULEMATE, Maxico, www.rule-industries.com	RULEMATE, Maxico		<u>TECHNICAL SPECIFICATION - RULEMATE, Maxico, www.rule-industries.com Capacity: 1100GPH, with Skin fitting, One NRV, 5m flexible hose & hose clamp, 12V @ 3.4 Amp, Height: 4 1/4?, Width: 6?, Depth:3.25?, Footprint:2.75?x4.5?, Hose Size: 1 1/8?, Fuse size: 5</u> <u>GENERAL SPECIFICATION - RULEMATE, Maxico, www.rule-industries.com Capacity: 1100GPH, with Skin fitting, One NRV, 5m flexible hose & hose clamp, 12V @ 3.4 Amp, Height: 4 1/4?, Width: 6?, Depth:3.25?, Footprint:2.75?x4.5?, Hose Size: 1 1/8?, Fuse size:5</u>	
39	DNF95131	CMS-118	599870521930 4 / POWER EXTENSION BOARD CAMELLION MODEL CMS-118	SM RACK	2 / EACH/N UMBER	CMS-118 (CAMELLION)	NA	Commercially Of The Shelf (COTS)/Local Market	COTS		<u>TECHNICAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan</u> <u>GENERAL SPECIFICATION - 220V Power Connection Board. Used in mounting racks.pakistan</u>	
40	SNF51754	ACC24 25BB-3	592572512913 9 / CIRCUIT BREAKER 24VDC, 25AMPS(F8)	CUMMUNICAT ION SYSTEM	2 / EACH/N UMBER			GR	DIGI TECH DENSO HALL KARACHI		<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
41	DNJ95270	17471-98J01-000	292076522209 9 / PANEL, PUMP CASE UNDER	SUZUKI DF300AP 300 HP OBM	3 / EACH/N UMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u> <u>GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u>	
42	DNF95398	683-576	341379513775 3 / DRILLING MACHINE	DRILILING MACHINE	1 / EACH/N UMBER	NO DATA AVAILAB LE		UK	AIR SYSTEM UK LTD		<u>TECHNICAL SPECIFICATION - a. Product: Tiger 600W drill with accessories. b. Input: 600W. c.</u>	

LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										Capacity: 20mm. SPEED 0 TO 1500 CHUCK 3 JAW 10MM POWER 240V 50HZ GENERAL SPECIFICATION - a. Product: Tiger 600W drill with accessories. b. Input: 600W. c. Capacity: 20mm. SPEED 0 TO 1500 CHUCK 3 JAW 10MM POWER 240V 50HZ	
DNJ92238	6CE-81975-00	5340765203987 / PLATE, RECTIFIER FITTING	YAMAHA OBM	1 / EACH/NUMBER	NO DATA AVAILAB LE	6CE-1029885, 6CF-1009814	YAMAHA MOTOR CO. LTD JAPAN	JAPAN		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
DNF95321	06070301	2590999100334 / HORN ELECTRICAL 24V AC/DC 3AMP C/W BRACKET (SOGO CHINA BRAND)		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM, M/S SOGO GROUP COMPNIES CHINA. WWW. SOGOLIGHTINGWORLD. COM GENERAL SPECIFICATION - OEM, M/S SOGO GROUP COMPNIES CHINA. WWW. SOGOLIGHTINGWORLD.COM	
DNF94985	6 242 01	6130997427670 / CHARGER PANEL LIGHT, TYPE 10-MODIFIED 110/130V AND 200/250V 50/60HZ	PANNEL LIGHT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - country of origin uk GENERAL SPECIFICATION - country of origin uk	
46 DNG95844	MIL-I-24391	5970004194291 / TAPE INSULATION ELECT ADHES PLASTIC BLK LG1296"W.75" TH.0085"	CIWS consumble	30 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILAB GENERAL SPECIFICATION - NO DATA AVAILABLE	
47 DNF92651	380V/2500W LOCAL	7310PK5075718 / COOKING PLATE 380V 2500W LG 11.5" W 11.5"	COOCKING SYS.	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB GENERAL SPECIFICATION - NO DATA AVAILABLE	
48 DNF92678	38109-829 rev D/ GS-55	5910735120721 / pro Dynamic CARDIOD VOCAL MICROPHONE	PA SYSTEM	2 / EACH/NUMBER	ELECTR O VOICE					TECHNICAL SPECIFICATION - OEM, ELECTRO-VOICE USA. TECH-SPECS, Wired handheld microphones. DYNAMIC N/DYM MAGNET 45HZ-15000 HZ CARDIOD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			Electro-voice								Non reflecting black finish. On/Off switch. 3-pin XLR connector. Weight 238gm <u>GENERAL SPECIFICATION - OEM, ELECTRO-VOICE USA. TECH-SPECS, Wired handheld microphones. DYNAMIC N/DYM MAGNET 45HZ-15000 HZ CARDIOD</u> Non reflecting black finish. On/Off switch. 3-pin XLR connector. Weight 238gm	
49	DNF95585	6105.563910	615012364863 8 / POWER SUPPLY CABLE		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
50	DNF76594	AS(U) M332M500 DF1	591075531634 5 / CAPACITOR 3300 uf 500V DC AYX-HR (M)		9 / EACH/NUMBER	AYX-HR (M)					<u>TECHNICAL SPECIFICATION - Capacitor 3300MF 500V BATTERY CHARGING SYSTEM INDICATION MONITORING SYSTEM ANTI CONDENSATION HEATER AUDIBLE ALARM SYSTEM LIGHT INDICATOR FOR POWER ON/OFF SEPARATE CONTROL AND BATTERY BANK CABINET WITH WHEEL MOUNTING FOR EASE OF MOVEMENT.</u> <u>GENERAL SPECIFICATION - Capacitor 3300MF 500V BATTERY CHARGING SYSTEM INDICATION MONITORING SYSTEM ANTI CONDENSATION HEATER AUDIBLE ALARM SYSTEM LIGHT INDICATOR FOR POWER ON/OFF SEPARATE CONTROL AND BATTERY BANK CABINET WITH WHEEL MOUNTING FOR EASE OF MOVEMENT.</u>	
51	DCW94674		843050000002 9 / BOOT DMS SIZE 7		90 / PAIR						<u>TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7</u> <u>GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7</u>	ITEMS AS PER SPECIFICATION
52	DCW94680		843050000003 5 / BOOT DMS SIZE 9		90 / PAIR						<u>TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9</u> <u>MEDIUM GENERAL SPECIFICATION</u>	ITEMS AS PER SPECIFICATION

LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		MEDIUM								SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9 MEDIUM	TION
DCW94686		8430500001577 / BOOT DMS SIZE 14 MEDIUM		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 MEDIUM GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 MEDIUM	ITEMS AS PER SPECIFICATION
DCW94679		8430500000036 / BOOT DMS SIZE 9L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L	ITEMS AS PER SPECIFICATION
DNF94694	134-88-01	5998795284989 / KEYPAD		1 / EACH/NUMBER	134-88-01					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
DCW94682		8430500000034 / BOOT DMS SIZE 9S		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S	ITEMS AS PER SPECIFICATION
57 DNJ91674	65770-90J02	2990765310258 / PUMP, SQUEEZE		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - Rubber material (resistant to gasoline and ethanol blends)/ one way direction and internal check valves must prevent fuel from flowing back to tank once primed. Dimensions: Approximately 8 x 3 x 2 inches (203 x 76 x 51 mm) Weight: Approximately 0.4 lbs (0.18 Kg) Hose/ Fitting Size: Typically uses an 8mm (5/16 inch) hose connection Material: Made of specific rubber/ plastic that is resistant to gasoline and ethanol blends) GENERAL SPECIFICATION - Rubber material (resistant to gasoline and ethanol blends)/ one way direction and internal check valves must prevent fuel from flowing back to tank once primed. Dimensions: Approximately 8 x 3 x 2 inches (203 x 76 x 51 mm) Weight:	PDF.js viewer

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Approximately 0.4 lbs (0.18 Kg) Hose/ Fitting Size: Typically uses an 8mm (5/16 inch) hose connection Material: Made of specific rubber/ plastic that is resistant to gasoline and ethanol blends)	
58	SNC933 71	X0000342 0	293012386012 0 / ELBOW TO PLATE-CORE COOLE		1 / EACH/N UMBER	8V 2000 M84					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
59	DCW946 85		843050000157 8 / BOOT DMS SIZE 14 LARGE		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE	ITEMS AS PER SPECIFICA TION
60	DNO952 66	US050361 CSOOOO OO	543075535016 5 / PRESSURE TANK 50 litre 10 bar		1 / EACH/N UMBER	varem- maxivare m ls					TECHNICAL SPECIFICATION - PRESSURE MEMBRANE TANK 50 LITRE 10 BAR DIMM= 793X393X403 MM WEIGHT 12.9KG CAPACITY 50LITERS MAX PRESSURE 10BAR TEST PRESSURE 15 BARGENERAL SPECIFICATION - PRESSURE MEMBRANE TANK 50 LITRE 10 BAR DIMM= 793X393X403 MM WEIGHT 12.9KG CAPACITY 50LITERS MAX PRESSURE 10BAR TEST PRESSURE 15 BAR	
61	DNF9532 3	SBS- MF 673-22 / WINXP (SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MA C/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		1 / EACH/N UMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLEGENERAL SPECIFICATION - 4G DATA WINGLE	
62	DNF9553 3	SBS- MF 673-22 / WINXP (SP3 ONWARD S)	599870527756 7 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		12 / EACH/N UMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLEGENERAL SPECIFICATION - 4G DATA WINGLE	

LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimensions
	VISTAWIN 7/ WINS WIN10/MA C/LINUX										
DCW946 76		843050000003 3 / BOOT DMS SIZE 8L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8L <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8L	ITEMS AS PER SPECIFICA TION
DNF9469 6	134-88-25	599879528499 1 / LCD ASSEMBLY		1 / EACH/N UMBER	134-88-25					TECHNICAL SPECIFICATION - null <u>GENERAL SPECIFICATION -</u> null	
SNC933 72	X5941450 0018/87	281572530067 1 / EXHAUST PIPE BELOWS		1 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - WEIGHT: 13.500KG <u>GENERAL</u> SPECIFICATION - WEIGHT: 13.500 KG	
DCW946 83		843050000004 5 / BOOT DMS SIZE 12L		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L	ITEMS AS PER SPECIFICA TION
DN09300 7	RK 50/65- SEW	281578528496 8 / rEDUCER COUPLING (DN 50 TO DN 65 - 2 INCH TO 3 INCH) FOR FF HOSE		4 / EACH/N UMBER	RK 50/65- SEW					TECHNICAL SPECIFICATION - ALUMINIUM ALLOY COUPLING WITH RUBBER SEALS <u>GENERAL</u> SPECIFICATION - ALUMINIUM ALLOY COUPLING WITH RUBBER SEALS	PDF.js viewer
DCW946 73		843050000002 5 / BOOT DMS SIZE 6S		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 6S <u>GENERAL</u> SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 6S	items as per specification
DNF9469 5	A074A900	599879528498 8 / system control board scb1		1 / EACH/N UMBER	NA					TECHNICAL SPECIFICATION - OEM:M/S HARTRIDGE NETWORK RADCLIVE ROAD ,BUCKINGHM,MK 18,4FD,UK LOCAL SOURCE:M/S COUNTRY WIDE TRADE LINKERS 9-D,1ST FLOOR.CANTT BAZAR AREA MALIR CANTT KARACHI- 75070. <u>GENERAL SPECIFICATION -</u> OEM:M/S HARTRIDGE NETWORK	

https://www.wims.nl/IMS/press/PI/BI/DA/DCST.xhtm?M=6975355687577475277

1/20/26, 3:23 PM

LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimensio
										RADCLIVE ROAD ,BUCKINGHM,MK 18,4FD,UK LOCAL SOURCE:M/S COUNTRY WIDE TRADE LINKERS 9-D,1ST FLOOR,CANTT BAZAR AREA MALIR CANTT KARACHI-75070.	1/20/26 3:23 PM
DCW95602		8430500759140 / BATH ROOM CHAPPLE FOR SURGEON		350 / PAIR						TECHNICAL SPECIFICATION - BATH ROOM CHAPPLE FOR SURGEON GENERAL SPECIFICATION - BATH ROOM CHAPPLE FOR SURGEON	items on required as per specifications
DCW94678		8430500000031 / BOOT DMS SIZE 8S		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8S GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8S	ITEMS AS PER SPECIFICATION
DNJ91673	15642-88L10	2940765308432 / FILTER		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - The part is a pre-filter (coarse mesh strainer). Body made of special plastic and filter mesh made of SS. Dimensions: 4 in x 4 in x 2 in (10 cm x 10 cm x 5 cm) Approx. Weight: 0.2 lbs GENERAL SPECIFICATION - The part is a pre-filter (coarse mesh strainer). Body made of special plastic and filter mesh made of SS. Dimensions: 4 in x 4 in x 2 in (10 cm x 10 cm x 5 cm) Approx. Weight: 0.2 lbs	PDF is viewer
73 DCW94684		8430500001576 / BOOT DMS SIZE 13 LARGE		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 13 LARGE GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 13 LARGE	ITEMS AS PER SPECIFICATION
74 DCW94677		8430500000032 / BOOT DMS SIZE 8 M		90 / PAIR						TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8 M GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 8 M	ITEMS AS PER SPECIFICATION