

PAKISTAN NAVY
TENDER BULLETIN

INVITATION TO TENDER TO BE OPENED ON 11-02-2026

TERMS & CONDITION

1. INTERESTED FIRMS/ SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT / PAY ORDER/ CROSSED CHEQUE OF RS. 500/- (NON REFUNDABLE) ALONGWITH THEIR QUOTATION IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT".

2. FOR ANY AMPLIFIED DETAILS, INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON, THROUGH TELEPHONE, VIA EMAIL OR HARD MAIL. DELIVERY TIME OF LOCALLY AVAILABLE AND IMPORTED ITEMS ARE 15 AND 45 DAYS RESPECTIVELY.

3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGT96593	707	5530FM036007 6 / 5 LAYERS PLYWOOD	WEAPON AND AMMUNITION STORAGE SYSTEM	17 / EACH/N UMBER	NIL		FENGTAI DISTRICT YUNGANG NORTH WEST BEIJING CHINA Tel : 86-13911121951 Fax : 86-010-68191140 Email : lujirui@live.cn	BEIJING ELECTR OMECHA NICAL ENGINEE RING INSTITUT E,CHINA		<u>TECHNICAL SPECIFICATION -</u> AVAILABLE IN TPI <u>GENERAL SPECIFICATION -</u> AVAILABLE IN TPI	
2	DGE96744	MIL-I-46852	597000177162 7 / TAPE INSULATION ELECTRICAL NOMINAL WD 1.5		60 / ROLL	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> PVC TAPE OSAKA Tape insulation electrical ADHES plastic BLK WD 19 mm thickness 0.2mm <u>GENERAL SPECIFICATION -</u> PVC TAPE OSAKA Tape insulation electrical ADHES plastic BLK WD 19 mm thickness 0.2mm	
3	DGT96750	NO DATA AVAILABL E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTAB LISHMENT	43 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI		<u>TECHNICAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM <u>GENERAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									. TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.			
4	DGT96785	NO DATA AVAILAB E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTAB LISHMENT	50 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		<u>TECHNICAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM <u>GENERAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	
5	DGT96782	NO DATA AVAILAB E	934070514992 3 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB TO 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE	WOOD WORKS SHIPS&ESTAB LISHMENT	10 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI		<u>TECHNICAL SPECIFICATION -</u> SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB <u>GENERAL</u> <u>SPECIFICATION -</u> SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			RESISTANT						. TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.			
6	DGE96814	NO DATA AVAILABLE	0476590000063 / GLOVES-LEATHER RIGHT HAND		38 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10 GENERAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10	
7	DGE96799	04769430557, BS2992TABLE8ITEM 8/5	0476599430557 / BRUSH VARNISH TYNEX FIBER FLAT SQUARE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUARE EDGE 4. Packaging Separately packed/ wrapped/ any suitable GENERAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUARE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
8	DGE96728	NIL	0476599430558 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		45 / EACH/NUMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
9	DGE96738	C-268	0476599430559 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		15 / EACH/NUMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
10	DGE96709	NIL	0559794444897 / SLEEVE		10 / METER						TECHNICAL SPECIFICATION - SPECS= BS 2848 OEM: UK TYPE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			INSULATION ELECT CERAMIC, VARNISH GLASS FIBer, I/D 2MM								OF SLEEVE W.R.T CONSTRUCTION: HEAT PROOF SLEEVE. COLOUR: WHITE GENERAL SPECIFICATION - SPECS= BS 2848 OEM: UK TYPE OF SLEEVE W.R.T CONSTRUCTION: HEAT PROOF SLEEVE. COLOUR: WHITE	
11	DGE968 01	0415-2502	0415599231450 / CORK AND RUBBER SHEET, LG.01 MTR WIDTH 01 MTR THICK 3.175MM. SYNTHETIC RUBBER DEF 22		16 / SHEET						TECHNICAL SPECIFICATION - CORK AND RUBBER SHEET,Item Specification: DEF-22,THIC=3.175mm,LG=01 MTR WIDTH 01 MTR Synthetic Rubber. GENERAL SPECIFICATION - CORK AND RUBBER SHEET,Item Specification: DEF-22,THIC=3.175mm,LG=01 MTR WIDTH 01 MTR Synthetic Rubber.	
12	DGT967 00	NO DATA AVAILABL E	0100546002290 / BAMBOO SIZE 28FT-30FT LONG	DEISEL GENERATOR	30 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10-30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREE GENERAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10-30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREE	
13	DGT966 99		5510705007248 / HARD BOARD WHITE FORMICA NO 253		64 / SQ FEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
14	DGT966 98	NO DATA AVAILABL E	01000000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	48 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
15	DGT967 48	NO DATA AVAILABL E	01000000000004 / HARD BOARD 12FT X 4FT X 1/8 IN (3.66MTR X		48 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			1.22MTR X 3.175MM)									
16	DGT967 81	NO DATA AVAILAB E	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	836 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 <u>GENERAL</u> <u>SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
17	DGT967 49	NO DATA AVAILAB E	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	1280 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 <u>GENERAL</u> <u>SPECIFICATION - 1.</u> BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
18	DGE968 15	ITD	841570508793 1 / CLOTH CURTAIN MATERIAL FIRE RETARDANT		45 / METER						TECHNICAL SPECIFICATION - Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150 Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire Retardancy test as Type-B of BS-5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1) GENERAL SPECIFICATION - Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150 Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire Retardancy test as Type-B of BS-5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1)	
19	DGE967 42	ITD	841570508793 1 / CLOTH CURTAIN MATERIAL FIRE		45 / METER						TECHNICAL SPECIFICATION - Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			RETARDANT								Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire Retardancy test as Type-B of BS-5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1) GENERAL SPECIFICATION - Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150 Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire Retardancy test as Type-B of BS-5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1)	
20	DGT967 10	NO DATA AVAILAB E	010050000002 9 / Ply wood, Marine All Shesham, 13- Ply, GD-II, (WBP, Treated with Preservative) Size: L=8FT, W=4FT, TH=25MM, (Core inner plies & veneer) (Wood Should be all		2 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER GENERAL SPECIFICATION _1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Shesham)									
21	DGE968 22	NO DATA AVAILABLE	0451500000113 / MATTRESS FOAM BUNK SAILORS 72X30X4 INCH		15 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Brand: Diamond Supreme FOAM Size: 24" inch Width x 72" inch Length Warranty Period: 05 Years <u>GENERAL SPECIFICATION -</u> Brand: Diamond Supreme FOAM Size: 24" inch Width x 72" inch Length Warranty Period: 05 Years	
22	DGT967 84	NO DATA AVAILABLE	0100500000039 / TIMBER FIR HIMALAYA/ SPRUCE SLEEPER, WELL SEASONED LOCAL/ IMPORTED, SIZE: L=8'-15', W=8"-14", h=4"-10"	(3.05MTR X254 MM X127 MM) SPECE/PSG 69	30 / CUBIC FOOT	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%, <u>GENERAL SPECIFICATION -</u> SPECS= PSG/69 well-seasoned wood, moisture content = 12% ± 02%,	
23	DGE968 23	IS8021	0476546004785 / Coated Rigger Gloves with Rubberized Cuff		10 / PAIR						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
24	DGT967 76	BS 1088 & BS 6566 OF 1985	0100546001443 / PLYWOOD 7PLY GDII SIZE 8X4FTX1/2INCH TYPE GRADE (INT)		20 / SQ FEET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
25	DGE967 14	ASTM D 6413	7210505155170 / FIRE RETARDANT SPRING MATTRESS (L6'XW2'XH4)	MATRESSES FOR BED	30 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		<u>TECHNICAL SPECIFICATION -</u> FIRE RETARDANT SPRING MATTRESS (L6'XW2'XH4) <u>GENERAL SPECIFICATION - FIRE RETARDANT SPRING MATTRESS (L6'XW2'XH4)</u>	
26	DGB943 61	39X131	5999785140091 / WIRE MESH	HOOPER DECK	200 / EACH/NUMBER	NO DATA AVAILABLE		CH	CHINA		<u>TECHNICAL SPECIFICATION - MS, 11X4 FEET</u> <u>GENERAL SPECIFICATION - MS, 11X4 FEET</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			11X4FEET									
27	DGE88603	ALM7140A	841573513973 6 / DIVING GLOVES	DIVING	15 / PAIR	ISF PROLINE		OC	TIWAN		TECHNICAL SPECIFICATION - SOFT,THICK RUBBER, SIZE: NORMAL SIZE GENERAL SPECIFICATION - SOFT,THICK RUBBER, SIZE: NORMAL SIZE	
28	DGE85456	NO DATA AVAILABLE	933070505435 4 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PN CREST	5 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DGB91163		530699124362 8 / BOLT MACHINE ISO STEEL HEX HD SIZE 16X5X38 MM	FASTENINGS, BOLTS AND STUDS.	120 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE: 16X5X38 MM, MATERIAL: MS, Grade AISI 4140, BOLT HEAD HEXAGON GENERAL SPECIFICATION - SIZE: 16X5X38 MM, MATERIAL: MS, Grade AISI 4140, BOLT HEAD HEXAGON	
30	DGE94710	NO DATA AVAILABLE	045150000000 5 / CLOTH FOR CURTAIN WIDTH 46 INCHES.		142 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
31	DGB91180	NO DATA AVAILABLE	021459003561 3 / BOLT MACHINE STEEL BLACK BSW HEX HD SZ 1.500X0.250		70 / TEN						TECHNICAL SPECIFICATION - a. Material: MS BSW b. Length of bolt: 38 MM c. Length of thread: Full thread d. Diameter :06 MM e. Shape: HEX MATERIAL GRADE EN 4140 GENERAL SPECIFICATION - a. Material: MS BSW b. Length of bolt: 38 MM c. Length of thread: Full thread d. Diameter :06 MM e. Shape: HEX MATERIAL GRADE EN 4140	
32	DGE82108	SA9-27020	626001196013 6 / LIGHT, CHEMILUMINESCENT 6INCH YELLOW	REPLENISHMENT LIGHT	30 / EACH/NUMBER			CYALUME TECHNOLOGIES SA 295 R MAYOR DE MONTRICHER AIX EN PROVENCE FRANCE AIX EN PROVENCE CEDEX 04 42 37 17 80 04 42 37 17 99	CYALUME TECHNOLOGIES		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								XFARCY@CYALUME.COM WWW.CYALUME.COM				
33	DGB97163	R-02	668570534480 3 / FON GAS REGULATOR, SIZE.20 mm. R-02		4 / EACH/NUMBER	R-02					TECHNICAL SPECIFICATION - FON GAS REGULATOR 1. SIZE 20MM 2. INPUT PRESSURE 16 BAR 3. EXPENSION PRESSURE 0-4 BAR 4. GUARANTED OUTPUT 0-8 KG/HRS 5. TYPE OF GAS PROPANE - BUTANE & LPG High pressure Regulator-Quick on fixed pressure. Corrosion-resistant materials for longevity. Size Inlet: 20mm Outlet: 10mm Pressure: 0-4 bar Easy installation and maintenance. Child lock: On a regulator is a safety feature designed to prevent accidental changes or tampering with the regulator's settings. GENERAL SPECIFICATION - FON GAS REGULATOR 1. SIZE 20MM 2. INPUT PRESSURE 16 BAR 3. EXPENSION PRESSURE 0-4 BAR 4. GUARANTED OUTPUT 0-8 KG/HRS 5. TYPE OF GAS PROPANE - BUTANE & LPG High pressure Regulator-Quick on fixed pressure. Corrosion-resistant materials for longevity. Size Inlet: 20mm Outlet: 10mm Pressure: 0-4 bar Easy installation and maintenance. Child lock: On a regulator is a safety feature designed to prevent accidental changes or tampering with the regulator's settings.	
34	DGH94626	GDHBMK4092040	4010FT1007918 / STEEL WIRE ROPE (20MM/40M/NON-ROTATING/GALVANIZED)	9M COMBINED BOAT CRANE	6.75 / EACH/NUMBER	GD.HBM.K.S-40/6-PG&40/9	N/A	GURDESAN GEMI MAK. SAN.TIC.A.S, DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM, KOCAELI, TURKEY TEL # 9.02627E+11 FAX # 9.02627E+11 INFO@GURDESAN.COM.	GURDESAN GEMI MAK. SAN.TIC.A.S		TECHNICAL SPECIFICATION - A. Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								TR			20mm H. Approx Weight (KG/100m): Not held in OEM technical manual <u>GENERAL SPECIFICATION - A.</u> Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual	
35	DGT97094	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	100 / FOOT	NO DATA AVAILABLE		PK	TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		<u>TECHNICAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required <u>GENERAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
36	DGT94058	NO DATA AVAILABLE	9340705149922 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTABLISHMENT	9 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETANI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE		<u>TECHNICAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM <u>GENERAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									0322-2578654.			
37	DGE894 12		047659943041 4 / BRUSH PAINT SQ EDGE S/TOOL 8 STCL MRKG EXP DIA 1.125" LG 2.8"		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DGE966 60		035059571312 8 / ROPE NYLON, HAWSERLAID, 3-STRAND, Z- LAY, NOM DIA: 20MM, (13/16") CIRC: 2.50 INCH, TYPE-1		1400 / FATHO M						TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI GENERAL SPECIFICATION _1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI	
39	DGE96712	NO DATA AVAILABLE	035059571313 2 / ROPE NYLON, 3- STRAND, CIRC: 4-INCH, DIA: 32MM		120 / FATHOM	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM. 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI <u>GENERAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI	
40	DGB95445		028359571145 6 / ROD NAVAL BRASS RD DIA 2.12 INCH WT.13.14 PER FOOT(LB)	SP.BS 2874,CZ 112M	1 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
41	DGB97182		021450214060 4 / BOLT AND NUTS STEEL HEX HD SZ 5.000X1. 000 IN		28 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
42	DGB74640		027370910447 6 / DIVIDERS SPRING LG OF LEG 06IN		20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
43	DGB96820	NO DATA AVAILABL E	027378000942 6 / BLADE HACKSAW SIZE 12IN TP1- 32		6 / DOZEN	Eclipse Plus, Griffon,(or any other brand)					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
44	DGB93553	1A2672	027579910547 3 / PICK HEAD, DIGGING TYPE , CHISEL&POIN		27 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - STANDARD/SPECIFICATION=BS1421TABLE-2(AS PER BR320D) <u>GENERAL SPECIFICATION</u> - STANDARD/SPECIFICATION=BS14	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			T SZ,4.50LBS EYE, UNIVERSAL NO2								21TABLE-2(AS PER BR320D)	
45	DGE966 61	C1560	033059571325 0 / TWINE HEMP WHITING LINE 40YDS STRENDS 3 MIN BREAKING 48 LBS, C1559	ALSO KNOWN AS FISHING LINE TO BS 2019	15 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - a.</u> Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019 <u>GENERAL SPECIFICATION -</u> a. Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019	
46	DGE966 58		033059571325 2 / TWINE NYLON MACKEREL LINE 3 STRD MIN BKG STRENGTH 140 LBS.		16 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Dimensions: 3 STRD 2mm x 218 yard BS 6125 OF 1981 TABLE 12 <u>GENERAL SPECIFICATION -</u> Dimensions: 3 STRD 2mm x 218 yard BS 6125 OF 1981 TABLE 12	
47	DGE948 24	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-STRAND, Z-LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	240 / FATHOM						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
48	SGB93209		027679910583 2 / SCRAPER ENGINEER LG 6"		10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
49	DGB96819		027679910583 2 / SCRAPER ENGINEER LG 6"		40 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
50	DGB94064		026659001603 0 / WASHER FLAT ROUND MILD STEEL 0.625X0.687X1.375X0.128IN	O/D 34.925 INCH THK 0.128 INCH SPEC=BS 1769	146 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER REQUIREMENT IS REQUIRED <u>GENERAL SPECIFICATION</u> - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM),	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DIAMETER 1.375" INCH (34.925 MM), THICKNESS 0.128" INCH (3.25 MM), NO TEMPER REQUIREMENT IS REQUIRED	
51	DGE96641	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	420 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
52	DGE96485	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
53	DGB969 81		025770128378 2 / BOLT MACHINE BRASS BSW HEX HD TPI 8 SZ 1.000X3. 000X2.000 IN		12 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - material grade of brass is naval brass (c46400) 60 % copper, 39.2% zinc and 0.8% tin <u>GENERAL SPECIFICATION</u> - material grade of brass is naval brass (c46400) 60 % copper, 39.2% zinc and 0.8% tin	
54	DGB969 82		025770128378 3 / BOLT MACHINE BRASS BSW HEX HD SZ 1.000X1. 750X4.000 IN		16 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
55	DGB969 75	1473	024879129614 8 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE,DOOR NOT LESS THAN3/8"THK-	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03 <u>GENERAL SPECIFICATION</u> - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03	
56	DGB968 18		026259000627 4 / RAT GUARD DIAMETER OF ROPE 5-6 1/2 INCH		70 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
57	DGB792 14		025159411964 8 / HINGE- BUTT-BRASS-		116 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SINGLE								AVAILABLE	
58	DGE78220		422050510192 9 / LIFE JACKETS (Orange/Camo uflage)	FOR PERSONNAL SAFETY,PNS QASIM,PRIZE ENT	65 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - (1) Buoyancy: 7.5kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003</u> <u>GENERAL SPECIFICATION - (1) Buoyancy: 7.5 kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003</u>	
59	DGB96761	66694	451099761024 5 / MIXER SHOWER UNIT 1/2" DUPLEX MIX FITTING TOP OUTLEY FOR 15MM	INLETS CHROME PLATED(COLD &WARM WATER)	5 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
60	DGB96821	ANT COUPLIN G-	472070505711 2 / FIRE HOSE SIZE 2-1/2" X100 FEET DURLANE 500 LIGHT ALLOY INST-	FOR FIRE FIGHTING	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
61	DGE89091		533070505066 3 / CARD BOARD SHEET SIZE 31"X50 1/2" THICKNESS 05MM.	FOR PACKING PURPOSE FOR PP CENTRE	100 / SHEET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
62	DGT94179		551050507742 5 / WOODEN BEEDING DESIGNED		100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE WIDTH 2" THICK 1/2"									
63	DGH94671	TSGU-400	614500110634 1 / CABLE ELECT 3- COND/0.742" SI & GLASS INSUL PVC JKT 1000V 400A		250 / METER						TECHNICAL SPECIFICATION - 04 ton Ac Compressor MIL-C- 24643/16 GENERAL SPECIFICATION - 04 ton Ac Compressor MIL-C-24643/16	
64	DGH94330		614570505767 9 / CABLE ELEC 4COR O/D-52MM N/STRAND-36 S/D-2MM C/D- 18MM 280AMP		250 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DGE94091	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		60 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
66	DGB96708	NO DATA AVAILABL E	024850000001 5 / SAFE- STEEL-WITH- COMBINATION -LOCK FOR CBs SZ 28X20X16 5/8		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record GENERAL SPECIFICATION - A. BODY: 16	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record	
67	DGB94658	NO DATA AVAILAB LE	026850000004 7 / WEIGHING MACHINE 50 KG - 300 kg		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - a.</u> Make Model: OMEGA TAIWA/KINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g <u>GENERAL SPECIFICATION - a.</u> Make Model: OMEGA TAIWA/KINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g	
68	DGB97022	NO DATA AVAILAB LE	026850000004 7 / WEIGHING MACHINE 50 KG - 300 kg		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - a.</u> Make Model: OMEGA TAIWA/KINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g <u>GENERAL SPECIFICATION - a.</u> Make Model: OMEGA TAIWA/KINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g	
69	DGD96803		773070504806 1 / SAUCER TEA GOLDEN CRESTED		6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u> <u>GENERAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u>	
70	DGD96810	NO DATA AVAILAB LE	773070504805 3 / PLATE DINNER 26CM GOLDEN CRESTED		6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 26CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u> plate dinner o/a dia 26 cm golden crested <u>GENERAL SPECIFICATION - 26CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u> plate dinner o/a dia 26 cm golden crested	
71	DGD96809		773070504805 5 / PLATE		6 / EACH/N						<u>TECHNICAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED ,</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PUDDING FLAT 19CM GOLDEN CRESTED		UMBER						MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
72	DGD970 20		773070504805 5 / PLATE PUDDING FLAT 19CM GOLDEN CRESTED		100 / EACH/N UMBER						TECHNICAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
73	DGD970 26		773070504805 8 / PLATE SOUP 9INCH GOLDEN CRESTED		100 / EACH/N UMBER						TECHNICAL SPECIFICATION - 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
74	DGD968 04		773070504806 0 / CUP TEA GOLDEN CRESTED		6 / EACH/N UMBER						TECHNICAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
75	DGE890 87	NO DATA AVAILABL E	043250000002 6 / HELMET PROTECTIVE DESPATCH RIDER SIZE 6 5/8"		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
76	DGE943 75	NO DATA AVAILABL E	046150000008 6 / GOGGLE CHIPPING		60 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band. <u>GENERAL SPECIFICATION</u> - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.	
77	DGE93945		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIES)	OLIVE GREEN WATERPROOF INNER LINING OF,	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 50 X 20 FEET (± 6 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 07 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 850 GSM OR ABOVE AND WITH ROT-PROOF, WATERPROOF AND VAT-DYED TREATMENT. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a. IRON POLES:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b. IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. THE PARTICIPANT OF THE TENT TO BE PROVIDED A CERTIFICATE OF MEMBERSHIP FROM PCTMEA (PAKISTAN CANVAS AND TENTS MANUFACTURERS AND EXPORTERS ASSOCIATION) OR AN AUTHORITY LETTER FROM MEMBER ALONG WITH TECHNICAL QUOTATION. 7. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.<u>GENERAL SPECIFICATION - 1.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 50 X 20 FEET (± 6 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 07 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 850 GSM OR ABOVE AND WITH ROT-PROOF, WATERPROOF AND VAT-DYED TREATMENT. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b. IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. THE PARTICIPANT OF THE TENT TO BE PROVIDED A CERTIFICATE OF MEMBERSHIP FROM PCTMEA (PAKISTAN CANVAS AND TENTS MANUFACTURERS AND EXPORTERS ASSOCIATION) OR AN AUTHORITY LETTER FROM MEMBER ALONG WITH TECHNICAL QUOTATION. 7. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.	
78	DGE94837		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE AND WITH ROT-PROOF, WATERPROOF AND VAT-DYED TREATMENT. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											STEEL), OUTER DIA 50 MM $\pm$ 02 MM & THICKNESS 02 MM $\pm$ 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM $\pm$ 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. THE PARTICIPANT OF THE TENT TO BE PROVIDED A CERTIFICATE OF MEMBERSHIP FROM PCTMEA (PAKISTAN CANVAS AND TENTS MANUFACTURERS AND EXPORTERS ASSOCIATION) OR AN AUTHORITY LETTER FROM MEMBER ALONG WITH TECHNICAL QUOTATION. 7. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1. SIZE/ DIMENSION</u> a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET ($\pm$ 3 INCH) b. HEIGHT OF TENT: 12 FEET ($\pm$ 2 INCH) c. HEIGHT OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WALL: 06 FEET ($\pm$ 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE AND WITH ROT-PROOF, WATERPROOF AND VAT-DYED TREATMENT. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM $\pm$ 02 MM & THICKNESS 02 MM $\pm$ 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM $\pm$ 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. THE PARTICIPANT OF THE TENT TO BE PROVIDED A CERTIFICATE OF MEMBERSHIP FROM PCTMEA (PAKISTAN CANVAS AND TENTS MANUFACTURERS AND EXPORTERS ASSOCIATION) OR AN AUTHORITY LETTER FROM MEMBER ALONG WITH TECHNICAL QUOTATION. 7. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
79	DGE94011		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE AND WITH ROT-PROOF, WATERPROOF AND VAT-DYED TREATMENT. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LENGTH 18 INCHES, THICKNESS 20 MM $\pm$2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. THE PARTICIPANT OF THE TENT TO BE PROVIDED A CERTIFICATE OF MEMBERSHIP FROM PCTMEA (PAKISTAN CANVAS AND TENTS MANUFACTURERS AND EXPORTERS ASSOCIATION) OR AN AUTHORITY LETTER FROM MEMBER ALONG WITH TECHNICAL QUOTATION. 7. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION</u> - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET ($\pm$ 3 INCH) b. HEIGHT OF TENT: 12 FEET ($\pm$ 2 INCH) c. HEIGHT OF WALL: 06 FEET ($\pm$ 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE AND WITH ROT-PROOF, WATERPROOF AND VAT-DYED TREATMENT. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM $\pm$ 02 MM & THICKNESS 02 MM $\pm$ 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM $\pm$ 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. THE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PARTICIPANT OF THE TENT TO BE PROVIDED A CERTIFICATE OF MEMBERSHIP FROM PCTMEA (PAKISTAN CANVAS AND TENTS MANUFACTURERS AND EXPORTERS ASSOCIATION) OR AN AUTHORITY LETTER FROM MEMBER ALONG WITH TECHNICAL QUOTATION. 7. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
80	DGT93912	NO DATA AVAILABLE	0100000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	78 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
81	DGE96647	NO DATA AVAILABLE	0310500000006 / CANVAS COTTON NATURAL GREY (WD: 36 INCH)		150 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION: Features: Water proof and Rot Proof Width & Length: 36" and 50 Meter roll Weight: 12 OZ per Sq. Yard Colour: Natural Grey GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY. GENERAL SPECIFICATION - SPECIFICATION: Features: Water proof and Rot Proof Width & Length: 36" and 50 Meter roll Weight: 12 OZ per Sq. Yard Colour: Natural Grey GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY.	
82	DGE96657	NO DATA AVAILABLE	8340505039262 / QANAT COMPLETE SIZE 18.X 7. OUT SIDE GREEN PRINTED CLOTH, 100%		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COTTON.								100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON,BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED. <u>GENERAL SPECIFICATION</u> - Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
83	DGE94602		834070508924 9 / CAMOUFLAGE NET, SIZE: 30X25FT FOR COVER 12.7-MM GUNS	TO COVER COMOUFLAG E TE 12.7MM GUNS	5 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION OF ITEM : 1. 100% POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A).	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH G1 COATED 300 G/SQ METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438 <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM : 1. 100% POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH G1 COATED 300 G/SQ METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438	
84	DGE94132	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	2 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					<u>TECHNICAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. <u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
85	DGE89076	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	25 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					<u>TECHNICAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. <u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
86	DGT97098	NO DATA AVAILAB LE	010050000001 0 / PLY WOOD GD 1, 11 PLY (CORE AND INNER PLIES OF POPLAR AND BOTH FACE AND BACK VENEER OF)		32 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 8 FEET WIDTH=4 FEET TH=22 MM Specification 1. Moisture Content BS EN 322 : 1993 2. Bonding Quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993 <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TYPE OF BOND INT, TREATED WITH PRESERVATE D.								SIZE: LENGTH= 8 FEET WIDTH=4 FEET TH=22 MM Specification 1. Moisture Content BS EN 322 : 1993 2. Bonding Quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993	
87	DGB94070	NO DATA AVAILABLE	0265500001302 / HINGES-PYANO-STEEL- LG 6 FT 0.750-INCH WIDTH		109 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
88	DGB96816	NO DATA AVAILABLE	7110705036067 / SAFE STEEL WITH KEYS AND COMB LOCK OF C/B 18" X18"X17"TH 1/8"	FOR GENERAL PERPOSE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less than 3/8" d. No of levers: Minimum 02 GENERAL SPECIFICATION - Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less than 3/8" d. No of levers: Minimum 02	
89	DGB96759		2530705124260 / SHANK WASH BASIN		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
90	DGD82195		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		6 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
91	DGD96808	NO DATA AVAILAB E	003150000005 4 / DISH FLAT RICE 33cm GOLDEN CRESTED (AS PER STOCK SAMPLE)		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - GOLDEN CRESTED ,MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) make/brand cera-e- noor material procelain size 12" (30cm) golden crested with pn logo (same standardised item is already issue to various pn unit ref haibat/03/7762412 GENERAL SPECIFICATION - GOLDEN CRESTED ,MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) make/brand cera-e- noor material procelain size 12" (30cm) golden crested with pn logo (same standardised item is already issue to various pn unit ref haibat/03/7762412	
92	DGE85332	k817-r	534070527873 4 / rubber wheel (under carriage)		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - A) 6" RED PP WHEEL NYLON MATERIAL WITH REUOLING BRACKET COMPLETE (MADE BY LOCAL) B) 6" RED PP WHEEL NYLON MATERIAL WHEEL ONLY (MADE BY LOCAL)GENERAL SPECIFICATION - A) 6" RED PP WHEEL NYLON MATERIAL WITH REUOLING BRACKET COMPLETE (MADE BY LOCAL) B) 6" RED PP WHEEL NYLON MATERIAL WHEEL ONLY (MADE BY LOCAL)	
93	DGB78617	VE-SB-1168	545050533278 1 / SIDE BRACKET 3 10		105 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
94	DGD96925	SWP-900	732070533280 2 / rOTI wedge press		1 / EACH/N UMBER	latest					TECHNICAL SPECIFICATION - Production Capacity: 800-1000 pcs/hour roti weight: 70-100 grms roti size: dia 7-9 inch thickness 2mm to 3mm electric motors: 1hp with variable speed controller electric heater: 4000 watts 220v/50hz construction: heavy duty body frame made of ms angle iron and covered with stainless steel sheets Parent equipment: electric roti plantGENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Production Capacity: 800-1000 pcs/hour roti weight: 70-100 grms roti size: dia 7-9 inch thickness 2mm to 3mm electric motors: 1hp with variable speed controller electric heater: 4000 watts 220v/50hz construction: heavy duty body frame made of ms angle iron and covered with stainless steel sheets Parent equipment: electric roti plant	
95	DGH858 71	10830-1600	4010795160140 / STAINLESS STEEL WIRE ROPE (6X19+SE) 16MM	FORE & MAIN LOWER/UPPER FOOF ROPES /STIRRUPS/FLAM	50 / METER	10830/1600		MANUFACTURE ADDRESS: JACOB UK MMA ARCHITECHUARL SYS BROADWAY HOUSE, UNIT 5.SECOND AVENUE WESTFIED INUSTRIAL ESTATE MIDSOMER NORTON SOMERSET.BA3 4BH	JACOB UK MMA ARCHITECHUARL		<u>TECHNICAL SPECIFICATION -</u> MANUFACTURE ADDRESS: JACOB UK MMA ARCHITECHUARL SYS BROADWAY HOUSE,UNIT 5. SECOND AVENUE WESTFIED INUSTRIAL ESTATE MIDSOMER NORTON SOMERSET.BA3 4BH TEL:0845 1300 185 FAX:0845 1300 136 E-MAIL:sales@jacob.co.uk <u>GENERAL SPECIFICATION -</u> MANUFACTURE ADDRESS: JACOB UK MMA ARCHITECHUARL SYS BROADWAY HOUSE,UNIT 5. SECOND AVENUE WESTFIED INUSTRIAL ESTATE MIDSOMER NORTON SOMERSET.BA3 4BH TEL:0845 1300 185 FAX:0845 1300 136 E-MAIL:sales@jacob.co.uk	
96	DGE971 17	NIL	6515705181277 / TOWEL PAPER 24 ROLLS PER PACK	NIL	12 / CARTON			LOCAL MARKET	NOT KNOWN		<u>TECHNICAL SPECIFICATION -</u> No of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 Inch <u>GENERAL SPECIFICATION -</u> No of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 Inch	
97	DGE970 24		7210505155172 / FIRE RETARDANT SPRING MATTRESS (L6'XW2'XH6)	MATRESSES FOR BED	30 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		<u>TECHNICAL SPECIFICATION -</u> size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 <u>GENERAL SPECIFICATION -</u> size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
98	DGB972 29	24340	9515705231776 / STEEL PANNELING	ships galley (officer washroom)	15 / SHEET	Pakistran	Nil	Umair Brothers street # 10 , Abu Bakr Siddique colony, opposite new khan, Band	Umair Brothers		<u>TECHNICAL SPECIFICATION -</u> THICKNESS SWG 22 (22 GAUGE), MATERIAL GRADE 304, Size 8 x 4	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SHEET (STAINLESS STEEL), SIZE 8 X 4 (FEET), Thickness SWG 22 (22 Gauge), Material Grade 304					Road LAHORE contact # 0321-8400118 Office # 042-37465031			(feet)GENERAL SPECIFICATION - THICKNESS SWG 22 (22 GAUGE), MATERIAL GRADE 304, Size 8 x 4 (feet)	
99	DGB97230	CC500-009	9515505225456 / ALUMINUM SHEET (4FT X 8FT), THICKNESS 1 MM	Customized Container STUS	14 / EACH/NUMBER	-CC500-009	NIL	M/s Global Traders C-39, Naval Housing Scheme Clifton Karachi Cell # 0300-8262549 Tel # 02135877485 Email: Globaltraders39@gmail.com	M/s Global Traders		TECHNICAL SPECIFICATION - ALUMINUM SHEET SIZE (4FT X 8FT), THICKNESS 1 MM POWDER COATEDGENERAL SPECIFICATION - ALUMINUM SHEET SIZE (4FT X 8FT), THICKNESS 1 MM POWDER COATED	
100	DGE97143	HEN003007	8010795208198 / FABRIC 1300 GSM MILITARY GREY (HYPALONE)	RHIB BOAT	4 / METER		NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON, SOMERSET, BA9 9RX, TEL*01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHAW INFLATABLES LTD		TECHNICAL SPECIFICATION - 1. EXTERNAL COATING= CSM (CHLOROSULFONATED POLYETHYLENE) OVER LAYER OF CR (NEOPRENE), 2. INTERNAL COATING= CR (NEOPRENE), 3. TENSILE STRENGTH= >=350 DAN/GCM, 4. TEAR RESISTANCE= >=16 DAN, 5. WEIGHT= 1300 (+/- 100G) G/M2, 6. BASE FABRIC= POLYESTER (HIGH TENACITY 1100 DTEX-990 DENIERS), 7. MARINE STANDARD, RESISTANT TO UV RAYS, ABRASION, HYDROCARBONS AND EXTREME TEMPERATURES, FIRE AND HEAT RESISTANT, AIR TIGHT, FLEXIBLE AND EASY TO BOND TO MANY MATERIALS, 8. MAKE/ OEM COUNTRY OF ORIGIN/ MANUFACTURE= HENSHAW COMPANY, UNITED KINGDOMGENERAL SPECIFICATION - 1. EXTERNAL COATING= CSM (CHLOROSULFONATED POLYETHYLENE) OVER LAYER OF CR (NEOPRENE), 2. INTERNAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COATING= CR (NEOPRENE), 3. TENSILE STRENGTH= >=350 DAN/GCM, 4. TEAR RESISTANCE= >=16 DAN, 5. WEIGHT= 1300 (+/- 100G) G/M2, 6. BASE FABRIC= POLYESTER (HIGH TENACITY 1100 DTEX-990 DENIERS), 7. MARINE STANDARD, RESISTANT TO UV RAYS, ABRASION, HYDROCARBONS AND EXTREME TEMPERATURES, FIRE AND HEAT RESISTANT, AIR TIGHT, FLEXIBLE AND EASY TO BOND TO MANY MATERIALS, 8. MAKE/ OEM COUNTRY OF ORIGIN/ MANUFACTURE= HENSHAW COMPANY, UNITED KINGDOM	
101	DGB97180		0283700001608 / INGOT-BRASS		20 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg <u>GENERAL SPECIFICATION -</u> Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg	
102	DGB97172		0283705711230 / ALUMINIUM ALLOY ANGLE EQUAL SIDED	BR 320 D/1976 UNIT OF AVAIL 12-30 FT LG	320 / METER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: FOR CHEMICAL COMPOSITION BS EN 573-3 OF 2019 + A2: 2022FOR MECHANICAL PROPERTIES BS 755-2 OF 2025 GRADE: ENAW 5083 SIZE: LENGTH OF LEG: 2X2 INCHES. THICKNESS: 1/4 INCHES. WEIGHT PER FEET (POUNDS): 1.02 POUNDS. RUNNING LENGTH: 12 TO 30 FEET. <u>GENERAL SPECIFICATION - SPECIFICATION:</u> FOR CHEMICAL COMPOSITION BS EN 573-3 OF 2019 + A2: 2022FOR MECHANICAL PROPERTIES BS 755-2 OF 2025 GRADE: ENAW 5083 SIZE: LENGTH OF LEG: 2X2	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCHES. THICKNESS: 1/4 INCHES. WEIGHT PER FEET (POUNDS): 1.02 POUNDS. RUNNING LENGTH: 12 TO 30 FEET.	
103	DGE970 54		041459000437 1 / SHEET C-A-F (E-1/4927/1322 DT:21.07.92)		30 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
104	DGE967 01		047659000006 2 / GLOVES LEATHER LEFT HAND.		38 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable GENERAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable	
105	DGE970 97	NO DATA AVAILABLE	047659000006 3 / GLOVES-LEATHER RIGHT HAND		46 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10 GENERAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10	
106	DGE971 51	NIL	055979444490 1 / SLEEVEING GLASS INSULATION CERAMIC VARNISHED GLASS FIBRE 6MM	GENERAL ELECTIC USE	35 / METER						TECHNICAL SPECIFICATION - BS 2848 (5970994444901) GENERAL SPECIFICATION - BS 2848 (5970994444901)	
107	DGE971 13	U1901 AND P35M	041459923069 9 / PACKING ASSY MICA SZ.1.5/32,OD. 3/4,I/D 13/64 2 PERSET SQ. C/S		20 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
108	DGE971 47	L/NO.E-1/4927-A/520 DT. 110698.	041459924554 2 / CLOTH ASBESTOS 1/8		25 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
109	DGE970 52		041359923875 1 / WASHER		12 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			RUBBER 1.125X0. 625X0.500IN								<u>SPECIFICATION - NO DATA AVAILABLE</u>	
110	DGE96931		046250220180 3 / TUBING PLASTIC POLYETHLEN E LAY FLAT WD.48	DC/FF	30 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317 <u>GENERAL SPECIFICATION -</u> 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317	
111	DGE97099	04769430557, BS2992TABLE8ITEM 8/5	047659943055 7 / BRUSH VARNISH TYNEX FIBER FLAT SQUIRE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	116 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 2.</u> Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable <u>GENERAL SPECIFICATION - 2.</u> Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
112	DGE97100	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		94 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - bs</u> 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES <u>GENERAL SPECIFICATION - bs</u> 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
113	DGE97145		046159000386 6 / WICK COTTON FOR ENGINE ROOM LANTERN LENGTH 6"		1 / DOZEN						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WIDTH 1"									
114	DGE97144		0461590005946 / TAPE MEASURING 5 FT LENGTH (PLASTIC) USE FOR TAILORING		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
115	DGB97220		0283709233504 / ZINC INGOT 99.995% PURITY LG 16",BREADTH 8",HT 1.75"		210 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005% GENERAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005%	
116	DGB97049		0283709233504 / ZINC INGOT 99.995% PURITY LG 16",BREADTH 8",HT 1.75"		250 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005% GENERAL SPECIFICATION - BS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005%	
117	DGB96359	0283-12403	0283595711504 / ROD COPPER RD ANNEALED DIA 1.25 INCH SPEC.BS 2874 C 107-0		10 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
118	DGB97221		0283595711213 / ALUMINIUM BRONZE RoD ROUND SOLUTION HEAT TREATED, DIA 3 inch, running LENGTH 6-10 feet, wt. per pound 25.500 (lbs).		3 / METER						<u>TECHNICAL SPECIFICATION</u> - DEF STAN 02-833. DIA: 3 INCH. RUNNING LENGTH: 6-10 FEET. WT. PER POUND: 25.500 (LBS). <u>GENERAL SPECIFICATION</u> - DEF STAN 02-833. DIA: 3 INCH. RUNNING LENGTH: 6-10 FEET. WT. PER POUND: 25.500 (LBS).	
119	SGB97125	BS1453, 0283-12060	0283592015141 / ROD WELDING BRASS 57.0-63.0 % COPPER DIA 1/4 LG 36		40 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - b. Product Name Brass Welding Rod c. Diameter 1/4 inch (6.35mm) d. Product Category Welding Filler Material e. Color Yellow f. Standard/ Grade AWS A5.8 RBCuZn-C ISO 3677 B-CuZn40 g. Chemical Composition Copper (Cu) 57.0% to 63.0% Zinc (Zn) 40% h. Length 36 inches (914mm) j. Packaging Bundled in 5KG/ 10 KG <u>GENERAL SPECIFICATION</u> - b. Product Name Brass Welding Rod c. Diameter 1/4 inch (6.35mm) d. Product Category Welding Filler Material e. Color Yellow f. Standard/ Grade AWS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											A5.8 RBCuZn-C ISO 3677 B-CuZn40 g. Chemical Composition Copper (Cu) 57.0% to 63.0% Zinc (Zn) 40% h. Length 36 inches (914mm) j. Packaging Bundled in 5KG/ 10 KG	
120	DGB971 78		028359571144 7 / ROD NAVAL BRASS RD DIA 01 INCH	GENERAL USE	1 / METER						TECHNICAL SPECIFICATION - BS EN 12163 OF 1998, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT : (LBS), R-LENGTH-03 METERS (EACH)GENERAL SPECIFICATION - BS EN 12163 OF 1998, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT : (LBS), R-LENGTH-03 METERS (EACH)	
121	DGB963 64		028359571145 7 / ROD NAVAL BRASS RD DIA 2.25" WT PER FT 14.73(LB)		6.35 / METER						TECHNICAL SPECIFICATION - Specifications: BSEN 12163 of 1998 Grade CW 712R (M), Running Length (Min): 02 meterGENERAL SPECIFICATION - Specifications: BSEN 12163 of 1998 Grade CW 712R (M), Running Length (Min): 02 meter	
122	DGB971 79		028359571145 9 / ROD NAVAL BRASS RD DIA.2.50 INCH WT PER MTR 27.49 KG		17 / METER						TECHNICAL SPECIFICATION - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU zN 39 SN 1GENERAL SPECIFICATION - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU zN 39 SN 1	
123	DGE970 88	NO DATA AVAILABL E	045159451001 3 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	240 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINSGENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	
124	DGE971 50	0414-5160	041459923093 4 / SHEET, ASBESTOS, COMPRESSE D TH 1/16", WD 54"X63" IN WT PER SHEET 22LBS		205 / KILOGR AMME						TECHNICAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)GENERAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(COLOURED RED BOTH SURFACES)	
125	DGE97111	NIL	041359923892 4 / RUBBER SHEET SOLID NATURAL		6 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 1154 OF 1992 COMPUND Y2 COMPOUND CLASSIFICATION Y-50 Cloth insert, also known as rubber insertion, Thick: 0.063 inch, width: 43 inch, No of PLY: 01 Approx, wt per sq ft: ½ Lbs, tensile strength 17Mpa, Hardness: 50+5-4. Spec: BS 1154 GENERAL SPECIFICATION - BS 1154 OF 1992 COMPUND Y2 COMPOUND CLASSIFICATION Y-50 Cloth insert, also known as rubber insertion, Thick: 0.063 inch, width: 43 inch, No of PLY: 01 Approx, wt per sq ft: ½ Lbs, tensile strength 17Mpa, Hardness: 50+5-4. Spec: BS 1154	
126	DGE97112	NO DATA AVAILABLE	041359923969 2 / HOSERUBBER NATURAL RUBBER INNER SURFACE COTTON BRAND ENFORCEMENT INTERNAL DIA. 2.00 NO PLIES 3" WALT HIK 23/64		30 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DGB96356		021259571069 9 / BAR STEEL CORROSION RESISTING H/R RD 0.50		19 / METER						TECHNICAL SPECIFICATION - material grade: SS316L GENERAL SPECIFICATION - material grade: SS316L	
128	DGB96353	BS970/EN 58J, L-42H35	021259571070 0 / BAR-STEEL-HOT-ROLLED-RD-DIA. 5/8	GENERAL PURPOSE	10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
129	DGB95441		021259923280 2 / BAR STEEL CORROSION RESISTING H/R RD 1.25"		1 / METER						TECHNICAL SPECIFICATION - minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J (AS PER BR320D) GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WT PER FT 4.209LBS								minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D)	
130	SGB971 19	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	25 / KILOGRAMME						TECHNICAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface GENERAL SPECIFICATION _a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
131	DGB963 52		028359571152 2 / ROD COPPER ALLOY NICKEL RD DIA 2.00INCH WT PER FT 12.00(LB)		25 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
132	DGB971 81		021259571004 7 / BAR- STEEL- CARBON- COLD- FINISHED-1.37 INCH		140 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
133	DGE971 22	947- 430229	H94799560058 2 / RUBBER STRIP	GENERAL PURPOSE	33 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
134	DGE971 05	NO DATA AVAILABLE	055979901422 1 / INSULATION- SLEEING- 1MMRED		1 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
135	DGE971 06	NO DATA AVAILABLE	055979901803 2 / INSULATION- SLEEING- YELLOW-5MM	GENERAL USE	1 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
136	DGE97107	NO DATA AVAILABLE	0559799018033 / INSULATION-SLEEVING-BLUE-5MM		1 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
137	DGE97146	NO DATA AVAILABLE	0559799004675 / INSULATION-SLEEVING-ELECT-1.5MM-RED DIA 1.500		1 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
138	DGE97089	NO DATA AVAILABLE	0461500006792 / CHALK WHITE SOFT	W/T DOORS & FIT	217 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
139	DGE96934		0462592202406 / TUBING PLASTICS POLYTHYLENE LAY FLAT TH.0.005 (127MICRON) WD 12INCHES.	PACAGING /PRESERVATION	40 / KILOGRAMME						TECHNICAL SPECIFICATION - SPECS= BS 7344 , 1990 GENERAL SPECIFICATION - SPECS= BS 7344 , 1990	
140	DGB97244		4710995711787 / PIPING STEEL SEAMLESS DIAMETER 76.20 MM, THICKNESS 4.877 MM	GENERAL USE	3 / METER						TECHNICAL SPECIFICATION - Outer Diameter: 76.2 mm, Inner Diameter: 66.446 mm, Thickness: 4.877 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel S275JR GENERAL SPECIFICATION - Outer Diameter: 76.2 mm, Inner Diameter: 66.446 mm, Thickness: 4.877 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel S275JR	
141	DGB97228		4710995712125 / TUBING COPPER NICKLE ALLOY (90/10 copper nickle) size: external dia: 2.128 inch wall thickness		35 / METER						TECHNICAL SPECIFICATION - 1. DEFSTAN:02-779/2000 2. Defstan: 02-878 3.bs en 12449 of 1999 (grade cw352h) GENERAL SPECIFICATION - 1. DEFSTAN:02-779/2000 2. Defstan:02-878 3.bs en 12449 of 1999 (grade cw352h)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(nom): 0.064 inch length : 06 meter nom size : 02 inch									
142	DGE97109	NO DATA AVAILABLE	4220795055193 / WHISTLE PLASTIC FOR GENERAL SERVICE LIFE JACKET	LIFE JACKET MK-1,ORALLY INFLATED	45 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
143	SGB97067	200-GK	5120012894310 / RIVETER BLIND HAND SIZE 3/32 1/8 5/32		15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
144	DGE97114	MILR6855 CLASS1GRADE40	5330002615433 / RUBBER SHEET-SD 1-8 THK	NOZZLE TY 1.5IN PSI 60T125GPM	60 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DGE97116	NO DATA AVAILABLE	5970705047304 / Nylon Transparent Tape (1 inch size).		30 / ROLL						TECHNICAL SPECIFICATION - manufacturer with following details: a. Manufacturer Name: Gold Star (GS) b. Item Name: Nylon Transparent Tape c. Size: 1 inch d. Price: Rs 55/- SAME ITEM IS ALSO AVAILABLE FROM LOCAL market GENERAL SPECIFICATION - manufacturer with following details: a. Manufacturer Name: Gold Star (GS) b. Item Name: Nylon Transparent Tape c. Size: 1 inch d. Price: Rs 55/- SAME ITEM IS ALSO AVAILABLE FROM LOCAL market	
146	DGE97149	NO DATA AVAILABLE	0330780000221 / HAVING LINE NYLON 025.4MM 467MS	MSI	2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
147	DGE97050	NO DATA AVAILABLE	0413500000133 / EAR DEFENDER		53 / PAIR	PELTOR H10A/ OPTIME 105					TECHNICAL SPECIFICATION - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip) <u>GENERAL SPECIFICATION</u> - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip)	
148	DGE97148	NO DATA AVAILABLE	0413500000152 / P.V.C.BEND FOR PIPE DIA 1.25".		11 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
149	DGE97091	NO DATA AVAILABLE	0462500000022 / TAPE-BROWN-PAPER-GUMMED (DTLD. NSD/TD/19/286 . DT.090492		12 / ROLL	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - Make/Model/Brand Transparent/Brown Carton Sealing Packing Tapes, Brand 7M,Pakistan. Detailed Specification/Technical Data 38-48 MICRON, 69-72 METER/YARD LENGTH, 46-48 MM WIDTH, WEBSITE:WWW.7mbrand.com Approx Price:Rs/-499 x 6 pieces, (www.daraz.com) <u>GENERAL SPECIFICATION</u> - Make/Model/Brand Transparent/Brown Carton Sealing Packing Tapes, Brand 7M,Pakistan. Detailed Specification/Technical Data 38-48 MICRON, 69-72 METER/YARD LENGTH, 46-48 MM WIDTH, WEBSITE:WWW.7mbrand.com Approx Price:Rs/-499 x 6 pieces, (www.daraz.com)	
150	DGE97093	NO DATA AVAILABLE	0474500000307 / FENDER COIR ROUND		21 / EACH/NUMBER	600MM 24" ROUND					<u>TECHNICAL SPECIFICATION</u> - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
						COIR BOAT FENDER					OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES. WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY .GENERAL SPECIFICATION- CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES. WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.	
151	DGD972 33		773070504805 5 / PLATE PUDDING FLAT 19CM GOLDEN CRESTED		112 / EACH/N UMBER						TECHNICAL SPECIFICATION- FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
152	DGD972 34		773070504805 8 / PLATE SOUP 9INCH GOLDEN CRESTED		100 / EACH/N UMBER						TECHNICAL SPECIFICATION- 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
153	DGE971 18	NO DATA AVAILABL E	792000543649 2 / PAPER TOWEL		50 / BOX						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
154	DGE97087	NO DATA AVAILABLE	0451500000075 / HOOKS FOR CURTAIN		141 / DOZEN	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
155	DGE97120	NIL	8105011242645 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217-9451	STATIC SAFETY OF EQUIPMENT/COMPONENTS	40 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557 <u>GENERAL SPECIFICATION -</u> ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
156	DGE97124	TPT400-F1755	8305995275924 / GLASS CLOTH FIBER, PLAIN WEAVE, COLOUR NATURAL, FOR LAGGING PURPOSE	FOR LAGGING PURPOSE	4 / METER						<u>TECHNICAL SPECIFICATION -</u> testing criteria: DEFSTAN02-801, PART-2, WIDTH: 01 METER (39.4 INCH) FIBER MATERIAL: GLASS, CLOTH WEIGHT: 800 GRMS PER SQUARE METER, SPECIAL FEATURES: PLAIN WEAVE, MULTIFILAMENT WARP YARN, NATURAL COLOUR, 50 METERS PER ROLL <u>GENERAL SPECIFICATION -</u> testing criteria: DEFSTAN02-801, PART-2, WIDTH: 01 METER (39.4 INCH) FIBER MATERIAL: GLASS, CLOTH WEIGHT: 800 GRMS PER SQUARE METER, SPECIAL FEATURES: PLAIN WEAVE, MULTIFILAMENT WARP YARN, NATURAL COLOUR, 50 METERS PER ROLL	
157	DGT97025	NO DATA AVAILABLE	01005000000018 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8',	SPECEFICATION.IM-2581 (E)	2000 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			W=4', TH=12MM								314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 <u>GENERAL SPECIFICATION</u> - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
158	DGT96910	NO DATA AVAILABLE	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFICATION.IM-2581 (E)	1600 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 <u>GENERAL SPECIFICATION</u> - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
159	DGE97051	NO DATA AVAILABLE	041350000019 0 / TUBING PLASTIC		486 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - Size Wall Thick: 2.5MM Length of Tube: 50FT O/D: 32MM I/D: 27MM Spec:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TRANSPAREN T(G/USE) O/D 32MM I/D 27MM TH.2.5 MM, LENGTH (MIN) 50 METER, MATERIAL: PLASTIC GRADE-1								5039 PG 99 Material: Plastic Grade-1 <u>GENERAL SPECIFICATION</u> - Size Wall Thick: 2.5MM Length of Tube: 50FT O/D: 32MM I/D: 27MM Spec: 5039 PG 99 Material: Plastic Grade-1	
160	DGE969 62	ITD	841570508793 1 / CLOTH CURTAIN MATERIAL FIRE RETARDANT		45 / METER						<u>TECHNICAL SPECIFICATION</u> - Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150 Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire Retardancy test as Type-B of BS- 5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1) <u>GENERAL SPECIFICATION</u> - Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150 Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire Retardancy test as Type-B of BS- 5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
161	DGE97236	ITD	841570508793 1 / CLOTH CURTAIN MATERIAL FIRE RETARDANT		45 / METER						TECHNICAL SPECIFICATION - Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150 Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire Retardancy test as Type-B of BS-5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1) GENERAL SPECIFICATION - Material: 100% Polyester. Inheritably Flame Retardant Polyester Fiber Weight: 270 gm/sq.m +/-5% Width: 58 Inches +/- 2% Wrap Count: 150 Denier Flame Retardant Polyester Filament Yarn. Weft Count: Ne 30/3 Ply- Polyester Spun Yarn +/- Ne3 Color: Light Brown with Box Pattern. Fire Retardant STD: Item is to be tested Fire Retardancy as per BS 5867. Test is to be conducted through M/s SGS Laboratories through its Foreign Source. Fire Retardancy test as Type-B of BS-5867 Part-2 Length of Roll: 30 Mtr Clock Curtain material: (twill fabric 2/1)	
162	DGT96911	NO DATA AVAILAB E	010050000001 0 / PLY WOOD GD 1, 11 PLY (CORE AND INNER PLIES OF POPLAR AND BOTH FACE AND BACK VENEER OF)		100 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 8 FEET WIDTH=4 FEET TH=22 MM Specification 1. Moisture Content BS EN 322 : 1993 2. Bonding Quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993 GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TYPE OF BOND INT, TREATED WITH PRESERVATIVE D.								SIZE: LENGTH= 8 FEET WIDTH=4 FEET TH=22 MM Specification 1. Moisture Content BS EN 322 : 1993 2. Bonding Quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993	
163	DGT96941	NO DATA AVAILABLE	0100500000028 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLYS OF SHESHAM WOOD) 5-PLY	2.440X1.220MTRX6.35MM) SPECE/BS-1088	360 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, GENERAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM.	
164	DGE97095	NO DATA AVAILABLE	0476590000033 / BRUSH WRITEING GOOSE		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
165	DGD91425		0035500000520 / UTENSILS COOKING ALUMINUM O/D 24 TO 26"		14 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			, H12 TO 14" TH 10 SWG WITH OUT COVER								H12 to 14" TH 10 SWG WITH out COVER <u>GENERAL SPECIFICATION</u> - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
166	DGD97184		0035500000520 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		12 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER <u>GENERAL SPECIFICATION</u> - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
167	DGD91423		0035500000520 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		11 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER <u>GENERAL SPECIFICATION</u> - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
168	DGD91532		0035500000520 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		14 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER <u>GENERAL SPECIFICATION</u> - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
169	DGB97219	STJ19	5340725283924 / TRICLAD ALUMINIUM/S TEEL TRANSITION JOINT PLATE 3800X1350X19 MM		15 / EACH/NUMBER	TRICLAD					TECHNICAL SPECIFICATION - NOBLECLAD ORDER NO. 02466, SAMPLE NOS. 655/15.003, 655/15.007, HEAT TREATMENT REQUIREMENT TEMPERATURE 300 0C FOR DURATION 15 MINUTES, CUSTOMER: MERREM & LA PORTE B.V. GENERAL SPECIFICATION - NOBLECLAD ORDER NO. 02466, SAMPLE NOS. 655/15.003, 655/15.007, HEAT TREATMENT REQUIREMENT TEMPERATURE 300 0C FOR DURATION 15 MINUTES, CUSTOMER: MERREM & LA PORTE B.V.	
170	DGE97121	d000-004	8440735270720 / cotton gloves (pack of 12 gloves)		5 / PAIR	na					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
171	DGB73645	0264	4030795153885 / SPLIT THIMBLES (316 STAINLESS STEEL)14MM	TAL SHIP SAILING RIG	130 / EACH/NUMBER			BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST,HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET.COM.WEB;WWW.BASELINEHARDWARE.CO.UK	UK		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY ; BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET.COM.WEB;WWW.BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX;+44(0) 1489578835. GENERAL SPECIFICATION - SOURCE OF AVAILABILITY ;BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET.COM.WEB;WWW.BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX;+44(0) 1489578835.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
172	DGB94364		953599571140 1 / PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 3600 mm X WIDTH 910 mm X 6.4 MM BASE THICKNESS CROSS - SECTION THICKNESS: 8.8MM base thickness 6.4 MM	MATERIAL SPEC.BS 1477HP 30SPEC. ADSP1098A	30 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 3600 MM X WIDTH 910 MM X 6.4 MM BASE THICKNESS CROSS - SECTION THICKNESS: 8.8MM British Specification 1474 along with Material Grade 6082 and heat treatment condition T6. Embossed pattern height: 2.4 mm ± 0.5 mm above the base metal. basic shape style: b2 pattern no 10 density: 18.95 KG/M2 DEFSTAN 02-840 (NES- 840) <u>GENERAL SPECIFICATION -</u> PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 3600 MM X WIDTH 910 MM X 6.4 MM BASE THICKNESS CROSS - SECTION THICKNESS: 8.8MM British Specification 1474 along with Material Grade 6082 and heat treatment condition T6. Embossed pattern height: 2.4 mm ± 0.5 mm above the base metal. basic shape style: b2 pattern no 10 density: 18.95 KG/M2 DEFSTAN 02-840 (NES- 840)	
173	DGB95195		028259571216 2 / PIPING COPPER ROUND SEAMLESS (External dia 0.50 INCH)		60 / METER						<u>TECHNICAL SPECIFICATION -</u> material grade: acr (astm B280), C- 10200 or C-12200. EXTERNAL DIAMETER: 0.50 INCH WALL THICKNESS: 0.032"(MULLAR USA MAKE) Specifications:BS 2871 AND DESIGNATION C-106 (Relevant to Tubes for equipment) METARIAL DESIGNATION: Copper & Copper Alloys Seamless, Round Tubes for Air Conditioning & Refrigeration Temper Condition: soft fully anealled coils Conditioning & Refrigeration system Running Length: In shape of Coil/Roll of 50 feet length (equivalent 15.24 meters) <u>GENERAL SPECIFICATION -</u> material grade: acr (astm B280), C-10200 or C-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											12200. EXTERNAL DIAMETER: 0.50 INCH WALL THICKNESS: 0.032" (MULLAR USA MAKE) Specifications: BS 2871 AND DESIGNATION C-106 (Relevant to Tubes for equipment) METARIAL DESIGNATION: Copper & Copper Alloys Seamless, Round Tubes for Air Conditioning & Refrigeration Temper Condition: soft fully annealed coils Conditioning & Refrigeration system Running Length: In shape of Coil/Roll of 50 feet length (equivalent 15.24 meters)	
174	DGE87090	NIL	055979444490 1 / SLEEVING GLASS INSULATION CERAMIC VARNISHED GLASS FIBRE 6MM	GENERAL ELECTIC USE	45 / METER						<u>TECHNICAL SPECIFICATION - BS 2848 (5970994444901)</u> <u>GENERAL SPECIFICATION - BS 2848 (5970994444901)</u>	
175	DGE83648	NIL	055979444489 7 / SLEEVE INSULATION ELECT CERAMIC, VARNISH GLASS FIBer, I/D 2MM		40 / METER						<u>TECHNICAL SPECIFICATION - SPECS= BS 2848 OEM: UK TYPE OF SLEEVE W.R.T CONSTRUCTION: HEAT PROOF SLEEVE. COLOUR: WHITE</u> <u>GENERAL SPECIFICATION - SPECS= BS 2848 OEM: UK TYPE OF SLEEVE W.R.T CONSTRUCTION: HEAT PROOF SLEEVE. COLOUR: WHITE</u>	
176	DGB97044		028359571145 5 / ROD NAVAL BRASS DIA 2 INCH (WT PER FT 11.72 LB)		5 / METER						<u>TECHNICAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.</u> <u>GENERAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.</u>	
177	DGB94365		021259571025 9 / BAR STEEL		300 / METER						<u>TECHNICAL SPECIFICATION - Specs: BS970, Grade EN3A/070M20</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CARBON HOT ROLLED FLAT 2-1/2"X3/8"WT PER FT3. 19LBS								, Running Length: 06 meter GENERAL SPECIFICATION - Specs: BS970, Grade EN3A/070M20 , Running Length: 06 meter	
178	DGB72878		0273702731395 / AXE HAND 3.5 LBS		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
179	DGB97397		0267595213278 / PIPING STEEL GALVANIZED SEAMLESS, L : 6.1 M, E/DIA 26.9MM, TH 2.6 MM, N/BORE:19.1 MM	UTS LENGTH. BULK SUPPLY	228 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS GENERAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS	
180	DGB87160	6211ZZ, 211SS	3110001556277 / BEARING BALL ANNULAR SZ 55.00X100.00X21.00MM		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
181	DGB79513		5110715056595 / ALLEN KEYS SET 1.5 MM TO 10MM 09PIECE	TENSILE TESTING MACHINE	4 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
182	DGB39396	MODEL P-40	5130765016394 / ELECTRIC PORTABLE PLANNER AND GROOVERS (C/WD 136 MAX-C/D 3MM)	GENERAL USE	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
183	DGE78372	NO DATA AVAILABLE	0413500000134 / EAR DEFENDER LARGE SIZE		15 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
184	DGH94577		9515505017879 / PLATE STEEL HT SZ		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			7300X2470X012MM								AVAILABLE	
185	DGH94653		9515705031217 / PLATE STEEL FLOOR ROLLED	FOR GENERAL USED	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTOGRAPH ATTACHED <u>GENERAL SPECIFICATION -</u> BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTOGRAPH ATTACHED	
186	DGH94623		9515705031217 / PLATE STEEL FLOOR ROLLED	FOR GENERAL USED	15 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTOGRAPH ATTACHED <u>GENERAL SPECIFICATION -</u> BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTOGRAPH ATTACHED	
187	DGB81967		0277599106231 / SPANNER O/JAW FXD D. E 0.625X0.688" W0.563X0.625" L MAX12X10.25		14 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	