

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 31-03-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPC993 43	205-6611 (05 Ltr) / 205-6612 (20 Ltr)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (05 Liter Can)	CP AIR COMP	21 / LITER						TECHNICAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205- 6612 FOR 20 LTR GENERAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTR	
2	DPC995 28	B71003, B71046 OR ACCELRA TOR G (POLYAC C P-A)	681073100100 0 / CRYSTIC ACCELRA TOR G (OEM = SCOTT BADER) OR ACCELRA TOR G (POLYACC P-A)		10 / KILOGR AMME						TECHNICAL SPECIFICATION - Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25 KG GENERAL SPECIFICATION - Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											KG	
3	DNH99384	NO DATA AVAILAB LE	1308500530125 / REFRIG 12CUFT DOUBLE DR 220V(DLT. NSSD/HM/PATT/467 DT. 121093)	12 CUF	1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
4	SPC99310	XCJ	6850FP0990003 / SILICA GEL MOISTURE ABSORPTION AGENT		800 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
5	SPC99312	GB7820-1987	6850FP0990004 / DESICCANT		200 / KILOGR AMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
6	DNM96769	7564870	5331735245513 / 189.5x3 90sh o-ring		8 / EACH/N UMBER	CLASSIC V					TECHNICAL SPECIFICATION - 189.5X3 90SH O-RING SHB 90 GENERAL SPECIFICATION - 189.5 X3 90SH O-RING SHB 90	
7	DNM96756	2419630	5305735244812 / M10x30 12.9 DIN 912 hexagon socket head screw		8 / EACH/N UMBER	CLASSIC V					TECHNICAL SPECIFICATION - M10X30 12.9 DIN 912 HEXAGON SOCKET HEAD SCREW GENERAL SPECIFICATION - M10X30 12.9 DIN 912 HEXAGON SOCKET HEAD SCREW	
8	DNM98920	464-4900/5543548	2950715238328 / TURBO CHARGER GP		1 / EACH/N UMBER	C7-1502-117					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
9	DPC99561	ZEEPER114	8010705332849 / ZEEPER 114 CLEANER		20 / KILOGR AMME	ZEEPER.114					TECHNICAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years GENERAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
10	DNM96771	2866640	5305735244965 / clamp screw		4 / EACH/N UMBER	CLASSIC V					TECHNICAL SPECIFICATION - grade MS 8.8 dia 8 inch GENERAL SPECIFICATION - grade MS 8.8 dia 8 inch	
11	DNM967	7653768	536573524570		2 /	CLASSIC					TECHNICAL SPECIFICATION - M S	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	63		1 / suction ring		EACH/N UMBER	V					GRADE 8.8 GENERAL SPECIFICATION - M S GRADE 8.8	
12	DNM989 21	9V-3811	530501297176 3 / BOLT 12 POINT HEAD (1/2-20X2.25- IN)		4 / EACH/N UMBER	C7-1502- 117					TECHNICAL SPECIFICATION - Thread of the Hole: 20 Grade: 11.9 Type: 12 Point Head Bolt Screw Length (In): 2 1/4 Material: STEEL Screw Type: 12 Point Material Description: Head Mal 1 2 Thread: Fine Thread Size (in - TPI) (in): 112- 20 Head Height (In): 0.5 Flange Diameter (In): 0.75 GENERAL SPECIFICATION - Thread of the Hole: 20 Grade: 11.9 Type: 12 Point Head Bolt Screw Length (In): 2 1/4 Material: STEEL Screw Type: 12 Point Material Description: Head Mal 1 2 Thread: Fine Thread Size (in - TPI) (in): 112-20 Head Height (In): 0.5 Flange Diameter (In): 0.75	
13	DPC997 07	407A	683079529301 8 / REFRIGERAN T GAS 407A (in non returnable cylinder of 40 kg net)		40 / KILOGR AMME	407A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
14	DNM967 62	2352085	530673524477 1 / M8x30 8.8 zn DIN 933 hexagon bolt		8 / EACH/N UMBER	CLASSIC V					TECHNICAL SPECIFICATION - M8X30 8.8ZN DIN 933 HEXAGON BOLT GENERAL SPECIFICATION - M8X30 8.8ZN DIN 933 HEXAGON BOLT	
15	DPC995 71	RELAY+on	801070533282 3 / VIRKON SURFACE DISINFECTAN T POWDER		5 / LITER	ZEEPER- 114					TECHNICAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal GENERAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal	
16	DNM967 54	2417090	530573524481 0 / M8x25 8.8 zn DIN 912 hexagon socket head screw		8 / EACH/N UMBER	CLASSIC V					TECHNICAL SPECIFICATION - M8X25 8.8ZN DIN 912 HEXAGON SOCKET HEAD SCREW GENERAL SPECIFICATION - M8X25 8.8ZN DIN 912 HEXAGON SOCKET HEAD SCREW	
17	DPC995 62	A020EEV2	801070533282 5 / HIGHLY		5 / LITER	HIGHLY PERFUM					TECHNICAL SPECIFICATION - PRODUCT INFORMATION:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PERFUMED BACTERICIDAL WASHROOM CLEANER.			ED					<p>APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.</p> <p><u>GENERAL SPECIFICATION - PRODUCT INFORMATION:</u> APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.</p>	
18	DNM96757	2426581	530573524481 7 / M20x60 12.9 DIN 912 hexagon socket head screw		8 / EACH/NUMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
19	DNM967 65	2901630	531073524499 9 / 22,0x68x5 washer		8 / EACH/N UMBER	CLASSIC V					TECHNICAL SPECIFICATION - 22,0 X68X5 WASHER MS GRADE 8.8 GENERAL SPECIFICATION - 22,0 X68X5 WASHER MS GRADE 8.8	
20	DPC995 60	PINAX	801070533282 4 / CLEANER ZEEPER liquid PINAX		30 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. GENERAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
21	DPC995 25	PINAX	801070533282 4 / CLEANER ZEEPER liquid PINAX		1000 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. GENERAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
22	DNM96752	2358360	530673524480 3 / M20x50 10.9 DIN 933 hexagon bolt		8 / EACH/N UMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION -</u> M20X50 10.9 DIN 933 HEXAGON BOLT <u>GENERAL SPECIFICATION -</u> M20X50 10.9 DIN 933 HEXAGON BOLT	
23	DNM96770	2915241	531073524505 1 / M10 DIN 6340 washer, 10.5 x 28 x 4din 6340 zn washer		8 / EACH/N UMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION -</u> M10 DIN 6340 WASHER,10.5 X 28x4 DIN <u>GENERAL SPECIFICATION -</u> M10 DIN 6340 WASHER,10.5 X 28x4 DIN	
24	DNM96764	7654121	533173524572 6 / 180x3 90sh o-ring		8 / EACH/N UMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION -</u> 180X3 90SH O-RING SHB 90 <u>GENERAL SPECIFICATION -</u> 180X3 90SH O-RING SHB 90	
25	DNM96758	2451160	531073524483 4 / M20 washer		8 / EACH/N UMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION -</u> M20 WASHER <u>GENERAL</u> <u>SPECIFICATION - M20 WASHER</u>	
26	DNM96755	2354043	530573524478 2 / m12x 25 8.8 zn screw		8 / EACH/N UMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION -</u> M12X 25 8.8ZN SCREW <u>GENERAL</u> <u>SPECIFICATION - M12X 25 8.8ZN</u> SCREW	
27	DNM96760	2451118	531073524483 2 / M12 zn DIN 125 washer		8 / EACH/N UMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION -</u> M12 ZN DIN 125 WASHER <u>GENERAL</u> <u>SPECIFICATION - M12 ZN DIN 125</u> WASHER	
28	DNM73043	4327370 / fs36260	294079528080 4 / fuel water separator		1 / EACH/N UMBER	qs213-g5					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
29	DNM96753	2410939	530573524480 9 / M10x25 DIN 7991 hexagon socket head screw		8 / EACH/N UMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION -</u> M10X25 DIN 7991 HEXAGON SOCKET HEAD SCREW <u>GENERAL</u> <u>SPECIFICATION - M10X25 DIN</u> 7991 HEXAGON SOCKET HEAD SCREW	
30	DNM96766	2358051	530573524480		8 / EACH/N	CLASSIC V WMAD					<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			1 / m20x 60 8.8 zn di screw		UMBER						M20X 60 8.8ZN DI SCREW MS GRADE 8.8 <u>GENERAL SPECIFICATION - M20X 60 8.8ZN DI SCREW MS GRADE 8.8</u>	
31	DNM967 68	2430806	531073524482 3 / M20 8zn DIN 934 nut		8 / EACH/N UMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION - M20 8ZN DIN 934 NUT</u> <u>GENERAL SPECIFICATION - M20 8ZN DIN 934 NUT</u>	
32	DNM967 67	2917077	533173524515 0 / , 3,55x529 nbr 90 sh o-ring		8 / EACH/N UMBER	CLASSIC V					<u>TECHNICAL SPECIFICATION - 3,55 X529 NBR 90 SH O-RING SHB 90</u> <u>GENERAL SPECIFICATION - 3,55X529 NBR 90 SH O-RING SHB 90</u>	
33	DPC993 47	N/A	793070518128 0 / DETERGENT WATER SOLUBLE	GENERAL ITEM	30 / LITER			LOCKEL MARKET		GENERA L ITEM	<u>TECHNICAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE</u> <u>GENERAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE</u>	
34	DPC993 41	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25- 200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	17 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.		ORIGNAL COLOR CHIPS,A DIVISION	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
35	DPC995 27	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25- 200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	100 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.		ORIGNAL COLOR CHIPS,A DIVISION	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
36	DNQ991 44	17- 2879003	635073522605 7 / SMOKE & HEAT DETECTOR FOR ALARM SYSTEM	MAB	1 / EACH/N UMBER	TSD-1	NIL	SATEL sp. z o.o. ul. Schuberta 79 80-172 Gdansk POLSKA Tel : 58 320 94 00 info@satel.pl / www.satel.pl		SATEL, POLAND	<u>TECHNICAL SPECIFICATION - 9.5 V -30V DC Class A1& A1R</u> <u>GENERAL SPECIFICATION - 9.5V -30V DC Class A1& A1R</u>	
37	DNQ990 10	464748 ABN.	473001435510 6 / REPAIR KIT,PIPE, EMERGENCY DAMAGE	EMERGENCY CONTROL , PIPE REPAIR KIT.	2 / KIT			OEM: c IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110		INDUMAR PRODUC TS INC DBA STOP ..	<u>TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			CONTROL					HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM			STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM GENERAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	
38	DPC99539	WD40	803001418900 8 / WD40 (PACKING 440ML SPRAY BOTTLE)	0	21 / EACH/NUMBER	0	0	1061 CUDAHY PL, SAN DIEGO, CA SAN DIEGO CA	WD-40 COMPANY Y		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
39	DPK99546	Shell Gadus S2 V100 3/ Shell Alvania R3	9150PK507811 7 / SHELL GADUS S2 V100 3/ SHELL GREASE Alvania R-3 (Old Name) (18 KG PKING)	50	2 / KILOGRAMME			M/S SHELL PAKISTAN Ltd	M/S SHELL PAKISTAN Ltd		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY:IMRAN OIL TRADERS 19-20,FATIMA GIRLS COLLEGE,NISHTAR ROAD, GARDEN WEST ,KARACHI. GENERAL SPECIFICATION - SOURCE OF AVAILABILITY:IMRAN OIL TRADERS 19-20,FATIMA GIRLS COLLEGE,NISHTAR ROAD, GARDEN WEST ,KARACHI.	
40	DNM99323	100-3751	530601471576 2 / BOLT (M8X1.25X65-MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	2 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		TECHNICAL SPECIFICATION - notes: thread length (mm) 43 hole thread tip: 1.25 material description: dimension, tolerance, material and quality requirements for hex flange bolts. metric-iso 4162 hexagon bolts with flange. inch-asma b18.2.1 flanged hex head bolts screw length (in): 2.56 (65mm) screw type: hex flange head coating : galvanized zinc (saline mist 96 h) cable length (in): 1.69 thread: coarse thread size (in-tpi) (in): m8-1.25 GENERAL SPECIFICATION - notes: thread length (mm) 43 hole thread tip: 1.25 material description: dimension, tolerance, material and quality requirements for hex flange bolts.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											metric-iso 4162 hexagon bolts with flange. inch-asme b18.2.1 flanged hex head bolts screw length (in): 2.56 (65mm) screw type: hex flange head coating : galvanized zinc (saline mist 96 h) cable length (in): 1.69 thread: coarse thread size (in-tpi) (in): m8-1.25	
41	DNM989 22	451-0548	530671522852 1 / BOLT	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/N UMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA		ALLIED CAT	TECHNICAL SPECIFICATION - thread size: m14 material: steel zinc plated inner diameter: 9 mm (0.35 in) cross hole diameter: 5.5mm (0.21 in) screw type: banjo screw hex size (in): 0.75 material; description: steel GENERAL SPECIFICATION - thread size: m14 material: steel zinc plated inner diameter: 9 mm (0.35 in) cross hole diameter: 5.5mm (0.21 in) screw type: banjo screw hex size (in): 0.75 material; description: steel	
42	DNM888 68	162-2177	472001321828 2 / HOSE	CATTER PILLER GENSET 3512B USA	8 / EACH/N UMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA		CATTER PILLER USA	TECHNICAL SPECIFICATION - hose assembly (non metallic /reinforced) cat 3512b diesel engine (fluid routing) reinforced rubber convet pressurized fluid. reinforced engine hose rubber composite hose with braids GENERAL SPECIFICATION - hose assembly (non metallic /reinforced) cat 3512b diesel engine (fluid routing) reinforced rubber convet pressurized fluid. reinforced engine hose rubber composite hose with braids	
43	DNM922 42	3886126	156073517562 0 / FITTING	IPS 500	1 / EACH/N UMBER	IPS 500	IPS- F3940012 979	VOLVO PENTADEN		VPL SWEDEN VOLVO PENTA	TECHNICAL SPECIFICATION - VOLVO PENTA ips marine propulsion associated: lock nut, prop nut, lock plate, frease, cones marine grade alloy metals GENERAL SPECIFICATION - VOLVO PENTA ips marine propulsion associated: lock nut, prop nut, lock plate, frease, cones marine grade alloy metals	
44	SPC9931 1	7930-00- 965-4868	793000965486 8 / Soap laundry Alkaline	NIL	100 / BOX	NA	NA	UNIVAL CORP, BOYNTON BEACH, USA Postal Code: 33437-1814		UNIVAL CORP, USA	TECHNICAL SPECIFICATION - PMS Item GENERAL SPECIFICATION - PMS Item	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			bar									
45	DNM993 21	88101	531575518065 8 / QUICK RELEASE MECHANISM / KONG (QRM/QRK)	QRK	2 / EACH/N UMBER			KONG SPA 1-23804 MONTE MARENZZP (LC) - ITALY	ITALY		<u>TECHNICAL SPECIFICATION - MATERIAL: A WEAR RESISTANT STAINLESS STEEL. GENERAL SPECIFICATION - MATERIAL: A WEAR RESISTANT IN STAINLESS STEEL.</u>	
46	DPC996 73	CC 2748M (5 liters packing) CC2750M (20 liters packing)	681071522985 7 / ES Complete EG premix coolant	MAIN ENGINE	300 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS / FLEETGUARD		<u>TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol</u>	
47	DNM969 74	3918521	473001368939 8 / CLAMP HOSE	DIESEL GENERATOR CUMMINS	2 / EACH/N UMBER	NO DATA AVAILAB LE		US	M/S CUMMINS INC 500 JAKSON ST COLUMBUS IN USA 47201-6258 TEL:377-3920 FAX 812-377-1715 E. MAIL: STEVE.AHEWITT@COMMINS.COM		<u>TECHNICAL SPECIFICATION - CLAMP HOSE (band type) adjustable band type 59-83 mm diameter clamp 80g approx width 12-16 mm screw tightening (worm gear style) / band screw zinc plated or corrosion resistant steel GENERAL SPECIFICATION - CLAMP HOSE (band type) adjustable band type 59-83 mm diameter clamp 80g approx width 12-16 mm screw tightening (worm gear style) / band screw zinc plated or corrosion resistant steel</u>	
48	DNQ953 10	2352169	668599300963 2 / PRESSURE GUAGE	FIRE FIGHTING EQUIPMENT	50 / EACH/N UMBER	NO DATA AVAILAB LE		UK	UK ENGLAN D		<u>TECHNICAL SPECIFICATION - bourdon tube pressure guage Dial with pointer back or bottom mount oftem 0-60 bar (0-870 psi) media compatibility: air water hydraulic fluid non corrosive gases /liquidGENERAL SPECIFICATION - bourdon tube pressure guage Dial with pointer back or bottom mount oftem 0-60 bar (0-870 psi) media compatibility: air water hydraulic fluid</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											non corrosive gases /liquid	
49	DNQ99494	8930	9390999808079 / TAPE LUMINOUS / LUMINOUS SHEETING ROLL 150MM WIDE 45M LONG FLAME RETARDANT	SMOKE CURTAIN(FF)	1 / EACH/NUMBER	NO DATA AVAILAB LE		UK			TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
50	DNQ95308	0244-244005	5340995251965 / INDICATOR TEST PLUG TYPE B	FIRE FIGHTING EQUIPMENT	4 / EACH/NUMBER	NO DATA AVAILAB LE		UK			TECHNICAL SPECIFICATION - threaded test /indicator pug mpt or bsp tapered hex or square drive steel or brass Elastomer or tapered metal lock feature type b GENERAL SPECIFICATION - threaded test /indicator pug mpt or bsp tapered hex or square drive steel or brass Elastomer or tapered metal lock feature type b	
51	DNQ99011	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILAB LE		UK			TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCR GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCR	
52	DNM96298	3921691	533001523012	CUMMINS 200 KVA DG	1 / EACH/NUMBER	6CTA8.3	78515443	Cummins Americas Inc, 3350 SW 148 AVENUE,	USA		TECHNICAL SPECIFICATION - FSC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			1 / Gasket, Exh Out Connection		UMBER			SUITE 205 Miramar, FL, 33027 USA Tell (1-954) 431-5511 Fax (1-954)433-5797			5330 PACKING & GASKET METERIALS TEMPERATURE RANGE TPTO 900c THICKNESS 1.0-2.5 MM OUTER DIAMETER: 70-120 MM GENERAL SPECIFICATION - FSC 5330 PACKING & GASKET METERIALS TEMPERATURE RANGE TPTO 900c THICKNESS 1.0-2.5 MM OUTER DIAMETER: 70-120 MM	
53	DNM96500	3802202	2910014635200 / INJECTOR ASSEMBLY,F	CUMMINS 200 KVA DG	6 / EACH/NUMBER	6CTA8.3	78515443	Cummins Americas Inc, 3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Tell (1-954) 431-5511 Fax (1-954)433-5797	USA		TECHNICAL SPECIFICATION - fuel injector assembly (injector body, nozzle & internal components) INJECTION TYPE: MECHANICAL INJECTOR FUEL TYPE: DIESEL HIGH PRESSURE ATOMIZATION MOUNTING THREADED AND SEALED <u>GENERAL SPECIFICATION - fuel injector assembly (injector body, nozzle & internal components) INJECTION TYPE: MECHANICAL INJECTOR FUEL TYPE: DIESEL HIGH PRESSURE ATOMIZATION MOUNTING THREADED AND SEALED</u>	
54	DNM96297	3837348	2940015230008 / Cleaner, Air	CUMMINS 200 KVA DG	1 / EACH/NUMBER	6CTA8.3	78515443	Cummins Americas Inc, 3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Tell (1-954) 431-5511 Fax (1-954)433-5797	USA		TECHNICAL SPECIFICATION - FILTER TYPE HIGH EFFECIENCY OLEATED MEDIA HOUSING STAMPED STEEL OR MOLDED POLYMER PLEATED CELLULOSE AND SYNTHETIC FIBERS END CAP METAL OR PLASTIC SEALS ELASTOMER GASKET GASTENERS CLAMPS SCREWS <u>GENERAL SPECIFICATION - FILTER TYPE HIGH EFFECIENCY OLEATED MEDIA HOUSING STAMPED STEEL OR MOLDED POLYMER PLEATED CELLULOSE AND SYNTHETIC FIBERS END CAP METAL OR PLASTIC SEALS ELASTOMER GASKET GASTENERS CLAMPS SCREWS</u>	
55	DNH991	NIL	412073513911	AIR	2 /	NO DATA		OC	THILAND		TECHNICAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	19		7 / AIR CONDITIONER SPLIT 1.5 TONS	CONDITIONING	EACH/NUMBER	AVAILABLE					GENERAL SPECIFICATION - -	
56	DNM97783	5744543/416-8319	2815015431148 / PUSH ROD,ENGINE POPPET VALVE	CATERPILLAR GENSET D3512B (YBB1) USA	64 / EACH/NUMBER	D3512B	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - CAT 3500 SERIES (3512B, 3516) SOLID CYLINDRICAL ROD (STEEL) LENGTH: 260-300 MM (10.2-11.8) (3500 SERIES) OUTER DIAMETER: 15-20 MM (ENGINE VALVE SIZE) HARDENED ALLOY STEEL BODY BALL/CUP OR FALT CONTACT ENDS MACHINED LIFTER & ROCKER ARM GENERAL SPECIFICATION - CAT 3500 SERIES (3512B, 3516) SOLID CYLINDRICAL ROD (STEEL) LENGTH: 260-300 MM (10.2-11.8) (3500 SERIES) OUTER DIAMETER: 15-20 MM (ENGINE VALVE SIZE) HARDENED ALLOY STEEL BODY BALL/CUP OR FALT CONTACT ENDS MACHINED LIFTER & ROCKER ARM	
57	DNM92371	EOCR-SS-60NW7PQ	5945705216490 / ELECTRONIC OVERLOAD RELAY (EOCR)	HVAC AHU 24 TON CWCU	2 / EACH/NUMBER	EOCR-SS-60NW7PQ	NIL	CHINA / KOREA/LOCAL MARKET COOL POINT LAHORE LOCAL MARKET	CHINA / KOREA		TECHNICAL SPECIFICATION - ELECTRONIC OVER LOAD CURRENT RELAY, 5-70 AMPER DIGITA ELECTRONIC OVERLOAD RELAY MODULES ADJUSTABLE RANGE AC THREE-PHASE 50-60 HZ LED 7-SEGMENT DISPLAY GENERAL SPECIFICATION - ELECTRONIC OVER LOAD CURRENT RELAY, 5-70 AMPER DIGITA ELECTRONIC OVERLOAD RELAY MODULES ADJUSTABLE RANGE AC THREE-PHASE 50-60 HZ LED 7-SEGMENT DISPLAY	
58	DNM97802	1H-9696	5331715202150 / O RING	CATERPILLAR GENSET D3512B (YBB1) USA	1 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - 0 ring seal nitrile rubber (nbr) 75a shore engine sealing (fuel, hydraulic, general & machinery) 44.04 mm (inside) approx 3.53 mm (cross section) GENERAL SPECIFICATION - 0 ring seal nitrile rubber (nbr) 75a	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
59	DNH991 22	HRE-ARP-1217-1	732070521036 7 / FULL AUTOMATED ROTI PLANT COMPLETE BODY	COMPLETE HRE-APR-1217 PAKISTAN	1 / EACH/N UMBER	HRE- APR- 1217/A15 00/A3000	NA	SMALL INDUSTRIAL ESTATE 3, GUJRANWALA MIR MUZAFFAR ROAD GUJRANWALA	HR ENTERP RISES		shore engine sealing (fuel, hydraulic, general & machinery) 44.04 mm (inside) approx 3.53 mm (cross section) TECHNICAL SPECIFICATION - model no a1500 & a3000 mechanical data a. electrical heater b. work space required 40" x 13" room with well ventilation c. length 12 feet width 3.5 to 4.5 feet height 4.5 feet (app) d. ALL MATERIAL STRUCTURE IN MS PIPE. E. OUTER CASSING 22 SWG G I SHEET F. REVOLVING WHEELS. ELECTRICAL DATA A. GEAR MOTOR 1.5 KW B. CONTROL PANNEL C. AUTO VARIABLE PANEL D. 06 NOS OF CONTRACTORS E. 02 NOS OF HEAT CONTROLLER F. HEATER AS PER EXISTING G. 02 NOS THERMOC COUPLES H. MAIN POWER CABLE 05 FEET J. ALL HEATER PROTECTIVE TO ANY HAZARDS. MATERIAL grade: SS 304 TYPE CAPICITY: 3000 CHAPATI PER HOUR GENERAL SPECIFICATION - model no a1500 & a3000 mechanical data a. electrical heater b. work space required 40" x 13" room with well ventilation c. length 12 feet width 3.5 to 4.5 feet height 4.5 feet (app) d. ALL MATERIAL STRUCTURE IN MS PIPE. E. OUTER CASSING 22 SWG G I SHEET F. REVOLVING WHEELS. ELECTRICAL DATA A. GEAR MOTOR 1.5 KW B. CONTROL PANNEL C. AUTO VARIABLE PANEL D. 06 NOS OF CONTRACTORS E. 02 NOS OF HEAT CONTROLLER F. HEATER AS PER EXISTING G. 02 NOS THERMOC COUPLES H. MAIN POWER CABLE 05 FEET J. ALL HEATER PROTECTIVE TO ANY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											HAZARDS. MATERIAL grade: SS 304 TYPE CAPICITY: 3000 CHAPATI PER HOUR	
60	DPC994 98	NO DATA AVAILABL E	047350224769 5 / REFINED SODIUM BICARBONAT E (OEM = ICI PAKISTAN) Packing = 25kg Bag		8 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DPC996 80		047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	831 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
62	DPC995 34		047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	676 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
63	DPC996 64	0461-3951, CS2879	046159224056 2 / WATER INDICATING PASTE FOR FUEL (03 OZ TUBE)		55 / TUBE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DPC995 32	NO DATA AVAILABL E	047450000702 8 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		72 / BAG						TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Cao+Mgo: LESS THEN 2.0	
65	DPC99536	NO DATA AVAILAB L E	047450474009 5 / MOLASSES (PACKING 25 KG CAN)	PORT MAIN FIRE PUMP	400 / KILOGR AMME						<p>TECHNICAL SPECIFICATION - MOLASSES COMPOSITION: BRIX SPINDLE: 86.0LBS WEIGHT/GALLON: 11.8-12.0 LBS NITROGEN: 1.01%CRUDE PROTEIN: 6.30% TOTAL SUGARS: 48.3% DENSITY: 11.8% DRY MATTER: 76.5% MOISTURE: 23.5% ASH; 16.0% ORGANIC MATTER: 62.5% REDUCING SUBSTANCE AS DEXTROSE: 11.5% SUCROSE: 35.9% FRUCTOSE:5.6% GLUCOSE: 2.6% PH:4.9-5.</p> <p>GENERAL SPECIFICATION - MOLASSES COMPOSITION: BRIX SPINDLE: 86.0LBS WEIGHT/GALLON: 11.8-12.0 LBS NITROGEN: 1.01%CRUDE PROTEIN: 6.30% TOTAL SUGARS: 48.3% DENSITY: 11.8% DRY MATTER: 76.5% MOISTURE: 23.5% ASH; 16.0% ORGANIC MATTER: 62.5% REDUCING SUBSTANCE AS DEXTROSE: 11.5% SUCROSE: 35.9% FRUCTOSE:5.6% GLUCOSE: 2.6% PH:4.9-5.</p>	
66	DPC99526	G-1200	047550220561 3 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		20 / TUBE						<p>TECHNICAL SPECIFICATION - NO DATA AVAILAB L E</p> <p>GENERAL SPECIFICATION - NO DATA AVAILAB L E</p>	
67	DPC99339	G-1200	047550220561 3 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		24 / TUBE						<p>TECHNICAL SPECIFICATION - NO DATA AVAILAB L E</p> <p>GENERAL SPECIFICATION - NO DATA AVAILAB L E</p>	
68	DPC99497	NO DATA AVAILAB L E	047350000537 0 / SILICA GEL (grain size 2-3mm)	Transformers Humidity Control	135 / KILOGR AMME						<p>TECHNICAL SPECIFICATION - Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											up. <u>GENERAL SPECIFICATION - Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.</u>	
69	DPC993 25	NO DATA AVAILABL E	044250442003 9 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	198 / LITER						<u>TECHNICAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN</u>	
70	DPC996 68	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1390 / LITER						<u>TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABELGENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u>	
71	DPC994 92	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		2100 / LITER						<u>TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABELGENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u>	
72	DNQ993 81	NO DATA AVAILABL E	034059923624 3 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
73	DPC994 20	NO DATA AVAILABL E	044350443000 5 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		15 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Check at 110PSI, Valve Tightness at 120~150 Torque. GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120-150 Torque.	
74	DPC993 60	NO DATA AVAILABL E	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		36 / KILOGR AMME						<p>TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Di Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas</p> <p>GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Di Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas</p>	
75	DPC994 82	SUPERSE DED BY DGS 1035	044250220202 0 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	464 / LITER						<p>TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed</p> <p>GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed</p>	
76	DPC996 59	SPEC,DEF 1052 COLOURS TO BS 381C	044250910703 5 / PAINT FNISHING GLOSS (SIGNAL RED)		755 / KILOGR AMME						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</p> <p>GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NO537). NS/C01/GEN/5 66DT210902									
77	DNQ993 85	DEVELOP ED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H6O 6.5MM DIA		8 / EACH/N UMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
78	DPC995 00	-	047350473004 9 / SILICA GEL (Packing = 5 KG Bag)		10 / KILOGR AMME						TECHNICAL SPECIFICATION - A. SILICA GEL (DESICCANT) IN GRAIN FORM FOR TRANSFORMERS HUMIDITY CONTROL. B. GRAIN SIZE 2.0 – 3.0 MM. C. CAPABLE TO ABSORB MOISTURE AT ROOM TEMPERATURE AND RELEASE MOISTURE WHEN HEATED UP. D. SMALL POROUS, WHITE STANDARD.GENERAL SPECIFICATION - A. SILICA GEL (DESICCANT) IN GRAIN FORM FOR TRANSFORMERS HUMIDITY CONTROL. B. GRAIN SIZE 2.0 – 3.0 MM. C. CAPABLE TO ABSORB MOISTURE AT ROOM TEMPERATURE AND RELEASE MOISTURE WHEN HEATED UP. D. SMALL POROUS, WHITE STANDARD.	
79	DPC993 33	-	047350473004 9 / SILICA GEL (Packing = 5 KG Bag)		40 / KILOGR AMME						TECHNICAL SPECIFICATION - A. SILICA GEL (DESICCANT) IN GRAIN FORM FOR TRANSFORMERS HUMIDITY CONTROL. B. GRAIN SIZE 2.0 – 3.0 MM. C. CAPABLE TO ABSORB MOISTURE AT ROOM TEMPERATURE AND RELEASE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MOISTURE WHEN HEATED UP. D. SMALL POROUS, WHITE STANDARD. <u>GENERAL SPECIFICATION - A. SILICA GEL (DESICCANT) IN GRAIN FORM FOR TRANSFORMERS HUMIDITY CONTROL. B. GRAIN SIZE 2.0 – 3.0 MM. C. CAPABLE TO ABSORB MOISTURE AT ROOM TEMPERATURE AND RELEASE MOISTURE WHEN HEATED UP. D. SMALL POROUS, WHITE STANDARD.</u>	
80	DPK99600	LG 280	047450910050 2 / GREASE LG-280 (XG-286)	FIVE /G SERVICE PUMP NO.3	6 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - SUPERCEDED VIDE</u> CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128 <u>GENERAL SPECIFICATION - SUPERCEDED VIDE</u> CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128	
81	DPK99419	LG 280	047450910050 2 / GREASE LG-280 (XG-286)	FIVE /G SERVICE PUMP NO.3	115 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - SUPERCEDED VIDE</u> CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128 <u>GENERAL SPECIFICATION - SUPERCEDED VIDE</u> CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128	
82	DNM84746	S551A	294079507453 2 / AIR CLENER ELEMENT (AIR INTAKE SYS) DORMAN D/E 6SETCR	DORMAN DIESEL ENGINE (ENGLAND)	2 / EACH/NUMBER	6ASETCR					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
83	DNQ99566	PN SPEC-11-004	421099129513 4 / FIRE EXT STORED PRESS D/CHEMICAL POWDER 10KG DEEP	AS PER DRAWING TD-1480/2001 DT 10.2.2001	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DRAWN BODY									
84	DNQ99569	72720 (SPEC: DEFSTAN 42-2/2)	4210991295842 / FIRE EXTINGUISHER 9 LITRE WATER & GAS	FOR GENERAL USE	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DNQ95304	COLUMBUS 300/306	4240997956910 / FABRIC, FLAME RETARD.	SMOKE CURTAIN USE	100 / METER						TECHNICAL SPECIFICATION - 1.50 MM X 50M = 75SQM PER ROLL @ 555G/SQM SILVR GREY SILICONE COATING TO BOTH SIDES GENERAL SPECIFICATION - 1.50 MM X 50M = 75SQM PER ROLL @ 555G/SQM SILVR GREY SILICONE COATING TO BOTH SIDES	
86	DNH99329	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
87	DNH99327	NO DATA AVAILABLE	4110731001910 / WATER COOLER 40/45 LITER ELECT220 AKS 40PW/FRONT STEELBODY	WATER COOLER	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
88	DNH99326		4110735060828 / REFRIGERATOR 18-CUFT DOUBLE DOOR PEL/DAWLANCE		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
89	DNQ99324		4720795087429 / FLEXIBLE HOSE REINFORCED WITH WIRE STRANDS LG-150.FEET	AQUA HYDRAULICS WATER JET MACHINE (ENG)	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Reinforced with wire strands Pressure upto 100 Bar MAKE: UK GENERAL SPECIFICATION - Reinforced with wire strands Pressure upto 100 Bar MAKE: UK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			I/D1/2"									
90	SPC99313	ZSG-12/99, ZSA-12/99	5330995314222 / JOINTING COMPOUND, S/RUBER & ASBESTOS A/GRADE D3-SV 3	OEM; ZAHABIYA CHEMICAL INDUSTRIES KARACHI	200 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
91	DNQ98544	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DPC99531	NO DATA AVAILABLE	0474500000062 / POWDER CHALK, COMP CALCIUM CARBONATE 98% PURITY		30 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
93	DPC99328		0473500000068 / GUM SHELLAC (ORANGE) Packing 20 TO 25 KG SACK		22 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. USED WITH VARNISH / POLISH FOR SURFACE FINISHING OF WOOD PRODUCTS 2. STANDARD TRADE PRODUCT. 3. ADVANCE SAMPLE TO BE APPROVED BY END USER THROUGH CINS PRIOR BULK SUPPLY. GENERAL SPECIFICATION - 1. USED WITH VARNISH / POLISH FOR SURFACE FINISHING OF WOOD PRODUCTS 2. STANDARD TRADE PRODUCT. 3. ADVANCE SAMPLE TO BE APPROVED BY END USER THROUGH CINS PRIOR BULK SUPPLY.	
94	DNQ99568	NO DATA AVAILABLE	0091599107983 / FIRE BUCKET	FIRE FIGHTING PURPOSE	18 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. 09 liters water filled standard. b. made of galvanized steel of at least no.22 uss gauge c. rounded bottom welded in place or otherwise suitably reinforced. d. furnished with stamped ears welded in place e. strong wire bail and losse fitting metal covers to exclude debris and retard evaporation. f. should be painted	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>bright red with the word "fire" stenciled in large letter on their outside with contrasting colored paints. g. bucket tanks should be coated with red lead. <u>GENERAL SPECIFICATION</u> - a. 09 liters water filled standard. b. made of galvanized steel of at least no.22 uss gauge c. rounded bottom welded in place or otherwise suitably reinforced. d. furnished with stamped ears welded in place e. strong wire bail and losse fitting metal covers to exclude debris and retard evaporation. f. should be painted bright red with the word "fire" stenciled in large letter on their outside with contrasting colored paints. g. bucket tanks should be coated with red lead.</p>	
95	DPC996 66	NO DATA AVAILABL E	685078503110 4 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANE R(UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMEN T FOR PNS NASR	30 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B- 8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. <u>GENERAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B- 8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.</p>	
96	DPC996 63	ARCOBUR AG-P21	681070508041 8 / SCALE REMOVER packing 25 ltr	A/C PLANT CHILLER CONDENSER HEAT	25 / LITER						<p><u>TECHNICAL SPECIFICATION -</u> DETAILED SPECIFICATION / TECHNICAL DATA: greenish blue granular powder; converts to gold</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
				EXCHANG							when solution is made. colour variations of ARCOburag-p21 has no effect on performance odour: irritating. solubility in water: 10% at 75 degree f b. Brands: ARCOCHEMICALS c. OEM: M/S Arcochemicals Suite 103 Fortune Centre, 45A Block 6 P.E.C.H.S Sharah-e Faisal Karachi- 75400. Ph : 3438992623-25 <u>GENERAL SPECIFICATION - DETAILED SPECIFICATION / TECHNICAL DATA</u> : greenish blue granular powder; converts to gold when solution is made. colour variations of ARCOburag-p21 has no effect on performance odour: irritating. solubility in water: 10% at 75 degree f b. Brands: ARCOCHEMICALS c. OEM: M/S Arcochemicals Suite 103 Fortune Centre, 45A Block 6 P.E.C. H.S Sharah-e Faisal Karachi- 75400. Ph : 3438992623-25	
97	DPC978 28	N/A	793070518128 0 / DETERGENT WATER SOLUBLE	GENERAL ITEM	30 / LITER			LOCKEL MARKET		GENERA L ITEM	<u>TECHNICAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE</u> <u>GENERAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE</u>	
98	DNM623 19	0402-0968-04	289571526752 2 / ISOLATOR, VIBRATION		4 / EACH/N UMBER	C22 D5					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
99	DNQ973 47	464748 ABN.	473001435510 6 / REPAIR KIT,PIPE, EMERGENCY DAMAGE CONTROL	EMERGENCY CONTROL , PIPE REPAIR KIT.	3 / KIT			OEM: c IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.		INDUMAR PRODUC TS INC DBA STOP ..	<u>TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM</u> <u>GENERAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								COM			713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	
100	DPC997 49	WD40	803001418900 8 / WD40 (PACKING 440ML SPRAY BOTTLE)	0	1 / EACH/N UMBER	0	0	1061 CUDAHY PL, SAN DIEGO, CA SAN DIEGO CA	WD-40 COMPAN Y		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
101	DNQ949 87	Smartigt/G/ Smartloop/ 2080G	635075516389 6 / LOOP FIRE ALARM CONTROL PANEL WITH KEY,PAD DISPLAY	FIRE ALARM SYS	1 / EACH/N UMBER	Smartigt/ G		OEM:INIM ELECTRONICS S R L VIA FOSSO ANTICO CENTOBUCHI 63076 MONTEPRANDONE (AP) ITALY.	OEM:INIM ELECTR ONICS S R L VIA FOSSO ANTICO		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
102	DNM989 28	067-6366	531001524029 7 / WASHER	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/N UMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - OEM: CATERPILLAR GENERAL SPECIFICATION - OEM: CATERPILLAR</u>	
103	DNM947 01	1088603	533000358269 5 / LINE GP FUEL INJECTION	SSDG	1 / SET	N03306B		CATERPILLAR INC.IDBA CATERPILLAR DIV DEFENSE &FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 309-578-6941 309-578- 3739 HTTP://WWW.CAT. COM	CATERPI LLAR INC.IDBA CATERPI LLAR DIV DEFENS E &FED		<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
104	DPC956 28	CC 2748M (5 liters packing) CC2750M (20 liters packing)	681071522985 7 / ES Complete EG premix coolant	MAIN ENGINE	360 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMIN S/ FLEETGU ARD		<u>TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol</u>	
105	DPC997 88	CC 2748M (5 liters packing) CC2750M	681071522985 7 / ES Complete EG premix coolant	MAIN ENGINE	199 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMIN S/ FLEETGU ARD		<u>TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		(20 liters packing)									SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
106	DPC97160	CC 2748M (5 liters packing) CC2750M (20 liters packing)	681071522985 7 / ES Complete EG premix coolant	MAIN ENGINE	200 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMIN S/ FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
107	DPK95723	FCW NMMA	915076522310 7 / SUZUKI/ADDIN OL MARINE 4 STROKE ENGINE OIL 10W-40	ENGINE OIL SUZUKI	350 / LITER	NA		SUZUKI THAILAND	OBM SUZUKI THAILAN D		TECHNICAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40 CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5 GENERAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40 CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5	
108	DNQ94865	8005L	841501447821 2 / GLOVES, DISPOSABLE	PERSONAL PROTECTIVE EQUIPMENT	15 / EACH/N UMBER	NA	NA	TILLOTSON CORPORATION DBA BEST MANUFACTURING DIVISION 579 EDISON ST MENLO GA 30731-6335 UNITED STATES	TILLOTS ON CORPOR ATION DBA BEST MANUFA CTURING DIVIS		TECHNICAL SPECIFICATION - ADZC ENVIRONMENTAL PROTECTION CHEMICAL RESISTANT AJMX GARMENT SIZE LARGE ASRN HAND FOR WHICH DESIGNED AMBIDEXTROUS HUES COLOR BLUE OVERALL LGTH LENGTH 9.500 INCHES THKS THICKNESS 8.0 MILLIMETERS GENERAL SPECIFICATION - ADZC ENVIRONMENTAL PROTECTION CHEMICAL RESISTANT AJMX GARMENT SIZE LARGE ASRN HAND FOR WHICH DESIGNED AMBIDEXTROUS HUES COLOR BLUE OVERALL LGTH LENGTH 9.500 INCHES THKS THICKNESS 8.0 MILLIMETERS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
109	DNQ94865	8005L	841501447821 2 / GLOVES, DISPOSABLE	PERSONAL PROTECTIVE EQUIPMENT	15 / EACH/N UMBER	NA	NA	TILLOTSON CORPORATION DBA BEST MANUFACTURING DIVISION 579 EDISON ST MENLO GA 30731- 6335 UNITED STATES	TILLOTS ON CORPOR ATION DBA BEST MANUFA CTURING DIVIS		TECHNICAL SPECIFICATION - ADZC ENVIRONMENTAL PROTECTION CHEMICAL RESISTANT AJMX GARMENT SIZE LARGE ASRN HAND FOR WHICH DESIGNED AMBIDEXTROUS HUES COLOR BLUE OVERALL LGTH LENGTH 9.500 INCHES THKS THICKNESS 8.0 MILLIMETERS GENERAL SPECIFICATION - ADZC ENVIRONMENTAL PROTECTION CHEMICAL RESISTANT AJMX GARMENT SIZE LARGE ASRN HAND FOR WHICH DESIGNED AMBIDEXTROUS HUES COLOR BLUE OVERALL LGTH LENGTH 9.500 INCHES THKS THICKNESS 8.0 MILLIMETERS	
110	DPC97820	NO DATA AVAILABL E	047350000537 2 / SILICA GEL		50 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
111	DPK94850	DEFSTAN 91-44/1	047550943132 4 / OIL OM 13 NATO O-134 ALIGHT MINERAL OIL PACKING 25 LTR	FOR USE IN GUN MOUNTING	75 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
112	DPK94900	DEFSTAN 91-44/1	047550943132 4 / OIL OM 13 NATO O-134 ALIGHT MINERAL OIL PACKING 25 LTR	FOR USE IN GUN MOUNTING	125 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
113	DPC97830	BS 3981	047350942925 0 / PIGMENT POWDER BURNT SIENA (Packing 56 LB or 400 Gram) TIGER BRAND	USE DRY INGREDIENTS FOR PAINTS	5 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 3981 BRAND= TIGERGENERAL SPECIFICATION - BS 3981 BRAND= TIGER	
114	DPC97153	NO DATA AVAILABL	047450000702 8 / SAND		40 / BAG						TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	YORKSHIRE FOR STEEL MOULDING (50 KG BAG)								STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 <u>GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0</u>	
115	DPC978 22	NO DATA AVAILABL E	047450474009 5 / MOLASSES (PACKING 25 KG CAN)	PORT MAIN FIRE PUMP	25 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - MOLASSES COMPOSITION: BRIX SPINDLE: 86.0LBS WEIGHT/GALLON: 11.8-12.0 LBS NITROGEN: 1.01%CRUDE PROTEIN: 6.30% TOTAL SUGARS: 48.3% DENSITY: 11.8% DRY MATTER: 76.5% MOISTURE: 23.5% ASH; 16.0% ORGANIC MATTER: 62.5% REDUCING SUBSTANCE AS DEXTROSE: 11.5% SUCROSE: 35.9% FRUCTOSE:5.6% GLUCOSE: 2.6% PH:4.9-5.</u> <u>GENERAL SPECIFICATION - MOLASSES COMPOSITION: BRIX SPINDLE: 86.0LBS WEIGHT/GALLON: 11.8-12.0 LBS NITROGEN: 1.01%CRUDE PROTEIN: 6.30% TOTAL SUGARS: 48.3% DENSITY: 11.8% DRY MATTER: 76.5% MOISTURE: 23.5% ASH; 16.0% ORGANIC MATTER: 62.5% REDUCING SUBSTANCE AS DEXTROSE: 11.5% SUCROSE: 35.9% FRUCTOSE:5.6% GLUCOSE: 2.6% PH:4.9-5.</u>	
116	DPK9850 4	0474-7021 (0475-99- 224-2137)	047450224213 7 / TALLOW WHITE (GREASE) (200 KG DRUM)		50 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
117	DPC968	G-1200	047550220561		12 /						<u>TECHNICAL SPECIFICATION - NO</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	11		3 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		TUBE						DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
118	DPC978 25	G-1200	047550220561 3 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		12 / TUBE						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
119	DPC965 57	G-1200	047550220561 3 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		40 / TUBE						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
120	DPC956 93		044250442005 1 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	220 / LITER						<u>TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg</u> <u>GENERAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg</u>	
121	DPC969 33		044250442005 1 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal	FINISHING INTERIOR	340 / LITER						<u>TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg</u> <u>GENERAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing								- 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
122	DPC969 26	NO DATA AVAILAB L E	044250001064 4 / THINNER FOR VARNISH (Packing C4 liter)		152 / LITER						TECHNICAL SPECIFICATION - DEF STAN 80-38/2 195 1. FLASH POINT: 16°C 2. INGREDIENTS PROPERTIES BY VOLUME: - METHY ISO BUTYL KETONE: 32 ± 3% - ETHYLENE GLYCOL ACETATE: 7 ± 3% - ISO BUYYLE ALCOHAOL : 25 ± 3% OEM M/S FALAH TRADING AGENCY GENERAL SPECIFICATION - DEF STAN 80-38/2 195 1. FLASH POINT: 16°C 2. INGREDIENTS PROPERTIES BY VOLUME: - METHY ISO BUTYL KETONE: 32 ± 3% - ETHYLENE GLYCOL ACETATE: 7 ± 3% - ISO BUYYLE ALCOHAOL : 25 ± 3% OEM M/S FALAH TRADING AGENCY	
123	DPC997 50	S NO 120 SIMILAR	044250442006 3 / PAINT WEATHER WORK(DARK GREY) (NSSD/C01/04 42/GEN/173DT 060393)	WEATHER WORK	700 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABE	
124	DPC955 08		044250442006 4 / PAINT WEATHER WORK (LIGHT GREY)NHQ LTR NS/G/1303/C DT 270199	WEATHER WORK	300 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABE	
125	DPC969		044279942354		228 /						TECHNICAL SPECIFICATION - 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	27		2 / Paint Marking, Stenciling (Signal Red) flash point: 32 degree C (Min) method of application: brushing & stenciling type: Alkyed Packing: 04 liter tin gauge of tin 26 to 28 SWG		LITER						DEFSTAN 80-68/4 2. NS/P/012 OF 2013 (REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996 <u>GENERAL SPECIFICATION - 1. DEFSTAN 80-68/4 2. NS/P/012 OF 2013 (REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996</u>	
126	DPC969 39		044250942937 4 / VARNISH MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	USE ONWOOD UNDER CONDITIONS OF MARINE EX	340 / LITER						<u>TECHNICAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED</u> <u>GENERAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED</u>	
127	DPC954 96		044250442004 1 / PAINT ENAMEL (WHITE), Brushing, Flash Point 32C(Min), ALKYED Type (04 LTR TIN)	3 INCH ROCK LAUNCH	200 / LITER						<u>TECHNICAL SPECIFICATION - DEFSTAN 80-59/1 OF 1976 Stage inspection prescribed 04 ltr tin Flash point: 32 C Type: ALKYED</u> <u>GENERAL SPECIFICATION - DEFSTAN 80-59/1 OF 1976 Stage inspection prescribed 04 ltr tin Flash point: 32 C Type: ALKYED</u>	
128	DPC969 36		044250442004 3 / PAINT FINISHING MID BROWN GLOSS FLASH POINT 32C (04 LTR Packing)	MULTI COAT FINISH PRIMED SEEL ALUMINUM	280 / LITER						<u>TECHNICAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996</u> <u>GENERAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996</u>	
129	DNQ958 37	NO DATA AVAILABL	034059923624 3 / BAG		2 / EACH/N						<u>TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		E	CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		UMBER						PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
130	DPC969 24	SUPERSEDED BY DGS 1035	0442502202020 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	400 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
131	DNH990 06		2340705059829 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SOHRAB/SHAHEEN/SUMAC DELUXE		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE: 22 INCHES GENERAL SPECIFICATION - SIZE: 22 INCHES	
132	DNQ990 05	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											timber.	
133	DPK9723 1		047450910052 4 / GREASE NAVAL GRAPHITE XG-460 3 KG PACK	XG-460	63 / KILOGR AMME						<p>TECHNICAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460)</p> <p>GENERAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460)</p>	
134	DPK9678 9	LG 280	047450910050 2 / GREASE LG-280 (XG- 286)	FIVE /G SERVICE PUMP NO.3	125 / KILOGR AMME						<p>TECHNICAL SPECIFICATION - SUPERCEDED VIDE CICIP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128</p> <p>GENERAL SPECIFICATION - SUPERCEDED VIDE CICIP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128</p>	
135	DPK9614 2	LG 280	047450910050 2 / GREASE LG-280 (XG- 286)	FIVE /G SERVICE PUMP NO.3	288 / KILOGR AMME						<p>TECHNICAL SPECIFICATION - SUPERCEDED VIDE CICIP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128</p> <p>GENERAL SPECIFICATION - SUPERCEDED VIDE CICIP/NSD/5021 DT 23 OCT 09 AND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											DEFSTAN 01-5 ISSUE 16 PG305, 128	
136	DNH975 14	NO DATA AVAILABL E	411070504164 1 / DEEP FREEZER 4.5 CUFT 220V AC 50HZ	DEEP FREEZER 4.5 CUFT 220V 50HZ	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
137	DNQ958 42	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
138	DNQ970 79	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
139	DNQ973 36	0413-2183	597099923966 3 / TAPE INSULATION ELECTRICAL	GENETAL USE	145 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Brand: OSAKA, NEETO . Packing details: 10-12 in each packing <u>GENERAL SPECIFICATION -</u> Brand: OSAKA, NEETO . Packing details: 10-12 in each packing	
140	DPC969 29	BS 2451, DEFSTAN: 80-73/1 OF 1977	801070100413 6 / PAINT NON SLIPING PREMIXED (LIGHT GREY) BS2451, DEFSTAN 80-73/1	FINISHING NON SLIP	100 / LITER						<u>TECHNICAL SPECIFICATION -</u> Grit Aggregate Size = 0.5mm to 1.0mm Thickness Level = 2.0mm to 3.0 mm <u>GENERAL SPECIFICATION -</u> Grit Aggregate Size = 0.5mm to 1.0 mm Thickness Level = 2.0mm to 3.0 mm	
141	DPC997 89	NO DATA AVAILABL E	685078503110 4 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANE R(UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMEN T FOR PNS NASR	215 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. <u>GENERAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
142	DPK97188	TELLUS S2 M-32	9150701003319 / Lub Oil TELLUS S2 MX 32 HIGH PREMIUM HYDRAULIC OIL	HYDRAULIC SYSTEM	130 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
143	DPC97829		0473546004703 / SODA CAUSTIC (PACKING 25 KG)		50 / KILOGRAMME						TECHNICAL SPECIFICATION - Soda Caustic (chemical nomenclature SODIUM HYDROOXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments GENERAL SPECIFICATION - Soda Caustic (chemical nomenclature SODIUM HYDROOXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments	
144	DNM97168	CPMU-18	4920705126467 / AIR INTAKE FILTER	AIR COND SYS CWM-2C70-PN	73 / EACH/NUMBER	CWM-2C70-PN					TECHNICAL SPECIFICATION - M/S COOL POINT ADDA PLOT SHARIZ JATTI UMRAH ROAD LAHORE TEL: 9242 35322612-7 GENERAL SPECIFICATION - M/S COOL POINT ADDA PLOT SHARIZ JATTI UMRAH ROAD LAHORE TEL: 9242 35322612-7	
145	DPK98500	AN002-200	6850143407653 / REALAY&CON		6 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			T CLEANER100 % TIRCHLOROE THANE (KF SITOSEC FPS) 200ML Packing OEM = CRC Industires France								AVAILABLE	
146	DPK9536 0	XL740HT	915078534429 6 / hp air compressor oil XL740HT INGERSOLL RAND		5 / GALLO N	H15T4					TECHNICAL SPECIFICATION - XL-740HT SYNTHETIC OIL BASE OIL TYPE DIESTER BASE SYNTHETIC VISCOSITY ISO 100 GRADE FLASH POINT 485F (252C) POUR POINT -35F (-37C)GENERAL SPECIFICATION - XL-740HT SYNTHETIC OIL BASE OIL TYPE DIESTER BASE SYNTHETIC VISCOSITY ISO 100 GRADE FLASH POINT 485F (252C) POUR POINT -35F (-37C)	
147	DNM992 19	323-9312	530601622659 6 / BOLT (M10X1X50- MM)		32 / EACH/N UMBER	C7.1					TECHNICAL SPECIFICATION - LENGTH: 50MM, COATING: PHOSPHATE & OIL GENERAL SPECIFICATION - LENGTH: 50MM, COATING: PHOSPHATE & OIL	
148	DNM964 62	3393041/4 334439	533071517706 1 / RING, WEAR	MAIN ENGINE KTA50M2	1 / EACH/N UMBER			CUMMINS Ins SOUTH CAROLINA USA	CUMMIN S USA		TECHNICAL SPECIFICATION - RING, WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL. GENERAL SPECIFICATION - RING, WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE CUMMINS KTA50M2 16 CYL.	
149	DNM954 94	1280317 / 3492654	533001457076 7 / GASKET KIT JW PUMP	MAIN ENGINE	1 / EACH/N UMBER	C 18	T2P01338	3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905	CATTER PILLAR		TECHNICAL SPECIFICATION - CATERPILLAR ENGINE C 18 GASKET KIT JW PUMP 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905GENERAL SPECIFICATION - CATERPILLAR ENGINE C 18 GASKET KIT JW PUMP 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
150	DPC95664	N/A	7930705181280 / DETERGENT WATER SOLUBLE	GENERAL ITEM	10 / LITER			LOCKEL MARKET	GENERAL ITEM		TECHNICAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE GENERAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE	
151	DNM95414	3803002	2815715199912 / KIT, ENGINE PISTON	CUMMINS DG VTA28-G5 USA	12 / EACH/NUMBER	VTA28-G5	25354882	CUMMINS ENGINE COMPANY, INC. BOX 3005 COLUMBUS, INDIANA, USA 47202	CUMMINS ENGINE COMPANY, INC. USA		TECHNICAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA PISTON SET GENERAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA PISTON SET	
152	DNM95415	AR11330	4320001320237 / PUMP, LUBE OIL	CUMMINS DG VTA28-G5 USA	1 / EACH/NUMBER	VTA28-G5	25354882	CUMMINS ENGINE COMPANY, INC. BOX 3005 COLUMBUS, INDIANA, USA 47202	CUMMINS ENGINE COMPANY, INC. USA		TECHNICAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA OIL PUMP GENERAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA OIL PUMP	
153	DPK95704	HA5430H	9150735164284 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	70 / QUART	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	TELEFLEX MARINE CANADA		TECHNICAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858 GENERAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	
154	DPK95980	ANDEROL 750	9150705200816 / ANDEROL 750 COMPRESSOR oil (PACKING CAN= 05 US GALLON or 05 ltr can)	ALKIN COMPRESSOR W4-18-225/330 FP6M USA	1 / LITER	W4-18-225/330 FP6M	948560	Anderol specialty lubricates adivision of chemture corporation 215 merry lane east hanover,NJ 07936 USA Ph no +1.203573.4595 fax 203.573.2324	USA		TECHNICAL SPECIFICATION - ANDEROL 750 COMPRESSOR OIL GENERAL SPECIFICATION - ANDEROL 750 COMPRESSOR OIL	
155	DNM95841	BH125	2895715222695 / BH 125 (ENGINE	BLACKHAWK 125 LITTE 2 STROKE	2 / EACH/NUMBER	BLACKHAWK 125 LITTE 2	BLACKHAWK 125 LITTE 2	M/S BLACK HAWK PARAMOTOR USA 8591 HOGAN ROAD VALLEY	BLACK HAWK PARAMO		TECHNICAL SPECIFICATION - ENGINE:BLACK HAWK 125 LITE 2 STROKE 23 HP SPEED:45 TO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ONLY - NO THROTTLE)			STROKE	STROKE	SPRING CA USA TEL 209-418-5990	TOR USA		50KM/H MAX RPM 9600 NOISE 100DB START METHOD ELECTRIC START ALTITUDE 6000FT REDUCTION TYPE CENTRIFUGAL CLUTCHGENERAL SPECIFICATION - ENGINE:BLACK HAWK 125 LITE 2 STROKE 23 HP SPEED:45 TO 50KM/H MAX RPM 9600 NOISE 100DB START METHOD ELECTRIC START ALTITUDE 6000FT REDUCTION TYPE CENTRIFUGAL CLUTCH	
156	DPC956 63	FG-K2-005-KW	482079513257 9 / TAN-(0-6) LUB OIL TESTING KIT	LUB OIL TESTING KIT KITTIWAKE	1 / EACH/N UMBER	NO DATA AVAILAB LE		UK	UK		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
157	DNM930 71	0503-3094	473071519610 7 / CLAMP HOSE	CUMMINS D/G 150 KVA 6BTAA5.9-G5 USA	5 / EACH/N UMBER	6BTAA5.9-G5	84093540	CUMMINS USA CUMMUNS ENGINE COMPANY INC BOX 3005 COLUMBUS IN	CUMMIN S USA		TECHNICAL SPECIFICATION - SAID ITEM IS SUPPORTED OF DIESEL GENERATORGENERAL SPECIFICATION - SAID ITEM IS SUPPORTED OF DIESEL GENERATOR	
158	DPC955 88	CC 2748M (5 liters packing) CC2750M (20 liters packing)	681071522985 7 / ES Complete EG premix coolant	MAIN ENGINE	200 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMIN S/ FLEETGU ARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
159	DPK9572 4	99000-22B55	915076522310 6 / ECSTAR OUT BOARD MOTOR GEAR OIL SUZUKI SAE-90 GL-5	SUZUKI OBM ENGINE	150 / MILLILI TER	NIL		SHOWA SHELL SEQIYU K K. 3-2 DAIBA-2-CHOME, MINATO-KU, TOKYO, 135-8074, JAPAN	OBM SUZUKI		TECHNICAL SPECIFICATION - ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE AUTOMOTIVE GEAR OIL GENERAL SPECIFICATION - ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE AUTOMOTIVE GEAR OIL	
160	DNQ953 05	DSLE/LE4 3562	512099918371 7 / SCREW	SCREW DRIVER(F)	1 / EACH/N UMBER	NO DATA AVAILAB		UK	UK ENGLAN		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			DRIVER RATCHET FLAT BLADE 250MM LONG		UMBER	LE			D			
161	DPK97782	OMALA 68	9150270001857 / SHELL OMALA OIL S2 GX 68 (PACKING 209 LTR DRUM)	MTP 750DD HUB OIL	209 / LITER	NO DATA AVAILAB LE		OC	TURKEY		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
162	DNM95456	244076/1/15/3	5120725141409 / TORQUE WRENCH (RANGE 8-30MKP)	DECK CRANE	1 / EACH/UMBER	NO DATA AVAILAB LE		JP	M/S RAHSOL SOLINGEN GERMANY		<u>TECHNICAL SPECIFICATION -</u> OEM : RAHSOL SOLINGEN GERMANY <u>GENERAL SPECIFICATION -</u> OEM : RAHSOL SOLINGEN GERMANY	
163	DPK98410	3809442	9150145297370 / SYNTHETIC TRANSMISSION OIL SAE 75W-90 (5L PACKING)	VOLVO PENTA ENGINES	20 / LITER	SAE75W-90	VOLVO PENTA ENGINES	AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	VOLVO PENTA		<u>TECHNICAL SPECIFICATION -</u> AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669 <u>GENERAL SPECIFICATION -</u> AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	
164	DPC97156		0474504740082 / CUPREX 1 BLOCK (PACKING 1 KG)	4FI SSDG SEA WATER PUMP	2 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> packing 1 kg <u>GENERAL SPECIFICATION -</u> packing 1 kg	
165	DPC95517		0473502202307 / PAINT REMOVER ORGANIC SOLVENT TYPE WATER RINSABLE (04 LTR TIN)		16 / LITER						<u>TECHNICAL SPECIFICATION -</u> 1. DEFSTAN80-14/1 OF 1970. type brushing <u>GENERAL SPECIFICATION -</u> 1. DEFSTAN80-14/1 OF 1970. type brushing	
166	DPC98495	NO DATA AVAILAB LE	0474500007028 / SAND YORKSHIRE		43 / BAG						<u>TECHNICAL SPECIFICATION -</u> JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FOR STEEL MOULDING (50 KG BAG)								(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 <u>GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0</u>	
167	DPC956 65		047350000360 8 / POWDER FRENCH CHALK (PACK IN 25 KG BAG)		25 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
168	DPC955 03	NO DATA AVAILABE	044250220116 4 / PAINT FINISHING GLOSS BLACK DLT LTR NS/G/1303/C DT 270199	PRIMED STEEL ALUMINUM OR WOOD	800 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
169	DPC956 31	WHO/SIF/ 13.R5	044250220120 1 / Lambda Cyhalothrin 2.5 or 25% EC. 01LTR PLASTIC PACKING WITH REGISTERED LABEL.	KEROCANE OIL.	120 / LITER						<u>TECHNICAL SPECIFICATION - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label.</u> <u>GENERAL SPECIFICATION - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label.</u>	
170	DPC957 50	PROPRIETARY PAINT EPOXY (TANCLENE)	044250220120 6 / PAINT PROTECTIVE EPOXY RED (NSSD/C01/04 42/GEN/173DT		300 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			060393)									
171	DPC957 43		044250943447 9 / PAINT PRIMING, LIGHT ADMIRALTY GREY FLASH POINT 23 DEGREE C	PRIMER FOR FINISHING ACID AND ALKALI	40 / LITER						TECHNICAL SPECIFICATION - 1. DEFSTAN 80-72/3 OF 2006 2. COLOUR SHADE NO 697 OF BS: 381 OF 1996 GENERAL SPECIFICATION - 1. DEFSTAN 80- 72/3 OF 2006 2. COLOUR SHADE NO 697 OF BS:381 OF 1996	
172	DPC957 21	NO. NS/C01/G EN/566 DT 210902	044250942912 0 / PAINT OIL FINISHING G, O.S.B. (GREEN)	FINISHING	160 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
173	DPC955 06	106 OF BS381-C OF 1996	044250442006 1 / PAINT VEHICLE CELLULOSE (ROYAL NAVY BLUE)	VEHICLES, DECORATIVE FINISHING	100 / LITER						TECHNICAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996. GENERAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.	
174	DPC951 12		044250942937 4 / VARNISH MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	USE ONWOOD UNDER CONDITIONS OF MARINE EX	60 / LITER						TECHNICAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION - PRESCRIBED GENERAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED	
175	DPC955 05	SUPERSE DED BY DGS 1035	044250220202 0 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	200 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed GENERAL SPECIFICATION - DEFSTAN 80- 151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
176	DPC957 25		044250942911 9 / PAINT OIL	FINISGING	180 / KILOGR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FINISHING FOR MEASURES (BLUE)		AMME						SPECIFICATION - NO DATA AVAILABLE	
177	DNQ973 03	0254-254050	025478420315 3 / CLAMP HOSE SZ 5.500 TO 6.250 BS 5315 71/226		41 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
178	DNQ958 40	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
179	DPK9776 1	LG 280	047450910050 2 / GREASE LG-280 (XG-286)	FIVE /G SERVICE PUMP NO.3	100 / KILOGRAMME						TECHNICAL SPECIFICATION - SUPERCEDED VIDE CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128 GENERAL SPECIFICATION - SUPERCEDED VIDE CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128	
180	DPK9719 4	LG 280	047450910050 2 / GREASE LG-280 (XG-286)	FIVE /G SERVICE PUMP NO.3	100 / KILOGRAMME						TECHNICAL SPECIFICATION - SUPERCEDED VIDE CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128 GENERAL SPECIFICATION - SUPERCEDED VIDE CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128	
181	DPK9723 7	XG-274, D-Stan 91-105xg-291.	047450474005 6 / GREASE NAVAL G.PXG-274 (XG-291)		74 / KILOGRAMME						TECHNICAL SPECIFICATION - SPECIFICATION:GREASE AIR CRAFT XG-271 OBSOLETE AND HAS BEEN REPLACED WITH XG-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											291(NATO G-382&G-421_VIDE DEF STAN 91-105 ISSUE-16 (Mar09).GENERAL SPECIFICATION - SPECIFICATION:GREASE AIR CRAFT XG-271 OBSOLETE AND HAS BEEN REPLACED WITH XG-291(NATO G-382&G-421_VIDE DEF STAN 91-105 ISSUE-16 (Mar09).	
182	DNM95265	328-21600	294001332606 1 / FILTER ELEMENT FLUID	LISTER/PETTER DIESEL ENGINE (USA)	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
183	DNM97930	1.524-975.0/1.524.972.0	432072510761 2 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	2 / EACH/NUMBER	HD 8/18-4 M* KAR					TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control GENERAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
184	DPC97821	NO DATA AVAILABLE	047450000006 2 / POWDER CHALK, COMP CALCIUM CARBONATE 98% PURITY		20 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
185	DPC95978	NO DATA AVAILABLE	803099225168 7 /	30MM GUN	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		E	LOCTITE222		UMBER						SPECIFICATION - NO DATA AVAILABLE	
186	DPC95589	205-6611 (05 Ltr) / 205-6612 (20 Ltr)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (05 Liter Can)	CP AIR COMP	100 / LITER						TECHNICAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTR GENERAL SPECIFICATION - CAT ELC TM EXTENDED LIFE COOLANT PREMIX MIXING RATIO 50 /50 % PART NUMBER: 205-6611 FOR 05 LTR PART NUMBER: 205-6612 FOR 20 LTR	
187	DPC95537	NO DATA AVAILAB L E	681073100099 9 / CRYSTIC 406E NON ACCELERATE D VERSION LOW EXOTHERM MARINE GRADE POLYESTER RESIN OR EQUIVALENT LLOYDS APPROVED PRODUCT	FOR GRP BOAT	225 / KILOGR AMME						TECHNICAL SPECIFICATION - General purpose unsaturated, polyester resin un promoted thixotropic, laminating type orthophatalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 "C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time,30oC with accelerator & MEKP Minutes 22 (Min) i. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max) GENERAL SPECIFICATION - General purpose unsaturated, polyester resin un	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>promoted thixotropic, laminating type orthophatalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 °C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time,30oC with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max)</p>	
188	DNM930 68	0149-2889	291071526755 3 / JOINT-FUEL PUMP TO TIMING CASE		1 / EACH/N UMBER	C22 D5					<p><u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u></p>	
189	DNM930 64	0104-2142	281571526750 3 / FLYWHEEL & STARTER RING ASSEMBLY (40DE0257+00 410264)		1 / EACH/N UMBER	C22 D5					<p><u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u></p>	
190	DPC957 41	RELAY+on	801070533282 3 / VIRKON SURFACE DISINFECTANT POWDER		90 / LITER	ZEEPER-114					<p><u>TECHNICAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal</u> <u>GENERAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal</u></p>	
191	DNM930	0122-0931	533079523738		1 /	C110D5					<p><u>TECHNICAL SPECIFICATION -</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	78		4 / GASKET OIL FILTER		EACH/N UMBER						nullGENERAL SPECIFICATION - null	
192	DPK95729	6G8-11325-23	915074523409 4 / Yamalube G14 Gear Oil Sae90 Tube		2 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - Yamalube G14 Gear Oil Sae90 Tube GENERAL SPECIFICATION - Yamalube G14 Gear Oil Sae90 Tube	
193	DNM93065	0115-0545	289571526753 5 / TAPPET		6 / EACH/N UMBER	C22 D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
194	DPK97232	EP 0	915073523263 7 / MOBILUX EP 0		20 / LITER	EP 0					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
195	DNM93070	0114-0429	311079526430 5 / BEARING CONNECTING ROD		6 / EACH/N UMBER	C110D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
196	DPC95535	174-6854	916077524990 9 / Cleaner, liquid, Hydrosolv 100		15 / EACH/N UMBER	CA 900198C A 900129C A 900191C A 900208C A 900207					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
197	DPC97159	008154Z03885	935077527416 8 / REFRACTORY MORTAR READY MIX		125 / KILOGRAMME	FIBERSTICK 1600					TECHNICAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 c GENERAL SPECIFICATION - FIBER STICK1600 is a wet air setting mortor and because of the choice of raw material usable upto 1550 c	
198	DPK95726	ZIC ATF 3	915073522136 9 / ZIC ATF 3 DEXRON SYNTHETIC TRANSMISSION FLUID	TILT & TRIM ASSEMBLY	30 / LITER	ZIC ATF 3	NIL	SK LUBRICANTS 26, JONG-RO-JONGNO-GU, SEOUL,KOREA www.skzic.com Made in Korea	SK LUBRICANTS		TECHNICAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly) GENERAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly)	
199	DNQ96253	CEN1000063D	5510FT101983 3 / Wooden Plug 250 x 100	Portable Firefighting and Damage	150 / EACH/N UMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR	CENAK GIDA TUR.INS.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			x 40 mm	Control Equipment System				TÜRK YE	MUH. MAK. SAN.LTD. STI.			
200	DNM95644	9510227/85148526	5999735161488 / CORROSION PROTECTION	IPS 500 (PROPULSION & STEERING SYSTEM)	4 / EACH/NUMBER			M/S VOLVO PENTA, GOTEBOG SWEDEN	M/S VOLVO PENTA		TECHNICAL SPECIFICATION - CORROSION PROTECTION GENERAL SPECIFICATION - CORROSION PROTECTION	
201	DNM92362	3831132/F S1212	2940795207857 / Filter, Fuel	320 KVA DG	2 / EACH/NUMBER	NT-855-G6	11518	CUMMINS POWER GENERATION COLUMBUS AVENUE MANSTON PARK MANSTON RAMSGATE KENT CT12 5BF UNITED KINGDOM	CUMMINS		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
202	DNQ95400	15199001	4220795289489 / SOLAS SOFTPACK RFD (FIRST AID KIT) FOR LIFE RAFT - LIFE BOAT		13 / EACH/NUMBER	life raft					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
203	DPC96441	NO DATA AVAILABLE	6840705057111 / INSECTICIDE K-OTHRINE ec 15 (01 LITER PACKING) (OEM M/S Bayer Environmental Sciences)	TO CONTROL INSECT PASTS COCKROACHES BUGS	15 / LITER						TECHNICAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label. GENERAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.	
204	DPK98211	G-32	9150795024119 / SHELL HIGH QUALITY REFRIGRATOR OIL S2FR-A46	REFRIGERANT COMPRESSOR OIL	209 / LITER						TECHNICAL SPECIFICATION - REFRIGERATOR OIL GROUP: DIN 51503, KAA, KCG GENERAL SPECIFICATION - REFRIGERATOR OIL GROUP: DIN 51503, KAA, KC	
205	DPC96443		6840705057109 / Insecticide-K-Othrine 25 WP (Wetable Powder)	TO CONTROL INSECTS COCKROACHES ANTS ETC	25 / KILOGRAMME						TECHNICAL SPECIFICATION - Permethrin 0.5% D Insecticide ACTIVE INGREDIENT (A.1) Permethrin 0.5% Dust W/W PACKING: 1 Kg Polyethylene Packing with registered label GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Permethrin 0.5% D Insecticide aCTIVE Ingredience (A.1) Permethrin 0.5% Dust W/W PACKING: 1 Kg Polyethylene Packing with registered label	
206	DPK9820 5	BSE 32	087006189916 0 / COLD/COOL ROOM(FV) BASE OIL (BITZER BSE 32 OIL) (01 Liter Packing)		40 / LITER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
207	DPC964 20		047450224246 3 / SOAP SCRUBBING		1008 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose.</u>	
208	DNJ9831 3	90794- 46911	291076523164 1 / FILTER ELEMENT	YAMAHA ENGINE 100HP	50 / EACH/N UMBER			YAMAHA MOTOR CO. LTD MARINE ENGINE DIVISION 2500 SHINGAI IWATA SHI IWATA SHIZUOKA KEN JAPAN	YAMAHA JAPAN		<u>TECHNICAL SPECIFICATION - 10 Micron fuel/ water separator filter, typically a spin-on canister style. Height: 2.67 Inch DIMENSION / SIZE: Width: 2.66 Inch Inner hole: 0.80 Inch</u> <u>GENERAL SPECIFICATION - 10 Micron fuel/ water separator filter, typically a spin-on canister style. Height: 2.67 Inch DIMENSION / SIZE: Width: 2.66 Inch Inner hole: 0.80 Inch</u>	
209	DNF9841 1	HTS-SFP- 850	591570524869 6 / SFP MODULE		4 / EACH/N UMBER	SFP-850					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
210	DNS988 26	2526438/2 52-6438	533001526667 1 / Seal-Inlet Valve	Caterpillar Emergency DG Marine Genset C 4.4 USA	6 / EACH/N UMBER	Marine Genset C 4.4	ZRE0132 3	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-349-8400	CATERPI LLAR USA		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
211	DNS988 26	2526438/2 52-6438	533001526667 1 / Seal-Inlet Valve	Caterpillar Emergency DG Marine Genset C 4.4 USA	6 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									MENTAL AND DEFENSE PRODUCTS			
212	SNG98502	02.08.0026	076071000000 1 / TS SINGLE ENGINE CONTROL	GM DETROIT D/ENGINE FOR GRP BOATS	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - M/S EXALTO EMIRATES MARINES EQUIPMENT SHARJAH PO BOX 21567 KALBA ROAD INDUSTRIAL AREA 18 SHARJA UAE GENERAL SPECIFICATION - M/S EXALTO EMIRATES MARINES EQUIPMENT SHARJAH PO BOX 21567 KALBA ROAD INDUSTRIAL AREA 18 SHARJA UAE	
213	SNG98501		512000277148 3 / WRENCH PIPE LG 06" TO 11.50" SURFACE 0.125" TO 0.500"		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
214	DNF95457	177-300	512076510133 3 / REVERSABLE BEARING PULLER (ARM 3.65-300MM)	PORTABLE INDUCTION HEATER FOR FMG	1 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
215	DNZ98418	ITD/DC-108	621078503122 9 / FLUORESCENT LAMP 220V2X30W (LENGTH 3 FEET) COMPLETE LIGHT FITTING CQ-0001	SOCKET AND JUNCTION BOX NASR	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 220 2 X 30 W (LENGTH 3 FEET) COMPLETE LIGHT FITTING GENERAL SPECIFICATION - 220 2 X 30 W (LENGTH 3 FEET) COMPLETE LIGHT FITTING	
216	DNF98417	ITD/DP-176 / DP-103	621078503105 2 / FLUORESCENT LIGHT ASSAMBLY	SOCKETS AND JUNCTION BOX	3 / EACH/NUMBER	DMS 1X20					TECHNICAL SPECIFICATION - LOCAL ADDRESS:DIGI TECH, SHOP NO2 NEW MEMON CHAMBERS,ALTAH HUSSAIN ROAD,DENSO HALL KARACHI-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			220V 2X20W DOUBLE TUBE LIGHT								7400.TEL:021-2639514.GENERAL SPECIFICATION - LOCAL ADDRESS:DIGI TECH,SHOP NO2 NEW MEMON CHAMBERS,ALTAF HUSSAIN ROAD,DENSO HALL KARACHI-7400.TEL:021-2639514.	
217	DNF98078	F20T12/CW	624000152299 6 / TUBE LIGHT ROD 18W	LIGHTING	50 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
218	DNF98076	TTB3450S / SC005	791070505097 5 / MACHINE FLOOR POLISHER 120/220V AC 50/60HZ 1000W 150RPM	SELF	1 / EACH/NUMBER	UPDATE D MODED TT 3450S, NUMATIC , UK.					TECHNICAL SPECIFICATION - UPGRADED MODEL : TT3450S, NUMATIC, UK.GENERAL SPECIFICATION - UPGRADED MODEL : TT3450S, NUMATIC, UK.	
219	DNF98421	210883-1	665500162247 9 / EXPENDABLE BATHY PROBE T7	LEANDER CLASS DEPOT PACKAGE	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
220	DNF96576		666501510764 8 / METALLIC MINE DETECTOR	EXPLOSIVE SAFETY EQUIPMENT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
221	DNZ98245	NO DATA AVAILAB LE	058278000001 0 / STERN LANTERNS 24V, 40 WATTS PB SERIES 700		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - MESSRS J.H PETTERS AND BEY GMBH KARPFANGERSTR,8/14 2000 HAMBURG 11,WEST GERMANY. BABA LIGHT QUALITY GODOWN MARKET SHOP NO D5-D7 PLOT NO D-283 MAIN SHERSHAH ROAD KARACHIGENERAL SPECIFICATION - MESSRS J.H PETTERS AND BEY GMBH KARPFANGERSTR,8/14 2000 HAMBURG 11,WEST GERMANY. BABA LIGHT QUALITY GODOWN MARKET SHOP NO D5-D7 PLOT NO D-283 MAIN SHERSHAH ROAD KARACHI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
222	DNF98621	L-30	4510785290919 / Hot Water Tap		10 / EACH/NUMBER	FS-30B					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
223	DNJ97786	65910-98J01	2910765344908 / FUEL FILTER / FUEL WATER SEPARATOR ELEMENT		2 / EACH/NUMBER	65910-98J01-000					TECHNICAL SPECIFICATION - FUEL FILTER / FUEL WATER SEPARATOR ELEMENT GENERAL SPECIFICATION - FUEL FILTER / FUEL WATER SEPARATOR ELEMENT	
224	DN094125	H/LWSAP-CJJQ-TJ /CJJQ-TJ 0103	2990FP1150003 / Mesh pad stage (INTAKE FILTER)		8 / EACH/NUMBER	CJJQ-TJ 0103					TECHNICAL SPECIFICATION - The mesh pad stage uses the condensation principle to capture and coalesce the tiny salt spray aerosol particles in the air intake into large droplets, most of which fall into the drain tank along the mesh by gravity dimension / size: 1800×1300×300 (mm) GENERAL SPECIFICATION - The mesh pad stage uses the condensation principle to capture and coalesce the tiny salt spray aerosol particles in the air intake into large droplets, most of which fall into the drain tank along the mesh by gravity dimension / size: 1800×1300×300 (mm)	
225	DNF97334	12-Fiber SMF G. 652.D	7045705249620 / Optical fiber cables CLT		120 / METER	12-Fiber SMF G. 652.D					TECHNICAL SPECIFICATION - Complete details regarding OFC 12-Fiber are available on page 18 of the provided Brochure named "PTCL Product Catalogue" NOTE: SM G. 652.D is the common standard for all type of OFC just the number of fibers varies i.e. 2 Fiber, 4 Fiber, 8 Fiber, 24 Fiber etc GENERAL SPECIFICATION - Complete details regarding OFC 12-Fiber are available on page 18 of the provided Brochure named "PTCL Product Catalogue" NOTE: SM G.652.D is the common standard for all type of OFC just the number of fibers varies i.e. 2 Fiber, 4 Fiber, 8 Fiber, 24 Fiber etc	
226	DNO977	126-0577	294077526610		12 /	3516E					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	87		9 / BREATHER AS (CHROME) (CRANKCASE)		EACH/N UMBER						BREATHER AS (CHROME) (CRANKCASE)GENERAL SPECIFICATION - BREATHER AS (CHROME) (CRANKCASE)	
227	DN098352	DL-473WDL02 4-02-07-02 / 473WDL02 4-02-07-02/ZACR-061-SEW	4110FP305006 1 / Anti-corrosion zinc bar (Fresh keeping device)		8 / EACH/N UMBER	473WDL0 24-02-07-02					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
228	DNO97800	518-5131	530677526678 5 / BOLT-HEAD (M8X1.25X25-MM)		48 / EACH/N UMBER	3516E					TECHNICAL SPECIFICATION - BOLT-HEAD (M8X1.25X25-MM) GENERAL SPECIFICATION - BOLT-HEAD (M8X1.25X25-MM)	
229	DNV97586	456-7957	611001692768 2 / PANEL CONTROL ELECTRICAL-ELECTRONIC EQUIPMENT		1 / EACH/N UMBER	mcs-3					TECHNICAL SPECIFICATION - mcs-3 deif controller of caterpillar c4.4 supply: 12/24v, 2amp fuse relay output: 250v ac/24v dc, 5 amp analogue output: 0-20 maGENERAL SPECIFICATION - mcs-3 deif controller of caterpillar c4.4 supply: 12/24v, 2amp fuse relay output: 250v ac/24v dc, 5 amp analogue output: 0-20 ma	
230	DNZ98419	G4 BVP 432 PHILIPS	623070522925 9 / FLOODLIGHT PHILIPS TANGO G4-BVP 432 LED/NW 120W	FloodLight	6 / EACH/N UMBER	G4 BVP 432 PHILIPS	TANGO G3-BVP38X	Philips.Co		Philips Lighting	TECHNICAL SPECIFICATION - Input Voltage : 220-240V Input Power : 400W Input Frequency : 50/60 Hz Light Source Colour : Neutral white Colour Temperature : 4000KGENERAL SPECIFICATION - Input Voltage : 220-240V Input Power : 400W Input Frequency : 50/60 Hz Light Source Colour : Neutral white Colour Temperature : 4000K	
231	SNM61060	6V4365	533101438178 0 / SEAL O RING	MAIN ENGINE	10 / EACH/N UMBER	C-18 ACERT	T2P01491	CATERPILLAR USA		CATERPILLAR	TECHNICAL SPECIFICATION - CATTER PILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189GENERAL SPECIFICATION -CATTER PILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189	
232	DSB9597 9	ITD/22320 18-ITD- VTX	295054534496 2 / Nut of Impeller		2 / EACH/N UMBER	MAIN ENGINE					TECHNICAL SPECIFICATION - The Impeller Nut is a precision- engineered fastener designed to securely lock the impeller onto the shaft. It ensures stable rotation, prevents loosening under vibration and maintains proper alignment during pump or engine operation. Typically made form high-strength, corrosion-resistant material for long- term reliability. GENERAL SPECIFICATION - The Impeller Nut is a precision-engineered fastener designed to securely lock the impeller onto the shaft. It ensures stable rotation, prevents loosening under vibration and maintains proper alignment during pump or engine operation. Typically made form high- strength, corrosion-resistant material for long-term reliability.	
233	DPC956 03	NO DATA AVAILABL E	044350443000 5 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		10 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 - 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,</p>	
234	DNF98636	COM-FDPSM9-ST/PC-ST/PC-03	6015715103128 / FIBER OPTICL PATCH CORD ST/PC - ST/PC SM9/125UM OS2 D.652D LSZH DUPLEX SC-SC, 3M COLOR YELLOW	COMPUTER NETWORK	12 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - ST/PC - ST/PC SM9/125UM OS2 D. 652D LSZH DUPLEX SC-SC, 3M COLOR YELLOW OEM COMBRIDGE WWW.COMBRIDGENETWORKS. COMGENERAL SPECIFICATION - ST/PC - ST/PC SM9/125UM OS2 D. 652D LSZH DUPLEX SC-SC, 3M COLOR YELLOW OEM COMBRIDGE WWW.COMBRIDGENETWORKS. COM</u></p>	
235	DNF98708	SUA1000V APC BRAND	6130705090301 / UPS OF APC BRAND 240V 1000VA BBACKUP	UPS	2 / EACH/NUMBER	APC BRAND					<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			TIME 1-1.30 HOURS									
236	DNF99396	ADAMJEE / bs-4678 (n)	5330705118843 / CHANNEL PATTI duraduct p/w 3m 01" INCH (16x25) adamjee	CHANNEL PATTE	710 / EACH/NUMBER	BS-4678 (N) adamjee					TECHNICAL SPECIFICATION - oem, adam jee karachi pakistan GENERAL SPECIFICATION - oem, adam jee karachi pakistan	
237	DSA90227	C6689-B3	6630144773770 / OXYGEN SENSOR (CELLULE ELECTROCHIM)		1 / EACH/NUMBER	∫ F3013 (NATO Code)					TECHNICAL SPECIFICATION - Dimension are as under: Height 20mm Dia 31.5 mm Circumference 104 mm GENERAL SPECIFICATION - Dimension are as under: Height 20mm Dia 31.5 mm Circumference 104 mm	
238	DRS78551	BC24VDC-2001	6130ZO5231597 / AUTOMATIC BATTERY CHARGER (BRAND STABOL)		1 / EACH/NUMBER	ELECTR OWAYS LAHORE					TECHNICAL SPECIFICATION - INPUT 180-230VAC 1PH 50HZ OUTPUT 12/24VDC UPTO 300AH BATTERY OUTPUT : 12/24V DC 300 AH BATTERY (RECHARGEABLE BATTERY) GENERAL SPECIFICATION - INPUT 180-230VAC 1PH 50HZ OUTPUT 12/24VDC UPTO 300AH BATTERY OUTPUT : 12/24V DC 300 AH BATTERY (RECHARGEABLE BATTERY)	
239	DSA87243	VISF6188-sew/BHQ1 CC100030T	5305142686188 / VISF90M10X30X25		200 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
240	DSB93455	pstn-11647316-vtx	4820705344317 / ball valve ported		2 / EACH/NUMBER	PSTN-11647316-VTX					TECHNICAL SPECIFICATION - ∫ Length = 116mm & Dia = 47 mm ∫ Material Stainless Steel grade 316 GENERAL SPECIFICATION - ∫ Length = 116mm & Dia = 47 mm ∫ Material Stainless Steel grade 316	
241	DSA86262	E75-206A32AS PECIAL60 L7V	5130142573586 / MEULE		306 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
242	DSB99116	12185615 /ams1310	4130705232486 / BOXSTAINLES		52 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Material Grade SS 304 Size:10"x10" x6" Length Width and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SSTEEL FOR IR8 GRANULE								DepthGENERAL SPECIFICATION - Material Grade SS 304 Size:10"x10" x6" Length Width and Depth	
243	DSB100055	12185615 /ams1310	4130705232486 / BOXSTAINLES SSTEEL FOR IR8 GRANULE		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Material Grade SS 304 Size:10"x10" x6" Length Width and DepthGENERAL SPECIFICATION - Material Grade SS 304 Size:10"x10" x6" Length Width and Depth	
244	DSB99936	12185615 /ams1310	4130705232486 / BOXSTAINLES SSTEEL FOR IR8 GRANULE		52 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Material Grade SS 304 Size:10"x10" x6" Length Width and DepthGENERAL SPECIFICATION - Material Grade SS 304 Size:10"x10" x6" Length Width and Depth	
245	DSB98741	CM7PS-D1-SEW	5935703399197 / 7PIN MALE DEUTSCH		11 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
246	DRG95541	I-633C5TB OR CAA33-5SB	4330705147278 / VELCON COALESCER ELEMENT (COALESCER FILTER)		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
247	DSB99590	E27311H120M50AVTL	5305142912075 / BOLT 12 X 50		3770 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Dia: 12mm b. Length: 50mm c. Head: (hexagonal)GENERAL SPECIFICATION - a. Dia: 12mm b. Length: 50mm c. Head: (hexagonal)	
248	DRG95809	TYRE 2.50 X18	2610ZO6571595 / TYRE SIZE-2.50X18		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SIZE-2.50X18(BRAND SERVICE, PANTHER) GENERAL SPECIFICATION - SIZE-2.50X18 (BRAND SERVICE,PANTHER)	
249	DNM97069	3588745/3588770	3426171227297 / ANODE KIT ZINC ANODE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBORG, SWEDEN	AB VOLVO PENTA		TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887	
250	DNF99729	PAM-195-P	5945735173093 / SOLINIDS SUPPLY MODULE AZMIUTH	TUC AZMIUTH THRUSTER	2 / EACH/NUMBER	WARTSILA 9L20		WARTSILA FINLAND	WARTSILA FINLAND		TECHNICAL SPECIFICATION - WARTSILA FINLAND MAKE/BRAND: W-E-ST ELECTRONICS GMBH GERMANY. GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			THRUSTER								WARTSILA FINLAND MAKE/BRAND: W-E-ST ELECTRONICS GMBH GERMANY.	
251	DNC977 93	7009117- 060-150/ JB-05	394072535051 5 / LIFTING BELT SLINGS CAPACITY 05 TON, LENGTH 06 METER, WIDTH 125MM COLOUR RED		2 / EACH/N UMBER	7009117- 060-150					<u>TECHNICAL SPECIFICATION -</u> LIFTING BELT SLINGS RED 05 TON CAPACITY LENGTH 06 METER WIDTH 150MM EN1492 <u>GENERAL SPECIFICATION</u> -LIFTING BELT SLINGS RED 05 TON CAPACITY LENGTH 06 METER WIDTH 150MM EN1492	
252	DNF1000 78	RG- NBS3100- 24GT4SFP /RUIJIE/J9 776A / J9772A+j4 859c/RG- NBS3100- 24GT4SFP	589578520783 3 / NETWORK SWITCH HP 2530 24G/48G WITH 2/4 SFP MODULES	NETWORK SWITCH J9772A CHINA	1 / EACH/N UMBER	RG- NBS5200- 48GT4xS/ R8N88A- HP/J9776 AJ9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA		<u>TECHNICAL SPECIFICATION -</u> ATTACHED <u>GENERAL</u> <u>SPECIFICATION - ATTACHED</u>	
253	DNF9973 0	SUA 10001 APC	613072514039 3 / APC UPS 1KVA 230VAC WITH 2X BATTERIES 12V 12AH	BERQ PROJECT	6 / EACH/N UMBER	APC BRAND		GE		ROHDE & SCHWAR Z INTL GMBH GERMAN Y	<u>TECHNICAL SPECIFICATION -</u> ONE PC average voltage consumption in 250 Watts Battery backup time of said UPS is: Backup Time = AH *12V*N*Efficiency of Battery / Load in watts Where: AH= Ampere hour Capacity of battery (12AH) N= Number of 12 batteries attached (2) Efficiency of Battery = 0.8 12AH*12v*2*0.8/250 = 0.9216 hours Approx. : 30 minutes 230VAC WITH@X BATTERIED 12V 12AH <u>GENERAL SPECIFICATION</u> -ONE PC average voltage consumption in 250 Watts Battery backup time of said UPS is: Backup Time = AH *12V*N*Efficiency of Battery / Load in watts Where: AH= Ampere hour Capacity of battery (12AH) N= Number of 12 batteries attached (2) Efficiency of Battery = 0.8 12AH*12v*2*0.8/250 = 0.9216 hours Approx. : 30 minutes 230VAC WITH@X BATTERIED 12V 12AHM	
254	DNF9756	H12L/ M	635077515345	GRP POLICE	1 /	M 12L		M/S VETUS N.V.	VETUS		<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	1	12L	7 / ELECTRIC MARINE HORN	BOAT (NAVIGATION SYS)	EACH/N UMBER			FOKKERSTRAAT 571 SCHIEDAM NETHERLANDS 3125 BD 010-4377700 / 010-4152634 KVK 24219798 0000 SALES@VETUS.NL	HOLLAN D		OEM:M/S VETUS N.V. FOKKERSTRAAT 571 SCHIEDAM NETHERLANDS 3125 BD 010-4377700 / 010-4152634 KVK 24219798 0000 SALES@VETUS.NL GENERAL SPECIFICATION - OEM: M/S VETUS N.V. FOKKERSTRAAT 571 SCHIEDAM NETHERLANDS 3125 BD 010-4377700 / 010-4152634 KVK 24219798 0000 SALES@VETUS.NL	
255	DNF1000 87	9248 / 9116	599571514803 1 / COAX-CATV CABLE	DVBS-2 HUB	100 / METER	NO DATA AVAILAB LE		US	KARACHI ELECTR ONIC HASSAN CENTER / = M/S COMM CABLE ESSA ELECTR ONIC / = CITY CABLE ALKABIR CENTER		TECHNICAL SPECIFICATION - Use with DVBS KU Band for transmission & reception 50-70 OHM GENERAL SPECIFICATION - Use with DVBS KU Band for transmission & reception 50-70 OHM	
256	DNF9993 1	346069002 0	589515206988 8 / CONTROL UNIT	PROPLUSIO N SYSTEM	1 / EACH/N UMBER	OS2	P2P01436	BOSCH REXROTH SPA CIT CERNUSCO SUL NAVIGLIO (MILANO) CTR ITALY PSC 20062 TEL 02923651	ITALY		TECHNICAL SPECIFICATION - REMOTE CONTROL MAREX OS2 MAIN PCB REQUIRED FOR ENGINE OPERATION GENERAL SPECIFICATION - REMOTE CONTROL MAREX OS2 MAIN PCB REQUIRED FOR ENGINE OPERATION	
257	DNS100 000	2526438/2 52-6438	533001526667 1 / Seal-Inlet Valve	Caterpillar Emergency DG Marine Genset C 4.4 USA	6 / EACH/N UMBER	Marine Genset C 4.4	ZRE0132 3	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-349-8400	CATERPI LAR USA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
258	DNF9973 2	PS-1280 F2/WP7-12-LONG	614071513869 9 / BATTERY 12 VDC 7.5AH/ 8AH	UPS 6KVA	32 / EACH/N UMBER	PS-1280 F2/WP7-12-LONG		US	POWER SONIC USA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
259	DNF9973	Dell	702515182385	UFFAQ	1 /	Dell		Dell Computer Corporation	Dell		TECHNICAL SPECIFICATION - As	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	3	Optiplex 9020	1 / Dell Optiplex 9020 Work Station		EACH/N UMBER	Optiplex 9020		One Dell Way Round Rock, Texas 78682, USA Ph:(888)560-8324 / (888) -915-3355: Fax: (800) 317-3355 Web: www.Dell.com	Computer Corporation, USA		Attached country of origin italy <u>GENERAL SPECIFICATION -</u> As Attached country of origin italy	
260	DNS100 000	2526438/2 52-6438	533001526667 1 / Seal-Inlet Valve	Caterpillar Emergency DG Marine Genset C 4.4 USA	6 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
261	DNF9993 8	A/p SPECCS pak cable/ Allied Cable	614570513268 3 / POWER CABLE 2 CORE 3/29 P. V.C WIRE 220/440 VOLTS	CCTV SYSTEM	1 / METER	PAK CABLE		PK	M/S AYUB ENGINEE RING MANUFA CTURES, REPAIRI NG & GENER AL SUPPLIE R GROUND FLOOR, NORTH WING, MULES MANSION , KEAMARI , KARACHI		<u>TECHNICAL SPECIFICATION -</u> brand: pakistan cable equivalent: Allied Cable ;1.5mm 2 core flat pvc insulated 300/500v (brochure Attached) 2. 2 core 3 strains copper wire per core with cross sectional area .646 mm2 outer daimeter: 0.282 ohm/km pure copper wire 99% current carrying capacity: 11 aMps acceptance criteria: item shouldd satisfied all mentioned specifications testing: testing is to be performed to verify all the mentioned specs. <u>GENERAL SPECIFICATION -</u> brand: pakistan cable equivalent: Allied Cable ;1.5mm 2 core flat pvc insulated 300/500v (brochure Attached) 2. 2 core 3 strains copper wire per core with cross sectional area .646 mm2 outer daimeter: 0.282 ohm/km pure copper wire 99% current carrying capacity: 11 aMps acceptance criteria: item shouldd satisfied all mentioned specifications testing: testing is to be performed to verify all the mentioned specs.	
262	DNF9972 8	12X50 Aculon	055279001907 1 /		10 / EACH/N	NIKON 12X50					<u>TECHNICAL SPECIFICATION -</u> Nikon 12x50 Black <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
		A211	BINOCULAR 12X50 BLACK		UMBER						SPECIFICATION - Nikon 12x50 Black	
263	DNF99994	N250 PLUS EXIDE / OSAKA OR EQUALENT	056279562000 6 / BATTERY LEAD ACID 12V 200AH	DG USED	6 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA SIZE: 511X280X246MM EXIDE PAKISTAN.GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA SIZE:511X280X246MM EXIDE PAKISTAN.	
264	DNF99727	7-427-510	392050505695 8 / TROLLY ELECT FOOD WARMING SYSTEM S/STEEL 220V 1PH 44X30X41/48 Inch.	PNS SHIFA	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - (a)- Main frame (top/body)in SS201 material, machine pressed and international standard finishing. (b)- Four iron synthetic Plastic covered tires castors 6" with 2 casters with breaks. (c)- Two top doors opening along with side rest for door support. GENERAL SPECIFICATION - (a)- Main frame (top/body)in SS201 material, machine pressed and international standard finishing. (b)- Four iron synthetic Plastic covered tires castors 6" with 2 casters with breaks. (c)- Two top doors opening along with side rest for door support.	
265	DNG98635	5000S482 3F841499 REVG	473000926962 6 / STRAINER SEDIMENT SIZE 1/1/2 INCH BRONZE	HPAC	14 / EACH/NUMBER						TECHNICAL SPECIFICATION - bronze body size: 1/1/2 INCH threaded or flanged pipeline inline mouting naval ship piping system cast brinze corrosion-resistant housing removable perforated or mesh filter element threaded clean out cap sealing gasket GENERAL SPECIFICATION - bronze body size: 1/1/2 INCH threaded or flanged pipeline inline mouting naval ship piping system cast brinze corrosion-resistant housing removable perforated or mesh filter element threaded clean out cap sealing gasket	
266	DNF99886	TOA	596576508853 9 / HORN	SRE SUSTEM	5 / EACH/NUMBER	TOA					TECHNICAL SPECIFICATION - NO DATA AVAILBLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SPEAKER 10 WATT WITH MATCH TRANSFORMER TOA JAPAN		UMBER						SPECIFICATION - NO DATA AVAILABLE	
267	DNF100036	(Cannon EOS R-100)/Nikon Z50II /D3500 /D-3000	6710765087447 / NIKON DIGITAL STILL CAMERA WITH FLASH GUN SB-900 /NIKON Z50II	DIGITAL CAMERA	1 / EACH/NUMBER	(Cannon EOS R-100)					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
268	DNF100024	DL105 / 0208061	6140705118956 / BATTERY 12V 75AH (BLACK II)RC 130MIN MAINT.FREE	STATIC FREQUENCY CONVERTER/ UPS(DR 3000)	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
269	DNZ98407	AXN-21-18J-18K	4520705265883 / HEATER ELEMENT 400V 50HZ FLANGE TYPE 20KW 3 PHASE STAR CONNECTED LENGHT 22-30 INCH		2 / EACH/NUMBER	AXN-18J					TECHNICAL SPECIFICATION - 400 V, 50 Hz, flange type, 20 KW, 3 phase, Star Connected, Length 22-30 Inches from flange, flange Dia 5 inches GENERAL SPECIFICATION - 400 V, 50 Hz, flange type, 20 KW, 3 phase, Star Connected, Length 22-30 Inches from flange, flange Dia 5 inches	
270	DNF95579	Winner pro1K	6150TA5249659 / UPS 1KVA		4 / EACH/NUMBER	Winner pro1K					TECHNICAL SPECIFICATION - Complete Details regarding 2KVA & 1KVA UPS are avialable in the attached Brochure named "WinnerPro" GENERAL SPECIFICATION - Complete Details regarding 2KVA & 1KVA UPS are avialable in the attached Brochure named "WinnerPro"	
271	DNC97792	7009120-140-210/jb-10	3940725350514 / LIFTING BELT SLINGS CAPACITY 10 TON, LENGTH 15 METER, WIDTH 250MM,		2 / EACH/NUMBER	7009120-140-210					TECHNICAL SPECIFICATION - LIFTING BELT SLINGS ORANGE 10 TON CAPACITY HGS DUPLIX LENGTH 14 METER, WIDTH 210MM, STANDARD EN 1429 SLINGS OF POLYESTER 04 OR 05 LAYERS with eye hole at both ends GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COLOUR ORANGE								LIFTING BELT SLINGS ORANGE 10 TON CAPACITY HGS DUPLIX LENGTH 14 METER, WIDTH 210MM, STANDARD EN 1429 SLINGS OF POLYESTER 04 OR 05 LAYERS with eye hole at both ends	
272	DNZ98405	AXN-21-56P-12K	452070526542 6 / HEATER ELEMENT 400V 50HZ FLANGE TYPE 15KW LENGHT 55-57 INCH FROM FLANGE		2 / EACH/ UMBER	21-56P					TECHNICAL SPECIFICATION - 400 V, 50 Hz, flange type, 15 KW, 3 phase, Star Connected, Length 55-57 Inches from flange, flange Dia 5 inches GENERAL SPECIFICATION - 400 V, 50 Hz, flange type, 15 KW, 3 phase, Star Connected, Length 55-57 Inches from flange, flange Dia 5 inches	
273	DNC97794	7009117-040-150/ JB-05	394072535051 6 / LIFTING BELT SLINGS CAPACITY 05 TON, LENGTH 04 METER, WIDTH 125MM, COLOR RED		4 / EACH/ UMBER	7009117-040-150					TECHNICAL SPECIFICATION - LIFTING BELT SLINGS RED 05 TON CAPACITY HGS DUPLIX LENGTH 04 METER, WIDTH 150MM, STANDARD EN 1429 GENERAL SPECIFICATION - LIFTING BELT SLINGS RED 05 TON CAPACITY HGS DUPLIX LENGTH 04 METER, WIDTH 150MM, STANDARD EN 1429	
274	DNF99939	HAC-HFW1500 CP-A/DH- HAC- HFW1500 TL-A	676078524886 1 / 5MP, IR BULLET FIX CAMERA, WITH ACCESSORIE S		3 / EACH/ UMBER	HAC- HFW1500 TL- A/HAC- HFW1500 cP-A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
275	DNO97799	4W-3034	473099731633 9 / CLAMP- HOSE		12 / EACH/ UMBER	3516E					TECHNICAL SPECIFICATION - CLAMP-HOSE GENERAL SPECIFICATION - CLAMP-HOSE	
276	DNO100109	349-7378/369-7561	662077524994 1 / SENSOR GP- PRESSURE		2 / EACH/ UMBER	C9.3					TECHNICAL SPECIFICATION - SENSOR GP-PRESSURE GENERAL SPECIFICATION - SENSOR GP-PRESSURE	
277	DNF100025	N-220	616073524492 8 / battery 12v 170 ah		2 / EACH/ UMBER	CLASSIC V					TECHNICAL SPECIFICATION - DRY BATTERY VOLT: 12 AMP: 170 AH DIMENSION: LENGTH 19.9" WIDTH 8.4" HEIGHT 9.2" APPROX WEIGHT: 30-40 KG GENERAL SPECIFICATION - DRY BATTERY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											VOLT: 12 AMP: 170 AH DIMENSION: LENGTH 19.9" WIDTH 8.4" HEIGHT 9.2" APPROX WEIGHT: 30-40 KG	
278	DNZ98406	axn-21-22n-12k	4520705265427 / heater element 400v 50hz flange type 15 kw length 22-30 inches		2 / EACH/NUMBER	21-22n					TECHNICAL SPECIFICATION - 400 V, 50 Hz, flange type, 15 KW, Length 22-30 Inches from flange, flange Dia 5 inches GENERAL SPECIFICATION - 400 V, 50 Hz, flange type, 15 KW, Length 22-30 Inches from flange, flange Dia 5 inches	
279	DNF99721	dgs-1510-28p / DGS-1510-28X, DEM-310GT,	5930705246333 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT)		1 / EACH/NUMBER	dgs-1510-28x,DEM-310GT,					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
280	DNF100085	ub500 / ZA3000E	6350785246359 / WALK THROUGH GATE WITH MONITOR & FACE CAPTURE CAMERA		2 / EACH/NUMBER	ub500 /ZA3000E					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
281	DNC97795	7009117-050-150/JB-05	3940725350517 / LIFTING BELT SLINGS CAPACITY 05 TON , LENGTH 05 METER, WIDTH 125MM, COLOR RED		2 / EACH/NUMBER	7009117060					TECHNICAL SPECIFICATION - LIFTING BELT SLINGS RED 05 TON CAPACITY HGS DUPLIX LENGTH 05 METER, WIDTH: 150MM, STANDARD EN 1429 GENERAL SPECIFICATION - LIFTING BELT SLINGS RED 05 TON CAPACITY HGS DUPLIX LENGTH 05 METER, WIDTH: 150MM, STANDARD EN 1429	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
282	DNT99999	SD6032-02	6685CH5310385 / SENSOR, EXH GAS TEM		6 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
283	DNF99656	zkx8s	5815151717958 / zk-teco zk-8s/ZKTECO G3 PLUS biometric finger print reader		1 / EACH/NUMBER	zkx8s/ZK Teco G3 Plus					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
284	DNF99998	DJ 12-7/WP7-12/WP1236W/CP1270	6140795140462 / 12V7AH LEAD ACID MAINTENANCE FREE BATTERY	FIRE ALARM / UPS 6KVA STABMATIC	64 / EACH/NUMBER	CP1270		UK		STABIMATIC CO LTD UK	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
285	DNF95462	0102-034021-226	4820785154465 / OIL TEMPERATURE CONTROLLER RANGE 0-300 C	L PAC /AC/PLANT	2 / EACH/NUMBER	OMRON ESC4	100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674.		CHINA	TECHNICAL SPECIFICATION - DIGITAL TEMPERATURE CONTROLLER /INDICATOR THERMOCOUPLE rtd OFTEN 199.9 TO 900c LED /LCD PANEL INDICATING RELAY OR SSR DRIVE (ALARM /CONTROL) 100-240 VAC (PANEL MOUNT) GENERAL SPECIFICATION - DIGITAL TEMPERATURE CONTROLLER /INDICATOR THERMOCOUPLE rtd OFTEN 199.9 TO 900c LED /LCD PANEL INDICATING RELAY OR SSR DRIVE (ALARM /CONTROL) 100-240 VAC (PANEL MOUNT)	
286	DNO99029	13509102	4810775237127 / (C), CHECK VALVE, 1207, STORM TYPE, RIGHT-ANGLES, DN65, FLANGE, PN 10, FL;PN 10, CAST IRON GG 40.3 (ENJS 1020), COATED, WITH		1 / EACH/NUMBER	Not Known					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LOCKING DE									
287	DNF96273	AS-PISTOLE-17	692070520865 6 / AIMING SENSOR	G-3 SIMULATOR 2017 PAK	1 / ASSEMBLY	AS-PISTOLE-17	NA	M/S SOFT INOVATION SYSTEM 34-A/2, 1ST FLOOR LUXURY HOTEL, LALAZAR. MT KHAN ROAD KARACHI +9221385610277	M/S SOFT INNOVATIVE SYSTEMS		TECHNICAL SPECIFICATION - AIMING SENSOR AS PISTOLE-17 TECHONOLGY INFRA RED VOLTAGE 3.0 VDC -4.0 VDC+-10% CURRENT 100 mA +-20% GENERAL SPECIFICATION - AIMING SENSOR AS PISTOLE-17 TECHONOLGY INFRA RED VOLTAGE 3.0 VDC -4.0 VDC+-10% CURRENT 100 mA +-20%	
288	SNF99307	SM-170-380	594573522833 4 / PHASE SEQUENCE RELAY	STEERING CONTROL	8 / EACH/NUMBER	SM-170-380	NIL	M/S FATEK AUTOMATION CORPORATION 26FL, No 29, Sec.2, jung.jeng E Road Danshuei Dist, New Taipei city 25170, Taiwan, R.O.C. TEL : +886-2-2808-2192 FAX : +886-2-2809-2618.	FATEK TAIWAN		TECHNICAL SPECIFICATION - M/S FATEK AUTOMATION CO TAIWAN GENERAL SPECIFICATION - M/S FATEK AUTOMATION CO TAIWAN	
289	SNF99304	LC1-D32-BL	599973522833 7 / CONTACTOR	STEERING CONTROL	5 / EACH/NUMBER	LC1-D32-BL	NIL	M/S FATEK AUTOMATION CORPORATION 26FL, No 29, Sec.2, jung.jeng E Road Danshuei Dist, New Taipei city 25170, Taiwan, R.O.C. TEL : +886-2-2808-2192 FAX : +886-2-2809-2618.	FATEK TAIWAN		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
290	DNS97525	5268375	432001603876 8 / PUMP SEA WATER	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD USA	2 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s IMPEX NINE INC		TECHNICAL SPECIFICATION - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565 USA CAGE 65KD2 USA GENERAL SPECIFICATION - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565 USA CAGE 65KD2 USA	
291	DNZ90597	D100801	431079513881 0 / CYLINDER LINER	MAIN AIR COMPRESSOR	2 / EACH/NUMBER	NO DATA AVAILAB LE		UK	COMPAIR UK LTD		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
292	DNF99126	ST4000NM0053/ST4000VX000	702578520784 9 / 4TB SURVEILLANCE HARD DISK-SATA FOR NVR	CCTV System ST4000VX000 CHINA	1 / EACH/NUMBER	ST4000VX000	NA	Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888	CHINA		TECHNICAL SPECIFICATION - Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32 GENERAL SPECIFICATION - Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											up to 32	
293	DNF96274	AS-G3E-17	2990705207575 / AIMING SENSOR	G-3 SIMULATOR 2017 PAKISTAN	1 / EACH/NUMBER	AS-G3E-17	NA	M/S SOFT INOVATIVE SYSTEM 34-A/2, 1ST FLOOR,OPP LUXURY HOTEL, LALAZAR OFF. MT KHAN ROAD KARACHI TEL: +922135610429 +9221385610277	M/S SOFT INNOVATIVE SYSTEM S		TECHNICAL SPECIFICATION - TECHNOLOGY = INFRE RED VOLTAGE = 3 Vdc -4 Vdc +- 10 % CURRENT = 100 mA +- 20 % COLOR = BLACK WEIGHT = .025 KG WITH CLAMP GENERAL SPECIFICATION - TECHNOLOGY = INFRE RED VOLTAGE = 3 Vdc -4 Vdc +- 10 % CURRENT = 100 mA +- 20 % COLOR = BLACK WEIGHT = .025 KG WITH CLAMP	
294	DNS97525	5268375	4320016038768 / PUMP SEA WATER	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD USA	2 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	CUMMINS		TECHNICAL SPECIFICATION - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565 USA CAGE 65KD2 USA GENERAL SPECIFICATION - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565 USA CAGE 65KD2 USA	
295	DNZ97745	A12150	2530785158980 / BRAKE LINING MATERIAL SIZE. 5/8	PORT DRAG HEAD WINCH	100 / FOOT			M/S CSTC CHINA/ABBASI TRADERS LTD	M/S CSTC CHINA..		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
296	DNF99207	5842NL-PE6PT	6605785168381 / 6 POWER POINTS EXTENSION BOARD	6 POWER POINTS EXTENSION BOARD	3 / EACH/NUMBER			PAK MAC 55A ST £ 48 F-B/4 ISLAMABAD PH 2850772-76	PAK MAC		TECHNICAL SPECIFICATION - PAK MAC 55A ST £ 48 F-B/4 ISLAMABAD PH 2850772-76 GENERAL SPECIFICATION - PAK MAC 55A ST £ 48 F-B/4 ISLAMABAD PH 2850772-76	
297	DNS96456	3161223	4710270355354 / OIL PIPE	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	1 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60	AB Volvo Penta Sweden		TECHNICAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT) GENERAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)	
298	DNF97170	05-00-0049-00	6350715197061 / 160 KV CONTROLLER	SCANNING MACHINE XIS-6545 USA	1 / EACH/NUMBER	XIS-6545	ASTNC16 OSS2299	INC. 21481 FERRERO PARKWAY CITY OF INDUSTRY, CA-91789USA	ASTROP HYSICS USA		TECHNICAL SPECIFICATION - Used for Luggage Mail / Baggage Scanning GENERAL SPECIFICATION - Used for Luggage	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Mail / Baggage Scanning	
299	DNF96300	DCC/HFB M/HW/127	662570521320 2 / HEADPHONES WITH MIC	OPERATOR CONSOLE DCC-2012016 PAKISTAN	20 / EACH/NUMBER	DCC-2012016	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, KHI 021-35363212	DCC		<u>TECHNICAL SPECIFICATION -</u> Headphones with Mic DRIVER DIAMETER: 40MM EAR CUP OUTER 80-100 MM CABLE LENGTH 1.2 - 1.5 M 100G -300G 4 MM DIA MIC SIZE <u>GENERAL SPECIFICATION -</u> Headphones with Mic DRIVER DIAMETER: 40MM EAR CUP OUTER 80-100 MM CABLE LENGTH 1.2 - 1.5 M 100G -300G 4 MM DIA MIC SIZE	
300	DNF95463	5133311	291573513331 1 / OIL PRESSURE SENSOR	150KVA GENSET	2 / EACH/NUMBER	150KVA GENSET			OC	RA ELECTRONICS GROUP ENGINEERING SERVICE SUIT 216 2ND FLOOR MASHRIQUE CENTRE GULSHAN-E-IQBAL KARACHI	<u>TECHNICAL SPECIFICATION -</u> PART OF DIESEL GENERATOR PORT CATERPILLER 55 KW CONTROL SYSTEM <u>GENERAL SPECIFICATION -</u> PART OF DIESEL GENERATOR PORT CATERPILLER 55 KW CONTROL SYSTEM	
301	DNF97078	N1537	611070515526 0 / ENERGY SAVER 220V-240V ,11W. (screw type)	SELF, FOR DISTRIBUTION SYS.	25 / EACH/NUMBER			SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI.	PHILIPS CO LTD.		<u>TECHNICAL SPECIFICATION -</u> SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/I,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi <u>GENERAL SPECIFICATION -</u> SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/I,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi '	
302	DNF97970	A/p SPECCS pak cable/ Allied Cable	614570513268 3 / POWER CABLE 2 CORE 3/29 P. V.C WIRE 220/440 VOLTS	CCTV SYSTEM	450 / METER	PAK CABLE		PK		M/S AYUB ENGINEERING MANUFACTURES, REPAIRING &GENERAL SUPPLIER GROUND FLOOR, NORTH WING, MULES MANSION , KEAMARI , KARACHI	TECHNICAL SPECIFICATION - brand: pakistan cable equivalent: Allied Cable ;1.5mm 2 core flat pvc insulated 300/500v (brochure Attached) 2. 2 core 3 strains copper wire per core with cross sectional area .646 mm2 outer daimeter: 0.282 ohm/km pure copper wire 99% current carrying capacity: 11 aMps acceptance criteria: item shouldd satisfied all mentioned specifications testing: testing is to be performed to verify all the mentioned specs. GENERAL SPECIFICATION - brand: pakistan cable equivalent: Allied Cable ;1.5mm 2 core flat pvc insulated 300/500v (brochure Attached) 2. 2 core 3 strains copper wire per core with cross sectional area .646 mm2 outer daimeter: 0.282 ohm/km pure copper wire 99% current carrying capacity: 11 aMps acceptance criteria: item shouldd satisfied all mentioned specifications testing: testing is to be performed to verify all the mentioned specs.	
303	SNG99407	DO38012-003-0360-0	0000LLTRR7135 / MORES CABLE 30FT	G.M DETROIT FOR GRP BOATS MAKE USA	7 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
304	DNF98268	0582-16063 (999235744)	0582599235744 / COMBINED-BOW-LIGHT ITEMS REQ/LENS, RED, GREEN,	GRP BOATS	11 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			M/NAVIGATIONAL									
305	DNF99004	DEFSTAN 61-3PT1	0562799101155 / BATTERY DRY LECLANCHET YPE 90 1.5V 4.125X3. 187X8.703IN		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
306	DNF95989	CHINA A/P DESCRIPTION	0565799005691 / SOLDERING IRON ELECTRIC 25W 110/220V TIP PENCIL (CHINA BRAND)	SOLDING EQUIP.	11 / EACH/NUMBER	CHINA BRAND					TECHNICAL SPECIFICATION - 25W 110/220V TIP PENCIL GENERAL USE GENERAL SPECIFICATION - 25W 110/220V TIP PENCIL GENERAL USE	
307	DNF95487	1001-7928-01	0561UK5061888 / RADIATORY WIRE BOTTOM (SINGLE CORE)	ANTENNA MC/LP NTS LANDHI	250 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
308	DNG96722	1108833	2920715060537 / STARTER SELF 12V-CW-MODEL-1990472-TEETH 11 BASE SIZE 110X110	GM DETRIOT D/E-4-71 (MODEL 1042-5000)	1 / EACH/NUMBER	1042-5000					TECHNICAL SPECIFICATION - STARTER MOTOR SELF STARTER 12V DC TEETH 11 BASE SIZE 110X110 05 KG UPTO 15 KG (POWER) SEALED ELECTRICAL GENERAL SPECIFICATION - STARTER MOTOR SELF STARTER 12V DC TEETH 11 BASE SIZE 110X110 05 KG UPTO 15 KG (POWER) SEALED ELECTRICAL	
309	DNZ97931		4540CH5076895 / SUPPORT FOR WASH BASIN FOR JALALAT-II	JALALAT-II	25 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
310	DNZ95340		4820CH5074917 / GLOBE VALVE SIZE 3"	SPARES RETURN FROM D/YARD FOR JALALAT-II	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - GENERAL SPEC: KSI BRAND PN 16 CHINA GENERAL SPECIFICATION - GENERAL SPEC: KSI BRAND PN 16 CHINA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
311	DNF95534	654018	613099742571 1 / CHARGER MODULE	STATIC FREQUENCY CHANGER & ACCESSORIES	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - country of origin uk. BATTERY CHARGER /DC POWER SUPPLY AC (110/220 VAC AT 50/60 HZ DC FOR CHARGING LEAD ACID POWER TRANSFORMER RECTIFIER /REGULATOR CIRCUITRY GENERAL SPECIFICATION - country of origin uk. BATTERY CHARGER /DC POWER SUPPLY AC (110/220 VAC AT 50/60 HZ DC FOR CHARGING LEAD ACID POWER TRANSFORMER RECTIFIER /REGULATOR CIRCUITRY	
312	DNF97337	PP3 , 6F22, (6135-00-900-2139)	613570100411 8 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25.75X017MM	AVO METER	13 / EACH/NUMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
313	DNF97744	PP3 , 6F22, (6135-00-900-2139)	613570100411 8 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25.75X017MM	AVO METER	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
314	DNF94979	1354-01	625000299596 2 / STARTER FLUORESCENT 2PINS 110/220V	TUBE LIGHTES	300 / EACH/NUMBER						TECHNICAL SPECIFICATION - STARTER FLUORESCENT LAMP a. TERMINAL QTY: 2 b. BODY DIAMETER: 0.810 INCHES c. BODY LENGTH: 1.500 INCHES. d. LAMP WATAGE RATING WATTS: 4.0 AND 6.0 AND 8.0 e. LAMP CURRENT TYPE: AC. f. LAMP VOLTAGE RATING IN VOLTS: 118.0 MINIMUM AND 120.0 MAXIMUM g. STARTER TYPE: GLOW h. TERMINAL TYPE: TWIST TYPE. GENERAL SPECIFICATION - STARTER FLUORESCENT LAMP a.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>TERMINAL QTY: 2 b. BODY DIAMETER: 0.810 INCHES c. BODY LENGTH: 1.500 INCHES. d. LAMP WATAGE RATING WATTS: 4.0 AND 6.0 AND 8.0 e. LAMP CURRENT TYPE: AC. f. LAMP VOLTAGE RATING IN VOLTS: 118.0 MINIMUM AND 120.0 MAXIMUM g. STARTER TYPE: GLOW h. TERMINAL TYPE: TWIST TYPE.</p>	
315	DNF98241	CAT6 E/CAT 5E	701070511899 6 / STP CAT 5E/CAT6E NETWORK CABLE (4 PAIR) AMP/AVAYA (1000 FFFT)	FAWMIS NETWORKING CABLE	3 / ROLL						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
316	DNA97340	NO DATA AVAILABE	6685UK507204 0 / GAUGE TEMPRATURE 20-240 F	MAIN ENGINE	5 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - TEMPERATURE GUAGE (ENGINE COOLANT /ENGINE TEMP INDICATOR) 20 F TO 240 F ANALOG DIAL GUAGE WITH NEEDLE POINTER GENERAL SPECIFICATION - TEMPERATURE GUAGE (ENGINE COOLANT /ENGINE TEMP INDICATOR) 20 F TO 240 F ANALOG DIAL GUAGE WITH NEEDLE POINTER</p>	
317	DNG97605	ACB/MCC B 600A	000050000082 7 / AIR CIRCUIT BREAKER 600AMPS 500 VOLTS AC3PHASE 60HZ FUJIEA60		1 / EACH/NUMBER	EG603C					<p>TECHNICAL SPECIFICATION - 600 AMP (03 PHASE) 500 VOLTS AC (50/60 HZ) OVERLAD SHORT CIRCUIT TRIP (AIR BREAKER) TRIP TYPE: THERMAL MAGNETIC OR ELECTRONIC TRIP UNIT PANEL OR SWITCHBOARD MOUNT IEC/UL TYPE PROTECTION GENERAL SPECIFICATION - 600 AMP (03 PHASE) 500 VOLTS AC (50/60 HZ) OVERLAD SHORT CIRCUIT TRIP (AIR BREAKER) TRIP TYPE: THERMAL MAGNETIC OR ELECTRONIC TRIP UNIT PANEL OR SWITCHBOARD MOUNT</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											IEC/UL TYPE PROTECTION	
318	DNC96164	5321420215	2990725319134 / FLANGE		3 / EACH/NUMBER	BR2000 CR					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
319	DNO97978	GP-0183	7230775241051 / SHOWER CURTAIN		8 / EACH/NUMBER	Ecomotive 6.66					TECHNICAL SPECIFICATION - Not Know GENERAL SPECIFICATION - Not Know	
320	DNF96972	P19720-B21	7025795255196 / HPE PROLIANT DL380 SERVER WITH ACCESSORIES		1 / EACH/NUMBER	GEN 10 8sFF NC Configure to order					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
321	DNO97801	450-5413	5310775266884 / BRIDGE		16 / EACH/NUMBER	3516E					TECHNICAL SPECIFICATION - COMPONENT TYPE : VALVE BRIDGE MATERIAL: FORGED /MACHINED ALLOY STEEL HARDNESS: APPROX 50*60 HRC LUBRICATION: SPALASH OP TEMP: 200-250C GENERAL SPECIFICATION - COMPONENT TYPE : VALVE BRIDGE MATERIAL: FORGED /MACHINED ALLOY STEEL HARDNESS: APPROX 50*60 HRC LUBRICATION: SPALASH OP TEMP: 200-250C	
322	DNV99035	r1-e-9-26	6740705274793 / THERMAL PRINTER		2 / EACH/NUMBER	THERMAL PRINTER					TECHNICAL SPECIFICATION - 1.2 TB SSD GENERAL SPECIFICATION - 1.2 TB SSD	
323	DNO96480	349-7378/369-7561	6620775249941 / SENSOR GP-PRESSURE		1 / EACH/NUMBER	C9.3					TECHNICAL SPECIFICATION - SENSOR GP-PRESSURE GENERAL SPECIFICATION - SENSOR GP-PRESSURE	
324	DN096651	0610.155050.4.0	2815FP3030508 / O-RING		2 / EACH/NUMBER	TBD620V 12					TECHNICAL SPECIFICATION - O-RING circular cross - section sealing ring nbr / fluorocarbon (viton) NBR (-30 TO +100 c) VITON (-20 + 200c) GENERAL SPECIFICATION - O-RING circular cross - section sealing ring nbr / fluorocarbon (viton) NBR (-30 TO +100 c) VITON (-20 + 200c)	
325	DNF97737	05-00-5497-00 /	5810715300651 / PC AVATAR		1 / EACH/NUMBER	XIS-100XD					TECHNICAL SPECIFICATION - MACHINE LENGTH: 1524 MM.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		05-00-3395-00	- PC Based with Windows OS 7, Intel Core i7		UMBER						WIDTH: 770 MM, HEIGHT: 1212 MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM GENERAL SPECIFICATION - MACHINE LENGTH: 1524 MM, WIDTH: 770 MM, HEIGHT: 1212 MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM	
326	DNO97803	417-2406	5365775266826 / SPRING		1 / EACH/NUMBER	3516E					TECHNICAL SPECIFICATION - COIL SPRING HIGH GRADE SPRING STEEL HEAT TREATED ABSORBS SHOCK 0.1361 KG APPROX CATERPILLAR GENERAL SPECIFICATION - COIL SPRING HIGH GRADE SPRING STEEL HEAT TREATED ABSORBS SHOCK 0.1361 KG APPROX CATERPILLAR	
327	DNF98988	320623770280	5995705312146 / ufone 4g blaze device		1 / EACH/NUMBER	MF920U					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
328	DNO99030	3213-600GPD	4620705345046 / 600gpd commercial ro water purifier with pressure gauge and indicator board		1 / EACH/NUMBER	3213-600gpd					TECHNICAL SPECIFICATION - NAME: 600GPD COMMERCIAL RO WATER PURIFIER WITH PRESSURE GAUGE AND INDICATOR BOARD MODEL: 3213-600GPD SALT REJECTION RATE: 99.0% CAPACITY: 600GPD BRAND: HELLOPURE TYPE: 600GPD FLOW:95L/H TANK: 11G STEEL TANK GENERAL SPECIFICATION - NAME: 600GPD COMMERCIAL RO WATER PURIFIER WITH PRESSURE GAUGE AND INDICATOR BOARD MODEL: 3213-600GPD SALT REJECTION RATE: 99.0% CAPACITY: 600GPD BRAND: HELLOPURE TYPE: 600GPD FLOW:95L/H TANK: 11G STEEL TANK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
329	DNO96482	424-4490	3414775262396 / GEAR		1 / EACH/NUMBER	C 9.3					TECHNICAL SPECIFICATION - GEAR GENERAL SPECIFICATION - GEAR	
330	DNC96163	X59414500018/87	2815725300671 / EXHAUST PIPE BELOWS		3 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - WEIGHT: 13.500KG GENERAL SPECIFICATION - WEIGHT: 13.500 KG	
331	DNF96272	AS-MP5E-17	6920705208654 / AIMING SENSOR	G-3 SIMULATOR 2017	1 / ASSEMBLY	AS-MP5E-17	NA	M/S SOFT INOVATION SYSTEM 34-A/2, 1ST FLOOR LUXURY HOTEL, LALAZAR. MT KHAN ROAD KARACHI +9221385610277	M/S SOFT INNOVATIVE SYSTEMS		TECHNICAL SPECIFICATION - AIMING SENSOR AS-MP5E-17 TECHNOLOGY INFRA RED VOLTAGE 3.0 VDC-4.0 VDC +-10% CURRENT 100 MA +-20% GENERAL SPECIFICATION - AIMING SENSOR AS-MP5E-17 TECHNOLOGY INFRA RED VOLTAGE 3.0 VDC-4.0 VDC +-10% CURRENT 100 MA +-20%	