

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 22-04-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGT994 48	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	10 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
2	DGE100 045	YCR105 or 1260	830578516309 0 / CERAMIC FIBER CLOTH	GENRAL USE	100 / METER	YCR105		OEM:CHINA MANUFACTURERS NINGBO RUIFENG SEALING MATERIAL COMPANY LTD KUANGVAN TOWN CIXI : 86-574- 63531211.63531433.	PANASO NIC SADDAR KARACI. TECHNO POWER SYSTEM		<u>TECHNICAL SPECIFICATION -</u> size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, temperature resistance= 700 °C (degree centigrade), max thermal conductivity= 0.16 w/m.K <u>GENERAL</u> <u>SPECIFICATION -</u> size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, temperature resistance= 700 °C (degree centigrade), max thermal conductivity= 0.16 w/m.K	
3	DGE100	NIL	651570518127	NIL	5 /			LOCAL MARKET	NOT		<u>TECHNICAL SPECIFICATION - No</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	425		7 / TOWEL PAPER 24 ROLLS PER PACK		CARTON				KNOWN		of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 Inch GENERAL SPECIFICATION - No of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 Inch	
4	DGH100 438	614599521 8490	6145995218490 / CABLE POWER ELECTRICAL 3CORE 440V 34A	CABLES	1500 / METER	DG SHIPS 212	NA	MINISTRY OF DEFENCE (NAVY) SHIPS SUPPORT AGENCY DME ME253, ROOM 19, BLOCK B FOXHILL, BATH, UK TEL: 01225 883293 FAX: 01225 883548	DG SHIPS 212 UK		TECHNICAL SPECIFICATION - AS PER NMCRL AND DG SHIPS 212 GENERAL SPECIFICATION - AS PER NMCRL AND DG SHIPS 212	
5	DGE100 453	NIL	721050515517 2 / FIRE RETARDANT SPRING MATTRESS (L6' X W2' X H6")	MATRESSES FOR BED	25 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		TECHNICAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 GENERAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
6	DGE995 82	NIL	721050515517 2 / FIRE RETARDANT SPRING MATTRESS (L6' X W2' X H6")	MATRESSES FOR BED	2 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		TECHNICAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 GENERAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
7	DGE100 105	ASTM D 6413	721050515517 4 / FIRE RETARDANT SPRING MATTRESS (L6.5'XW2.5'H6)	MATRESSES FOR BED	8 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		TECHNICAL SPECIFICATION - FIRE RETARDANT SPRING MATTRESS (L6.5'XW2.5'H6) GENERAL SPECIFICATION - FIRE RETARDANT SPRING MATTRESS (L6.5'XW2.5'H6)	
8	DGE997 18		042270515841 1 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	3000 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTIC S, SADDAR KARACHI		TECHNICAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
9	DGE997		042270515841	SELF	2000 /			M/S ANWAR PLASTICS,	M/S		TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	64		1 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)		SQ FEET			SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	ANWAR PLASTIC S, SADDAR KARACHI		SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM <u>GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM</u>	
10	DGE997 09	GGG-H-142	841500935190 6 / SAFETY HELMET YELLOW	PERSONAL PROTECTION	30 / EACH/N UMBER			FEDERAL SPECIFICATIONS UNITED STATES CAGE CODE 81348	FEDERAL SPECIFIC ATIONS		<u>TECHNICAL SPECIFICATION - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000</u> <u>GENERAL SPECIFICATION - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000</u>	
11	DGB995 57	Morgan TPC 843	047479520862 6 / Morgan Silicon Carbide Crucible, Top Dia: 420MM, Bottom Dia: 295MM	TILTING FURNACE NO 3006 TYPE CA F-23 (PLL) RECORD	1 / EACH/N UMBER	N/A	N/A	MOLTEN ADVANCED MATERIALS PLC REGISTERED IN ENGLAND AND WALES REGISTRATION NO 286773 & INDIA MANUFACTURED	MORGAN ITE CRUCIBL E LTD		<u>TECHNICAL SPECIFICATION - Morgan Silicon Carbide Crucible, Height: 675MM, Top Dia: 420MM, Bottom Dia: 295MM, Part No. TPC 843 (drawing enclosed)</u> <u>GENERAL SPECIFICATION - Morgan Silicon Carbide Crucible, Height: 675MM, Top Dia: 420MM, Bottom Dia: 295MM, Part No. TPC 843 (drawing enclosed)</u>	
12	DGE994 53	RSAFE-RG01	841570520869 6 / hvbss GLOVES	MSW TEAM	50 / PAIR	NIL	NA	PLOT NO 433, SECTOR 7/A KORANGI INDUSTRIAL AREA KARACHI PHONE NO: 0092-21-35122452 FAX NO: 0092-2135122453 CELL NO: 00923332300653 WEBSITE: www.ras-sons.com E Mail: shoukat123@cyber.net.pk	RASHEE D AHMED AND SONS PAK		<u>TECHNICAL SPECIFICATION - BACK FINGER TIPS WITH COW SHIP LEATHER THUMB AND SIDE PATCH PROTECTION HELO REPELLING</u> <u>GENERAL SPECIFICATION - BACK FINGER TIPS WITH COW SHIP LEATHER THUMB AND SIDE PATCH PROTECTION HELO REPELLING</u>	
13	DGE100 054	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	1000 / EACH/N UMBER	SSP-01-LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTA N		<u>TECHNICAL SPECIFICATION - AS PER LETTER ATTACH</u> <u>GENERAL SPECIFICATION - AS PER LETTER ATTACH</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
14	DGE100420	-	561099200438 6 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	50 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCR ETE UK LTD THE FLOORIN G TECHNO LOGIES CENTRE BOOTH LANE SANDBA TCH CHESHIR E CW11 3QF UK PH:+44(0) 1270 753000 & FAX :+44 (0)1270 753333		TECHNICAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&I(M) DC&FF <u>GENERAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&I(M) DC&FF.</u>	
15	DGE99302	-	561099200438 6 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	5 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCR ETE UK LTD THE FLOORIN G TECHNO LOGIES CENTRE BOOTH LANE SANDBA TCH CHESHIR E CW11 3QF UK PH:+44(0) 1270 753000 & FAX :+44 (0)1270 753333		TECHNICAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&I(M) DC&FF <u>GENERAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&I(M) DC&FF.</u>	
16	DGE100212	NO DATA AVAILABLE	035059923357 6 / FENDER MARINE ROUND SISAL	MARINE ROUND SISAL WT 71 LBS OVERALL DIA	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10" <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			WT 71 LBS OVERALL DIA 2'6 INTERNAL DIA 10"	2'6							MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'6" INTERNAL DIA 10"	
17	DGE997 12		046150461015 1 / POLISHING FELT ROUND DIA 200 MM THICKNESS 38 MM		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
18	DGE995 48		047659000006 2 / GLOVES LEATHER LEFT HAND.		47 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable GENERAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable	
19	DGE995 47	NO DATA AVAILABL E	047659000006 3 / GLOVES- LEATHER RIGHT HAND		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10 GENERAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10	
20	DGE993 38	NO DATA AVAILABL E	047659943474 3 / TUFF GRADE 1" PAINT BRUSH	HANGAR DOOR	12 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch GENERAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch	
21	DGE992 73	NO DATA AVAILABL E	055979002055 2 / INSULATION TAPE ELECTRICAL SHRINKABLE	GENERAL ELECTRIC USE	4 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WD 2IN RUBBER									
22	DGE100065	NO DATA AVAILABLE	0559790020552 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	30 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DGE99305	0413-2433 (4720-99-923-8770)	0413599238770 / HOSE RUBBER INTERNAL 0.625"X0.875" X60FT		70 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
24	DGE100428	0.75X0.007INCH-50MTR-	0559790015244 / INSULATION-TAPE-VARNISHED WOVEN GLASS-FIBRE-(STRAIGHT CUT)		15 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
25	DGE100092		0414599230911 / PACKING MATERIAL HEMP FOR FURNACE FUEL, SIZE= 1/4" SQ		35 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DGE99746		0461590000976 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE NO.0		120 / SHEET	local					TECHNICAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0 GENERAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0	
27	DGE99270		0461590000976 / PAPER ABRASIVE 9" X11" WATER PROOF		25 / SHEET	local					TECHNICAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0 GENERAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MATERIAL GLASS GRADE NO.0									
28	DGE997 13	NIL	047659000775 8 / GLOVES SEAMLESS DIPPED RUBBER		25 / PAIR	202- GNFG					TECHNICAL SPECIFICATION - a. Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc GENERAL SPECIFICATION - a. Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc	
29	DGE997 48	NO DATA AVAILABL E	046159000098 0 / CLOTH ABRASIVE 9		30 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
30	DGE997 63		046259000598 9 / TUBING PLASTIC POLYTHYNE LAY FLAT 0.005"TH.WD. 27"WEIGHT PER		30 / KILOGR AMME						TECHNICAL SPECIFICATION - TUBING PLASTIC POLYTHYNE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches thickness: 0.005 inches (DOUBLE SIDE) GENERAL SPECIFICATION - TUBING PLASTIC POLYTHYNE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches thickness: 0.005 inches (DOUBLE SIDE)	
31	DGE100 361	NIL	055979444489 8 / INSULATION	GENERAL ELECTRIC USE	10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SLEEV ELEC INT DIA 3MM THICK0.500 MATER CERAMIC								AVAILABLE	
32	DGB100 094		027779910621 5 / SPANNER BOX TUBULAR DOUBLE ENDED 1.000 X1.125 W 0.875X1.000		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
33	DGB995 76	NO DATA AVAILABL E	028370000164 1 / SILVER SOLDER EASYFLO FOR STAINLESS STEEL IN ROD FORM		2700 / GRAM						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DGE993 01	NO DATA AVAILABL E	041354600479 4 / EAR DEFENDER LARGE SIZE		30 / PAIR	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
35	DGB995 72		028359351743 1 / ALUMINIUM BRONZE INGOT		45 / KILOGR AMME						TECHNICAL SPECIFICATION - 1076 D GENERAL SPECIFICATION - 1076 D	
36	DGE992 88	NO DATA AVAILABL E	041354600479 2 / EAR DENFENDER- SMALL SIZE		30 / PAIR	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DGE997 61	TYRE 10X03	041159000692 0 / TRUCK HAND PLATFORM 4- WHEELED TURNTABLE 60X36X15" CAP2240LBS		4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DGE100 213	NIL	035059571323 1 / ROPE SISAL, HAWSERLAID, 3-STRD, CIRC: 1, 1/8 INCH		1500 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DIA: 10-MM								ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
39	DGB100 175		021450214058 9 / BOLT AND NUTS STEEL HEX HD SZ 2.500X0.875 IN		100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> material: ms bsw Length of bolt: 38 mm length of thread: full thread diameter: 06 mm shape: hex MATERIAL GRADE EN4140 <u>GENERAL SPECIFICATION -</u> _material: ms bsw Length of bolt: 38 mm length of thread: full thread diameter: 06 mm shape: hex MATERIAL GRADE EN4140	
40	DGH100 076		021250212049 0 / BAR STEEL CHANNEL SIZE 3.50"X2" X5/16"		10 / METER						<u>TECHNICAL SPECIFICATION -</u> Item Specification:BS EN OF 2004, GRADE S-275 JRG <u>GENERAL SPECIFICATION -</u> Item Specification:BS EN OF 2004, GRADE S-275 JR	
41	DGB995		021459013141		3300 /						<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	77		4 / BOLT MACHINE, THREAD SERIES: BSF, MEDIUM CLASS, HEXAGON, SIZE (0.875X3.500X1.750 INCH)		EACH/NUMBER						HEAD: HEXAGON, THREAD SIZE: 7/8 INCH, NOMINAL LENGTH: 3 1/2 INCH, LENGTH OF THREAD: 1 3/4 INCH. SPECIFICATION: DEF STAN 02-862 Part 2, Issue 3 Class III, MATERIAL GRADE: BS EN 10269 42CrMo5-6 (OR) BS EN 10269 40CrMoV4-6 GENERAL SPECIFICATION - HEAD: HEXAGON, THREAD SIZE: 7/8 INCH, NOMINAL LENGTH: 3 1/2 INCH, LENGTH OF THREAD: 1 3/4 INCH. SPECIFICATION: DEF STAN 02-862 Part 2, Issue 3 Class III, MATERIAL GRADE: BS EN 10269 42CrMo5-6 (OR) BS EN 10269 40CrMoV4-6	
42	DGB100114		027279910879 5 / DRILL TWIST HIGH SPEED STEEL DIA 1-5/16" (1.3125) FLUTE LG		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
43	DGB99677		021479013080 8 / BOLT, MACHINE, THREAD SERIES: BSF, HEX HD	BR 320 D/78	25 / TEN						TECHNICAL SPECIFICATION - THREAD SIZE: 1/2 INCH. NOMINAL LENGTH: 2 INCH. LENGTH OF THREAD: 1 INCH. MATERIAL SPECS PD970:2005 MATERIAL GRADE EN16(605 M36) or EN100 (945 M38), HEAT TREATMENT CONDITION: R as per BR-320D (Catalog of Naval Stores) OEM COC/MTC REQUIRED GENERAL SPECIFICATION - THREAD SIZE: 1/2 INCH. NOMINAL LENGTH: 2 INCH. LENGTH OF THREAD: 1 INCH. MATERIAL SPECS PD970: 2005 MATERIAL GRADE EN16(605 M36) or EN100 (945 M38), HEAT TREATMENT CONDITION: R as per BR-320D (Catalog of Naval Stores) OEM COC/MTC REQUIRED	
44	DGB100437	AWS E308-16	028370001185 3 /	WELDING SYSTEMS	6 / KILOGR						TECHNICAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ELECTRODE WELDING LG 10	(STAINLESS STEEL)	AMME						13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface GENERAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm-13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
45	DGE99300	NO DATA AVAILABLE	0413546004793 / EAR DEFENDER MEDIUM SIZE		30 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DGB100174		0214590130806 / Bolt Machine, Thread Series: BSF, Medium Class, Head: Hexagon, Thread Size: 1/2", Nominal Length: 1 1/2", Length of Thread 1"	BR 320D/78	6 / TEN						TECHNICAL SPECIFICATION - DGS 8060 Class 1(B), BS 970. Material Grade EN16 (605 M36) or EN 100 (945 M38), Condition: R GENERAL SPECIFICATION - DGS 8060 Class 1(B), BS 970. Material Grade EN16 (605 M36) or EN 100 (945 M38), Condition: R	
47	DGB100172		0214590130809 / BOLT MACHINE STEEL BSF HEX HD SZ 0.500X2.250X1.000 IN		31 / TEN						TECHNICAL SPECIFICATION - MATERIAL GRADE EN 4140 GENERAL SPECIFICATION - MATERIAL GRADE EN 4140	
48	DGB100093		0274502741418 / GUN GREASE		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DGB99455	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE, DOOR NOT LESS THAN 3/8" THK-	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03 GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MINIMUM. 03	
50	DGD100196	S NO 32 MODEL 2018	003550000038 6 / MINCING MACHINE MEDIUM		1 / EACH/NUMBER	2018					TECHNICAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450 GENERAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450	
51	DGD96806	NO DATA AVAILABLE	003154600077 1 / DISH VEGETABLE (DONGA) GOLDEN CRESTED		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - (Ceramic) with (lid) cover GENERAL SPECIFICATION - (Ceramic) with (lid) cover	
52	DGH100203	BS EN 10025-2/2004, MATERIAL GRADE S 275 JR	021259571071 8 / ANGLE STEEL CARBON E/S BLACK 1.25 X 1.25 X 0.25 INCH		60 / METER						TECHNICAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mArterial grade s 275 jr GENERAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mArterial grade s 275 jr	
53	DGB100160		026759521327 8 / PIPING STEEL GALVANIZED SEAMLESS, L 6.1 M, E/DIA 26.9MM, TH 2.6 MM, N/BORE:19.1 MM	UTS LENGTH. BULK SUPPLY	60 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS GENERAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS	
54	DGE100432	NO DATA AVAILABLE	033054600448 4 / HEAVING LINE 06MM L50MM 466MS	MSI	660 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DGB100106		132572335001 0 / BLADE POWER HACK SAW HSS 18X1-1/2X0.075" 6TPI		5 / EACH/NUMBER	AISI M2 HSS (Super Hardened)					TECHNICAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 1/2 x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened) GENERAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 1/2 x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened)	
56	DGB995		132572335001		20 /	AISI M2					TECHNICAL SPECIFICATION - 450	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	65		0 / BLADE POWER HACK SAW HSS 18X1-1/2X0. 075" 6TPI		EACH/ UMBER	HSS (Super Hardened)					x 38 x 2 (mm) 18 x 1 ½ x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened) <u>GENERAL</u> <u>SPECIFICATION</u> - 450 x 38 x 2 (mm) 18 x 1 ½ x 0.075 (inches) GRADE AISII M2 HSS (Super Hardened)	
57	DGE992 86	81349, MIL-H- 15217	472000203633 3 / HOSE RUBBER, NON- METTALIC, INTERNAL DIA 1", NO OF LAYERS= 4, (IMPREG. FAB), LENGTH= 50 FT		150 / FOOT						<u>TECHNICAL SPECIFICATION</u> - tech specs: Internal dia = 1 Inch, EQUILANT= 4-PLY, RUBBER TYPE/ FLEXIBLE, MINIMUM Working Pressure = 10 Bar, Maximum Working pressure = 30 Bar, Temp Range = -35 to 80 °C, Packing = Plastic Paper oem coc/DOCUMENTS /dealer certificate= REQUIRED, PARENT EQUIP= CHIPPING MACHINE <u>GENERAL</u> <u>SPECIFICATION</u> - tech specs: Internal dia = 1 Inch, EQUILANT= 4- PLY, RUBBER TYPE/ FLEXIBLE, MINIMUM Working Pressure = 10 Bar, Maximum Working pressure = 30 Bar, Temp Range = -35 to 80 °C, Packing = Plastic Paper oem coc/DOCUMENTS /dealer certificate= REQUIRED, PARENT EQUIP= CHIPPING MACHINE	
58	DGE100 266	NO DATA AVAILABL E	402099923712 4 / ROPE NYLON (POLYAMIDE) HAWSERLAID, DIA: 12-MM, 3- STRAND, WHITE	GEMNI CRAFT	280 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - 1. MIN BK STRENGTH 2.9 TONN COIL, WEIGHT: 23 KILOS, 2. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 3. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 4. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 5. LENGTH: PER COIL: 220 METER. 6. OEM COC REQUIRED. <u>GENERAL</u> <u>SPECIFICATION</u> - 1. MIN BK STRENGTH 2.9 TONN COIL, WEIGHT: 23 KILOS. 2. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											3. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 4. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 5. LENGTH: PER COIL: 220 METER. 6. OEM COC REQUIRED.	
59	DGE997 44	NO DATA AVAILABL E	422079502032 8 / DINGHY BUOYANCY AID LIFE JACKET SM/ADULT		20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
60	DGE100 354	NO DATA AVAILABL E	422079505519 3 / WHISTLE PLASTIC FOR GENERAL SERVICE LIFE JACKET	LIFE JACKET MK-1,ORALLY INFLATED	5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
61	DGB995 52	0251-9681	401099411968 1 / CHAIN WELDLESS BRASS B13304 429012BR	ELECTRO HYDROLIC STEEING GEAR BALL SHAH	2 / EACH/N UMBER	PUMP					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
62	DGE100 091	nil	533000038292 2 / PACKING- MATERIAL	FUEL OIL SERVICE PMP	33 / METER						<u>TECHNICAL SPECIFICATION - SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON- ASBESTOS, TEM UPTO: 400 °C</u> <u>GENERAL SPECIFICATION - SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON- ASBESTOS, TEM UPTO: 400 °C</u>	
63	DGE997 10	A-A-1201, P-P-121, ANSIB74- 18	535000186882 0 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE 110-A		65 / SHEET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
64	DGT100 435	NO DATA AVAILABL E	553070504293 3 / PLY WOOD NATURAL TEAK FINISH ONE SIDE (NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W= 4' TH=03mm to 04mm	PRESENTATIO N BOXES FOR VVIPS	128 / SQ FEET						TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm GENERAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm	
65	DGE994 56	MIL-P- 15280	564000237482 7 / INSULATION SLEEVING THERMAL		15 / EACH/N UMBER						TECHNICAL SPECIFICATION - mil- p-15280 Sleeve Sizes: LENGTH: 72- INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p- 15280 Sleeve Sizes: LENGTH: 72- INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
66	DGE994 59	MIL-P- 15280	564000237482 8 / INSULATION SLEEVING THERMAL		15 / EACH/N UMBER						TECHNICAL SPECIFICATION - MIL- P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
67	DGE100 042	NO DATA AVAILABL E	593572507749 3 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 35/12, LG 01 METER		50 / METER						TECHNICAL SPECIFICATION - A. Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW-3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714, Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion. GENERAL SPECIFICATION - A. Product Category :Dual Wall B. Product Name: TAT-25 C. Operating Temperature °C: -55 to 110 D. Min Full recovery TEMPERATURE °C: 121 E. Color: Standard Black F. Specification: TAT-125 SCD; RW-3032; AS23053/4, Cl. 2; UL 224 G. Flammability rating: ASTM D26714, Procedure B H. Typical Application: Insulate and protect electrical connections, wires and cables from environmental factors like moisture, heat and abrasion.	
68	DGE100 043	NO DATA AVAILABL E	593572507749 4 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 31/8 LG, 01 METER		50 / METER						TECHNICAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B. PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224</p> <p>G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT AND ABRASION. <u>GENERAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B. PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK</u></p> <p>F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224</p> <p>G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT AND ABRASION.</p>	
69	DGE100423	NIL	792070510179 1 / BROOM NYLON SIZE:1. X2"(BRUSH NYLON)		3 / DOZEN						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
70	DGE99747	NO DATA AVAILABL E	04135000004 0 / SHEET EBONITE WHALE BRAND TYPE 1 LG.48		3 / SHEET	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
71	DGE99309	NO DATA AVAILABL E	04625000001 8 / INSECTICIDE EMULSION		5 / LITER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
72	DGE99743	DATA AVAILABL E	04615000015 2 / POLISHING-		4 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FELT ROUND								40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch GENERAL SPECIFICATION - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch	
73	DGE100422	NO DATA AVAILABLE	792000543649 2 / PAPER TOWEL		5 / BOX						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DGE100057	NO DATA AVAILABLE	043250000002 7 / HELMET PROTECTIVE DESPATCH RIDER WITH VISOR SIZE 6 3/4		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218) GENERAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218)	
75	DGE99481		813570504263 2 / STRETCH FILM WRAPPER SIZE 20"X30" IN	PACKING MATERIAL L&E BRANCH NSSD	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
76	DGE100077	NO DATA AVAILABLE	046150000002 4 / PAPER ABRASIVE 9" X11" WATERPROOF MATERIAL EMERY GRADE P-		10 / SHEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			120D									
77	DGE997 62	NO DATA AVAILABL E	046150000008 6 / GOGGLE CHIPPING		45 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.</p> <p><u>GENERAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.</p>	
78	DGT100 436	NO DATA AVAILABL E	010000000000 3 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	192 / SQ FEET	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
79	DGE100 058	R	834570504262 9 / Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter)	ITEM REQUIRED FOR MAKING OF GIFT BOXES	30 / METER						<p><u>TECHNICAL SPECIFICATION -</u> Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											boxes GENERAL SPECIFICATION - Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes	
80	DGE997 17	NO DATA AVAILABL E	834050503926 1 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIE S 3 IN NO		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length. 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhalar : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos GENERAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos	
81	DGE100 198	NO DATA AVAILABL E	834050503926 2 / QANAT COMPLETE SIZE 18.X 7. OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		6 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION -</u> Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). ζ Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON,BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.GENERAL SPECIFICATION - Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). ζ Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
82	DGE100333	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	2 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAGE					<p>STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.</p> <p><u>TECHNICAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p> <p><u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
83	DGE997 15	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATIO N	3 / EACH/N UMBER	OPTICAL INFRARE D CAMOUF LAGE NET, ANTI RADAR CAMOUF LAG					TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p>	
84	DGT995 63	NO DATA AVAILABL E	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	64 / SQ FEET	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 GENERAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
85	DGT100 431	NO DATA AVAILABL E	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	640 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 GENERAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
86	DGT100 178	NO DATA AVAILABL E	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	192 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 GENERAL SPECIFICATION - 1. BS-6566 OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
87	DGT100 434	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	96 / SQ FEET	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p>GENERAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop	
88	DGT100 433	NO DATA AVAILABL E	010050000002 8 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLYS OF SHESHAM WOOD) 5-PLY	2.440X1. 220MTRX6. 35MM) SPECE/BS- 1088	96 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, GENERAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,	
89	DGT100 197	NO DATA AVAILABL E	010050000002 9 / Ply wood, Marine All Shesham, 13- Ply, GD-II,		64 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(WBP, Treated with Preservative) Size: L=8FT, W=4FT, TH=25MM, (Core inner plies & veneer) (Wood Should be all Shesham)								METERGENERAL SPECIFICATION - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER	
90	DGD100188	NO DATA AVAILABLE	024750000019 / GAS BURNER WITH HANDLE VALVE FITTED IN A ROUND STEEL FRAME TH 6mm, H 8" WITH 20FT RUBBER TUBE		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - ROUND STEEL FRAME THickness: 6MM, Hieght: 8" WITH 20FT RUBBER TUBE GENERAL SPECIFICATION - ROUND STEEL FRAME THickness: 6MM, Hieght: 8" WITH 20FT RUBBER TUBE	
91	DGE100062	NO DATA AVAILABLE	7330701002289 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDUS/JOY0).		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - WITH FULLCOVER GENERAL SPECIFICATION - WITH FULLCOVER	
92	DGE99268	NO DATA AVAILABLE	7330701002289 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDUS/JOY0).		9 / EACH/NUMBER						TECHNICAL SPECIFICATION - WITH FULLCOVER GENERAL SPECIFICATION - WITH FULLCOVER	
93	DGE100421	NO DATA AVAILABLE	9330705054354 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PN CREST	2 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
94	DGT99579	BELFONT TRUWOOD TEAK	9330992246097 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		5 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
95	DGE100364	NIL	9340731000995 / E-GLASS FIBER (POWDER) CHOPPED STRAND MAT	GRP BOATS	150 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2 GENERAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2	
96	DGE99708	GGGH142	8415009353137 / HELMET SAFTY		78 / EACH/NUMBER						TECHNICAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 brochure attached as document GENERAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 brochure attached as document	
97	DGD100173	ss-1000-ls	7340705101873 / LUNCH TRAY STAINLESS STEEL 4 COMPARTMENT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	275 / EACH/NUMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE GENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
98	DGD100358	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTMENT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	275 / EACH/NUMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE GENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE	
99	DGD100048	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTMENT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	259 / EACH/NUMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE GENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE	
100	DGD99580	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTMENT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	275 / EACH/NUMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE GENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE	
101	DGD100262	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTMENT	MESS UTENSILS, OFFICER WARD PNS SHIFA	275 / EACH/NUMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NT PLATES DINNER MESS PLATES								SAMPLEGENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE	
102	DGD997 11	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTME NT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	250 / EACH/N UMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLEGENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE	
103	DGD100 110	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTME NT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	259 / EACH/N UMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLEGENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE	
104	DGE100 046	NO DATA AVAILABL E	955573043028 2 / INSULATING SLEEVE		6 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DGD997 39		00355000052 0 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" H12 TO 14" TH 10 SWG WITH OUT		4 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD). DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER GENERAL SPECIFICATION - SPECIFICATION:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COVER								FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
106	DGE100426	NO DATA AVAILABLE	0559780000183 / SLEEVE PLASTIC GREEN 0.3X3 55P(DELETED NS/TD/32/611DT280989)		5 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DGE100059		8345705119862 / SATTON CLOTH WHITE	PRESENTATION VIP ITEM	30 / METER						TECHNICAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches GENERAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches	
108	DGE99303	NO DATA AVAILABLE	7920FP0010003 / SOFT CLOTH		12 / BAG	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
109	DGE99716	5012568166895	4020993960753 / ROPE FIBROUS, POLYESTER/ PROPYLENE MIX, 08-STRAND, DIA: 40MM		660 / METER						TECHNICAL SPECIFICATION - SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 40-MM DIA BLACK BERTHING POLYESTER/ PROPYLENE MIX. 8-STRAND MOORING NUMBER-5, MBL 26.4 TONNES, MB-67 TABLE-3, 3.8, PLAIN ENDS UV STABILISED ISO 9554 of 2019. 3. STANDARD ACCORDANCE TO ISO 2307 PACKAGING. 4. STANDARD OF MANUFACTURE ISO 2307 OF 2019 5. CONFIRMATION OF STANDARD EN-ISO 2307 OF 2019. 6. 220 METER PER COILS. 7. CERTIFICATIONS: VALID LLOYD TEST CERTIFICATE REQUIRED INDICATION BATCH/LOT NUMBER OF IDENTIFICATION AND WORKING / BREAKING AND STRENGTH OF STORES. 8. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM Phone: +44(0) 1323444444 EMAIL: sales@marlowropes.com</p> <p><u>GENERAL SPECIFICATION - SPECIFICATION:</u></p> <p>1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 40-MM DIA BLACK BERTHING POLYESTER/ PROPYLENE MIX, 8-STRAND MOORING NUMBER-5, MBL 26.4 TONNES, MB-67 TABLE-3, 3.8, PLAIN ENDS UV STABILISED ISO 9554 of 2019. 3. STANDARD ACCORDANCE TO ISO 2307 PACKAGING. 4. STANDARD OF MANUFACTURE ISO 2307 OF 2019 5. CONFIRMATION OF STANDARD EN-ISO 2307 OF 2019. 6. 220 METER PER COILS. 7. CERTIFICATIONS: VALID LLOYD TEST CERTIFICATE REQUIRED INDICATION BATCH/LOT NUMBER OF IDENTIFICATION AND WORKING / BREAKING AND STRENGTH OF STORES. 8. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM Phone: +44(0)</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											1323444444 EMAIL: sales@marlowropes.com	
110	DGB100 351	Aw- AL20/500	614573534449 4 / Solid Aluminium Wire 2.0mm for E fence		33600 / METER	N/A					<p><u>TECHNICAL SPECIFICATION -</u> 2mm Solid Aluminium Wire Material Aluminium Alloy Diameter 2.0mm Resistance 14 Ohms/km breaking Strength 96 Kg weight 3.3kg/roll</p> <p><u>GENERAL SPECIFICATION - 2mm</u> Solid Aluminium Wire Material Aluminium Alloy Diameter 2.0mm Resistance 14 Ohms/km breaking Strength 96 Kg weight 3.3kg/roll</p>	
111	DGE100 356	ITD/SP- GCF/ tpt400- f1755 (DITD)	830559533484 7 / GLASS CLOTH FIBER, PLAIN WEAVE, COLOUR NATURAL, FOR LAGGING PURPOSE		25 / METER	SP-GCF/ TPT400- F1755					<p><u>TECHNICAL SPECIFICATION -</u> <u>MATERIAL AND MANUFACTURE 1.</u> Requirements for the materials and methods of manufacture, plus physical thermal and other properties of Glass fiber product used for specific applications, a/c to Annexes B to E of this specifications. a . Yarn: The yarn shall be made from Type E low alkali glass. Unless otherwise stated in the PN Specifications /contract or order the yarn construction shall be: 2/136 Tex OR EC9 136Zx 2S. b. Nominal Yarn Count: The yarn for both warp and weft of the Glass cloth fiber shall be spun yarn with a construction given at Annex B. c. Cloth: The cloth shall be a double equal plain cloth stitched together by both Warp and weft and repeated over 24 ends and 24 picks; and have 142 warp ends and 142 weft picks per 10 cm. tolerance \pm 2.5%. Unless otherwise stated in the PN Specifications /contract. d. Weight: The weight of the cloth shall be 800 g/m . A tolerance 2 of \pm 10 g/m will be permitted. Unless otherwise stated in the PN Specifications / contract. e. Width: Unless otherwise stated in the contract or order, the width of the cloth, including selvedge, shall be 1.5</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>m (51 inches). A tolerance of $\pm 1.5\%$ will be permitted. Unless otherwise stated in the PN Specifications /contract. f. Length: Unless otherwise stated in the contract or order, the length of the cloth shall be 50-60 m. A tolerance of ± 05 m will be permitted. Unless otherwise stated in the PN Specifications /contract. g. Selvedge: The cloth is to be uniformly woven. The selvages are to be either fully woven or tucked feather, well made, substantially straight and even, and are to have the same tension as the remainder of the cloth. A plain feather selvedge is not acceptable. Unless otherwise stated in the PN Specifications /contract. h. Finish: The woven cloth is to be given a finishing treatment that locks the weave so that the amount of loose fiber released when the material is cut is reduced to the minimum. The amount of weave locking is not to be so great as to seriously affect the handling and draping qualities necessary to ensure the satisfactory use of the GCF as a covering for insulation blankets. The finishing treatment is to be compatible with the vapor barriers/coatings as specified in DEFSTAN 02 -703 and DEF STAND 02-805 part 1. <u>GENERAL SPECIFICATION - MATERIAL AND MANUFACTURE</u> 1. Requirements for the materials and methods of manufacture, plus physical thermal and other properties of Glass fiber product used for specific applications, a/c to Annexes B to E of this specifications, a . Yarn: The yarn shall be made from Type E low alkali glass. Unless otherwise stated in the PN Specifications /contract or order the yarn construction shall be: 2/136</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Tex OR EC9 136Zx 2S. b. Nominal Yarn Count: The yarn for both warp and weft of the Glass cloth fiber shall be spun yarn with a construction given at Annex B. c. Cloth: The cloth shall be a double equal plain cloth stitched together by both Warp and weft and repeated over 24 ends and 24 picks; and have 142 warp ends and 142 weft picks per 10 cm. tolerance $\pm 2.5\%$. Unless otherwise stated in the PN Specifications /contract. d. Weight: The weight of the cloth shall be 800 g/m . A tolerance 2 of ± 10 g/m will be permitted. Unless otherwise stated in the PN Specifications / contract. e. Width: Unless otherwise stated in the contract or order, the width of the cloth, including selvedge, shall be 1.5 m (51 inches). A tolerance of $\pm 1.5\%$ will be permitted. Unless otherwise stated in the PN Specifications /contract. f. Length: Unless otherwise stated in the contract or order, the length of the cloth shall be 50-60 m. A tolerance of ± 05 m will be permitted. Unless otherwise stated in the PN Specifications /contract. g. Selvedge: The cloth is to be uniformly woven. The selvages are to be either fully woven or tucked feather, well made, substantially straight and even, and are to have the same tension as the remainder of the cloth. A plain feather selvedge is not acceptable. Unless otherwise stated in the PN Specifications /contract. h. Finish: The woven cloth is to be given a finishing treatment that locks the weave so that the amount of loose fiber released when the material is cut is reduced to the minimum. The amount of weave locking is not to be so great as to seriously affect the</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											handling and draping qualities necessary to ensure the satisfactory use of the GCF as a covering for insulation blankets. The finishing treatment is to be compatible with the vapor barriers/coatings as specified in DEFSTAN 02 -703 and DEF STAND 02-805 part 1.	
112	DGD100 208	QSB-01	731070526966 3 / SOUNDLESS BLENDER		1 / EACH/N UMBER	QSB-01					TECHNICAL SPECIFICATION - MATERIAL ABS+UNBREAKABLE PC/TRITAN, TOUCH PAD CONTROL PANEL, EASY OPERATION, 1800W POWERFUL COPPER MOTOR, HIGH SPEED 27000-30000 RPM <u>GENERAL SPECIFICATION - MATERIAL ABS+UNBREAKABLE PC/TRITAN, TOUCH PAD CONTROL PANEL, EASY OPERATION, 1800W POWERFUL COPPER MOTOR, HIGH SPEED 27000-30000 RPM</u>	
113	DGB995 58	VE-SB-305	545050533279 4 / SIDE BRACKET 1FT		105 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - null <u>GENERAL SPECIFICATION - null</u>	
114	DGH873 82	NO DATA AVAILABL E	5305ZO656804 5 / LAWN MOVER MACHINE		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - <u>GENERAL SPECIFICATION -</u>	
115	DGB746 13	0140	403079515388 7 / SPLIT THIMBLES (316 STAINLESS STEEL)10MM	TAL SHIP SAILING RIG	14 / EACH/N UMBER			BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST,HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE. MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE. CO.UK	UK		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY ; BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE. SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX:+44(0) 1489578835. <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILITY ;BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST,</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET.COM.WEB:WWW.BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX;+44(0) 1489578835.	
116	DGT977 58	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	104 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
117	DGD100 582	JE-01	732070526966 4 / STAINLESS STEEL JUICE EXTRACTOR		1 / EACH/N UMBER	UDZZ- A2000					TECHNICAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201 GENERAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201	
118	DGD100 580	SSD-1	733070526967 7 / DECK PIZZA OVEN WITH GI STAND (ELECTRIC)		1 / EACH/N UMBER	ssd-1					TECHNICAL SPECIFICATION - one deck 2 tray capacity, lpg/natural gas operated, tray size 400x600mm, 220v/1000w (voltage and power), net weight 115kg, dimention. 1400x900x780mm GENERAL SPECIFICATION - one deck 2 tray capacity, lpg/natural gas operated, tray size 400x600mm, 220v/1000w (voltage and power), net weight 115kg, dimention. 1400x900x780mm	
119	DGE649 31	CTLCB100 08025	534073526741 0 / CANTILEVER BRACKET 3'		72 / EACH/N UMBER	CANTILE VER BARACK ET 3'					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(1000 X 80 X 2.5MM)			CTLCB10 008025					POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
120	DGB742 49	FTK38/ 201082	345572528080 7 / CUTTING DISC RHODIUS FTK38 SIZE 100x2x16		20 / EACH/ NUMBER	RHODIUS TOPLINE					TECHNICAL SPECIFICATION - Product Dimension: 100x2x16mm Shape long version: Depressed Cutting Disc Shape Short version: Shape 42 Working Speed: 80 m/s Max revolution: 15300 U/min Material Suitability: Stain less steel Machine Suitability: Free Hand angle grinder Safety and application IDENTIFICATION: Iron and sulphur free = 0.1% Abrasive marking according to EN12413: A24U9BF1338 A NUMBER OF RHODIUS FREEHAND CUTTING DISCS WHICH ARE ONLY 2MM WIDE. THIS ACHIEVES A FASTER AND COOLER CUT GENERAL SPECIFICATION - Product Dimension: 100x2x16mm Shape long version: Depressed Cutting Disc Shape Short version: Shape 42 Working Speed: 80 m/s Max revolution: 15300 U/min Material Suitability: Stain less steel Machine Suitability: Free Hand angle grinder Safety and application IDENTIFICATION: Iron and sulphur free = 0.1% Abrasive marking according to EN12413: A24U9BF1338 A NUMBER OF RHODIUS FREEHAND CUTTING DISCS WHICH ARE ONLY 2MM WIDE. THIS ACHIEVES A FASTER AND COOLER CUT	
121	DGD100 564	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS	MESS UTENSILS, OFFICER WARD PNS	275 / EACH/ NUMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			STEEL 4 COMPARTMENT PLATES DINNER MESS PLATES	SHIFA							NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE GENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE	
122	DGE844 11		9330992246090 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4. X0.60 to 0.70 MM	GENERAL USE	25 / SHEET						TECHNICAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 GENERAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
123	SGE342 46	NO DATA AVAILAB LE	0476500000061 / GLOVES LEATHER FOR WELDING, treated with presservative, standard quality		650 / PAIR	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex GENERAL SPECIFICATION - 1. DESCRIPTION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL</p> <p>details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 ~ 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex</p>	
124	DGT844 20	NO DATA AVAILABL E	010050000004 9 / TEAK WOOD BURMESE GRADE-I SLEEPER	SPECE/IM. 2763 (A)	10 / CUBIC FOOT	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - P-SG/730 (B) SIZE: LENGTH=12-16 FT, WIDTH=09-18 INCH, THICKNESS=8-10 INCH. Moisture Content= 12%±02% GENERAL SPECIFICATION - P-SG/730 (B) SIZE: LENGTH=12-16 FT, WIDTH=09-18 INCH, THICKNESS=8-10 INCH. Moisture Content= 12%±02%</p>	
125	DGE100 359	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATIO N	2 / EACH/N UMBER	OPTICAL INFRARE D CAMOUF LAGE NET, ANTI RADAR CAMOUF					<p>TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
						LAG					<p>SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
126	DGE651 15	NO DATA AVAILABL E	834050503926 2 / QANAT COMPLETE SIZE 18.X 7. OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		21 / EACH/N UMBER						WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. TECHNICAL SPECIFICATION - Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON,BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.GENERAL SPECIFICATION - Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
127	DGD100 273		773070504805 9 / DISH		6 / EACH/N						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			BUTTER GOLDEN CRESTED		UMBER						SPECIFICATION - NO DATA AVAILABLE	
128	DGB914 66		024874512026 6 / CB SAFE SIZE LENTH X BRTH X HT 33" X19"X17"(INCH QUIB) IRON	FOR WARDROOM ON BOARD S/M	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Security safe Steel with combination lock size 48"X30"X29" inner body 16 Gauge outer body 18 gauge mild steel grade CRS S400, Door outer steel gauge 4mm complete door not less than 3/8" thickness (Front door nonmagnetic steel S S Steel, other body mild steel)GENERAL SPECIFICATION - Security safe Steel with combination lock size 48" X30"X29" inner body 16 Gauge outer body 18 gauge mild steel grade CRS S400, Door outer steel gauge 4mm complete door not less than 3/8" thickness (Front door nonmagnetic steel S S Steel, other body mild steel)	
129	DGB709 53	NO DATA AVAILABL E	512073100058 2 / SOCKET SPANNER STANDARD 10-32MM 26PCSSET		13 / SET						TECHNICAL SPECIFICATION - a. Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21, 22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16) Sliding bar (10 inches) Flip drive ratchet c. Drive type: 1/2" square drive d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chromeGENERAL SPECIFICATION - a. Included Items: 20 Sockets 10,11,12,13,14,15,16,17,18,19,20,21, 22,23,24, 26,27,28,30 and 32mm b. 06 accessories: 02 extension bars (125mm and 250mm) Universal joint Spark plug socket (6-point, 13/16) Sliding bar (10 inches) Flip drive ratchet c. Drive type: 1/2" square drive d. Socket type: 12-point sockets e. Material: High quality steel f. Finish: High polishing chrome	
130	DGB738		513370504927	COMMON	3 /						TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	61		1 / DRILL BITS SETS 29 PCS	TOOLS GYRO REPAIRE FACILITY JAPAN	EACH/N UMBER						DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
131	DGB742 40		512073100118 1 / PLIERS PISTON RING 90-140MM ELORA-235/1		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
132	DGE742 25	621100/30 68.184	422079522956 2 / FINS SWIM RUBBER BLACK	FOR DIVING	5 / PAIR						TECHNICAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95LBs(2.25Kg,MADE USA. GENERAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95LBs(2.25Kg,MADE USA.	
133	DGE740 05	621100/30 68.184	422079522956 2 / FINS SWIM RUBBER BLACK	FOR DIVING	11 / PAIR						TECHNICAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95LBs(2.25Kg,MADE USA. GENERAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE-SCUBA-PRO,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											WEIGHT-4.95LBs(2.25Kg,MADE USA.	
134	DGE72173	0472-99-425-8913	0472UK511799 8 / HYDROSTATI C RELEASE		8 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
135	DGE72300	C-134	085158000007 6 / DEFENCER EAR C-134 62TD		57 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
136	DGB100466		132572335002 4 / BLADE BAND SAW 15X01MM 6TP- 10MM REGULAR RAKER CARBON STEEL	100 FT ONE ROLL	200 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
137	DGB79224		027378910575 1 / BLADE HAND HACKSAW FLEXIBLE PITCH MEDIUM NOM LG 9IN TEETH24		32 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
138	DGE94922	SL-130A	534070521963 4 / DEADBOLT LOCK SOCA SL-130A	SNIDS SECURITY SYSTEM	3 / EACH/N UMBER	SL-130A		MECHATRONICS PLOT NO 169 ST-9 SECTOR I 10/3 INDUSTRIAL AREA ISLAMAABAD, PAKISTAN PHONE: 051-4430370 MOBILE: 0333-5513377		MECHAT RONICS PAKISTA N	TECHNICAL SPECIFICATION - Power supply DC 12V Operation current 880 Ma Holding current 250mA Door position detecting points N.C. Bolt position points X Re lock function X Application All type of 90- 180 door Delay time 0,3,5,9,Sec (available to set) Mechanic life More then 500,000 time Door open contact Photo coupler contact Overloaded current protection Available Operation temperature Usual:0c/ Long unlocked:500c±50c Range of the door crack Maximum of 10mm Length of bolt 16mm Weight 750g (included wrapping). GENERAL SPECIFICATION - Power supply DC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											12V Operation current 880 Ma Holding current 250mA Door position detecting points N.C. Bolt position points X Re lock function X Application All type of 90-180 door Delay time 0.3,5,9,Sec (available to set) Mechanic life More then 500,000 time Door open contact Photo coupler contact Overloaded current protection Available Operation temperature Usual:0c/ Long unlocked:500c±50c Range of the door crack Maximum of 10mm Length of bolt 16mm Weight 750g (included wrapping).	
139	DGH100588	LUKUF90105210OM	7125705206257 / FRAME 10' X 3.5'	Racking	12 / EACH/NUMBER	NA		M/s Habib & Sons 3rd Floor, 83-C, Phase II Extension, Main National Highway, Defense Housing Society Karachi-Pakistan		M/s Habib & Sons	TECHNICAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated GENERAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 90 x 0150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated	
140	DGH100581		7125705137234 / UPRIGHT FRAME SIZE 4800MM X 900MM	RACKING MATERIAL	26 / EACH/NUMBER	NO DATA AVAILABLE		PK		HABIB	TECHNICAL SPECIFICATION - SPECIFICATION SIZE 4800MM X 900MM --MADE OF C.R.C PROFILE SECTION SIZE 80MM X 70MM X 2.5MM WITH CROSS BRACING OF 25MM X 25MM X 1.2 MM AND BASE PLATES GENERAL SPECIFICATION - SPECIFICATION SIZE 4800MM X 900MM --MADE OF C.R.C PROFILE SECTION SIZE 80MM X 70MM X 2.5MM WITH CROSS BRACING OF 25MM X 25MM X 1.2MM AND BASE PLATES	
141	DGH100569	LCKHB1081182B	3020705202580 / BEAM PR 2740X240	RACKS	20 / EACH/NUMBER			OFFICE:3RD FLOOR 83 C, PHASE2. EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726		HABIB & SONS	TECHNICAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5GENERAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
142	DGH100570	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	20 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI		HABIB & SONS	TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MMGENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
143	DGE100476		047659000006 2 / GLOVES LEATHER LEFT HAND.		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durableGENERAL SPECIFICATION - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable	
144	DGE100478		041459923091 1 / PACKING MATERIAL HEMP FOR FURNACE FUEL, SIZE= 1/4" SQ		35 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DGE100488		041459923091 1 / PACKING MATERIAL HEMP FOR FURNACE FUEL, SIZE= 1/4" SQ		45 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
146	DGE79278	NIL	047659943055 8 / BRUSH,		152 / EACH/N						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		UMBER						POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
147	DGB759 57		028359571143 7 / ROD NAVAL BRASS HEX A F 1.67 INCH		6 / METER						TECHNICAL SPECIFICATION - BSEN-12163, MATERIAL GRADE CW712R, MATERIAL CONDITION: M WEIGHT: 9.010 LB/FT AS PER BR-320D. RUNNING LENGTH: Minimum 8 foot. GENERAL SPECIFICATION - BSEN-12163, MATERIAL GRADE CW712R, MATERIAL CONDITION: M WEIGHT: 9.010 LB/FT AS PER BR-320D. RUNNING LENGTH: Minimum 8 foot.	
148	DGE796 84	0414-5160	041459923093 4 / SHEET, ASBESTOS, COMPRESSE D TH 1/16", WD 54"X63" IN WT PER SHEET 22LBS		21 / KILOGRAMME						TECHNICAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES) GENERAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)	
149	DGB739 46	THT53321	027379910589 7 / CUTTER PIPE HAND OPERATED TYPE WHEEL 3-32MM CUTTING RANGE		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Cutting Range: 1-3 inch (25-80mm) OLD RANGE: 1.5TO03IN GENERAL SPECIFICATION - Cutting Range: 1-3 inch (25-80mm) OLD RANGE: 1.5 TO03IN	
150	DGB880 00		027779910631 6 /		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			EXTENSION SOCKET SPANNER BAR TYPE 06" LG		UMBER						SPECIFICATION - NO DATA AVAILABLE	
151	DGB745 82	H 20026	027559910553 3 / Plier Snipe Nose Side Cutter 05" Plastic Coated Bowed Handle		24 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
152	DGE100 540	NIL	721050515517 2 / FIRE RETARDANT SPRING MATTRESS (L6' X W2' X H6")	MATRESSES FOR BED	25 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		TECHNICAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 GENERAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
153	DGH987 80		614570533282 9 / electrical cable 30mm 4 core flexible cu/ pvc/ pvc,		50 / METER	4 CORE FLEXIBLE CABLE					TECHNICAL SPECIFICATION - ELECTRICAL CABLE 30MM 4 CORE FLEXIBLE CU/ PVC/ PVC GENERAL SPECIFICATION - ELECTRICAL CABLE 30MM 4 CORE FLEXIBLE CU/ PVC/ PVC	
154	DGE985 85	T53442	422073100036 2 / CLAYPSO AQUA LUNG 105100	T-50300	17 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1ST STAGE: a. 1st stage technology Piston: not Balanced b. Mechanism: In line c. Maximum working pressure: 232 bar on DIN version et on yoke version d. ACD system: Conversion kit available e. Number of HP ports: 1 (7/16" UNF) f. Number of MP ports: 4 (4/8" UNF) g. Average pressure: 8 to 10 bar h. Airflow (surface, hose): 1300 l/min (45.9 cubic feet/min) with HP = 200 bar i. Body: Bright brass with multi layer chrom j. Spring: Stainless steel k. Conical: filter Nickel plated bronze l. O-Rings: EPDM 2ND STAGE: a. 2nd stage technology: Non balanced b. Mechanism: Downstream valve c. Cracking effort: 2.5 a 4 mbr d. Venture effect	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>adjustment: Yes e. Housing, exhaust diffuser VENTURE SWITCH: ABS f. Cover: Polyurethane g. Mouthpiece , exhaust valve, DIAPHRAGM, VALVE: Silicon h. Adjustable seat: Stainless steel LUNG DEMAND REGULATOR VALVE WITH EXTENDEGENERAL SPECIFICATION - 1ST STAGE: a. 1st stage technology Piston: not Balanced b. Mechanism: In line c. Maximum working pressure: 232 bar on DIN version et on yoke version d. ACD system: Conversion kit available e. Number of HP ports: 1(7/16" UNF) f. Number of MP ports: 4(4/8" UNF) g. Average pressure: 8 to 10 bar h. Airflow (surface, hose): 1300 l/min (45.9 cubic feet/min) with HP = 200 bar i. Body: Bright brass with multi layer chrom j. Spring: Stainless steel k. Conical: filter Nickel plated bronze l. O-Rings: EPDM 2ND STAGE: a. 2nd stage technology: Non balanced b. Mechanism: Downstream valve c. Cracking effort: 2.5 a 4 mbr d. Venture effect adjustment: Yes e. Housing, exhaust diffuser VENTURE SWITCH: ABS f. Cover: Polyurethane g. Mouthpiece , exhaust valve, DIAPHRAGM, VALVE: Silicon h. Adjustable seat: Stainless steel LUNG DEMAND REGULATOR VALVE WITH EXTENDE</p>	
155	DGE990 51		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN TRANSPAREN T L X W X THIC 48"X48"X0.		12 / SHEET						<p><u>TECHNICAL SPECIFICATION -</u> Manfr/Tech.Sponcer Code reference: DTD 5592<u>GENERAL</u> <u>SPECIFICATION -</u> Manfr/Tech. Sponcer Code reference:DTD 5592</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			250"									
156	DGE98184	BSF67	041359923970 2 / HOSE RUBBER SYNTHETIC I/D 2.5,O/D 3IN 4PLIES 200PSI (60MONTH		12 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
157	DGH100192		399070533118 3 / MULTI-PURPOSE TROLLEY		4 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
158	DGE98104	0461-931-8996	046059931899 6 / TAPE COTTON ADHASIVE COMPOUND WIDTH 3" THICK 0.038" LG.10 MTR.	30 MM GUN.	40 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
159	DGE98964	NIL	810501124264 5 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217-9451	STATIC SAFETY OF EQUIPMENT/COMPONENTS	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557 GENERAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
160	DGT100177	NO DATA AVAILAB LE	010050000008 8 / Ply wood GD-I, 9 ply.	X 19.05 MM)	320 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p><u>GENERAL SPECIFICATION -</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: Length= 8', Width=4' & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p>	
161	DGE98970	NO DATA AVAILABLE	047450000307 / FENDER COIR ROUND		8 / EACH/NUMBER	600MM 24" ROUND COIR BOAT FENDER					<p><u>TECHNICAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE.</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY. <u>GENERAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.</u>	
162	DGE98183		045154600445 9 / HOOKS FOR CURTAIN		10 / DOZEN						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
163	DGE98099	NIL	041359923891 4 / SHEET RUBBER SOLID NATURAL BLACK LG 1830.0mm WD 1220.0mm THICKNESS 2.0mm		1 / METER						<u>TECHNICAL SPECIFICATION - BS 1154 COMPOUND Z14 HARDNESS RATING 62"-70" TS-2000PSI</u> <u>GENERAL SPECIFICATION - BS 1154 COMPOUND Z14 HARDNESS RATING 62"-70" TS-2000PSI</u>	
164	DGE98997	NO DATA AVAILAB LE	047659000006 3 / GLOVES-LEATHER RIGHT HAND		20 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10</u> <u>GENERAL SPECIFICATION - Size, colour & material: as per sample size: 9 1/2 - 10</u>	
165	DGE98124	NO DATA AVAILAB LE	046154600568 3 / PAPER ABRASSIVE		15 / SHEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WATER PROOF 9" X11".								AVAILABLE	
166	DGB990 17	C60	047450448149 7 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	FOUNDRY USE OEM MORGANITE UK FAX NO	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
167	DGE989 65	0413-2184	597099923966 4 / TAP INSULATION ELECT ADHESIVE PLASTIC RED W1	FOR RED PHASE	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing GENERAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing	
168	DGE989 67	NO DATA AVAILABLE	597070504730 4 / Nylon Transparent Tape (1 inch size).		48 / ROLL						TECHNICAL SPECIFICATION - manufacturer with following details: a. Manufacturer Name: Gold Star (GS) b. Item Name: Nylon Transparent Tape c. Size: 1 inch d. Price: Rs 55/- SAME ITEM IS ALSO AVAILABLE FROM LOCAL market GENERAL SPECIFICATION - manufacturer with following details: a. Manufacturer Name: Gold Star (GS) b. Item Name: Nylon Transparent Tape c. Size: 1 inch d. Price: Rs 55/- SAME ITEM IS ALSO AVAILABLE FROM LOCAL market	
169	DGB728 84		132572335001 0 / BLADE POWER HACK SAW HSS 18X1-1/2X0.075" 6TPI		29 / EACH/NUMBER	AISI M2 HSS (Super Hardened)					TECHNICAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 1/2 x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened) GENERAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 1/2 x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened)	
170	DGE989 66	1756654	597000184200 2 / TAPE-INSULATION		15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
171	DGE989 95	NIL	351070518127 8 / TRAY BLEECH	NIL	3 / EACH/NUMBER	NIL		LOCAL MARKET	NOT KNOWN		TECHNICAL SPECIFICATION - GENERAL ITEM GENERAL SPECIFICATION - GENERAL ITEM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
172	DGE989 12	MIL-P- 15280	564000237482 8 / INSULATION SLEEVING THERMAL		105 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p> <p>GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p>	
173	DGE989 13	MIL-P- 15280	564000237482 7 / INSULATION SLEEVING THERMAL		105 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p> <p>GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p>	