

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 20-05-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828, 48508720

WHATSAPP NO. 092-322-0188121, 092-341-0201888 (Message Only)

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE971 47	L/NO E- I/4927- A/520 DT. 110698.	041459924554 2 / CLOTH ASBESTOS 1/8		25 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
2	DGE994 59	MIL-P- 15280	564000237482 8 / INSULATION SLEEVING THERMAL		15 / EACH/N UMBER						TECHNICAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
3	DGE101 723	MIL-P- 15280	564000237482 8 / INSULATION SLEEVING THERMAL		40 / EACH/N UMBER						TECHNICAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL. COLOR: BLACK. DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
4	DGH102045	TSGU-400	614500110634 1 / CABLE ELECT 3- COND/0.742" SI &GLASS INSUL PVC JKT 1000V 400A		250 / METER						TECHNICAL SPECIFICATION - 04 ton Ac Compressor MIL-C-24643/16 GENERAL SPECIFICATION - 04 ton Ac Compressor MIL-C-24643/16	
5	DGE101835	0413-2184	597099923966 4 / TAP INSULATION ELECT ADHESIVE PLASTIC RED W1	FOR RED PHASE	14 / EACH/N UMBER						TECHNICAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing GENERAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing	
6	DGE101374	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		40 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
7	DGE101994	NO DATA AVAILABLE	0330500000139 / TWINE FLEX FINE 0.50 LBS.	LOAD=26 LBS. 2PLY	30 / KILOGRAMME	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION - a.</u> Specifications of Item Material: Synthetic fiber/ polypropylene thread Shape: Twisted multi-strand rope Flexibility: Highly flexible for easy layout and marking Usage: used for ground marking, layout marking in industrial areas b. Dimensions/ Sizes and etc Length: 50 meter in roll form Thickness: 01 mm</p> <p><u>GENERAL SPECIFICATION - a.</u> Specifications of Item Material: Synthetic fiber/ polypropylene thread Shape: Twisted multi-strand rope Flexibility: Highly flexible for easy layout and marking Usage: used for ground marking, layout marking in industrial areas b. Dimensions/ Sizes and etc Length: 50 meter in roll form Thickness: 01 mm</p>	
8	DGE101844	NO DATA AVAILABLE	0330500000139 / TWINE FLEX FINE 0.50 LBS.	LOAD=26 LBS. 2PLY	20 / KILOGRAMME	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION - a.</u> Specifications of Item Material: Synthetic fiber/ polypropylene thread Shape: Twisted multi-strand rope Flexibility: Highly flexible for easy layout and marking Usage: used for ground marking, layout marking in industrial areas b. Dimensions/ Sizes and etc Length: 50 meter in roll form Thickness: 01 mm</p> <p><u>GENERAL SPECIFICATION - a.</u> Specifications of Item Material: Synthetic fiber/ polypropylene thread Shape: Twisted multi-strand rope Flexibility: Highly flexible for easy layout and marking Usage: used for ground marking, layout marking in industrial areas b. Dimensions/ Sizes and etc Length: 50 meter in roll form Thickness: 01 mm</p>	
9	DGE99747	NO DATA AVAILABLE	0413500000040 / SHEET EBONITE WHALE BRAND TYPE		3 / SHEET	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			1 LG.48									
10	DGE99309	NO DATA AVAILAB LE	046250000018 / INSECTICIDE EMULSION		5 / LITER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
11	DGD69267		7730705048075 / plate Dinner 23cm blue crested (as per stock sample)		124 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material:PORCELINGENERAL SPECIFICATION - Material: PORCELIN	
12	DGE99743	DATA AVAILAB LE	0461500000152 / POLISHING-FELT ROUND		4 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch GENERAL SPECIFICATION - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch	
13	DGE100057	NO DATA AVAILAB LE	0432500000027 / HELMET PROTECTIVE DESPATCH RIDER WITH VISOR SIZE 6 3/4		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218) GENERAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218)	
14	DGE101445	NO DATA AVAILAB LE	0461500000024 / PAPER ABRASIVE 9" X11"		200 / SHEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WATERPROOF MATERIAL EMERY GRADE P-120D									
15	DGE101726	NO DATA AVAILABLE	046150000086 / GOGGLE CHIPPING		148 / EACH/NUMBER	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.</p> <p><u>GENERAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.</p>	
16	DGE99762	NO DATA AVAILABLE	046150000086 / GOGGLE CHIPPING		45 / EACH/NUMBER	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band. <u>GENERAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.	
17	DGE100 439		8340PK507382 7 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIE S		3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>GREEN, COLOR CODE: RAL-6003, d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER. MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL). WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM). 02 x BAG FOR THE TENT</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
18	DGE101722		8340PK507382 7 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIE S		2 / EACH/NUMBER						<p>BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p>TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER. MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND=</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE), MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER. MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM). 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p>	
19	DGE101 823		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - 1.</u> SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS. WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER. MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO. MATERIAL: MS (MILD STEEL). WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
20	DGE101 966		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/ UMBER						<p>TECHNICAL SPECIFICATION - 1.</p> <p>SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2.</p> <p>OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS. WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p>GENERAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER. MATERIAL: NYLON/COTTON, DIA MINIMUM 16</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS. WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p>	
21	DGE101760		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD), b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>STEEL). OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO. MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM). 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER. MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
22	DGT101 975	NO DATA AVAILABL E	010000000000 3 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	217 / SQ FEET	NO DATA AVILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DGE899		834070511704		7 /						TECHNICAL SPECIFICATION - 02 x	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	24		1 / MESS TENT COMPLETE WITH ACCESSORIES WALLS-152CM		EACH/NUMBER						iron standing poles length 12 ft 01 x rich iron length 06 ft tent size (20 x 20ft) qanat size (18 x 18ft) rope strops 40 in no length 10ft iron pegs: 40 in no(length 2.5ft) hammer large 02 in no capacity 3.5 kg bambo 12 feet: 08 in no <u>GENERAL SPECIFICATION</u> - 02 x iron standing poles length 12 ft 01 x rich iron length 06 ft tent size (20 x 20ft) qanat size (18 x 18ft) rope strops 40 in no length 10ft iron pegs:40 in no(length 2.5ft) hammer large 02 in no capacity 3.5 kg bambo 12 feet: 08 in no	
24	DGE99669	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	4 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					<u>TECHNICAL SPECIFICATION</u> - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS. 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT. QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. <u>GENERAL SPECIFICATION</u> - 1. 100% POLYESTER FABRIC, WITH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD. (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
25	DGE100 430	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATIO N	2 / EACH/N UMBER	OPTICAL INFRARE D CAMOUF LAGE NET, ANTI RADAR CAMOUF LAG					TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tendor Remarks	TECH / GEN SPECS	Dimension
											<p>CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS. 3. SIZE= 6.8 x 6.8 METERS. 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p>	
26	DGE100 333	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATIO N	2 / EACH/N UMBER	OPTICAL INFRARE D CAMOUF LAGE NET,					<p>TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
						ANTI RADAR CAMOUF LAG					<p>FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS. 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p> <p><u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR</p> <p>FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS. 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT. QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
27	DGT102075	NO DATA AVAILAB LE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	448 / SQ FEET	NO DATA AVILAB LE					<p>TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p>GENERAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
28	DGT101 973	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply.	X 19.05 MM)	1268 / SQ FEET	NO DATA AVAILAB LE					<p>SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p><u>TECHNICAL SPECIFICATION - 1.</u> Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply. Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p><u>GENERAL SPECIFICATION - 1.</u> Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply. Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop	
29	DGE101 631	PD-87066	841501013738 4 / GLOVES CHEMICAL		10 / PAIR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
30	DGE101 408	NO DATA AVAILABL E	8415PK506744 2 / CLOTH PARASHUTE GRAY		500 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
31	DGE101 637	NO DATA AVAILABL E	733070100228 9 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDU S/JOY0).		15 / EACH/N UMBER						TECHNICAL SPECIFICATION - WITH FULLCOVER GENERAL SPECIFICATION - WITH FULLCOVER	
32	DGT995 79	BELFONT TRUWOO DTEAK	933099224609 7 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM,SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		5 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
33	DGT101 976	BELFONT TRUWOO	933099224609 7 / PLASTIC		7 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		DTEAK	SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)								bs 476pt 1class 1GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
34	DGH101 881	QQ-F-461	951500187395 5 / SHEET MILD STEEL	GENERAL USE	100 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
35	DGE101 443	60-501-001	615076502401 1 / TIE WRPA (CABLE TIE) P/N 60-501-001	GRADIOMETE R SYSTEM	360 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held GENERAL SPECIFICATION - a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held	
36	DGE101 630		721070503053 7 / WATER COOLER PLASTIC 5 LTR (BRAND REHBAR/INDU STRY/JOY	WATER CONTAINER	50 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DGD102 073	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTME NT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	220 / EACH/N UMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE GENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 760 ± 5 GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX AS PER STOCK SAMPLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
38	DGE100046	NO DATA AVAILABLE	955573043028 2 / INSULATING SLEEVE		6 / EACH/ NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
39	DGE101440		046154600451 5 / PAPER ABRASIVE 9" X11" WATERPROOF MATERIAL EMERY GRADE P- 400C		200 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
40	DGE101661	IS8021	047654600478 5 / Coated Rigger Gloves with Rubberized Cuff		30 / PAIR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DGE101993		033054600356 2 / TWINE FLEX FINE 0.50 LBS.		100 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DGE101525	NO DATA AVAILABLE	055978000018 1 / SLEEVE PLASTIC RED 0.5X10 59P (NSD/TD/19/33 4 DT:15.05.93		35 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
43	DGE101524	NO DATA AVAILABLE	055978000018 5 / SLEEVE PLASTIC		35 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DGT101980	NO DATA AVAILABLE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		8 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
45	DGE99303	NO DATA AVAILABLE	7920FP0010003 / SOFT CLOTH		12 / BAG	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DGE101999	5012568166895	4020993960753 / ROPE FIBROUS, POLYESTER/ PROPYLENE MIX, 08-STRAND, DIA: 40MM		660 / METER						TECHNICAL SPECIFICATION - SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 40-MM DIA BLACK BERTHING POLYESTER/ PROPYLENE MIX, 8-STRAND MOORING NUMBER-5, MBL 26.4 TONNES, MB-67 TABLE-3, 3.8. PLAIN ENDS UV STABILISED ISO 9554 of 2019. 3. STANDARD ACCORDANCE TO ISO 2307 PACKAGING. 4. STANDARD OF MANUFACTURE ISO 2307 OF 2019 5. CONFIRMATION OF STANDARD EN-ISO 2307 OF 2019. 6. 220 METER PER COILS. 7. CERTIFICATIONS: VALID LLOYD TEST CERTIFICATE REQUIRED INDICATION BATCH/LOT NUMBER OF IDENTIFICATION AND WORKING / BREAKING AND STRENGTH OF STORES. 8. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM Phone: +44(0) 1323444444 EMAIL: sales@marlowropes.com GENERAL SPECIFICATION - SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 40-MM DIA BLACK BERTHING POLYESTER/ PROPYLENE MIX, 8-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>STRAND MOORING NUMBER-5, MBL 26.4 TONNES, MB-67 TABLE-3, 3.8, PLAIN ENDS UV STABILISED ISO 9554 of 2019. 3. STANDARD ACCORDANCE TO ISO 2307 PACKAGING. 4. STANDARD OF MANUFACTURE ISO 2307 OF 2019 5. CONFIRMATION OF STANDARD EN-ISO 2307 OF 2019. 6. 220 METER PER COILS. 7. CERTIFICATIONS: VALID LLOYD TEST CERTIFICATE REQUIRED INDICATION BATCH/LOT NUMBER OF IDENTIFICATION AND WORKING / BREAKING AND STRENGTH OF STORES. 8. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM Phone: +44(0) 1323444444 EMAIL: sales@marlowropes.com</p>	
47	DGE101 634	NO DATA AVAILABLE	046154600460 2 / BOX FIRST AID 728 MS		3 / EACH/ NUMBER						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
48	DGE101 762	1-401- 47845	830599125222 3 / COTTON CLOTH		50 / KILOGR AMME	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - 100 % Cotton 1 x 1 Feet Lint Free GENERAL SPECIFICATION - 100 % Cotton 1 x 1 Feet Lint Free</p>	
49	DGE101 638	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT	PCB FABRICATION	58 / EACH/ NUMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-	GERMAN Y		<p>TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%)</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LAB COATS.					34302153-4			CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (\pm 1%) COTTON + 3% (\pm 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
50	DGE101441	NIL	3510705181278 / TRAY BLEECH	NIL	1 / EACH/NUMBER	NIL		LOCAL MARKET	NOT KNOWN		<u>TECHNICAL SPECIFICATION - GENERAL ITEM</u> <u>GENERAL SPECIFICATION - GENERAL ITEM</u>	
51	DGH100438	6145995218490	6145995218490 / CABLE POWER ELECTRICAL 3CORE 440V 34A	CABLES	1500 / METER	DG SHIPS 212	NA	MINISTRY OF DEFENCE (NAVY) SHIPS SUPPORT AGENCY DME ME253, ROOM 19, BLOCK B FOXHILL, BATH, UK TEL: 01225 883293 FAX: 01225 883548	DG SHIPS 212 UK		<u>TECHNICAL SPECIFICATION - AS PER NMCRL AND DG SHIPS 212</u> <u>GENERAL SPECIFICATION - AS PER NMCRL AND DG SHIPS 212</u>	
52	DGE94922	SL-130A	5340705219634 / DEADBOLT LOCK SOCA SL-130A	SNIDS SECURITY SYSTEM	3 / EACH/NUMBER	SL-130A		MECHATRONICS PLOT NO 169 ST-9 SECTOR I 10/3 INDUSTRIAL AREA ISLAMABAD, PAKISTAN PHONE: 051-4430370 MOBILE: 0333-5513377	MECHATRONICS PAKISTAN		<u>TECHNICAL SPECIFICATION - Power supply DC 12V Operation current 880 Ma Holding current 250mA Door position detecting points N.C. Bolt position points X Re lock function X Application All type of 90-180 door Delay time 0,3,5,9,Sec (available to set) Mechanic life More then 500,000 time Door open contact Photo coupler contact Overloaded current protection Available Operation temperature Usual:0c/ Long unlocked:500c\pm50c Range of the door crack Maximum of 10mm Length of bolt 16mm Weight 750g (included wrapping). <u>GENERAL SPECIFICATION - Power supply DC</u></u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											12V Operation current 880 Ma Holding current 250mA Door position detecting points N.C. Bolt position points X Re lock function X Application All type of 90-180 door Delay time 0,3,5,9,Sec (available to set) Mechanic life More then 500,000 time Door open contact Photo coupler contact Overloaded current protection Available Operation temperature Usual:0c/ Long unlocked:500c±50c Range of the door crack Maximum of 10mm Length of bolt 16mm Weight 750g (included wrapping).	
53	DGE101660	NIL	721050515517 2 / FIRE RETARDANT SPRING MATRESS (L6' X W2' X H6")	MATRESSES FOR BED	23 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.		AL-KHAIR HOUSE-43-T	TECHNICAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 GENERAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
54	DGE102002	QA263527	402099083318 4 / ROPE FIBROUS 8 STRAND, DIA 48MM,		220 / METER	NO DATA AVAILAB LE		UK		MARLOW ROPE LTD SOUTH ROAD HAILSHAM EAST SUSSEX UNITED KINGDOM	TECHNICAL SPECIFICATION - SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 48-MM DIA. BERTHING HAWSER BLK CONT FILAMENT POLYESTER & SS POLYPROPYLENE, 3. MIN BREAKING LOAD: 36.5 TONNES, 4. SUPPLIED IN 220 MTR COIL 5. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 6. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 7. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>BSI/ IACS MEMBER SOCIETY CERTIFICATION. 8. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM, Phone: +44(0)1323 444 444 EMAIL: sales@marlowropes.com</p> <p><u>GENERAL SPECIFICATION - SPECIFICATION:</u> 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 48-MM DIA. BERTHING HAWSER BLK CONT FILAMENT POLYESTER & SS POLYPROPYLENE. 3. MIN BREAKING LOAD: 36.5 TONNES. 4. SUPPLIED IN 220 MTR COIL 5. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 6. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 7. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 8. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM, Phone: +44(0)1323 444 444 EMAIL: sales@marlowropes.com</p>	
55	DGT102044	NO DATA AVAILAB E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic	WOOD WORKS SHIPS&ESTAB LISHMENT	36 / SHEET	NO DATA AVAILAB LE		PK			<p>SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE,</p> <p><u>TECHNICAL SPECIFICATION -</u> BSEN-822-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM <u>GENERAL SPECIFICATION -</u> BSEN-822-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			meter SIZE: L=8' W=4' TH=16MM						SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.			
56	DGE101526	828 653-H9020051	801079520819 8 / FABRIC 1300 GSM MILITARY GREY (HYPALONE)	RHIB BOAT	5 / METER		NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON, SOMERSET, BA9 9RX, TEL*01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHAW INFLATABLES LTD		<u>TECHNICAL SPECIFICATION - TDS IS ENCLOSED WITH RWIMSGENERAL SPECIFICATION -TDS IS ENCLOSED WITH RWIMS</u>	
57	DGH101782	LCKHB1081182B	3020705202580 / BEAM PR 2740X240	RACKS	85 / EACH/NUMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726	HABIB & SONS		<u>TECHNICAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: i-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5</u> <u>GENERAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: i-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5</u>	
58	DGH101839	LCKHB1081182B	3020705202580 / BEAM PR 2740X240	RACKS	85 / EACH/NUMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726	HABIB & SONS		<u>TECHNICAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: i-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											01:01.5GENERAL SPECIFICATION - Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
59	DGE101 970	C1512	033050571327 0 / TWINE LINEN SEAMING MEDIUM 2STRD NATURAL MIN BKG STRGTH 36LB	MATERIAL FLEX SPEC, BS-6125 OF1981	20 / KILOGR AMME						TECHNICAL SPECIFICATION - Medium 2 STRD Size 2 180 Mtr length 2 2mm diameter 2 Material Cotton 2 Color White 1. Supply Denomination: 12X12X8cm 250 Gram Cops 2. Dimension/Size: 2mm, 180M packing 3. Detailed Specification: Twine Line Seaming Medium 2 STRD 4. OEM COC: L-E Latief Sons Thread Works Pindi Bhattian PakistanGENERAL SPECIFICATION - Medium 2 STRD Size 2 180 Mtr length 2 2mm diameter 2 Material Cotton 2 Color White 1. Supply Denomination: 12X12X8cm 250 Gram Cops 2. Dimension/Size: 2mm, 180M packing 3. Detailed Specification: Twine Line Seaming Medium 2 STRD 4. OEM COC: L-E Latief Sons Thread Works Pindi Bhattian Pakistan	
60	DGE100 212	NO DATA AVAILABL E	035059923357 6 / FENDER MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6 INTERNAL DIA 10"	MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6	12 / EACH/N UMBER						TECHNICAL SPECIFICATION - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10"GENERAL SPECIFICATION - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10"	
61	DGE997 12		046150461015 1 / POLISHING FELT ROUND DIA 200 MM THICKNESS 38 MM		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
62	DGE997	319-	047659000003		10 /	319-					TECHNICAL SPECIFICATION - 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
45		SIVLER-DE	1 / BRUSH STEEL WIRE SURFACE CLEANING SMALL		EACH/NUMBER	SILVER-DE					ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN B07RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle. Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement <u>GENERAL SPECIFICATION - 1.</u> ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN B07RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle. Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement	
63	DGE101380	319-SIVLER-DE	047659000003 1 / BRUSH STEEL WIRE SURFACE CLEANING SMALL		40 / EACH/NUMBER	319-SILVER-DE					<u>TECHNICAL SPECIFICATION - 1.</u> ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN B07RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle. Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement <u>GENERAL SPECIFICATION - 1.</u> ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN B07RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle, Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement	
64	DGE99273	NO DATA AVAILAB LE	055979002055 2 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	4 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DGE100065	NO DATA AVAILAB LE	055979002055 2 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	30 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
66	DGE99305	0413-2433 (4720-99- 923-8770)	041359923877 0 / HOSE RUBBER INTERNAL 0.625"X0.875" X60FT		70 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
67	DGE101628	0.75X0. 007INCH- 50MTR-	055979001524 4 / INSULATION- TAPE- VARNISHED WOVEN GLASS-FIBRE- (STRAIGHT CUT)		45 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
68	DGE100092		041459923091 1 / PACKING MATERIAL HEMP FOR		35 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FURNACE FUEL, SIZE= 1/4" SQ									
69	DGE101452	NO DATA AVAILAB LE	046159000098 0 / CLOTH ABRASIVE 9		162 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DGE101639	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		23 / EACH/N UMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
71	DGE101633	LETTER NO.E- I/4927/A/4 45DT0509 02	046159000391 4 / CLOTH POLESHING		25 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
72	DGE102001	nil	035059571312 1 / Rope Nylon, Hawser laid, White, 3- Strand, Cir: 1- Inch, Diameter: 8-MM		200 / FATHO M						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019. 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM, 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.</p>	
73	DGE102 065		035059571313 0 / ROPE NYLON, HAWSERLAID, 3-STRAND, CIRC: 3-1/2 INCH, NOM DIA: 24MM, TYPE-1,	TOWING & BERTHING ROPE	240 / METER						<p>TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM, 9 VALID LLOYD'S/BSI TEST</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021. 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY. 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.</p>	
74	DGB99576	NO DATA AVAILABLE	028370000164 1 / SILVER SOLDER EASYFLO FOR STAINLESS STEEL IN ROD FORM		2700 / GRAM						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
75	DGE101905	0415-2501	041559923144 9 / CORK AND RUBBER SHEET SIZE. 36"X24"X1/16" THICK		10 / SHEET						<p>TECHNICAL SPECIFICATION - DEF SPEC 22 GENERAL SPECIFICATION - DEF SPEC 22</p>	
76	DGE101635	NO DATA AVAILABLE	043452000015 6 / LEAD WEIGHT 1KG WITH CLAMP TYPE LOCK.T.	DIVING BREATHING APPARATUS T-9651 LARIII	10 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			40761									
77	DGE101 632	NIL	041359923892 3 / RUBBER SHEET SOLID NATURAL (CLOTH INSERT)		50 / KILOGR AMME						<p>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCRL: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.</p> <p>GENERAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCRL: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.</p>	
78	DGB101 888		026759521328 5 / Piping Steel Galv 3050x4. 0x0.250		240 / METER						<p>TECHNICAL SPECIFICATION - BS 3602. Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											also usable. <u>GENERAL SPECIFICATION - BS 3602</u> , Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable.	
79	DGT101 882	NO DATA AVAILABLE	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD- II (CORE INNER & OUTER PLYS OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIV E		320 / SQ FEET						<u>TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088</u> , part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) <u>GENERAL SPECIFICATION - SPECIFICATION: BS-1088</u> , part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
80	DGH101 880		021159230669 5 / SHEET STEEL CARBON 2440X910X5M M		100 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
81	DGH100 076		021250212049 0 / BAR STEEL CHANNEL SIZE 3.50"X2" X5/16"		10 / METER						<u>TECHNICAL SPECIFICATION - Item Specification:BS EN OF 2004</u> , GRADE S-275 JR <u>GENERAL SPECIFICATION - Item Specification:BS EN OF 2004</u> , GRADE S-275 JR	
82	DGH101 884	DNC S15	021159119996 8 / STEEL PLATE CARBON SIZE 2500X1250X6 MM. **SIZE 2500X1220X6 MM (Only acceptable		5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025</u> .STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr <u>GENERAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025</u> .	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			against demand based LPO).								STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr	
83	DGH101783	DNC S15	021159119996 8 / STEEL PLATE CARBON SIZE 2500X1250X6 MM. **SIZE 2500X1220X6 MM (Only acceptable against demand based LPO).		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025. STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr GENERAL SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025. STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr	
84	DGE101967	NO DATA AVAILABE	033059571326 0 / TWINE COTTON CHALK LINE G/PURPOSE MIN BKG STRG25 LB20YDS LG; DIA 1.5mm	GENERAL PURPOSE BS 2019	57 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 6125 of 1981 GENERAL SPECIFICATION - BS 6125 of 1981	
85	DGE102005	NIL	035059923712 6 / ROPE NYLON ,CIRC 2". DIA: 16-MM. HAWSERLAID, 3-sTRAND, Z-LAY, 120 FM PER COIL.	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	120 / FATHOM						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019. 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5. OEM COC REQUIRED, 6. FURNISH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.</u></p>	
86	DGE101 827	NIL	035059923712 8 / ROPE NYLON, HAWSERLAID, Z-LAY, 3- STRANDS, NOM DIA: 20MM, CIRC: 2.50 INCH, TYPE: 1, MINIMUM BREAKING	MIN BRKG STRENGTH UNIT OF AVAILABILITY	120 / FATHO M						<p><u>TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LOAD: 8.3 TONS								<p>SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E</p> <p>DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
87	DGE102004	NIL	035059923712 9 / ROPE NYLON, HAWSERLAID, 3-STRANDS, CIRCI 3", NOM DIA: 24MM, Z-	STRENGTH 11.800 TONS UNIT OF AVAILABILIT	120 / FATHOM						<p><u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			LAY, TYPE-1, MINIMUM BREAKING LOAD : 12 TONS								<p>REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
88	DGE102003	NO DATA AVAILABL	0350599237130 / ROPE	MIN BRKG STRENGTH	120 / METER	NO DATA AVAILAB					<p><u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	NYLON HAWSERLAID, DIA: 28-MM, 3-STRAND	15.500 TONS UNIT OF		LE					<p>SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
89	DGE101 997	BS2570	033050571326 7 / TWINE LINEN SEAMING COARSE 2STRD NATURAL MIN BKG STRGTH 45LB		20 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
90	DGB100 437	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	6 / KILOGR AMME						TECHNICAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm-13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface GENERAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm-13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
91	DGE993 00	NO DATA AVAILABL E	041354600479 3 / EAR DEFENDER MEDIUM SIZE		30 / PAIR	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DGH101 847		028150281168 0 / DIVIDER		138 / EACH/N UMBER						TECHNICAL SPECIFICATION - see attached file GENERAL SPECIFICATION - see attached file	
93	DGB102 014		021459941001 9 / BOLT MACHINE STEEL UNC class 2a HEX HD SZ 0.625 X3.000X1.500 IN	BR-320 D/78	25 / EACH/N UMBER						TECHNICAL SPECIFICATION - AISI PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED GENERAL SPECIFICATION - AISI PD 970: 2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED	
94	DGH101 846		028150281167 0 / BACK PLATE		14 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material : Metal Sheet Length : 10 Feet Width : 5.2 Feet Mounting Type	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											: Back Mount Color : Gray Features : Quick in installation, Helpful in partitioning of storage pace, Robust & Durable. High grade Oil Paint Construction. <u>GENERAL SPECIFICATION</u> - Material : Metal Sheet Length : 10 Feet Width : 5.2 Feet Mounting Type : Back Mount Color : Gray Features : Quick in installation, Helpful in partitioning of storage pace, Robust & Durable. High grade Oil Paint Construction.	
95	DGB792 24		027378910575 1 / BLADE HAND HACKSAW FLEXIBLE PITCH MEDIUM NOM LG 9IN TEETH24		32 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
96	DGH100 203	BS EN 10025- 2/2004, MATERIAL GRADE S 275 JR	021259571071 8 / ANGLE STEEL CARBON E/S BLACK 1.25 X 1.25 X 0.25 INCH		60 / METER						<u>TECHNICAL SPECIFICATION</u> - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr <u>GENERAL SPECIFICATION</u> - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr	
97	DGB885 81	AMARICA N(OR UNIFIND) NUMBER	026659000300 8 / WASHER FLAT ROUND BRASS 3 BA 0.177X0. 341X0.028IN	SPEC=BS 3410 MATERIAL BRASS	104 / TEN						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
98	DGB100 472		026759521327 8 / PIPING STEEL GALVANIZED SEAMLESS, L 6.1 M, E/DIA 26.9MM, TH 2.6 MM, N/BORE:19.1 MM	UTS LENGTH. BULK SUPPLY	90 / METER						<u>TECHNICAL SPECIFICATION</u> - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS <u>GENERAL SPECIFICATION</u> - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
99	DGE101520	NO DATA AVAILABLE	033054600448 4 / HEAVING LINE 06MM L50MM 466MS	MSI	1620 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
100	DGB100466		132572335002 4 / BLADE BAND SAW 15X01MM 6TP-10MM REGULAR RAKER CARBON STEEL	100 FT ONE ROLL	200 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
101	DGE72300	C-134	085158000007 6 / DEFENCER EAR C-134 62TD		57 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
102	DGE101820	NO DATA AVAILABLE	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC. GRADE: 300D; SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p>GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D. SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p>TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY:</p>	
103	DGE102067	NO DATA AVAILAB LE	424050508870 5/ CAMOUFLAGE	TO COVER/CAMO FLAGE THE 14.5MM GUNS	1/ EACH/N UMBER							

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NETS, SIZE 26 X 26 FT								<p>FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 08 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>BROWN AND GRAY COMBINATION); 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p>	
104	DGE101 965	NO DATA AVAILABL E	424050508870 5/ CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	2/ EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC. GRADE: 300D. SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS. FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH. LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET</p> <p>ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
105	DGE101761	NO DATA AVAILAB LE	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	2 / EACH/N UMBER						<p>LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS. FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS. FOR JOINING MULTIPLE NETS (06</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM. CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 08 INCH, LENGTH: 08 FT. QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p>	
106	DGE102 000	NIL	402099923712 1 / ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00", DIA 0.3125" (8MM)	NGTH 1,330 TONS UNIT OF AVAILABILITY	120 / FATHO M						<p><u>TECHNICAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. <u>GENERAL SPECIFICATION</u> - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM.</p>	
107	DGE100 382		402099923713 7 / ROPE NYLON HAWSERLAID, 3-STRND, Z- LAY, TYPE-1, NOM DIA: 64- MM, CIRC: 08- INCH.	NOR-SHIPS- USE-NASAR	33.3 / FATHO M						<p><u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM, 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WORKING/ BREAKING STRENGTH OF STORES.GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019. 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5. OEM COC REQUIRED. 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
108	DGE99744	NO DATA AVAILAB LE	422079502032 8 / DINGHY BUOYANCY AID LIFE JACKET SM/ADULT		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB LEGENERAL SPECIFICATION - NO DATA AVAILABLE	
109	DGE100354	NO DATA AVAILAB LE	422079505519 3 / WHISTLE PLASTIC FOR GENERAL SERVICE LIFE JACKET	LIFE JACKET MK-1,ORALLY INFLATED	5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB LEGENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DGB99552	0251-9681	401099411968 1 / CHAIN WELDLESS BRASS B13304 429012BR	ELECTRO HYDROLIC STEEING GEAR BALL SHAH	2 / EACH/N UMBER	PUMP					TECHNICAL SPECIFICATION - NO DATA AVAILAB LEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
111	DGE100 091	nil	533000038292 2 / PACKING- MATERIAL	FUEL OIL SERVICE PMP	33 / METER						<p><u>TECHNICAL SPECIFICATION -</u> SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON- ASBESTOS, TEM UPTO: 400 °C</p> <p><u>GENERAL SPECIFICATION -</u> SPECIFIATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NON- ASBESTOS, TEM UPTO: 400 °C</p>	
112	DGE101 725	MIL-P- 15280	564000237482 7 / INSULATION SLEEVEING THERMAL		30 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - mil- p-15280 Sleeve Sizes: LENGTH: 72- INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</u></p> <p><u>GENERAL SPECIFICATION - mil-p- 15280 Sleeve Sizes: LENGTH: 72- INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</u></p>	
113	DGB746 13	0140	403079515388 7 / SPLIT THIMBLES (316 STAINLESS STEEL)10MM	TAL SHIP SAILING RIG	14 / EACH/N UMBER			BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST,HAMPSHIRE.PO15 5SX UK.E MAIL: BASELINE. MARINE@BTINTERNET. COM.WEB:WWW. BASELINEHARDWARE. CO.UK	UK		<p><u>TECHNICAL SPECIFICATION -</u> SOURCE OF AVAILABILITY ; BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE. SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB:WWW. BASELINEHARDWARE.CO.UK TEL: +44(0)1489 576349.FAX:+44(0) 1489578835. <u>GENERAL</u> <u>SPECIFICATION - SOURCE OF</u> <u>AVAILABILITY :BASELINE MARINE</u> <u>PRODUCTS LTD.UNIT 10 APPLE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											INDUSTRIAL ESTATE,WHITTLE AVENUE,SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL: BASELINE.MARINE@BTINTERNET.COM.WEB:WWW. BASELINEHARDWARE.CO.UK TEL: +44(0)1489 576349.FAX:+44(0) 1489578835.	
114	DGE871 37	FEC 1735511	653270517259 3/ LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	10 / EACH/N UMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4		GERMAN Y	<p><u>TECHNICAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω</p> <p><u>GENERAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω</p>	
115	DGE100 476		047659000006 2 / GLOVES LEATHER LEFT HAND.		2 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION -</u> Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable</p> <p><u>GENERAL SPECIFICATION</u> - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable</p>	
116	DGE100 428	0.75X0. 007INCH- 50MTR-	055979001524 4/ INSULATION- TAPE- VARNISHED		15 / ROLL						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WOVEN GLASS-FIBRE-(STRAIGHT CUT)									
117	DGE997 63		046259000598 9 / TUBING PLASTIC POLYTHYINE LAY FLAT 0.005"TH.WD. 27"WEIGHT PER		30 / KILOGR AMME						TECHNICAL SPECIFICATION - TUBING PLASTIC POLYTHYINE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches thickness: 0.005 inches (DOUBLE SIDE) GENERAL SPECIFICATION - TUBING PLASTIC POLYTHYINE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches thickness: 0.005 inches (DOUBLE SIDE)	
118	DGE100 361	NIL	055979444489 8 / INSULATION SLEEV ELEC INT DIA 3MM THICK0.500 MATER CERAMIC	GENERAL ELECTRIC USE	10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
119	DGB759 57		028359571143 7 / ROD NAVAL BRASS HEX A F 1.67 INCH		6 / METER						TECHNICAL SPECIFICATION - BSEN-12163, MATERIAL GRADE CW712R, MATERIAL CONDITION: M WEIGHT: 9.010 LB/FT AS PER BR-320D. RUNNING LENGTH: Minimum 8 foot. GENERAL SPECIFICATION - BSEN-12163, MATERIAL GRADE CW712R, MATERIAL CONDITION: M WEIGHT: 9.010 LB/FT AS PER BR- 320D. RUNNING LENGTH: Minimum 8 foot.	
120	DGB995 72		028359351743 1 / ALUMINIUM BRONZE INGOT		45 / KILOGR AMME						TECHNICAL SPECIFICATION - 1076 D GENERAL SPECIFICATION - 1076 D	
121	DGE100 213	NIL	035059571323 1 / ROPE SISAL, HAWSERLAID,		1500 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			3-STRD. CIRC: 1,1/8 INCH DIA: 10-MM								MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
122	DGB739 46	THT53321	027379910589 7 / CUTTER PIPE HAND OPERATED TYPE WHEEL 3-32MM CUTTING RANGE		2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - Cutting Range: 1-3 inch (25-80mm) OLD RANGE: 1.5TO03IN <u>GENERAL SPECIFICATION</u> - Cutting Range: 1-3 inch (25-80mm) OLD RANGE: 1.5 TO03IN	
123	DGB880 00		027779910631 6 / EXTENSION SOCKET SPANNER BAR TYPE 06" LG		20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
124	DGB778 12	BS1780 / EN 837-1 NS 100	024259942044 7 / GAUGE- PRESSURE INDICATING DIAL (0- 100PSI)		5 / EACH/N UMBER	111.10					TECHNICAL SPECIFICATION - NOMINAL SIZE (NS): 100 MM (4 INCH) CONNECTION LOCATION: LOWER MOUNT (RADIAL) MATERIAL: STEEL BLACK MEASURING ELEMENT: BOURDON TUBE, C-TYPE OR HELICAL GENERAL SPECIFICATION - NOMINAL SIZE (NS): 100 MM (4 INCH) CONNECTION LOCATION: LOWER MOUNT (RADIAL) MATERIAL: STEEL BLACK MEASURING ELEMENT: BOURDON TUBE, C- TYPE OR HELICAL	
125	DGB885 82		025770419503 9 / NUT-PLAIN- WING-TH-SZ- 0.25"WG.HT0. 718(BRASS) WING-SPRD 1.187"		48 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
126	DGE100 432	NO DATA AVAILABL E	033054600448 4 / HEAVING LINE 08MM L50MM 466MS	MSI	660 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DGB990 17	C60	047450448149 7 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	FOUNDRY USE OEM MORGANITE UK FAX NO	3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
128	DGE721 73	0472-99- 425-8913	0472UK511799 8 / HYDROSTATI C RELEASE		8 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
129	DGE992 86	81349, MIL-H- 15217	472000203633 3 / HOSE RUBBER, NON- METTALIC, INTERNAL DIA 1", NO OF LAYERS= 4,		150 / FOOT						TECHNICAL SPECIFICATION - tech specs: Internal dia = 1 Inch, EQUILANT= 4-PLY, RUBBER TYPE/ FLEXIBLE, MINIMUM Working Pressure = 10 Bar, Maximum Working pressure = 30 Bar, Temp Range = -35 to 80 °C, Packing = Plastic Paper oem coc/DOCUMENTS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(IMPREG. FAB), LENGTH= 50 FT								/dealer certificate= REQUIRED, PARENT EQUIP= CHIPPING MACHINE GENERAL SPECIFICATION - tech specs: Internal dia = 1 Inch, EQUILANT= 4-PLY, RUBBER TYPE/ FLEXIBLE, MINIMUM Working Pressure = 10 Bar, Maximum Working pressure = 30 Bar, Temp Range = -35 to 80 °C, Packing = Plastic Paper oem coc/DOCUMENTS /dealer certificate= REQUIRED, PARENT EQUIP= CHIPPING MACHINE	
130	DGE100 266	NO DATA AVAILABL E	402099923712 4 / ROPE NYLON (POLYAMIDE) HAWSERLAID, DIA: 12-MM, 3- STRAND, WHITE	GEMNI CRAFT	280 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. MIN BK STRENGTH 2.9 TONN COIL, WEIGHT: 23 KILOS, 2. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 3. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 4. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 5. LENGTH: PER COIL: 220 METER. 6. OEM COC REQUIRED. GENERAL SPECIFICATION - 1. MIN BK STRENGTH 2.9 TONN COIL, WEIGHT: 23 KILOS, 2. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 3. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 4. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 5. LENGTH: PER COIL: 220 METER. 6. OEM COC REQUIRED.	
131	DGE100 423	NIL	792070510179 1 / BROOM NYLON SIZE:1. X2"(BRUSH NYLON)		3 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
132	DGT100	NO DATA	0100000000000	SPECE/BSS	192 /	NO DATA					TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	436	AVAILABLE	3 / HARD BOARD SIZE 12'X4'X1/4"	1142/1971	SQ FEET	AVAILABLE					DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
133	DGE997 17	NO DATA AVAILABLE	834050503926 1 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length. 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos GENERAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length. 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
134	DGE100359	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	2 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET. ANTI RADAR CAMOUFLAGE					<p>insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p> <p><u>TECHNICAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p> <p><u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
135	DGE997 15	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATIO N	3 / EACH/N UMBER	OPTICAL INFRARE D CAMOUF LAGE NET, ANTI RADAR CAMOUF LAG					3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25- INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
											TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC. WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI- SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25- INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC. WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS. 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.</p>	
136	DGT993 92	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply.	X 19.05 MM)	480 / SQ FEET	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8'. Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply. Both face and back veneers of Gurjan-wood. and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shopGENERAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop	
137	DGE100426	NO DATA AVAILAB LE	055978000018 3 / SLEEVE PLASTIC GREEN 0.3X3 55P(DELETED NS/TD/32/611D T280989)		5 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
138	DGE99716	501256816 6895	402099396075 3 / ROPE FIBROUS, POLYESTER/		660 / METER						TECHNICAL SPECIFICATION - SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556, 2.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PROPYLENE MIX, 08-STRAND, DIA: 40MM								<p>40-MM DIA BLACK BERTHING POLYESTER/ PROPYLENE MIX, 8-STRAND MOORING NUMBER-5, MBL 26.4 TONNES, MB-67 TABLE-3, 3.8, PLAIN ENDS UV STABILISED ISO 9554 of 2019. 3. STANDARD ACCORDANCE TO ISO 2307 PACKAGING. 4. STANDARD OF MANUFACTURE ISO 2307 OF 2019 5. CONFIRMATION OF STANDARD EN-ISO 2307 OF 2019. 6. 220 METER PER COILS. 7. CERTIFICATIONS: VALID LLOYD TEST CERTIFICATE REQUIRED INDICATION BATCH/LOT NUMBER OF IDENTIFICATION AND WORKING / BREAKING AND STRENGTH OF STORES. 8. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM Phone: +44(0) 1323444444 EMAIL: sales@marlowropes.com</p> <p>GENERAL SPECIFICATION - SPECIFICATION:</p> <p>1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 40-MM DIA BLACK BERTHING POLYESTER/ PROPYLENE MIX, 8-STRAND MOORING NUMBER-5, MBL 26.4 TONNES, MB-67 TABLE-3, 3.8, PLAIN ENDS UV STABILISED ISO 9554 of 2019. 3. STANDARD ACCORDANCE TO ISO 2307 PACKAGING. 4. STANDARD OF MANUFACTURE ISO 2307 OF 2019 5. CONFIRMATION OF STANDARD</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											EN-ISO 2307 OF 2019. 6. 220 METER PER COILS. 7. CERTIFICATIONS: VALID LLOYD TEST CERTIFICATE REQUIRED INDICATION BATCH/LOT NUMBER OF IDENTIFICATION AND WORKING / BREAKING AND STRENGTH OF STORES. 8. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BS/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM Phone: +44(0) 1323444444 EMAIL: sales@marlowropes.com	
139	DGE64931	CTLCB10008025	5340735267410 / CANTILEVER BRACKET 3' (1000 X 80 X 2.5MM)		72 / EACH/NUMBER	CANTILEVER BARACKET 3' CTLCB10008025					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
140	DGB99558	VE-SB-305	5450505332794 / SIDE BRACKET 1FT		105 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
141	DGB95196	SPEC: NES837, DG SHIPS 8556B	0282595712163 / PIPING COPPER RD SEAMLESS EXT.DIA 0.625" THK.0.036" SWG 20		30 / METER						TECHNICAL SPECIFICATION - a. External Diameter : 0.625 inch b. External Thickness : 0.036 inch SWG 20 c. Parent Equipment: Air Conditioning & Refrigeration system d. Specifications: BS EN 12735/2 (relevant to Tubes for equipment) e. Material Designation: Copper & Copper Alloys Seamless, round	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											tubes for Air Conditioning & Refrigeration f. Temper Condition: Soft fully annealed copper coils g. Length of Item: In shape of Coil/ Roll of 50 feet length h. MTC: Not known/ Not available Material: Copper Pipe Shape: Round (RD) Manufacturing Type: Seamless External DIA: 0.625 inches Wall Thickness: 0.036 inches Standard Wire Gauge (SWG): 20 SWG Grade: Type L <u>GENERAL SPECIFICATION - a.</u> External Diameter : 0.625 inch b. External Thickness : 0.036 inch SWG 20 c. Parent Equipment: Air Conditioning & Refrigeration system d. Specifications: BS EN 12735/2 (relevant to Tubes for equipment) e. Material Designation: Copper & Copper Alloys Seamless, round tubes for Air Conditioning & Refrigeration f. Temper Condition: Soft fully annealed copper coils g. Length of Item: In shape of Coil/ Roll of 50 feet length h. MTC: Not known/ Not available Material: Copper Pipe Shape: Round (RD) Manufacturing Type: Seamless External DIA: 0.625 inches Wall Thickness: 0.036 inches Standard Wire Gauge (SWG): 20 SWG Grade: Type L	
142	DGE98911	NO DATA AVAILABLE	5895705124080 / CARD BOARD POSTAL BAG 12'X12'X06'804 ADJUST PARTITION		300 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
143	DGB97497		0283595711459 / ROD NAVAL BRASS RD DIA.2.50 INCH WT PER MTR 27.49 KG		4 / METER						<u>TECHNICAL SPECIFICATION - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU zN 39 SN</u> <u>GENERAL SPECIFICATION - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU zN 39 SN</u> 1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
144	DGB97178		028359571144 7 / ROD NAVAL BRASS RD DIA 01 INCH	GENERAL USE	1 / METER						TECHNICAL SPECIFICATION - BS EN 12163 OF 1998, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT :(LBS), R-LENGTH-03 METERS (EACH)GENERAL SPECIFICATION - BS EN 12163 OF 1998, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT : (LBS), R-LENGTH-03 METERS (EACH)	
145	DGB96259	NO DATA AVAILABL E	027770000347 7 / SPANNER OPEN JAW ADJ 0.50" X 0.57"		14 / EACH/N UMBER						TECHNICAL SPECIFICATION - Brand: Bahco Overall Length: 257 mm Wrench type: Adjustable Spanner Jaw Capacity: 33 mm Handle Type : Plastic/ Steel Material: Alloy SteelGENERAL SPECIFICATION - Brand: Bahco Overall Length: 257 mm Wrench type: Adjustable Spanner Jaw Capacity: 33 mm Handle Type : Plastic/ Steel Material: Alloy Steel	
146	DGE96647	NO DATA AVAILABL E	031050000000 6 / CANVAS COTTON NATURAL GREY (WD: 36 INCH)		150 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: Features: Water proof and Rot Proof Width & Length: 36" and 50 Meter roll Weight: 12 OZ per Sq. Yard Colour: Natural Grey GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY.GENERAL SPECIFICATION - SPECIFICATION: Features: Water proof and Rot Proof Width & Length: 36" and 50 Meter roll Weight: 12 OZ per Sq. Yard Colour: Natural Grey GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY.	
147	DGB96363	SPEC BS 2874 C 107-0	028359961098 2 / ROD COPPER RD ANNEALED		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABE	