

**LOCAL PURCHASE DIVISION – PAKISTAN NAVY**

**TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 03-06-2026**

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGB102063		021259571000 6 / BAR STEEL CARBON HOT ROLLED RD DIA 5/8"WT PER FT 1.043 LBS		190 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
2	DGH102061	NO DATA AVAILABL E	021159525922 5 / PLATE STEEL CARBON SIZE 2500X1250X05 MM .		4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025.STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010.</u> <u>GENERAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025.STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010.</u>	
3	DGB102079	1B1783	027559910551 4 / PLIERS NOSE FLATE 06" SINGLE JOINT, TO SPEC. BS 3087 TABLE 6	GENERAL USE (BR 320 D/76)	4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - BS 3087</u> <u>GENERAL SPECIFICATION - BS 3087</u>	
4	DGB102104	NO DATA AVAILABL E	02485000147 8 / CHEST 6 LEVER LOCK 33-5/8X26- 3/4X24-5/8		4 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH THICK 3/8 INCH									
5	DGB102 166	MILE2220 0-2QA	343900878215 4 / ELECTRODE WELDING AWS E308-16 DIA: 2.6MM (LENGTH PER UNIT/ELECTR ODE: 300 MM)	WELDING (STEEL)	20 / KILOGR AMME						<p><u>TECHNICAL SPECIFICATION - Ø:</u> 2.6 mm Spec: AWS A5.4-81 E 308-16 Chemical Composition C 0. 02 Si 0.8 Mn 1.0 Ni 10.0 Cr 19.5 Tensile STRENGTH : 590 N/mm2 Current RANGE: 60-90 Amps Area reduction: 50.0% Elongation: 40.0% Packaging: 01 kg per bag. Final delivery with one batch/lot Classification SOCIETY: Approval of any international classification i.e. LR,BV,ABS,DNV. GL,Ce,JIS,ISO-9001-2015</p> <p><u>GENERAL SPECIFICATION - Ø: 2.6 mm Spec: AWS A5.4-81 E 308-16 Chemical Composition C 0. 02 Si 0.8 Mn 1.0 Ni 10.0 Cr 19.5 Tensile STRENGTH : 590 N/mm2 Current RANGE: 60-90 Amps Area reduction: 50.0% Elongation: 40.0% Packaging: 01 kg per bag. Final delivery with one batch/lot Classification SOCIETY: Approval of any international classification i.e. LR,BV,ABS,DNV. GL,Ce,JIS,ISO-9001-2015</u></p>	
6	DGB102 244		512000247074 8 / WRENCH SET SOCKET 13 COMPONENT S		4 / SET						<p><u>TECHNICAL SPECIFICATION -</u> Contains 1 each Chrome Plated: 06 Points: 3/8 Inch. Female SQ Drive: Deepweel: Fractional sizes: (1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, and 1 Inch make: UK / USA</p> <p><u>GENERAL SPECIFICATION -</u> Contains 1 each Chrome Plated: 06 Points: 3/8 Inch. Female SQ Drive: Deepweel: Fractional sizes: (1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, and 1 Inch make: UK / USA</p>	
7	DGB102 081	NO DATA AVAILABL E	512099910596 2 / SPANNER OPEN JAW ADJ 04 4 IN AF .05 INCH	TOOLS FOR ELECT EQUIPMENT NASR	4 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
8	DGB101	C60	047450448149	FOUNDRY	1 /						<p><u>TECHNICAL SPECIFICATION - NO</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	951		7 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	USE OEM MORGANITE UK FAX NO	EACH/NUMBER						DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DGE101960	N/A	9330705181279 / PLASTIC SHEET	GENERAL ITEM	5 / ROLL			LOCAL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
10	DGE102145	N/A	9330705181279 / PLASTIC SHEET	GENERAL ITEM	20 / ROLL			LOCAL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
11	DGE101587	N/A	9330705181279 / PLASTIC SHEET	GENERAL ITEM	15 / ROLL			LOCAL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
12	DGE101896	N/A	9330705181279 / PLASTIC SHEET	GENERAL ITEM	15 / ROLL			LOCAL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
13	DGT101829	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	96 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ONLY) moisture contents: 06 % to 18%	
14	DGE101 949	2040	5330705131806 / RUBBER STRIP	DOOR&HATCHES SEAL	20 / METER	NO DATA AVAILABLE		PK		ABBASI TRADER S RUBBER STORE PH#2416 152	TECHNICAL SPECIFICATION - 1GENERAL SPECIFICATION - 1	
15	DGE101 943	NOT KNOWN	7920705181271 / BROOM SCRUBBING DECK (FOR DECONTAMINATION)	NIL	16 / EACH/NUMBER		NIL	LOCAL MARKET		NIL	TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21 GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21	
16	DGE101 448	NIL	6515705181277 / TOWEL PAPER 24 ROLLS PER PACK	NIL	22 / CARTON			LOCAL MARKET		NOT KNOWN	TECHNICAL SPECIFICATION - No of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 Inch GENERAL SPECIFICATION - No of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 Inch	
17	DGE101 721	6540967	4510014922928 / Toilet Bowl	Vacuum Toilet	2 / EACH/NUMBER	Evac, 910 Wall Prestige Silent	0	1445 HUNTWOOD DR CHERRY VALLEY IL		EVAC NORTH AMERICA INC.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
18	DGE101 623	NIL	7210505155172 / FIRE RETARDANT SPRING MATTRESS (L6' X W2' X H6")	MATRESSES FOR BED	23 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX:		AL-KHAIR HOUSE-43-T	TECHNICAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 GENERAL SPECIFICATION - size: length: 6 Feet width: 2 Feet	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								042-5716588,5753719.			height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
19	DGE101772	NIL	7210505155172 / FIRE RETARDANT SPRING MATTRESS (L6' X W2' X H6")	MATRESSES FOR BED	22 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		<u>TECHNICAL SPECIFICATION</u> - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413 <u>GENERAL SPECIFICATION</u> - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
20	DGE102112		0422705158411 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	1800 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTICS, SADDAR KARACHI		<u>TECHNICAL SPECIFICATION</u> - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM <u>GENERAL SPECIFICATION</u> - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
21	DGE101954	GGG-H-142	8415009351906 / SAFETY HELMET YELLOW	PERSONAL PROTECTION	4 / EACH/NUMBER			FEDERAL SPECIFICATIONS UNITED STATES CAGE CODE 81348	FEDERAL SPECIFICATIONS		<u>TECHNICAL SPECIFICATION</u> - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000 <u>GENERAL SPECIFICATION</u> - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000	
22	DGE101831	7920-00-148-9666	7920001489666 / Rag wiping Cotton & cotton synthetic 50 lbs	NIL	250 / SET	NA	NA	ALFA LAVAL TUMBA AB, HANS STAHLER VAG 7 TUMBA SWEDEN	ALFA LAVAL TUMBA AB, SWEDEN		<u>TECHNICAL SPECIFICATION</u> - PMS Item <u>GENERAL SPECIFICATION</u> - PMS Item	
23	DGE101378	7920-00-148-9666	7920001489666 / Rag wiping Cotton & cotton synthetic 50 lbs	NIL	60 / SET	NA	NA	ALFA LAVAL TUMBA AB, HANS STAHLER VAG 7 TUMBA SWEDEN	ALFA LAVAL TUMBA AB, SWEDEN		<u>TECHNICAL SPECIFICATION</u> - PMS Item <u>GENERAL SPECIFICATION</u> - PMS Item	
24	DGE101897	NIL	7460705141092 / REVOLVING COMPUTER CHAIR	REVOLVING COMPUTER CHAIR	6 / EACH/NUMBER	NO DATA AVAILABLE		PK	MASTER AUTHORIZED DEALER SHAHRA FAISAL KARACHI		<u>TECHNICAL SPECIFICATION</u> - OEM ADD:M/S TIME&TUNE,60 A-8,1ST FLOOR,KHAN CHAMBERS, CANNING ROAD,RAWALPINDI, PAKISTAN <u>GENERAL SPECIFICATION</u> - OEM ADD:M/S TIME&TUNE,60 A-8,1ST FLOOR, KHAN CHAMBERS,CANNING ROAD,RAWALPINDI,PAKISTAN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
25	DGE101 941	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	1000 / EACH/N UMBER	SSP-01- LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTA N		TECHNICAL SPECIFICATION - AS PER LETTER ATTACH GENERAL SPECIFICATION - AS PER LETTER ATTACH	
26	DGE101 666	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	1000 / EACH/N UMBER	SSP-01- LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTA N		TECHNICAL SPECIFICATION - AS PER LETTER ATTACH GENERAL SPECIFICATION - AS PER LETTER ATTACH	
27	DGT101 748	NO DATA AVAILABL E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTAB LISHMENT	35 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92- 21- 32776064 .MOBILE 0322- 2578654.		TECHNICAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM GENERAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	
28	DGB101 854	F06DSS	403079515299 3 / STAINLESS STEEL SHACKLE 06 MM DEE TYPE (S.W.L)	TAL SHIP SAILING RIG	20 / EACH/N UMBER			EURO PRODUCTS. INC, TELL:206 789 6468#800 577 5877 FAX:206 784 E MAIL; EUROPRODUCTSINC. COM#SALES@	UK		TECHNICAL SPECIFICATION - EURO PRODUCTS. INC,TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC. COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG.GENERAL SPECIFICATION - EURO PRODUCTS. INC,TELL;206 789	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC. COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG.	
29	DGB101 857	F12DSS	403079515299 2 / STAINLESS STEEL SHACKLE 12 MM DEETYPE (S.W.L)	TAL SHIP SAILING RIG	20 / EACH/NUMBER			EURO PRODUCTS, INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL; EUROPRODUCTSINC. COM#SALES@	UK		TECHNICAL SPECIFICATION - EURO PRODUCTS, INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC. COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG.GENERAL SPECIFICATION - EURO PRODUCTS, INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC. COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG.	
30	DGE101 591	H R 550	802000598408 0 / COVER PAINT ROLLER	PAINT ROLLER	15 / EACH/NUMBER	CAGE CODE ODRR8		FEDERAL SPECIFICATION USA CAGE CODE 81348ODRR8	FEDERAL SPECIFICATION S USA		TECHNICAL SPECIFICATION - MATERIAL FIBER , POLYESTER PILE HEIGHT 0.625 INCHES NOMINAL , NOMINAL LENGTH 7.000 INCHESGENERAL SPECIFICATION - MATERIAL FIBER , POLYESTER PILE HEIGHT 0.625 INCHES NOMINAL , NOMINAL LENGTH 7.000 INCHES	
31	DGE101 968	EM 3061	593572512993 6 / RAYCHEM HEAT SHRINK	-	2 / EACH/NUMBER			GR	GMBH GERMAN Y		TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
32	DGE101 571	5557 SERIES	685071518046 0 / WATER CONTACT INDICATOR tape 5 X 5 MM	ADHESIVE TYPE INDICATION TAPE	10 / EACH/NUMBER	MSDS MATERIAL		3M	3M USA		TECHNICAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm) GENERAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm)	
33	DGE101 894	5557 SERIES	685071518046 0 / WATER CONTACT INDICATOR tape 5 X 5 MM	ADHESIVE TYPE INDICATION TAPE	10 / EACH/NUMBER	MSDS MATERIAL		3M	3M USA		TECHNICAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm) GENERAL SPECIFICATION - color :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm)	
34	DGE101567	-	561099200438 6 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	124 / KILOGRAMME	NO DATA AVAILAB LE		UK	FLOWCR ETE UK LTD THE FLOORIN G TECHNO LOGIES CENTRE BOOTH LANE SANDBA TCH CHESHIR E CW11 3QF UK PH:+44(0)1270 753000 & FAX :+44 (0)1270 753333		TECHNICAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&i(M) DC&FF.GENERAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&i(M) DC&FF.	
35	DGE102159		033050942726 7 / FLANNELETTE CLOTH WHITE GROUND WITH RED STRIPT 4"X50 YARDS	SMALL ARMS CLEANING	610 / METER						TECHNICAL SPECIFICATION - BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural.GENERAL SPECIFICATION _BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural.	
36	DGB102249		027779433464 4 / TOOL BOX PORTABLE 18X6X 1-15/16IN STEEL ENAM		4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	-
37	DGB101866		028370000160 6 / ELECTRODE		80 / METER						TECHNICAL SPECIFICATION - a. Size 3.25 x 350 mm b. Current 90-120 c. Polarity DC Electrode	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			MONO METAL 08 SWG								Negative (DCEN) d. Position Flat, Horizontal, Vertical, Overhead e. Type of Arc Medium, Moderate, Penetration f. Material Low Carbon Steels g. Technique Use short Arc length with electrode angle 30o + 15o , to the line of weld. h. (8SWG) Mild Steel (HYUNDAI) <u>GENERAL SPECIFICATION</u> - a. Size 3.25 x 350 mm b. Current 90-120 c. Polarity DC Electrode Negative (DCEN) d. Position Flat, Horizontal, Vertical, Overhead e. Type of Arc Medium, Moderate, Penetration f. Material Low Carbon Steels g. Technique Use short Arc length with electrode angle 30o + 15o , to the line of weld. h. (8SWG) Mild Steel (HYUNDAI)	
38	DGB102 248		027779923816 4 / TOOL BOX PORTABLE		4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm <u>GENERAL SPECIFICATION</u> - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm	
39	DGE101 627	0413-8532 &0413_92 3_8899, BS1154	041359923889 9 / RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 HARDNESS RATING 42- 50°,TENSILE STRENGTH : 2500 PSI		650 / KILOGR AMME						<u>TECHNICAL SPECIFICATION</u> - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 <u>GENERAL SPECIFICATION</u> - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21	
40	DGE101 996	0413-8532 &0413_92 3_8899, BS1154	041359923889 9 / RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 HARDNESS RATING 42- 50°,TENSILE STRENGTH : 2500 PSI		20 / KILOGR AMME						TECHNICAL SPECIFICATION - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 GENERAL SPECIFICATION - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21	
41	DGE101 811	BS 2848	055979444489 9 / INSULAT. SLEEVE ELEC. VARNISHED GLASS FIBRE I/D 4MM,TH 0.5 MM	GENERAL ELECTIC USE	30 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DGE101 373	NO DATA AVAILABL E	055979020048 5 / INSULATION- TAPE- POLYETHYLE NE TERAPHALAT E(TERYLENE) W/0.75		45 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
43	DGE101 977	NO DATA AVAILABL E	055979020048 5 / INSULATION-TAPE-POLYETHYLE NE TERAPHALAT E(TERYLENE) W/0.75		10 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DGE101 669	U1901 AND P35M	041459923069 9 / PACKING ASSY MICA SZ.1.5/32,OD. 3/4,I/D 13/64 2 PERSET SQ. C/S		2 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DGE101 449	NO DATA AVAILABL E	055979002055 2 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DGE101 979	NO DATA AVAILABL E	055979002055 2 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	28 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DGE101 447	DGS 6971	041359923876 1 / HOSE RUBBER, LENGTH= 60- FEET, NOMINAL OVERALL INTERNAL DIA= 0.500 INCHES, OUTSIDE DIA= 0.875 INCHES		50 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
48	DGE101814	NO DATA AVAILABLE	0559794444690 / RUBBER-TAP-INSULATION		35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DGE101974	0.75X0.007INCH-50MTR-	0559790015244 / INSULATION-TAPE-VARNISHED WOVEN GLASS-FIBRE-(STRAIGHT CUT)		15 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
50	DGE101369	0414-7801	0414599230902 / PACKING MATERIAL COTTON YARN FOR FRESH WATER PUMP SIZE 1/4"SQ		9 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
51	DGE101947	04769430557, BS2992TABLE8ITEM 8/5	0476599430557 / BRUSH VARNISH TYNEX FIBER FLAT SQUARE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	19 / EACH/NUMBER						TECHNICAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUARE EDGE 4. Packaging Separately packed/ wrapped/ any suitable GENERAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUARE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
52	DGE101944	NIL	0476599430558 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OUNCES	
53	DGE101 981	NIL	055979444489 8 / INSULATION SLEEV ELEC INT DIA 3MM THICK0.500 MATER CERAMIC	GENERAL ELECTRIC USE	43 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
54	DGE101 809	NIL	055979444489 8 / INSULATION SLEEV ELEC INT DIA 3MM THICK0.500 MATER CERAMIC	GENERAL ELECTRIC USE	10 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
55	DGE102 172	NO DATA AVAILABL E	035059571311 8 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875") (5MM)		120 / FATHO M	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI</u> <u>GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021,</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI</p>	
56	DGE102 119	nil	035059571312 1 / Rope Nylon, Hawser laid, White, 3- Strand, Cir: 1- Inch, Diameter: 8-MM		120 / FATHO M						<p>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
57	DGB101 842	AWS S- 8018-B2	028370001183 8 / ELECTRODE WELDING 2.6 MM AWS S- 8018-B2	WELDING SYSTEMS	120 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
58	DGB102 031		028359571143 3 / ROD NAVAL BRASS HEX SIZE A/F 1.10"WT PER FT 3.910(LB)		1 / METER						<u>TECHNICAL SPECIFICATION</u> - SPECS BSEN 12163, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet <u>GENERAL SPECIFICATION</u> - SPECS BSEN 12163, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet	
59	DGB102 008		028359571145 6 / ROD NAVAL BRASS RD DIA 2.12	SP.BS 2874,CZ 112M	4 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH WT.13.14 PER FOOT(LB)									
60	DGB102 099		028359571147 4 / SHEET- NAVAL- BRASS- ANNEALED 48		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
61	DGB102 246	FA14774/ EC2002M	027670910527 0 / SOLDERING IRON NON ELECT.ST. TYPE.WT.12 OZ.BIT SZ. 3/4SQIN.D.T		2 / EACH/N UMBER	T0053298 399					TECHNICAL SPECIFICATION - Make: Germany Brand: WELLER WE1010GENERAL SPECIFICATION - Make: Germany Brand: WELLER WE1010	
62	DGE101 991	BS 1154	041359923892 1 / RUBBER SHEET SOLID NATURAL LG. 72 WD 48 INCH THICKNESS 01 INCH		20 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
63	DGE101 442	NO DATA AVAILABL E	045159451001 3 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	55 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINSGENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	
64	DGE101 957	0414-5160	041459923093 4 / SHEET, ASBESTOS, COMPRESSE D TH 1/16", WD 54"X63" IN WT PER SHEET 22LBS		25 / KILOGR AMME						TECHNICAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)GENERAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)	
65	DGE101 662	0414-5160	041459923093 4 / SHEET,		3 / KILOGR						TECHNICAL SPECIFICATION - BS2815, GRADE A, FOR WATER,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ASBESTOS, COMPRESSE D TH 1/16", WD 54"X63" IN WT PER SHEET 22LBS		AMME						STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)GENERAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)	
66	DGE101 956	0414-5162	041459923093 5 / ASBESTOS SHEET COMPRESSE D,	GENERL PERPOSE	28 / KILOGR AMME						TECHNICAL SPECIFICATION - a. Standard/ Grade: BS 2815, Grade A b. Length = 60 Inch c. Width = 60-80 INCH d. Thickness= 3-MM e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS-2815GENERAL SPECIFICATION - a. Standard/ Grade: BS 2815, Grade A b. Length = 60 Inch c. Width = 60-80 INCH d. Thickness= 3-MM e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS-2815	
67	DGE101 990	NIL	041359923892 3 / RUBBER SHEET SOLID NATURAL (CLOTH INSERT)		25 / KILOGR AMME						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCRL: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL. GENERAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCRL: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.	
68	DGE101 989	NIL	041359923892 4 / RUBBER SHEET SOLID NATURAL		30 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - BS 1154 OF 1992 COMPUND Y2 COMPOUND CLASSIFICATION Y-50 Cloth insert, also known as rubber insertion, Thick: 0.063 inch, width: 43 inch, No of PLY: 01 Approx, wt per sq ft: ½ Lbs, tensile strength 17Mpa, Hardness: 50+5-4. Spec: BS 1154</u></p> <p><u>GENERAL SPECIFICATION - BS 1154 OF 1992 COMPUND Y2 COMPOUND CLASSIFICATION Y-50 Cloth insert, also known as rubber insertion, Thick: 0.063 inch, width: 43 inch, No of PLY: 01 Approx, wt per sq ft: ½ Lbs, tensile strength 17Mpa, Hardness: 50+5-4. Spec: BS 1154</u></p>	
69	DGE101 544	0413-8553	041359923892 6 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		87 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLIES=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"</u></p> <p><u>GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLIES=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
70	DGE101988	0413-8553	041359923892 6 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		25 / KILOGRAMME						TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50" GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"	
71	DGE101955	NO DATA AVAILABLE	041359923969 2 / HOSE RUBBER NATURAL RUBBER INNER SURFACE COTTON BRAND ENFORCED INTERNAL DIA. 2.00 NO PLYS 3" WALL THICK 23/64		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
72	DGB102092		026759521328 5 / Piping Steel Galv 3050x4.0x0.250		40 / METER						TECHNICAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable. GENERAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable.	
73	DGB102090		026759521328 1 / PIPING STEEL GALV SEAMLESS,	GENERAL USE	60 / METER						TECHNICAL SPECIFICATION - 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			EXT DIA: 60.3 mm,WALL THKNESS: 3.6 mm,N/BORE: 50.8mm, running length 6 meter								Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships. <u>GENERAL SPECIFICATION -</u> 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships.	
74	DGT101 750	NO DATA AVAILAB L E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIV E		320 / SQ FEET						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) <u>GENERAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
75	DGT101 833	NO DATA AVAILAB L E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIV E		320 / SQ FEET						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) <u>GENERAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
76	DGH102 182	SPEC: DNC/S.30	021159923017 8 / SHEET		6 / EACH/N						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILAB L E	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			STEEL CARBON COLD ROLLED SIZE 1830X910X2M M		UMBER						SPECIFICATION - NO DATA AVAILABLE	
77	DGH102 038		023159571531 3 / WIRE ROPE GRIP STEEL DIA 0.398".		100 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
78	SGB102 041		021459043020 6 / NUT-PLAIN- HEXAGON- BSW-0.56INCH THREAD SIZE 9/16"THICK 0.500		120 / TEN						TECHNICAL SPECIFICATION - AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) Spec: BS-970 material grade: EN4140 THICKNESS: 1/4" INNER DIA: 1/2" OUTER DIA: 7/8" THREAD SIZE: 9/16" Material Grade EN4140 coc/mtc required GENERAL SPECIFICATION - AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) Spec: BS- 970 material grade: EN4140 THICKNESS: 1/4" INNER DIA: 1/2" OUTER DIA: 7/8" THREAD SIZE: 9/16" Material Grade EN4140 coc/mtc required	
79	DGB101 867	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	150 / KILOGR AMME						TECHNICAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm- 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface GENERAL SPECIFICATION _a. Dia: 3.2mm b. Length: 350 mm- 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
80	DGB102 247		027379000411 4 / CUTTER INSULATION REMOVING DIAMETER	USE: PYROTENAX CABLE	6 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CAPACITY 0.744IN									
81	DGH102 183	SPEC:BS 826	028159455963 6 / Panel storage & Display Shelving		24 / EACH/N UMBER						TECHNICAL SPECIFICATION - GREY 63"H X 18.25" W 3XSIDES SHEET METALIC. SIZE 3,63"H X 18 1/4"NOMINAL BAY DEPTH GENERAL SPECIFICATION - GREY 63"H X 18.25" W 3XSIDES SHEET METALIC. SIZE 3,63"H X 18 1/4"NOMINAL BAY DEPTH	
82	DGB102 240	NO DATA AVAILABL E	026359923698 7 / THIMBLE, ROPE STEEL BS 970-EN 3A GALVANISED PEAR SHAPED OPEN TYPE WT 1.75LBS SIZE 1.25	SPEC NO DGS 5031NO.40	400 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	DGE101 547		005070000038 4 / CORRECTING- TAPE- HERMESTOP- TRONIC-21		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
84	DGB101 952		026459124068 6 / CHESTTOOLKI T		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DGB102 007	NO DATA AVAILABL E	024378000108 7 / CEASING WIRE 1MM 2185MB	S/M	5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DGB102 243	0251- 14505	025170411973 7 / FERRULE- WIRE-ROPE 1.5 INCH (12mm)		190 / EACH/N UMBER						TECHNICAL SPECIFICATION - MATERIAL aluminum alloy SHAPE ELLIPSE TYPE COLOR SILVER INTERNAL WIDTH 26 MM INTERNAL HEIGHT 13 MM OUTER DIA 36 MM OUTER LENGHT 42 MM BODY THICKNESS 05 MM GENERAL SPECIFICATION - MATERIAL aluminum alloy SHAPE ELLIPSE TYPE COLOR SILVER INTERNAL WIDTH 26 MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											INTERNAL HEIGHT 13 MM OUTER DIA 36 MM OUTER LENGHT 42 MM BODY THICKNESS 05 MM	
87	DGB102096		0267595213274 / PIPING STEEL BLACK 5.00X5.500X0.192IN		20 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
88	DGE101963	947-430229	H947995600582 / RUBBER STRIP	GENERAL PURPOSE	26 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
89	DGE102019		2040PK5101052 / RUBBER SHEET SIZE WEIGHT: 10-KG, LENGTH: 7-ft, WIDTH: 1-FT, THICKNESS: 3/8-INCH	FENDER	20 / KILOGRAMME						TECHNICAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@LIVE.COM (2) LONGMAN KAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552 GENERAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552	
90	DGE101570	NO DATA AVAILAB L E	047654600594 7 / BRUSH SABLE HAIR NO.4.		10 / EACH/N UMBER	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - NO DATA AVAILAB L E GENERAL SPECIFICATION - NO DATA AVAILAB L E	
91	DGE101984	NO DATA AVAILAB L E	047659923891 9 / RUBBER SHEET (SIZE: L 2250 x W 2250 x THKNES S 12MM)		15 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILAB L E GENERAL SPECIFICATION - NO DATA AVAILAB L E	
92	DGE101568	NO DATA AVAILAB L E	047654600594 9 / BRUSH WRITING NO-6		15 / EACH/N UMBER	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - NO DATA AVAILAB L E GENERAL SPECIFICATION - NO DATA AVAILAB L E	
93	DGE101945	NO DATA AVAILAB L E	046150000679 2 / CHALK WHITE SOFT	W/T DOORS & FIT	28 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILAB L E GENERAL SPECIFICATION - NO DATA AVAILAB L E	
94	DGE101558	NO DATA AVAILAB L E	046154600568 3 / PAPER ABRASSIVE WATER PROOF 9" X11".		30 / SHEET	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - NO DATA AVAILAB L E GENERAL SPECIFICATION - NO DATA AVAILAB L E	
95	DGB102146	FAG 6310 ZC3 (3110-00-891-8891)	311000927791 7 / BEARING BALL ANNULAR SZ 50.00X110.00X27.00MM	NO 1&3 FUEL OIL SERVICE	11 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB L E GENERAL SPECIFICATION - NO DATA AVAILAB L E	
96	DGE102158	NO DATA AVAILAB L E	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH &amp; LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u>  SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
97	DGE101 450	FEC-32- 5113	424070511240 9 / GAS MASK RESPIRATOR 3M		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
98	DGB101 841	CATLOG- NO.(USA) 42-059- 008WHITE	343971506689 2 / ELECTRODE (WHITE)TUFF COTE CUTTING U/WATER DIA 5/16X18	FOR GENERAL USE	300 / PACKE T						<u>TECHNICAL SPECIFICATION -</u> Size: 3/8" x 18" Polarity: DC Electrode Negative (DCEN) Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration Material: Low Carbon Steels Technique: Use short Arc length with electrode angle 30o +15o, to the line of weld. UTILIZED DURING UNDERWATER WELDING OPERATION. MUST BE AS PER ISO 9000 STANDARD. MUST HAVE WATER PROOF COATING. <u>GENERAL SPECIFICATION -</u> Size: 3/8" x 18" Polarity: DC Electrode Negative (DCEN) Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration Material: Low Carbon Steels Technique: Use short Arc length with electrode angle 30o +15o, to the line of weld. UTILIZED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DURING UNDERWATER WELDING OPERATION. MUST BE AS PER ISO 9000 STANDARD. MUST HAVE WATER PROOF COATING.	
99	DGE101602	NO DATA AVAILABLE	4220795055193 / WHISTLE PLASTIC FOR GENERAL SERVICE LIFE JACKET	LIFE JACKET MK-1, ORALLY INFLATED	30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
100	DGB101840	NO DATA AVAILABLE	3439715045032 / WET WELDING ELECTRODE UW-CS-1 (1/8" OR 3.2 MM)	UNDERWATER WELDING DURING SALVAGE OPS/TRAINING	1000 / PACKET						TECHNICAL SPECIFICATION - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration GENERAL SPECIFICATION - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration	
101	DGB101869	NO DATA AVAILABLE	3439715045034 / ELECTRODE SEA WELD 5/32X14 IN		1000 / PACKET						TECHNICAL SPECIFICATION - a. Detailed Specifications : UW-CS-2 Electrode Welding 5/32 Inches (4.0 mm) b. Technical data : AWS E70XX c. Polarity : DC Electrode Negative (DCEN) d. Position : Flat, Horizontal, Vertical, Overhead e. Type of Arc : Medium, Moderate, Penetration f. Material : Low Carbon Steels g. Technique : Use short Arc length with electrode angle 30 o + 15 o , to the line of weld. 2. Acceptance criteria : Item will be accepted upon technical rep inspection. GENERAL SPECIFICATION - a. Detailed Specifications : UW-CS-2 Electrode Welding 5/32 Inches (4.0 mm) b. Technical data : AWS E70XX c. Polarity : DC Electrode Negative (DCEN) d. Position : Flat, Horizontal,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Vertical, Overhead e. Type of Arc : Medium, Moderate, Penetration f. Material : Low Carbon Steels g. Technique : Use short Arc length with electrode angle 30 o + 15 o , to the line of weld. 2. Acceptance criteria : Item will be accepted upon technical rep inspection.	
102	DGB102 147	6308ZZ	311000158816 1 / BEARING BALL ANNUAL SIZE . 40X90X23.		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM: SKF Model: AB SKF 6308ZZ, Origin USA/ Sweden, Locally available. GENERAL SPECIFICATION - OEM: SKF Model: AB SKF 6308ZZ, Origin USA/ Sweden, Locally available.	
103	DGB102 255	SKF 6217ZZ	311000155633 5 / BEARING BALL ANNULAR SKF 6217ZZ SZ 85.00X150.00X28.00MM		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
104	DGE101 667	NIL	343876501061 5 / WELDING GOGGLES FOR GAS WELDER SET	MARINE AC ARC WELDER 500A (SV BHER PAIMA	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DGB102 281	NO DATA AVAILAB L E	512073100065 4 / SCREW DRIVER FLAT PIONT 8PCS SET INTERCHANG EABLE(CHINA MADE)		1 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DGB102 245		512073100118 4 / SCREWDRIVE R IMPACT SET 1/2IN SQ DRIVE		3 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DGE101 531		535000235013 7 / PAPER ABRASIVE 9" X11" WATER		225 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PROOF MATERIAL GLASS GRADE 2/0									
108	DGE101 586	A-A-1201, P-P-121, ANSIB74-18	5350001868820 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE 110-A		20 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
109	DGE101 572	A-A-1201	5350002210882 / PAPER ABRASIVE	FIRE FIGHTING EQUIPMENT	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DGE101 581	GRADE 320	5350PK5104070 / WATER PROOF SAND PAPER GRADE 320	WOODEN & GRP BOATS,, AQUATIC CLUB D/YARD	50 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
111	DGE101 598	GRADE400	5350PK5104071 / WATER PROOF SAND PAPER GRADE400	WOODEN & GRP BOATS,, AQUATIC CLUB D/YARD	100 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
112	DGE101 561	GRADE600	5350PK5104072 / WATER PROOF SAND PAPER GRADE 600	WOODEN & GRP BOATS,, AQUATIC CLUB D/YARD	120 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
113	DGT101 752	NO DATA AVAILAB L E	5530705042933 / PLY WOOD NATURAL TEAK FINISH ONE SIDE (NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W=4' TH=03mm to 04mm	PRESENTATIO N BOXES FOR VVIPS	160 / SQ FEET						TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm GENERAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer =	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											0.6mm	
114	DGE101 942	000W280	599999784543 2 / BRAID-BANDAGE (WIRE MES KNITTED)	GLASS WOOL (DC BOX)	8 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
115	DGE101 375	0413-2184	597099923966 4 / TAP INSULATION ELECT ADHESIVE PLASTIC RED W1	FOR RED PHASE	60 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing</u> <u>GENERAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing</u>	
116	DGE101 948	SA9-27077PF.	626001178556 0 / LIGHT, CHEMILUMINE SCENT 6inch BLUE	REPLENISHMENT LIGHT	275 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
117	DGE101 589	NIL	792070510179 1 / BROOM NYLON SIZE:1. X2"(BRUSH NYLON)		6 / DOZEN						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
118	DGE101 539	NO DATA AVAILABLE	041350000013 3 / EAR DEFENDER		61 / PAIR	PELTOR H10A/OPTIME 105					<u>TECHNICAL SPECIFICATION - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar &amp; Industrial Safety Equip)</u> <u>GENERAL SPECIFICATION - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(HAC Hardwar & Industrial Safety Equip)	
119	DGB102165	NO DATA AVAILAB E	026850000003 6 / AVERY- SCALE- PLATFORM- NO3205CAPA CITY250KG SELF INDICATING	AND MOUNTED ON WHEEL.SIZE OF PLATFORM24"	2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
120	DGB102018	NO DATA AVAILAB E	026350000127 6 / TURN BUCKLE HOOK & EYE		30 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - Complete Dimensions: Length- 295 mm (11.61 Inches) Thread-12.7 mm (0.5 Inch) Material grade:forgad galvanized steel Testing/acceptance criteria: 1000lbs make, model, brand: Aashi Enterprises Suite # 48, 3rd, Floor Moosa Market / Shah rah Liaquat Karachi-74000. PH- +92-21-32427508 +92-21-32465654 Fax- +92-21-32432083 E-mail: ashenterprises.gsel@gmail.co ma shenterprises@hotmail.com</u> <u>GENERAL SPECIFICATION - Complete Dimensions: Length- 295 mm (11.61 Inches) Thread-12.7 mm (0.5 Inch) Material grade:forgad galvanized steel Testing/acceptance criteria: 1000lbs make, model, brand: Aashi Enterprises Suite # 48, 3rd, Floor Moosa Market / Shah rah Liaquat Karachi-74000. PH- +92-21-32427508 +92-21-32465654 Fax- +92-21-32432083 E-mail: ashenterprises.gsel@gmail.co ma shenterprises@hotmail.com</u>	
121	DGE101599	NO DATA AVAILAB E	047450000030 7 / FENDER COIR ROUND		4 / EACH/N UMBER	600MM 24" ROUND COIR BOAT FENDER					<u>TECHNICAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY. <u>GENERAL SPECIFICATION -</u> CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.	
122	DGE101 582	NO DATA AVAILABLE	046150000109 / PAPER ABRASSIVE WATER PROOF 9" X11".		200 / SHEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
123	DGE102 130	NO DATA AVAILABLE	7920005436492 / PAPER TOWEL		7 / BOX						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
124	DGE102 175	NIL	8105011242645 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217-9451	STATIC SAFETY OF EQUIPMENT/COMPONENTS	20 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557 <u>GENERAL SPECIFICATION -</u> ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
125	DGE101 964		813570506488 2 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
126	DGE101 608		830599129238 7 / CLOTH, CURTAING PLASTIC FOR BATHROOM (LENGTH 2 meters x WIDTH 1.37 meters x THICK 0.02 meters)	SPECIAL CLOTH DESIGEN	50 / METER						TECHNICAL SPECIFICATION - LENGTH 2 meters x WIDTH 1.37 meters x THICK 0.02 meters standard packing updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085093 dated 13 aug 21 GENERAL SPECIFICATION - LENGTH 2 meters x WIDTH 1.37 meters x THICK 0.02 meters standard packing updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085093 dated 13 aug 21	
127	DGT101 830	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM )	160 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' &amp; THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p>	
128	DGT101751	NO DATA AVAILAB LE	010050000002 8 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLYS OF SHESHAM WOOD) 5-PLY	2.440X1.220MTRX6.35MM) SPECE/BS-1088	520 / SQ FEET	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - 1.</u>            SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I &amp; II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM. 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, <u>GENERAL SPECIFICATION -</u>            1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I &amp; II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,	
129	DGE101588	NO DATA AVAILAB L E	04765000006 1 / GLOVES LEATHER FOR WELDING, treated with presservative, standard quality		32 / PAIR	NO DATA AVAILAB L E					<p><u>TECHNICAL SPECIFICATION - 1.</u>  DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL  <u>details:</u> 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex  <u>GENERAL SPECIFICATION - 1.</u>  DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex	
130	DGE101 913	NO DATA AVAILABL E	04765000006 1 / GLOVES LEATHER FOR WELDING, treated with presservative, standard quality		147 / PAIR	NO DATA AVILAB LE					<p>TECHNICAL SPECIFICATION - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL            details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex</p> <p>GENERAL SPECIFICATION - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex	
131	DGB102163	NO DATA AVAILAB LE	026850000006 1 / SCALE- SPRING- BALANCE-20- STONE-280- LBS		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow <u>GENERAL SPECIFICATION -</u> Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow	
132	DGE102160	NO DATA AVAILAB LE	045150000001 6 / TAPE- WHITE- COTTON		750 / YARD	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILAB <u>LE</u> <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
133	DGE101371	MIL-G-1149	932000282662 4 / RUBBER SHEET LG 50 FT, WD 03 FT, TH 2.5 MM		15 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILAB <u>LE</u> <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
134	DGE101961	NO DATA AVAILAB LE	933070505435 4 / PLASTIC SHEET BLACK	FOR PN CREST	2 / SHEET						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILAB <u>LE</u> <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH 1220MM WIDTH 610MM THICKNESS 12MM								AVAILABLE	
135	DGE101 600	NO DATA AVAILABL E	933070505435 4 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PN CREST	6 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
136	DGT101 832	BELFONT TRUWOOD DTEAK	933099224609 7 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		12 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
137	DGE101 959		614579502372 4 / CABLE TIE 2.5 MM NYLON BLACK	TX/RX VRM	100 / PACKE T						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
138	DGH102 184		712599129769 4 / ANGLE POSTS STORAGE SHELVING 123		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material : Steel/ Aluminum Length: 6 feet to 24 feet Width: 02" to 6" Angle : 90 Degrees (standard) Thickness: 1/4" to 1" Size: 2x2x 1/4" (50.8 x50.8x6. 35mm) 2x4x 1/4" (50.8 x101.6.8 x 6.35 mm) 3x3x 1/2" (76.2 x76.2 x 12.7mm) MATERIAL GRADE SS 400 GENERAL SPECIFICATION - Material : Steel/ Aluminum Length: 6 feet to 24 feet Width: 02" to 6" Angle : 90 Degrees (standard) Thickness: 1/4" to 1" Size: 2x2x 1/4" (50.8 x50.8x6. 35mm) 2x4x 1/4" (50.8 x101.6.8 x 6.35 mm) 3x3x 1/2" (76.2 x76.2 x 12.7mm) MATERIAL GRADE SS 400	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
139	DGD102307	MS-563XDLG	734070511750 1 / MICROWAVE OVEN LG 56 LTRS		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
140	DGE101983	BS419/156	055954600536 2 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		20 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
141	DGD102371	NO DATA AVAILAB LE	003550000045 2 / UTENSILS COOKINGALU M O/D 10" TO 10.5" "H 4" TO 5.5" TH 12 SWH WITH COVER		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd) DIMENSION: O/D 10" to 10.5" "H 4" to 5.5" TH 12 SWg ALUMINIUM GRADE 3003, 1100, 2024 AND 5052 GENERAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd) DIMENSION: O/D 10" to 10.5" "H 4" to 5.5" TH 12 SWg ALUMINIUM GRADE 3003, 1100, 2024 AND 5052	
142	DGD102364	NO DATA AVAILAB LE	003550000045 4 / UTENSIL COOKING ALUMINIUM WITH COVER O/D 16-17", INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESS 10 SWG		20 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) GENERAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD)	
143	DGE101971	NO DATA AVAILAB LE	055978000018 3 / SLEEVE PLASTIC GREEN 0.3X3 55P(DELETED NS/TD/32/611D T280989)		5 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
144	DGE101972	NO DATA AVAILAB LE	055978000018 5 / SLEEVE PLASTIC		5 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DGE101812	NO DATA AVAILAB LE	055979000198 5 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR	GENERAL ELECTRIC USE	7 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
146	DGT101753	NO DATA AVAILAB LE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		21 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
147	DGE101548		047654600477 6 / BRUSH SABLE HAIR NO-3 FOR WRITING		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
148	DGE101584	DEFSTAN 53.4	535099129393 7 / PAPER, ABRASIVE		120 / SHEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - OVERALL WIDTH: 230.00 MM NOMINAL. LENGTH: 280.00 MM NOMINAL. ABRASIVE MATERIAL: SILICON CARBIDE. SCREEN GRIT SIZE DESIGNATOR: 240. ABRASIVE FINISHING/ POLISHING GRADE DESIGNATOR: 7/0. WATER PROOF FEATURE: INCLUDED. SPECIAL FEATURES: C WEIGHT; PAPER BACKING MATERIAL. GENERAL SPECIFICATION - OVERALL WIDTH: 230.00 MM NOMINAL. LENGTH: 280.00 MM NOMINAL. ABRASIVE MATERIAL: SILICON CARBIDE. SCREEN GRIT SIZE DESIGNATOR: 240.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ABRASIVE FINISHING/ POLISHING GRADE DESIGNATOR: 7/0. WATER PROOF FEATURE: INCLUDED. SPECIAL FEATURES: C WEIGHT; PAPER BACKING MATERIAL.	
149	DGE101768	havana	711070524754 1 / master havana high back chair		3 / EACH/NUMBER	NIL					TECHNICAL SPECIFICATION - BACK: 24" ARM: 27 SEAT: 21.5" HEIGHT: 20" BACK HEIGHT: 47" A. CHROME BASE B. CHROME ARMS GENERAL SPECIFICATION - BACK: 24" ARM: 27 SEAT: 21.5" HEIGHT: 20" BACK HEIGHT: 47" A. CHROME BASE B. CHROME ARMS	
150	DGH102037	NO DATA AVAILABLE	5305ZO656804 5 / LAWN MOVER MACHINE		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
151	DGE101918	565665	534070524611 1 / leatherite for wallpaper		1500 / SQ FEET	565665					TECHNICAL SPECIFICATION - leatherite wallpaper sheets GENERAL SPECIFICATION - leatherite wallpaper sheets	
152	DGE102532	NIL	934073100099 5 / E-GLASS FIBER (POWDER) CHOPPED STRAND MAT	GRP BOATS	688 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2 GENERAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2	
153	DGE102308		614579502372 4 / CABLE TIE 2.5 MM NYLON BLACK	TX/RX VRM	100 / PACKET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
154	DGH102415		951570503121 7 / PLATE STEEL FLOOR ROLLED	FOR GENERAL USED	7 / EACH/NUMBER						TECHNICAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTOGRAPH ATTACHED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTGRAPH ATTACHED	
155	DGH102 398		951570503121 7 / PLATE STEEL FLOOR ROLLED	FOR GENERAL USED	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTGRAPH ATTACHED GENERAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTGRAPH ATTACHED	
156	DGH102 491		951570503121 7 / PLATE STEEL FLOOR ROLLED	FOR GENERAL USED	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTGRAPH ATTACHED GENERAL SPECIFICATION - BSEN 10025-2 OF 2019. GRADE S-275JR. SIZE: LENGTH-2500MM. BASE THICKNESS: 6MM width: 1220mm in lieu of 1250mm HEIGHT PROJECT PATTERN (1.75 - 2.25 MM) PROJECT PATTERN PHOTGRAPH ATTACHED	
157	DGE102 497		711070511488 8 / master AURA LOW BACK REVOLVING	MASTER OFFICE CHAIR	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CHAIR								<p>(4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240</p> <p><b>GENERAL SPECIFICATION - Specification Of Item:</b> (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240	
158	DGE102 493	IS8021	047654600478 5 / Coated Rigger Gloves with Rubberized Cuff		50 / PAIR						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
159	DGE102 483	NO DATA AVAILABL E	041354600366 1 / TUBING PLASTIC TRANSPAREN T(G/USE) O/D 32MM I/D 27MM TH.2.5 MM		300 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
160	DGE102 301	NO DATA AVAILABL E	055978000018 7 / SLEEVE PLASTIC DIA 0.5CM		5 / ROLL	NO DATA AVAILABL E					<u>TECHNICAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S,NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black</u> <u>GENERAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S, NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black	
161	DGE102 302	NO DATA AVAILABL E	055978000018 5 / SLEEVE PLASTIC		5 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
162	DGE102 391	NO DATA AVAILABL E	830570512795 0 / RUBBER FABRIC (PVC COATED) CLOTH IN SHIP SIDE GREY COLOUR	FOR PNS SHIFA	500 / METER						TECHNICAL SPECIFICATION - 1. APPLICATION= COVERAGE FOR SHIPS, ETC 2. TOTAL WEIGHT (DIN EN ISO 2286-2)= 500 g/m2 3. SUPPORT CLOTH (DIN 6000)= POLYESTER 4. TYPE OF COATING = PVC COATED ON BOTH SIDES 5. YARN (DIN EN ISO 2060)= 1000 X 1000D 6. SPECIFICATION (DIN EN 1049-2)= 18 X 18 PER INCH (PLAIN WEAVE) 7. DIMENSION (DIN EN ISO 2286-1)= WIDTH: 01 METER & ROLL 50 METER 8. TENSILE STRENGTH (DIN 53354)= 2500/2400 N/ 5CM 9. TEAR STRENGTH (DIN 53363)= 270/250 N 10. ADHESION STRENGTH (DIN 53357)= 100 N /5CM 11. TEMPERATURE RESISTANCE= -30 C° TO +70 C° 12. FEATURE= HIGH TENACITY POLYESTER YARN ENSURES SUPERIOR DURABILITY UV PROTECTION TREATED 13. PACKING= CRAFT PAPER OR PE 14. RUBBER FABRIC BASE MATERIAL= POLYESTER, 15. CHEMICAL RESISTANCE= 98% SULFURIC ACID, 38% HYDROCHLORIC ACID AND 40% SODIUM HYDROXIDE, 16. ABRASION RESISTANCE= >1000 ZYKLEN, 17. WATER RESISTANCE= >0.8 BAR, 18. COATING THICKNESS= 0.5 MM, 19. FLAME RETARDANCY AND CERTIFICATION= M2 GENERAL SPECIFICATION - 1. APPLICATION= COVERAGE FOR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SHIPS, ETC 2. TOTAL WEIGHT (DIN EN ISO 2286-2)= 500 g/m2 3. SUPPORT CLOTH (DIN 6000)= POLYESTER 4. TYPE OF COATING = PVC COATED ON BOTH SIDES 5. YARN (DIN EN ISO 2060)= 1000 X 1000D 6. SPECIFICATION (DIN EN 1049-2)= 18 X 18 PER INCH (PLAIN WEAVE) 7. DIMENSION (DIN EN ISO 2286-1)= WIDTH: 01 METER & ROLL 50 METER 8. TENSILE STRENGTH (DIN 53354)= 2500/2400 N/ 5CM 9. TEAR STRENGTH (DIN 53363)= 270/250 N 10. ADHESION STRENGTH (DIN 53357)= 100 N /5CM 11. TEMPERATURE RESISTANCE= -30 C° TO +70 C° 12. FEATURE= HIGH TENACITY POLYESTER YARN ENSURES SUPERIOR DURABILITY UV PROTECTION TREATED 13. PACKING= CRAFT PAPER OR PE 14. RUBBER FABRIC BASE MATERIAL= POLYESTER, 15. CHEMICAL RESISTANCE= 98% SULFURIC ACID, 38% HYDROCHLORIC ACID AND 40% SODIUM HYDROXIDE, 16. ABRASION RESISTANCE= >1000 ZYKLEN, 17. WATER RESISTANCE= >0.8 BAR, 18. COATING THICKNESS= 0.5 MM, 19. FLAME RETARDANCY AND CERTIFICATION= M2	
163	DGT102 116	NO DATA AVAILABL E	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		10 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - _SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) _GENERAL SPECIFICATION _SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
164	DGT102 561	NO DATA AVAILABL E	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		30 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
165	DGE102 350	d000-004	844073527072 0 / cotton gloves (pack of 12 gloves)		5 / PAIR	na					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
166	DGE102 330	MEDIUM 66.2 LTRS 2000 PLUS	811570525959 8 / COLEMAN or EQUIVALENT ICE BOXES (MEDIUM) 66.2 LTRS 2000 (PLUS)		1 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - BOTH SIDE HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200 (plus) approx. GENERAL SPECIFICATION - BOTH SIDE HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200 (plus) approx.	
167	DGT102 406	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
168	DGT102 343	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	68 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
169	DGH102 006	LNKPN201 510	3020PK520265 1 / PINS	RACK	1850 / UNIT			3RD FLOOR 83C,PHASE 2, EXTENSION,MAIN NATIONAL HIGHWADEFENCE KARACHIY,,021538726		HABIB & SONS	<u>TECHNICAL SPECIFICATION</u> - YEILD STRENGTH:245MPA16MM MATERIAL:SS400 TENSILE STRENGTH:400-510MPA THICKNESS:1.3MM SURFACE FINISH:GALVANIZED/POWDER COATED HEXAGONE NUT AND BOLT:M10*80*2 <u>GENERAL SPECIFICATION</u> - YEILD STRENGTH:245MPA16MM MATERIAL:SS400 TENSILE STRENGTH:400-510MPA THICKNESS:1.3MM SURFACE FINISH:GALVANIZED/POWDER COATED HEXAGONE NUT AND BOLT:M10*80*2	
170	DGE102 311	YCR105 or 1260	830578516309 0 / CERAMIC FIBER CLOTH	GENRAL USE	23 / METER	YCR105		OEM:CHINA MANUFACTURERS NINGBO RUIFENG SEALING MATERIAL COMPANY LTD KUANGVAN TOWN CIXI : 86-574-63531211.63531433.		PANASO NIC SADDAR KARACI. TECHNO POWER SYSTEM	<u>TECHNICAL SPECIFICATION</u> - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, tempErature resistance= 700 °C (degree centigrade), max thermal conDuctivity= 0.16 w/m.K <u>GENERAL SPECIFICATION</u> - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, tempErature resistance= 700 °C (degree centigrade), max thermal conDuctivity= 0.16 w/m.K	
171	DGE102 496	AS/NZS 1716 P3, EN143: 2000 P3 R	845570518127 6 / DISC IDENTITY RED FOR	NIL	200 / EACH/N UMBER		NIL	LOCAL MARKET		NIL	<u>TECHNICAL SPECIFICATION</u> - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			RESPIRATION AND HAVERSACK								March 2015)GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015)	
172	DGE102 393	NIL	651570518127 7 / TOWEL PAPER 24 ROLLS PER PACK	NIL	5 / CARTON			LOCAL MARKET	NOT KNOWN		TECHNICAL SPECIFICATION - No of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 InchGENERAL SPECIFICATION - No of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 Inch	
173	DGH102 046	614599521 8490	614599521849 0 / CABLE POWER ELECTRICAL 3CORE 440V 34A	CABLES	300 / METER	DG SHIPS 212	NA	MINISTRY OF DEFENCE (NAVY) SHIPS SUPPORT AGENCY DME ME253, ROOM 19, BLOCK B FOXHILL, BATH, UK TEL: 01225 883293 FAX: 01225 883548	DG SHIPS 212 UK		TECHNICAL SPECIFICATION - AS PER NMCRL AND DG SHIPS 212GENERAL SPECIFICATION - AS PER NMCRL AND DG SHIPS 212	
174	DGH102 498	BS EN 10025 S 275 JR	952070513605 2 / ANGLE STEEL BULB BAR 140MM X 09MM	DOCK,S HULL	40 / METER	NO DATA AVAILAB LE		PK	M/S RUBY TRADER S IRON & STEEL SHERSH AH RD KARACHI -2573339		TECHNICAL SPECIFICATION - BS EN 10025 GRADE S 275 JRGENERAL SPECIFICATION - BS EN 10025 GRADE S 275 JR	
175	DGE102 290	10MM	597070513347 6 / GLASS SLEEVING 10MM	MOTOR WINDING FOR CABLE	12 / EACH/NUMBER	NO DATA AVAILAB LE		PK	GREEN WAY ELECTRI C STORE SHOP NO.1-5 ARAMBA GH KARACHI		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
176	DGB102 455	24340	951570523177 6 / STEEL PANNELING SHEET (STAINLESS STEEL), SIZE 8 X 4 (FEET), Thickness	ships galley (officer washroom)	5 / SHEET	Pakistran	Nil	Umair Brothers street # 10 , Abu Bakr Siddique colony, opposite new khan, Band Road LAHORE contact # 0321-8400118 Office # 042-37465031	Umair Brothers		TECHNICAL SPECIFICATION - THICKNESS SWG 22 (22 GAUGE), MATERIAL GRADE 304, Size 8 x 4 (feet)GENERAL SPECIFICATION - THICKNESS SWG 22 (22 GAUGE), MATERIAL GRADE 304, Size 8 x 4 (feet)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SWG 22 (22 Gauge), Material Grade 304									
177	DGT102 407	NIL	723070513291 0 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	4050 / FOOT	NO DATA AVAILAB LE		PK		TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI	<u>TECHNICAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required <u>GENERAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
178	DGE102 351	P. 295/2400	597000816605 6 / Tape insulation electrical	NIL	24 / EACH/N UMBER	NA	NA	US Postal Code 08701- 4537, 1990 RUTGERS BLVD, LAKEWOOD, USA		NITTO, INC, USA	<u>TECHNICAL SPECIFICATION -</u> PMS Item <u>GENERAL SPECIFICATION - PMS Item</u>	
179	DGH102 460	TZ38.2	614572512914 2 / CABLE ELECTRICAL 24VDC, 2X10MM2 (F8)	CUMMUNICAT ION SYSTEM	400 / METER					DIGI TECH DENSO HALL KARACHI	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
180	DGE102 299	EM 3061	593572512993 6 / RAYCHEM HEAT SHRINK	-	2 / EACH/N UMBER					GMBH GERMAN Y	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
181	DGE102 322		041359923889 6 / SHEET RUBBER SOLID NATURAL OFF WHITE SQ 02 LBS 0.250 X48X72IN		25 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
182	DGE102 293	0413-8532 &0413_92 3_8899, BS1154	041359923889 9 / RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE		200 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI								packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 GENERAL SPECIFICATION - RUBBER SHEET, SOLID, NATURAL RUBBER, LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21	
183	DGE102 342	9-27061 (NSN 6260-01-074-4230)	047350473015 9 / LIGHT, CHEMILUMINE SCENT YELLOW	LIGHT STICK (SAFETY LIGHT)-YELLOW	120 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
184	DGE102 333	BS 2848	055979444489 9 / INSULAT. SLEEVE ELEC. VARNISHED GLASS FIBRE I/D 4MM, TH 0.5 MM	GENERAL ELECTIC USE	20 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
185	DGE102 397	0559-15270	055979444490 0 / INSULATION-SLEEVING-ELECTRICAL-5.0MM - THICK.0.500/0.750MM		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
186	DGE102 501	NO DATA AVAILABLE	047659943474 3 / TUFF GRADE 1" PAINT BRUSH	HANGAR DOOR	17 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch GENERAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch	
187	DGE102 335	NO DATA AVAILABL E	055979444469 0 / RUBBER-TAP-INSULATION		35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
188	DGE102 304	0.75X0.007INCH-50MTR-	055979001524 4 / INSULATION-TAPE-VARNISHED WOVEN GLASS-FIBRE-(STRAIGHT CUT}		15 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
189	DGE102 352		041459923091 1 / PACKING MATERIAL HEMP FOR FURNACE FUEL, SIZE= 1/4" SQ		30 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
190	DGE102 347	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		19 / EACH/N UMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
191	DGE102 392	LETTER NO.E- I/4927/A/4 45DT0509 02	046159000391 4 / CLOTH POLESHING		150 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
192	DGB102 331	NO DATA AVAILABL E	028370000162 4 / ROD WELDING MANGANESE BRONZE 1/8" 0.12"SPEC BS1453C2B (LOCAL)		5 / KILOGR AMME						TECHNICAL SPECIFICATION - length: 1 Meter thickness: 1/8 inch Packing: 5kg/ Packet GENERAL SPECIFICATION - length: 1 Meter thickness: 1/8 inch Packing: 5kg/ Packet	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
193	DGB102329	NO DATA AVAILABLE	0283599236800 / SOLDER PASTE SELFLUX TYPE TCC SELF SOLDERING 1 LB TIN	BR 320D/76	2 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
194	DGB102451	NO DATA AVAILABLE	0283595711155 / SHEET ALUMINIUM ALLOY ANNEALED		11 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN:573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251). GENERAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN: 573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).	
195	DGE102500	NO DATA AVAILABLE	0451594510013 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	40 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS GENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	
196	DGE102395	NO DATA AVAILABLE	0451594510013 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	20 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS GENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	
197	DGE102320	BS-1145 HARDNESS 42-50	0413599238900 / SHEET RUBBER SOLID NATURAL OFF WHITE SQ 05 LBS 0.625	TENSILE STRENGTH 2500PSI	20 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			X48X72IN									
198	DGE102 394	NO DATA AVAILABL E	045159910816 0 / TABLE- CLOTH- WOOLEN GREEN,100% WOOL,WIDTH 5FT-LETTER NO E- 1/4927/1496 DT 07 NOV 95		20 / YARD						<u>TECHNICAL SPECIFICATION - .em</u> Specification TABLE CLOTH WOOLEN MATERIAL:100%WOOL- DIMENSIONS:WIDTH-5FT,LENGTH- AS PER WOS,COLOUR: GREEN , PRICE 300/-PER YARD <u>GENERAL</u> <u>SPECIFICATION - .em</u> Specification TABLE CLOTH WOOLEN MATERIAL:100%WOOL- DIMENSIONS:WIDTH-5FT,LENGTH- AS PER WOS,COLOUR: GREEN , PRICE 300/-PER YARD	
199	DGE102 384		045159129298 9 / CLOTH COATED PVC FOR FURNITURE UPHOLSTERY COLOUR BLUE WD,50 INCH	FOR SPECS SEE CMD 8	300 / METER						<u>TECHNICAL SPECIFICATION -</u> ISO7617-2 OF 1994 colour blue wd . 50 INCH <u>GENERAL</u> <u>SPECIFICATION - ISO7617-2 OF</u> 1994 colour blue wd .50 INCH	
200	DGT102 117	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD- II (CORE INNER & OUTER PLYS OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIV E		416 / SQ FEET						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS- 4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB- 2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) <u>GENERAL SPECIFICATION</u> <u>- SPECIFICATION: BS-1088, part</u> BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
201	DGT102 560	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD- II (CORE INNER & OUTER PLYS		320 / SQ FEET						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS- 4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB- 2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE								(±1MM)GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
202	DGB102 453	BS 3602/HFS STEEL 23	026759571170 4 / PIPING STEEL BLACK 6.00X6.500X0.176IN		50 / METER						TECHNICAL SPECIFICATION - BSEN/0216-2 OF 2002 GRADE P265GHGENERAL SPECIFICATION - BSEN/0216-2 OF 2002 GRADE P265GH	
203	DGH102 390		021159923019 6 / SHEET GI ZINC COATED 1800X900X02 MM		36 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. DETAILS SIZE: LENGTH 1800MM, WIDTH 900MM, THICKNESS 02MM, WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p><b>SPECIFICATION - 1. DETAILS SIZE:</b>  LENGTH 1800MM, WIDTH 900MM, THICKNESS 02MM, WT/SQFT 1.4 KG, WT/SHEET 26 KG  <b>GALVANIZED STEEL SHEETS</b>  <b>GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated</b>  a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)</p>	
204	DGH102 494		021159923019 6 / SHEET GI ZINC COATED 1800X900X02 MM		30 / EACH/ NUMBER						<p><b>TECHNICAL SPECIFICATION - 1. DETAILS SIZE:</b> LENGTH 1800MM, WIDTH 900MM, THICKNESS 02MM, WT/SQFT 1.4 KG, WT/SHEET 26 KG  <b>GALVANIZED STEEL SHEETS</b>  <b>GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE</b></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated</p> <p>a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)<u>GENERAL SPECIFICATION - 1. DETAILS SIZE:</u> LENGTH 1800MM, WIDTH 900MM, THICKNESS 02MM, WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)	
205	DGH102 411		021159923019 6 / SHEET GI ZINC COATED 1800X900X02 MM		10 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. dETIALS SIZE: LENGTH 1800MM, WIDTH 900MM, THICKNESS 02MM, WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated</p> <p>a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)GENERAL</p> <p>SPECIFICATION - 1. dETIALS SIZE: LENGTH 1800MM, WIDTH 900MM, THICKNESS 02MM, WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated</p> <p>a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING : 120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)</p>	
206	DGH102499		021259571098 1 / STEEL T-Section Carbon STEEL (FINISH BLACK) 04X3X3/8"		60 / METER						<p>TECHNICAL SPECIFICATION - BS EN 10025 / 2019 Material Grade S-275 JR T-SECTION MANUFACTURED IN RADIUSED ROOT &amp; TOES FIGURE ATTECHED. SIZE : NOMINAL DEPTH OF SECTION: 03 INCH; NOMINAL WIDTH OF FLANGE:04 INCH; THICKNESS: 3/8 INCH (UNIFORM) WEIGHT PER SQ/FT : 8.49 LBS <u>GENERAL</u></p> <p>SPECIFICATION - BS EN 10025 / 2019 Material Grade S-275 JR T-SECTION MANUFACTURED IN RADIUSED ROOT &amp; TOES FIGURE ATTECHED. SIZE : NOMINAL DEPTH OF SECTION: 03 INCH; NOMINAL WIDTH OF FLANGE:04 INCH; THICKNESS: 3/8 INCH (UNIFORM) WEIGHT PER SQ/FT :</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											8.49 LBS	
207	DGH102 506	BS EN 10025-2/2004, MATERIAL GRADE S 275 JR	021259571071 8 / ANGLE STEEL CARBON E/S BLACK 1.25 X 1.25 X 0.25 INCH		80 / METER						TECHNICAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr GENERAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr	
208	DGH102 358	BS EN 10025-2/2004, MATERIAL GRADE S 275 JR	021259571071 8 / ANGLE STEEL CARBON E/S BLACK 1.25 X 1.25 X 0.25 INCH		60 / METER						TECHNICAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr GENERAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr	
209	DGB102 362		026759521327 8 / PIPING STEEL GALVANIZED SEAMLESS, L : 6.1 M, E/DIA 26.9MM, TH 2.6 MM, N/BORE:19.1 MM	UTS LENGTH. BULK SUPPLY	100 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS GENERAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS	
210	DGB102 452	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	100 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS: 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS: 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
211	DGE102 259	NO DATA AVAILABL E	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH &amp; LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u>  SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
212	DGE102324	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH &amp; LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH &amp; LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH &amp; LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
213	DGE102 323		402099923713 7 / ROPE NYLON HAWSERLAID, 3-STRND, Z- LAY, TYPE-1, NOM DIA: 64- MM, CIRC: 08- INCH,	NOR-SHIPS- USE-NASAR	33.3 / FATHO M						<p><u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
214	DGE102 298	MWTM 95/29-1200	593572507749 1 / HEAT SHRINK SLEEVE		5 / METER						TECHNICAL SPECIFICATION - Dimensions: Size: 95/29 Expanded Diameter: 95mm Recovered Diameter: 29mm Cable Range Diameter:32-86 mm Length: 1m GENERAL SPECIFICATION - Dimensions: Size: 95/29 Expanded Diameter: 95mm Recovered Diameter: 29mm Cable Range Diameter:32-86 mm Length: 1m	
215	DGE102 297	ECW0090 3-12	593572507749 2 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SIZE 48/16 LG 1 METER		3 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
216	DGE102 480	ECW0090 3-12	593572507749 2 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SIZE 48/16 LG 1 METER		5 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
217	DGE102 296	NO DATA AVAILABL E	593572507749 4 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 31/8 LG, 01 METER		3 / METER						TECHNICAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B. PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224 G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AND ABRASION. <u>GENERAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B. PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224 G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT AND ABRASION.</u>	
218	DGE100789	0413-2184	5970999239664 / TAP INSULATION ELECT ADHESIVE PLASTIC RED W1	FOR RED PHASE	30 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing</u> <u>GENERAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing</u>	
219	DGE102262	NO DATA AVAILABLE	0340500000010 / CANVAS COVER WATER PROOF		5 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - Water Proof, In single sheet Size: 30 x 30 feet Colour: Olive Green Usage: Multipurpose use for NA Stores Weight: 60 + 5 KG Material: 100% Cotton Canvas Cloth Thickness: As per sample dimension: 01 sq ft is 56.32 gm. Stock Sample / Reference Sample Material as per sample (enclosed by hand)</u> <u>GENERAL SPECIFICATION - Water Proof, In single sheet Size: 30 x 30 feet Colour: Olive Green Usage: Multipurpose use for NA Stores Weight: 60 + 5 KG Material: 100% Cotton Canvas Cloth Thickness: As per sample dimension: 01 sq ft is 56.32 gm. Stock Sample / Reference Sample Material as per sample (enclosed by hand)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
220	DGE102 349	NO DATA AVAILABL E	04135000013 3 / EAR DEFENDER		200 / PAIR	PELTOR H10A/ OPTIME 105					<p><u>TECHNICAL SPECIFICATION -</u> accaptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar &amp; Industrial Safety Equip) <u>GENERAL SPECIFICATION -</u> accaptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar &amp; Industrial Safety Equip)</p>	
221	DGE102 396	NO DATA AVAILABL E	04225000002 7 / IMPROVED VERSION PVC TILES MAROON SIZE 300X300X3MM		50 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE<u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE</p>	
222	DGE102 481	NO DATA AVAILABL E	04615000008 6 / GOGGLE CHIPPING		60 / EACH/N UMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at &gt;5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits -</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>most along with fire- resistant head band.<u>GENERAL SPECIFICATION</u> - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at &gt;5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.</p>	
223	DGE102256		8340PK5073827 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIES		2 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH &amp; WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD &amp; INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET &amp; 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>MM &amp; THICKNESS 02 MM ± 0.50  MM b. IRON PEGS: QTY 20 NOS,  LENGTH 18 INCHES, THICKNESS  20 MM ± 2 MM AND MILD STEEL  PIN QTY 28 NOS, LENGTH 06  INCHES. c. ROPE: QTY: 40 NOS  MINIMUM OR AS RECOMMENDED  BY MANUFACTURER, MATERIAL:  NYLON/COTTON, DIA MINIMUM:  16-MM. d. HAMMER: QTY 01 NO,  MATERIAL: MS (MILD STEEL),  WEIGHT 05 KGS WITH WOODEN  HANDLE LENGTH 1.5 FEET. e.  FLAPPER FOR GROUND=  MATERIAL: POLYPROPYLENE,  180-200 GSM. 4. VENTILATION  FEATURE: WINDOW: 02 (SIZE: 2 x  2 FEET) WITH MOSQUITO  NETTING FOR AIRFLOW AND  DOOR 02 REQUIRED ON BOTH  SIDES OF THE TENT. 5. PACKING  REQUIRED: QTY 03 TOTAL BAGS  MADE OF CANVAS COTTON (475  GSM), 02 x BAG FOR THE TENT  BODY AND 01 FOR THE  ACCESSORIES. 6. ADVANCE  SAMPLE TO BE APPROVED BY  CINS/ SPECIALIST END USER  PRIOR TO BULK PRODUCTION.</p> <p><u>GENERAL SPECIFICATION - 1.</u>  SIZE/DIMENSION a. TENT SIZE  (LENGTH &amp; WIDTH): 20 X 16 FEET  (± 3 INCH) b. WALL HEIGHT: 06  FEET (± 2 INCH) c. HEIGHT OF  TENT: 12 FEET (± 3 INCH) 2.  OTHER SPECIFICATIONS a. 100%  CANVAS COTTON: DOUBLE FLY  WITH SINGLE FOLD (OUTER FLY  WITH SINGLE FOLD &amp; INNER FLY  WITH DOUBLE FOLD). b.  MATERIAL: 475 GSM OR ABOVE  WITH ROT-PROOF AND  WATERPROOF. c. COLOR FOR  OUTER/ INNER FLY: OLIVE  GREEN, COLOR CODE: RAL-6003.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET &amp; 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM &amp; THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p>	
224	DGE102325		8340PK5073827 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIE		2 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH &amp; WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			S								<p>OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD &amp; INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET &amp; 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM &amp; THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.</p> <p><u>GENERAL SPECIFICATION - 1.</u></p> <p>SIZE/DIMENSION a. TENT SIZE (LENGTH &amp; WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD &amp; INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET &amp; 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM &amp; THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
225	DGT102 153	NO DATA AVAILABL E	010050000002 8 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLYS OF SHESHAM WOOD) 5-PLY	2.440X1. 220MTRX6. 35MM) SPECE/BS- 1088	788 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, <u>GENERAL SPECIFICATION -</u> 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,	
226	DGE102 341	NO DATA AVAILABL E	047650000006 1 / GLOVES LEATHER FOR WELDING,		95 / PAIR	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			treated with preservative, standard quality								<p>LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex <u>GENERAL SPECIFICATION</u> - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL details: 1. PRODUCT CLASSIFICATION: Welding gloves 2.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex	
227	DGE102423	NO DATA AVAILAB LE	04515000001 6 / TAPE- WHITE- COTTON		150 / YARD	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
228	DGE102306	PLATILON C	933099225122 3 / PLASTIC SHEET,TRAN SPIRIT,200M ROL,1.8M WIDE	STRUCTURE CASING FORGINS	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
229	DGE102312	NO DATA AVAILAB LE	933070505435 4 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PN CREST	2 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
230	DGE102482	NO DATA AVAILAB LE	933070505435 4 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PN CREST	2 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	