

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 10-06-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGB736 45	0264	403079515388 5 / SPLIT THIMBLES (316 STAINLESS STEEL) 14MM	TAL SHIP SAILING RIG	130 / EACH/N UMBER			BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST,HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE. MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE. CO.UK	UK		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY ; BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE. SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX:+44(0) 1489578835. <u>GENERAL</u> SPECIFICATION - SOURCE OF AVAILABILITY ;BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX:+44(0) 1489578835.	
2	DGB995 18		531099124047 4 / NUT PLAIN HEX 3/8INBSW AF0.600THK0. 312		30 / TEN						TECHNICAL SPECIFICATION - PD 970 Material Grade 605 M(36) (EN16C)GENERAL SPECIFICATION - PD 970 Material Grade 605 M(36) (EN16C	
3	DGE101 893	lc-08-ssp- 01	562070522765 1 / DUST PRESSED, UNGLAZED	DECK	1000 / EACH/N UMBER	SSP-01- LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTA N		TECHNICAL SPECIFICATION - AS PER LETTER ATTACHGENERAL SPECIFICATION - AS PER LETTER ATTACH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PROCELAIN TILES (MASTER)									
4	DGE100 946	QA263527	402099083318 4 / ROPE FIBROUS 8 STRAND, DIA 48MM,	-	880 / FATHO M	NO DATA AVAILAB LE		UK		MARLOW ROPE LTD SOUTH ROAD HAILSHA M EAST SUSSEX UNITED KINGDO M	<p><u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 48-MM DIA, BERTHING HAWSER BLK CONT FILAMENT POLYESTER & SS POLYPROPYLENE, 3. MIN BREAKING LOAD: 36.5 TONNES, 4. SUPPLIED IN 220 MTR COIL 5. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 6. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 7. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 8. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM, Phone: +44(0)1323 444 444 EMAIL: sales@marlowropes.com</p> <p><u>GENERAL SPECIFICATION -</u> SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 48-MM DIA, BERTHING HAWSER BLK CONT FILAMENT POLYESTER & SS POLYPROPYLENE, 3. MIN BREAKING LOAD: 36.5 TONNES, 4. SUPPLIED IN 220 MTR COIL 5. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OF STORES. 6. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 7. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 8. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM, Phone: +44(0)1323 444 444 EMAIL: sales@marlowropes.com	
5	DGE100 649	NIL	402099923713 0 / ROPE NYLON, HAWSERLAID, Z-LAY, CIRC: 2.50", NOM DIA: 20MM,	ITSELF	1100 / FATHO M			NAM: MARLOW ROPES LTD ST1: ROPEMAKER PARK, DIPLOCKS WAY STT: EAST SUSSEX CTR: UNITED KINGDOM TEL: 01323 444444 FAX: 01323 444455	UK		TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED." 6. SPECS: BS4928 GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED." 6. SPECS: BS4928	
6	DGB993 06		028259571212 9 / PIPING- COPPER- ALLOY EXT DIA MAX 4.184"MIN		72.4 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILBLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			4.178"INT DIA 4"									
7	DGE100 800	0413-2556	041359923703 8 / HOSE POLYVINYL PVC INT 0.375 ET 0.77 L 14.5 3PSI WT 3LB S/Q"		50 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
8	DGB995 20	HA-4153	047279000010 7 / WIRE FAIRLEADS	ENTERPRIZE CLASS SAILING BOAT	15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DGE991 11	nil	035059571312 1 / Rope Nylon, Hawser laid, White, 3-Strand, Cir: 1-Inch, Diameter: 8-MM		120 / FATHOM						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
10	DGE99104	NO DATA AVAILAB LE	035059571312 9 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 3.00", DIA: 1.00" (24MM)		240 / FATHO M	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
11	DGE99196		035059571313 0 / ROPE NYLON, HAWSERLAID, 3-STRAND, CIRC: 3-1/2 INCH, NOM DIA: 24MM, TYPE-1,	TOWING & BERTHING ROPE	20 / METER						<p>TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY. 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S/BSI TEST</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 ROPE BEING PROVIDED TO PN ARE TO BE SAME QUALITY/STANDARD AS BEING PROVIDED TO MOD(UK) /RN/ RELATED COUNTRY. 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.</u></p>	
12	DGE99198	NO DATA AVAILAB L E	035059571313 2 / ROPE NYLON, 3- STRAND, CIRC: 4-INCH, DIA: 32MM		240 / FATHO M	NO DATA AVILAB LE					<p><u>TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI</p> <p><u>GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL. 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM. 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI</u></p>	
13	DGB991 95	BS1453, 0283- 12060	028359201514 1 / ROD WELDING BRASS 57.0- 63.0 % COPPER DIA 1/4 LG 36		2 / KILOGR AMME						<p><u>TECHNICAL SPECIFICATION - b.</u> Product Name Brass Welding Rod c. Diameter ¼ inch (6.35mm) d. Product Category Welding Filler Material e. Color Yellow f. Standard/ Grade AWS A5.8 RBCuZn-C ISO 3677 B-CuZn40 g. Chemical Composition Copper (Cu) 57.0% to 63.0% Zinc (Zn) 40% h. Length 36 inches (914mm) j. Packaging Bundled in 5KG/ 10 KG</p> <p><u>GENERAL SPECIFICATION - b.</u> Product Name Brass Welding Rod c. Diameter ¼ inch (6.35mm) d. Product</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Category Welding Filler Material e. Color Yellow f. Standard/ Grade AWS A5.8 RBCuZn-C ISO 3677 B-CuZn40 g. Chemical Composition Copper (Cu) 57.0% to 63.0% Zinc (Zn) 40% h. Length 36 inches (914mm) j. Packaging Bundled in 5KG/ 10 KG	
14	DGE991 60		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN TRANSPAREN T L X W X THIC 48"X48"X0. 250"		4 / SHEET						TECHNICAL SPECIFICATION - Manfr/Tech.Sponcer Code reference: DTD 5592GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference:DTD 5592	
15	DGH990 74	DNC/S-23	021259571097 3 / SECTION T STEEL CARBON BLACK 51 MM X51 MM WT PER FT 4.76 KG		90 / METER						TECHNICAL SPECIFICATION - BS- EN-10025-2:2004 GRADE S273RGENERAL SPECIFICATION - BS-EN-10025-2:2004 GRADE S273R	
16	DGH991 67		022259090360 6 / SWIVEL PIECE		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
17	DGB992 26	SPEC. DGS 8062 (5310-99- 120-0297)	021470124029 7 / WASHER FLAT ROUND NOM 1.000X1. 625X0.160IN		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
18	DGE993 80	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sSTRAND, Z- LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	240 / FATHO M						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.</u></p>	
19	DGE100 647	NIL	035059923712 9 / ROPE NYLON, HAWSERLAID, 3-STRANDS,	STRENGTH 11.800 TONS UNIT OF AVAILABILIT	220 / FATHO M						<p><u>TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CIRCI 3", NOM DIA: 24MM, Z-LAY, TYPE-1, MINIMUM BREAKING LOAD : 12 TONS								<p>ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
20	DGB991 94	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	10 / KILOGR AMME						<p>TECHNICAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm- 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface</p> <p>GENERAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm- 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface</p>	
21	DGE991 08		035059923713 2 / ROPE NYLON, 3- STRD, CIR: 4.50", DIA 1.4375" (36- mm)		440 / METER						<p>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
22	DGE99191	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	1800 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
23	DGE99103	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHO M						<p>TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</u>	
24	DGB99189		0214580001016 / BOLT WITH NUT STEEL 252TD SZ 15X14 AND 12X5MM	S/M	30 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
25	DGH99071		0212595710796 / Angle steel carbon black 05X03X7/16" LG 19.10"		57 / METER						<u>TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER Forecasted qty: 57 MTR MATERIAL TEST CERTIFICATE REQUIRED</u> <u>GENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER Forecasted qty: 57 MTR MATERIAL TEST CERTIFICATE REQUIRED</u>	
26	DGE101		402099923713	NOR-SHIPS-	133.2 /						<u>TECHNICAL SPECIFICATION - 1.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	042		7 / ROPE NYLON HAWSERLAID, 3-STRND. Z- LAY, TYPE-1, NOM DIA: 64- MM, CIRC: 08- INCH,	USE-NASAR	FATHO M						<p>TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p> <p><u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
27	DGE100 955	BS 2052	402099942504 2 / ROPE SISAL HAWSERLAID CIR 12MM 3 STRAND	MIN BKG LOAD 955 KG	120 / FATHO M						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
28	DGB990 18	NO DATA AVAILABL E	026850000004 6 / SALTER- CHECKWEIGH ER-MODLE 652-CAPACITY 30KG WITH HANGING PAN	30 KG X100G DIVISION DIAL 12" FITTTED	2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DGT100 804	NO DATA AVAILABL E	010000000004 8 / TIMBER SHESHAM SLEEPER WELL SEASONED LOCAL		10 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH IM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL USE GENERAL SPECIFICATION - SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH IM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL USE	
30	DGB990 64	0812-05- 01001	5975FT103095 2 / 3U Rack		13 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A	
31	DGE100 782	P- 295/2400	597000816605 6 / Tape insulation electrical	NIL	20 / EACH/N UMBER	NA	NA	US Postal Code 08701- 4537, 1990 RUTGERS BLVD, LAKEWOOD, USA	NITTO, INC, USA		TECHNICAL SPECIFICATION - PMS Item GENERAL SPECIFICATION - PMS Item	
32	DGB100 960	GM-009 G	482070529232 7 / G.M/ Bronze Globe Valves flange type".		8 / EACH/N UMBER	GM-009 G					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
33	DGE100 823		422079514763 0 / SEAMAN KNIFE	BA	10 / EACH/N UMBER	Pk-085 gul		UK	GILL MARINE KILDALE MARINE LTD KINGSTO N ST- HULL MARINA HU1 2DQ TEL:+44 (0) 1482 227 464 EMAIL: INFO*GIL LMARINE .COM		<p>TECHNICAL SPECIFICATION - a. Blade Material :High Grade Stainless Steel b. Blade Lenght: 3.5 – 4 inches for optimal handling in various seamanship evolutions. c. Blade Design: (1) Sheepfoot Blade. Prevents accidental puncturing, commonly preferred in maritime environments. (2) Serrated Section. For cutting of ropes, nets and synthetic materials with ease. (3) Non-reflective finish. Matte or black oxide coating to reduce glare and prevent rust. d. Handle: (1) Material. Reinforced Fiberglass or G10 composite, which is water resistant, lightweight and non-slip. (2) Grip Design. Ergonomic shape with texture or grooves to ensure secure handling even in wet conditions. (3) Lanyard Hole. Allows secure attachment to a cord or carabiner for retention. e. Locking Mechanism: Reliable lock-back or Frame lock Mechanism which prevents accidental closing during use and ensures safety. f. Additional Tools (Attached with Seaman knife): (1) Marlin Spike. For untangling knots. (2) Shackle Key. Facilitates quick work with shackles and similar hardware on deck. g. Sheath: Durable Nylon or Hard Plastic provided with belt clip or any compatible attachment for versatility in carrying. Size 99x41x19mm Blade Length 65mm Overall Length 218mm Blade Material Stainless Steel Brand VIGO RMDS GENERAL SPECIFICATION - a. Blade Material : High Grade Stainless Steel b. Blade Lenght: 3.5 – 4 inches for optimal handling in various seamanship evolutions. c. Blade Design: (1) Sheepfoot Blade. Prevents accidental</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>puncturing, commonly preferred in maritime environments. (2) Serrated Section. For cutting of ropes, nets and synthetic materials with ease. (3) Non-reflective finish. Matte or black oxide coating to reduce glare and prevent rust. d. Handle: (1) Material. Reinforced Fiberglass or G10 composite, which is water resistant, lightweight and non-slip. (2) Grip Design. Ergonomic shape with texture or grooves to ensure secure handling even in wet conditions. (3) Lanyard Hole. Allows secure attachment to a cord or carabiner for retention. e. Locking Mechanism: Reliable lock-back or Frame lock Mechanism which prevents accidental closing during use and ensures safety. f. Additional Tools (Attached with Seaman knife): (1) Marlin Spike. For untangling knots. (2) Shackle Key. Facilitates quick work with shackles and similar hardware on deck. g. Sheath: Durable Nylon or Hard Plastic provided with belt clip or any compatible attachment for versatility in carrying. Size 99x41x19mm Blade Length 65mm Overall Length 218mm Blade Material Stainless Steel Brand VIGO RMDS</p>	
34	DGE981 16	5557 SERIES	685071518046 0 / WATER CONTACT INDICAT or tape 5 X 5 MM	ADHESIVE TYPE INDICATION TAPE	20 / EACH/N UMBER	MSDS MATERIA L		3M		3M USA	<p><u>TECHNICAL SPECIFICATION -</u> color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm) <u>GENERAL SPECIFICATION - color :</u> white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm)</p>	
35	DGE100 628	9914	4240TY520254 4 / RESPIRATOR	SAFETY	70 / SET	9914		3M		3M	<p><u>TECHNICAL SPECIFICATION - EN</u> 149.2001+A1.2009 FFP1 NRD PROTECTION DUST MIST</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			S 3M 7502 HALF MASK WITH 6051 CARTRIDGE+5 01 ADOPTER+5N 11 FILTER								NUISANCE LEVEL ORGANIC VAPOURS MAX USAGE 10XTLV FOR OZONE,10XTLV FOR PARTICULATESGENERAL SPECIFICATION - EN 149.2001+A1. 2009 FFP1 NRD PROTECTION DUST MIST NUISANCE LEVEL ORGANIC VAPOURS MAX USAGE 10XTLV FOR OZONE,10XTLV FOR PARTICULATES	
36	DGE100 793	-	561099200438 6 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	50 / KILOGR AMME	NO DATA AVAILAB LE		UK	FLOWCR ETE UK LTD THE FLOORIN G TECHNO LOGIES CENTRE BOOTH LANE SANDBA TCH CHESHIR E CW11 3QF UK PH:+44(0) 1270 753000 & FAX :+44 (0)1270 753333		TECHNICAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&(M) DC&FF.GENERAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&(M) DC&FF.	
37	DGE990 01	-	561099200438 6 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	16 / KILOGR AMME	NO DATA AVAILAB LE		UK	FLOWCR ETE UK LTD THE FLOORIN G TECHNO LOGIES CENTRE BOOTH LANE SANDBA TCH CHESHIR E CW11 3QF UK		TECHNICAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&(M) DC&FF.GENERAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&(M) DC&FF.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									PH:+44(0)1270753000 & FAX :+44(0)1270753333			
38	DGE100420		561099200438 6 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	50 / KILOGRAMME	NO DATA AVAILAB LE		UK	FLOWCR ETE UK LTD THE FLOORIN G TECHNO LOGIES CENTRE BOOTH LANE SANDBA TCH CHESHIR E CW11 3QF UK PH:+44(0)1270753000 & FAX :+44(0)1270753333		TECHNICAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&l(M) DC&FF. GENERAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&l(M) DC&FF.	
39	DGE101128		033050942726 7 / FLANNELETTE CLOTH WHITE GROUND WITH RED STRIPT 4*X50 YARDS	SMALL ARMS CLEANING	2200 / METER						TECHNICAL SPECIFICATION - BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural. GENERAL SPECIFICATION - BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural.	
40	DGB101274		027779923816 4 / TOOL BOX PORTABLE		6 / EACH/UMBER						TECHNICAL SPECIFICATION - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm GENERAL SPECIFICATION - A. multiple tool box for stowage of diff sizes tools. B.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm	
41	DGE100 947	NO DATA AVAILABL E	035059923357 6 / FENDER MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6 INTERNAL DIA 10"	MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6	10 / EACH/N UMBER						TECHNICAL SPECIFICATION - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10"GENERAL SPECIFICATION - MARINE ROUND SISAL WT 71 LBS OVERALL DIA 2'.6" INTERNAL DIA 10"	
42	DGE100 788	NO DATA AVAILABL E	055979020048 5 / INSULATION-TAPE-POLYETHYLE NE TERAPHALAT E(TERYLENE) W/0.75		25 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
43	DGE100 786	0.75X0. 007INCH- 50MTR-	055979001524 4 / INSULATION-TAPE-VARNISHED WOVEN GLASS-FIBRE-(STRAIGHT CUT)		20 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DGE100 785	NO DATA AVAILABL E	046254600578 4 / TAPE-BROWN-PAPER-GUMMED (DTLD. NSD/TD/19/286 . DT.09		70 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DGE989 91	047694305 57, BS2992TA BLE8ITEM 8/5	047659943055 7 / BRUSH VARNISH TYNEX FIBER FLAT SQUIRE EDGE LENGTH 2.5 INCH, THICK	DR CL PS. HIN. SE	5 / EACH/N UMBER						TECHNICAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitableGENERAL SPECIFICATION -2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			0.750 INCH								EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
46	DGE989 93	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
47	DGE989 94	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
48	DGE100 883	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
49	DGB100 094		027779910621 5 / SPANNER BOX TUBULAR DOUBLE ENDED 1.000 X1.125 W 0.875X1.000		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
50	DGB963 57		028359571150 5 / ROD COPPER RD ANNEALED DIA 1.50 INCH WT PER FT6. 849LBS		11 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
51	DGE977 06		043359924862 6 / KNIFE,	OEM: USA, ITALY(SS	1 / EACH/N	RC 556000					TECHNICAL SPECIFICATION - Material Stainless Steel Blade	

NSN / Description	S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
BWPAS HANDLE				DIVERS (SHEATH 7" & HANDLE 5)	MATERIAL, MAGNETIC TYPE)	UMBER						Length: 17.8 cm/7.01 inch Overall Length: 30 cm/11.82 inch Blade Width: 32mm/1.25 inch Blade Thickness: 5.5mm/0.22 inch Knife Weight: 450gm/0.99 LB Weight with Seaboard: 600gm/1.32 LB GENERAL SPECIFICATION - Material Stainless Steel Blade Length: 17.8 cm/7.01 inch Overall Length: 30 cm/11.82 inch Blade Width: 32mm/1.25 inch Blade Thickness: 5.5mm/0.22 inch Knife Weight: 450gm/0.99 LB Weight with Seaboard: 600gm/1.32 LB	
	52	DGE985 20	04159061	041559923141 9 / SAFETY WALK TREAD NONMETALIC, NON-SKID, LENGTH= 2- FEET, WIDTH= 6-INCH,		600 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. Make / Model / Brand / Equivalent be endorsed: Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated : Anti- Skid Safety Walk Used Over Stairs, 4. Detailed specifications / Technical data Testing : Safety Walk Thread Nonmetallic Nonskid SIZE: Length 2- FEET, Width 6-INCH GENERAL SPECIFICATION - 1. Make / Model / Brand / Equivalent be endorsed: Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated : Anti-Skid Safety Walk Used Over Stairs, 4. Detailed specifications / Technical data Testing : Safety Walk Thread Nonmetallic Nonskid SIZE: Length 2- FEET, Width 6-INCH	
	53	DGB728 76		027670910659 2 / VICE ENGINEERS WIDTH OF JAW 4.5", NOM OPENING 5- 1/2",	JAW 3-1/4" PARALLEL, QUICK RELEASE	7 / EACH/N UMBER						TECHNICAL SPECIFICATION - Jaw Opening: 5.5 Inch Depth of Jaw: 3 Inch Weight with stationary base: 91.1 kg Make/ Model: England GENERAL SPECIFICATION - Jaw Opening: 5.5 Inch Depth of Jaw: 3 Inch Weight with stationary base: 91.1 kg Make/ Model: England	
	54	DGB962 12		027770277015 1 / METRIC SOCKET SET		14 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			10 TO 32MM CONSIST 24 PIECES WITH BOX								AVAILABLE	
55	DGE724 06	NO DATA AVAILABL E	043254600555 9 / HELMET PROTECTIVE WITH VISER COLOUR WHITE (FULL HE		44 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DGH990 73		022159002100 6 / ANCHOR MARINE BOAT IRON WT 20 LBS		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Grapnel Anchor, Chain and Rope GENERAL SPECIFICATION - Grapnel Anchor, Chain and Rope	
57	DGB990 15		026359414965 6 / SHACKLE BOW TO SCREW FOR RIGGING		18 / EACH/N UMBER						TECHNICAL SPECIFICATION - Length: 48 mm Material: Stainless Steel Load Capacity: 0.15 Ton GENERAL SPECIFICATION - Length: 48 mm Material: Stainless Steel Load Capacity: 0.15 Ton	
58	DGE989 99	947- 430229	H94799560058 2 / RUBBER STRIP	GENERAL PURPOSE	10 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DGE100 624	bp310/saa b sp-675	209070050000 1 / CHAIR TUBULAR WHITE PLASTIC SEAT		30 / EACH/N UMBER	bp310					TECHNICAL SPECIFICATION - height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand" GENERAL SPECIFICATION + height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand"	
60	DGH100 893		056159521849 2 / CABLE, power, ELECT ELASTOMERI C LFH , 3 cores, cond276/0.40 440 v, 160 amp, 100 lg.		100 / METER						TECHNICAL SPECIFICATION - 3 CORES, COND276/0.40 440 V, 160 AMP, 100 LG. DEFSTAN 02-526 GENERAL SPECIFICATION - 3 CORES, COND276/0.40 440 V, 160 AMP, 100 LG. DEFSTAN 02-526	
61	DGE970 89	NO DATA AVAILABL	046150000679 2 / CHALK	W/T DOORS & FIT	217 / KILOGR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	WHITE SOFT		AMME						SPECIFICATION - NO DATA AVAILABLE	
62	DGE100 897	NO DATA AVAILABL E	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	2 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p>GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p>	
63	DGE101 263	NO DATA AVAILABL E	424050508870 5/ CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	1/ EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p>	
64	DGE101 130		402099923713 7 / ROPE NYLON HAWSERLAID, 3-STRND, Z- LAY, TYPE-1, NOM DIA: 64- MM, CIRC: 08- INCH,	NOR-SHIPS- USE-NASAR	166.5 / FATHO M						<p><u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.<u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
65	DGB99193	NO DATA AVAILABLE	343971504503 2 / WET WELDING ELECTRODE UW-CS-1 (1/8" OR 3.2 MM)	UNDERWATER WELDING DURING SALVAGE OPS/TRAINING	1000 / PACKAGE						<p>TECHNICAL SPECIFICATION - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration</p> <p>GENERAL SPECIFICATION - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration</p>	
66	DGB100817		473099531137 6 / FLANGE, PIPE STEEL, ROUND Nominal BORE 1.00 inch	FOR PIPE FITTING/AS&AS P-6 KHAIBER, TARIQ	38 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - MATERIAL GRADE: MILD STEEL MILD STEEL, STANDARD: BS-10 OF 2009, GRADE S235-JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3-1/4 INCH, OUTER DIA: 4-1/2 INCH, BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH</p> <p>GENERAL SPECIFICATION - MATERIAL GRADE: MILD STEEL MILD STEEL, STANDARD: BS-10 OF 2009, GRADE S235-JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3-1/4 INCH, OUTER DIA: 4-1/2 INCH,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH	
67	DGB100956		473099531137 6 / FLANGE, PIPE STEEL, ROUND Nominal BORE1.00 inch	FOR PIPE FITTING/AS&A S P-6 KHAIBER, TARIO	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - MATERIAL GRADE: MILD STEEL MILD STEEL, STANDARD: BS-10 OF 2009, GRADE S235-JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3- 1/4 INCH, OUTER DIA: 4-1/2 INCH, BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH GENERAL SPECIFICATION - MATERIAL GRADE: MILD STEEL MILD STEEL, STANDARD: BS-10 OF 2009, GRADE S235-JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3- 1/4 INCH, OUTER DIA: 4-1/2 INCH, BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH	
68	DGB99517		530699124362 8 / BOLT MACHINE ISO STEEL HEX HD SIZE 16X5X38 MM	FASTENINGS, BOLTS AND STUDS.	20 / EACH/N UMBER						TECHNICAL SPECIFICATION - SIZE: 16X5X38 MM, MATERIAL: MS, Grade AISI 4140, BOLT HEAD HEXAGON GENERAL SPECIFICATION - SIZE: 16X5X38 MM, MATERIAL: MS, Grade AISI 4140, BOLT HEAD HEXAGON	
69	DGE100813	NIL	597070504730 3 / nomex paper-12		5 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DGE101181	NO DATA AVAILABL E	792000543649 2 / PAPER TOWEL		15 / BOX						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	DGB99190	NO DATA AVAILABL E	021459003338 1 / SCREW MACHINE BSW STEEL		50 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - MATERIAL GRADE EN 4140 GENERAL SPECIFICATION - MATERIAL GRADE EN 4140	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HEX HD SZ 1.500X0.625IN									
72	DGE100 796	NO DATA AVAILABL E	046150000002 4 / PAPER ABRASIVE 9" X11" WATERPROO F MATERIAL EMERY GRADE P- 120D		100 / SHEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DGE100 598	NO DATA AVAILABL E	046150000002 4 / PAPER ABRASIVE 9" X11" WATERPROO F MATERIAL EMERY GRADE P- 120D		20 / SHEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DGE100 792	NO DATA AVAILABL E	046150000008 6 / GOGGLE CHIPPING		30 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band. GENERAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.	
75	DGE98105	NO DATA AVAILAB LE	04615000008 6 / GOGGLE CHIPPING		44 / EACH/N UMBER	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band</p> <p>GENERAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
76	DGE100 663	NO DATA AVAILABL E	04325000002 8 / HELMET PROTECTIVE WITH VISER COLOUR WHITE (FULL HEAD)		6 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DGE100 798	NIL	810501124264 5 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217- 9451	STATIC SAFETY OF EQUIPMENT/C OMPONENTS	20 / EACH/N UMBER						TECHNICAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897- 1557 GENERAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
78	DGE100 597	NIL	810501124264 5 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217- 9451	STATIC SAFETY OF EQUIPMENT/C OMPONENTS	20 / EACH/N UMBER						TECHNICAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897- 1557 GENERAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
79	DGE100 790		813570506488 2 / TAPE TRANSPAREN T ADHESIVE WATER PROOFED	GENERAL USE.	6 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WD.12 MM LG. 66 MTR.									
80	DGE100 899		031050000000 4 / CANVAS COTTON GREY (WD: 24")		40 / METER	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - a. Width 24' b. Weight 340-425 gsm c. Thickness 1-2mm d. Weave Tight weave for water resistance e. Material 100% Cotton with waterproof coating f. Thread Cotton 150-200-Thread per inch g. Waterproof Yes h. Water resistance 1000 mm WEIGHT 24 OZ PER SQ YD ROT PROOF & WATER PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance</p> <p>GENERAL SPECIFICATION - a. Width 24' b. Weight 340-425 gsm c. Thickness 1-2mm d. Weave Tight weave for water resistance e. Material 100% Cotton with waterproof coating f. Thread Cotton 150-200-Thread per inch g. Waterproof Yes h. Water resistance 1000 mm WEIGHT 24 OZ PER SQ YD ROT PROOF & WATER PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance</p>	
81	DGT100 805	NO DATA AVAILAB LE	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	320 / SQ FEET	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993</p> <p>GENERAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
82	DGT100 940	NO DATA AVAILABL E	010000000004 8 / TIMBER SHESHAM SLEEPER WELL SEASONED LOCAL		8 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH iM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL <u>USEGENERAL SPECIFICATION -</u> SIZE: LENGTH= 6-8 FEET WIDTH= 15-17 INCH BREATH= 12-14 INCH iM 2692 (E) OF 1970 and both ends cutting after inspection, desired by inspector PSG-847 MOISTURE CONTENT: 30% (±5%) PARENT EQUIPMENT : GENERAL USE	
83	DGE987 43	Is219004p k	841576100337 8 / HELMET CRASH VIP ESCORT RIDER W/SUN VISER, NYL/BELT FOAM COAT		15 / EACH/N UMBER	ff353 rapid single mono					<u>TECHNICAL SPECIFICATION -</u> colour: gloss white (2) Serial No 1003378 size: xxl carton no. 102-57 W/Sun Viser, Size 23.23"-23.62" NYL/Belt Foam (56-60 cm) <u>GENERAL SPECIFICATION -</u> colour: gloss white (2) Serial No 1003378 size: xxl carton no. 102-57 W/Sun Viser, Size 23.23"-23.62" NYL/Belt Foam (56-60 cm)	
84	DGE100 700	DEFSTAN 84-2- 22495 SIZE 27	844099978449 8 / STOCKING WHITE FOR SEA BOOTS	FIRE FIGHTING	4 / PAIR						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
85	DGB101 202		451054601339 4 / WASH BASIN CEREMIC.		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATIONS: L: 22" W: 15" H: 40" REMARKS: WHITE COLOR FANCY COMPANY: MASTER/DAIMOND <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - SPECIFICATIONS: L: 22" W: 15" H: 40" REMARKS: WHITE COLOR FANCY COMPANY: MASTER/DAIMOND	
86	DGD100 625	NO DATA AVAILABL E	003550000050 7 / STRAINERSRI CE FOR POTS ALU 20X10 INCH		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kgGENERAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kg	
87	DGD821 94		003550000052 0 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" H12 TO 14" TH 10 SWG WITH OUT COVER		4 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" H12 to 14" TH 10 SWG WITH out COVER GENERAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
88	DGD741 67		003554600061 4 / POT ALU 15/7" WITH COVER		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - 200 TO 250 LBSGENERAL SPECIFICATION - 200 TO 250 LBS	
89	DGE100 924	NO DATA AVAILABL E	055979000198 5 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR	GENERAL ELECTRIC USE	35 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
90	DGE100 599	NO DATA AVAILABL E	055979000198 5 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR	GENERAL ELECTRIC USE	10 / ROLL	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
91	DGE98185	QB/T 1103-2001 (1)	7920FP0020001 / BRUSH 1		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DGE100882	ASTM D-120-87	8415011589454 / Gloves electrical workers		4 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A	
93	DGE98127	7920-00-148-9666	7920001489666 / Rag wiping Cotton & cotton synthetic 50 lbs	NIL	60 / SET	NA	NA	ALFA LAVAL TUMBA AB, HANS STAHL VAG 7 TUMBA SWEDEN	ALFA LAVAL TUMBA AB, SWEDEN		TECHNICAL SPECIFICATION - PMS Item GENERAL SPECIFICATION - PMS Item	
94	DGE98995	NIL	3510705181278 / TRAY BLEECH	NIL	3 / EACH/NUMBER	NIL		LOCAL MARKET	NOT KNOWN		TECHNICAL SPECIFICATION - GENERAL ITEM GENERAL SPECIFICATION - GENERAL ITEM	
95	DGB101209	XT10/209822	3455725280806 / CUTTING DISC RHODIUS XT10 SIZE 105x1x16		20 / EACH/NUMBER	RHODIUS TOPLINE					TECHNICAL SPECIFICATION - MATERIAL SPECIFICATIONS: STAINLESS STEEL, RUST AND ACID PROOFED STEELS, HIGH TENSILE, HIGH ALLOYED STEELS, TOOL STEELS, HARDENED STEELS, HARDOX, HIGH TENSILE METAL SHEETS GENERAL SPECIFICATION - MATERIAL SPECIFICATIONS: STAINLESS STEEL, RUST AND ACID PROOFED STEELS, HIGH TENSILE, HIGH ALLOYED STEELS, TOOL STEELS, HARDENED STEELS, HARDOX, HIGH TENSILE METAL SHEETS	
96	DGE101134	100-65F	7920993008997 / CLEANING LINT FREE CLOTH (GUC ITEM)	CLEANING CLOTH	140 / EACH/NUMBER	NO DATA AVAILABLE		UK		MEMO HCG/MS D/03/336 DT 2/7/08	TECHNICAL SPECIFICATION - Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											sealed edges (+/- 3mm accuracy). <u>GENERAL SPECIFICATION</u> - Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy).	
97	DGB995 57	Morgan TPC 843	047479520862 6 / Morgan Silicon Carbide Crucible, Top Dia: 420MM, Bottom Dia: 295MM	TILTING FURNACE NO 3006 TYPE CA F-23 (PLL) RECORD	1 / EACH/NUMBER	N/A	N/A	MOLTEN ADVANCED MATERIALS PLC REGISTERED IN ENGLAND AND WALES REGISTRATION NO 286773 & INDIA MANUFACTURED	MORGAN ITE CRUCIBLE LTD		<u>TECHNICAL SPECIFICATION</u> - Morgan Silicon Carbide Crucible, Height: 675MM, Top Dia: 420MM, Bottom Dia: 295MM, Part No. TPC 843 (drawing enclosed) <u>GENERAL SPECIFICATION</u> - Morgan Silicon Carbide Crucible, Height: 675MM, Top Dia: 420MM, Bottom Dia: 295MM, Part No. TPC 843 (drawing enclosed)	
98	DGH990 75	5510A	403079515388 1 / STAINLESS STEEL WIRE ROPE	TAL SHIP SAILING RIG	193 / METER			BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST,HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET.COM.WEB:WWW.BASELINEHARDWARE.CO.UK	UK		<u>TECHNICAL SPECIFICATION</u> - 7 x 19 stainless steel wire rope flexible (10mm) with minimum breaking strength 5670 kg grade: 316 (A4) marine grade mill test certificate: Required from OEM with bulk supply <u>GENERAL SPECIFICATION</u> - 7 x 19 stainless steel wire rope flexible (10mm) with minimum breaking strength 5670 kg grade: 316 (A4) marine grade mill test certificate: Required from OEM with bulk supply	
99	DGE993 02	-	561099200438 6 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	5 / KILOGRAMME	NO DATA AVAILAB LE		UK	FLOWCR ETE UK LTD THE FLOORIN G		<u>TECHNICAL SPECIFICATION</u> - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE. ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									TECHNOLOGIES CENTRE BOOTH LANE SANDBA TCH CHESHIRE CW11 3QF UK PH:+44(0)1270 753000 & FAX :+44 (0)1270 753333		2011.&l(M) DC&FF.GENERAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&l(M) DC&FF.	
100	DGB81967		027759910623 1 / SPANNER O/JAW FXD D. E 0.625X0.688" W0.563X0.625" L MAX12X10. 25		14 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
101	DGE101267	NO DATA AVAILABLE	035059571324 4 / SPUN YARN SISAL "S" TWIST ROT PROOFED, 3/20 YARN, LENGTH PER COIL 811+-5% (FM)		450 / KILOGR AMME						TECHNICAL SPECIFICATION - BS-2052/65 TABLE 27 GENERAL SPECIFICATION - BS-2052/65 TABLE 27	
102	DGE81364		041370506324 3 / ANTI SKID DOTTED RUBBER FLOORING COLOUR GREEN 15" X36"0.17".		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
103	DGE101132		035059571303 2 / ROPE COIR HAWSERLAID CIR 2"		400 / FATHO M						TECHNICAL SPECIFICATION - 3 STRD CIR 2" DIA 0.625 MATERIAL COIR (Husk of CoConut) GENERAL SPECIFICATION - 3 STRD CIR 2"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											DIA 0.625 MATERIAL COIR (Husk of CoConut)	
104	DGE769 14		047659943044 1 / BRUSH ARTISTS QUILL FERRULE;RED SABLE HAIR EXPOSED LG. 0.500"		10 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DGE769 12		047659943045 3 / BRUSH ARTISTS CAMEL HAIR SWAN SMALL EXPOSED LG 1 3/16 INCH		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DGE866 36	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		318 / EACH/N UMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
107	DGE102 867	nil	035059571312 1 / Rope Nylon, Hawser laid, White, 3- Strand, Cir: 1- Inch, Diameter: 8-MM		120 / FATHO M						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.</p>	
108	DGE99012	NO DATA AVAILABLE	041354600479 4 / EAR DEFENDER LARGE SIZE		6 / PAIR	NO DATA AVAILABLE					<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
109	DGE98104	0461-931-8996	046059931899 6 / TAPE COTTON ADHASIVE COMPOUND	30 MM GUN.	40 / ROLL						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			WIDTH 3" THICK 0.038" LG.10 MTR.									
110	DGE99057	NIL	041359923891 6 / SHEET RUBBER SOLID NATURAL BLACK LENGTH 6 FT, WIDTH 48 INCH, THICKNESS: 0.188 INCH	.HARDNESS RATING:62-70, TENSILE STRENGTH: 14 MPQ 2000 PSI, COMPOUND CLASSIFICATI ON: Z 14	10 / KILOGR AMME						TECHNICAL SPECIFICATION - SHEET RUBBER BLACK LENGTH= 6 FEET WIDTH= 48 INCH THICKNESS= 0.188 INCH APPROX WIGHT= 1.50LBS PER SQ FEET REPLACING DEXINE MATERIAL. COMPOUND CLASSIFICATION- Z 60. HARDNESS AFTER VULCANIZATION (IRHD): 60+5-4) TENSILE STRENGTH: 17 (MPA) MINIMUM BS-1154 OF 1992 COMPOUND CLASSIFICATION- Z 60 ADVANCE SAMPLE TO BEAPPROVED BY CINS SPECS UPDATED VIDE IND NO 2211205 DT 12-08-22GENERAL SPECIFICATION - SHEET RUBBER BLACK LENGTH= 6 FEET WIDTH= 48 INCH THICKNESS= 0.188 INCH APPROX WIGHT= 1.50LBS PER SQ FEET REPLACING DEXINE MATERIAL. COMPOUND CLASSIFICATION- Z 60. HARDNESS AFTER VULCANIZATION (IRHD): 60+5-4) TENSILE STRENGTH: 17 (MPA) MINIMUM BS-1154 OF 1992 COMPOUND CLASSIFICATION- Z 60 ADVANCE SAMPLE TO BEAPPROVED BY CINS SPECS UPDATED VIDE IND NO 2211205 DT 12-08-22	
111	DGE101135	NO DATA AVAILABL E	043452000015 6 / LEAD WEIGHT IKG WITH CLAMP TYPE LOCK,T-40761	DIVING BREATHING APPARATUS T-9651 LARIII	10 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
112	DGE98103	NO DATA AVAILABL E	041559923141 0 / SHEET PLASTIC TRASPARENT		16 / SHEET						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LG.48 WD 36TH 0.125 MATERIAL METHYL METHACRYLA TE PLAIN REF DTD 5592									
113	DGE971 75	0330-1225	035059923386 8 / FENDER MARINE LENGTH 9.0 INCHES WIDTH 5.0 INCHES		8 / EACH/N UMBER						TECHNICAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT. GENERAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT.	
114	DGB992 09		021459941001 9 / BOLT MACHINE STEEL UNC class 2a HEX HD SZ 0.625 X3.000X1.500 IN	BR-320 D/78	36 / EACH/N UMBER						TECHNICAL SPECIFICATION - AISI PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED GENERAL SPECIFICATION - AISI PD 970: 2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED	
115	DGB101 273	SPEC; BS1769	026659001603 1 / WASHER FLAT ROUND MILD STEEL O/D1.625"/I/D0. 792"THICK0. 128"		40 / KILOGR AMME						TECHNICAL SPECIFICATION - Spec: BS-970 EN 3A GENERAL SPECIFICATION - Spec: BS-970 EN 3A	
116	DGB941 71	NO DATA AVAILABL E	026359923698 7 / THIMBLE, ROPE STEEL BS 970-EN 3A GALVANISED PEAR SHAPED OPEN TYPE	SPEC NO DGS 5031NO.40	350 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WT 1.75LBS SIZE 1.25									
117	DGB101 261	MATERIAL GRADE EN 4140	021459941638 8 / BOLT MACHINE STEEL UNC HEX HD 0.75 X12X2 INCH TPI 10 (LOCAL)		116 / EACH/N UMBER						TECHNICAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED GENERAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
118	DGB990 19	CHC 38 (6350-99- 411-9601)	025159411960 1 / SHIP BELL BRASS MADE WATCH 45 POUNDS		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - oem/cOUNTRY of Origin already UK oem coc or mtc : any local supplier GENERAL SPECIFICATION _oem/cOUNTRY of Origin already UK oem coc or mtc : any local supplier	
119	DGB101 203	NO DATA AVAILABL E	024559245103 3 / COMMODE CHAIR (3 STAR CERAMICS COMMODE)		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Specifications: L: 16" W: 28" H: 26" Remarks: WHITE COLOR FANCY Company: Master/Daimond GENERAL SPECIFICATION - Specifications: L: 16" W: 28" H: 26" Remarks: WHITE COLOR FANCY Company: Master/Daimond	
120	DGE981 24	NO DATA AVAILABL E	046154600568 3 / PAPER ABRASSIVE WATER PROOF 9" X11".		15 / SHEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
121	DGE990 03	NO DATA AVAILABL E	055999923462 8 / PHASC TAP PVC (G)	INSULATION AND MARKING TAPE	7 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DGE101 129	NO DATA AVAILABL E	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC; GRADE: 300D, SAFETY; FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.</p> <p><u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS. FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY</p>	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD. (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED,	
123	DGE977 10	621100/30 68.184	422079522956 2 / FINS SWIM RUBBER BLACK	FOR DIVING	12 / PAIR						TECHNICAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES, COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95LBs(2.25Kg,MADE USA. GENERAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES, COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95LBs(2.25Kg,MADE USA.	
124	DGB101 210	CATTLOG NO.(USA) 42-059- 007	343971506689 3/ ELECTRODE CUTTING TYPE SEA CUTT SIZE 5/6"X18" (BLUE)	FOR GENERAL USE	150 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILBLEGENERAL SPECIFICATION - NO DATA AVAILBLE	
125	DGB738 61		513370504927 1 / DRILL BITS	COMMON TOOLS GYRO	3 / EACH/N						TECHNICAL SPECIFICATION - NO DATA AVAILBLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SETS 29 PCS	REPAIRE FACILITY JAPAN	UMBER						SPECIFICATION - NO DATA AVAILABLE	
126	SGB99408	0254-254009	473099420313 4 / TEE EQUAL	FOR GENERAL USE	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - TEE EQUAL IS DN 1.5" AND MATERIAL IS EITHER BRASS, BRONZE OR GUN METAL DIMENSION: BORE 1 1/2" material: LEADED GUNMETAL-LG2 tensile strength mpa: 270 metarial grade: BS-1400 GENERAL SPECIFICATION - TEE EQUAL IS DN 1.5" AND MATERIAL IS EITHER BRASS, BRONZE OR GUN METAL DIMENSION: BORE 1 1/2" material: LEADED GUNMETAL-LG2 tensile strength mpa: 270 metarial grade: BS-1400	
127	DGE101124		535000235013 7 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE 2/0		65 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
128	DGE98913	MIL-P-15280	564000237482 7 / INSULATION SLEEVING THERMAL		105 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
129	DGE994 56	MIL-P- 15280	564000237482 7 / INSULATION SLEEVING THERMAL		15 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p> <p>GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p>	
130	DGE989 12	MIL-P- 15280	564000237482 8 / INSULATION SLEEVING THERMAL		105 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p> <p>GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.</p>	
131	DGE989 66	1756654	597000184200 2 / TAPE- INSLATION		15 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</p> <p>GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
132	DGE989	NO DATA	597070504730		48 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	67	AVAILABLE	4 / Nylon Transparent Tape (1 inch size).		ROLL						manufacturer with following details: a. Manufacturer Name: Gold Star (GS) b. Item Name: Nylon Transparent Tape c. Size: 1 inch d. Price: Rs 55/- SAME ITEM IS ALSO AVAILABLE FROM LOCAL market <u>GENERAL SPECIFICATION</u> - manufacturer with following details: a. Manufacturer Name: Gold Star (GS) b. Item Name: Nylon Transparent Tape c. Size: 1 inch d. Price: Rs 55/- SAME ITEM IS ALSO AVAILABLE FROM LOCAL market	
133	DGE99080	CHR4440, MIL-I-46852	5970009494846 / INSULATION TAPE ELECTRIC, ADHESIVE, WD 1		38 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
134	DGE98970	NO DATA AVAILABLE	0474500000307 / FENDER COIR ROUND		8 / EACH/NUMBER	600MM 24" ROUND COIR BOAT FENDER					<u>TECHNICAL SPECIFICATION</u> - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE. BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION. STORAGE-WET AND DRY. <u>GENERAL SPECIFICATION</u> - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE. BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
135	DGE99040	NO DATA AVAILABLE	043250000006 / DUST RESPIRATOR		25 / EACH/NUMBER	M 511-N95					RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY. <u>TECHNICAL SPECIFICATION -</u> packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size: Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95 China (GB 2626-2006) Filtering Rate: = 95% <u>GENERAL SPECIFICATION -</u> packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size: Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95 China (GB 2626-2006) Filtering Rate: = 95%	
136	DGE101139	NO DATA AVAILABLE	046150000008 / GOGGLE CHIPPING		110 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band. <u>GENERAL SPECIFICATION -</u> Concurrence to CSA Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.	
137	DGE989 64	NIL	810501124264 5 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217- 9451	STATIC SAFETY OF EQUIPMENT/C OMPONENTS	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897- 1557 <u>GENERAL SPECIFICATION -</u> ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
138	DGT101 279	NO DATA AVAILABL E	010000000000 3 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	222 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
139	DGE101 268		031050000000 4 / CANVAS COTTON GREY (WD: 24")		40 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - a.</u> Width 24' b. Weight 340-425 gsm c. Thickness 1-2mm d. Weave Tight weave for water resistance e. Material 100% Cotton with waterproof coating f. Thread Cotton 150-200- Thread per inch g. Waterproof Yes h. Water resistance 1000 mm WEIGHT 24 OZ PER SQ YD ROT PROOF & WATER PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SPECIFICATION - a. Width 24' b. Weight 340-425 gsm c. Thickness 1-2mm d. Weave Tight weave for water resistance e. Material 100% Cotton with waterproof coating f. Thread Cotton 150-200-Thread per inch g. Waterproof Yes h. Water resistance 1000 mm WEIGHT 24 OZ PER SQ YD ROT PROOF & WATER PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance</p>	
140	DGT101 206	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	1480 / SQ FEET	NO DATA AVILAB LE					<p>TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p>GENERAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO.	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop	
141	DGE100563	BA111131/5931052	8465725022150 / BAG CARRYING FOR DIVING EQUIPMENT		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - (1) Volume : 130 Liters (2) Dimension : 85 cm x35 cm x 45 cm (3) Made from : Bag made with Tarpolin (4) Shape : U shape for opening (5) Appearance : 2 handles and shoulder strips/ 2 screwed valves GENERAL SPECIFICATION - (1) Volume : 130 Liters (2) Dimension : 85 cm x35 cm x 45 cm (3) Made from : Bag made with Tarpolin (4) Shape : U shape for opening (5) Appearance : 2 handles and shoulder strips/ 2 screwed valves	
142	DGE75573		9330992246090 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4. X0.60 to 0.70 MM	GENERAL USE	12 / SHEET						TECHNICAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794GENERAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
143	DGE98183		0451546004459 / HOOKS FOR CURTAIN		10 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
144	DGB101201		4510705123201 / BATH MIXER WALL TYPE WITH		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			UNIVERSAL SHOWER (MUSLIM BIB COCK									
145	DGE101 270	501256816 6895	402099396075 3 / ROPE FIBROUS, POLYESTER/ PROPYLENE MIX, 08-STRAND, DIA: 40MM		440 / METER						<p>TECHNICAL SPECIFICATION - SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 40-MM DIA BLACK BERTHING POLYESTER/ PROPYLENE MIX, 8-STRAND MOORING NUMBER-5, MBL 26.4 TONNES, MB-67 TABLE-3, 3.8, PLAIN ENDS UV STABILISED ISO 9554 of 2019. 3. STANDARD ACCORDANCE TO ISO 2307 PACKAGING. 4. STANDARD OF MANUFACTURE ISO 2307 OF 2019 5. CONFIRMATION OF STANDARD EN-ISO 2307 OF 2019. 6. 220 METER PER COILS. 7. CERTIFICATIONS: VALID LLOYD TEST CERTIFICATE REQUIRED INDICATION BATCH/LOT NUMBER OF IDENTIFICATION AND WORKING / BREAKING AND STRENGTH OF STORES. 8. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM Phone: +44(0) 1323444444 EMAIL: sales@marlowropes.com</p> <p>GENERAL SPECIFICATION - SPECIFICATION: 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO-10556. 2. 40-MM DIA BLACK BERTHING POLYESTER/ PROPYLENE MIX, 8-</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>STRAND MOORING NUMBER-5, MBL 26.4 TONNES, MB-67 TABLE-3, 3.8, PLAIN ENDS UV STABILISED ISO 9554 of 2019. 3. STANDARD ACCORDANCE TO ISO 2307 PACKAGING. 4. STANDARD OF MANUFACTURE ISO 2307 OF 2019 5. CONFIRMATION OF STANDARD EN-ISO 2307 OF 2019. 6. 220 METER PER COILS. 7. CERTIFICATIONS: VALID LLOYD TEST CERTIFICATE REQUIRED INDICATION BATCH/LOT NUMBER OF IDENTIFICATION AND WORKING / BREAKING AND STRENGTH OF STORES. 8. SUPPLY FIRM SHALL OBTAIN AND FURNISH MANUFACTURE CERTIFICATE TO PN AS SAME QUALITY/ STANDARD AS BEING PROVIDED TO MoD (UK)/ RN/ RELATED COUNTRY. 9. ROPE ARE TO BE SUPPLIED WITH VALID LLOYD'S/ BSI/ IACS MEMBER SOCIETY CERTIFICATION. 10. OEM ADDRESS: MARLOW ROPES LTD HAILSHAM EAST SUSSEX UNITED KINGDOM Phone: +44(0) 1323444444 EMAIL: sales@marlowropes.com</p>	
146	DGB101 248	HME-AB- UNI- FERROL- 20MM- 003	473070535123 6 / union connector ferrol type dia 20mm		40 / EACH/N UMBER	SS304 SURFAC E					<p><u>TECHNICAL SPECIFICATION - UNION CONNECTOR TYPE FERROL DIA 20MM material stainless steel</u> <u>GENERAL SPECIFICATION - UNION CONNECTOR TYPE FERROL DIA 20MM material stainless steel</u></p>	
147	DGE990 07	A-A-50162	792000634240 8 / Towel, machinery wiping	0	1 / PACKE T	0	0	1333 ISAAC HULL AVE S E, WASHINGTON NAVY YARD, DC	NAVAL SEA SYSTEM S COMMAN D		<p><u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u></p>	
148	DGH102 828		951570511915 4 / PLATE		100 / EACH/N						<p><u>TECHNICAL SPECIFICATION -</u> <u>Dimension: 6000mm(length) x</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			STEEL CARBON 6.X2. 9..X6MM		UMBER						2900mm(width) x 6mm(thickness) <u>GENERAL SPECIFICATION -</u> Dimension: 6000mm(length) x 2900mm(width) x 6mm(thickness)	
149	DGT102 876	NO DATA AVAILABL E	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		12 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) <u>GENERAL SPECIFICATION</u> - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
150	DGT102 611	NO DATA AVAILABL E	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		30 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) <u>GENERAL SPECIFICATION</u> - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
151	DGE102 345		933070530065 4 / telic sheet (TRANSPARE NT sheet) THICKNESS: 0.35MM WIDTH:54 INCH LENGTH: 25-30 meter		160 / SQ FEET	sheet					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
152	DGE102 887	honey/mk/ 22	597070526728 8 / Honey Comb Hole matt rubber 20"x36"x1/2"		200 / EACH/N UMBER	NA					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
153	DGD102 628	MM-32	731070526967 3 / MEAT MINCER		1 / EACH/N UMBER	mm-32					<u>TECHNICAL SPECIFICATION -</u> capacity: 200kg/hr, power: .90 kw <u>GENERAL SPECIFICATION -</u> capacity: 200kg/hr, power: .90 kw	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
154	DGD102 618	DS-10	731070526967 6 / MULTI PURPOSE DOUGH KNEADING MACHINE		1 / EACH	ssd80d					TECHNICAL SPECIFICATION - voltage (v/hz): 380/50, input power (w): 4000, volume(l): 80, capacity (kg): 30, rod speed(r/min): 250/125, bowl speed(r/min): 20, net weight (kg): 510, width'depth'height(mm): 590*1040*1230 GENERAL SPECIFICATION - voltage (v/hz): 380/50, input power(w): 4000, volume(l): 80, capacity (kg): 30, rod speed(r/min): 250/125, bowl speed (r/min): 20, net weight(kg): 510, width'depth'height(mm): 590*1040*1230	
155	DGE102 861	565665	534070524611 1 / leatherite for wallpaper		200 / SQ FEET	565665					TECHNICAL SPECIFICATION - leatherite wallpaper sheetsGENERAL SPECIFICATION - leatherite wallpaper sheets	
156	DGD102 622	QSB-01	731070526966 3 / SOUNDLESS BLENDER		1 / EACH/N UMBER	QSB-01					TECHNICAL SPECIFICATION - MATERIAL ABS+UNBREAKABLE PC/TRITAN, TOUCH PAD CONTROL PANEL, EASY OPERATION, 1800W POWERFUL COPPER MOTOR, HIGH SPEED 27000-30000 RPM GENERAL SPECIFICATION - MATERIAL ABS+UNBREAKABLE PC/TRITAN, TOUCH PAD CONTROL PANEL, EASY OPERATION, 1800W POWERFUL COPPER MOTOR, HIGH SPEED 27000-30000 RPM	
157	DGH102 829	LNKPN201 510	3020PK520265 1 / PINS	RACK	1000 / UNIT			3RD FLOOR 83C,PHASE 2, EXTENSION,MAIN NATIONAL HIGHWADEFENCE KARACHIY.,021538726		HABIB & SONS	TECHNICAL SPECIFICATION - YEILD STRENGTH:245MPA16MM MATERIAL:SS400 TENSILE STRENGTH:400-510MPA THICKNESS:1.3MM SURFACE FINISH:GALVANIZED/POWDER COATED HEXAGONE NUT AND BOLT:M10*80*2 GENERAL SPECIFICATION - YEILD STRENGTH:245MPA16MM MATERIAL:SS400 TENSILE STRENGTH:400-510MPA THICKNESS:1.3MM SURFACE FINISH:GALVANIZED/POWDER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											COATED HEXAGONE NUT AND BOLT:M10*80*2	
158	DGE102 598	YCR105 or 1260	830578516309 0 / CERAMIC FIBER CLOTH	GENRAL USE	100 / METER	YCR105		OEM:CHINA MANUFACTURERS NINGBO RUIFENG SEALING MATERIAL COMPANY LTD KUANGVAN TOWN CIXI : 86-574-63531211.63531433.	PANASO NIC SADDAR KARACI. TECHNO POWER SYSTEM		TECHNICAL SPECIFICATION - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, tempErature resistance= 700 °C (degree centigrade), max thermal conDuctivity= 0.16 w/m.K GENERAL SPECIFICATION - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, tempErature resistance= 700 °C (degree centigrade), max thermal conDuctivity= 0.16 w/m.K	
159	DGE101 231	NIL	721050515517 2 / FIRE RETARDANT SPRING MATTRESS (L6' X W2' X H6")	MATRESSES FOR BED	20 / EACH/N UMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		TECHNICAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413GENERAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
160	DGE102 868		042270515841 1 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	500 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTIC S, SADDAR KARACHI		TECHNICAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
161	DGE102 729		042270515841 1 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	1500 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTIC S, SADDAR KARACHI		TECHNICAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
162	DGD102	29161900	650570519305	MRE PACKS	600 /	N/A	N/A	PANA FORCE FOODS	PANA		TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	512		8 / FUEL TABLETS	(04 IN ONE PACKET)	PACKET			ASC NOWSHEHRA KPK	FORCE FOODS		N/AGENERAL SPECIFICATION - N/A	
163	DGE102727	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	1090 / EACH/NUMBER	SSP-01-LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTAN		TECHNICAL SPECIFICATION - AS PER LETTER ATTACH GENERAL SPECIFICATION - AS PER LETTER ATTACH	
164	DGE102681	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	1100 / EACH/NUMBER	SSP-01-LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTAN		TECHNICAL SPECIFICATION - AS PER LETTER ATTACH GENERAL SPECIFICATION - AS PER LETTER ATTACH	
165	DGE102883	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	1280 / EACH/NUMBER	SSP-01-LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTAN		TECHNICAL SPECIFICATION - AS PER LETTER ATTACH GENERAL SPECIFICATION - AS PER LETTER ATTACH	
166	DGB102802	BS1476/NE 8-M	028370571122 6 / ALUMINIUM ALLOY ANGLE EQUALSIDED RT ANGLE LG 1.50"X1.50" X1/8"		72 / METER						TECHNICAL SPECIFICATION - Item Specification: BSEN-573-3 OF 1995 (CHEMICAL COMPOSITION) BSEN-485-2 OF 1995 (MECHANICAL PROPERTIES) GRADE ENAW 5083 GENERAL SPECIFICATION - Item Specification: BSEN-573-3 OF 1995 (CHEMICAL COMPOSITION) BSEN-485-2 OF 1995 (MECHANICAL PROPERTIES) GRADE ENAW 5083	
167	DGB102641	BS1476/NE 8-M	028370571122 6 / ALUMINIUM ALLOY ANGLE EQUALSIDED RT ANGLE LG 1.50"X1.50" X1/8"		300 / METER						TECHNICAL SPECIFICATION - Item Specification: BSEN-573-3 OF 1995 (CHEMICAL COMPOSITION) BSEN-485-2 OF 1995 (MECHANICAL PROPERTIES) GRADE ENAW 5083 GENERAL SPECIFICATION - Item Specification: BSEN-573-3 OF 1995 (CHEMICAL COMPOSITION) BSEN-485-2 OF 1995 (MECHANICAL PROPERTIES) GRADE ENAW 5083	
168	DGB102632		028370571124 5 / ANGLE-		108 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			ALUMINIUM-EQUAL-SIDE-LH1.25TH-.18"								SPECIFICATION - NO DATA AVAILABLE	
169	DGB102801		0283705711245 / ANGLE-ALUMINIUM-EQUAL-SIDE-LH1.25TH-.18"		216 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
170	DGE102900	ISO-11812004, BS-2087	0350595713232 / ROPE SISAL 3 STRAND CIRC 1.25 DIA 13/32 (0.40625) ROT PROOFED	GENERAL USE	120 / FATHOM						TECHNICAL SPECIFICATION - ISO-1181 2004, BS-2087, STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABEL & MARKING AS PER ISO 2307 & 9554 GENERAL SPECIFICATION - ISO-1181 2004, BS-2087, STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABEL & MARKING AS PER ISO 2307 & 9554	
171	DGE102563	BS2052 DEF STAN 40-3	0350595713246 / SPUN YARN SISAL S TWIST R. FROOFED 4/20 YARN LENGTH PER COIL 608-5% (FM)		120 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor) GENERAL SPECIFICATION - 1. Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor)	
172	DGE102759		0462590005989 / TUBING PLASTIC POLYTHYNE LAY FLAT 0.005"TH.WD. 27"WEIGHT PER		260 / KILOGRAMME						TECHNICAL SPECIFICATION - TUBING PLASTIC POLYTHYNE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches thickness: 0.005 inches (DOUBLE SIDE) GENERAL SPECIFICATION - TUBING PLASTIC POLYTHYNE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches thickness: 0.005 inches (DOUBLE SIDE)	
173	DGE101140	C-268	0476599430559 / BRUSH VARNISH TYNEX FLAT		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SQUARE EDGE WD.4								thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
174	DGE654 91	NO DATA AVAILABL E	046159000648 0 / PAINT ROLLER, LENGTH= 7- INCH, DIA= 2- INCH, C/W SHEEP SKIN COVER AND HANDLE STEEL FRAME, WOODEN HANDLE	BLST PAINT UNDER WATER HULL	215 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - a.</u> Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip</p> <p><u>GENERAL SPECIFICATION - a.</u> Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip</p>	
175	DGE103 042		035059571312 8 / ROPE NYLON, HAWSERLAID, 3-STRAND, Z- LAY, NOM DIA: 20MM, (13/16") CIRC: 2.50 INCH, TYPE-1		400 / FATHO M						<p><u>TECHNICAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S</p> <p><u>COTESIGENERAL SPECIFICATION -1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI	
176	DGB102 586		028359571143 2 / ROD NAVAL BRASS HEX A/F 1.01" WT PER FT 3.244 LB. (RUNNING LENGTH: MINIMUM 6 FT)	SERVICE PUMP	5 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2016 GRADE CW 712 (R) M RUNNING LENGTH: minimum 6 ft GENERAL SPECIFICATION - BSEN 12163 OF 2016 GRADE CW 712 (R) M RUNNING LENGTH: minimum 6 ft	
177	DGB102 631		028359571143 8 / ROD NAVAL BRASS HEX SIZE A/F 1.86 INCH	GENERAL PURPOSE (FOR SHIPS)	5 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 1998 GRADE CW 712 R(M) GENERAL SPECIFICATION - BSEN 12163 OF 1998 GRADE CW 712 R(M)	
178	DGB102 620	NO DATA AVAILABL E	028359571115 5 / SHEET ALUMINIUM ALLOY ANNEALED		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN:573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251) GENERAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment.	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN: 573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).	
179	DGE102 832	0414-5160	041459923093 4 / SHEET, ASBESTOS, COMPRESSE D TH 1/16", WD 54"X63" IN WT PER SHEET 22LBS		25 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES) <u>GENERAL</u> SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)	
180	DGE102 831	0414-5162	041459923093 5 / ASBESTOS SHEET COMPRESSE D,	GENERL PERPOSE	15 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - a.</u> Standard/ Grade: BS 2815, Grade A b. Length = 60 Inch c. Width = 60-80 INCH d. Thickness= 3-MM e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS-2815 <u>GENERAL</u> SPECIFICATION - a. Standard/ Grade: BS 2815, Grade A b. Length = 60 Inch c. Width = 60-80 INCH d. Thickness= 3-MM e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS-2815	
181	DGE103 044	NIL	035059571323 1 / ROPE SISAL, HAWSERLAID, 3-STRD, CIRC: 1,1/8 INCH DIA: 10-MM		1500 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BS/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
182	DGB102 626		026759521638 2 / PIPING STEEL SEAMLESS GALVANIZED, L: 6.1M, EXT DIA: 0.844", W/THICKNESS : 0.104", N/BORE: 0.5"	FOR WATER SYSTEM AND OIL ESCAPES ONLY	36 / METER						<u>TECHNICAL SPECIFICATION -</u> BSEN 10216-2 OF 2002, GRADE P265GH, BSEN ISO 1461:2022 FOR GALVANIZING <u>GENERAL</u> <u>SPECIFICATION - BSEN 10216-2</u> OF 2002, GRADE P265GH, BSEN ISO 1461:2022 FOR GALVANIZING	
183	DGB102 625		026759521638 3 / PIPING STEEL SEAMLESS, GALVANIZED, L:6 M, E/DIA: 1.344", W/THICKNESS :0.128", N/BORE:1.0"	NIL	36 / METER						<u>TECHNICAL SPECIFICATION - BS</u> EN 10216-2 :2019 GALVANIZATION BS EN ISO 10240 GALVANIZATION THICKNESS: 55 UM INSIDE AND OUTSIDE OF PIPE <u>GENERAL</u> <u>SPECIFICATION - BS EN 10216-2 :</u> 2019 GALVANIZATION BS EN ISO 10240 GALVANIZATION THICKNESS: 55 UM INSIDE AND OUTSIDE OF PIPE	
184	DGT102 879	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD- II (CORE INNER & OUTER PLIES		416 / SQ FEET						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: BS-1088, part BS- 4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB- 2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE								(±1MM)GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM)	
185	DGH102 580		021159204455 3 / SHEET STEEL STAINLESS SIZE 3050X1220X3 MM	DEEP FRYER 2PAN	8 / EACH/ NUMBER						TECHNICAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MMGENERAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0. 25MM	
186	DGH102 667		021159204455 3 / SHEET STEEL STAINLESS SIZE 3050X1220X3 MM	DEEP FRYER 2PAN	3 / EACH/ NUMBER						TECHNICAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MMGENERAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0. 25MM	
187	DGH102 666		021159923019 6 / SHEET GI ZINC COATED 1800X900X02 MM		31 / EACH/ NUMBER						TECHNICAL SPECIFICATION - 1. DETAILS SIZE: LENGTH 1800MM, WIDTH 900MM, THICKNESS 02MM, WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM (STANDARD FOR STRUCTURE REPAIRS)GENERAL</p> <p><u>SPECIFICATION - 1. dETIALS SIZE:</u> LENGTH 1800MM, WIDTH 900MM, THICKNESS 02MM, WT/SQFT 1.4 KG, WT/SHEET 26 KG GALVANIZED STEEL SHEETS GRADE :JIS G 3302 OR EN 10346 : 2015 SPECIFICATION BSEN 10025 OF 2004, MATERIAL GRADE S 275 JR, ASTM A1063M WITH COATING DESIGNATION Z90. SPECIAL INSTRUCTIONS: (A) MILL TEST CERTIFICATE (MTC) REQUIRED ALONG WITH SUPPLY. THE CERTIFICATE SHOULD HAVE INFORMATION ON MECHANICAL AND CHEMICAL PROPERTIES, STEEL GRADE, BATCH AND HEAT NUMBER ALONG WITH DATE. (B) EACH PLATE SHALL HAVE A SUITABLE STAMP AT A CORNER INDICATING BATCH NUMBER, GRADE AND MANUFACTURER FOR CASE IDENTIFICATION. (C) MATERIAL SHOULD BE FRESHLY ROLLED AND FREE FROM ALL DEFECTS. (D)Sheet GI Zinc coated a. BS EN 10025 of 2004 Grade : s 275 JR b. ASTM A 1063 M with coating designation Z 90 MASS COATING :120-275 G/MM</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(STANDARD FOR STRUCTURE REPAIRS)	
188	DGB103061		0214599410019 / BOLT MACHINE STEEL UNC class 2a HEX HD SZ 0.625 X3.000X1.500 IN	BR-320 D/78	100 / EACH/NUMBER						TECHNICAL SPECIFICATION - AISI PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED GENERAL SPECIFICATION - AISI PD 970: 2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED	
189	DGE102424	NIL	0350599237135 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
190	DGE102 562	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHO M						<p>TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021.</p> <p>2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. GENERAL</p> <p>SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
191	DGH102 668	BS EN 10025-2/2004, MATERIAL GRADE S 275 JR	021259571071 8 / ANGLE STEEL CARBON E/S BLACK 1.25 X 1.25 X 0.25 INCH		32 / METER						TECHNICAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr GENERAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr	
192	DGH102 581	BSEN 10025 GRADE S275 JR	021259571072 3 / ANGLE STEEL CARBON BLACK 1-1/2X1-1/2X1/4"		10 / METER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED GENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED	
193	DGB102 630		026759521327 8 / PIPING STEEL GALVANIZED SEAMLESS, L : 6.1 M, E/DIA 26.9MM, TH 2.6 MM,	UTS LENGTH. BULK SUPPLY	36 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS GENERAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			N/BORE:19.1 MM								10240 GALVANIZING THICKNESS: 40 MICRONS	
194	DGB102 627	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	36 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
195	DGB102 583	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	120 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
196	DGB102 662		021259571007 8 / BAR STEEL CARBON ALLOY HOT ROLLED RD DIA 1 INCH, WT/FT 2.670 LBS	SPEC.BS 970EN 16 (R)	27.73 / METER						TECHNICAL SPECIFICATION - PD 970 DIA 1 INCH, WT/FT 2.670 LBS MATERIAL GRADE: 605M36 RUNNING LENGTH: 10 TO 15 FT GENERAL SPECIFICATION - PD 970 DIA 1 INCH, WT/FT 2.670 LBS MATERIAL GRADE: 605M36 RUNNING LENGTH: 10 TO 15 FT	
197	DGE102 862		422072501370 4 / O RING P/N R18694 SET OF 10		80 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILBLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
198	DGE102 866	NIL	402099923712 1 / ROPE NYLON,	NGTH 1.330 TONS UNIT OF AVAILABILITY	120 / FATHO M						TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HAWSERLAID, 3-STRD, CIR 1.00", DIA 0.3125" (8MM)								2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. <u>GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021,</u> 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM.	
199	DGE103 027	MIL-A-A- 59565	472078503397 3 / HOSE RUBBER INT. DIA.50MM. THICK.5MM. LG.15 MTR. MAX.PRES.12 BAR	WATER RIG OF PNS NASR	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
200	DGB103016		5306999418759 / BOLT PRECISION HEXAGON HEAD UNC SZ 1 1/2X1 1/4X1/2" TPI.13	FASTENINGS, BOLTS AND STUDS.	30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
201	DGE102730	9-27052	6260010744230 / LIGHT CHEMILUMINE SC		600 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
202	DGD102735	MS-3443-A/DW-136G	7310705121904 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	1 / EACH/NUMBER	DW-136G					TECHNICAL SPECIFICATION - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI GENERAL SPECIFICATION - brand name: (i.e. WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI	
203	DGE102863	NO DATA AVAILAB LE	0413500000133 / EAR DEFENDER		55 / PAIR	PELTOR H10A/OPTIME 105					TECHNICAL SPECIFICATION - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip) GENERAL SPECIFICATION - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip)	
204	DGE102 833	NO DATA AVAILABL E	041378000048 8 / HOSE RUBBER 135X121X111 MM	BOOSTER ENGINE L12V 180	4 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
205	DGE102 864	NO DATA AVAILABL E	043250000000 6 / DUST RESPIRATOR		18 / EACH/N UMBER	M 511-N95					TECHNICAL SPECIFICATION - packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size: Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95 China (GB 2626-2006) Filtering Rate: = 95% GENERAL SPECIFICATION - packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size: Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95 China (GB 2626-2006) Filtering Rate: = 95%	
206	DGE102 826	NO DATA AVAILABL E	047678000010 5 / BRUSH PAINT 1		35 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
207	DGE102 825	NO DATA AVAILABL E	047678000011 2 / BRUSH PAINT 3		48 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
208	DGE102 951	32B1296	813599220336 3 / TUBING PLASTIC POLYETHYLE NE TYPE -1 LAY FLAT WD. 36 THIKNESS 0.010 INCH		155 / KILOGR AMME						TECHNICAL SPECIFICATION - AS AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll(no need of packing) locally available GENERAL SPECIFICATION -AS AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll (no need of packing) locally available	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
209	DGT102 875	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	1440 / SQ FEET	NO DATA AVAILAB LE					<p>TECHNICAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: Length= 8', Width=4' & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17 December 2025 end user: PND 107 w/shop</p> <p>GENERAL SPECIFICATION - 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: Length= 8', Width=4' & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS density i.e 700 to 850 kilograms per cubic meter for Ply Wood Marine All Shesham GD-II and 550-750 kilograms per cubic meter for Ply Wood Grade-I is acceptable. by end user vide letter: PN/GM (ME Sur) /GENERAL/3870705 dated 17</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											December 2025 end user: PND 107 w/shop	
210	DGE103068	NO DATA AVAILABLE	04765000006 1 / GLOVES LEATHER FOR WELDING, treated with preservative, standard quality		18 / PAIR	NO DATA AVAILABLE					<p>TECHNICAL SPECIFICATION - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL</p> <p>details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING : 1 dozen pair per polybag broucher uploaded as annex</p> <p>GENERAL SPECIFICATION - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex	
211	DGE102991	NO DATA AVAILAB LE	045150000001 6 / TAPE- WHITE- COTTON		600 / YARD	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILABLE	
212	DGT102880		933099224609 0 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4. X0.60 to 0.70 MM	GENERAL USE	10 / SHEET						TECHNICAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 GENERAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
213	DGT102878	BELFONT TRUWOOD TEAK	933099224609 7 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM,SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		8 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
214	DGD102538	NO DATA AVAILAB LE	003550000045 2 / UTENSILS COOKINGALU M O/D 10" TO 10.5" "H 4" TO 5.5" TH 12 SWH WITH COVER		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd) DIMENSION: O/D 10" to 10.5" "H 4" to 5.5" TH 12 SWg ALUMINIUM GRADE 3003, 1100, 2024 AND 5052 GENERAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											DIMENSION: O/D 10" to 10.5" "H 4" to 5.5" TH 12 SWg ALUMINIUM GRADE 3003, 1100, 2024 AND 5052	
215	DGD102 523		003550000045 7 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		3 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
216	DGD102 540		003550000052 0 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER GENERAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
217	DGD102 758		003550000052 0 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		7 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER GENERAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
218	DGD102 542	NO DATA AVAILABL	003550000045 4 / UTENSIL		1 / EACH/NUMBER	NO DATA AVAILAB					TECHNICAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		E	COOKING ALUMINIUM WITH COVER O/D 16-17", INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESS 10 SWG		UMBER	LE					and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) GENERAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD)	
219	DGE102 680		834570511986 2 / SATTON CLOTH WHITE	PRESENTATIO N VIP ITEM	100 / METER						TECHNICAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches GENERAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches	
220	DGE102 566	NO DATA AVAILABL E	589570512408 0 / CARD BOARD POSTAL BAG 12'X12'X06' & 04 ADJUST PARTITION		250 / EACH/UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
221	DGE102 824		422079514763 0 / SEAMAN KNIFE	BA	40 / EACH/UMBER	Pk-085 gul		UK		GILL MARINE KILDALE MARINE LTD KINGSTON ST-HULL MARINA HU1 2DQ TEL:+44 (0) 1482 227 464 EMAIL: INFO@GILLMARINE.COM	TECHNICAL SPECIFICATION - a. Blade Material :High Grade Stainless Steel b. Blade Lenght: 3.5 – 4 inches for optimal handling in various seamanship evolutions. c. Blade Design: (1) Sheepfoot Blade. Prevents accidental puncturing, commonly preferred in maritime environments. (2) Serrated Section. For cutting of ropes, nets and synthetic materials with ease. (3) Non-reflective finish. Matte or black oxide coating to reduce glare and prevent rust. d. Handle: (1) Material. Reinforced Fiberglass or G10 composite, which is water resistant, lightweight and non-slip. (2) Grip Design. Ergonomic shape with texture or grooves to ensure secure handling even in wet conditions. (3) Lanyard Hole. Allows secure attachment to a cord or carabiner for retention. e. Locking Mechanism: Reliable lock-back or Frame lock	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Mechanism which prevents accidental closing during use and ensures safety. f. Additional Tools (Attached with Seaman knife): (1) Marlin Spike. For untangling knots. (2) Shackle Key. Facilitates quick work with shackles and similar hardware on deck. g. Sheath: Durable Nylon or Hard Plastic provided with belt clip or any compatible attachment for versatility in carrying. Size 99x41x19mm Blade Length 65mm Overall Length 218mm Blade Material Stainless Steel Brand VIGO RMDS <u>GENERAL SPECIFICATION</u> - a. Blade Material : High Grade Stainless Steel b. Blade Length: 3.5 – 4 inches for optimal handling in various seamanship evolutions. c. Blade Design: (1) Sheepfoot Blade. Prevents accidental puncturing, commonly preferred in maritime environments. (2) Serrated Section. For cutting of ropes, nets and synthetic materials with ease. (3) Non-reflective finish. Matte or black oxide coating to reduce glare and prevent rust. d. Handle: (1) Material. Reinforced Fiberglass or G10 composite, which is water resistant, lightweight and non-slip. (2) Grip Design. Ergonomic shape with texture or grooves to ensure secure handling even in wet conditions. (3) Lanyard Hole. Allows secure attachment to a cord or carabiner for retention. e. Locking Mechanism: Reliable lock-back or Frame lock Mechanism which prevents accidental closing during use and ensures safety. f. Additional Tools (Attached with Seaman knife): (1) Marlin Spike. For untangling knots. (2) Shackle Key. Facilitates quick work with shackles and similar</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											hardware on deck. g. Sheath: Durable Nylon or Hard Plastic provided with belt clip or any compatible attachment for versatility in carrying. Size 99x41x19mm Blade Length 65mm Overall Length 218mm Blade Material Stainless Steel Brand VIGO RMDS	