

**LOCAL PURCHASE DIVISION – PAKISTAN NAVY**

**TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 02-06-2026**

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828, 48508720

WHATSAPP NO. 092-322-0188121, 092-341-0201888 (Message Only)

**TENDER BULLETIN**

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNQ96207	CEN1000063A	5510FT1019830 / Wooden Plug, 200 x 30 x 8 mm	Portable Firefighting and Damage Control Equipment System	165 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
2	DSB102457	AV19990970045	0870131703439 / Aluminum Filter Metal AL-Mg 4.5 M		56 / KILOGRAMME	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 GENERAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183</u>	
3	DNQ96252	CEN1000063E	5510FT1019834 / Wooden Plug 300 x 120 x 50 mm	Portable Firefighting and Damage Control Equipment System	150 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
4	DNM96974	3918521	4730013689398 / CLAMP HOSE	DIESEL GENERATOR CUMMINS	2 / EACH/NUMBER	NO DATA AVAILAB LE		US	M/S CUMMINS INC 500 JAKSON ST COLUMB US IN USA		<u>TECHNICAL SPECIFICATION - CLAMP HOSE (band type) adjustable band type 59-83 mm diameter clamp 80g approx width 12-16 mm screw tightening (worm gear style) / band screw zinc plated or corrosion resistant steel GENERAL SPECIFICATION - CLAMP HOSE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									47201-6258 TEL:377-3920 FAX 812-377-1715 E. MAIL: STEVE.AHEWITT@COMMI NS.COM		(band type) adjustable band type 59-83 mm diameter clamp 80g approx width 12-16 mm screw tightening (worm gear style) / band screw zinc plated or corrosion resistant steel	
5	DNM92362	3831132/F S1212	2940795207857 / Filter, Fuel	320 KVA DG	2 / EACH/NUMBER	NT-855-G6	11518	CUMMINS POWER GENERATION COLUMBUS AVENUE MANSTON PARK MANSTON RAMSGATE KENT CT12 5BF UNITED KINGDOM	CUMMINS		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
6	DPC99664	0461-3951, CS2879	0461592240562 / WATER INDICATING PASTE FOR FUEL (03 OZ TUBE)		55 / TUBE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
7	DPC97153	NO DATA AVAILABLE	0474500007028 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		40 / BAG						TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0	
8	DPC98495	NO DATA AVAILABLE	0474500007028 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		43 / BAG						TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 <u>GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0</u>	
9	DPC99532	NO DATA AVAILABL E	0474500007028 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		72 / BAG						<u>TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 <u>GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0</u></u>	
10	DNQ84439	NO DATA AVAILABL E	0091599107983 / FIRE BUCKET	FIRE FIGHTING PURPOSE	30 / EACH/ N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - a. 09 liters water filled standard. b. made of galvanized steel of at least no.22 uss gauge c. rounded buttom welded in place or otherwise suitably reinforced. d. furnished with stamped ears welded in place e. strong wire bail and losse fitting metal covers to exclude debris and retard evaporation. f. should be painted bright red with the word "fire" stenciled in large letter on their outside with contrasting colored paints. g. bucket tanks should be coated with red lead.</u> <u>GENERAL SPECIFICATION - a. 09 liters water filled standard. b. made of galvanized steel of at least no.22 uss gauge c. rounded buttom welded in place or otherwise suitably reinforced. d. furnished with stamped ears welded</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
11	DPK97416	MAGNAFLUX (A DIVISION OF ITW LTD) WCP-2	6850TY671534 1 / WCP-2 WHITE CONTRAST PAINT		5 / EACH/NUMBER	NO DATA AVAILABLE					<p>in place e. strong wire bail and loose fitting metal covers to exclude debris and retard evaporation. f. should be painted bright red with the word "fire" stenciled in large letter on their outside with contrasting colored paints. g. bucket tanks should be coated with red lead.</p> <p><u>TECHNICAL SPECIFICATION - A.</u> WCP-2 IS A BRIGHT WHITE OPAQUE NDT CONTRAST PAINT. IT PROVIDES A HIGH CONTRAST BACKGROUND TO IMPROVE PROBABILITY OF DETECTION AND SENSIBILITY DURING INSPECTION. B. IT CAN BE USED AT A WIDE RANGE OF TEMPERATURE FROM 6°C TO 48°C. C. IT HAS THE ABILITY TO DRY EVENLY AND QUICKLY TO CREATE AN OPTIMAL SURFACE FOR FASTER INDICATION FORMATION D. IT IS A FAST-DRYING PAINT AEROSOL SPRAY WITHOUT FLAKING. E. IT IS IDEAL FOR FIELD TESTING, SPOT INSPECTIONS AND IN-SERVICES INSPECTIONS. F. IT CAN BE USED WITH ALL TYPES OF COLORED AND VISIBLE MAGNETIC PARTICLES. G. IT CAN BE USED WITH WET OR DRY METHOD MAGNETIC PARTICLES. H. IT HAS 360° AEROSOL SPRAYER, HIGH OPACITY, STRONG SURFACE</p> <p><u>GENERAL SPECIFICATION - A.</u> WCP-2 IS A BRIGHT WHITE OPAQUE NDT CONTRAST PAINT. IT PROVIDES A HIGH CONTRAST BACKGROUND TO IMPROVE PROBABILITY OF DETECTION AND SENSIBILITY DURING INSPECTION. B. IT CAN BE USED AT A WIDE RANGE OF TEMPERATURE FROM 6°C TO</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											48°C. C. IT HAS THE ABILITY TO DRY EVENLY AND QUICKLY TO CREATE AN OPTIMAL SURFACE FOR FASTER INDICATION FORMATION D. IT IS A FAST-DRYING PAINT AEROSOL SPRAY. WITHOUT FLAKING. E. IT IS IDEAL FOR FIELD TESTING, SPOT INSPECTIONS AND IN-SERVICES INSPECTIONS. F. IT CAN BE USED WITH ALL TYPES OF COLORED AND VISIBLE MAGNETIC PARTICLES. G. IT CAN BE USED WITH WET OR DRY METHOD MAGNETIC PARTICLES. H. IT HAS 360° AEROSOL SPRAYER, HIGH OPACITY, STRONG SURFACE	
12	DPC83761	GLDO1	681070527975 2 / ADVANCE COAT POLYETHYLENE COATING POWDER GOLDEN SHADE		20 / KILOGRAMME	POLYETHYLENE					TECHNICAL SPECIFICATION - POLYETHYLENE COATING POWDER GOLDEN SHADE GENERAL SPECIFICATION - POLYETHYLENE COATING POWDER GOLDEN SHADE	
13	DSB100187	LOCAL LPH03-PM-0721-VTX	471072524743 9 / HOSE WITH DN 651 M200 LONG		2 / EACH/NUMBER	DN65					TECHNICAL SPECIFICATION - a. Material - Steel Wire Reinforce Hose b. Dia - 3 Inch c. Length - 45 Inch d. Testing Pressure - 04 bar e. End Fitting - Stainless Steel 316 Flange f. Part No - LPH03-PM-0721-VTX g. Manufacture - Vertex Engineering GENERAL SPECIFICATION - a. Material - Steel Wire Reinforce Hose b. Dia - 3 Inch c. Length - 45 Inch d. Testing Pressure - 04 bar e. End Fitting - Stainless Steel 316 Flange f. Part No - LPH03-PM-0721-VTX g. Manufacture - Vertex Engineering	
14	DSB102178	LOCAL ITEM	000000050000 1 / GARBAGE BAG		500 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag <u>GENERAL SPECIFICATION</u> - Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag</p>	
15	DSB102294	LOCAL ITEM	0000000500001 / GARBAGE BAG		300 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION</u> - Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag <u>GENERAL SPECIFICATION</u> - Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag	
16	DNM97788	3930523	2990795270101 / INJECTOR		6 / EACH/NUMBER	6CTAA8.3G7					TECHNICAL SPECIFICATION - INJECTOR GENERAL SPECIFICATION - INJECTOR	
17	DSB102185	LW-PM-14-3KVTX/ LW-PM-14-VTX (LOCAL)	5310705251577 / lock washer dn14 (LOCAL)		1014 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm GENERAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm	
18	DSB102295	AV19990970045	0870131703439 / Aluminum Filter Metal AL-Mg 4.5 M		56 / KILOGRAMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 GENERAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183	
19	DSB102595	AV19990970045	0870131703439 / Aluminum Filter Metal AL-Mg 4.5 M		50 / KILOGRAMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 GENERAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183	
20	DNQ96249	CEN1000063C	5510FT1019832 / Wooden Plug 250 x 70 x 20 mm	Portable Firefighting and Damage Control Equipment System	150 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
21	DNQ100	NIL	512099787684	FIRE	1 /	NO DATA		UK	UK		TECHNICAL SPECIFICATION --	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	686		8 / HAMMER 910G (2LB) BALL PEIN	FIGHTING	EACH/NUMBER	AVAILABLE					<u>GENERAL SPECIFICATION --</u>	
22	DSB92943	102834	341572516667 7 / Flap Grinding Disk		25 / EACH/NUMBER	EN13743					<u>TECHNICAL SPECIFICATION -</u> • OEM Rhodius Germany • Model No. EN13743 • Size 180x22.23 • Outer dia 180 mm • Inner hole dia 22.23 mm • Packing details (enclosed) , expiry date of Flap Grinding Disk is not mandatory. <u>GENERAL SPECIFICATION -</u> • OEM Rhodius Germany • Model No. EN13743 • Size 180x22.23 • Outer dia 180 mm • Inner hole dia 22.23 mm • Packing details (enclosed) , expiry date of Flap Grinding Disk is not mandatory.	
23	DNH98179	NIL, LOCAL	732070516360 7 / ELECTRIC ROTI PLANT 1000 CHAPATI /HRS	ROTI PLANT	1 / EACH/NUMBER	Automatic Electric Roti Plant		M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN GUJRANWALA.	M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN GUJRAN		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
24	DNQ100685		027359910422 7 / CHISEL FIRMER TANG TYPE OVERALL LG 6-1/2IN 137/226		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
25	DNQ100689	BS1102	472099534339 0 / HOSE, RUBBER	PUMP PORTABLE	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
26	DNQ99403	RADTARGE-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		10 / EACH/NUMBER	RADTARGE-H					<u>TECHNICAL SPECIFICATION -</u> electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting <u>GENERAL SPECIFICATION -</u> electronics	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig	
27	DNQ99013	RADTARG E-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		2 / EACH/NUMBER	RADTAR GE-H					<p><u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig</p> <p><u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig</p>	
28	DNQ100459	RADTARG E-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		2 / EACH/NUMBER	RADTAR GE-H					<p><u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig</p> <p><u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig</p>	
29	DRG98998	ZO6567888	2610ZO656788 8 / TYRE WITH TUBE FRONT SIZE 6.50-10.10PR		3 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION</u> - BRAND:BRIDGESTONE,SIZE 6.50-10 10PR,U LUG TYPE MADE JAPAN OR INDONESIA. <u>GENERAL SPECIFICATION</u> - BRAND: BRIDGESTONE,SIZE 6.50-10 10PR, U LUG TYPE MADE JAPAN OR INDONESIA.</p>	
30	DRG987	ZO654793	2915ZO654793		1 /	NO DATA					<u>TECHNICAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	44	2	2 / REGULATOR HIGH PRESSURE		EACH/N UMBER	AVAILAB LE					S2500 GP SINGLE STAGE REG FOR OXY/INERT GAS SVCE EAX INLET PRESS:300BAR/4350PSI, OUTLET PRESS:172BAROR 2500 PSI GENERAL SPECIFICATION - S2500 GP SINGLE STAGE REG FOR OXY/INERT GAS SVCE EAX INLET PRESS:300BAR/4350PSI, OUTLET PRESS:172BAROR 2500 PSI	
31	DNM991 48	5P-7277	662501594433 1 / VOLTAGE TESTER		2 / EACH/N UMBER	DE-660EO CATERPILLAR GENERATOR C18 600 KVA /480KW					TECHNICAL SPECIFICATION - 6v - 24v dc hardened steel tip cable length: 1-1.5 meters high temperature oil resistant GENERAL SPECIFICATION - 6v - 24v dc hardened steel tip cable length: 1-1.5 meters high temperature oil resistant	
32	DRG991 87	59428	2610ZO656704 5 / TYRE WITH TUBE (10.00 X20 16PR - NHS-WATTS-14"WIDTH)		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - HPT INDUSTRIAL PNEUMATICS TYRES (HEAVY DUTY BEAD TOBEAD CROSS PLY CONSTRUCTION)PLY 16, TREAD PATTERN "J", WT: 80KG, DIMENSION RIM SECTION: 7.50 TO 8.00, INFLATION PRESSURE:9 BAR(+/-15%) WATTS BRAND UK/EU GENERAL SPECIFICATION - HPT INDUSTRIAL PNEUMATICS TYRES (HEAVY DUTY BEAD TOBEAD CROSS PLY CONSTRUCTION)PLY 16, TREAD PATTERN "J", WT: 80KG, DIMENSION RIM SECTION: 7.50 TO 8.00, INFLATION PRESSURE:9 BAR(+/-15%) WATTS BRAND UK/EU	
33	DRG100 520	TRI CYCLE	2340ZO656952 9 / TRI CYCLE		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. Overall dimensions of tricycle to be as per drawing. 2. Steel frame of welded tubing. 3. Wooden frame mounted on rear axle behind seat for loading of items. 4. Rear axle to be supported on shock absorbers (coil or leaf springs). 5. Internal side of Wooden frame to be lined with 1 inch	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>soft rubber padding. 6. Chain length of approximately 9 ft 2 inches 7. Tricycle to be delivered in yellow paint scheme (minimum 2 coats). 8. Rear tires to be heavy duty used on motorcycles (CG125) Part No 42701-KCS- 65K or equivalent. 9. Tricycle to be provided with following set of standard spares: a. 1 x seat b. 1 x chain c. 1 x set of Brake pads d. 2 x brake wires e. 1 x set of pedals f. 3 x air charging nozzles PHOTO COPY OF DRAWING HELD WITH TECH LIB MADE IN PAKISTAN <u>GENERAL SPECIFICATION</u> - 1. Overall dimensions of tricycle to be as per drawing. 2. Steel frame of welded tubing. 3. Wooden frame mounted on rear axle behind seat for loading of items. 4. Rear axle to be supported on shock absorbers (coil or leaf springs). 5. Internal side of Wooden frame to be lined with 1 inch soft rubber padding. 6. Chain length of approximately 9 ft 2 inches 7. Tricycle to be delivered in yellow paint scheme (minimum 2 coats). 8. Rear tires to be heavy duty used on motorcycles (CG125) Part No 42701-KCS- 65K or equivalent. 9. Tricycle to be provided with following set of standard spares: a. 1 x seat b. 1 x chain c. 1 x set of Brake pads d. 2 x brake wires e. 1 x set of pedals f. 3 x air charging nozzles PHOTO COPY OF DRAWING HELD WITH TECH LIB MADE IN PAKISTAN</p>	
34	DRG100 280	A5476VLP	2915ZO652752 5 / REGULATOR LP AIR		1 / EACH/ NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 &amp; 0-4000 PSI RANGE),TANAKA JAPAN GENERAL SPECIFICATION - AIR</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN	
35	DPK99257	15W40 (API CF-4/SG) /870234	9150SV1210006 / LUBE OIL CUMMINS VALVOLINE PREMIUM BLUE 7800 15W40	MAINE AND EMERGENCY GENSET	220 / LITER	CUMMINS VALVOLINE VI TOPFLITE	KH180429(BVO1, BVO2, BVO3, BVO4)	SHANGHAI VCLUBRICATING OIL CO, LTD.CHINA		CHEVRON MARINE	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
36	DPK101559	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/ADDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	123 / LITER	JAPAN		JAPAN		SHELL	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
37	DSB96648	GSM 1487 DET-7 (39679)	4730143059081 / PLANE FLANGE		33 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Material - Mild Steel b. Dia - DE 76.1 mm c. Testing Pressure - less and equal to 70 bars GENERAL SPECIFICATION - a. Material - Mild Steel b. Dia - DE 76.1mm c. Testing Pressure - less and equal to 70 bars	
38	DPK102960	HA5440	9150735164285 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	100 / GALLON	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW.seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858		TELEFLEX MARINE CANADA	TECHNICAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW.seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858 GENERAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V.1P6 FAX: 604-270-7172 WWW.seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	
39	DPK102952	L-AN68 GB443-89	9150705139825 / MACHINERY OIL	LADDER, FANGER DOOR, CABLE WI	15 / LITER	NO DATA AVAILABLE		UK		UK	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
40	DPC102767	CON-EDDC-1PP1-P30	8010705204660 / EZIKLEAN DE-GREASER, CARBON AND SURFACE CLEANER CO	KACRHER MACHINE	75 / LITER	1PP1	RM-110	HEAD OFFICE: NURISTAA @ BUILDING NO 85, BLOCK DD CCA, PHASE 4, DHA LAHORE PH: +92 322-388-888-2 www.nuristaa.com E-mail: sales@nuristaa.com	PAKISTAN		TECHNICAL SPECIFICATION - ITEM REQUIRED FOR all metal surfaces (ferrous and no ferrous) stainless steel surface brass and chrome surface, glass surface, marble ceramic, procelain, plastic and wooden floor, kitchen equipment, plastic, rubber and leather surface GENERAL SPECIFICATION - ITEM REQUIRED FOR all metal surfaces (ferrous and no ferrous) stainless steel surface brass and chrome surface, glass surface, marble ceramic, procelain, plastic and wooden floor, kitchen equipment, plastic, rubber and leather surface	
41	DPC102838	CC 2748M (5 liters packing) CC2750M (20 liters packing)	6810715229857 / ES Complete EG premix coolant	MAIN ENGINE	150 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS / FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
42	DPK102903	SAE 90 (80W90)	9150251145135 / ENGINE GEAR OIL SAE 90 (80W90) (03 Ltr to 18 Ltr PACKING)	YAMAHA OUTBOARD ENGINE	20 / LITER	NO DATA AVAILAB LE		US	SOCIETY OF AUTOMOTIVE ENGINEERS INC, COMMAN WEALTH DRIVE, WARREN DALE, USA., PSC: 15096, TEL#724-776-4841		TECHNICAL SPECIFICATION - SAE 90 (80W90) GENERAL SPECIFICATION - SAE 90 (80W90)	
43	DNQ100683	23/90538	4210997485226 / DISCHARGE HEAD ASSY	FIRE FIGHTING EQUIPMENT	50 / EACH/NUMBER	NO DATA AVAILAB LE		UK	UK ENGLAND		TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
44	DPC102573	INTERSHIELD 300	8010190035529 /	External Deck PNFT ENA301	30 / LITER	ENA301		"International Paint Pvt Ltd, STONEYGATE LANE,	International Paint		TECHNICAL SPECIFICATION - Technical Details included in Data	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		ENA301-ALUMINIO /ENA303	INTERSHIELD 300 (ALUMINIUM) (EPOXY COATING KIT)	UK				FELLING, GATESHEAD, UK. Ph:0191 4696111	Pvt Ltd, uk		SheetGENERAL SPECIFICATION - Technical Details included in Data Sheet	
45	DPK102904	OMALA 68	915027000185 7 / SHELL OMALA OIL S2 GX 68 (PACKING 209 LTR DRUM)	MTP 750DD HUB OIL	110 / LITER	NO DATA AVAILAB LE		OC	TURKEY		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
46	DPK102901	TEXAMATIC 1888 SAE DEXRON-III	915001487853 0 / STEERING LUB OIL (PETROL/DIESEL ENGINE MT VEHICLES) (01 ltrs packing)	MT VEHICLE	7 / BOTTLE			GENERAL MOTORS CORP 3044 W GRAND BLVD DETROIT MI UNITED STATES PSC: 48202-3091 TEL: 248-857-2576	GENERAL MOTORS CORP		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
47	DPC102805	NO DATA AVAILAB LE	047450000702 8 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		2 / BAG						TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0	
48	DPC99659	SPEC,DEF 1052 COLOURS TO BS 381C	044250910703 5 / PAINT FNHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/5 66DT210902		755 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DNQ101756	G4A1H012 1CMOD	024399531692 7 / FIRE HOSE DURALINE/GO MTEX I/D2	FOR FIRE FIGHTING EQUIPMENT	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - length: 40 feet (1+1m)/female couplingGENERAL SPECIFICATION - length: 40 feet (1+1m)/female	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH: 40 FEET (1+1M) /FEMALE COUPLING								coupling	
50	DNA100687	M10605	4730997914568 / CLAMP HOSE		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
51	DNQ100681	11655778/SL60CP12	5120999105966 / SPANNER OPENJAW ADJ 12IN 1-1/4 A/F TYPE (CRESCENT) 31.75 MM		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
52	DPC102539	NO DATA AVAILABLE	6840705057111 / INSECTICIDE K-OTHRINE ec 15 (01 LITER PACKING) (OEM M/S Bayer Environmental Sciences)	TO CONTROL INSECT PASTS COCKROACHES BUGS	20 / LITER						TECHNICAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label. GENERAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.	
53	DPC102574	BS 2451, DEFSTAN: 80-73/1 OF 1977	8010701004136 / PAINT NON SLIPING PREMIXED (LIGHT GREY) BS2451, DEFSTAN 80-73/1	FINISHING NON SLIP	457 / LITER						TECHNICAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0mm Thickness Level = 2.0mm to 3.0 mm GENERAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0 mm Thickness Level = 2.0mm to 3.0 mm	
54	DPC102869	COMP A = 430-101-04	8010PK5064838 / PERMOBEL EPOXY FINISH (COMPONENT A-SILVER-GREY-430-101-04) (04 Liter Packing)		5 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DPC102882	850-761-04	8010PK5064841 / EPOXY THINNER 850-		140 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			761-04 (04 Liter Packing)								AVAILABLE	
56	DPC102732	NO DATA AVAILABLE	8010705098453 / SPRAY PAINT TIN (BOSNY no 39 black + BOSNY no 40 White) (300 GM bottle each)	PRESSURE GAUGES FOR REPAIR/CALIBRATION	60 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DPC102761	NO DATA AVAILABLE	8010705112537 / SOLIGNUM WOOD LACOUER	FOR WOOD WORK	10 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DPC102544	NO DATA AVAILABLE	6850785031104 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMENT FOR PNS NASR	409 / EACH/NUMBER						TECHNICAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. GENERAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
59	DPC102834	KUA752/ KUA759	8010785265948 / intergard 7500 aluminium		160 / LITER	INTERGARD7500 ALUMINIUM					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
60	DPC102794	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		400 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. <u>GENERAL SPECIFICATION</u> - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
61	DNQ100606	RADTARG E-H	666578527404 1 / HIGH SENSITIVE PERSONAL DOSIMETER		2 / EACH/NUMBER	RADTAR GE-H					<u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumolative dose graph data log and export user device, management tresh hold time settig <u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumolative dose graph data log and export user device, management tresh hold time settig	
62	DPK102891	GB11120-2011 ISO VG 32	9140FP001002 1 / ISO VG 32 GB11120-2011 TURBINE OIL		2 / LITER	GB11120-2011					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
63	DSB77552	06-0298	2815TY671994 5 / SLEAVE		6 / EACH/NUMBER	P30/43-130					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
64	DPK102990	EP 0	915073523263 7 / MOBILUX EP 0		240 / KILOGRAMME	EP 0					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
65	DPC102778	RELAY+on	8010705332823 / VIRKON SURFACE DISINFECTANT POWDER		50 / LITER	ZEEPER-114					TECHNICAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal GENERAL SPECIFICATION - High level surface disinfectant Verucidal Bactericidal Fungicidal	
66	DPC102797	A020EEV2	8010705332825 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		600 / LITER	HIGHLY PERFUMED					TECHNICAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation. GENERAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.	
67	DSB96707	GSM 1487 DET-7 (39679)	473014305908 1 / PLANE FLANGE		24 / EACH/ NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - a. Material - Mild Steel b. Dia - DE 76.1 mm c. Testing Pressure - less and equal to 70 bars GENERAL SPECIFICATION - a. Material - Mild Steel b. Dia - DE 76.1mm c. Testing Pressure - less and equal to 70 bars	
68	DPC102546	N/A	793070518128 0 / DETERGENT WATER SOLUBLE	GENERAL ITEM	90 / LITER			LOCKEL MARKET		GENERAL ITEM	TECHNICAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE GENERAL SPECIFICATION - TRANSPARENT 20M ROLL 1.8M WIDE	
69	DSB82183	CDCNPL4 7899/ MAT128- 0004F8/ (LOCAL) TR090RH- SEW	533014356877 8 / SEAL PLAIN FSP(JNB) (MESMA) TEFLON, S/STEEL & O- RING		15 / EACH/ NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Make: NG France, Item locally available through M/s Star Engineering Specification: Item is combination of Teflon Seal, Rubberized O-ring & Metallic piece. Material inspection: Material inspection criteria not held Acceptance Criteria: Item can be accepted upon physical inspection GENERAL SPECIFICATION - Make: NG France, Item locally available through M/s Star Engineering Specification: Item is combination of Teflon Seal, Rubberized O-ring & Metallic piece. Material inspection: Material inspection criteria not held Acceptance Criteria: Item can be accepted upon physical inspection	
70	DSA94013	local df-gf- 747-m84- vtx	433070524322 1 / FILTER DEMINEALiz ar ,(CHEMICAL RESIN: UPWM84. PRESSURE: 100 PSI MATERIAL: POLYETHYLE		1 / EACH/ NUMBER	no data available					TECHNICAL SPECIFICATION - ACCESSORIES DETAIL: A. 02 X FLEXIBLE PIPE, B. 04 X JUBLEE CLAMPS, C. 01 X VENT RISER ON THE TOP OF CAP, D. 02 X NIPPLES GENERAL SPECIFICATION - ACCESSORIES DETAIL: A. 02 X FLEXIBLE PIPE, B. 04 X JUBLEE CLAMPS, C. 01 X VENT RISER ON THE TOP OF CAP,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NE (COATED WITH GLASS FIBRE), WITH ACCESSORIES,								D. 02 X NIPPLES	
71	DSB101546	ITD/2232987-ITD-VTX	295054534501 2 / Pin		1 / EACH/NUMBER	MAIN ENGINE					<p><b>TECHNICAL SPECIFICATION</b> - This Pin is a precision-machined fastener featuring threaded end on one side for secure installation. The opposite end includes a slotted (minus-type) drive head, allowing easy tightening or removal with a flat-head screwdriver. Designed for reliable positioning and fastening in mechanical assemblies. <b>GENERAL SPECIFICATION</b> - This Pin is a precision-machined fastener featuring threaded end on one side for secure installation. The opposite end includes a slotted (minus-type) drive head, allowing easy tightening or removal with a flat-head screwdriver. Designed for reliable positioning and fastening in mechanical assemblies.</p>	
72	SRP100646	NT80	5970ZO655358 3 / ADHESIVE CEMENTEX GRADE NT80 WEIGHT 3KG/TIN Z		10 / TIN	NO DATA AVAILABLE					<p><b>TECHNICAL SPECIFICATION</b> - REQD IN OEM PACKING. <b>GENERAL SPECIFICATION</b> - REQD IN OEM PACKING.</p>	
73	DSB95906	JZ-600N	494078531634 2 / HI-SPEED ARC SPRAYING MACHINE		1 / EACH/NUMBER	JZ-600N					<p><b>TECHNICAL SPECIFICATION</b> - 1. Input Current: 3-Phase AC 380V , 50HZ 2. Rated Input Current: 32.6 KVA 3. Rated Current: 600A 4. Output No-Load Voltage: 21-45V 5. Load Rate: 80% 6. Voltage Regulation Level: 9 gears in total 7. Over all Dimensions: 750 x 600 x1010 8. Weight: 210 Kg 9. Insulation Level: <b>GENERAL SPECIFICATION</b> - 1. Input Current: 3-Phase AC 380V , 50HZ 2. Rated Input Current: 32.6 KVA 3. Rated Current: 600A 4. Out</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Put No-Load Voltage: 21-45V 5. Load Rate: 80% 6. Voltage Regulation Level: 9 gears in total 7. Over all Dimensions: 750 x 600 x1010 8. Weight: 210 Kg 9. Insulation Level: E	
74	DSB100894	906-2-21-15	934014367290 1 / FENETRE, OBSERVATION		6 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
75	DSB93932	732	451014215973 2 / POMME-DE-DOUCHE-DE-80		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Stainless Steel used in bathroom Dimension Dia= 90mm GENERAL SPECIFICATION - Stainless Steel used in bathroom Dimension Dia= 90mm	
76	DGB97674		473070534454 2 / ELBOW 45*G.I. 2-1/2"		30 / EACH/NUMBER	01					TECHNICAL SPECIFICATION - ELBOW 45*G.I. 2-1/2" ELBOW 2 1/2" 45° MATERIAL G.I. GENERAL SPECIFICATION - ELBOW 45*G.I. 2-1/2" ELBOW 2 1/2" 45° MATERIAL G.I	
77	DSB95699	LW-7235596-VTX /L23350-80CA	531014209559 6 / WASHER KEY/RONDELL E FREIN PLA 8 Z3CN18-10		87 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - PRESSURE TESTING / PHYSICALLY CHECK GENERAL SPECIFICATION - PRESSURE TESTING / PHYSICALLY CHECK	
78	DSB97945	EMBM4PS-D1-SEW	593570517462 1 / EMBASE 4PIN MALE		5 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
79	DSA95674	CUASB-HYD-8412-VTX/220573 / R93920B024	533014229841 2 / JOINT METALLO FERME 24,2 X32X2		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: 24.2 X 32 X 2 MATERIAL: COPPER GENERAL SPECIFICATION - SIZE: 24.2 X 32 X 2 MATERIAL: COPPER	
80	DSB97877		933050671408 7 / FORMICA GREEN WITH WHITE FACE SIZE 1000X600MMX 2		4 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
81	DSA97319	H-SNL	451070523252 2 / DRAIN		6 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Brass, Aluminum Bronze GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COLLECTOR COMPLETE SET STAINER NUT/BOLT/SCREW		UMBER	LE					SPECIFICATION - Brass, Aluminum Bronze	
82	DSB97940	DCPF4P-B1-SEW	593570383862 5 / DETTCH CABLE PLUG 4 PIN FEMALE		5 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
83	DSA99336	LOCAL Q1-52-10X100	531074524019 7 / RACCORD DROIT (GREASING NUT UNION)		100 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - MARINE STANDARD ALUMINUM BRONZE SET: 03 X PIECES FERRULE LENGTH: 10MM NUT LENGTH: 16MM (14X1.5) PRESSURE: 200 BAR GENERAL SPECIFICATION - MARINE STANDARD ALUMINUM BRONZE SET: 03 X PIECES FERRULE LENGTH: 10MM NUT LENGTH: 16MM (14X1.5) PRESSURE: 200 BAR	
84	DRG100284	111-523	4720ZO653683 8 / PIPE HP AIR		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - OUTER DIA-1",LENGTH-10 MTR, PIPE RUBBER WITH WIRE MESH (TO WITH STAND)(PRESSURE UPTO 5000 PSI) HP AIR TESTED ONE PIECE OF 10 METER LENGTH BOTH ENDS FEMALE. GENERAL SPECIFICATION - OUTER DIA-1", LENGTH-10 MTR,PIPE RUBBER WITH WIRE MESH(TO WITH STAND)(PRESSURE UPTO 5000 PSI) HP AIR TESTED ONE PIECE OF 10 METER LENGTH BOTH ENDS FEMALE.	
85	DSA101160	CH 25601	666512145416 4 / MANOXYDE-CARBONE-SC-CH25601		10 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LE GENERAL SPECIFICATION - NO DATA AVAILAB LE	
86	DSB93933	GSM131-02DETAB	597514242598 4 / CAPUCHON DE PROTECTION		20 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Rubber material used in NFOT DIMENSION: L=150mm, Outer Dia = 60mm, Inner Hole Dia = 30mm GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Rubber material used in NFOT DIMENSION: L=150mm, Outer Dia = 60mm, Inner Hole Dia = 30mm	
87	DRG100 349	A5476VLP	2915ZO652752 5 / REGULATOR LP AIR		1 / EACH/ UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN GENERAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN	
88	DRG100 068	A5476VLP	2915ZO652752 5 / REGULATOR LP AIR		1 / EACH/ UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN GENERAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN	
89	DGB976 73	R.Tee G.I. 2-1/2*1-1/2	451070534454 1 / UNEQUALØ TEE EQUAL 2 1/2" x Ø 2 1/2" x 1 1/2"		40 / EACH/ UMBER	01					TECHNICAL SPECIFICATION - UNEQUALØ TEE EQUAL 2 1/2" X Ø 2 1/2" X 1 1/2" material G1GENERAL SPECIFICATION - UNEQUALØ TEE EQUAL 2 1/2" X Ø 2 1/2" X 1 1/2" material G1	
90	DSB9992 6	ORB- SSVOU/00 /V1/23/369 8	596370531207 9 / CONTROL PANEL BOX		2 / EACH/ UMBER	Oval500					TECHNICAL SPECIFICATION - Input: 24VDC Output: 115VAC Dimension: 250mmx250mmx1 50mm (LxWxD)GENERAL SPECIFICATION - Input: 24VDC Output: 115VAC Dimension: 250mmx250mmx1 50mm (LxWxD)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
91	DSA95668	RVS-HYD-249-VTX/41214 / 41214A	4820142272429 / CLAPET MONTE SPECIAL 41214		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SIZE: 27 X 14.5 MAGNET STEEL RUBBER GENERAL SPECIFICATION - SIZE: 27 X 14.5 MAGNET STEEL RUBBER	
92	DSB98554	ITD/22320 16-ITD-VTX	299054534496 1 / Screw M16x55x40		4 / EACH/NUMBER	MAIN ENGINE					TECHNICAL SPECIFICATION - The Allen bolt is a high-strength fastener featuring a hexagonal socket head designed for tightening with an Allen (hex) key. It provides secure fastening in compact spaces and is commonly used in machinery, engines, and precision assemblies for reliable, vibration-resistant performance. GENERAL SPECIFICATION - The Allen bolt is a high-strength fastener featuring a hexagonal socket head designed for tightening with an Allen (hex) key. It provides secure fastening in compact spaces and is commonly used in machinery, engines, and precision assemblies for reliable, vibration-resistant performance.	
93	DSA97318	10-1600	451014303944 4 / MELANG MONOTRO LAVAB 10-1		5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Stainless Steel GENERAL SPECIFICATION - Stainless Steel	
94	DSB102914	LW-PM-14-3KVTX/ LW-PM-14-VTX (LOCAL)	531070525157 7 / lock washer dn14 (LOCAL)		300 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm GENERAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm	
95	DSB101579	LW-PM-14-3KVTX/ LW-PM-14-VTX (LOCAL)	531070525157 7 / lock washer dn14 (LOCAL)		204 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm GENERAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
96	DSB102485	AV19990970045	0870131703439 / Aluminum Filter Metal AL-Mg 4.5 M		56 / KILOGRAMME	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183</p> <p><u>GENERAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183</p>	
97	DSB102915	AV19990970045	0870131703439 / Aluminum Filter Metal AL-Mg 4.5 M		20 / KILOGRAMME	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183</p> <p><u>GENERAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183</p>	
98	DSB96733	AV19990970045	0870131703439 / Aluminum Filter Metal AL-Mg 4.5 M		7 / KILOGRAMME	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183</p> <p><u>GENERAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183</p>	
99	DSA97322	H-SNC	4510705232521 / DRAIN COLLECTOR COMPLETE SET STRAINER NUT/BOLT/SCREW		10 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> Brass, Aluminum Bronze</p> <p><u>GENERAL SPECIFICATION -</u> Brass, Aluminum Bronze</p>	
100	DSB94221	GSM131-02DETA	5975142425983 / CAPUCHON MANCHETTE TYPE A		20 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> Rubber material used in NFOT DIMENSION: L=125mm, Outer Dia = 60mm, Inner Hole Dia = 30mm</p> <p><u>GENERAL SPECIFICATION -</u> Rubber material used in NFOT DIMENSION: L=125mm, Outer Dia = 60mm, Inner Hole Dia = 30mm</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
101	DRG100072	4720ZO6555500	4720ZO6555500 / PIPE HIGH PRESSURE		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - EACH PIPE LENGTH 25 FEET WITH FEMALE FITTING ON BOTH END TESTED ON 5000PSI PIPE OF HIGH TENSION MATERIAL RUBBER, USED FOR CHARGING NITROGEN IN A/C TYRES.OD:15.6 MM. GENERAL SPECIFICATION - EACH PIPE LENGTH 25 FEET WITH FEMALE FITTING ON BOTH END TESTED ON 5000PSI PIPE OF HIGH TENSION MATERIAL RUBBER, USED FOR CHARGING NITROGEN IN A/C TYRES.OD:15.6 MM.	
102	DRG100279	4720ZO6555500	4720ZO6555500 / PIPE HIGH PRESSURE		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - EACH PIPE LENGTH 25 FEET WITH FEMALE FITTING ON BOTH END TESTED ON 5000PSI PIPE OF HIGH TENSION MATERIAL RUBBER, USED FOR CHARGING NITROGEN IN A/C TYRES.OD:15.6 MM. GENERAL SPECIFICATION - EACH PIPE LENGTH 25 FEET WITH FEMALE FITTING ON BOTH END TESTED ON 5000PSI PIPE OF HIGH TENSION MATERIAL RUBBER, USED FOR CHARGING NITROGEN IN A/C TYRES.OD:15.6 MM.	
103	DSA97326	GSM131-02DETA0	5975142425987 / CAPUCHON MANCHETTE TYPE AO		29 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - RubberGENERAL SPECIFICATION - Rubber	
104	DNM99661	9L8925	5306011651934 / BOLT (5/16-8 X 1.25 INCH)	MAIN ENGINE	14 / EACH/NUMBER	C-18 ACERT	T2P01491	CATERPILLAR USA	CATERPI LLAR		TECHNICAL SPECIFICATION - CATTER PILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189GENERAL SPECIFICATION - CATTER PILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189	
105	DNM996 42	9L-6647	303014563534 2 / V BELT	MAIN ENGINE C-18 ACERT T2P1UP USA	1 / EACH/N UMBER	C-18 ACERT T2P1UP	1	3701 STATE ROAD 20 BAST TOWN ALFA VETTE,IN POST CODE 47905 USA	CATERPI LLER USA		<u>TECHNICAL SPECIFICATION - C-18 ACERT I - section temp -30 to +100c wrapped /cogged</u> <u>GENERAL SPECIFICATION - C-18 ACERT I - section temp -30 to +100c wrapped /cogged</u>	
106	DNQ953 08	0244- 244005	534099525196 5 / INDICATOR TEST PLUG TYPE B	FIRE FIGHTING EQUIPMENT	4 / EACH/N UMBER	NO DATA AVAILAB LE		UK	UK ENGLAN D		<u>TECHNICAL SPECIFICATION - threaded test /indicator pug mpt or bsp tapered hex or square drive steel or brass Elastomer or tapered metal lock feature type b</u> <u>GENERAL SPECIFICATION - threaded test /indicator pug mpt or bsp tapered hex or square drive steel or brass Elastomer or tapered metal lock feature type b</u>	
107	DNM986 30	0140-3840	294071505184 8 / AIR FILTER	C55 D5 (4BT 3.3 G2) SERIAL NO. 68048207	1 / EACH/N UMBER	C55 D5					<u>TECHNICAL SPECIFICATION - OEM: CUMMINS POWER GENERATION SYSTEM UPDATED VIDE GMT ORMARA LETTER GNT/YSD/5285 DATED 03 FEB 14</u> <u>GENERAL SPECIFICATION - OEM: CUMMINS POWER GENERATION SYSTEM UPDATED VIDE GMT ORMARA LETTER GNT/YSD/5285 DATED 03 FEB 14</u>	
108	DNM995 30	150/68194 11	432072509001 1 / DRIVING SPINDLE	CARGO FUEL OIL PUMP GERMANY	3 / EACH/N UMBER	LEISTERI TZ 2008					<u>TECHNICAL SPECIFICATION - MMODEL NO LEISTERITZ 2008 TYPE L2NG 070/096 SCREW PUMP LEISTREZ PUMPEN GMBH DRIVING SPINDLE SCR W PUMP / TWIN /TRIPLE SCREW) TORQUE SCREW ELEMENT HIGH GRADE ALLOY STEEL PERSISION GROUND CASE HARDENED ANTI WEAR A/ ANTI CORROSION HELICAL OR STRAIGHT SHAFT</u> <u>GENERAL SPECIFICATION - MMODEL NO LEISTERITZ 2008 TYPE L2NG 070/096 SCREW PUMP LEISTREZ PUMPEN GMBH DRIVING SPINDLE SCR W PUMP /</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											TWIN /TRIPLE SCREW) TORQUE SCREW ELEMENT HIGH GRADE ALLOY STEEL PERSISION GROUND CASE HARDENED ANTI WEAR A/ ANTI CORROSION HELICAL OR STRAIGHT SHAFT	
109	DSB101398	4011890052334	5130725155229 / FLAP GRINDING DISK (SIZE 125 X 22.23 MM)		20 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Size: 125 X 22.23MM 3 YEARS FROM DATE OF MANUFACTURE oem/made: RHODIUS GERMANY Acceptance Criteria: Concerned rep will inspect and practically test in workshop. GENERAL SPECIFICATION - Size: 125 X 22.23 MM 3 YEARS FROM DATE OF MANUFACTURE oem/made: RHODIUS GERMANY Acceptance Criteria: Concerned rep will inspect and practically test in workshop.	
110	DNQ100849	NO DATA AVAILAB LE	5120999105866 / SCREW DRIVER CROSS HEAD LENGTH9.51N WOOD HANDLE BLAD61NCQ111	TOOLS FOR ELECT EQUIPMENT NASR	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB LEGENERAL SPECIFICATION - NO DATA AVAILAB LE	
111	DNQ100965	NO DATA AVAILAB LE	5120999105866 / SCREW DRIVER CROSS HEAD LENGTH9.51N WOOD HANDLE BLAD61NCQ111	TOOLS FOR ELECT EQUIPMENT NASR	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB LEGENERAL SPECIFICATION - NO DATA AVAILAB LE	
112	DNQ98544	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB LEGENERAL SPECIFICATION - NO DATA AVAILAB LE	
113	DPC99531	NO DATA AVAILAB LE	0474500000062 / POWDER CHALK, COMP CALCIUM		30 / KILOGRAMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB LEGENERAL SPECIFICATION - NO DATA AVAILAB LE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			CARBONATE 98% PURITY									
114	DRG999 92	SA10929 (287548)	294001484134 4 / AIR CLEANER ELEMENT HOBERT GPU		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - AS PER PUBLICATION GENERAL SPECIFICATION - AS PER PUBLICATION	
115	DNQ100 822	DGS1165	401099543413 7 / WIRE STEEL G1 SZ DIA 2.7MM LG 200 MTR WT 158KG BREAKING STR	NBCD & DAMAGE CONTROL FIRE FIGHTING EQPT	2 / REEL						TECHNICAL SPECIFICATION - 200 MTR LENGTH GENERAL SPECIFICATION - 200 MTR LENGTH	
116	DPK1007 87	ZIC ATF 3	915073522136 9 / ZIC ATF 3 DEXRON SYNTHETIC TRANSMISSION FLUID	TILT & TRIM ASSEMBLY	30 / LITER	ZIC ATF 3	NIL	SK LUBRICANTS 26, JONG-RO-JONGNO-GU, SEOUL, KOREA www.skzic.com Made in Korea	SK LUBRICANTS		TECHNICAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly) GENERAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly)	
117	DNM100 384	274-4491	530501564526 7 / SCREW	MAIN ENGINE	12 / EACH/NUMBER	C-18 ACERT T2P1UP	T2P01436	3701 TATE ROAD 20 BAST TOWN ALFA VETTEIN POST CODE 47905 USA	CATTERPILLER		TECHNICAL SPECIFICATION - FITTED IN ROCKER ARM ASSEMBLY GENERAL SPECIFICATION - FITTED IN ROCKER ARM ASSEMBLY	
118	DNM100 384	274-4491	530501564526 7 / SCREW	MAIN ENGINE	12 / EACH/NUMBER	C-18 ACERT T2P1UP	T2P01436	3701 TATE ROAD 20 BAST TOWN ALFA VETTEIN POST CODE 47905 USA	CATTERPILLER		TECHNICAL SPECIFICATION - FITTED IN ROCKER ARM ASSEMBLY GENERAL SPECIFICATION - FITTED IN ROCKER ARM ASSEMBLY	
119	DPC102 142	CC 2748M (5 liters packing) CC2750M (20 liters packing)	681071522985 7 / ES Complete EG premix coolant	MAIN ENGINE	260 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTERS	CUMMINS / FLEETGUARD		TECHNICAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol GENERAL SPECIFICATION - Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
120	DPC102 100		047350224770 1 / GUM ACACIA TECHNICAL		20 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
121	DPC102107		0473504730004 / FLUXITE SOLDERING PASTE (ZINC CHLORIDE)		5 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DNM100401	167-4407	5331715270249 / SEAL O RING FOR F/W LINE		1 / EACH/NUMBER	DE-660EO CATERPILLAR GENERATOR C18 600 KVA /480KW					TECHNICAL SPECIFICATION - SEAL O RING FOR F/W LINE cross section 3.53mm id: 69.44mm 70a shore GENERAL SPECIFICATION - SEAL O RING FOR F/W LINE cross section 3.53mm id: 69.44mm 70a shore	
123	DNQ100652	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
124	DNQ100906	0264-264034 LOCALLY DEVELOPED	2090994633937 / SPLINTER BOX 350X350X125 MM		1 / EACH/NUMBER	LOCALLY DEVELOPED					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
125	DNQ100964	H6880	5120991365595 / SCREW DRIVER FLAT TIP LENGTH: 505 MM. BLADE LENGTH: 300 MM. TIP WIDTH:16 MM. MATERIAL HANDLE: WOOD.	FOR FIRE FIGHTING	7 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 2559 PART 1. GENERAL SPECIFICATION - BS 2559 PART 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MATERIAL BLADE: STEEL.									
126	DNQ100858	RANGE 120 TO 140MM (P/N 2201/0017	473099533297 3 / CLAMP HOSE WORM DRIVE STEEL ZINC PLTD WD 13MM THK 1MM 70/226	E16 MACHINERY SPACE DAMAGE CONTROL TOOLB	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DNM100005	2767476/3 89-7188/5749 895	281571524613 3 / KIT RING		6 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - piston ring kit (sets) one piston ring set (compression + oil control rings) GENERAL SPECIFICATION - piston ring kit (sets) one piston ring set (compression + oil control rings)	
128	DNQ100409	15199001	422079528948 9 / SOLAS SOFTPACK RFD (FIRST AID KIT) FOR LIFE RAFT - LIFE BOAT		1 / EACH/NUMBER	life raft					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
129	DNQ100456	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
130	DPK103015	FCW NMMA CERTIFIED	915076517954 6 / YAMALUBE/A DDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	120 / LITER	JAPAN		JAPAN		SHELL	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
131	DPK103012	6G8-11325-23	9150745234094 / Yamalube G14 Gear Oil Sae90 Tube		2 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - Yamalube G14 Gear Oil Sae90 Tube GENERAL SPECIFICATION - Yamalube G14 Gear Oil Sae90 Tube	
132	DNH102490	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
133	DNH103267	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	2 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
134	DNH103170	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	2 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
135	DNM102536	FF5488/3959612	4330015300044 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD	2 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s Cummins Inc		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
136	DNM102536	FF5488/3959612	4330015300044 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD	2 / EACH/NUMBER	QSB6.7-305MD	74126404	CUMMINS ENGINE COMPANY, INC PO BOX 3005 COLUMBUS IN 47202-9982	CUMMINS ENGINE COMPANY		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
137	DPK103082	Shell Gadus S2 V100 3/ Shell Alvania R3	9150PK5078117 / SHELL GADUS S2 V100 3/ SHELL GREASE Alvania R-3 (Old Name) (18 KG PKING)	50 LUBRICATING PAINTS (CONVERTORS)	18 / KILOGRAMME			M/S SHELL PAKISTAN Ltd	M/S SHELL PAKISTAN Ltd		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY:IMRAN OIL TRADERS 19-20,FATIMA GIRLS COLLEGE,NISHTAR ROAD, GARDEN WEST ,KARACHI: GENERAL SPECIFICATION - SOURCE OF AVAILABILITY:IMRAN OIL TRADERS 19-20,FATIMA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											GIRLS COLLEGE, NISHTAR ROAD, GARDEN WEST, KARACHI.	
138	DNM102654	10000-05563	5331795199017 / SEAL FRONT END OIL	PERKIN DG P200-3 UK	1 / EACH/NUMBER	P200-3	PR83167 R007362 A	F.G.WILSON (ENGINEERING) LTD CHURCH ROAD WHITE HOUSE NEWTOWNABBEY, BELFAST BT367LN NORTHERN IRELAND, UK		PERKIN UK	TECHNICAL SPECIFICATION - ITEM USED IN FUEL SYSTEM GENERAL SPECIFICATION - ITEM USED IN FUEL SYSTEM	
139	DPK103094	SHELL OMELA VISCOSITY-68	2590735165521 / HUB OIL	MJP	10 / LITER	MJP 750 SERIES		MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN		MJP OSTERBY	TECHNICAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN GENERAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	
140	DNQ102526	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	1 / ROLL	NO DATA AVAILABLE		UK		UK ENGLAND	TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
141	DNQ103185	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	1 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND		TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCR GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCR	
142	DNM102639	127-2176	533101477196 1 / SEAL- INTEGRAL	CATTER PILLER GENSET 3512B USA	12 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N. E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
143	DPK103097	0x-8	047570220234 8 / HYDRAULIC FLUID		459 / LITER						TECHNICAL SPECIFICATION - SAE J1704. DEFSTAN 01-005 ISSUE 20. GENERAL SPECIFICATION - SAE J1704. DEFSTAN 01-005 ISSUE 20.	
144	DPC101843	NO DATA AVAILABLE	044250442005 7 / PAINT FOR UNDER COAT (Light Grey)	VEHICLES	53 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DPC101890	NO DATA AVAILABLE	044250220238 1 / PAINT PRIMING GRAPHITE BASIS (RED LEAD)	BUXLY/ICI/BERGER/KOSAR GRP-E VIDE NHQ LT	300 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
146	DPC102634	NO DATA AVAILABLE	044350443000 5 / CYLINDER FOR COOKING		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. grade-1 i. a. w (dot 4wb hse). colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GAS (EMPTY) CAPACITY 45.40KG								<p>CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque. <u>GENERAL SPECIFICATION</u> - 1. grade-1 i. a. w (dot 4wb hse) colour: yellow need. 2.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Specification: DOT-4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
147	DPK103091	LG 280	047450910050 2 / GREASE LG-280 (XG-286)	FIVE /G SERVICE PUMP NO.3	839 / KILOGR AMME						TECHNICAL SPECIFICATION - SUPERCEDED VIDE CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128 GENERAL SPECIFICATION - SUPERCEDED VIDE CICP/NSD/5021 DT 23 OCT 09 AND DEFSTAN 01-5 ISSUE 16 PG305, 128	
148	DNM102529	QP407PA A	431076502189 8/ COMPRESSO R 2 TON BTU 24000 ROTARY 220V 50 HZT	A/C 02 TON WINDOW TYPE	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
149	DNQ102613		421079510135 3 / ED BA LOCKERS (EXTENSION LOCKER)	EDBA	8 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Required Materia - Stainless Steel Grade-316 (non-magnetic). b. Body Gauge - 12 gauge (Thickness = 2.656mm). c. Paint Coating - Painting not required. d. Lock Type - Keyless Spring Latch. SIZE/ DIMENSION IN INCHES: H 35 w 18.5 b 10 material: aluminum paint scheme: fluorescent red GENERAL SPECIFICATION - a. Required Materia - Stainless Steel Grade-316 (non-magnetic). b. Body Gauge - 12 gauge (Thickness = 2.656mm). c. Paint Coating - Painting not required. d. Lock Type - Keyless Spring Latch. SIZE/ DIMENSION IN INCHES: H 35 w 18.5 b 10 material: aluminum paint scheme: fluorescent red	
150	DNQ103160	PURIFIED LOCALLY DEVELOP ED	422079505518 8/ EMERGENCY PURIFIED DRINKING WATER CONTENT 500 ML (LIFE RAFT).	S/PACK USED IN 20MEN LIFE RAFT	276 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
151	DNH103008	NO DATA AVAILABLE	4110PK5073820 / WATER COOLER STORAGE TYPE CAPACITY 30 LITERS 220V .33HP	WATER COOLER STORAGE TYPE	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
152	DNH102487	AEL18E7-HF	4120009054238 / A/C 2 TON SPLIT BRAND GENERAL/LG/ PEL		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
153	DNH102486	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
154	DNH102989	NO DATA AVAILABLE	4130705058558 / WATER COOLER 40 litre STORAGE TYPE CAPACITY OF COMPRESSOR-1	USER SIM DIVISION PNS DOCKYARD	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
155	DNH103191	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
156	DNH103162		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	1 / EACH/NUMBER	WA60000514					TECHNICAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											W Cooling Power 100 W GENERAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W	
157	DNQ103173	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
158	DNQ103072	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
159	DNM102655	5610141310	6130725114669 / E/P CONVERTOR	SRP550 FP-SCHOTTLE SYS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
160	DNQ103189	0413-2183	5970999239663 / TAPE INSULATION ELECTRICAL	GENETAL USE	110 / EACH/NUMBER						TECHNICAL SPECIFICATION - Brand: OSAKA, NEETO . Packing details: 10-12 in each packing GENERAL SPECIFICATION - Brand: OSAKA, NEETO . Packing details: 10-12 in each packing	
161	DNQ102612	NO DATA AVAILABLE	0461500000280 / SAFETY GOGGLES WITH SUN GLASSES		76 / EACH/NUMBER						TECHNICAL SPECIFICATION - MAKE/ BRAND/ EQUIVALENT: CHINA Color: Black Lenses Material: Polycarbonate Frame Material: PVC/PC Scratch Resistance: Yes Fog Resistant: Yes Weight: 40-50 gm (approx) Built in side shields to provide An ever greater level of impact protection. Petersafe/any well reputed firm having import/export license. GENERAL SPECIFICATION - MAKE/ BRAND/ EQUIVALENT: CHINA Color: Black Lenses Material: Polycarbonate Frame Material: PVC/PC Scratch Resistance: Yes Fog Resistant: Yes Weight: 40-50 gm (approx) Built in side shields to provide An ever greater level of impact protection. Petersafe/any well reputed firm having import/export	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											license.	
162	DPC102949	HRC-407C (HFC-407C) GENETRON R-407C	6830705118136 / GAS FOR (A/C) R-407C (packing = 11.3 kg) (Purity level 99% Min)	A/C SPLIT (02TONS)	102.15 / KILOGRAMME						TECHNICAL SPECIFICATION - OEM: HONEYWELL (USA) GENERAL SPECIFICATION - OEM: HONEYWELL (USA)	
163	DPK103084	20W-50	9150PK5079480 / LUB OIL 20W50 PKG 4LTR ( FOR PETROL VEHICLES)	PETROL VEHICLES	738 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
164	DNH102790	NO DATA AVAILABLE	1308500530125 / REFRIG 12CUFT DOUBLE DR 220V(DLT. NSSD/HM/PAT T/467 DT. 121093)	12 CUF	1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
165	DNH103052	NO DATA AVAILABLE	1308750530106 / REFRIGERATOR 10.CU FT-220V AC (NO FROST)		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
166	DPK103025		9150FP0020002 / GREASE SHELL GADUS S2 V 100 2 (18 KG Packing)		30 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
167	DNQ103175	15199001	4220795289489 / SOLAS SOFTPACK RFD (FIRST AID KIT) FOR LIFE RAFT - LIFE BOAT		4 / EACH/NUMBER	life raft					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
168	DPK103242	B150SH (91511707)	9150725312306 / REFERIGERATION OIL FOR SCREW		60 / LITER	B150SH (91511707)					TECHNICAL SPECIFICATION - this refrigeration oil is type of synthetic lubricant use in refrigerant system. GENERAL SPECIFICATION - this refrigeration oil is type of synthetic	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COMPRESSOR								lubricant use in refrigerant system.	
169	DNM96754	2417090	5305735244810 / M8x25 8.8zn DIN 912 hexagon socket head screw		8 / EACH/NUMBER	CLASSIC V					TECHNICAL SPECIFICATION - M8X25 8.8ZN DIN 912 HEXAGON SOCKET HEAD SCREW GENERAL SPECIFICATION - M8X25 8.8ZN DIN 912 HEXAGON SOCKET HEAD SCREW	
170	DNM102643	135326206	2940994713392 / main air filter		5 / EACH/NUMBER	135326206					TECHNICAL SPECIFICATION - External Diameter: 146.3mm Internal Diameter: 77mm Length: 322mm WIDTH: 356 MM HEIGHT: 152 MM DEPTH: 152 MM WEIGHT: 0.86 KG GENERAL SPECIFICATION - External Diameter: 146.3mm Internal Diameter: 77mm Length: 322mm WIDTH: 356 MM HEIGHT: 152 MM DEPTH: 152 MM WEIGHT: 0.86 KG	
171	DNM102657	2485513	6685015330759 / REGULATOR	MAIN ENGINE	4 / EACH/NUMBER	C 18	T2P01336	3701 STATE ROAD 26 EAST TOWN LAFA IN POST CODE 47905	USA		TECHNICAL SPECIFICATION - REGULATOR CATERPILLAR C18 3701 STATE ROAD 26 EAST TOWN LAFA IN POST CODE 47905 GENERAL SPECIFICATION - REGULATOR CATERPILLAR C18 3701 STATE ROAD 26 EAST TOWN LAFA IN POST CODE 47905	