

Ref: SSGC/FP/14325-Corr1-add/2026  
Dated: June 15<sup>th</sup>, 2026

**CORRIGENDUM# 1 / ADDENDUM**

## **PRESSURE CONTROL VALVES**

**TENDER ENQUIRY# SSGC/FP/PT/14325**

Dear Sir,

This refers to the above mentioned tender enquiry & Letter Ref# SSGC/FP/14325-Clar2-Ext1/2026, dated: 11<sup>th</sup> June-2026. In this regard, it is requested to kindly amend to read the bid submission date as **“16-July-2026 at 1000 Hrs.”** instead of **“30-June-2026 at 1000 Hrs.”**.

Further, Please find enclosed **Additional Data Sheets of 2” & 6” Control Valves** for more clarity in addition to the existing (Section-4).

Therefore, kindly treat the enclosed Additional Data Sheets of 2” & 6” Control Valves as an integral part of the tender document & quote accordingly, please.

Please note that in case if the bid bond validity fall short of 150 days due to extension in bid submission date, the bidders are liable to extend the bid bond validity up to 150 days within 30 days of the opening of technical proposals.

**Important Note:** All prospective bidders who intend to submit bid against the subject tender enquiry and want to submit bid bond in shape of Bid Bond Guarantee, the format of Bid Bond Guarantee should be same as the format of Bid Bond given in the tender document else the bid will be liable for rejection.

All other terms & conditions will remain unchanged.

Inconvenience caused is highly regretted please.

  
For **General Manager (P)**

**DATA SHEET NO. DOC. 250425**

|           |   |  |               |
|-----------|---|--|---------------|
| <b>1.</b> | <b>Control Valve</b>  |  |               |
| 1.1       | Size  | 2 inch   |               |
| 1.2       | ANSI Rating:  | CLASS 600  |               |
| 1.3       | End Connection:   | RTJ  |               |
| 1.4       | Fluid   | Natural Gas  |               |
| 1.5       | Specific Gravity:   | 0.6 to 0.68  |               |
| 1.6       | Gas Temperature:  | 2 to 120°C   |               |
| 1.7       | Port size :   | 2 5/16 inch or above.  |               |
| 1.8       | Trim Type:  | Equal Percentage   |               |
|           | Trim Construction:  | Single Seated, Single Seated, Gauge Guided Balanced Plug Type.   |               |
| 1.9       | Flow Range:   |  |               |
| 1.9.1     | Case 1:   | Inlet Pressure   | 850-1050 Psig |
|           |   | Outlet Pressure  | 800-850 Psig  |
|           |   | Flow rate  | 10-15 MMSCFD  |
| 1.10      | <b>Material of Construction:</b>  |  |               |
| 1.10.1    | Trim (Plug, seat & seat Ring):  | Stainless Steel Type 316   |               |
| 1.10.2    | Stem:   | Stainless Steel Type 316   |               |
| 1.10.3    | Body:   | Cast Carbon Steel to ASTM A216 WCB   |               |
| <b>2.</b> | <b>Actuator</b>   |  |               |
| 2.1       | Type:   | Spring and Diaphragm Type.   |               |
| 2.2       | Bench Set :   | 6 to 30 psig.  |               |
| 2.3       | Fail action on loss of power gas:   | Pushdown to close  |               |
| 2.4       | Body Material:  | Cast Carbon Steel to ASTM A216 WCB   |               |
| 2.5       | Stem Packing Material:  | PTFE or Equivalent   |               |
| <b>3.</b> | <b>Pressure Controller</b>  |  |               |
| 3.1       | Type:   | Field Mounted Pneumatic Indicating Pressure Controller   |               |
| 3.2       | Scale Size:   | 100 mm minimum   |               |
| 3.3       | Scale visibility:   | Full Range   |               |
| 3.4       | Set Point:  | Manually adjustable over full range of scale   |               |
| 3.5       | Control Action :  | Proportional + Integral.   |               |
| 3.6       | Out put :   | 6 to 30 psig.  |               |
| 3.7       | Supply / Out put pressure gauge;  | 0 to 60 psig.  |               |
| 3.8       | Power Source for controller:  | Natural gas  |               |
| 3.9       | Manual Loader built - in  |  |               |
| 3.10      | Field Selectable for Direct / Reverse Action.   |  |               |
| 3.11      | Auto Manual Control Mode Selector Switch.   |  |               |
| 3.12      | Auto Manual Out put differential indicator for bump less transfer of control mode.  |  |               |
| 3.13      | All weather proof construction / IP 65.   |  |               |
| 3.14      | Ambient temperature 0 to 60 Deg C   |  |               |
| 3.15      | Instrument Air Supply System at 5-35 Psig complete with high pressure regulator & filter and low pressure regulator & filter. |  |               |
| 3.16      | Input signal Connection :   | ¼ inch NPTF Thread.  |               |
| 3.17      | Output signal Connection :  | ¼ inch NPTF Thread.  |               |
| 3.18      | Air supply Connection :   | ¼ inch NPTF Thread.  |               |
| 3.19      | Pressure Controller Mounting Accessories :  | Mounting bracket should be designed for mounting on 2 inch dia pipe. It contain 1No. Mounting Bracket, 2Nos. U-Bolt, 4Nos. Washers, 4Nos. Hex. Nuts, 4Nos. Hex. Head Screw, 4Nos. Round Head Screw. (All Accessories Material: SS 316) |               |
| 3.20      | Bourden tube range:   | 0-300 Psig   |               |
| 3.21      | Stainless Steel Bourdon Tube suitable for sweet gas use as instrument air.  |  |               |

12



|                               |   |   |                |
|-------------------------------|---|---|----------------|
| <b>1. Control Valve</b>       |   |   |                |
| 1.1                           | Size:   | 6 inch  |                |
| 1.2                           | ANSI Rating:  | CLASS 600   |                |
| 1.3                           | End Connection:   | F. B. RTJ   |                |
| 1.4                           | Fluid:  | Natural Gas   |                |
| 1.5                           | Specific Gravity:   | 0.6 and 0.6   |                |
| 1.6                           | Gas Temperature:  | 30 to 150 C   |                |
| 1.7                           | Port size :   | 6 inch or above   |                |
| 1.8                           | Trim Type:  | Whisper Trim or equal percentage (to be specified by the bidder)  |                |
| 1.9                           | Trim Construction :   | Single ported (single seated), Cage guided balanced Plug.   |                |
| 1.10                          | Flow Range:   |   |                |
| 1.10.1                        | Case 1:   | Inlet Pressure  | 1030-1050 Psig |
|                               |   | Outlet Pressure   | 1000-1025 Psig |
|                               |   | Flow rate   | 40-50 MMSCFD   |
| 1.11                          | <b>Material of Construction:</b>  |   |                |
| 1.11.1                        | Trim (Plug, seat & seat Ring):  | Stainless Steel Type 316  |                |
| 1.11.2                        | Stem:   | Stainless Steel Type 316  |                |
| 1.11.3                        | Body:   | Cast Carbon Steel to ASTM A216 WCB  |                |
| <b>2. Actuator</b>            |   |   |                |
| 2.1                           | Type:   | Spring and Diaphragm Type.  |                |
| 2.2                           | Bench Set :   | 6 to 30 psig.   |                |
| 2.3                           | Fail action on loss of power gas:   | Pushdown to close   |                |
| 2.4                           | Body Material:  | Cast Carbon Steel to ASTM A216 WCB  |                |
| 2.5                           | Stem Packing Material:  | PTFE or Equivalent  |                |
| <b>3. Pressure Controller</b> |   |   |                |
| 3.1                           | Type:   | Field Mounted Pneumatic Indicating Pressure Controller  |                |
| 3.2                           | Scale Size:   | 100 mm minimum  |                |
| 3.3                           | Scale visibility:   | Full Range  |                |
| 3.4                           | Set Point:  | Manually adjustable over full range of scale  |                |
| 3.5                           | Control Action :  | Proportional + Integral.  |                |
| 3.6                           | Out put :   | 6 to 30 psig.   |                |
| 3.7                           | Supply / Out put pressure gauge;  | 0 to 60 psig.   |                |
| 3.8                           | Power Source for controller:  | Natural gas   |                |
| 3.9                           | Manual Loader built – in  |   |                |
| 3.10                          | Field Selectable for Direct / Reverse Action.   |   |                |
| 3.11                          | Auto Manual Control Mode Selector Switch.   |   |                |
| 3.12                          | Auto Manual Out put differential indicator for bump less transfer of control mode.  |   |                |
| 3.13                          | Weather proof construction / IP 65.   |   |                |
| 3.14                          | Ambient temperature 0 to 60 Deg.C   |   |                |
| 3.15                          | Instrument Air Supply System at 5-35 Psig complete with high pressure regulator & filter and low pressure regulator & filter. |   |                |
| 3.16                          | Input signal Connection :   | ¼ inch NPTF Thread.   |                |
| 3.17                          | Output signal Connection :  | ¼ inch NPTF Thread.   |                |
| 3.18                          | Air supply Connection :   | ¼ inch NPTF Thread.   |                |
| 3.19                          | Pressure Controller Mounting Accessories:   | Mounting bracket should be designed for mounting on 2 inch dia pipe. It contain 1No.Mounting Bracket, 2Nos.U-Bolt, 4Nos. Washers, 4Nos. Hex. Nuts, 4Nos. Hex. Head Screw, 4Nos. Round Head Screw.(All Accessories Material: SS 316) |                |
| 3.20                          | Bourden tube range:   | 0 to 1500 psig  |                |
| 3.21                          | Stainless Steel Bourdon Tube and Bellows suitable for sweet gas use as instrument air.  |   |                |

R





Ref: SSGC/FP/PT/25-26-27-28-29-30-31-32-33-34-35-36-37-38-39-40-41-42-43-44-45-46-47-48-49-50-51-52-53-54-55-56-57-58-59-60-61-62-63-64-65-66-67-68-69-70-71-72-73-74-75-76-77-78-79-80-81-82-83-84-85-86-87-88-89-90-91-92-93-94-95-96-97-98-99-100-101-102-103-104-105-106-107-108-109-110-111-112-113-114-115-116-117-118-119-120-121-122-123-124-125-126-127-128-129-130-131-132-133-134-135-136-137-138-139-140-141-142-143-144-145-146-147-148-149-150-151-152-153-154-155-156-157-158-159-160-161-162-163-164-165-166-167-168-169-170-171-172-173-174-175-176-177-178-179-180-181-182-183-184-185-186-187-188-189-190-191-192-193-194-195-196-197-198-199-200-201-202-203-204-205-206-207-208-209-210-211-212-213-214-215-216-217-218-219-220-221-222-223-224-225-226-227-228-229-230-231-232-233-234-235-236-237-238-239-240-241-242-243-244-245-246-247-248-249-250-251-252-253-254-255-256-257-258-259-260-261-262-263-264-265-266-267-268-269-270-271-272-273-274-275-276-277-278-279-280-281-282-283-284-285-286-287-288-289-290-291-292-293-294-295-296-297-298-299-300-301-302-303-304-305-306-307-308-309-310-311-312-313-314-315-316-317-318-319-320-321-322-323-324-325-326-327-328-329-330-331-332-333-334-335-336-337-338-339-340-341-342-343-344-345-346-347-348-349-350-351-352-353-354-355-356-357-358-359-360-361-362-363-364-365-366-367-368-369-370-371-372-373-374-375-376-377-378-379-380-381-382-383-384-385-386-387-388-389-390-391-392-393-394-395-396-397-398-399-400-401-402-403-404-405-406-407-408-409-410-411-412-413-414-415-416-417-418-419-420-421-422-423-424-425-426-427-428-429-430-431-432-433-434-435-436-437-438-439-440-441-442-443-444-445-446-447-448-449-450-451-452-453-454-455-456-457-458-459-460-461-462-463-464-465-466-467-468-469-470-471-472-473-474-475-476-477-478-479-480-481-482-483-484-485-486-487-488-489-490-491-492-493-494-495-496-497-498-499-500-501-502-503-504-505-506-507-508-509-510-511-512-513-514-515-516-517-518-519-520-521-522-523-524-525-526-527-528-529-530-531-532-533-534-535-536-537-538-539-540-541-542-543-544-545-546-547-548-549-550-551-552-553-554-555-556-557-558-559-560-561-562-563-564-565-566-567-568-569-570-571-572-573-574-575-576-577-578-579-580-581-582-583-584-585-586-587-588-589-590-591-592-593-594-595-596-597-598-599-600-601-602-603-604-605-606-607-608-609-610-611-612-613-614-615-616-617-618-619-620-621-622-623-624-625-626-627-628-629-630-631-632-633-634-635-636-637-638-639-640-641-642-643-644-645-646-647-648-649-650-651-652-653-654-655-656-657-658-659-660-661-662-663-664-665-666-667-668-669-670-671-672-673-674-675-676-677-678-679-680-681-682-683-684-685-686-687-688-689-690-691-692-693-694-695-696-697-698-699-700-701-702-703-704-705-706-707-708-709-710-711-712-713-714-715-716-717-718-719-720-721-722-723-724-725-726-727-728-729-730-731-732-733-734-735-736-737-738-739-740-741-742-743-744-745-746-747-748-749-750-751-752-753-754-755-756-757-758-759-760-761-762-763-764-765-766-767-768-769-770-771-772-773-774-775-776-777-778-779-780-781-782-783-784-785-786-787-788-789-790-791-792-793-794-795-796-797-798-799-800-801-802-803-804-805-806-807-808-809-810-811-812-813-814-815-816-817-818-819-820-821-822-823-824-825-826-827-828-829-830-831-832-833-834-835-836-837-838-839-840-841-842-843-844-845-846-847-848-849-850-851-852-853-854-855-856-857-858-859-860-861-862-863-864-865-866-867-868-869-870-871-872-873-874-875-876-877-878-879-880-881-882-883-884-885-886-887-888-889-890-891-892-893-894-895-896-897-898-899-900-901-902-903-904-905-906-907-908-909-910-911-912-913-914-915-916-917-918-919-920-921-922-923-924-925-926-927-928-929-930-931-932-933-934-935-936-937-938-939-940-941-942-943-944-945-946-947-948-949-950-951-952-953-954-955-956-957-958-959-960-961-962-963-964-965-966-967-968-969-970-971-972-973-974-975-976-977-978-979-980-981-982-983-984-985-986-987-988-989-990-991-992-993-994-995-996-997-998-999-1000

CLARIFICATION# 2 / EXTENSION# 1

# PRESSURE CONTROL VALVES

TENDER ENQUIRY# SSGC/FP/PT/14325

Dear Sir,

This refers to the above mentioned tender enquiry, one of the prospective bidder has raised a query and the response to that query is being forwarded to all the prospective bidders to maintain the transparency.

| S.# | Bidder's Query  | SSGC's Response   |
|-----|---|---|
| 1   | I checked the specs but flow rate given 40-50 MMCFD seems not correct with given pressure also 10-15 MMCFD for 2" size seems incorrect. | Please see the SOR in the tender document, where the required flow rates and pressure data for the 6" CV and 2" CV are already specified. |

Further, the bid submission date of the subject tender enquiry has been extended up to "30-June-2026 at 1000 Hrs." instead of existing.

Please note that in case if the bid bond validity fall short of 150 days due to extension in bid submission date, the bidders are liable to extend the bid bond validity up to 150 days with the expiry of the opening of technical proposals.

**Important Note:** All prospective bidders who intend to submit bid against the subject tender enquiry and want to submit bid bond in shape of Bid Bond Guarantee, the format of Bid Bond Guarantee should be same as the format of Bid Bond given in the tender document else the bid will be liable for rejection.

All other terms & conditions will remain unchanged.

Inconvenience caused is highly regretted please.

  
\_\_\_\_\_  
For General Manager (P)

NOT FOR BIDDING PURPOSE

# PRESSURE CONTROL VALVES

FOB/C&F & FOR (Only for Local Manufacturers SRO 827(1)/2001)

*Bids are to be invited on Under Single Stage Two Envelope Bidding Procedure  
Under PPRA Rules 2004, Rule# 36 (b)*

TENDER ENQUIRY NO:  
SSGC / FP / PT / 14325

Bid Closing date & time: 15-06-2026 at 1000 Hrs.

Bid Opening date & time: 15-06-2026 at 1030 Hrs.

Fixed Bid Security, USD=75,000 OR PKR=218,000.

Note: Tender document is also available online on SSGC website for view only. Bidder is eligible to participate in bidding process only after purchasing the tender documents from Tender Room SSGC Head Office as per the procedure mentioned in the Press Publication / SSGC website.

It is mandatory for bidders to attach original Token Slip in front of the Sealed Envelope (used at the time of Purchasing) as an evidence that supplier has purchased the Tender documents. Further, any Corrigendum/Clarification/Addendum/Extensions issued to be notified to only those bidders who have purchased Tender documents.

#### Venue:

Tender Room, CRD Building, Ground Floor  
SSGC Head office complex Karachi -75300  
Ph.99021024 – 99021173 - 99021116.



## Sui Southern Gas Company Limited

Procurement Department, 2<sup>nd</sup> Floor, SI-4/B, Block-14, Sir Shah Suleman Road, Gulshan-e-Iqbal,  
Karachi-Pakistan. Phone: 99021231, 99021223, Fax: 99231583 [www.ssgc.com.pk/ssgc](http://www.ssgc.com.pk/ssgc)

## Checklist for Bidders

Enquiry No. \_\_\_\_\_ Opening Date \_\_\_\_\_ Time \_\_\_\_\_  
 M/s. \_\_\_\_\_ Phone No. \_\_\_\_\_

Please ensure before submitting the bid, that following information / documents have been submitted / provided along your bid. Check ( ) appropriate box.

| S. No. | Details of required information / documents   | Yes | No |
|--------|---|-----|----|
| 1.     | Each & Every Page of the bidding documents shall be signed and stamped by the bidder.   |     |    |
| 2.     | Technical Compliance sheet (if applicable) has been filed.  |     |    |
| 3.     | Fixed Bid Bond as specified in the tender document.   |     |    |
| 4.     | Bid validity as specified is mentioned.   |     |    |
| 5.     | Delivery period has been specified.   |     |    |
| 6.     | Country of Origin.  |     |    |
| 7.     | Standard Warranty Guarantee (if applicable).  |     |    |
| 8.     | Original Performance Bonds of Principal.  |     |    |
| 9.     | Original Technical Literature.  |     |    |
| 10.    | Original Authorization Letter of Principal.   |     |    |
| 11.    | Original Authorization Letter of Manufacturer.  |     |    |
| 12.    | Estimated item wise weight including gross weight & volume of consignments.   |     |    |
| 13.    | Port of Shipment (specific name of port/Sea Port is required) in case the city mentioned by the bidder does not have any port, the FOB charges to the port of shipment will be borne by the supplier. |     |    |
| 14.    | L/C confirmation charges (if desired by bidder) shall be borne by the supplier.   |     |    |
| 15.    | L/C charges at suppliers end shall be borne by the supplier.  |     |    |
| 16.    | Both FOB & C&F rates are quoted (C&F rates should be based on PNSC freight).  |     |    |
| 17.    | Sample (if necessary) is enclosed.  |     |    |
| 18.    | Alternative offer (if any) submitted should be on as per Section 3 Schedule of Requirement & Bid Form format. For each alternative offer separate fixed bid bond is required.                         |     |    |
| 19.    | Deviations from tender terms (if any) have been stated in Section 3 Schedule of Requirement & Bid Form format. At any stage of process and after acceptance, Tender terms will prevail.               |     |    |
| 20.    | Firm name of Beneficiary & Bank details with complete address of beneficiary.   |     |    |
| 21.    | Original Bid + One Copy is Submitted.   |     |    |
| 22.    | Form-X and bid securing declaration Duly Signed & Stamped.  |     |    |

**NOTE:**

Non-availability of the above information/documents, or incomplete/incorrect statement on this checklist may result in rejection of the bid at / after the bid opening.

As per SRD2967/2023 dated 08<sup>th</sup> March 2023 "E-Pak Procurement Regulations-2023" all bidders are advised to register in e-Pak Acquisition and Disposal System (EPADS).

\_\_\_\_\_  
 Bidders Authorized Representative



Sui Southern Gas Company Limited (SSGCL)

Contents

Part - A

|              |   |                        |
|--------------|---|------------------------|
| Section - 1  | General Terms & Conditions                | Included               |
| Section - 1A | Additional Terms & Conditions for FOB/C&F | Included               |
| Annexure-A   | Format of Bid Bond Bank Guarantee         | Included               |
| Annexure-B   | Format of Performance Bank Guarantee      | Included               |
| Annexure-C   | Declaration by Supplier                   | Included               |
| Section - 2  | Special Conditions of Tender Document     | Included /Not required |

Part - B

|             |  |                       |
|-------------|--|-----------------------|
| Section - 3 | Bid Form (Schedule of Requirement)                                     | Included              |
| Section - 4 | Specifications/Drawing (if applicable)                                 | Included/Not required |
| Section - 5 | Affidavit of Compliance with Integrated Management System (IMS) Manual | Included              |

**SUI SOUTHERN GAS COMPANY LIMITED**  
Procurement Department

M/a \_\_\_\_\_

Tender Enquiry No. \_\_\_\_\_

**INVITATION TO BID**

Sui Southern Gas Company Limited, (SSGCL) has pleasure in extending you an invitation, to submit bid for the subject material according to Terms and Conditions specified in the attached Tender Document. Please read following instructions before submission of bid:


1. Bids are to be submitted in sealed envelope provided with the tender, indicating Tender Enquiry Number & opening date and time on the face of the envelope.
2. Bid Bond of 2% of the total FOR / FOB value shall be enclosed with the bid without which bid will be rejected and returned to bidder unannounced. The Bid Bond shall remain valid till the last date of the month in which it is expiring.
3. In case the bid opening date falls on a holiday or due to some unavoidable circumstances, it is not possible to open on scheduled date, it will be opened on next working day at the same time and at the same venue.
4. The bidder shall bear all expenses associated with the preparation and delivery of its bid/sample and the Company will in no case be liable in this respect.
5. Prospective bidder requiring any information or clarification of the tender may notify the same by fax or at the mailing address. The Company will respond to any request for explanation or clarification, if received within reasonable time prior to submission of bids.
6. The Company reserves the right to cancel, amend, delete or amend tendered items/quantities/any part of the tender during the bidding period without assigning any reason. However, bidders shall be informed about it prior to bid opening process.
7. The Company reserves the right to accept or reject any bid or part of a bid or to amend the bidding process and reject all bids at any time prior to award of contract/purchase order without thereby incurring any liability to the affected bidder(s).
8. In case of Single stage two (02) envelope bidding procedure (if mentioned in press advertisement & Tender documents), sealed technical offer & sealed bid shall be submitted in separate envelopes Bid Bond will be enclosed with "commercial" bid. "Technical Proposal" and "Financial Proposal" is to be mentioned on the top of the envelopes. Technical offers will be opened and evaluated first. Financial offers of only technically compliant bidders will be opened at a later indicated date in presence of bidder's representatives. Financial proposal of technically non-compliant bidders will be returned un-opened along with their bid bond.
9. For Tenders invited on F.O.B/C&F basis, conditions as mentioned in section-1A will also apply.
10. The Company will appreciate confirmation by fax No 92-21-99231583 or email [enquiry@ssgc.com.pk](mailto:enquiry@ssgc.com.pk) or to DGM (Procurement) of your intention to submit the bid and if not interested in submission of bid, it will be appreciated if it is intimated through fax or email with mentioning of reasons.
11. Bids are required to be submitted at:

Tender Room, CRD Building, Head Office Complex, Sir Shah Sulaiman Road Gulshan-e-Iqbal, Karachi Pakistan. Ph. 0092-21-99021024, 0092-21-99021223, 0092-21-99021279, 0092-21-99013074, Fax # 0092-21-99231583, Email: [enquiry@ssgc.com.pk](mailto:enquiry@ssgc.com.pk)

Hope and look forward for your valued participation.

Thanking you

Yours sincerely

  
General Manager (Procurement)



## General Terms &amp; Conditions

## 1. Submission of bids:

- 1.1. Bids are to be submitted in sealed envelope provided with the tender (in such a manner that contents are fully kept enclosed and cannot be seen until opened) indicating tender enquiry number, its opening date and time on the top of the envelope. Envelopes shall be addressed to General Manager (Procurement Department) on the address provided on "invitation to bid". Envelope shall indicate the name and address of the bidder for returning the bid in case it is declared late or submitted without bid bond.
- 1.2. Sealed bids (as above) shall be mailed/submitted/dropped in tender box placed at Tender Room, CRD Building, SSGC Head Office. Bids are to be delivered on or before closing time after which they will not be entertained. In case bid is sent through courier, the same shall be delivered at least 24 hours before scheduled opening time.
- 1.3. The Company may at its discretion extend the closing date for the submission of bids, in which case all rights and obligations of the purchaser and bidders previously subject to the closing date will thereafter be subject to the date extended. However, any request for extension received from prospective bidders less than one week prior to bid opening date may not be entertained. In case of extension in bid opening date, the same will be advertised in press and simultaneously shall be intimated to prospective bidder who had purchased the tender documents.
- 1.4. The bid shall contain no interlineations, erasures or overwriting except as necessary to correct the errors made by the bidder, in case of any correction etc. It shall be signed and stamped by the person signing the bid.
- 1.5. The quoted price shall be inclusive of all duties/taxes except GST, which is to be mentioned separately. The supplier shall certify (if applicable) regarding non-applicability of GST for which documentary evidence shall be submitted or could be produced upon demand.
- 1.6. Rates shall be item-wise, as given in price schedule/schedule of requirement/Bid Form unless otherwise specified.
- 1.7. Bidder is responsible for timely delivery of bids at location specified 1.2 above. Company will not be responsible for misplacement/tampering/non-attendance/delay or any other incident in case the bid is not delivered at the designated place & time.
- 1.8. Any bid received late after the closing date and time, will be rejected and returned unopened.
- 1.9. The quotation shall only be acceptable on/as per Bid Form. In case for foreign tender when Local Agent submits bid on behalf of different bidders, a separate Bid Bond for each Bid is required. Likewise for tender when bidder submit alternative bids, separate bid bond for each bid is required or else bid will be liable for rejection.
- 1.10. Deviation from tender terms and conditions is not allowed. However, in unavoidable circumstances, these shall be mentioned at the bottom of "Section - Bid Form" deviation on any other page will not be entertained.
- 1.11. Discount offered (if any) shall be mentioned on the "bid form" only.
- 1.12. The bidder(s) or their authorized representative shall put his full signature with stamp & date on each page of tender document as well as enclosure vis-a-vis drawings, specifications etc. Any correction, overwriting shall be duly signed & stamped.
- 1.13. The bid is to be completed and returned to the Company in accordance with General terms & conditions. General terms & conditions duly signed & stamped (as a token of acceptance) shall be submitted along with Bid Form (Price schedule) duly completed as per requirement. However, specifications/drawing is to be retained by bidder for their future references.

## 2. Eligible Countries / bidders:

The invitation for bids is open to all manufacturers/suppliers/stockiest/dealers/pre-qualified bidders but is not applicable to those countries where inter trade protocols with Pakistan do not exist or those countries from where imports are not allowed by Government of Pakistan.

## 3. Qualification/Disqualification of Suppliers:

The Company, at any stage of the procurement proceedings, having credible reasons for or prima facie evidence of any defect in supplier's or contractor's capacities, may require the suppliers or contractors to provide information regarding their professional, technical, financial, legal or managerial competency.



whether already pre-qualified or not. The Company shall disqualify a supplier or contractor if it finds, at any time during the tender process, that the bidder's information regarding their qualification is false and materially inaccurate or inconsistent.

4. **Joint Ventures:**

In the event that the successful bidder is a joint venture (formation of two or more companies), the Company will require an undertaking on judicial stamp paper that the parties to the joint venture accept joint and several liabilities for all obligations under the purchase order/contract.

5. **Clarification of tender documents:**

Prospective bidders requiring any further information or clarification of the tender documents may notify the Company in writing or by fax or at the Company's mailing address indicated in the "invitation to bids". The Company will respond in writing to any request for information or clarification of the tender documents, if received five working days prior to closing date for the submission of bids prescribed by the Company. The Company response (including an explanation of the query) will be sent in writing or by fax/e-mail to all prospective bidders who have purchased the tender documents. Verbal instructions/queries will not be acceptable.

6. **Modification and withdrawal of bid:**

- 6.1 The bidder may modify or withdraw its bid after the bid submission, provided the written notice of the modification or withdrawal is received by the Company prior to the deadline prescribed for submission of bid. After the bids/quotations are opened, no bidder shall be allowed to revise, propose or request any change in the bid.
- 6.2 The bidder's modification or withdrawal notice shall be sealed and addressed to GM (P). A withdrawal notice may be sent by fax followed by a signed copy.
- 6.3 Bids once opened cannot be withdrawn during validity period.

7. **Bid validity:**

All offers shall remain valid up to 90 days (120 days in case of Two Envelope bidding procedure) from the date of opening of bids, until any further extension is given by the bidder. If the bidder agrees for extending bid validity the bid bond shall also be extended accordingly. A bidder giving extension to his bid validity will not be required or permitted to modify his bid. If there will be any query/clarification or extension request asked by the Company, the bidder should reply the same within 7 days after receipt of the same and if bidder takes more than 7 days the delay in reply will be added to their bid validity period.

8. **Rate Escalation:**

8.1 **All items except line-pipe:**

Quoted prices shall remain valid, firm, irrevocable and fixed till the fulfillment of obligations by the bidder and will not be subject to escalation/change on any account.

8.2 **Line-pipe only:**

- 8.2.1 Bidders are essentially required to submit detailed breakdown of rates indicating unit price of
  - a) HR Coil.
  - b) All other charges (including wastage, transportation, conversion cost etc).
- 8.2.2 Rate / price offered by the bidders shall be firm and irrevocable. However bidder offering pipe manufactured from Pakistan Steel Mills (PSM) HR coil are required to submit certified documentary evidence of HR coil rates. Adjustment in line-pipe rates (from the bid opening date till the currency of order) due to change in rate of HR coil manufactured by PSM is admissible to the extent of raw material cost without wastage. The bidders are required to submit certified documentary evidence of HR coil rates published by PSM, at the time of submission of bids. SSGC may verify the document/rates from PSM.
- 8.2.3 The variation clause however shall not be applicable on line-pipe quantities which were delivered within 20 days of the announcement of the variation (both days inclusive) in price of HR coil by PSM.



- 8.1.4 The variation clause also shall not be applicable on the line pipe quantities delivered after the specified delivery schedule (total or monthly consignment wise).
- 8.2.5 No escalation is applicable on line pipe manufactured from imported HR coil.

9. Bid bond (earnest money):

Bid bond equivalent to two percent (2%) of the total offer value, in favor of Sui Southern Gas Company Ltd. shall accompany the bid if bid value is above Rs.500,000 in the form of pay order, demand draft, call deposit receipt or a bank guarantee (specimen of bank guarantee is attached at Annexure-A), issued by a scheduled bank in Pakistan. The bid bond shall remain valid for 120 days (150 days in case of Two Envelope bidding procedure) unless specified otherwise. The bid bond shall be returned/refunded to the unsuccessful bidders while the bid bond of the successful bidder shall be retained, till submission of Performance bond (if applicable). Bids without bid bond will not be considered. In case the order value is less than Rs. 500,000 the bid bond in lieu of performance bond will be retained till fulfillment of obligation by the supplier. However, in either case the bidder is responsible to arrange the extension the bid bond validity as per requirement. If bid bond submitted by the supplier is more than 2% of ordered value, it may be replaced with appropriate value. If order value is less than Rs. 500,000, the bid bond will be returned along with the order. Bid bonds of non-compliant bidders may be released during evaluation process. The bid bond may be forfeited if a bidder withdraws the bid during validity period specified by the bidder or if successful bidder fails to:

- ✓ Accept purchase order.
- ✓ Furnish performance guarantee in accordance with clause 16 of Section 1,
- ✓ Supply material as per requirements and delivery schedule.

9.1 In the event of bid bond validity falling short of the prescribed period of 120 or 150 days as the case may be either (i) due to extension in the bid submission date or (ii) where so required by the procuring agency, then in such an event it shall be incumbent on the bidder to extend the bid bond validity upto 120/150 days within 30 days of the opening of technical proposal / bid, and / or where so required by the procuring agency.

9.2 In the event of the bid security amount deposited / furnished by the bidder falls short by 10% of the requisite Bid security amount. The procuring agency keeping in view the nature of the procurement may consider and allow the bidder to deposit / furnish the balance 10% amount, provided the bidder does so within 15 days of the opening of the bid. Notwithstanding that all other terms & conditions have been fully complied with.

10. Opening of bids:

Bids will be opened in presence of bidders or their authorized agents at the address provided on "invitation to bids". The bidder's representatives who are present shall sign the bid opening sheet (attendance sheet) to mark their attendance/witness. Commercial contents of bids will be announced/recorded in bid opening sheet.

11. Preliminary Examination of bids:

- 11.1 The Company will examine the bids to determine their completion, computational errors, provision of guarantees, authorized signature and other related matters.
- 11.2 Arithmetic errors will be rectified on the following basis. Discrepancy between unit price and the total price obtained by multiplying the unit price and quantity, the unit price shall prevail and the total price will be corrected. Discrepancy between total bid amount and the sum of total prices, the total prices shall prevail and the total bid amount will be corrected.
- 11.3 Prior to a composed evaluation, the Company will determine the substantial responsiveness of each bid to the bidding documents. In Company's opinion a substantially responsive bid is the one which conforms to all the terms and conditions of the bidding documents without any material deviation.
- 11.4 Bid determined as not substantially responsive will be rejected by the Company and cannot subsequently be made responsive by the bidder through correction of the non-conformity.



**12. Clarification of submitted bids:**

To assist in the examination, evaluation and comparison of bids, the Company may, at its discretion, inquire any clarification from bidder about their bid. All responses by bidders shall be provided in writing and no change in the price or substance of the bid shall be sought, offered or permitted.

**13. Technical Literature & Samples:**

The Bidder(s) shall submit the following:

- 13.1 Samples (if applicable/required)
- 13.2 Original or legible copy of technical literature/performance characteristics
- 13.3 Test Certificates (if applicable/required)
- 13.4 Documentary evidence for legal import in case of imported material. (At the time of delivery when quoted on FOR basis)
- 13.5 In case of pipeline operation material bidders must also attach a "proof from supplier/manufacturer, that goods offered have been used successfully on a high pressure natural gas pipeline elsewhere under tropical climatic conditions.

**13.6 Specification Compliance Sheet:**

Company requires a clause-by-clause commentary on the Specifications, demonstrating the materials responsiveness to those specifications by a statement of deviations and exceptions to the provisions of the specifications, if so required/desired. For purposes of the commentary to be furnished pursuant to above, the bidder shall note that standards for workmanship, material and equipment and references to brand names or catalogue numbers, designated by the Company in the specifications are intended to be descriptive only and not restrictive. The bidder may substitute other authoritative standards, brand names and catalogue numbers in its bid provided which demonstrates to the Company's satisfaction that the substitutes are equivalent or superior to those designated in the specifications by the Company.

Bid which does not possess above certificates, certificates etc, may be considered technically Non-compliant.

- 13.7 The offer shall be accompanied with all technical data/documents/certifications as required under the tender specifications. Evaluation shall be carried on the basis of data/documents/certifications submitted with the bid. No clarification, additional information may be sought / accepted after bid opening.

**13.8 Deviation to technical specifications:**

The bidder shall fill the "technical compliance sheet" and mention offered specifications along with reference to its technical brochure/literature (page/clause No etc). Statement such as "Compliant" or "Confirmed" is not acceptable. Deviation to tender terms and technical specification is not acceptable. However, if bidder feels to mention minor deviation, the same shall be referred categorically on the "Bid Form" as well as on the technical compliance sheet stating reference of its technical data sheet/brochure. In case of insufficient information, data or documents, the Company is not liable to seek clarification and the bid may be determined non-compliant on provided information.

**14. Award/Evaluation Criteria:**

- 14.1 In case of locally manufactured items e.g. service line material & meter components manufactured by local vendors, the lowest bidder will be awarded maximum quantity as per his declared capacity and past performance in respect of delivery and quality. New vendors / manufacturers shall also be considered for placement of a purchase order up to a maximum of 10% of the tender quantity if their submitted sample has been tested and approved and provided they have quoted lowest price or agree to accept the order on lowest received price.
- 14.2 Generally for other items other than above, ordering shall be based on technical compliance and lowest quoted price. Supplies may be subject to pre shipment inspection and post qualification by a third party in case of foreign material. If required during the process of manufacturing and / or inspection, SSGCL representative may visit the manufacture facility to witness the manufacturing / inspection process.



- 14.3 Evaluation may be carried out both on item or on group of items/single or multiple package basis depending upon the nature of requirement exclusively at the discretion of the company to ensure economic procurement.
- 14.4 Company reserve the right to select the final terms of supply with the lowest evaluated and commercially responsive bidder. Any effort by the bidder (s) to influence the outcome of bid evaluation or placement of purchase order may result in disqualification of the bidder.

#### 15. Loading of Bids:

Bids may be loaded with following if offer found to be deviated from specifications, delivery schedule, terms & conditions without stating the amount involved in such deviation by following method:

- 15.1 The cost of compensation / loading amount for that item shall be derived from the bid itself.
- 15.2 If 15.1 is not possible, average of rates of other bidders, who have quoted for that item conforming technical specification, shall form the basis for cost compensation/loading.
- 15.3 The company will encourage participation by local bidders who will be given price preference. A cost factor shall be determined as per prevailing Government policy / SRO. However they will submit details of local value addition on raw material imported by them and percentage of locally manufactured component with documentary evidence.

#### 16. Performance Bond:

- 16.1 In case purchase order value is above Rs:500,000, the successful bidder shall submit performance bond guarantee which to be submitted within ten days from receipt of LOI or order along with integrity part. The successful bidder shall submit a performance bank guarantee (PBG) in the form of a pay order or bank certificate (specimen attached at Annexure-B) issued by a scheduled bank in Pakistan, for an amount equivalent to 10% of the total value of the purchase order or as specified in the "letter of intent". The performance bond unless specified otherwise, shall remain valid till:
- 16.1.1 Completion of final satisfactory delivery in case of consumable items.
- 16.1.2 12-18 months from the date of satisfactory delivery of the equipment/machinery.
- 16.1.3 Satisfactory delivery/installation of system in case the installation responsibility is on supplier's part.
- 16.1.4 120 days in case of chemicals.
- 16.1.5 In case of locally manufacturing items, a PBG equivalent to 3 months delivery schedule will be required after placement of purchase order which should remain valid till completion of final satisfactory delivery of the ordered quantity.
- 16.1.6 In case of small diameter line pipe (MS/MDF) the PBG shall remain valid up to 3 months after completion of satisfactory final delivery.
- 16.1.7 In case of Vehicles, Manufacturer's Warranty is required in lieu of PBG.
- 16.2 The guarantee will be released after completion of this period, subject to satisfactory performance of the supplied equipment/machinery/system as mentioned at 16.1 above. The supplier shall keep the guarantee valid at their cost until fulfillment of the obligations.
- 16.3 In case the bidder does not submit the performance bond as specified, the delivery time of goods shall be deemed to have commenced 10 days (15 days in case of import) from the issuance of letter of intent/purchase order. The proceeds of the performance bond shall be payable to the Company as compensation for any loss resulting from the supplier's failure to complete its work under the purchase order/contract. The validity period of the performance bond is to be extended if the delivery date/period is being extended mutually by the Company/Supplier.
- 16.4 The performance bond will be discharged / returned by the Company not later than thirty (30) days following the date of completion of the supplier's work under the purchase order/contract including any warranty/guarantee performance obligations as specified in the special conditions of contract. The supplier shall not be absolved of their liability to perform in case of encashment of performance bond by the Company, who shall have the right to claim and receive all damages/losses incurred due to non-performance.
- 16.5 The Company shall promptly notify the supplier in writing for any claim arising under this guarantee. Upon receipt of such notice, the supplier shall promptly repair or replace the defective goods or parts thereof, without cost to the Company other than, where applicable the cost of inland delivery of the repaired or replaced goods or parts from the port of entry to the final destination.

14.



- 16.6 If the supplier, having been notified, fails to rectify the defect (s) in accordance with the purchase order/contract, the Company may proceed to take such remedial actions as may be necessary at the supplier's expense. Any amount payable by the supplier under this clause may be recovered by the Company by withdrawing from the performance bond without having to notify or seek the approval of the supplier.
- 16.7 Nothing herein contained shall be construed to limit supplier's obligation of performance of the order/contract to the value of the performance bond.
- 16.8 **Guarantee/Warranty:** In case where performance guarantee is not applicable, the supplier shall confirm that all supplied goods under the contract/purchase order are new, unused, of the most recent or current models and incorporate all recent improvements in design and goods unless provided otherwise in the contract/purchase order. This guarantee shall remain valid for a period of twelve to eighteen months after the goods have been delivered or commissioned.

17. **Purchase Order/Contract:**

Purchase order of quoted material may be placed on fulfillment of conditions mentioned at 14 & 16 above which is through formal confirmation for proceedings with the suppliers.

18. **Assurance:**

The successful bidder will be required to give satisfactory assurance of its ability and intention to deliver the goods, pursuant to the tender enquiry and contract within the time set forth therein.

19. **Force Majeure:**

19.1 In the event of either party hereto being rendered unable, wholly or partially, by force majeure circumstances to carry out obligations under the purchase order/contract documents, such party shall give notice and full particulars and other satisfactory evidence of such force majeure circumstance(s) in writing to the other party within 7 days after disoccurrence of the cause(s). Relied upon the obligations of the party giving such notice so far as they are affected by such force majeure shall be suspended for the period during cause(s) shall, as far as possible, be remedied and obviated with all reasonable dispatch. The term 'force majeure' as employed herein, shall mean acts of God or public enemy and insurrection, fires, floods, earthquakes or other physical disasters, order or request of government, blockade or embargo. It is, however, clarified that strikes, lockouts, shortage or non-availability of raw materials, rains, and disturbances, other labor dispute or congestion's in ports on the supplier's side shall not be included in the term 'force majeure'.

19.2 In case the force majeure contingencies last continuously for more than one month, both parties will agree on the necessary arrangements for the further implementation of the purchase order/contract. In case further implementation is unforeseen and impossible, both parties shall arrange for the termination of the purchase order/contract, but without prejudice to their rights and obligations prior to such termination it being understood that each party shall fulfill its contractual obligations so far as they have fallen due before the operation of force majeure.

20. **Amendment in purchase order/contract:**

20.1 The Company may at any time by a written notice to the supplier make changes within the general scope of the purchase order/contract in any one or more of the following:-

- 20.1.1 Drawings, designs or specifications where goods to be furnished under the purchase order/contract are to be specifically manufactured for the Company.
- 20.1.2 The method of shipment or packing.
- 20.1.3 The place of delivery.
- 20.1.4 Quantities of item up to a maximum variance of +15% of purchase order/contract value.

20.2 Company reserves the right to increase/decrease the quantities or delete any or all items listed in the price schedule/schedule of requirement/bid firms without assigning any reason.

20.3 Upon notification by the Company of such modifications the supplier shall submit to the Company an estimated cost for the proposed modification within ten (10) calendar days of receipt of notice of the modification and shall include an estimate of the impact (if any) of the modification on the delivery dates under the purchase order/contract, as well as a detailed schedule for the execution of the modification, if applicable.



- 20.4 The supplier shall not perform modification in accordance with clause 20.3 above until the Company have authorized a modification order in writing on the basis of the estimate provided by the supplier as described in clause 20.3.
- 20.5 Modifications mutually agreed upon shall constitute a part of the work under the purchase order/contract and the provisions and conditions of the contract shall apply to the said modification.
- 20.6 If modification made by the Company results in a variation in purchase order/contract quantities whose net cost effect is within 15% of the total value then the original purchase order/contract rates would be applicable. Any "modification" affecting the quantities and the corresponding cost effect beyond 15 percent would be mutually agreed upon between the Company and the supplier.
21. Extension in delivery period:
- 21.1 Delivery of the goods shall be made by the supplier in accordance with the schedule of requirements and delivery period; however, the supplier may claim extension of the time limits as set forth in the schedule of requirements and delivery period in case of
- 21.1.1 Modification in the goods ordered by the Company pursuant to clause 20.
- 21.1.2 Delay in provision of any services which are to be provided by the Company (services provided by the Company shall be interpreted to include all approvals by the Company under the contract).
- 21.1.3 Delay in performance of work caused by orders issued by the Company.
- 21.2 The supplier shall demonstrate to the Company's satisfaction that it has used its best endeavors to avoid or overcome such causes for delay and the parties will mutually agree upon remedies to mitigate or overcome such causes for delay.
- 21.3 Notwithstanding clause 21.1 above, the supplier shall not be entitled to an extension of time for completion unless the supplier at the time of such circumstances arising, immediately has notified the Company in writing of any delay that it may claim as caused by circumstances pursuant to clause 21.1 above and upon request of the Company, the supplier shall substantiate that the delay occurred is due to the circumstances referred to by the supplier.
22. Packing:
- 22.1 The material shall be in original/sealed packing to ensure delivery without any damage during transit.
- 22.2 If any of the good is discovered to be damaged or unacceptable at the point of embarcation, the supplier shall be responsible for replacement of those goods free of any charge and cost to the Company, within the delivery time schedule of the contract/purchase order.
- 22.3 The identification marks showing contents, quantity and contract/purchase order number shall be printed on each skid/metal container/case containing one copy of invoice or packing list.
- 22.4 Handling and Transportation:  
The Supplier shall arrange for the proper stacking of the Goods and for its proper storage and lashing and for other such provisions/suitable measures as may be necessary to safeguard against movement and damage to the Goods from the point of loading to its designated destination.
23. Inspection:
- 23.1 Pre-Delivery inspection may be carried-out at the premises of supplier(s) and/or post delivery inspection at company's any location, by the appointed inspector/inspection team, third party inspectors appointed by the Company.
- 23.2 The Company reserves the right to arrange inspections and tests to the goods or manufacturing processes at any stage at any of the premises of the supplier or its subcontractor(s) or and at the point of delivery and at the goods final destination. Where conducted on the premises of the supplier or its sub-contractor(s), all reasonable facilities and assistance including access to drawings and production data shall be furnished to the inspectors at no charge to the Company. Such inspection, however, shall not relieve the Supplier to fulfill the obligations under the



purchase order/contract. If goods fail to conform to the specifications, the Company may reject them.

#### 24. Delivery:

- 24.1 Free delivery at any of the following locations, unless specified otherwise:
- 24.1.1 R & D Section, Stores Department Abul Hasan Ispakani Road, Karachi.
  - 24.1.2 R & D Section, Stores Department F-37, SITE Karachi.
  - 24.1.3 R & D Section, Stores Department F-76, Dope Yard SITE, Karachi.
  - 24.1.4 Meter Manufacturing Plant, Sir Shah Saleman Road, Gulshan-e-Iqbal Karachi.
  - 24.1.5 Khadeji Store, 57th Kilometer at Super Highway Karachi.
  - 24.1.6 Any other location specified by the company.
- 24.2 Delivery period shall commence after 10 days (15 days in case of import) of the issuance of letter of intent or from the date of purchase order/contract whichever is earlier, unless otherwise specified.
- 24.3 The supplier shall replace defective material at their risk & cost including transportation, duty, etc.
- 24.4 CSRs, if applicable be submitted at R&D section Stores Department along with material & delivery challan.
- 24.5 Unloading and stacking through cranes, fork lifters, labor etc. will be arranged by supplier at delivery site (for material like Pipes/Heavy Machinery & Equipment etc).
- 24.6 Delivery is to be made strictly in accordance with "delivery schedule" as specified by the Company.
- 24.7 The rejected material to be collected/lifted by the supplier within a maximum period of one month after its intimating to the Company. Beyond specified period, the Company shall not be responsible for storage/safety of the uncollected material.

#### 25. Delivery Failure:

- 25.1 In case the supplier fails to supply the material within the stipulated period, the Company have the right to make an alternative arrangement for the purchase of the goods on such terms as may be offered. In such event all losses, cost and charges sustained/incurred by the Company on stated purchase shall be recovered from the supplier without prejudice to any other right or remedy available to the Company which includes recovery of losses sustained by the Company from any due payment of the said supplier.
- 25.2 In the event Company remains unable to make such alternative arrangements, the Company has the right to recover from the supplier any of all losses sustained as a result of the supplier's failure to ship/supply the goods as per schedule of delivery.
- 25.3 In the event Company being forced to purchase any quantity of any other alternative not specified in this document as a result of any failure to supply/ship the material, the Company shall have the right to terminate the contract/purchase order without prejudice to any other rights or remedies available to the Company.

#### 26. Payment:

- 26.1 The supplier after delivery of goods and its acceptance shall submit invoice to Finance Department of the Company, containing following information i.e.
- (a) Purchase order No. & date
  - (b) Items
  - (c) Quantity
  - (d) Price
  - (e) Invoice value
  - (f) Point of delivery
  - (g) Delivery challan indicating delivery date, etc.

Payment will be made within 30 days of completion of stated formalities.

- 26.2 Income Tax @ 3.5% or as applicable under the prevailing government rules will be deducted at source (except where the supplier provides an income tax exemption certificate). Quoted price shall be inclusive of all taxes, except GST, which shall be mentioned separately. Supplier(s) are required to submit signed and stamp acknowledgement slip, Sales Tax return, Annex "C" & Annex "T" (whichever applicable) in which Sales Tax (of relevant Sales Tax invoice) is paid.



- 26.3 In case supplier is not liable to pay tax under the income tax ordinance or is liable to pay tax at a lower rate the supplier shall obtain a certificate from the tax authorities in Pakistan to that effect. In case the required certificate is not produced by the supplier prior to the date of payment, then the Company shall deduct tax at source from the gross payment payable to supplier.

## 27. Liquidated damages:

- 27.1 If supplier fails to deliver ordered material within the stipulated period/scheduled time specified in purchase order, Company, without prejudice to any other remedies, shall deduct from the bill or any other due payments/guarantees, as liquidated damages, a sum equivalent to 0.1% per day of the undelivered goods up to maximum 10%. The liquidated damages shall also be applicable for the cancelled quantity of goods under clause 28.
- 27.2 Whenever liquidated damages become payable, in the event that delivery of all goods and equipment is not made within the time period specified except on account of force majeure, the Company shall quantify the same and shall serve notice to the supplier requiring payment thereof. If the supplier fails to remit payment within 15 days of receipt of such notice, the Company shall forthwith become entitled to recover the same without recourse to the supplier, by calling upon the Performance Bond, withdrawals by way of liquidated damages shall not reduce the value of the Performance bond.
- 27.3 The payment of liquidated damages shall not relieve the supplier from performing and fulfilling all its obligations under the contract/purchase order nor shall the right and entitlements of the Company be affected or reduced in any manner.
- 27.4 In case of order placed on FOB/C&F basis, the delivery period shall commence from the date of confirmation of L/C. However, delayed submission of PBG period in excess of time limit will be deducted from the delivery period for the purpose of recovery of late delivery charges.
- 27.5 The liquidated damages shall be the sum equivalent to point one (0.1%) percent of the Contract price of the delayed goods as well as for services for each day of delay, until actual delivery or performance, up to a maximum deduction of ten (10) percent of the Contract price. Once this maximum is reached, the Company may consider termination of the Contract at the risk and cost of the Supplier.

## 28. Default by Supplier:

- 28.1 The Company may, without prejudice to any other remedies by written "notice of default" sent to the supplier, cancel the purchase order whole or in part, if:
- 28.1.1 The supplier fails to deliver any or all of the ordered quantity as per specified delivery schedule or any extension thereof granted by the Company.
- 28.1.2 The supplier fails to perform any other obligation(s) under the purchase order.
- 28.1.3 The Company during the delivery period has reasons to believe that the supplier will not be able to fulfill the obligations under the purchase order/contract. The Company prior to exercising its right to cancel the purchase order/contract shall issue notice to the Supplier specifying the default(s) and the supplier shall submit an explanation within seven (07) days of receipt of such notice. If such explanation is not furnished within the stipulated time or if so furnished, is found to be unsatisfactory and/or the default(s) continues, purchase order/contract may be cancelled. The Company in addition to cancellation of purchase order/contract may suspend/cancel the entitlement of supplier.
- 28.2 The Company shall have the right to terminate/cancel the contract/purchase order concluded between the supplier and Company, if:
- 28.2.1 The successful bidder fails to furnish the performance bond as under clause 16 thereof.
- 28.2.2 The supplier fails otherwise to perform, fulfill or comply with terms, conditions, regulations and requirements of the contract/purchase order to carry out the work in accordance with the provisions thereof or abandons the shipment.
- 28.2.3 The supplier becomes bankrupt or insolvent or makes an assignment for the benefit of its creditors.
- 28.2.4 One or more consignments of material delayed by a period of more than three months or not-supplied.
- 28.2.5 Rejection of manufacturing items as a result of observation by inspection team



- 28.2.6 Penalty on higher rejection rate of supplied goods.
- 28.3 The supplier shall have the right to terminate the contract/purchase order if:-
- 28.3.1 The Company fails to establish the "letter of credit" within the stipulated period as required.
  - 28.3.2 The Company becomes bankrupt or insolvent or makes an assignment for the benefit of its creditors.
  - 28.3.3 The Company is in default and breach of its obligation and liabilities under the contract/purchase order.
29. **Resolution of dispute:**  
The Company and the supplier shall make every effort to resolve the disagreement or dispute arising between them amicably by direct discussion under or in connection with the purchase order/contract.
30. **Applicable law:**  
The purchase order/contract shall be governed by and interpreted in accordance with the laws of the Islamic Republic of Pakistan.
31. **Declaration of Integrity Fact/Certification:**
- 31.1 Successful supplier shall furnish the declaration (specimen attached at Annexure-C) within 10 days after issuance of LOI/order /contract if the order/contract value becomes Rs:10 million or above.
  - 31.2 In case of F.O.B/C&F purchase order/Contract, the Principal as well as "local agent" both will sign the "Integrity part" as required under this clause.
  - 31.3 Bidders to submit a certificate on Rs:100/- non-judicial stamp paper certifying that they are not black listed by the Government of Sindh and its various bodies and declared as defaulted supplier.
32. **Arbitration/resolution of disputes:**
- 32.1 Any difference or dispute arising out of or in connection with the contract between the Company and the supplier which can not be amicably resolved shall be referred to arbitration in Karachi, Pakistan, to two arbitrators, one appointed by each party of such difference/ dispute. In case the judgment of the said Arbitrator being at variance the matter shall be referred to an "umpire", who shall be appointed by both the side Arbitrators. The umpire shall be retired judge of a High Court or the Supreme Court of Pakistan. Such arbitrators and umpire shall together proceed to adjudicate the disputes in accordance with the Arbitration Act, 1940 as amended from time to time.
  - 32.2 Prior to exercising any right by the Company or supplier to terminate the purchase order/ contract under the conditions stipulated above, a return notice shall be required to be given to the other party specifying such default(s) and calling for submission of an explanation within seven (7) days of receipt of such notice. If such explanation is not furnished within the stipulated time or if so furnished, is found to be unsatisfactory, and the default(s) is/are continuous, the purchase order/contract be terminated with notes to other party.
  - 32.3 The agreement shall be governed by Law of Islamic Republic of Pakistan and the arbitration language shall be English.
  - 32.4 During the course of arbitration, the supplier shall not suspend the performance of his responsibilities and obligations under the contract unless authorized by the Company in writing to do so.
  - 32.5 In addition to the remedies as stated above, there is a "grievance committee" formed by the Company which can be approached by supplier in case of non-settlement of issues at any stage if supplier feels that settlement is not insight or not justified.
33. **Redressal of grievances by the procuring agency:-**
- 33.1- Grievance Committee is in place to address the complaints of bidders that may occur prior to entry into the procurement contract.
  - 33.2 \* Aggrieved bidder may lodge a written complaint concerning his grievances not later than fifteen days after the announcement of the bid evaluation report.
  - 33.3 Bidder is to submit complaint on letter head duly signed by the authorized person. Tender reference, details / nature of complaint, complainant active telephone, cell, postal address, email



address must necessarily be provided. Incomplete / anonymous complaints will not be responded at all.

- 35.4 The Committee shall investigate and decide upon the complaint within fifteen days of the receipt of the complaint.
- 35.5 Mere fact of lodging of a complaint shall not warrant suspension of the procurement process.

**34. Blacklisting of Suppliers and Contractors:**

The Company shall permanently blacklist or temporarily debar (at least for 6-months from participating in SSGC's tender proceedings) if, a supplier or contractor who either constantly fails to perform satisfactorily performance or found to be indulged in corrupt and fraudulent practices as defined below:

- 34.1 "Corrupt and fraudulent practices" includes the offering, giving, receiving, or soliciting of anything of value to influence the action of an official/Company.
- 34.2 If the supplier/contractor found responsible for the detriment of the Company during proceedings procurement/contract, process or its execution.
- 34.3 Misrepresentation of facts in order to influence the procurement process or the execution of the contract/order/contract.
- 34.4 Collusive practices among bidders (prior to or after bid submission) designed to establish bid prices at artificial, non-competitive levels and to deprive the Company of the benefits of free and open competition.

**35. Supplier's Guarantee and Responsibilities:**

The Bidder/Supplier shall guarantee that the materials supplied against this tender enquiry is new and is of acceptable quality and has been tried and approved on similar jobs. The validity and scope of such guarantee will be in accordance with conditions stated in this document. In case the opinion of the Company the Goods fail to perform the services in accordance with the specifications specified in Section IV, due to manufacturing defects, defective material and/or workmanship, the Supplier shall replace, repair or reconstruct such Goods at his own cost in Pakistan wherever the Goods shall be located so that such Goods shall be restored in such conditions that it shall perform in satisfactory operating condition or to replace it with new Goods at his own cost so that the goods shall perform in accordance with the specifications and details as set forth in the Contract tender documents. If the Supplier shall fail to do so after expiry of 15 days notice in this effect served on him by the Company, the Company shall be at liberty to repair, replace and/or reconstruct the Goods at its costs provided in the event, the Company shall be entitled to recover total cost of such replacement from the Supplier withdrawing from the Performance Guarantee.

**36. Language:**

The bid prepared by the bidder and all correspondence and documents relating to the bid exchanged by the bidder and the Company shall be written in English language. Any printed literature furnished by the bidder may be written in another language provided that this literature is accompanied by an English translation in which case for purpose of interpretation of the bid, English translation shall govern.

**37. Vehicle Applied by Authorized dealer of local manufacturer :**

In case of vehicle supplied by authorized dealer of local manufacturer, the authorized dealer will be responsible to get the vehicle (a) registered through Excise Department Government of Sindh and provide Original Registration book / Original Registration Invoice / Tax payment receipt / other related documents & provide the vehicle (a) number plate (b) to SSGC. Registration fee will be reimbursed by SSGC subject to submission of Government of Sindh Excise Department receipt.



## Additional Terms for Tenders on F.O.B.C&amp;F basis:

## 1. Submission of bids:

- 1.1 Bid bond (Earnest money) @ 2% of the total F.O.B value as per clause 9, of section 1 of "General terms & conditions" is required to be submitted with the bid. It may be noted that bids without bid bond will be rejected and returned to bidder.
- 1.2 In case the bidder is manufacturer the bid shall either be completely prepared by the foreign bidder including signing and stamping of all documents. In case, such documents are being signed by the local agent of the bidder, the bid shall essentially include supplier's original Performa invoice and an original authority letter in favor of local agent to sign the documents on their behalf. The bid is liable for rejection if these conditions are not met.
- 1.3 In case of Bidder offering to supply goods which the bidder did not manufacture or otherwise produce, the bidder shall be duly authorized by the goods manufacturer or the producer to submit bid or supply the goods on their behalf.
- 1.4 Bids shall be submitted (preferably through local agents) in two copies, (original + copy).
- 1.5 The price on F.O.B and C&F basis is to be quoted separately. Following are to be essentially indicated in the bid form:
- 1.5.1 Country of origin.
  - 1.5.2 Port of shipment.
  - 1.5.3 Estimated gross net weight, dimension & volume of offered item and estimated weight of each item.
  - 1.5.4 Delivery period or schedule in case of bulk quantities.
  - 1.5.5 Original technical literature.
  - 1.5.6 Beneficiary's complete address.

1.6 Foreign bank charges and L/C confirmation charges will be borne by the supplier.

## 1.7 Bid Currency:

The rates shall be quoted in bidder's home country or in United States Dollars. A bidder expecting to incur a portion of its expenditures in the performance of the contract in more than one currency and wishing to be paid accordingly shall indicate the same in their bid. However, bidder from Pakistan would be paid in Pak Rupee.

(Clause 1.5 of General Terms & Conditions is not applicable)

## 2. Bid bond:

- 2.1 Bid bond shall be equivalent to two percent (2%) of the total F.O.B value, in favor of Sui Southern Gas Company Limited and shall be in the form of pay order, demand draft, call deposit receipt or a bank guarantee (specimen attached at Annexure-A), issued by a scheduled bank in Pakistan. The bid bond shall remain valid for 120 days (150 days in case of Single Stage Two Envelope bidding procedure) unless specified otherwise. The bid bond shall be returned/refunded to the unsuccessful bidder while the bid bond of the successful bidder shall be retained, till submission of Performance bond. Bidder without bid bond will not be considered. In case the order value is less than US\$25,000 the bid bond in lieu of performance bond, will be retained till fulfillment of obligations by the supplier. However, in either case the bidder is responsible to arrange the extension of bid bond validity as per requirement. If bid bond submitted by the supplier is more than 2% of ordered value, it may be replaced with appropriate value. Bid bonds of non-compliant bidders may be released during evaluation process. The bid bond shall be denominated in the currency of the bid or any other freely convertible currency.

2.2 Bid submitted on behalf of different principals shall be required to submit separate bid bond along with the bid for each offer.

(Note as mentioned at Clause 9, 9.1 & 9.2 of General Terms & Conditions shall also apply).

## 3. Conversion to single currency:

In order to carry out evaluation and comparison, the Company will convert all bid prices expressed in various currencies to Pak Rupees at the buying exchange rates established by the State Bank of Pakistan or any other commercial bank in Pakistan for similar transactions on the date of opening of bids. In case of Two Envelope Bidding System, the exchange rates prevailing at the time of opening of Technical Proposal will be used for conversion and evaluation.



#### 4. Evaluation Criteria:

- 4.1 The evaluation of bids will be carried out on C&F / landed cost basis, however purchase order will be placed on FOB price on freight to collect basis. The bidders are required to submit best freight charges obtained by them from Pakistan National Shipping Corporation (PNSC) in order to have a uniform basis to arrive at C&F cost. Bill of lading to indicate "freight payable by the consignee at destination" in local currency. Foreign currency exchange rate (selling) will be considered as of bid "opening date".
- 4.2 In the case of goods to be offered from outside Pakistan, custom duties and other similar import taxes which are applicable shall be added to the bid.
- 4.3 In case shipment by air it shall be arranged through Company's airfreight forwarder (s) or their nominated agent. "on freight to collect basis".

(Clause No. 14.3 to 14.4 of General Terms & Conditions are also to be applicable).

#### 5. Loading of Bids

Freight charges from port of loading up to Karachi port or unit C&F value must be indicated in bid form, billing, which bid will be loaded by 5 to 10% freight charges. Bid will be declared non-compliant if loading results an extensive increase in price of material.  
(Clause 15 of General Terms & Conditions is also applicable).

#### 6. Performance bond:

- 6.1 In case purchase order value is Rs. 25,000/- or above or equivalent for other currencies, letter of intent will be issued to successful bidders on submission of performance bond guarantee which is to be submitted within 15 days from receipt of L.O.I. Successful bidders shall submit a performance bank guarantee (P.B.G) in the form of bank guarantee specimen attached at Annexure-B) issued by a scheduled bank in Pakistan, for an amount equivalent to 10% of the total value of the purchase order or as specified, in the letter of intent. The performance bond unless specified otherwise, shall remain valid till:
  - 6.1.1 Completion of final satisfactory delivery of consumable items.
  - 6.1.2 12-18 months from the date of satisfactory delivery of the equipment/machinery.
  - 6.1.3 Satisfactory delivery/installation of systems in case the installation facilities will be on supplier's part.
  - 6.1.4 120 days in case of chemicals.
- 6.2 The Letter of Credit shall be operative upon receipt of Performance Bond (as specified in para 6.1) and integrity pact, any delay due to late submission of Performance Bond will be on supplier's account. Late submission of PBG should not affect the delivery schedule.
- 6.3 The performance bond shall be denominated in foreign currency or in currency of the contract/purchase order or in a freely convertible currency acceptable to the Company and shall be in the form of a bank guarantee.
- 6.4 In very special case subject to approval of the management, the P.B.G could be acceptable in Pak Rupee. However, an undertaking should be given by the supplier that in case of encashment of P.B.G. supplier shall deposit short fall amount due in Pak Rupee exchange rate.
- 6.5 Warranty/Guarantee:  
In case where performance guarantee is not applicable, the supplier shall warrant that all goods supplied under the contract/purchase order are new, unused, of the most recent or current models and all recent improvements in design and goods have been incorporated, unless provided otherwise in the contract/purchase order. This guarantee shall remain valid for a period of twelve to eighteen months after the goods have been delivered or commissioned.  
(Clause 16.2 to 16.8 of General Terms & Conditions are also applicable).

#### 7. Delivery:

- 7.1 In case of "FOB" order/contract, shipment(s) shall be effected per vessel of Pakistan National Shipping Corporation (PNSC) owned or chartered vessels on "freight to collect" basis. Bill of lading to indicate "freight payable by the consignee at destination". In case goods ready for shipment and (if PNSC vessels is



not available at port of loading, supplier shall intimate the same to Company immediately so that matter could be taken with P.N.S.C. in Pakistan.

**7.2 In case of C&F order/contract, the supplier hereby guarantees/consure:**

- 7.2.1 To use clean and dry vessel suitable for marine transportation and shall not use tramp vessels.  
 7.2.2 The goods/material will be shipped/discharged with all care and diligence at their risk & cost and goods to be stored below deck. Accordingly, the supplier shall be responsible for all damages/losses during inland and marine transportation from the supplier's plant until arrival at Karachi port.  
 7.2.3 To provide as part of its work all services and functions related to handling, loading, unloading, lashing and securing in ship's holds and all costs, charges and expenses of which shall be included in the purchase order/contract price, unless otherwise specified.

**7.3 In case of FOB order/contract, the supplier's obligations shall be over after the goods have crossed the ship's rails. The co-ordination, scheduling and lining-up for a P.N.S.C. vessel shall be the obligation of the supplier.**

**7.4 The supplier shall reimburse the Company all additional duties, taxes and other such charges paid by the Company on account of short shipment by the supplier for all items subsequently shipped on a no-charge basis or otherwise by the supplier. The supplier shall also reimburse the Company all additional duties, taxes and other such charges paid by the Company on account of incorrect invoicing by the supplier.**

**7.5 Shipment shall be considered to have been made when the supplier has shipped the goods against a clean bill of lading and all other such documentation, as specified in clause 9.3 & 9.4 appearing next in sequence) have been furnished to the Company.**

**7.6 The supplier shall ensure that all above mentioned acts and other incidental and ancillary functions are conducted in accordance with sound and acceptable engineering practices. The Company shall be entitled to oppose any incorrect or inadequate practice adopted by supplier in this respect and the supplier shall take corrective action/measure forthwith to correct such omissions. If any goods are discovered to be damaged or unacceptable at the point of loading, the supplier shall be responsible for replacement free of all charges and costs to the Company within the delivery period specified in the purchase order/contract.**

**8. Insurance:**

8.1 All goods supplied under the purchase order/contract shall be fully insured in a freely convertible currency against loss or damage incidental to manufacture, acquisition, transportation, storage and delivery in the manner specified in delivery clause 7.

8.2 Marine Insurance shall be the responsibility of the Company unless otherwise specified.

8.3 The supplier shall advise the Company by fax at least (seven (7) days) prior to the expected date of shipment, the following particulars:-

- 8.3.1 Name of the vessel and of the shipping company.  
 8.3.2 Age of the vessel (which should be less than 20 years).  
 8.3.3 Lloyds 100A1 or equivalent classification of the vessel.  
 8.3.4 ETD from Port of dispatch and ETA at Karachi.  
 8.3.5 FOB/C&F value of the consignment.

The above information shall also be transmitted to the Company's underwriter M/s. National Insurance Corporation by fax No. 0092-21-9202779 and to the Company referring Point No. NIF/M/KAUP/002/73.

**9. Payment:**

9.1 Payment of FOB/C&F prices shall be made in the currency of bid through an irrevocable letter of credit (L/C) established in favor of the supplier, negotiable through the bank of their choice. Bidder shall indicate full name and address of the negotiating bank and the place at which they wish to negotiate the letter of credit. All bank charges outside Pakistan will be on supplier's account and all bank charges within Pakistan will be at Company's account. If confirmed letter of credit is required then charges for confirmation will be on supplier's account.

9.2 The supplier's request (s) for payment shall be made to the Company in writing as follows:

- 9.2.1 It shall be accompanied by an invoice describing, as appropriate, the goods delivered and the services incurred and by shipping documents submitted pursuant to Clause 9.4 hereof and upon fulfillment of other obligations stipulated in purchase order/contract.  
 9.2.2 Against shipping documents on arrival of ordered material at consignee destination, Bidder (s) will have to clearly mention, if they wish to opt for this mode of payment.

9.3 The letter of credit shall be available upon presenting the following documents to the negotiating bank within 15 days of the date of the bill of lading covering shipment of each consignment.



- 9.3.1- Invoice ----- 4 copies  
 9.3.2- Packing list ----- 4 copies  
 9.3.3- Bill of lading "freight to be paid by consignee at destination" evidencing shipment in terms of the purchase order to Karachi-Pakistan made copies. out to order in the name of Co.'s bank. Notify party Sul Southern Gas Company Ltd. ----- 3 originals & 6 non-negotiable
- 9.3.4- Certificate of Origin (Verified/ Endorsed by Chamber of Commerce) ----- 7 copies  
 9.3.5- Manufacturers test certificate/ ----- 2copies Inspection report.
- 9.4 Without prejudice to the supplier's responsibility for providing documents mentioned as at 9.3.1 to 9.3.5 above to bank, the supplier shall forward the following non-negotiable documents directly to Company immediately after shipment so as to reach the Company at least 15 days prior to the arrival of the vessel at Karachi port.
- 9.4.1 -Invoice ----- 6 copies  
 9.4.2 -Bill of Lading ----- 6 copies  
 9.4.3 -Packing List ----- 6 copies  
 9.4.4 -Certificate of Origin (Verified /Endorsed by Chamber of Commerce) ----- 2 copies  
 9.4.5 -Manufacturers Test Certificate/ ----- 2 copies  
 Inspection Report
- 9.4.6 The invoice to be exactly as per order/contract. Any deviation which render or cause the company to pay demurrage or any other charges with respect to clearance/handling etc. will be borne by the supplier.
- 9.5 No payment hereunder shall be deemed to be accepted by the Company of the goods covered by such payment nor release the supplier from responsibility thereof under the terms of the purchase order/contract.
- 9.6 If the Company is compelled to pay demurrage or storage charges or incur any loss or suffers any damage at Karachi Port on account of non-compliance by the supplier of above requirements, the Company shall be entitled at their sole discretion to recover the same amount from supplier.
10. Termination of purchase order by supplier:
- 10.1 The supplier shall have the right to terminate the contract/purchase order if:-
- 10.1.1 The Company fails to establish the letter of credit within the stipulated period as required under clause 9.1 hereof after the supplier has made compliance with all provisions of clause 6.
- 10.1.2 The Company becomes bankrupt or insolvent or makes an assignment for the benefit of its creditors.
- 10.1.3 The Company is in default and breach of its obligation and liabilities under the contract/purchase order.
- 11 Installation/Commissioning/Training:  
 If installation/commissioning and training is required, the charges will be paid in Pak Rupee and will be subject to deduction of all local duty and taxes (as applicable).
- 12 Vehicle (s) supplied by foreign manufacturer / principal:
- 12.1 In case of supply of any type of vehicle (s) / earth moving vehicle (s) by the foreign principal / manufacturer. After clearance of vehicle from the custom, the local agent of the foreign supplier / manufacturer / principal will be completely responsible to get the vehicle (s) registered through Excise Department Government of Sindh and provide Original Registration book / Original Registration Invoice / Tax payment receipt / other related documents & provide the vehicle (s) number plate (s) to SSGC. Registration fee will be reimbursed by SSGC subject to submission of Government of Sindh Excise Department receipt.
- 12.2 The bidder / supplier shall quote only those vehicle (s) / which fully comply to Pakistani environment and can operate in Pakistan. The bidder should ensure that vehicle (s) consumable i.e (fuel/oil & lubricant/spares) are easily available in Pakistan.



On Non Judicial Stamp Paper of Rs. 50/- (Fifty) Per 100,000  
Format of Bid Bond Guarantee

BANK GUARANTEE NO. \_\_\_\_\_  
DATE OF ISSUE \_\_\_\_\_  
DATE OF EXPIRY \_\_\_\_\_  
AMOUNT \_\_\_\_\_

TE # SSGIC/FP/\_\_\_\_\_

Sul Southern Gas Company Limited,  
5T, 4/B, Hfoc-14,  
Tulshan-e-Iqbal,  
Sir Shah Sulaiman Road,  
Karachi.

Dear Sir,

Bid Bond Bank Guarantee

In consideration of M/s \_\_\_\_\_ hereinafter called the Bidder  
having submitted the accompanying bid & in consideration of value received from Bidder we hereby agree and  
undertake as follows:

To make unconditional payment of Rs. \_\_\_\_\_ upon your written demand without further  
recourse, question or reference to the Bidder or any other person in the event of withdrawal of the aforesaid  
bid by the Bidder before the end of the period specified in the bid after the opening of the  
envelope for the validity thereof or if no such period is specified within 90 days (150 days in case of Single Stage Two  
Envelope bidding procedure) after said opening and or in the event that the Bidder shall within the period  
specified therefore or if no period specified within 15 days after the prescribed forms are presented to this  
Bidder for signature the Bidder shall fail to execute such further contractual documents if any, as may be  
required by the terms of the bid as accepted or on the Bidder failure to provide the requisite Performance Bond as  
may be required for the fulfillment of resulting contract.

To accept written intimation (s) from you as conclusive and sufficient evidence of the existence of a default  
of non-compliance as aforesaid on the part of Bidder and to make payment accordingly within 03 days of the  
receipt of the written intimation.

No grant of time or other indulgence to, or composition or arrangement with the Bidder in respect of this  
aforesaid Bid with or without notice to us shall in any manner, discharge or otherwise, howsoever affect this  
Guarantee and our liabilities & commitments hereunder.

This Guarantee shall be binding on us and our successors in interest and shall be irrevocable.

Ours faithfully,

(stamp and signature of the issuing bank)



On Non Judicial Stamp Paper of Rs. 50/- (Fifty) Per 100,000  
Format of Performance Bond Guarantee

BANK GUARANTEE NO. ....  
DATE OF ISSUE .....  
DATE OF EXPIRY .....  
AMOUNT .....

Sui Southern Gas Company Limited,  
ST. 4/B, Block-14  
Gulshan-e-Iqbal,  
Sir Shah Sulaiman Road,  
Karachi.

TE # SSGC/FP/ \_\_\_\_\_

Dear Sirs,

in the sum of Rs. .... Account .....  
to You in Karachi under the Purchase

In consideration of your having placed Purchase Order No. ....  
dated: ..... On M/s. .... called Supplier and in  
consideration for value received from Supplier we hereby agree and undertake as under:

1. To make unconditional payments to you from time to time as called upon or make an unconditional payments Rs. .... Being Ten Percent (10%) of the value of the Purchase Order price mentioned in the said Purchase Order, on your written demand(s) without further recourse, question or reference to Supplier or any other person, in the event of default or non-performance and / or non-fulfillment by Supplier of his obligations liabilities & responsibilities under and in pursuance of the said Purchase Order of which you shall be the sole judge.
2. To accept written intimation from you as conclusive and sufficient evidence of the existence of a default or breach as aforesaid on the part of Supplier and to make payment accordingly within 3 (three) days of receipt thereof.
3. To keep this guarantee in full force from the date hereof as specified in General or Special terms & conditions.
4. That on grant of time or other indulgence to amendment in the terms of the purchase order by agreement with Supplier in respect of the Performance of his obligations under said in particular of said Purchase Order with or without notice to us, shall in any manner discharge or otherwise, however, affect this Guarantee and our liabilities and commitments there under.
5. This Guarantee shall be binding on us and our successors in interest and shall be irrevocable.
6. This Guarantee shall not be affected by any change in the constitution of the Guarantor Bank or the constitution of M/s ..... the Supplier.

Yours faithfully,

(Stamp and signature of the issuing bank)



## (Format of Declaration)

General Manager (Procurement)  
Sui Southern Gas Company Limited,  
ST. 4/B, Block-14, Gulshan-e-Iqbal,  
Sir Shah Suleman Road, Karachi.  
Dear Sir,

**Declaration**

(The Seller/Supplier) hereby declares its intention not to obtain or induce the procurement of any contract, right, interest, privilege or other obligation or benefit from Sui Southern Gas Company Limited or any administrative subdivision or agency thereof or any other entity owned or controlled by it (SSGC) through any corrupt business practice.

Without limiting the generality of the foregoing, (The Seller/Supplier) represents and warrants that it has fully declared the brokerage, commission fees etc. paid or payable to anyone and not given or agreed to give and shall not to give or agree to give to anyone within or outside Pakistan either directly or indirectly through any natural or juridical person, including its affiliate, agent, associate, broker, consultant, director, promoter, shareholder, sponsor or subsidiary, any commission, gratification, bribe, finder's fee or kickback, whether described as consultation fee or otherwise, with the object of obtaining or inducing the procurement of a contract, right, interest, privilege or other obligation or benefit in whatsoever form from SSGC, except that which has been expressly declared pursuant hereto.

(The Seller/Supplier) certifies that it has made and will make full disclosure of all agreements and arrangements with all persons in respect of or related to the transaction with SSGC and has not taken any action or will not take any action in circumvent the above declaration, representation or warranty.

(The Seller/Supplier) accepts full responsibility and accountability for making any false declaration, not making full disclosure, misrepresenting facts or taking any action likely to defeat the purpose of this declaration, representation or warranty. It agrees that any contract, right, interest, privilege or other obligation or benefit obtained or procured as aforesaid shall, without prejudice to any other rights and remedies available to SSGC under any law, contract or other instrument, be voidable at the option of SSGC.

Notwithstanding any rights and remedies exercised by SSGC in this regard, (The Seller/Supplier) agree to indemnify SSGC for any loss or damage incurred by it on account of its corrupt business practices and further pay compensation to SSGC in an amount equivalent to ten times the sum of any commission, gratification, bribe, finder's fee or kickback given by (The Seller/Supplier) as aforesaid for the purpose of obtaining or inducing the procurement of any contract, right, interest, privilege or other obligation or benefit in whatsoever form from SSGC.

Yours faithfully,

Signature & Stamp (The seller/supplier)

Note:

1. The above declaration is required to be submitted by the Successful Bidder after issuance of Purchase Order (PO) or Letter of Intent (LOI) on Bidder's letter head, for purchase order / letter of intent of a total value of Rs. 10,000,000/- (Ten million) or above.
2. Please note that submitting the declaration is a mandatory requirement.



Tender Enquiry No. SSGC/FP/\_\_\_\_\_

**Special Conditions of Tender Document**

**Note:** In case of any conflict between Special Conditions of Tender Document and any other terms & conditions, the Special Conditions of Tender Document will govern / prevail.

**1. Warranty / Guarantee Coverage**

i) The successful bidder / supplier guarantee that the goods supplied against above tender enquiry are in all respect in accordance with the tender specifications & Purchase Order and that material used are in accordance with the latest approved standards and are of good workmanship / quality. Any item or part of item if found to be substandard or not meeting the specified criteria as per pre-shipment / post shipment inspection report, than in such as event the Supplier / Bidder hereby warrants and undertakes to replace the same on Duty Delivery Paid (DDP) basis (INCOTERMS 2010) i.e. free of all cost including but not limited to transportation, taxes and levies. In case successful bidder / supplier failure to replace the defective item / remove the defect(s) free of cost within the period specified by the Purchaser, the successful bidder / supplier will refund the relevant cost including all other expenses incurred by the purchaser in this regard.

ii) The successful bidder / supplier must confirm that the warranty for non-consumable items will remain valid for 18 months and for consumable items (i.e. Chemical, Battery etc.) will remain valid for 6 Months after the goods have been successfully delivered or commissioned.

iii) It is mandatory that the successful bidder / supplier will submit the attached undertaking at Annexure-II, duly filled, signed & stamped.

iv) In case where performance bank guarantee is not applicable, the supplier shall confirm that all supplied goods under the contract / purchase order are new, unused, of most recent or current models and incorporate all recent improvements in design and goods unless and otherwise provided in the contract / purchase order.

v) The Warranty Undertaking being provided by the local agent of the successful bidder (Principal) is required to be submitted at least on Rs.200/- Non-judicial Stamp paper and should be duly notarized / attested. In the event when this Warranty Undertaking is being submitted by the principal who is overseas resident in that case the same would required to be notarized by the notary public and attested by the Pakistan Embassy or High Commission in that particular jurisdiction. Needless, to mention that in both cases the Warranty Undertaking will be executed by the duly authorized representative of the local agent of the principal as the case may be.

**2. Bid Security:**

a) Bid bond submission (2%) of the bid amount as mentioned in the clause 1.1 & 2 of Additional Terms for tender on F.O.B/C&F basis & 9 of General Terms & Conditions, to be treated as null & void, however, other contents of clause 1.1 & 2 of Additional Terms for tender on F.O.B/C&F basis & 9 of General Terms & Conditions will remain unchanged. The submission of fixed amount of bid security is appearing in the Price Schedule/BOQ.

b) All the bidders are advised to furnish fixed bid security (Deposit Instrument) as per amount in Pak Rs. Or US\$ appearing in price schedule/BOQ failing which their bid will be rejected.

c) In case the bidder submit bid in the currency other than Pak Rs. Or US\$ their bid bond shall be equivalent after the conversion to the amount of fixed bid bond given in Pak Rs. Or US\$ as mentioned in Price Schedule/BOQ. The exchange rate (issued by the Treasury Management Group of the National Bank of Pakistan or the State Bank of Pakistan selling rate) prevailing at the time of bid opening date will be applicable.

d) The submission of fixed amount of bid security is also mandatory for all the bids including Rs.500,000/- or less.

e) The word lowest bidder or the lowest evaluated bid has been substituted to refer to most advantageous bid.

f) Sub-clause 9.2 of the General Terms & Conditions to be treated as null & void, however, other contents of clause 9 will remain unchanged.

**3. Method For Submission of Bid Bond (Under Single Stage Two Envelope Bidding Procedure):**

In case of Single Stage Two Envelope Tenders the fixed bid bond as per clause#09 of General Terms & Conditions and Clause# 02 of Additional Terms for tenders on F.O.B/ C&F basis to be placed in the Technical Proposal. However, if the bid bond is placed in the Financial proposal will also be considered. Without submission of bid bond (either in Technical proposal or Financial proposal) the bid will be rejected.

**4. Bid Validity:**

All offers shall remain valid up to 120 days from the date of opening of bids and bid bond shall remain valid for 150 days.

**5. Evaluation Criteria and Comparison of Bids**

In accordance with SRO 827 (1) / 2001 bidders tendering for Engineering goods produced in Pakistan and those Engineering goods specified in CGO-11 and amendments thereof by the Central Board of Revenue or Engineering Development Board. The successful bidder shall be accorded a Price preference in respect up to a specific percentage (in proportion to the value addition) of the lowest quoted landed cost of an item of foreign origin with similar specifications as mentioned in the tenders.



- i) Provided that:-
- The saving in foreign exchange is not less than the amount of price preference;
  - It is ensured that, in each case of such preference, the total import requirements for producing the supplies tendered for locally manufactured items has been duly indicated by the bidders.
- ii) Price preference shall be allowed as under:-
- Having minimum of twenty percent value addition through indigenous manufacturing, price preference shall be fifteen percent;
  - Having over twenty percent and up to thirty percent value addition through indigenous manufacturing, price preference shall be twenty percent, and
  - Having over thirty percent value addition through indigenous manufacturing, price preference shall be twenty five percent.
- iii) For the above purpose, we will require a complete breakdown of ex-factory price for goods manufactured in Pakistan. Any offer not accompanied with this cost breakdown will not be allowed to receive the above price preference.
- iv) Benefit of SRO 827 (I)/2001 shall be accorded to only those local manufacturers who are engaged in the manufacturing of goods specified in CGO - 11 of 2007 or its latest version or as certified by the EDB. However in case of offer on FOB basis, the landed cost to be determined in accordance with the following criteria be taken for evaluation in case of International bidders, and shall be taken for the purpose of comparison with the price quoted by local manufacturers, who shall also be accorded the price preference in terms of SRO 827 (I)/2001. The landed cost to be determined in accordance with the afore said criteria shall be taken for bid evaluation in case of international bidders and shall be taken for the purpose of comparison with the price quoted by the local manufacturers. Example of landed cost for evaluation of the international bidders is given here under:

**EXAMPLE**

| S. No. | Cost Components for computing landing cost of imported Engineering goods in terms of S.R.O 827 (I)/2001 in Pak Rupees.   |
|--------|--|
| i.     | FOB Value.   |
| ii.    | Sea Freight (Actual quoted by the bidder on the basis of FNSC rates, which shall be announced by the bidder at the time of opening of the bid).  |
| iii.   | C&F value (i + ii). (CFR value).   |
| iv.    | Insurance @ 1% of C&F Value given at iii above.  |
| v.     | CI F value (iii + iv).   |
| vi.    | Handling Charges @ 1 % of CIF Value given at v above.  |
| vii.   | Import Value (v + vi) for the purposes of levying Customs Duty.  |
| viii.  | Customs Duty at applicable rate, which shall be levied on the import value given at vii above.   |
| ix.    | Duty Paid Value.   |
| x.     | Sales Tax at applicable rate, which shall be calculated on the duty paid value given at ix above.  |
| xi.    | Duty & Sales Tax paid value (ix + x).  |
| xii.   | Withholding Tax at applicable rate, which shall be calculated on duty and sales tax paid value given at xi above.  |
| xiii.  | LC Charge @ 0.25% of FOB Value given at i above.   |
| xiv.   | Clearing Charges @ 0.25% of C&F Value given at iii above.  |
| xv.    | SFD at applicable rate, Which shall be calculated on the import value given at vii above to be taken as nil as it stands withdrawn.  |
| xvi.   | Provincial Infrastructure Cess (at applicable rate) on %age of import value given at vii   |
| xvii.  | KPT Wharfage @ Rs.140 per cubic meter or the prevailing rate.  |
| xviii. | Crane Loading & Other Charges @ 0.25% of C&F Value given at iii above.   |
| xix.   | Inland Transportation Charges from Port to Coating factory (From Port of final destination in case of products other than pipes, where coating is not required).                                 |
| xx.    | Cost of imported engineering goods (xi to xix).  |
| xxi.   | LESS: Handling Charges taken at Sr. No. vi (Notional Value taken for calculating assessed value for purpose of calculating custom duty, sales tax and withholding tax by the customs authority). |
| xxii.  | LESS: Sales tax taken at x above. (Adjustable as output tax).  |
| xxiii. | LESS: With Holding Tax. (Adjustable against final assessed tax).   |
| xxiv.  | Total deductions (xxi + xxii + xxiii)  |
| xxv.   | Net cost of imported engineering goods (xx minus xxiv)   |

- v) Foreign bidders are essentially required to submit letter of PNMC for ocean freight transportation rate for break bulk/hedges from their local agent
- vi) Please indicate approximate shipping specification, i.e. weight and measurements of the packages/trailers and also total gross weight (in terms of metric tons), and total gross volume (in terms of cubic meters) of each consignment separately.
- vii) For evaluation of bids customs duty, taxes and all other charges prevailing on the date of public opening of bids will be used, where applicable.
- viii) For the purpose of price comparison and evaluation of bids, financial charges will also be added to arrive at a landed cost, which will inter-alia include, mark up and L/C opening charges etc.



- ix) If the local manufacturer becomes the lowest evaluated bidder after Price Preference, order will be placed at the price (Landed Cost) quoted by the lowest evaluated international bidder. In case the local bidder does not accede to the request of SSGCL for best negotiated rates at par with those received from international bidder for particular item(s) then, the order will be placed on the lowest evaluated international bidder.
- x) "Price Preference" shall not be in "Value Terms" it should only be for the sake of reference for comparison purposes (local & foreign bids).
- xi) Bank details shall be mentioned by the bidders for the purpose of opening LC/ Payment.
6. **Declaration / Integrity Pact / Certification:**  
it is required to be submitted by the Successful Bidder on their letter heads after issuance of Purchase Order (PO) or Letter of Intent (LOI) for the value of Rs. 10,000,000/- (Ten Million) or above in case of local bidder and US\$ 100,000 & above in case of foreign bidder.  
Submission the declaration as at ANNEXURE-C is a mandatory requirement for successful bidder.
7. **Third Party Pre-Shipment Inspection Criteria /Scope of Work as given in the Tender Documents will be followed at the time of Third Party Inspection, which will be carried out by SSGCL nominated Third Party Inspection Firm in case the order value exceeds US\$100,000) except screwed pipe fitting tenders.**
8. *"The successful Bidder shall provide the revenue stamps and copy of challan, of value at the rate of twenty Five (25) paisa per every Hundred Rupees or part thereof of the amount of the purchase order, or at the prevailing rate as specified by the Government of Province of Sindh." Further as per Government of Sindh Board of Revenue notification NO. CTS/SW/11/HR&T-17/2022-808 dated 08-06-2022 all judicial and non-judicial stamp paper of the denomination of rupee five hundred and above shall be exclusively on e-stamp.*
9. *Bank Guarantee/Bid Bond/Guaranteed Performance Bank Guarantee) will be made on Non-Judicial stamp paper at the prevailing rate as specified by the respective Provinces. Further the bidder/contractor submitting the Bid Bond/guarantee/Performance Bond/guarantee being prepared by the State Bank's schedule banks should ensure that there should be no deletion/insertion/modification of any terms in the Bid Bond/(PBG) guarantee format as given in the tender document or else bid will be liable for rejection.*
10. *"Original counter slip of token which is issued with original tender document to be attached on the TOP of envelope at the time of bid submission."*
11. **Cancellation of Purchase Order**  
In case the supplier fails to deliver the material within the specified delivery schedule as given in purchase order (P.O.) and maximum upto 120 days after the expiry of the specified delivery schedule as per Purchase Order, the Purchase Order will be treated automatically as cancelled at supplier's sole risk & cost. However, for the sake of clarity liquidated damages (Clause-27 of General Terms Conditions) and Delay by Supplier (Clause-28 of General Terms Conditions) will be treated as given in the General Terms & Conditions of the tender documents.
12. **Correct Postal Address**  
Bidders are essentially required to provide correct and latest postal, e-mail & web addresses, phone/cell/fax numbers at the time of purchase of tender documents for effective and timely communication, failing which in event of any non-delivery of information / communication the procuring agency will be considered as non-responsive.
13. In case the local agent requires to offer bid from more than one principal / Manufacturer, it is mandatory to purchase separate tender document for each principal / Manufacturer, failing which the bid submitted with the original tender document will only be accepted and the bid with photocopy of tender document will be rejected.
14. **Blacklisting Mechanism of Suppliers and Contractors and their Local Agents**  
*Black listing mechanism is attached separately in the tender documents which will become an integral part of Tender Documents and now be followed / enforced in true letter & spirit and supersede the Black listing terms as mentioned in the General Terms & Conditions.*
15. *The Successful Contractor(s) / Supplier(s) / Consultant(s) shall submit a copy of Professional Tax Certificate with their Invoices / Bills falling which the payment will not be released.*
16. **Authentications of Performance Invoice / Authority Letter and other documents by the Principal / Manufacturer**  
The Authentication of Authority Letter and Performance Invoice will be obtained from the Principal / Manufacturer as and when required. If the authentication not received within the stipulated time frame the bid will be liable for rejection and the Bid Bond / Earnest Money will be encashed.
17. **Bid Bond & PBG (Performance Bank Guarantee) for Proprietary Tenders**  
*In case of proprietary Tenders, the Bid Bond & Performance Bank Guarantee (PBG) are not required / Applicable.*
18. *Any Bidder who change / amend the BOQ / Price Schedule (description / Bid Form, Quantity, UOM etc.) will render the bid as conditional bid and will be liable for rejection.*
19. *Delivery Schedule will commence after the opening of Letter of Credit (LC). In case the bidder does not submit the performance bond as specified, the delivery time of goods shall be deemed to have commenced 10 days (15 days in case of import) from the issuance of letter of intent / purchase order. The proceeds of the performance bond shall be payable to the Company as compensation for any loss resulting from the supplier's failure to complete its work under the purchase order / contract.*



20. In the event of release of Performance Bank Guarantee (PBG) after its encashment, the amount of the PBG to be released will be converted in Pak Rupees at the exchange rate prevailing at the time of encashment. The amount so converted will be released in Pak Rupee (PKR) to the foreign bidder or to their local agent duly authorized by the foreign principal.
21. SSGC will not pay invoices if they are turned in after 6 months of work completion / material delivered.
22. As per FBR Regulations Ruj# C.No.4 (24) IT- Bukhari/2021-142150-R, Dated: 23<sup>rd</sup> September, 2021 to make the payment online. Therefore, all the local manufacturers are required to provide their only one Bank Account number (IBAN number) on the 'FORM-X' attached duly signed & stamped as one time information, which shall be firm (not changeable) for all the future payment transactions. --
23. It is mandatory for the bidders to follow all the terms and conditions given in the tender documents without any addition / deletion / amendment and submit the bid accordingly. Therefore, in this context, the bidders are requested not to give their own terms and conditions as (tantamount towards the conditional bid. Otherwise their terms and conditions will not be considered and the Purchase Order / Contract will be awarded based on only as per SSGC tender terms and conditions.
24. **Payment:**  
The supplier after delivery of goods and its acceptance shall submit invoice to Finance Department of the Company, containing following information i.e:
- |                               |   |              |           |                   |
|-------------------------------|---|--------------|-----------|-------------------|
| (a) Purchase order No. & date | (b) Items   | (c) Quantity | (d) Price | (e) Invoice value |
| (f) Point of delivery         | (g) Delivery challan indicating delivery date, etc. |              |           |                   |
- (h) Supplier(s) are required to submit signed and stamp acknowledgement slip, Sales Tax return, Annex "C" & Annex "1" (wherever applicable) in which Sales Tax (of relevant Sales Tax invoice) is paid.
- Payment will be made within 30 days of completion of stated requirements.
25. **Joint Ventures:**  
In the event that the bidder is working as a Joint Venture, the Company will require the joint venture agreement duly executed by the parties to the joint venture to be submitted with the bid. The joint venture parties shall also furnish an undertaking to be jointly and severally liable for all liabilities arising out of obligation under the Purchase Order / Contract. The Joint Venture agreement of the parties must specify share of each partner and name of the lead partner along with their registration with the FBR, SST and etc. In the case may be failure to specify these two narrations the joint venture agreement will not be entertained.
26. In case the insurance policy submitted by the contractor is expired during the execution of job, it is the responsibility of the user department to coordinate with the contractor to get it renewed/updated till the period the job is completed/commissioned.
- In case the job is not completed within the given time as per tender terms and the insurance policy submitted by the contractor expires, the contractor is liable to get this insurance policy renewed / updated immediately till the period of the job is completed / commissioned as per tender terms failing which the contractor will be responsible for any loss to SSGC.
27. Bidders can quote their rates on both i.e. Price Schedule as well as Bill of Quantity (BOQ).
28. Company reserve the right to award the Purchase Order / LOI to the most advantageous bidder.
29. As per SRO 592(I)/2022 of PPRA Regulations, for Procurement Contracts / Purchase Orders worth of Rs. 50 million and above, bidders/contractors are required to submit the Beneficial Owner's Information for Public Procurement Contracts/Purchase Orders (Annexure-1).
30. In case quoted item(s) falls under SRO No. 604 (See attachment) i.e. Solar Power System PV Modules/Cells and allied accessories/parts/spares etc. - then in that case supplier is responsible to fully comply stated SRO and to arrange, provide and bear all associated costs for all necessary test reports, certificates, pre-shipment inspection reports, other documents etc. (as mentioned in SRO). Further, Pre-shipment Inspection should be from approved companies as mentioned in Appendix I of Import Policy Order (see attachment).
31. **Fixed Bid Security - Alternative Bid**  
A bidder cannot submit two bids/offers with a single fixed bid security/pay order. However, the alternative bids/offers with separate fixed bid security/pay order can be accepted, failing which the bids will be liable for rejection. In case the bidder quote different make/brands/model that will also be considered as an Alternative bid/offer and require to submit separate Bid bond for each make/brand/model.
32. Bidder will be blacklisted and henceforth cross debarred for participating in respective category of Public Procurement proceedings for a period of (not more than) six months, if fail to abide with a bid securing declaration (which is an integral part of tender document), however, without indulging in corrupt and fraudulent practices, if in breach of obligation(s) under the Bid conditions:
- a) The bidder have withdrawn or modified their bid during the period of bid validity as specified in the tender terms.



- b) Having been notified of the acceptance of bid by procuring agency during the period of bid validity (i) failure to sign the contract or accept purchase order (ii) fail or refuse to furnish the performance security or to comply with any other condition as mentioned in the tender document.
33. Wherever the "Rate Only" is mentioned (either on BOQ or anywhere in tender documents) the same shall only be applicable not exceeding 15% of the original procurement for the same items as given in the BOQ for package basis. In case the requirement is on item wise basis (not package basis) then not exceeding 15% of the original Procurement for the same items (on item wise basis) as given in the BOQ.
34. **Lots:** In case when the tender is floated on L.O.T basis, following clauses to be applied:
- a) The bidder(s) are essentially / mandatorily required to submit fixed bid bond as mentioned in the bid form/BOQ/Invitation to Bid. Separate fixed bid bond to be submitted against each individual L.O.T and its validity to be 150 days at the time of opening of technical proposal.
- b) Evaluation for each L.O.T will be carried out separately. Each LOT will be awarded separately.
35. For open competitive bidding if the most advantageous bidder is new local manufacturer, 10% trial order will be placed and remaining 90% order will be awarded to the next most advantageous bidder at their own quoted rates.
36. Subsequent to the issuance of Purchase Order/L.O.I, successful bidder has to submit 10% Performance Bank Guarantee of the Purchase Order/L.O.I value unless & until specified in the Tender Documents. Clause# 16.1.5 mentioned in General Terms & Conditions to be treated as null & void.
37. Where the Pre-shipment inspection is applicable and in case of partial shipment is required by the bidder the cost of the 1<sup>st</sup> Pre-shipment inspection will be borne by SSGC, whereas, cost of the 3<sup>rd</sup> Party inspection for the remaining shipment(s) will be borne by the bidder/manufacturer.
38. Purchase order value mentioned in clause # 6 of sub-clause # 6.1 (Performance Bond) of Additional Terms for Tenders on FOB/C&F basis (Section-1A) to be read as US \$ 10,000 instead of US \$ 25000. However, other contents of clause & sub-clauses of 6 (Performance Bond) of Additional Terms for tender on F.O.B/C&F basis will remain unchanged.
39. **Redressal of Grievances And Settlement of disputes:**
- Any bidder feeling aggrieved by any action of the procuring agency after the submission of his bid may lodge a written complaint concerning his grievances within seven days of announcement of the technical evaluation report and five days after issuance of final evaluation report.
  - In case, the complaint is filed against the technical evaluation report, the GRC shall suspend the procurement proceedings.
  - In case, the complaint is filed after the issuance of final evaluation report, the complainant cannot raise any objection on technical evaluation of the report. Provided that the complainant may raise the objection on any part of the final evaluation report in case where single stage single envelope bidding procedure is adopted.
40. The sub clauses 33.2, 33.4 & 33.5 of clause 33 of General Terms & Conditions to be treated as null & void.
41. All the bidders are allowed to participate in the subject procurement without regard to nationality/origin, except bidders of some nationality/origin, prohibited in accordance with policy of the Federal Government. Following countries are ineligible to participate in the procurement process:
- India
  - Israel
42. In Open Competitive Bidding Procedure where the quoted price is less than Rs. 500,000/- the Bid Bond will be retained in lieu of PBG.
43. In case the Bid Bond is not required, the bidder must submit the Form of Bid-Securing Declaration attached with the Tender Document else the Bid will be liable for rejection.
44. All Tenders floated through EPADS are to be governed by S.R.O. 296(I)/2023 dated: March 8, 2023 "E-Pak-Procurement Regulations 2023". In case of any conflict between SSGC Tender Terms / Instructions to Bidders and the PPRA EPADS Rules, the S.R.O. 296(I)/2023 will prevail.

45. Samples:



When sample submission is required, Suppliers/bidders must submit samples:

- a) Along with the bid, if stated in the tender documents.
- b) Within the time specified in the tender.
- c) Upon request from the User Department for technical evaluation, through official email/ letters.

**SAMPLE SUBMISSION LOCATION/ DEPARTMENT:**

All samples must be submitted to the Procurement Department - Tender Room, SSGC Head Office with Duly filled in form "Y" attached in the tender document. Samples submitted other than the Procurement Department - Tender Room, SSGC Head Office will not be considered/accepted.

**The supplier/bidder must:**

- Fill in all required details (e.g., Tender No., Bidder Name, and Sample Description).
- Attach supporting documents (if required).
- Submit the completed Form-Y along with the sample.

In absence of any of the above stated requirements the Samples will not be considered/accepted.



**NOT FOR BIDDING PURPOSE**

Declaration of Ultimate Beneficial Owners Information for Public Procurement Contracts.

1. Name
2. Father's Name/Spouse's Name
3. CNIC / NICOP/Passport No.
4. Nationality
5. Residential address
6. Email address
7. Date on which shareholding, control or interest acquired in the business.
8. In case of indirect shareholding, control or interest being exercised through intermediary companies, entities or other legal persons or legal arrangements in the chain of ownership or control, following additional particulars to be provided:

| 1    | 2   | 3                                    | 4                             | 5                | 6       | 7             | 8  | 9  | 10   |
|------|---|--------------------------------------|-------------------------------|------------------|---------|---------------|--|--|--|
| Name | Legal form<br>(Company/Limited<br>Liability Partnership<br>/Association of<br>Persons/Single<br>Member<br>Company/Partnership<br>Firm/Trusted/Any other<br>Individual, Body<br>Corporate (to be<br>Specified) | Date of Incorporation / Registration | Name of Registering Authority | Business Address | Country | Email Address | Percentage of<br>shareholding<br>control or<br>interest of BO<br>in the Legal<br>Person or<br>Legal<br>Arrangement | Percentage of<br>shareholding,<br>Control or<br>Interest of<br>Legal Person<br>or Legal<br>Arrangement in<br>the Company | Identity of<br>Natural Person<br>who Ultimately<br>owns or<br>Controls the<br>Legal Person or<br>Arrangement |
|      |   |                                      |                               |                  |         |               |  |  |  |

9. Information about the Board of Directors (details shall be provided regarding number of shares in the capital of the company as set opposite respective names).



| 1                                    | 2  | 3                                 | 4  | 5                           | 6          | 7  | 8  |  |
|--------------------------------------|--|-----------------------------------|--|-----------------------------|------------|--|--|--|
| Name and surname (in block Letter's) | CNIC no (In case of foreigner Passport No) | Father's / Husband's Name in Full | Current Nationality                                  | Any other Nationality (ies) | Occupation | Residentially address in full of the registered / principle office address for a subscribers other than natural Person | Numbers of shares taken by cash subscribers (In figures and words) |  |
|                                      |  |                                   |  |                             |            |  |  |  |
|                                      |  |                                   |  |                             |            |  |  |  |
|                                      |  |                                   | Total numbers of shares taken (in figures and words) |                             |            |  |  |  |

10. Any other information considered to or relevant to beneficial owner(s).

Name and signature  
(Person authorized to issue notice on behalf of the company)



**NOT FOR BIDDING PURPOSE**

ANNEXURE - II

WARRANTY UNDERTAKING

M/s. Sui Southern Gas Co. Ltd.  
SSGC House, Sir Shah Wali Khan Road,  
Gulshan-e-Iqbal, Karachi

From \_\_\_\_\_ (FIRM NAME)

Tender Enquiry No. \_\_\_\_\_ Date \_\_\_\_\_

1. In case we stand as the lowest bidder and the order is placed on us against the cited tender enquiry, we hereby guarantee that the goods supplied against above tender enquiry are in all respect in accordance with the tender specifications and that material used are in accordance with the latest approved standards and are of good workmanship and quality. Any item or part of item if found to be substandard or not meeting the specified criteria either pre-shipment / post shipment inspection report, then in such an event the Supplier hereby warrants and undertake to replace the same on DDP basis (INCOTERMS 2010) i.e. free of all cost including but not limited to transportation, taxes and levies.
2. In case of our failure to replace the defective item within the period specified by the Purchaser, we will refund the relevant amount including all other expenses incurred by the purchaser in this regard.
3. This warranty will remain valid for 18 months after the goods have been successfully delivered or commissioned.

Signature \_\_\_\_\_

Company Stamp \_\_\_\_\_



Supplier code: \_\_\_\_\_

**FORM-X**

**Bank account details form for all Beneficiaries**

**(Mandatory requirement for Digital Online Banking)**

As per FBR Regulations ref # C.No.4 (24) IT-Budget/2021-142150-R dated 23<sup>rd</sup> Sept'2021 to make the payment online w.e.f. 01-11-2021. All beneficiaries are required to fill in the below details, which is mandatory:

Name of Firm: \_\_\_\_\_

Address of Firm: \_\_\_\_\_

CNIC #: \_\_\_\_\_

NTN #: \_\_\_\_\_

Bank Name: \_\_\_\_\_

Bank A/C Title name: \_\_\_\_\_

Branch code: \_\_\_\_\_

Bank A/c #: \_\_\_\_\_

(16 Digits)

Bank IBAN #: \_\_\_\_\_

(24 Digits)

Information already submitted.

Note: Please be attached copy of Cheque / Account Maintenance Certificate. (Mandatory)



\_\_\_\_\_  
Authorized Sign & Stamp

Date: \_\_\_\_\_

Note: All payments transactions will be made on above mentioned Account details. This is only a one time information to be provided by the all beneficiaries. In case if the above detail has already submitted, please tick the box above "Information already submitted" and also ensure Form-X is duly signed & stamped.

**FORM "Y"**  
*(SSGC – sample submission form)*

**SECTION A: BIDDER INFORMATION**

| FIELD   | DETAILS |
|---|---------|
| Bidder Name / Firm Name   |         |
| NIN / GST No.   |         |
| Address   |         |
| Contact Person  |         |
| Contact Number  |         |
| Email Address   |         |
| <b>Declaration by Bidder</b>  |         |
| I/We hereby declare that the sample(s) submitted are in accordance with the tender specifications and terms.<br>I/We understand that failure to submit correct and complete samples may lead to disqualification. |         |
| Signature of Bidder:  |         |

**SECTION B: TENDER DETAILS**

| FIELD                                      | DETAILS |
|--|---------|
| Tender No.                                 |         |
| Tender Opening Date                        |         |
| Item(s) for which sample is submitted      |         |
| Quantity of Sample Submitted               |         |
| <b>Specification/Description of Sample</b> |         |
| Make:                                      |         |
| Brand:                                     |         |
| Serial No:                                 |         |
| Generics: size, height, weight, width:     |         |
| Other description:                         |         |

**SECTION C: FOR OFFICE USE ONLY (TO BE FILLED BY TENDER ROOM)**

| FIELD                                       | DETAILS |
|---|---------|
| Date & Time of Submission                   |         |
| Received By (Tender Room Staff Name & Sign) |         |
| Tender Room Stamp                           |         |
| Remarks (if any)                            |         |



*Handwritten signature/initials*

## Form of Bid-Securing Declaration

[The Bidder shall fill in this Form in accordance with the instructions indicated.]

Date: [date (as day, month and year)]

No.: [number of Bidding process]

Alternative No.: [insert identification No if this is a Bid for an alternative]

To: [complete name of Procuring Agency]

We, the undersigned, declare that

We understand that, according to your conditions, Bids must be supported by a Bid-Securing Declaration.

We accept that we will be blacklisted and henceforth cross debarred for participating in respective category of public procurement proceedings for a period of (not more than) six months, if fail to abide with a bid, securing declaration, however without indulging in corrupt and fraudulent practices, if we are in breach of our obligation(s) under the Bid conditions, because we

(a) have withdrawn our Bid during the period of Bid validity specified in the Letter of Bid; or

(b) having been notified of the acceptance of our Bid by the Procuring Agency during the period of Bid validity, (i) fail or refuse to sign the Contract; or (ii) fail or refuse to furnish the Performance Security (or guarantee), if required, in accordance with the ITB.

We understand, this Bid Securing Declaration shall survive if we are not the successful Bidder, upon the earlier of (i) our receipt of your notification to us of the name of the successful Bidder; or (ii) twenty-eight days after the expiration of our Bid.

Name of the Bidder: \_\_\_\_\_

Name of the person duly authorized to sign the Bid on behalf of the Bidder: \_\_\_\_\_

Title of the person signing the Bid: \_\_\_\_\_

Signature of the person named above: \_\_\_\_\_

Date signed: \_\_\_\_\_

\* In the case of the Bid submitted by joint venture specify the name of the Joint Venture as Bidder

\*\* Person signing the Bid shall have the power of attorney given by the Bidder attached to the Bid

[Note: In case of a joint Venture, the Bid-Securing Declaration must be in the name of all members to the joint Venture that submits the Bid.]



\* Only for local manufacturer

| Sr. No | Description  | Country of Origin / Make / Brand | Qty | Unit | Unit Or Price Per. of Loading | Total FOB Cost / Item (COL 4&5) | Unit Price C&F (Port of Entry Karachi) | Total C&F Port of Entry (COL 4&8) | Unit FOB Price | Total FOB Price (COL 4&10) |
|--------|--|----------------------------------|-----|------|-------------------------------|---------------------------------|--|-----------------------------------|----------------|----------------------------|
| 1      | 2  | 3                                | 4   | 5    | 6                             | 7                               | 8                                      | 9                                 | 10             | 11                         |
| 1      | <b>PRESSURE CONTROL VALVES</b><br>[ 1 ] 19280113<br>VALVE PRESSURE CONTROL W/ FLANGED ENDS RTJ CLASS 600 (AS PER SPECIFICATION ATTACHED)   |                                  | 2   | Each |                               |                                 |  |                                   |                |                            |
| 2      | <b>PRESSURE CONTROL VALVES WITH ACTUATOR &amp; INSTRUMENT GAS SUPPLY SYS. ACCESSORIES</b><br>[ 2 ] 19356453<br>VALVE PRESSURE CONTROL 2" SIZE, ANSI CLASS 600 FLANGED ENDS RTJ, AS PER SPECIFICATIONS ATTACHED |                                  | 2   | Each |                               |                                 |  |                                   |                |                            |

**Delivery Schedule:** Delivery Schedule as Annexure-II.  
FIXED BID SECURITY USD 760 OR PKR 218,000

**NOTE TO SUPPLIER:** \* According to SRO827(1)2001, "engineering goods" means good specified in DG011/2007, as per SRO the bidder will be considered as local manufacturer for the engineering goods if their names are appearing in the CGO list.

**IMPORTANT**

We draw your special attention to :

1. Prices given here in shall take into account with relevant factors including discounts, if any.
2. Proforma Invoice of the principal is mandatory required to be submitted by the Supplier which shall match with the price schedule.
3. In case when bidder submit alternate bids a separate bid bond for each bid is required, otherwise bid will be liable for rejection.
4. All offers shall remain valid up to 120 days from the date of opening of bids and bid bond shall remain valid for 150 days.
5. The prices on FOB and C&F (P&SC freight to be submitted by the bidder(s) is mandatory) basis should be quoted separately as given above.
6. Following information shall be mentioned in the bid.  
(a) Country of Origin (b) Port of Shipment (c) Estimated Gross weight / Volume
7. The bid validity and the delivery schedule shall match with the Schedule of Requirement / Bid Form. In all circumstances the bid validity and delivery schedule given on Schedule of Requirement / Bid Form will prevail without any further reference.
8. Any Bidder who change/amend the BOM or Price Schedule (Description, Quantity, UOM etc.) will render the bid as conditional bid and will be liable for rejection.

Signature : \_\_\_\_\_  
 Person Name : \_\_\_\_\_  
 Company's Name : \_\_\_\_\_  
 Date : \_\_\_\_\_

End of page, any entry beyond this line would be invalid





# SSGC SUI SOUTHERN GAS COMPANY LIMITED STATEMENT OF REQUIREMENTS

*Annexure-1*  
Annexure-1

|          |                |
|----------|----------------|
| REF. NO: |                |
| DATE     | 16   03   2026 |

DEPARTMENT: Planning & Development

DESCRIPTION OF JOB / PROJECT: 8" dia x 9 Km for receiving Pateji Gas Field from POD Sulawaj

JOB / PROJECT EXPECTED DATE OF COMMENCEMENT: Feb, 2026

JOB NUMBER: 51260001

SCHEDULE & PLACE OF DELIVERY: Khadeji Store

TYPE OF STOCK: Foreign Tendering of Control Valves

| SRL NO:   | DESCRIPTION OF MATERIAL REQUIRED   | INDEX NO: | UOM                           | QUANTITY |
|---|--|-----------|-------------------------------|----------|
| <b>Control Valves</b>   |  |           |                               |          |
| Pressure Control Valves with Accessories, Controllers and Instrument Gas supply system Accessories. |  |           |                               |          |
| 01  | Control Valves size 6", ANSI Class 600, Flange End to RTI and required as per following data           | 19266113  | Nos.                          | 02       |
|   | Body   |           | 6 Inche                       |          |
|   | Inlet & Outlet Rating  |           | ANSI Class-600, RTI           |          |
|   | Line Size  |           | 8" inches Sch: 80 (0.500" WT) |          |
|   | Fluid in Line  |           | Natural Gas                   |          |
|   | Gas Temperature  |           | 100 °F                        |          |
|   | Gas Flow Rate  |           | 40-50 MMCFD                   |          |
|   | Inlet Pressure   |           | 1030-1050 Psig                |          |
|   | Outlet Pressure  |           | 1010-1025 Psig                |          |
|   | Port Size  |           | Maximum Available (Full Port) |          |
| 02  | Port Size Control Valves size 2", ANSI Class-600, Flange End to RTI and required as per following data | 19356420  | Nos                           | 02       |
|   | Body   |           | 2 Inche                       |          |
|   | Inlet & Outlet Rating  |           | ANSI Class-600, RTI           |          |
|   | Line Size  |           | 8" inches Sch: 80 (0.500" WT) |          |
|   | Fluid in Line  |           | Natural Gas                   |          |
|   | Gas Temperature  |           | 100 °F                        |          |
|   | Gas Flow Rate  |           | 10-15 MMCFD                   |          |
|   | Inlet Pressure   |           | 850-1050 Psig                 |          |
|   | Outlet Pressure  |           | 800-850 Psig                  |          |
|   | Port Size  |           | Maximum Available (Full Port) |          |

**NOT FOR BIDDING PURPOSE**



*[Signature]*  
08/04/26

INDENTOR

Engr. AATIR SALMAN  
Dy. General Manager  
P & D - Transmission  
Sui Southern Gas Co. Ltd.

*[Signature]*  
HEAD OF DEPARTMENT  
(WITH STAMP)

SHAMIM HYDER  
Act. General Manager (P&D)  
Sui Southern Gas Co. Ltd.

*[Signature]*  
GENERAL MANAGER  
APPROVAL BY DIVISION HEAD  
Senior General Manager  
Sui Southern Gas Co. Ltd.

Annexure-II

DELIVERY SCHEDULE:

The above quantity of Control Valves are to be shipped in accordance with the following delivery schedule:

| Shipment | Goods  | Arrival date Karachi Port<br>(for C&F contracts)      | FOB/FOB Delivery                                      |
|----------|--|---|---|
| 1        | As per schedule of Requirement<br>(Annexure-f) | 24 weeks from the date of opening of Letter of Credit | 20 weeks from the date of opening of Letter of Credit |

Annexure

*A. Salmaan*  
08/04/2006  
INDENTOR

*M. Iqbal*  
HEAD OF DEPARTMENT  
Sui Southern Gas Co. Ltd.

*M. Iqbal*  
APPROVAL OF DIVISION HEAD  
(WITH STAMP)  
MULAM MOFEN BUTT  
Senior General Manager (TS)  
Sui Southern Gas Co. Ltd.

Engr. AATIR SALMAN  
Manager  
Procurement  
Sui Southern Gas Co. Ltd.



**NOT FOR BIDDING PURPOSE**



SUI SOUTHERN GAS COMPANY LIMITED (SSGC)

NOT FOR BIDDING PURPOSE

TECHNICAL SPECIFICATION FOR  
CONTROL VALVES

RECEIVED  
22 FEB 2024  
ASGM (T) Office-KT

RECEIVED ASGM (TS)  
23 FEB 2024  
Sui Southern Gas Co. Ltd.

RECEIVED  
24 FEB 2024  
HSE & QA





### TABLE OF CONTENTS

|    |                                     |    |
|----|-------------------------------------|----|
| 1  | GENERAL                             | 3  |
| 2  | ABBREVIATIONS / SYMBOLS             | 5  |
| 3  | CODES, REGULATIONS AND STANDARDS    | 6  |
| 4  | GENERAL REQUIREMENTS                | 8  |
| 5  | MANDATORY REQUIREMENTS              | 9  |
| 6  | TECHNICAL REQUIREMENT               | 10 |
| 7  | START-UP & COMMISSIONING SPARES     | 19 |
| 8  | INSPECTION AND TESTING REQUIREMENTS | 20 |
| 9  | EXTERNAL SURFACE TREATMENT          | 28 |
| 10 | MARKING                             | 26 |
| 11 | DOCUMENTS                           | 27 |
| 12 | DRAWING & DESIGN CALCULATION        | 29 |
| 13 | LUBRICANT                           | 30 |
| 14 | INSPECTION CERTIFICATE              | 30 |
| 15 | RESERVATIONS                        | 30 |
| 16 | PACKING                             | 31 |

**NOT FOR BIDDING PURPOSE**

|             |                                       |   |
|-------------|---------------------------------------|---|
| Reviewed By | For: Prepared<br>DCM-P&O Transmission | For: Technical All.<br>Manager (Transmission) |
| Approved By | A/SGM/ITSE                            | A/SGM/Transmission                            |



**1 GENERAL****1.1 Scope**

- 1.1.1 The purpose of this specification is to describe the minimum functional and technical requirements for Control Valves suitable for natural gas transportation.
- 1.1.2 This specification is to be applied in conjunction with the supporting procurement data sheet.

**1.2 Definitions**

PURCHASER means OWNER and MANUFACTURER means CONTRACTOR / SUPPLIER / BIDDER / VENDOR. This definition shall apply throughout this specification.

**1.3 Errors or Omissions**

Any errors or omissions noted by the Manufacturer in this Specification shall be immediately brought to the attention of the Purchaser.

**1.4 Deviations**

All deviations to this Specification shall be brought to the knowledge of the Purchaser in the bid. All deviations made during the procurement, design, manufacturing, testing and inspection shall be with written approval of the Purchaser prior to execution of the work. Such deviations shall be shown in the documentation prepared by the Manufacturer.

**1.5 Conflicting Requirements**

- 1.5.1 In the event of conflict, inconsistency or difficulty between the contract's scope of work, this Specification, and National Codes & Standards referenced in this Specification, the Purchaser shall be consulted and a ruling, in writing, shall be obtained before any work is started.
- 1.5.2 Some requirements in this specification may be modified by specific requirements in the datasheet. In case of conflict, the specific requirements supersede this specification.

**1.6 Service Conditions**

- 1.6.1 The Vendor shall take special note of environmental conditions associated with an installation being situated in Pakistan. It shall be considered that the Control Valves shall be installed in the extreme conditions of heat, humidity and dust.
- 1.6.2 The equipment shall be able to withstand temperature of 50°C for minimum of 25 days without having any degradation and loss of operability.

|             |                                      |                                       |
|-------------|--------------------------------------|---------------------------------------|
| Reviewed By | Fajz Ahmad<br>DCM - P&O Transmission | Mishbah Ali<br>Manager (Transmission) |
| Approved By | A/SGM (T&E)                          | A/SGM (Transmission)                  |



## 1.6.3 Parameters:

|                   |                   |
|-------------------|-------------------|
| Temperature       | -10°C to 75°C     |
| Relative Humidity | 5% to 95%         |
| Wind Velocity     | Maximum 160 Km/Hr |

## 1.7 Hazardous Area Requirements

1.7.1 In general, all field mounted electrical components of control valves (if any) shall be certified for use in the related Hazardous Area Classification and Zones detailed in the Data Sheet.

1.7.2 It is a requirement that a full certification dossier is produced to ensure that all hazardous area components are correctly certified. The certification dossier is to cover all construction components. In addition to Instrument items.

1.7.3 Equipment intended for use in hazardous areas shall conform to the requirements and be selected and installed in accordance with the Codes and Standards referenced in Section 3 of this specification.

1.7.4 All field mounted electrical equipment shall be certified for use in the intended area in accordance with the applicable standards from one of the following bodies:

|       |  |
|-------|--|
| IEC   | International Electro-technical Commission         |
| ATEX  | European Union Directive for Explosive Atmospheres |
| UL/FM | Underwriters Laboratories / Factory Mutual         |

1.7.5 Certification from any other authority shall be considered on a case-by-case basis.

1.7.6 Equipment installed in a hazardous area shall be certified for use in Zone 0, 1 or 2, Gas Group IIA, IIB or IIC and surface temperature class as specified on the equipment specification/data sheet/drawings.

1.7.7 The hazardous area equipment shall be certified by a testing station in accordance with the Codes and Standards referenced in Section 3 and shall have a Certificate of Conformity (COC). This COC shall determine the suitability of the electrical equipment for installation in a hazardous area.

1.7.8 The area classification mentioned on equipment specification data sheet applies to the area surrounding the package unit. If Vendor installs equipment in enclosed or below grade areas, in a Zone 2 area, the enclosed space or below grade location becomes a Zone 1 area and equipment shall therefore meet the requirements of Zone 1 area.

1.7.9 Similarly, if Vendor installs equipment in enclosed or below grade areas, in a Zone 1 area, the enclosed space or below grade location becomes a Zone 0 area and equipment shall therefore, meet the requirements of Zone 0 area.

|              |                                     |                                    |
|--------------|-------------------------------------|------------------------------------|
| Reviewed By: | Faz Ahmed<br>DCM - PED Transmission | Muhammad<br>Manager (Transmission) |
| Approved By: | APSGV, TSI                          | APSGM (Transmission)               |





1.7-10. Other equipment intended for hazardous areas shall conform to the requirements and be selected and installed in accordance with the Codes and Standards in Section 3.

**2 ABBREVIATIONS / SYMBOLS**

2.1 For the purpose of this document, the words and expressions listed below shall have the meanings assigned to them as follows:

| ABBREVIATION | NAME                                      |
|--------------|---|
| ANSI         | American National Standard Institute      |
| API          | American Petroleum Institute              |
| ASME         | American Society of Mechanical Engineers  |
| ASTM         | American Society of Testing and Materials |
| BW           | Butt Welding                              |
| CS           | Carbon Steel                              |
| D            | Diameter                                  |
| IEC          | International Electrotechnical Commission |
| Max          | Maximum                                   |
| MTC          | Material Test Certificate                 |
| PTFE         | Polytetrafluoroethylene                   |
| RF           | Raised Face                               |
| RTJ          | Ring Type Joint                           |
| SS           | Stainless Steel                           |
| WCB          | Wrought Carbon with Grade B               |
| WCC          | Wrought Carbon with Grade C               |

|             |                                      |                                       |
|-------------|--------------------------------------|---------------------------------------|
| Reviewed By | Fahz Ahmed<br>DCM - P&O Transmission | Mahmoud Al-<br>Mansour (Transmission) |
| Approved By | A/SGM (TS)                           | A/SGM (Transmission)                  |



### 3 CODES, REGULATIONS AND STANDARDS

3.1. Manufacturer shall meet or exceed the requirements of the latest edition of the following applicable codes, regulations and standards, except as superseded herein.

- ASME B31.8; Gas Transmission and Distribution Piping Systems
- ASME Section VIII, Div. -1, Pressure Vessels
- ASME Section IX, Qualification Standard for Welding and Brazing Procedures, Welders, Brazers and Welding and Brazing Operators
- ASME Section V, Non-Destructive Examination
- ASME B16.5, Steel Pipe Flanges and Flanged Fittings
- ASME B16.47, Large Diameter Steel Flanges (NPS 26 through NPS 60)
- ASME B16.20, Metallic Gaskets for Pipe Flanges - Ring Joint, Spiral Wound
- ASME B16.21, Nonmetallic Flat Gaskets for Pipe Flanges
- ASME B16.9, Wrought Steel Butt-Welding Fittings
- ASME B16.10, Face-to-Face and End-to-End Dimensions of Valves
- ASME B16.11, Steel Socket Weld Fittings
- ASME B16.34, Valves - Flanged, Threaded and Welding End
- ASME B36.10M, Welded and Seamless Wrought Steel Pipe
- ASME B36.19M, Stainless Steel Pipe
- ASME B40.100, Pressure Gauge and Gauge Attachments
- API 598, Valve Inspection and Testing
- API 5L, Specification for Seamless and Electrically Welded Steel Pipe
- ASTM Standards (as applicable)
- BS 1873, Steel Globe and Globe stop & Check Valves (Flanged & Butt welding ends)
- BS 5352, Steel wedge Gate, Globe and Check Valves (50 mm and smaller)
- BS 6755, Testing of valves Part 1, Production pressure testing requirements
- BS 6755, Testing of valves Part 2, Specification for fire type testing requirements
- ANSI/ISA 75, Industrial-Process Control Valves
- ANSI/FCI 70.2, Control Valve Seat Leakage
- ANSI/ISA 75.01.01, Industrial-Process Control Valves - Part 2 - Low Capacity - Sizing Equations for Fluid Flow under installed conditions
- ANSI/ISA 75.02.01, Control Valve Capacity Test Procedure
- ANSI/ISA 75.05.01, Control Valves Terminology

|             |                                      |  |
|-------------|--------------------------------------|--|
| Reviewed By | Fahd Ahmed<br>DCM - P&O Transmission | M. S. Khatib<br>Manager (Transmission) |
| Approved By | A. S. M. (S)                         | M. S. Khatib<br>M. S. Khatib           |





- ANSI/ISA 75.08.01, Face-to-Face Dimensions for Integral Flanged Globe Style Control Valves Bodies (Classes 125, 150, 250, 300 and 600)
- ANSI/ISA 75.08.06, Face-to-Face Dimensions for Flanged Globe Style Control Valve Bodies (Classes 900, 1500 and 2500)
- ANSI/ISA 75.08.08, Face-to-Centerline Dimensions for Flanged Globe Style Angle Control Valve Bodies (Classes 150, 300 and 600)
- ANSI/ISA 75.11.01, Inherent Flow Characteristics and Rangeability of Control Valves
- ANSI/ISA 75.19.01, Hydrostatic Testing of Control Valves
- ANSI/ISA 75.17, Control Valve Aerodynamic Noise Prediction
- ISA 88.25.23, Consideration for Evaluating Control Valve Cavitation
- ANSI/NACE MR0175/ISO 15156, Petroleum and Natural Gas Industries Materials for use in H<sub>2</sub>S containing environments in Oil & Gas Production
- ANSI/NACE MR0103/ISO 17945, Metallic Materials resistant to Sulfide Stress Cracking in corrosive petroleum refining environments
- NACE TM0177, Laboratory Testing of metals for resistance to sulfide stress cracking and stress corrosion cracking in H<sub>2</sub>S environments
- IEC 60079-0, Explosive atmospheres - Part 0: Equipment - General Requirements
- IEC 60079-1, Electrical apparatus for Explosive Atmospheres Part 1: Equipment protection by Flameproof Enclosures "d"
- IEC 60079-7, Electrical Apparatus for Explosive Atmospheres Part 7: Equipment protection by Increased Safety "e"
- IEC 60079-11, Explosive Atmospheres Part 11: Equipment protection by Intrinsic Safety "i"
- IEC 60529, Degrees of Protection Provided by Enclosures (IP Code)
- IEC 60534 (All parts), Industrial-process control valves
- IEC 60947-5-2, Low-voltage switchgear and controlgear - Control circuit devices and switching elements - Proximity switches
- IEC 61000 (All parts), Electromagnetic compatibility (EMC)
- MSS SP-25, Standard Marking System for Valves, Fittings, and Unions
- MSS SP-55, Quality Standard for Steel Castings for Valves, Flanges, Fittings and Other Piping Components
- MSS SP-91, Guidelines for Manual Operation of Valves

NOT FOR BIDDING PURPOSE

|             |  |                                       |
|-------------|--|---------------------------------------|
| Reviewed By | Felix Ahmed<br>DCM - P&ID Transmission | Approved By<br>Manager (Transmission) |
| Approved By | Waseem                                 | Approved Transmission                 |





#### 4 GENERAL REQUIREMENTS

4.1 This specification covers control valves intended for use in the natural gas service with design rating as specified in the Datasheet and temperature between -10°C and +75°C.

4.2 The Supplier shall be responsible for the design, manufacture, inspection, operability and fitness for service of the valves and actuators supplied under this Specification. Dimensions of all the valves shall conform to the dimensions for such valves as per manufacturer's standard.

4.3 The Bidder and the Supplier covered by this Specification shall provide the following particulars of the equipment quoted or ordered:

- Make, type or series
- Pressure class
- Nominal diameter, bore/port area
- Types of ends (flanged or welding or threaded)
- Full details of materials
- Type of coating (above ground service)
- Manufacturer's Mark

#### 4.4 Original Technical Literature

4.4.1 The Bidder shall submit with his bid detailed printed technical literature (in original) giving a description of the valve design and mode of operation, the materials used for each valve quoted to this specification.

4.4.2 Besides above, the bidder shall submit technical literature for the quoted actuator, positioner, pressure controller and instrument gas supply regulator and filter with bid documents.

4.4.3 Bids not in conformity to this requirement are liable for rejection. Each valve and actuator shall be fit for all year service on site.

#### 4.5 Sales Track Records

4.5.1 The Bidder shall submit the supporting documents of sales track record for the offered control valves, including copies of purchase order & satisfied certificate of operations of five (5) different end users related to Oil & Gas sector with similar requirement along with their email (email address of end user's company domain and not the commercial domain like Yahoo, Gmail, or Hotmail, etc.), fax telephone, address and name of persons to contact to whom they have supplied the offered control valves.

|             |                                      |                                       |
|-------------|--------------------------------------|---------------------------------------|
| Reviewed By | Egiz Ahmed<br>OCM - PSD Transmission | Reviewed At<br>Manager (Transmission) |
| Approved By | A/SGM (ITM)                          | A/SGM (Transmission)                  |



- within the last five (05) years and have been successfully installed and operated.
- 4.5.2 Simply submitting a list of customers to whom the Manufacturer has been supplying the offered control valves will not meet the intent and purpose of this requirement. Failure to comply with this requirement may result in rejection of the bid.
- 4.5.3 Following data should be included which will be considered during comparative evaluation of bids:
- Failure rate for each Failure Mode
  - Repair time
  - Cost of spares for the given Failure Mode
  - Cost of data
- 4.6 Inspection and testing shall be carried out by the Supplier at the manufacturing plant. All control valves shall be visually examined for conformity to Purchaser's specifications and tested under the applicable codes and standards to make sure they conform to their intended use.
- 4.7 The Supplier shall submit copies of Inspection and Material Test Certificates (MTC) to the Purchaser after placement of order and before manufacturing process. The Purchaser has right to reject the assignment if bidder has failed to provide MTC.

## 5 MANDATORY REQUIREMENTS

- 5.1 Bids are invited directly from the Manufacturer or their authorized local agents in Pakistan. Beside local agent, principle involvement would be acceptable as regional Sales Representative, if applicable. However, in any case, bids from stockist and Brokers will be rejected.
- 5.2 The local agents/suppliers are required to submit valid authorization letter from the Manufacturer failing which will make bid non-compliant.
- 5.3 The bidder shall provide a clear and concise clause for clause compliance or exception (with detail) commentary to these technical specifications duly signed and stamped by Manufacturer (compulsory) along with Local Agent/Principal which is mandatory for technical evaluation, failing to submit this document may be considered non responsive.
- 5.4 Before manufacturing any valve under this specification, the Supplier shall supply to the Purchaser drawings and a detailed description of the materials, fabrication methods,

|              |                                      |  |
|--------------|--------------------------------------|--|
| Reviewed By: | Fazl Ahmed<br>DCM - P&O / Production | Asif Raza Ali<br>Manager (Manufacturing) |
| Approved By: | A/SGM (IS)                           | A/SGM (Manufacturing)                    |





and testing procedures applicable to the valves to be manufactured. The documents related to the fabrication of the valve shall be reviewed by the Purchaser. The said review however shall in no way relieve the Supplier from any responsibilities and liabilities in connection with the Goods ordered and the specified delivery date.

5.5 The bidder shall quote and provide price list of recommended spares with Part # for the control valves for two years of operation along with the bidding document. The item wise break up for each Control Valve should be provided separately.

5.6 Each valve shall comply with the requirement of this specification. Valves which do not comply with the requirements of this specification are liable for rejection.

## 6 TECHNICAL REQUIREMENT

### 6.1 General

6.1.1 For complete technical specification, this specification shall be read in conjunction with the Datasheet.

6.1.2 This specification covers pressure control valves intended for use in the natural gas application as specified in the Datasheet.

6.1.3 Valves and associated parts and accessories shall be designed and constructed for the services and conditions specified in this Specification and the Datasheet.

6.1.4 The applicable codes and standards (latest editions) as given in Section 3, shall apply to the valves/operators manufactured and applied in accordance with this Specification and attached Datasheet.

6.1.5 The preferred valve type for control valve shall be Globe. The Contractor shall take permission of Owner if any other type is selected by the Contractor.

6.1.6 Contractor shall offer standard control valve models unless the process service conditions are so severe that special control valves are needed.

6.1.7 The Contractor shall be responsible for the design, manufacture, inspection, operability and fitness for service of the valves and integral parts supplied under this Specification.

6.1.8 The Control Valves shall be supplied in fully assembled and tested complete with actuators, positioner, instrument air supply regulator, filters and with stainless steel tubing and fitting.

6.1.9 Each valve shall be supplied with lubricant, fit for service on site. The lubricant shall resist dissolving, gumming or chemical change in service. Sealing shall be resistant to aromatic hydrocarbons.

6.1.10 Valves, Actuators, Positioner, filter regulators shall be tested before delivery of the

|             |                                       |                                      |
|-------------|---------------------------------------|--------------------------------------|
| Reviewed By | Faiz Ahmed,<br>DCM - E&E Transmission | Mehmet Ali<br>Manager (Transmission) |
| Approved By | A/SGM (E&E)                           | A/SGM (Transmission)                 |



valves. Where no specific Manufacturer or type is specified, the Manufacturer shall select a suitable type.

6.1.11 Control Valves and accessories shall preferably be supplied by the same Vendor/Manufacturer; however if a control valve is provided with an actuator and/or accessories from other source, but supplied as part of the control valve requisition, the responsibility of the overall valve assembly (valve complete with actuator and/or accessories) shall be with the Contractor.

6.1.12 The actuator wherever specified in this specification is an integral part of the valve and, as such shall be installed and tested before delivery of the valve. Where no specific manufacturer or type is specified, the manufacturer shall select a suitable type. The manufacturer shall test all functions of the valve and the operating equipment.

6.1.13 Each valve shall be so designed that any failure of the actuator will not affect any other part of the valve and the malfunction of the actuator shall be limited to these parts and any such defective component may be replaced without removing the valve from service.

6.1.14 Valve selection shall consider all possible effect of erosion, cavitation and noise.

6.1.15 Body rating and flange rating and facing shall be in accordance with the piping class specification for the associated piping.

6.1.16 Dimensions of all the valves shall conform to the dimensions for such valves as per manufacturer's standard.

6.1.17 Flow direction shall be stamped or cast on the body of all valves.

6.1.18 Contractor shall provide the following particulars of the Control Valve and integral part quoted or ordered:

- Make, type or series
- Pressure class
- Nominal diameter, bore/port area
- Types of ends (flanged or welding or threaded)
- Full details of materials
- Type of coating (above ground service)
- Manufacturer's Mark

## 6.2 Sizing (Valve Capacity)

6.2.1 Required valve capacities will be referred to in terms of Cv coefficients. Cv for these purposes will be defined as the GPM of water that the valve will pass with 1.0 PSI pressure drop at rated stroke.

|             |                                      |                                     |
|-------------|--------------------------------------|-------------------------------------|
| Reviewed By | Faiz Ahmed<br>QCM - P&D Transmission | Munir Ali<br>Manager (Transmission) |
| Approved By | A/SGM (SI)                           | A/SGM (Transmission)                |





SSGC

- 6.2.2 The Cv value shall be calculated in accordance with IEC 60534-2-1 Industrial-Process Control Valves - Part 2-1: Flow Capacity Using Equations for Fluid Flow under installed Conditions.
- 6.2.3 Valve sizing calculations shall be submitted with the bill to the purchaser for approval prior to start of valve fabrication.
- 6.2.4 The Control Valves shall be sized in accordance with ISA 75 and IEC 60534.
- 6.2.5 Control valves shall be sized by considering both maximum and minimum conditions, and other possible condition within given parameters and provide the range ability envelope for the selected valves.
- 6.2.6 Process conditions for use in the design/sizing of each Control Valve shall be as specified under the datasheet/specification of each Control Valve.
- 6.2.7 The Control Valve size shall not be less than 50% of the line size.
- 6.2.8 Generally valves shall be selected to have a minimum opening of 20% and maximum valve opening of 95% flow, or shall be within the Vendor's minimum throttling Cv recommendation.
- 6.2.9 Control valve size provided in the specification or datasheet shall be considered as tentative. Control valve vendor shall finalize the Control Valve size based on its sizing calculation.
- 6.3. Noise
  - 6.3.1 The valve Vendor shall calculate noise levels in accordance with IEC 60534-8-3 and IEC 60534-8-4.
  - 6.3.2 The limit for noise generated by control valves shall be 85dBA or less, as measured at 1 meter from the valve for any flow condition.
  - 6.3.3 The noise levels shall be calculated at different flow rates (including minimum, normal, maximum flow rates as well as start-up and shut-down) to determine the worst-case conditions. Where the valve differential pressure changes significantly with flow rate a noise calculation shall be made at the rate at which the product of mass flow and differential pressure is maximum.
  - 6.3.4 If the calculated noise level of a standard control valve exceeds the allowable limit, a control valve with special low-noise internals (such as welded control trim) should be selected.
  - 6.3.5 Control valve operation above 90 dBA for any time period shall be avoided!
  - 6.3.6 For control valves with calculated noise levels higher than the allowed limit, Vendor should quote a standard version valve and a low noise valve. Calculated noise levels for

|              |                                      |                                       |
|--------------|--------------------------------------|---------------------------------------|
| Reviewed By: | Far Ahmed<br>DCM - P&ID Transmission | Mehboob Ali<br>Manager (Transmission) |
| Approved By: | A/SGM (IS)                           | Asst. Mgr. (Transmission)             |



- both of these valves, shall be stated in the quotation for comparative analysis.
- 6.3.7 In extreme noise conditions, the Contractor shall provide technical recommendations to the Purchaser.
- 6.4 Valve Characteristic
- 6.4.1 Main characteristics are commonly applied: equal percentage, linear and quick opening.
- 6.4.2 The first choice for valve characteristics shall be equal percentage.
- 6.4.3 Equal percentage characteristics are desirable on loops that have variation in valve pressure drops, fast pressure control loops, and most flow control loops. In processes where no guidelines are available, equal percentage is usually the best choice.
- 6.4.4 Linear characteristics shall be considered for most level control loops and loops where the measurement is linear and the variation in the pressure drop across the control valve is small or constant.
- 6.4.5 Quick opening characteristics shall be considered primarily for on-off service.
- 6.5 Body Construction & Material
- 6.5.1 Valve Body
- 6.5.1.1 The preferred valve type for control valves shall be Globe. The Contractor shall take permission of Purchaser if another type is selected by the Contractor.
- 6.5.1.2 Globe valves shall be a single piece casting or forged body with a bolted bonnet design.
- 6.5.1.3 Globe valves shall be a single-port design.
- 6.5.1.4 Castings shall be free from injurious blow holes, porosity, shrinkage faults, cracks or other defects. Castings with defects that were plugged, welded, burned or impregnated are unacceptable. Wall thickness shall meet or exceed minimum requirements of applicable codes.
- 6.5.1.5 Internal passage ways shall offer minimum restriction to flow. Pockets and shoulders tending to create turbulence or solids accumulation shall be minimized.
- 6.5.1.6 Bonnets and blind heads shall be of the same material as the valve body and of integral or bolted type construction with fully retained gasketing. Threaded bonnets are not acceptable.
- 6.5.1.7 The pressure rating of the valve body shall be in accordance with the piping class or shall be greater than or equal to the pressure rating of the connected piping.
- 6.5.1.8 The use of line-size bodies with reduced trims shall be compared economically with the cost of an installation involving a smaller body size and piping reducers. In all

|             |                                     |                        |
|-------------|-------------------------------------|------------------------|
| Reviewed By | Faz Ahmed<br>DCM - P&D Transmission | Manager (Transmission) |
| Approved By | A/SGM (IT)                          | SGM (Transmission)     |



cases, the use of body sizes less than half the line size shall be avoided wherever possible.

6.5.1.9 When standard bonnet packing cannot meet the process design temperature limits, extension bonnet design may be used.

6.5.1.10 Each valve including actuator shall be fit for horizontal installation.

6.5.1.11 Lugs shall be welded to the body of each valve with a nominal diameter exceeding 10" for handling and lifting equipment transportation and installation.

6.5.1.12 Valves shall be fitted with manufacturer standard support ribs / legs unless otherwise specified in the attached data sheet.

6.5.1.13 Non-metallic parts and elements such as packing, seal, sealing, injectable material, sealants and lubricants as required shall be suitable for the service they are intended for.

#### 6.5.2 End Connections

6.5.2.1 Preferably, Control valves shall have flanged connections, unless otherwise specified in the datasheet. All flanges shall be in accordance with ASME B16.5.

6.5.2.2 The flange ANSI rating class shall be in accordance with the piping class unless otherwise specified in the data sheet.

6.5.2.3 If beveled butt welding ends are specified, the chemical composition of the weld ends shall meet the following requirements:

|                            |       |
|----------------------------|-------|
| Maximum Carbon contents    | 0.23% |
| Maximum Silicon contents   | 0.40% |
| Maximum Manganese contents | 1.50% |

6.5.2.4 The welding ends shall have dimension and strength properties equivalent to those of the line pipe in accordance with Figure 4 or 1-5 of ASME B31.3, Appendix 1.

6.5.2.5 Welding ends shall be free from defects such as inclusions which could impair the quality of the welds for a distance of not less than 2" from the bevel. Compliance with this provision shall be assured by appropriate testing.

#### 6.5.3 Face-to-Face Dimensions

6.5.3.1 The face to face dimensions of flanged globe bodied valves shall comply with IEC 60534-3.

#### 6.5.4 Seat Leakage

6.5.4.1 The seat leakage test shall be in accordance with ANSI/FCI 70.2 and IEC 60534-1, Standard for control valve leakage. All control valves shall have a leakage class of Class IV minimum.

|             |                                       |                                       |
|-------------|---------------------------------------|---------------------------------------|
| Reviewed By | Faiz Ahmad<br>OEM - P&ID Transmission | Mehboob Ali<br>Manager (Transmission) |
| Approved By | A/SGM (P&ID)                          | A/SGM (Transmission)                  |





6.5.5 Material

6.5.5.1 The material (selection of the body (including bonnet and/or bottom flange), external bolts, studs and nuts, shall be in accordance with the project piping class.

6.5.5.2 Bonnet and blind heads shall be of the same material as the valve body and of integral or bolted type construction with fully retained gasketing. Threaded bonnets are not acceptable.

6.5.5.3 Materials of construction for valve trim (internal components of a valve consisting of plug, seat rings and stem) parts shall be selected to meet the requirements as shall be described in the respective valve datasheet. Contractor shall confirm the availability of trim material.

6.5.5.4 The trim material for the control valves shall be minimum 316SS and shall be suitable with the process conditions.

6.5.5.5 The Contractor is responsible for the design and construction of the supplied control valves for the services and conditions specified in the requisition.

6.5.5.6 All parts of the valve which are exposed to the surrounding atmosphere shall have a corrosion resistant and protective coating.

6.5.5.7 All identification and/or instruction plates on the valve, actuator and accessories shall be of stainless steel and be attached with screws or rivets.

6.5.6 Flow Direction

6.5.6.1 The normal flow direction of all isolation valves shall be marked with an arrow as follows:

- permanently cast on the valve body,
- engraved on the valve body, or
- on a stainless steel plate riveted to the valve body.

6.6 Actuator

6.6.1 General

6.6.1.1 Direct acting, spring return, pneumatic diaphragm type shall be the primary choice for control valve actuators, unless otherwise specified in the attached datasheet.

6.6.1.2 Actuators shall be sized for maximum shut-off differential pressure and minimum control medium supply pressure.

6.6.1.3 The valve actuator shall be designed so that the valve fails closed on loss of hydraulic/gas supply pressure at failure of Control medium-deriving Solenoids, etc.

6.6.1.4 Natural Gas shall be the primary choice for control medium for control valve actuators, unless otherwise specified in the attached datasheet.

|             |                                      |  |
|-------------|--------------------------------------|--|
| Reviewed By | Falzi Ahmed<br>DOM - P&ID Inspection | Mehboob Ali<br>Manager (Manufacturing) |
| Approved By | A/SGM (IS)                           | A/SGM (Manufacturing)                  |





- 6.6.1.5 Actuators shall have a valve travel indicator and spring adjuster.
- 6.6.1.6 Actuators internals and actuator accessories shall be suitable for Natural gas service.

6.6.2 Yoke and Stem

- 6.6.2.1 Yokes shall be of suitable rigid material for open type construction and heavy duty.
- 6.6.2.2 Actuator stems shall have adequate strength to withstand maximum developed thrust of actuator.

6.6.2.3 All valves shall be equipped with a valve stem travel indicator where so feasible. The indicator on valves having non-linear flow characteristics shall show percent of maximum capacity for the corresponding percent of travel.

6.6.3 Diaphragm Type Actuators

6.6.3.1 Diaphragm cases shall be of steel construction with suitable corrosion protection for a refinery atmosphere.

6.6.3.2 Diaphragms shall be of molded age resistant material suitable for withstanding the pressure and chemical characteristics of the operating medium over a wide range of ambient temperatures.

6.6.3.3 Diaphragm effective area shall remain essentially constant throughout the full stroke. The required thrust to stroke the valve shall be accomplished by applying a 6-30 PSIA air signal to this effective area. When the Manufacturer's largest diaphragm area available does not produce sufficient thrust with a 6-30 PSIA signal, a multiplier thereof may be used. Other multipliers are not to be used in order to undersize actuator.

6.6.4 Hand Operated Actuators

Hand wheels where required shall be of the non-rising type with fine pitch threads for precise valve plug positioning. All threaded parts shall be precision fitted for minimum backlash.

6.7 Accessories

6.7.1 Air Filter Regulator Set

Whenever an independent air consuming device such as a programmer, transducer, multiplying relay, pressure control unit, etc. is supplied, the Contractor shall include an air filter regulator set designed for 0 to 100 PSIA inlet pressure.

|              |                                      |   |
|--------------|--------------------------------------|---|
| Reviewed By: | Faiz Ahmed<br>DCM - F&E Transmission | Amr Hatab Alt<br>Manager (Transmission) |
| Approved By: | A/SCM (F&E)                          | A/SEM (Transmission)                    |



## 6.7.2 Gauges

Gauges of suitable range shall be furnished for air supply, input signal and output signals of all accessory pneumatic equipment. Where no accessories are required, a 0-100 PSI gauge shall be mounted on the valve diaphragm or tagged and shipped separately for mounting on valve diaphragm. Unless noted otherwise, gauges are to be calibrated in English Units (PSI).

## 6.7.3 Positioners

6.7.3.1 Control valve shall be supplied with pre-installed valve positioner mounted on control valve as single assembly.

6.7.3.2 Valve positioner relates the input signal and the valve position, and will provide any output pressure to the actuator to satisfy this relationship, according to the requirements of the valve, and within the limitations of the maximum supply pressure.

6.7.3.3 A positioner may be used as a signal amplifier or booster. It accepts a low pressure air control signal and by using its own higher pressure input, multiplies this to provide a higher pressure output air signal to the actuator diaphragm, if required, to ensure that the valve reaches the desired position.

6.7.3.4 The positioner can either be electro/pneumatic (I/P) or pneumatic type (P/P), as specified in the attached Data Sheet.

6.7.3.5 Positioner from renowned vendor shall be supplied.

6.7.3.6 They shall be either yoke mounted, flange or integral force balance type and they shall not be affected mechanically or functionally by any vibration encountered when so mounted.

6.7.3.7 For high vibration prone area, contactless type magnetic positioners should be selected.

6.7.3.8 Positioner shall be fitted with gauges to indicate both input & output pressure.

6.7.3.9 Valve positioners shall be direct acting type; however, they shall be easily converted from direct to reverse acting.

6.7.3.10 Air connection size shall be compatible with the control ports of actuator and shall be of Vendor/manufacturer standard.

6.7.3.11 Positioner shall be rated for IP-65 weather protection.

6.7.3.12 Electro/Pneumatic (I/P) Positioner

6.7.3.12.1 Positioner shall be Digital "Smart" control valve positioners with HART Communications as standard; use of other types such as Analogue I/P (Electro-pneumatic) will require prior approval of Purchaser and will only be considered if

|             |                                     |                                      |
|-------------|-------------------------------------|--------------------------------------|
| Reviewed By | Fahim Ahmad<br>D/AF-ERD Transistion | Mehboob Ali<br>Manager (Fabrication) |
| Approved By | A/SGM (CS)                          | A/SGM (Fabrication)                  |



- Digital positioners are not available for the given application.
- 6.7.3.12.2 The device shall utilize two-wire, 4-20 mA HART, 24VDC loop-powered and.
- 6.7.3.13.1 The device shall provide self-diagnostics for the positioner and control valve through HART to allow calibration, configuration and on-line diagnostics taking place in the respective control system.
- 6.7.3.12.4 The digital positioner shall have a diagnostic feature to detect loss of power or air pressure.
- 6.7.3.12.5 Electrical classification for hazardous area will be specified in the datasheet.
- 6.7.3.11 Pneumatic (P/P) Positioner
- 6.7.3.13.1 A Pneumatic Positioner shall be used where there is unavailability of electrical power or as specified in the datasheet.
- 6.7.3.13.2 A Pneumatic Valve Positioner shall receive a pneumatic signal (typically 3-30 psig) as indicated in Data Sheet) from a pneumatic pressure controller.
- 6.7.3.13.3 Set Point of the Field Mounted Pneumatic Indicating Pressure controller shall be manually adjustable over full range of scale.
- 6.7.3.13.4 Field shall be selectable for Direct / Reverse Action.
- 6.7.3.13.5 Required Stainless Steel Bourdon Tube and Bellows OR as specified in Statement of Requirement.
- 6.7.3.13.6 Control Action shall be Proportional + Integral.
- 6.7.3.13.7 Required Manual Loader built in.
- 6.7.3.13.8 Required Auto/Manual Control Mode Selector Switch.
- 6.7.3.13.9 Required Auto/Manual Output differential indicator for bump-less transfer of control mode.
- 6.7.3.13.10 Required complete Instruments Air Supply System including high pressure regulator & filter and low pressure regulator & filter.
- 6.7.3.13.11 Bourdon tube range required to 1500 psig as specified in Statement of Requirement.
- 6.7.4 Limit Switches
- 6.7.4.1 Where limits switches are specified, they shall be supplied and fitted with the control valve and shall be wired to a junction box suitable for the environment and hazardous area classification in which the valve will be installed. The junction box shall be mounted on the valve assembly.
- 6.7.4.2 Electrical Limit shall be supplied from authorized Vendor.
- 6.7.4.3 Contact rating shall be 2-Amp minimum at 24V D.C.

|             |                                       |                                     |
|-------------|---------------------------------------|-------------------------------------|
| Reviewed By | Fais Ahmed<br>DCM - P&ID Transmission | Atefboabd<br>Manager (Transmission) |
| Approved By | A/SGM (TS)                            | A/SGM (Transmission)                |





SSGC

6.7.5. Quick Exhaust Valve.

6.7.5.1 In general, valve stroking time should be achieved by correct actuator design and without external speed controlling accessories.

6.7.5.2 Quick exhaust valves may be provided for services which require the control valve to move to its designated failure position faster than calculated stroking time.

6.7.5.3 The noise level generated during operation of the silencer shall not exceed the maximum allowable noise level specified for the control valve trim.

6.7.5.4 Quick exhaust valves shall have Bug Screens to prevent blockage from insects.

6.7.5.5 Quick exhaust valves shall be fitted directly to the port of the actuator.

6.7.6. Volume Booster

6.7.6.1 Volume boosters shall be provided if needed to achieve the stroking times specified. Volume boosters for pneumatic actuators shall be of the high capacity type with fast throttling facilities to control the required capacity.

6.7.6.2 Volume booster shall be fitted directly on the actuator and be provided with a separate pneumatic supply connection, not sharing the same filter regulator. The response of the volume booster shall be adjustable by means of an adjustment screw to match the loop requirements and can be locked in position or permanently sealed.

6.7.6.3 The noise level generated during operation of the silencer shall not exceed the maximum allowable noise level specified for the control valve trim.

6.7.7 Identification

Valve shall have the following identifying information:

- Purchase Order Number
- Equipment Identification Number (Tag Number)
- Pressure rating, material and size of valve and flow direction on the valve body.
- Manufacturer's name, model, serial number, valve action, characteristic, stem travel, Cv value, material of construction, size (height and trim) type of plug and spring range, maximum working pressure of the stem, etc. on the nameplate.

7 START-UP & COMMISSIONING SPARES

7.1 A listing of recommended spare parts for construction, Start-up/Commissioning and for two years operations shall be provided by the Vendor and will be detailed and included in the bid.

7.2 Any spare parts for the Control Valves used during the Warranty Period shall be replenished at the Vendor's expense.

|             |  |                                     |
|-------------|--|-------------------------------------|
| Reviewed By | Fazl Ahmad,<br>DCM - P&ID Transmission | M. J. Ali<br>Manager (Transmission) |
| Approved By | A/SGM (TS)                             | A/SGM (Transmission)                |





### 8 INSPECTION AND TESTING REQUIREMENTS

8.1 The valves shall be inspected and tested for the following items as minimum requirement and in accordance with applicable codes and Manufacturer's inspection and quality control programmes:

- Appearance Inspection (Workmanship)
- Visual Inspection
- Dimensional Inspection
- Welding and Non Destructive Testing
- Pressure Tests
- Seat Leakage Test
- Fugitive Emissions Test
- Functional Operational Test with Actuator installed

8.2 The Purchaser shall specify in the purchase order the intention to inspect valves and witness tests and examinations at the valve manufacturer's plant.

8.3 The Purchaser's representative/inspector shall have access to any part of the plant along with the area outside the manufacturer's plant which is responsible for fabrication of pressure containing parts of valves whenever work on the order is under way.


8.4 The valve manufacturer shall notify the Purchaser prior to the required valve testing and any specified supplementary inspections or examinations addressing the matters stated in the purchase order or as mutually agreed with the Purchaser.

8.5 The extent of inspection may be specified in the purchase order and, unless otherwise indicated, will be limited to the extent as mentioned in Section 4.4 of API 598.

8.6 If requested by the Purchaser, the Manufacturer shall provide Material Test Reports (MTRs) for specific valve components.

#### 8.7 Appearance Inspection (Workmanship)

- 8.7.1 Appearance inspection shall be done on all accessible surfaces of the valves.
- 8.7.2 Both inside and outside surfaces of casting material shall be free from harmful blowholes, fins, seizures of sand scales, sand inclusions and cracks and shall be in accordance with MSS-SP-55.
- 8.7.3 Machined surfaces shall be free from injurious defects to use and rust and finished condition shall be as per acceptable standards.

|             |  |  |
|-------------|--|--|
| Reviewed By | Fazl Ahmed<br>DCM - P&ID Transmission<br> | Mehcobe Ali<br>Manager (Transmission)<br> |
| Approved By | A/S&M (TS)<br>                            | A/S&M (Transmission)<br>                  |





**8.8 Visual Inspection**

The visual inspection is a mandatory test which shall be performed on all control valves. It is intended to ensure that all accessories are assembled and identified correctly. The paint finish is also checked.

**8.9 Dimensional Inspection**

**8.9.1** The face-to-face dimensions of flanged globe body control valves shall be as given in the relevant standard ASME B16.10 and IEC 60534-3-2.

**8.9.2** All dimensions including overall height shall be as shown on the Vendor's drawings.

**8.9.3** The flange face finish shall be in accordance with ASME B16.5 or as specified by the Purchaser.

**8.9.4** Dimensional inspection shall be done by using appropriate measuring instruments.

**8.9.5** Dimensional inspection shall confirm the parallelism, rectangularity and face to face dimensions, bore diameter etc. All other dimensions including actuators shall comply with the approved drawings.

**8.10 Welding and Non Destructive Testing**

**8.10.1** All factory welds shall be made in accordance with the requirements of the American Welding Society and ASME Section VIII, Division I.

**8.10.2** Procedure tests covering strength, hardness and toughness shall be made to show the fitness of the welding procedure used for factory welds shall be made by welders qualified in the procedure used, who have passed an appropriate welder qualification test. All welding operations shall be supervised by a qualified welding supervisor.

**8.10.3** All welds shall be inspected visually by the welding supervisor. Welds, welding ends and any repair welds shall be tested by appropriate non-destructive methods to demonstrate to the welding supervisor that all welds, welding ends and repair welds meet the requirements of these specifications.

**8.10.4** Without limitation of the generality of the foregoing, welds parallel to the longitudinal axis of the valves, and 10% of all circumferential welds shall be inspected by radiographic methods. Each welding end shall be tested by dye penetrant methods and each repair weld shall be tested by radiographic or ultrasonic methods. The welding ends of valves shall be solidly sound and shall not be cause of failure in radiographic examination of the joints with piping.

**8.10.5** Defects shall be removed, cleaned and prepared for inspection by magnetic particle or dye penetrant method to verify complete removal of the defect. Weld repair methods shall be in accordance with the approved welding procedures. All weld repairs

|             |                                     |                                      |
|-------------|-------------------------------------|--------------------------------------|
| Reviewed By | Faz Ahmed<br>DCM - P&C Transmission | MAR006 All<br>Manager (Transmission) |
| Approved By | A/SGM (P)                           | A/SGM (Transmission)                 |



to pressure containing parts shall be heat treated.

8.10.6 No weld in the body of any valve shall contain any lack of fusion. If feasible, body welds shall consist of both, external and internal runs. Each weld shall be smooth and free from cracks. No weld shall contain any major inclusions. The height of the weld above the surface of the parent metal shall not exceed 1/8 inch. Undercuts shall not exceed 10% of the wall thickness or 3/64 inch, whichever is lower. Each welded joint shall be completely filled. No weld shall be thicker than the wall thickness of the parent metal.

8.10.7 Magnetic particle or dye penetrant techniques shall be employed to test:

Pressure containing components smaller than 2 inch welded to other pressure components.

- Welds joining non-pressure components such as lifting lugs to pressure components.

- Weld build ups such as overlays.

8.10.8 Radiographic, ultrasonic or both techniques shall be used for full volume inspection of:

- Pressure containing fabrication welds for 2 inch or larger components.

- Weld repair to these components.

- Major weld repairs to pressure containing components.

8.10.9 Valve bodies of welded construction shall be annealed if they include wall thickness of 1.20 inches or higher. All cast valve bodies, irrespective of wall thickness, shall be annealed. The annealing process shall be carried out after all repair welds, if any, have been completed.

8.10.10 The inner surface of all steel castings shall be inspected by magnetic particle methods after cleaning. Machined surfaces of cast components and seat ring surfaces shall, after machining, be inspected by magnetic particle or dye penetration methods. All items shall be free of defects.

### 8.11 Pressure Tests

8.11.1 Pressure tests shall be performed by the valve manufacturer at the valve manufacturer's plant or at a facility mutually agreeable to both the manufacturer and Purchaser.

8.11.2 The equipment used to perform the required pressure tests shall not apply external forces that affect seat or body seal leakage.

8.11.3 Required protective coatings, such as paint, which can mask surface defects, shall not be applied to any surface before inspection or pressure testing.

|             |                                       |  |
|-------------|---------------------------------------|--|
| Reviewed By | Faiz Ahmed<br>DCM-IF&D (Transmission) | Mohammed Ali<br>Manager (Transmission) |
| Approved By | A/SGM (Transmission)                  | A/SGM (Transmission)                   |



8.11.4 The pressure tests shall be performed on each valve in accordance with written procedures and applicability as mentioned in Table 1 of API 598 or if specified otherwise.

#### 8.11.5 Shell Test

8.11.5.1 For shell test the test fluid shall be air, inert gas, kerosene, water, or a noncorrosive liquid with a viscosity not higher than that of water. Unless otherwise specified in the purchase order, the test fluid temperature shall be within the range 5°C (40°F) to 38°C (100°F).

8.11.5.2 Water used can contain water-soluble oil and/or corrosion inhibitor. When specified by the Purchaser, a wetting agent shall be included in the water.

8.11.5.3 When air or gas is used for shell test, the valve manufacturer shall be capable of demonstrating the adequacy of the method of leakage detection.

8.11.5.4 The shell test pressure shall be as listed in Table 2 of API 598.

8.11.5.5 For the shell test, the required test pressure shall be maintained for at least the minimum time specified in Table 4 of API 598.

8.11.5.6 Shell test procedure shall be as per Section 6.3 of API 598.

8.11.5.7 For shell tests, visually detectable leakage through the pressure boundary walls and any flanged body joint is not permitted. Hence when water is used, there shall be no visible evidence of drops on wetting of external surface of test valve whereas for air or inert gas, there shall be no leakage revealed by the established detection method.

#### 8.11.6 Backseat Test

8.11.6.1 Valves that have backseat feature shall have backseat test as mentioned in Table 1 of API 598.

8.11.6.2 At the manufacturer's option, the backseat test for valves that have the backseat feature may be either a high-pressure or a low-pressure test unless stated otherwise in the purchase order.

8.11.6.3 For backseat test, the test fluid shall be air, inert gas, kerosene, water, or a noncorrosive liquid with a viscosity not higher than that of water. Unless otherwise specified in the purchase order, the test fluid temperature shall be within the range 5°C (40°F) to 38°C (100°F).

8.11.6.4 Water used can contain water-soluble oil and/or corrosion inhibitor. When specified by the Purchaser, a wetting agent shall be included in the water.

8.11.6.5 For low-pressure backseat tests, the test fluid shall be air or inert gas.

8.11.6.6 When air or gas is used for backseat test, the valve manufacturer shall be capable of demonstrating the adequacy of the method of leakage detection.

|             |                                      |                                      |
|-------------|--------------------------------------|--------------------------------------|
| Reviewed By | Fahd Ahmed<br>DCM - P&D Transmission | Manbaob Al<br>Manager (Transmission) |
| Approved By | A/SGM ITM                            | A/SGM (Transmission)                 |





SSGC

- 8.11.6.7 Backseat test pressures shall be as listed in Table 3 of API 598.
- 8.11.6.8 For the backseat test, the required test pressure shall be maintained for at least the minimum time specified in Table 4 of API 598.
- 8.11.6.9 Backseat test procedure shall be as per Section 6.2 of API 598.
- 8.11.6.10 For backseat tests, visually detectable leakage is not permitted.
- 8.11.7 High Pressure and Low-Pressure Closure Test
- 8.11.7.1 When closure testing valves, the valve manufacturer's test procedure shall ensure that excessive force is not used to close the valve. The applied force may be determined from the appropriate figures mentioned in MSS SP-91 (Guidelines for Manual Operation of Valves).
- 8.11.7.2 High and low pressure closure test shall be as per requirement mentioned in Table 2 of API 598.
- 8.11.7.3 Valves for which high pressure closure test is optional as mentioned in Table 1 of API 598 are still required to be able to pass the tests. The results shall be supplied if required by the Purchaser.
- 8.11.7.4 For high-pressure closure tests, the test fluid shall be air, inert gas, kerosene, water, or a noncorrosive liquid with a viscosity not higher than that of water. Unless otherwise specified in the purchase order, the test fluid temperature shall be within the range 5°C (41°F) to 38°C (100°F). For low pressure closure test, test fluid shall be air or inert gas.
- 8.11.7.5 Water used can contain water-soluble oil and/or corrosion inhibitor. When specified by the Purchaser, a wetting agent shall be included in the water.
- 8.11.7.6 When air or gas is used for closure test, the valve manufacturer shall be capable of demonstrating the adequacy of the method of leakage detection.
- 8.11.7.7 Closure test pressures shall be as per Table 3 of API 598.
- 8.11.7.8 For closure tests, the required test pressure shall be maintained for at least the minimum time specified in Table 4 of API 598.
- 8.11.7.9 For both the low-pressure closure test and the high-pressure closure test, visual evidence of leakage through the disc, behind the seat rings, or from the shaft seals is not permitted and structural damage is not permitted. The allowable rate for leakage of test fluid at the seat-sealing surface interface, for the duration of the tests shall be as per Table 5 of API 598.
- 8.11.7.10 The allowable leakage rate for closure tests of valves with nonmetallic seat materials shall be equal to that specified in Table 5 of API 598 for a metal-seated valve of equivalent size and type.

|             |  |                                     |
|-------------|--|-------------------------------------|
| Reviewed By | Fahd Aljoudi<br>DCM - P&G Transactions | Melbaok Al<br>Manager (Transaction) |
| Approved By | A/SGM (T)                              | A/SGM (Transaction)                 |





8.11.7.11 Closure test procedure shall be as per Section 5.4 and 6.8 of API 598.  
8.11.7.12 For double block and bleed valve, the high-pressure closure test procedure shall be as per Section 6.6 of API 598.

8.11.8. High-Pressure Pneumatic Shell Test

8.11.8.1 When specified in the purchase order, a high-pressure pneumatic shell test shall be performed. This test shall be performed after the shell test, using appropriate safety precautions. The pneumatic shell test pressure shall be 110 % of the maximum allowable pressure at 38°C (100°F) or as specified in the datasheet. Visible leakage is not allowed.

8.11.9. Hydrostatic Testing

8.11.9.1 Hydrostatic shell test shall be carried out in accordance with IS 60534-4 or ISA 75.13.01.

8.11.9.2 The hydrostatic test medium shall be filtered, potable water with a chloride content not exceeding 200 mg/l.

8.11.9.3 On completion of hydrostatic testing, valves shall be drained of test fluids and dried.

8.12. Seat Leakage Test

8.12.1 The seat leakage test shall be in accordance with ANSI/FCI 70-2 and IEC-60534-4. Standard for control valve leakage.

8.12.2 For each control valve, in the shut-off position, the Vendor shall perform a leakage calculation at the test conditions as defined in the test procedure and at operating conditions with the specified fluid.

8.12.3 For each valve tested, the VENDOR will provide the following data:

- Flow direction;
- Test medium;
- Test differential pressure;
- Duration of test;
- Seat leakage flow rate - measured;
- Allowable seat leakage flow rate; and
- Seat leakage class (if applicable).

8.13. Fugitive Emissions Test

8.13.1 When specified in the purchase order, for natural gas transmission service, valves shall undergo fugitive emission qualification testing. This shall be performed in conformance to a national or international standard such as:

- API 624 for rising stem valves

|             |                                       |                                   |
|-------------|---------------------------------------|-----------------------------------|
| Reviewed By | Falzi Ahmed<br>DCM - P&D Transmission | Mehboob<br>Manager (Transmission) |
| Approved By | A/SEAT (1)<br>                        | A/SEM (Transmission)<br>          |



NOT FOR BIDDING PURPOSE



- API 641 for quarter-turn valves
- ISO 15848-1 for industrial valves

8.13.2 When specified in the purchase order, valves shall be fugitive emission production tested. The production fugitive emission testing of valves shall conform to ISO 15848-2.

**8.14 Functional Test**

8.14.1 Functional tests shall be performed on assembled valves with regulator and actuator control equipment using the positioner signal to verify:

- Set pressure for the air/other regulator;
- Specified power supply applied to the positioner/controller, position transmitters and solenoid valve, in case of Electro/Pneumatic Valve;
- Specific pressure applied to the positioner/controller, in case of Pneumatic Valve;
- Valve rate of travel;
- Actuator bench test;
- Position transmitter output, if applicable;
- Movement is smooth without any jerking.

8.14.2 The fail-safe position shall be checked for air supply and other supply failure.

**9 EXTERNAL SURFACE TREATMENT**

9.1 Valves shall be delivered, externally sandblasted and primed in accordance with the Manufacturer's standard painting specifications.


9.2 Manufacturer will submit the painting specification for Purchaser's approval.

**10 MARKING**

10.1 Each valve accepted shall be marked visibly and permanently in a suitable position. The marking shall include the following information:

- Project Mark: As per title of attached data sheet
- Purchase Order / Contract Number
- Manufacturer's Mark
- Diameter
- Pressure Rating
- Inspector's Stamp
- Traceability number

|             |                                     |                                     |
|-------------|-------------------------------------|-------------------------------------|
| Reviewed By | Faz Akbar<br>DCM - P&D Transmission | Mehboob Ali<br>Manager Transmission |
| Approved By | A/SGM (TS)                          | A/SGM (Transmission)                |



NOT FOR BIDDING PURPOSE



10.2 The actuator of all valves shall be labelled with name plates made of stainless steel to allow for cross reference with the operating manual. These name plates shall be engraved with:

- Name of Purchaser
- Name of Engineer/Inspector
- Identification Number of valve

**11. DOCUMENTS**

11.1 Prior to starting manufacture, the Manufacturer shall submit the following documents and receive written acceptance from the Purchaser:

- Control Copy of Quality Control Manual
- Welding Procedures
- Pressure Test Procedures
- Non-Destructive Test Procedures
- Drawings
- Inspection Test Plan
- Material Test Certificate
- Boiler and Pressure Vessel Fabrication Registration Certificate

**11.2 Quality Control Program**

11.2.1 The Manufacturer shall provide detailed information with the bidding documents for the in-house quality control program which shall be adhered to for the production of all manufactured items. This program must adhere to an internationally accepted quality control standard such as ISO 9000 series and AS 9100.

11.2.2 Failure to provide certification or proof of compliance may result in rejection of the bid.

11.3 Copies of the following documents shall be submitted four weeks before the delivery of the valves:

- Scale drawings with parts lists and material data
- Installation, operation and maintenance instructions for the diaphragm actuator, controller and valve
- Inspection test and material certificates
- Data sheets and diagrams
- Calculation sheets

|             |                                       |                                      |
|-------------|---------------------------------------|--------------------------------------|
| Reviewed By | Faz Ahmed<br>DCM - P&O Program Office | Mahboob Ali<br>Manager (Fabrication) |
| Approved By | A/SSM (TS)                            | A/SSM (Fabrication)                  |



- Description of manufacturing and test procedures.
- 11.4 All documents must be reproducible and suitable for microfilming. Any deviations from the approved specifications must be approved by the Purchaser. The Supplier must submit a detailed test program of the tests to be carried out on the valves which must be subject to review of the Purchaser.
- 11.5 All documents and drawings issued by the Vendor shall be produced in hard copies and in an electronic format compatible with recent and standard office computer software.
- 11.6 Final Documentation
- 11.6.1 A dossier shall be compiled concurrently with full records of the fabrication, materials, inspection and testing.
- 11.6.2 All items in the dossier shall be numbered and bound in an A4 four post binder, contents shall include but not be limited to the following (as applicable):
- Front cover sheet detailing:
    - P.O. No.
    - Project Title
    - Equipment Title
    - Equipment Item No.
  - Index
  - Purchaser Release Note
  - Purchase Order
  - A list of all applicable codes, standards and specifications
  - All drawings "As-built" (wherever legibility can be preserved, reduced to A3 and folded, where legibility cannot be preserved, drawings to be folded to A4 size and inserted into pre-punched plastic wallets.
  - NDT procedures
  - All NDT / PWHT / Hydrostatic / Performance test reports
  - Photocopy of Nameplate
  - Material chemical analysis and mechanical test certification
  - Final signed quality plan
  - Material test certificates
  - Mechanical design calculations
  - Procedure Qualification Records
  - Welding qualification Tests

|             |                                      |                                     |
|-------------|--------------------------------------|-------------------------------------|
| Reviewed By | Faiz Ahmed<br>DEM - R&D Transmission | Mehboobul<br>Manager (Transmission) |
| Approved By | A/S GM (TS)                          | A/S GM (Transmission)               |



- Painting inspection certificates
- Manufacturing Data Records (MDR)
- Installation Drawings and Procedures
- Operation and Maintenance Manual
- Schedules of commissioning spare parts

11.5.3 For all above documents, six (06) sets shall be submitted in clearly labeled ring white hard cover binders. All documents smaller and larger than A4 shall be inserted into A4 punched, top-opening plastic wallets with the project document number/titler block clearly visible to the front.

## 12. DRAWINGS & DESIGN CALCULATION

12.1 The below list of documents required is intended to define the minimum technical documents to be provided by the Vendor. This list is not exhaustive and additional documentation necessary for the work executing shall be provided by Vendor:

- Calculations of control valve capacity
- Noise calculation
- Seat leakage test report
- Details of selected actuator
- Pneumatic and electrical schematics for all accessories (if applicable)
- Dimensions and construction drawings of the control valve, including accessories and air lines
- Bill of materials
- Valve datasheets
- Production testing and inspection

12.2 The bidder shall submit design calculation for the size which specify software name of control valves considering both maximum and minimum conditions and other possible condition within given parameters & with the rangeability & range for the selected valves.

12.3 The bidder shall specify port diameter, gas rating coefficient values (at 100% percentage of valve opening ranging from 10% to 80% of the total travel), maximum Cv for the selected valves along with calculation sheets, selection sizing chart or catalogue, related technical literature for the valves, actuator, positioner etc. quoted.

12.4 P&ID showing interconnection of control valves, actuators, controller and other

|             |                                     |  |
|-------------|-------------------------------------|--|
| Reviewed By | Saiz Ahmed<br>SGM-P&ID Transmission | Muhammad Ali<br>Manager (Transmission) |
| Approved By | A/SGM (TS)                          | A/SGM (Transmission)                   |





accessories with main pipeline system is required to be submitted with the bidding documents.

12.5 All drawings, documents, information, correspondence, test reports, operating and maintenance instructions and similar items shall be in the English language and metric units.

12.6 Drawings of the offered control valves with make and model along with material, dimensional details and other important feature is required to be submitted along with the bid.

12.7 Failure to provide the above documents may result in rejection of bid documents.

### 13 LUBRICANT

13.1 Type of lubricant / sealant / packing lubricant and injecting opportunities should be specified and price quoted.

### 14 INSPECTION CERTIFICATES

14.1 The Supplier shall cause inspection certificates to be issued and certified by an inspector of his own quality assurance department appointed for this purpose.

14.2 Each such certificate shall show the results of tests made under these specifications such as tests of the functions of the valve to be supplied and correct dimensions and shall show the Purchaser's Contract Number.

### 15 RESERVATIONS

15.1 The Purchaser shall have the right to witness or deploy 3rd party inspection services at any time during the fabrication, testing and shipment of valves supplied in accordance with these specifications and to verify compliance with the terms and conditions of the contract and Terms of references (TOR) attached with the bid document.

15.2 The supplier shall give due and proper notice of commencement of valve fabrication and test under these specifications to the Purchaser/ Third party inspector appointed by SSGC.

15.3 The Purchaser reserves the right to increase, decrease and delete the quantity of all the items given herein the Data sheet.

|             |                                       |                                      |
|-------------|---------------------------------------|--------------------------------------|
| Reviewed By | Faiz Ahmad<br>DCM - P&ID Transmission | Wahab Ali<br>Engineer (Transmission) |
| Approved By | ASGM (P&ID)                           | ASGM (Transmission)                  |



**16 PACKING**

- 16.1 All valves (including actuators) shall be assembled prior to shipment and shall be ready for installation upon delivery. The valve shall be so packed, transported and stored as to prevent damage prior to delivery. The Supplier shall warrant that the valves will remain clean and dry during transportation and storage until installation.
- 16.2 Packing and crating shall be robust and sea worthy in wooden case.
- 16.3 Protection against corrosion/deterioration shall be given special attention. Machined steel and iron parts shall be heavily greased/varnished as a preventive measure against rust and where grease is used it shall be such that it retains its consistency, and does not melt at tropical temperatures and is acid free.
- 16.4 Valves shall be shipped with the faces of the flanges or the welding ends protected over the entire contact surfaces with suitable protectors securely attached to the valves.

NOT FOR BIDDING PURPOSE

|              |                                      |                                      |
|--------------|--------------------------------------|--------------------------------------|
| Reviewed By: | Faiz Ahmad<br>CCM - P&O Transmission | Mehnaz Ali<br>Manager (Transmission) |
| Approved By: | A/SGM (IS)                           | A/SGM (Transmission)                 |



## TERMS OF REFERENCE

### INSPECTION OF CONTROL VALVES

Third party inspection will be carried out as per attached Specification compliance sheet & witness the manufacturing process including following:

The following test/ points mentioned below, are mandatory and TPI to submit report.

1. Reference applicable Code/Standards/ documents as per specifications:
2. The valves shall be inspected and tested for the following items as minimum requirement and in accordance with latest edition of applicable codes/standards.
  - Appearance inspection
  - Visual inspection to be carried out before Hydro test.
  - Dimensional inspection
  - Marking inspection
  - Functional/operational test
  - Antistatic Device Test
3. All inspection/testing equipment shall be calibrated and their certificate should be available.
4. Material test certificates MTC's to be checked according to datasheet of valves.
5. EN 10204 3.1 MTC's contain at least RT reports, Painting reports, Hardness Report.
6. All parts of valves should be brand new, rust free and weld deposit material is not acceptable.
7. Welding and Nondestructive testing to be performed as specified in valves specifications.
8. Both inside and outside surfaces of casting material shall be free from harmful blowholes, fins, seizures of sand scales, sand inclusions and cracks and shall be in accordance with MSS-SP- 55.
9. Control Valve seat leakage test shall be performance in accordance with ANSI Class IV/ FCI 70-2.
10. Valve actuators shall be tested as per specifications.
11. Preservation & Packing checks to be performed as per specifications.
12. Upon completion of satisfactory testing all components to be thoroughly drained and dried prior to preparation for packing.



**SUI SOUTHERN GAS COMPANY LIMITED**

**UNDERTAKING OF COMPLIANCE WITH INTEGRATED MANAGEMENT SYSTEM (IMS) MANUAL AND BLACKLISTING MECHANISM**

I, \_\_\_\_\_ [Supplier's Authorized Representative Full Name], of \_\_\_\_\_ [Supplier Company Name], with principal \_\_\_\_\_ office \_\_\_\_\_ located \_\_\_\_\_ at \_\_\_\_\_ [Full Address], do hereby solemnly affirm and declare as follows:

1. That I am the duly authorized representative of \_\_\_\_\_ [Supplier Company Name], and have the legal authority to make this declaration on behalf of the company.
2. That I confirm having accessed, read, and fully understood the Integrated Management System (IMS) Manual provided by Sui Southern Gas Company Limited (SSGC), available at the official website: [https://www.ssgc.com.pk/web/ftp-content/uploads/2025/06/IMS-Manual-\[-\].pdf](https://www.ssgc.com.pk/web/ftp-content/uploads/2025/06/IMS-Manual-[-].pdf)
3. That \_\_\_\_\_ [Supplier Company Name] agrees to comply fully with all the policies, procedures, and responsibilities outlined in the IMS Manual, and will ensure that all relevant employees, contractors, and agents are made aware of and comply with the same.
4. That \_\_\_\_\_ [Supplier Company Name] acknowledges that failure to comply with the IMS Manual may result in corrective action, including but not limited to financial penalties as per SSGC policy and suspension or termination of business with Sui Southern Gas Company Limited (SSGC).
5. That the bidder has also read, understood, and accepted the Blacklisting Mechanism of Sui Southern Gas Company Limited (SSGC), available at: [https://www.ssgc.com.pk/web/ftp-content/uploads/2024/09/blacklisting\\_mechanism\\_2024.pdf](https://www.ssgc.com.pk/web/ftp-content/uploads/2024/09/blacklisting_mechanism_2024.pdf)
6. Any type of violation of the tender terms and/or performance will result in the enforcement of the Blacklisting Mechanism, which will be dealt with in accordance with the Blacklisting Rules/Mechanism.
7. This affidavit is made in good faith and for the purpose of affirming our commitment to health, safety, environmental standards, and compliance with the Integrated Management System (IMS) Manual and the Blacklisting Mechanism of Sui Southern Gas Company Limited (SSGC), as well as all other applicable policies and procedures of SSGC.

Signed at \_\_\_\_\_ [City] on this \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_.

Signature: \_\_\_\_\_  
Name: \_\_\_\_\_  
Designation: \_\_\_\_\_  
Company Name: \_\_\_\_\_  
Contact Details: \_\_\_\_\_

(Company Stamp / Seal Mandatory)

Witnessed by:

Signature of Witness: \_\_\_\_\_  
Name of Witness: \_\_\_\_\_  
Date: \_\_\_\_\_

Signature of Witness: \_\_\_\_\_  
Name of Witness: \_\_\_\_\_  
Date: \_\_\_\_\_

