

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 07-07-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

**TENDER BULLETIN**

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DRG103 660	6X120 (6X15)	6140ZO653869 8 / BATTERY LEAD ACID 12 VOLTS,105 AH		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH: 367MM W:173MM HIGHT: 228MM LEAD ACID 12V,105AH, EXIDE 6X15 GENERAL SPECIFICATION - LENGTH: 367MM W:173MM HIGHT:228MM LEAD ACID 12V,105AH,EXIDE 6X15	
2	DRG103 742	6X120 (6X15)	6140ZO653869 8 / BATTERY LEAD ACID 12 VOLTS,105 AH		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH: 367MM W:173MM HIGHT: 228MM LEAD ACID 12V,105AH, EXIDE 6X15 GENERAL SPECIFICATION - LENGTH: 367MM W:173MM HIGHT:228MM LEAD ACID 12V,105AH,EXIDE 6X15	
3	DRG100 194	I-6000T CC-6000 OR I- 633MMTB	291570515008 8 / COALESCER ELEMENT ASSY		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
4	DNQ962 49	CEN10000 63C	5510FT101983 2 / Wooden Plug 250 x 70 x 20 mm	Portable Firefighting and Damage Control Equipment System	150 / EACH/N UMBER	55580MT. 0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
5	DRG103 680	7133019	614001621916 8 / BATTERY 12V 95AH (MAINTENANC E FREE)		1 / EACH/N UMBER	TLD EUROPE					TECHNICAL SPECIFICATION - 12V 95AH GENERAL SPECIFICATION - 12V 95AH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
6	DPC102 372	555631	681025161721 1 / NITRITE NO 2 TABLETS		14 / BOTTLE	NITRITE NO 2 TABLETS					<p><b>TECHNICAL SPECIFICATION -</b>  Manufacturer Address Wilhelmsen  Ships Services AS P.O Box 33 NO-  1324 LYSAKER, NORWAY Tel:  +4767584550 Technical  Specifications Bottle contains 250  tablets Used for measuring Nitrite  contents in NALFLEET-2000 General  Specification Item is part of  SPECTRAPACK 309 Cooling Water  Test Kit (Part No 739466, NSN  6630735232429) <b>GENERAL</b>  <b>SPECIFICATION -</b> Manufacturer  Address Wilhelmsen Ships Services  AS P.O Box 33 NO-1324 LYSAKER,  NORWAY Tel: +4767584550  Technical Specifications Bottle  contains 250 tablets Used for  measuring Nitrite contents in  NALFLEET-2000 General  Specification Item is part of  SPECTRAPACK 309 Cooling Water  Test Kit (Part No 739466, NSN  6630735232429)</p>	
7	DNQ102 361	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	4 / EACH/N UMBER						<p><b>TECHNICAL SPECIFICATION - NO</b>  <b>DATA AVAILABLE</b>  <b>GENERAL</b>  <b>SPECIFICATION - NO DATA</b>  <b>AVAILABLE</b></p>	
8	DRG103 682	(1) N80 (N88) (N70A/N80 A) / (2) N- 80 new no n-85 12 v65ah 11 plates	6140ZO651014 2 / BATTERY LEAD ACID		1 / EACH/N UMBER	N80					<p><b>TECHNICAL SPECIFICATION -</b>  <b>TYPE: LEAD ACID BATTERY,</b>  <b>MODEL: N80, VOLTS : 12, PLATES:</b>  <b>11 PLATES PER CELL, AMPERE :</b>  <b>65AH, SIZE IN MM: L-259 X W-172</b>  <b>XH-224 (+/- 5MM), POLARITY</b>  <b>RIGHT THICK POLE, EQUIVALENT</b>  <b>AGS BATTERY MODEL GL85 13</b>  <b>PLATES 70AH, OEM/COUNTRY OF</b>  <b>ORIGIN: EXIDE PAKISTAN LTD,</b>  <b>OEM COC/AUTHORIZED DEALER</b>  <b>CERTIFICATE: N/A, ITEM</b>  <b>AVAILABLE IN LOCAL MARKET</b>  <b>GENERAL SPECIFICATION - TYPE:</b>  <b>LEAD ACID BATTERY, MODEL:</b>  <b>N80, VOLTS : 12, PLATES: 11</b>  <b>PLATES PER CELL, AMPERE :</b></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
9	DRG103 740	(1) N80 (N88) (N70A/N80 A) / (2) N- 80 new no n-85 12 v65ah 11 plates	6140ZO651014 2 / BATTERY LEAD ACID		3 / EACH/N UMBER	N80					65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE, EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET  TECHNICAL SPECIFICATION - TYPE: LEAD ACID BATTERY, MODEL: N80, VOLTS : 12, PLATES: 11 PLATES PER CELL, AMPERE : 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE, EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET  GENERAL SPECIFICATION - TYPE: LEAD ACID BATTERY, MODEL: N80, VOLTS : 12, PLATES: 11 PLATES PER CELL, AMPERE : 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE, EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET	
10	DRG998 87	I-6000T CC-6000 OR I- 633MMTB	291570515008 8 / COALESCER ELEMENT ASSY		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
11	DRG103 645	FLUKE MODLE-87 OR FLUKE 189	6625ZO658066 2 / DIGITAL MULTIMETER (FLUKE CORPORATIO		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FLUKE MODEL 87,187 OR 189 GENERAL SPECIFICATION - FLUKE MODEL 87,187 OR 189	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			N USA)									
12	DGP104706		599979522644 1 / LED TV 40 INCH	MAXV SMD	1 / EACH/NUMBER			M/S TAIKO UK	M/S TAIKO UK		TECHNICAL SPECIFICATION - MAKE: TCL GENERAL SPECIFICATION - MAKE: TCL	
13	DPC99532	NO DATA AVAILABLE	04745000702 8 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		72 / BAG						TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0	
14	DNM96974	3918521	473001368939 8 / CLAMP HOSE	DIESEL GENERATOR CUMMINS	2 / EACH/NUMBER	NO DATA AVAILABLE		US	M/S CUMMINS INC 500 JAKSON ST COLUMBUS IN USA 47201-6258 TEL:377-3920 FAX 812-377-1715 E. MAIL: STEVE.AHEWITT@COMMINS.COM		TECHNICAL SPECIFICATION - CLAMP HOSE (band type) adjustable band type 59-83 mm diameter clamp 80g approx width 12-16 mm screw tightening (worm gear style) / band screw zinc plated or corrosion resistant steel GENERAL SPECIFICATION - CLAMP HOSE (band type) adjustable band type 59-83 mm diameter clamp 80g approx width 12-16 mm screw tightening (worm gear style) / band screw zinc plated or corrosion resistant steel	
15	DPC101889		044250442013 9 / PAINT GLOSS ALKIDE RESIN,		170 / TIN					TDS/BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			THINNER: WHITE SPIRIT NAPTH COL 361							ENCLOSE D WITH QUOTATIO N.		
16	DPC102 016		044250942354 3 / PAINT MARKING (WHITE)		330 / LITER					TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N.	TECHNICAL SPECIFICATION - a. Colour White b. Viscosity 100-200 cps (centipoise) c. Density 1.2-1.5 g/cm3 d. Fast Drying 15-30 minutes e. Thickness 50-100 microns (dry film) f. Adhesion Excellent on Metal, Wood, concrete g. Durability Resistant to weathering, UV and Chemicals h. Reflectivity High(85- 90%)GENERAL SPECIFICATION - a. Colour White b. Viscosity 100-200 cps (centipoise) c. Density 1.2-1.5 g/cm3 d. Fast Drying 15-30 minutes e. Thickness 50-100 microns (dry film) f. Adhesion Excellent on Metal, Wood, concrete g. Durability Resistant to weathering, UV and Chemicals h. Reflectivity High(85- 90%)	
17	DPC101 696	NO DATA AVAILABL E	044350443000 5 / CYLINDER FOR COOKING GAS (EMPTY) CAPACITY 45.40KG		6 / EACH/N UMBER					TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N.	TECHNICAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>PIPE ring dimesion: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque, GENERAL SPECIFICATION - 1. grade-1 i. a . w (dot 4wb hse) colour: yellow need. 2. Specification: DOT- 4 BW (HSE) WELDED STEEL CYLINDERS OF DEFINITELY PRESCRIBED WITH ELECTRIC ARC WELDED LONGITUDINAL SEAM. 3. CYLINDER VALVE: OGRA APPROVED MANUFACTURER'S COMPACT VALVE DESIGN DATA: Product=LPG Cylinder, type=commercial 45.4 kg capacity, design pressure=270 psi, test pressure=540 psi, standard= dot-48w 270, water capacity=108 ltrs, overall length=1280 +/- 15s, pneumatic test pressure=110 psi, shell and doom dimensions: Sheet thickness=3mm or 3.2mm, off setting=9mm +/- 1, other dia=368mm +/- 1, height of shell with</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	---------------	----------------	------------------	-----------

18	DPC101 740	NO DATA AVAILABL E	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		90 / KILOGR AMME						<p>base to bung=1164mm +/- 10, base clearance from bottom=29mm +/- 2, PIPE ring dimension: thickness=2.1mm +/- 0.1, outer dia=240mm +/- 2, pipe dia=21mm +/- 1. FOOT ring dimensions: thickness=3mm, tolerance=as per pakistan steel tolerance standard, height=90mm +/- 2, Outer Dia=372mm +/- 2, drain hole bottom=3Nos. 9mm, painting: cylinder should be sand blasted before painting, colour=yellow or as per PN Requirements, primer and paint thickness=60 ~ 80 micron, monogram printing on shell as per PN requirements, bung dimension: material=jus g 311287 grade sr 24, height=21mm +/- 1, top dia=45mm +/- 0.5, collar dia=48mm +/- 1, collar height=7mm +/- 1, thread size=3/4" NGT, Cylinder Valve: OGRA Approved Manufacturer's Compact Valve TESTs: Volumetric Expansion, Hydrostatic Test, Burst Test, Radiography Test, Air Leak Valve Check at 110PSI, Valve Tightness at 120~150 Torque,</p> <p>TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate</p>	
----	---------------	--------------------------	--	--	------------------------	--	--	--	--	--	---	--

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
19	DPC99659	SPEC,DEF 1052 COLOURS TO BS 381C	044250910703 5 / PAINT FNSHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/5 66DT210902		755 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
20	DNQ101773	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
21	DNQ101553	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
22	DNQ101163	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6.5MM DIA								timber.GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
23	DNM99487	0240-2872	2990725008134 / COVER TUBE 0240-2872ED0147-11	DEUTZ DIESEL GENERATOR 60KW	24 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
24	DNM101564		3230731001865 / BLADE POWER HACKSAW HSS 18X1-1/4X1/16INX6TPI		2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - Dimensions (LXWXT): 18 X 1-1/4 X 1/16 X 6TPI (6 Teeth per inch) MATERIAL: HSS (HIGH SPEED STEEL) USE FOR CUTTING ON HACKSAW MACHINE GENERAL SPECIFICATION - Dimensions (LXWXT): 18 X 1-1/4 X 1/16 X 6TPI (6 Teeth per inch) MATERIAL: HSS (HIGH SPEED STEEL) USE FOR CUTTING ON HACKSAW MACHINE	
25	DNQ101322	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DPC102188	HRC-407C (HFC-407C) GENETRON R-407C	6830705118136 / GAS FOR (A/CS) R-407C (packing = 11.3 kg) (Purity level 99% Min)	A/C SPLIT (02TONS)	204.3 / KILOGRAMME						TECHNICAL SPECIFICATION - OEM: HONEYWELL (USA) GENERAL SPECIFICATION - OEM: HONEYWELL (USA)	
27	DNQ100846	159081	8465999244592 / FIREMAN'S BELTG, MODEL AUSTRIA WITH CARABINER	FIRE FIGHTING EQUIPMENT OEM:FIREKILINT	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - DSI, SIZE WAIST (75-110 CM) Weight: 1.5 kg Certified as to Austrian Standard ON F 4030:2008, EN 358, All polyester webbing, breaking load 2000kg. Dual thorn buckle. Comes with descender and steel snap hook, serving as a hand brake for self-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											rescue. Accepts leather hatchet hoder GENERAL SPECIFICATION - DSI, SIZE WAIST (75-110 CM) Weight: 1.5 kg Certified as to Austrian Standard ON F 4030:2008, EN 358, All polyester webbing, breaking load 2000kg. Dual thorn buckle. Comes with descender and steel snap hook, serving as a hand brake for self-rescue. Accepts leather hatchet hoder	
28	DPK89706	IN105270/ MOBIL XHP222 146379	915079510274 1 / GREASE MOBIL XHP222 ,16 /180 KG PACKING	HOVERCRAFT .GRIFFON HOVERCRAFT LTD,UK	36 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DPK101616	TCW3 NMMA	07215000001 3 / LUB OIL OMD-23 FOR TWO STROKE OUTBOARD GASOLINE ENGINE NMMA GRADE TCW3		282 / LITER	NO DATA AVAILAB LE				TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N.	TECHNICAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE GENERAL SPECIFICATION -ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE	
30	DPK101430	TCW3 NMMA	07215000001 3 / LUB OIL OMD-23 FOR TWO STROKE OUTBOARD GASOLINE ENGINE NMMA GRADE TCW3		250 / LITER	NO DATA AVAILAB LE				TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N.	TECHNICAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE GENERAL SPECIFICATION -ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE	
31	DPK90283	10250	597014340763 6 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	20 / KILOGR AMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
32	DPK87802	10250	597014340763 6 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	20 / KILOGR AMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
33	DNQ102157	15199001	4220795289489 / SOLAS SOFTPACK RFD (FIRST AID KIT) FOR LIFE RAFT - LIFE BOAT		2 / EACH/NUMBER	life raft				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
34	DSA101168	D-18677	5130765157117 / disc CUTTING 5 inch		60 / EACH/NUMBER	200611/ EN-12413					TECHNICAL SPECIFICATION - RHODIUS: FTK33 180X3.0X22.23MM DESPRESSED CENTER CUTTING DICS SHAPE-42 MINIMUM SHELF LIFE - 18 MONTHS Technical details: Series : FTK33 Diameter: 125mm Thickness: 3.0mm Center hole: 22.23mm with steel core out side Model No: 200611/ EN-12413 ALPHA LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWEKZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROHI/ GERMANY SHELF LIFE OF DISC: 3 years from date of manufacturing GENERAL SPECIFICATION - RHODIUS: FTK33 180X3.0X22.23MM DESPRESSED CENTER CUTTING DICS SHAPE-42 MINIMUM SHELF LIFE - 18 MONTHS Technical details: Series : FTK33 Diameter: 125mm Thickness: 3.0mm Center hole: 22.23mm with steel core out side Model No: 200611/ EN-12413 ALPHA LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWEKZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROHI/ GERMANY SHELF LIFE OF DISC: 3 years from date of manufacturing	
35	DNM101707	145046110	4730785235633 / THERMOSTAT		1 / EACH/NUMBER	SDG15PS				TDS/BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			HOUSING							BE ENCLOSED WITH QUOTATION.		
36	DPC101 871	DEFSTAN 80-37/2 OF 2006	0442504420124 / Paint Cellulose White Finsihing for vehicles principal component Nitro Cellulose Base Flash Point 23		50 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DPC101 859	DEF- 1145/1956	0442504420079 / THINNER (SPEC) DEF STAN 80-38/2 1985 (PACKING 20 LTRS DRUM)		107 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - DEFSTAN 80-38/2 of 1985 GENERAL SPECIFICATION - DEFSTAN 80-38/2 of 1985	
38	DPC101 817	WHO/SIF/ 13.R5	0442502201201 / Lambda Cyhalothrin 2.5 or 25% EC. 01LTR PLASTIC PACKING WITH REGISTERED LABEL.	KEROCANE OIL.	125 / LITER						TECHNICAL SPECIFICATION - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label. GENERAL SPECIFICATION - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label.	
39	DPC971 53	NO DATA AVAILAB L E	0474500007028 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		40 / BAG						TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe2O3: LESS THEN 1.5 AL2O3: LESS THEN 4.5 Cao+Mgo:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension	
											LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0		
40	DPC98495	NO DATA AVAILAB LE	0474500007028 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		43 / BAG						TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0		
41	DPK99257	15W40 (API CF-4/SG) /870234	9150SV1210006 / LUBE OIL CUMMINS VALVOLINE PREMIUM BLUE 7800 15W40	MAINE AND EMERGENCY GENSET	220 / LITER	CUMMINS VALVOLINE VI TOPFLITE	KH180429(BVO1, BVO2, BVO3, BVO4)	SHANGHAI VCLUBRICATING OIL CO. LTD.CHINA		CHEVRON MARINE	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null		
42	DNQ96252	CEN1000063E	5510FT1019834 / Wooden Plug 300 x 120 x 50 mm	Portable Firefighting and Damage Control Equipment System	150 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE		CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -		
43	DNQ101339	CEN1000063C	5510FT1019832 / Wooden Plug 250 x 70 x 20 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE		CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATIO	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
44	DNQ101337	CEN1000063A	5510FT1019830 / Wooden Plug, 200 x 30 x 8 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	N. TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N.	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
45	DNQ96207	CEN1000063A	5510FT1019830 / Wooden Plug, 200 x 30 x 8 mm	Portable Firefighting and Damage Control Equipment System	165 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
46	DNQ101312	464748 ABN.	4730014355106 / REPAIR KIT,PIPE, EMERGENCY DAMAGE CONTROL	EMERGENCY CONTROL , PIPE REPAIR KIT.	5 / KIT			OEM: c IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	INDUMAR PRODUC TS INC DBA STOP ..	TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM GENERAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM		
47	DPK101540	HA5440	9150735164285 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	30 / GALLO N	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW.seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	TELEFLEX MARINE CANADA		TECHNICAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW.seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858GENERAL SPECIFICATION - TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	
48	DPK101551	ZIC ATF 3	9150735221369 / ZIC ATF 3 DEXRON SYNTHETIC TRANSMISSION FLUID	TILT & TRIM ASSEMBLY	30 / LITER	ZIC ATF 3	NIL	SK LUBRICANTS 26, JONG-RO-JONGNO-GU, SEOUL,KOREA www.skzic.com Made in Korea	SK LUBRICANTS	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly) GENERAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly)	
49	DNH103170	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	2 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
50	DPK100787	ZIC ATF 3	9150735221369 / ZIC ATF 3 DEXRON SYNTHETIC TRANSMISSION FLUID	TILT & TRIM ASSEMBLY	30 / LITER	ZIC ATF 3	NIL	SK LUBRICANTS 26, JONG-RO-JONGNO-GU, SEOUL,KOREA www.skzic.com Made in Korea	SK LUBRICANTS		TECHNICAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly) GENERAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly)	
51	DNM98924	342-6510	5306715240108 / BOLT-TORX (M14X1.5X70-MM)		3 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - NOT KNOWN GENERAL SPECIFICATION - NOT KNOWN	
52	DN0102300	kiwi-dn50	4730705344196 / bulk head connector for dn-50		4 / EACH/NUMBER	dn-50				TDS/BROCHER OR PICS OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - fitted on bulkhead used for connecting DN-50 between two compartments fire hoses/ water hoses GENERAL SPECIFICATION - fitted on bulkhead used for connecting DN-50 between two compartments fire hoses/ water hoses	
53	DNJ103078	66T-14301-02	2910765344266 / CARBURETOR		1 / EACH/NUMBER	66T-14301-02				TDS/BROCHER OR PICS OF	TECHNICAL SPECIFICATION - AS PER TECHNICAL DATA / PART CATALOG GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ASSY 1							ITEM MUST BE ENCLOSED WITH QUOTATION	SPECIFICATION - AS PER TECHNICAL DATA / PART CATALOG	
54	DPK104526	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/A DDINOL API SJ SAE 10W-30 (4 Stroke Mamie Oil)(01 Liter Packing)	350HP YAMAHA	60 / LITER	JAPAN		JAPAN	SHELL		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
55	DPK104469	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/A DDINOL API SJ SAE 10W-30 (4 Stroke Mamie Oil)(01 Liter Packing)	350HP YAMAHA	500 / LITER	JAPAN		JAPAN	SHELL	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
56	DNM102841	100-3880	2815015067155 / PUSHROD-VALVE	CATERPILLAR GENSET D3512B (YBB1) USA	24 / EACH/NUMBER	D3512B	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - CATERPILLAR GENSET D3512B (YBB1) USA METALLIC PUSHROD-VALVE MATERIAL STEEL MAIN ENGINE CUMMINS GENERAL SPECIFICATION - CATERPILLAR GENSET D3512B (YBB1) USA METALLIC PUSHROD-VALVE MATERIAL STEEL MAIN ENGINE CUMMINS	
57	DNH103892	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	5 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
58	DNM101557	5289380	2815715193136 / INJECTOR	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.77305MD USA	6 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s IMPEX NINE INC		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											USA	
59	DNM102842	FF9003000	2910715170013 / FUEL FILTER	DIESEL ENGINE CUMMINS (GRP CREEK CRAFT)	2 / EACH/NUMBER	QSB.9-305 MCD		OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM.	NIL		TECHNICAL SPECIFICATION - OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM. GENERAL SPECIFICATION - OEM: M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A.HEWITT@CUMMINS.COM.	
60	DNM102775	265-7538	6115015558294 / BRIDGE (EXHAUST)	CATERPILLAR 3516 DIESEL ENGINE	12 / EACH/NUMBER	CATERPILLAR 3516	CATERPILLAR 3516	CATERPILLAR USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - IPC ATTACHED CATERPILLAR 3516 CATERPILLAR 3516 DIESEL ENGINE 265-7538 GENERAL SPECIFICATION - IPC ATTACHED CATERPILLAR 3516 CATERPILLAR 3516 DIESEL ENGINE 265-7538	
61	DNM79184	3588745/3588770	3426171227297 / ANODE KIT ZINC ANODE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBOG, SWEDEN	AB VOLVO PENTA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887 GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887	
62	DNM70191	3588745/3588770	3426171227297 / ANODE KIT ZINC ANODE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBOG, SWEDEN	AB VOLVO PENTA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887 GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887	
63	DPC104056	SUVA 410a /HFC-410a/R-410a//HON	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		EYWELL R-410A									DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
64	DNQ102 508	SEFSTAN 84-2	844099978449 6 / STOCKING WOOL WHITE FOOT SIZE 27CM	STOCKING SHIPS (FF)	6 / PAIR	NO DATA AVAILAB LE		UK		UK ENGLAN D	TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
65	DNM102 777	352-9766	610571522588 7 / MOTOR GP ELECTRICAL	GEN SET	1 / EACH/N UMBER	3512B	CAT3512 BEYBB00 583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA		CATERPI LLAR, USA	TECHNICAL SPECIFICATION - ITEM IS USED FOR STARTING SYSTEM OF CATERPILLER GEN SET 1. Rating: 1088 KW 2. Brand: CATERPILLAR DG 3. Model No: 3512B 4. ESN: BS500559 5. Unit: NMG (O), DG No 3GENERAL SPECIFICATION - ITEM IS USED FOR STARTING SYSTEM OF CATERPILLER GEN SET 1. Rating: 1088 KW 2. Brand: CATERPILLAR DG 3. Model No: 3512B 4. ESN: BS500559 5. Unit: NMG (O), DG No 3	
66	DPC104 523		047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	310 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSEGENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
67	DPC102 180	NO DATA AVAILAB LE	047350942924 4 / PIGMENT POWDER (LEAD CHROME) BS-282		31 / KILOGR AMME					TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N.	TECHNICAL SPECIFICATION - Yellow oxide (fine powder) Plastic packing 0.5 Kg Brand Name: Blue BirdGENERAL SPECIFICATION - Yellow oxide (fine powder) Plastic packing 0.5 Kg Brand Name: Blue Bird	
68	DPC102	NO DATA	047450000702		150 /					TDS/BROC	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	111	AVAILABLE	8 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		BAG					HER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe2O3: LESS THEN 1.5 AL2O3: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe2O3: LESS THEN 1.5 AL2O3: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0	
69	DPK10444	0474-7021 (0475-99-224-2137)	0474502242137 / TALLOW WHITE (GREASE) (200 KG DRUM)		200 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DPC104686		0442504420051 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	260 / LITER						TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg GENERAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
71	DPC104663	SPECIFICATION BS 479 SECTION 5	0442509429219 / NAPHTHA COALTAR (HEAVY) 90/190 (THINNER	THINNER FOR BOTTOM COMPOSITIO NS	20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FOR BOTTOM COMPOSITIO N									
72	DNQ103 178	0121-924-0372	012199924037 2 / LUMBER SOFT WOOD DIM SZ 100X100MM (LENGTH=07 FEETS)	NBCD DAMAGE CONTROL& FIRE FIGHTING EQUIP	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DNQ102 154	LOCALLY DEVELOPED	204099787817 2 / CLAMP DAMAGE REPAIR		16 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DNQ103 812	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		8 / EACH/N UMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
75	DPC104 416		047450474001 2 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
76	DNM103 981	26510342/ 901-048	294079505246 2 / MAIN ELEMENT, LENGTH 310MM O/D 153MM (2940-13-118-2373)	NTA855G2, PERKINS DIESEL GENERATOR 60 KVA	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DNM103 940	NR-20550/96	292072508958 7 / FOG GENERATOR TF-35 FOR CONTROL OF	FOR GENERATOR TF35FOR CONTROL (GERMANY)	1 / EACH/N UMBER	TF-35					TECHNICAL SPECIFICATION - IGEBA GENERAL SPECIFICATION - IGEBA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MOSQUITOES									
78	DNM103904	7W2327	2940795077526 / FILTER OIL	CATERPILLAR D/G ENGINE	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
79	DNM102373	0147-08-32 / 04149895	2815725051522 / SEAT INSERT INLET (CYLINDER HEAD)		12 / EACH/NUMBER	F8L413/F12L413					TECHNICAL SPECIFICATION - F8L413/F12L413 GERMANY. (CYLINDER HEAD) GENERAL SPECIFICATION - F8L413/F12L413 GERMANY. (CYLINDER HEAD)	
80	DNM103943	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	1 / EACH/NUMBER	HD 8/18-4 M* KAR					TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control GENERAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
81	DNH103801	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY	SELF	2 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, GENERAL, LG,					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			BRAND AS PER NHQ POLICY									
82	DNH103 914	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		8 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	DNH103 920		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	4 / EACH/NUMBER	WA60000 514					TECHNICAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W GENERAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W	
84	DNH103 902		4110735007240 / DEEP FREEZER 13CUFT 220AC 50/60HZ		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DNH103 913		4110705058486 / DEEP FREEZER 30 CUFT 220V 50HZ SINGLE	USER MRO LAHORE	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DNM102 078	6308ZZ	4620745049432 / PUMP BALL BEARINGS I/D40MM O/D 90MM	DISTILLATION PLANT ENTC-2.60	1 / EACH/NUMBER	ENTC-260					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
87	DNQ102 012	1-3-150 DEVELOPED BY DTD	4730992542747 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIOMENT	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
88	DNQ102 214	1-3-150 DEVELOP	4730992542747 / CLAMP	DAMAGE CONTROL	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		ED BY DTD	PIPE REPAIR-38-42MM LG 75MM	&FIRE FIGHTING EQUIOMENT	UMBER						SPECIFICATION - NO DATA AVAILABLE	
89	DNQ103 187	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL &FIRE FIGHTING EQUIOMENT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
90	DNM103 899	354/91	592570500895 1 / CIRCUIT BREAKER 600V 3POLE 50AMPS MODEL XE 50 NS MALASHIA	FOR STAP DOWN TRANSFORMOR	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Make: TERASAKI (Japan) 3P 50A b. Parent Equipment: Main Switch Board GENERAL SPECIFICATION - a. Make: TERASAKI (Japan) 3P 50A b. Parent Equipment: Main Switch Board	
91	DPK1043 28	Mobilux EP2	961179017039 6 / Mobilux Grease EP2 (16 OR 18 Kg Packing)		5 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
92	DPC104 058	HRC-407C (HFC-407C) GENETRON R-407C	683070511813 6 / GAS FOR (A/C) R-407C (packing = 11.3 kg) (Purity level 99% Min)	A/C SPLIT (02TONS)	102.15 / KILOGRAMME						TECHNICAL SPECIFICATION - OEM: HONEYWELL (USA) GENERAL SPECIFICATION - OEM: HONEYWELL (USA)	
93	DPK1045 42	20W-50	9150PK507948 0 / LUB OIL 20W50 PKG 4LTR ( FOR PETROL VEHICLES)	PETROL VEHICLES	20 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DPK1043 00	S-758/MIL-PRF-63460E/N YCOLUBE 127	915001053668 8 / CLEANER, LUBRICANT AND PRESERVATIVE WEAPON OIL	USE FOR DIESEL ENGINE/12.7 MM GUN, MPAC,MRTPS	15 / GALLON						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DPK1043 24	TYPE DEXRON	915070505244 2 / TORQUE		100 / LITER					TDS/BROCHER OR	TECHNICAL SPECIFICATION - SIZE: (01 LTR,04 LTRS,20 LTRS,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		II	CONVERTOR OIL							PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N.	208 LTR PACKING)GENERAL SPECIFICATION - SIZE: (01 LTR,04 LTRS,20 LTRS,208 LTR PACKING)	
96	DPK104541	TYPE DEXRON II	915070505244 2 / TORQUE CONVERTOR OIL		210 / LITER						TECHNICAL SPECIFICATION - SIZE: (01 LTR,04 LTRS,20 LTRS, 208 LTR PACKING)GENERAL SPECIFICATION - SIZE: (01 LTR,04 LTRS,20 LTRS,208 LTR PACKING)	
97	DNM102177	7139-540	291099829433 9 / LINER, TRANSFER PUMP	FUEL INJECTION PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DPK104331	TCW3 NMMA	072150000001 3 / LUB OIL OMD-23 FOR TWO STROKE OUTBOARD GASOLINE ENGINE NMMA GRADE TCW3		643 / LITER	NO DATA AVAILAB LE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N.	TECHNICAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLEGENERAL SPECIFICATION -ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE	
99	DNF103181	BG-424	599575512460 7 / CABLE ELECTRICAL MINIATURE 04 CORE FOR MIC	SRE SYSTEM ITALY	1260 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
100	DNM101917	140606941	471078523554 5 / OIL PIPE		1 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
101	DNM101903	2314F002	530578523561 6 / SCREW		26 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
102	DNM101910	131046650	530578523557 3 / SCREW		2 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
103	DNM101907	2481877	472078523563 1 / HOSE CLIP		2 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
104	DGE101318	HME-AB-CLAMP-	534070535124 3 / PIPE U		45 / EACH/NUMBER	SS304 SURFAC					TECHNICAL SPECIFICATION - PIPE U CLAMP PVC TYPE INNER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		PVC-20MM-009	CLAMP pvc type		UMBER	E					200mm outer dia 48mm height 38mm thickness 22mm GENERAL SPECIFICATION - PIPE U CLAMP PVC TYPE INNER 200mm outer dia 48mm height 38mm thickness 22mm	
105	DNM102425	067n3152	4820785312137 / thermostatic expansion valve		1 / EACH/UMBER	THERMOSTATIC EXPENSION VALVE tge 20					TECHNICAL SPECIFICATION - THERMOSTATIC EXPENSION VALVE TGE 20. MAX WORKING PRESSURE 49 BAR/711 psig GENERAL SPECIFICATION - THERMOSTATIC EXPENSION VALVE TGE 20. MAX WORKING PRESSURE 49 BAR/711 psig	
106	DNQ103819	RADTARG E-H	6665785274041 / HIGH SENSITIVE PERSONAL DOSIMETER		11 / EACH/UMBER	RADTAR GE-H					TECHNICAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time settig GENERAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time settig	
107	DNM101906	198217910	5310785235575 / SPRING		1 / EACH/UMBER	SDG15PS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
108	DPK104540	GB11120-2011 ISO VG 32	9140FP0010021 / ISO VG 32 GB11120-2011 TURBINE OIL		1 / LITER	GB11120-2011					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
109	DNM101911	135997120	2815785235668 / GASKET EXHAUST MANIFOLD		1 / EACH/UMBER	SDG15PS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
110	DRG103333	DIB-260	6140ZO6550740 / BATTERY LEAD ACID 24V (2 X 12V 220 AH) engine starter		1 / SET	DIB-260					TECHNICAL SPECIFICATION - Daewoo Deep Cycle Technology Batteries, Dimension: (519x217x269) (LxWxH) ,BATTERY LEAD ACID (12V 220 AH) general Specs: PACKAGE INCLUDES 02 X 12V	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											220AHGENERAL SPECIFICATION - Daewoo Deep Cycle Technology Batteries, Dimension: (519x217x269) (LxWxH) .BATTERY LEAD ACID (12V 220 AH) general Specs: PACKAGE INCLUDES 02 X 12V 220AH	
111	DNM102744	248-5513	5340715270350 / TEMPRATURE REGULATOR		4 / EACH/NUMBER	DE-660EO CATERPILLAR GENERATOR C18 600 KVA /480KW					TECHNICAL SPECIFICATION - TEMPRATURE REGULATORGENERAL SPECIFICATION - TEMPRATURE REGULATOR	
112	DNM101914	145537300	4730785235630 / HOSE		1 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
113	DNQ103824	15199001	4220795289489 / SOLAS SOFTPACK RFD (FIRST AID KIT) FOR LIFE RAFT - LIFE BOAT		9 / EACH/NUMBER	life raft					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
114	DNM101904	198217970	5140785235581 / TOOL		1 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
115	DNM101908	131246170	5310785235587 / BOLT		1 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
116	DNM101901	U11996410	5330785235657 / GASKET CYL HEAD COVER		1 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
117	DNM101909	2314F004	5306785235701 / SCREW		4 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
118	DGB101248	HME-AB-UNI-FERROL-20MM- 003	4730705351236 / union connector ferrol type dia 20mm		40 / EACH/NUMBER	SS304 SURFACE					TECHNICAL SPECIFICATION - UNION CONNECTOR TYPE FERROL DIA 20MM material stainless steel GENERAL SPECIFICATION - UNION CONNECTOR TYPE FERROL DIA 20MM material stainless steel	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
119	DNM101902	U45996051	533078523564 5 / GASKET THERMOSTST HSG		1 / EACH/N UMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
120	DNM101916	120216041	299078523553 2 / VALVE SPRING CAP		3 / EACH/N UMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
121	DNM101900	U35996951	533078523566 0 / GASKET		1 / EACH/N UMBER	SDG15PS					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
122	DNM101825	198586080 /T402621	311078523551 5 / BIG END BEARING KIT		1 / EACH/N UMBER	SDG15PS					TECHNICAL SPECIFICATION - PERKINS,DIESEL GENERATOR 15 KVA PERKINS ENGINE COMPANY LIMITED FRANK PERKINS WAY CAMBERIGH SHIRE PE 15 FQ UNITED KINGDOMGENERAL SPECIFICATION - PERKINS, DIESEL GENERATOR 15 KVA PERKINS ENGINE COMPANY LIMITED FRANK PERKINS WAY CAMBERIGH SHIRE PE 15 FQ UNITED KINGDOM	
123	DNN102751	STR100- WS-06	615050531267 5 / PDU (Power Distribution Unit)		2 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
124	DNH103409	058825A	444001310660 4 / DRYER CARTRIDGE/C ARTRIDGE, DEHYDRATOR		2 / EACH/N UMBER	o 26-d dps					TECHNICAL SPECIFICATION - 0 26-D DPS MEDIUM AIR CHARGIN RATE 26.4 SCFM INLET PRESSURE ATMOSPHERIC OPERATING PRESSURE 5000 PSIG AMBIENT TEMPERATURE 40 TO 115 F WEIGHT 2000 IBS APPROX TECHNICAL SPEC ENCLOSED GENERAL SPECIFICATION - 0 26-D DPS MEDIUM AIR CHARGIN RATE 26.4 SCFM INLET PRESSURE ATMOSPHERIC OPERATING PRESSURE 5000 PSIG AMBIENT TEMPERATURE 40 TO 115 F WEIGHT 2000 IBS APPROX TECHNICAL SPEC ENCLOSED	
125	DPK104477	SPIRAX S2 G 140	915079529305 0 / shell		2 / LITER	EMPERO EM.09.P					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SPIRAX S2 G 140								null	
126	DNM101912	U45996930	533078523564 1 / GASKET THERMOST HSG		1 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
127	DNM101898	U45537140	473078523569 1 / HOSE		2 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
128	DNM101899	U31426200	533178523560 2 / SEAL - INJECTOR		3 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
129	DSA101603	SC12SERI EWHA15-115V60HZ	411014324180 5 / FONTAINE REFT SC12		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB GENERAL SPECIFICATION - NO DATA AVAILAB LE	
130	DNM101915	2648A120	531078523556 0 / NUT		1 / EACH/NUMBER	SDG15PS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	