

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 29-07-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGB746 13	0140	403079515388 7 / SPLIT THIMBLES (316 STAINLESS STEEL)10MM	TAL SHIP SAILING RIG	14 / EACH/N UMBER			BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST,HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE. MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE. CO.UK	UK		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY ; BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE. SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX;+44(0) 1489578835. <u>GENERAL</u> SPECIFICATION - SOURCE OF AVAILABILITY ;BASELINE MARINE PRODUCTS LTD.UNIT 10 APPLE INDUSTRIAL ESTATE.WHITTLE AVENUE.SEGENSWORTH WEST, HAMPSHIRE.PO15 5SX UK.E MAIL; BASELINE.MARINE@BTINTERNET. COM.WEB;WWW. BASELINEHARDWARE.CO.UK TEL; +44(0)1489 576349.FAX;+44(0) 1489578835.	
2	DGT102 343	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	68 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 08 % to 18%	
3	DGB104 083	205426	345573522491 5 / disc CUTTING 5 INCH	CASINGS	8 / EACH/N UMBER	XT67	7*AH102	Rhodium Schleifwerkzeuge GmbH & co.KG GERMANY. www.rhodium-abrasives.com	RHODIUS		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
4	DGB103 985	205426	345573522491 5 / disc CUTTING 5 INCH	CASINGS	4 / EACH/N UMBER	XT67	7*AH102	Rhodium Schleifwerkzeuge GmbH & co.KG GERMANY. www.rhodium-abrasives.com	RHODIUS		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
5	DGD105 629	T52254 / E-6228	732099759431 1 / VEGETABLE PEELING MACHINE, ELECTRIC	GALLEY	1 / EACH/N UMBER	NO DATA AVAILAB LE		UK	HOBART MANUFA CTURING UK, STREET BRAUNT ON ROAD CITY BARNST APLE, STATE OR PROVINC E, DEVON, COUNTR Y UK POST-ZIP CODE. EX31 1GD, TELEPHO NE, 01271347 500, TELEFAX 01271347 502.		TECHNICAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT. 440V GENERAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT.440V	
6	DGH102 046	614599521 8490	614599521849 07 CABLE	CABLES	300 / METER	DG SHIPS 212	NA	MINISTRY OF DEFENCE (NAVY) SHIPS SUPPORT AGENCY	DG SHIPS 212 UK		TECHNICAL SPECIFICATION - AS PER NMCRL AND DG SHIPS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			POWER ELECTRICAL 3CORE 440V 34A					DME ME253, ROOM 19, BLOCK B FOXHILL, BATH, UK TEL: 01225 883293 FAX: 01225 883548			212GENERAL SPECIFICATION - AS PER NMCRL AND DG SHIPS 212	
7	DGE105 600	SFF6 1	259073517592 8 / POLYESTER BOAT LIFTING BELT 20000 KG LOAD	ENGINE	3 / EACH/NUMBER	NK	32568955	YONCA TURKEY LTD	YONCA		TECHNICAL SPECIFICATION - LENGTH 20 METER WLL 20000 KG BATCH NO YHTS-07-0105 TEMP -40 DEG C + 100 DEG C GENERAL SPECIFICATION - LENGTH 20 METER WLL 20000 KG BATCH NO YHTS-07-0105 TEMP -40 DEG C + 100 DEG C	
8	DGE104 681	SCOTCH 88	597099664876 4 / Tape, insulation, Electrical	0	50 / EACH/NUMBER	0	0	3M CENTRE, CAIN ROAD, BRACKNELL	3M UNITED KINGDOM PLC		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
9	DGE101 954	GGG-H-142	841500935190 6 / SAFETY HELMET YELLOW	PERSONAL PROTECTION	4 / EACH/NUMBER			FEDERAL SPECIFICATIONS UNITED STATES CAGE CODE 81348	FEDERAL SPECIFICATIONS		TECHNICAL SPECIFICATION - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000 GENERAL SPECIFICATION - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000	
10	DGE101 968	EM 3061	593572512993 6 / RAYCHEM HEAT SHRINK		2 / EACH/NUMBER			GR	GMBH GERMANY		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
11	DGE100 420		561099200438 6 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	50 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCR ETE UK LTD THE FLOORING TECHNOLOGIES CENTRE BOOTH LANE SANDBATCH CHESHIRE CW11 3QF UK PH: +44(0)		TECHNICAL SPECIFICATION - IN DESCRIPTION, LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&(M) DC&FF. GENERAL SPECIFICATION - IN DESCRIPTION, LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&(M) DC&FF.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									1270 753000 & FAX: +44 (0)1270 753333			
12	DGB101 274		027779923816 4 / TOOL BOX PORTABLE		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm <u>GENERAL</u> SPECIFICATION - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm	
13	DGE105 683		035059571323 5 / ROPE SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH (ROUNDED IN 9-MM)		120 / FATHOM						TECHNICAL SPECIFICATION - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554. <u>GENERAL</u> SPECIFICATION - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554.	
14	DGE105	BS2052	035059571324		40 /						TECHNICAL SPECIFICATION - 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	886	DEF STAN 40-3	6 / SPUN YARN SISAL S TWIST R. FROOFED 4/20 YARN LENGTH PER COIL 608-5% (FM)		KILOGR AMME						Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor) <u>GENERAL SPECIFICATION - 1.</u> Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor)	
15	DGE105 488		041370506324 3 / ANTI SKID DOTTED RUBBER FLOORING COLOUR GREEN 15" X36"0.17"		20 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
16	DGE102 322		041359923889 6 / SHEET RUBBER SOLID NATURAL OFF WHITE SQ 02 LBS 0.250 X48X72IN		25 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
17	DGE974 84	0413-8532 & 0413_92 3_8899, BS1154	041359923889 9 / RUBBER SHEET, SOLID, NATURAL RUBBER, LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI		300 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - RUBBER SHEET, SOLID, NATURAL RUBBER, LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21</u> <u>GENERAL SPECIFICATION - RUBBER SHEET, SOLID, NATURAL RUBBER, LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
18	DGE102 293	0413-8532 & 0413_92 3_8899, BS1154	041359923889 9 / RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI		200 / KILOGR AMME						MOAWIN/03/10085084 dated 13 aug 21 <u>TECHNICAL SPECIFICATION-</u> RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 <u>GENERAL SPECIFICATION-</u> RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21	
19	DGE101 627	0413-8532 & 0413_92 3_8899, BS1154	041359923889 9 / RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI		650 / KILOGR AMME						<u>TECHNICAL SPECIFICATION-</u> RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 <u>GENERAL SPECIFICATION-</u> RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42 , HARDNESS RATING 42-50°, TENSILE STRENGTH : 2500 PSI packing requirement: standard packing Updated vide	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21	
20	DGE105495	0413-8522	0413599238913 / RUBBER SHEET SOLID NATURAL (48 inch X 72 inch x 1/4 inch)	CONT OIL TANKS	100 / KILOGRAMME						TECHNICAL SPECIFICATION - ITEM SPECIFICATION: STANDARD BS.1154.GENERAL SPECIFICATION - ITEM SPECIFICATION: STANDARD BS 1154.	
21	DGE104684	0.75X0.007INCH-50MTR-	0559790015244 / INSULATION-TAPE-VARNISHED WOVEN GLASS-FIBRE-(STRAIGHT CUT)		20 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DGE100800	0413-2556	0413599237038 / HOSE POLYVINYL PVC INT 0.375 ET 0.77 L 14.5 3PSI WT 3LB S/Q"		50 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DGE101132		0350595713032 / ROPE COIR HAWSERLAID CIR 2"		400 / FATHOM						TECHNICAL SPECIFICATION - 3 STRD CIR 2" DIA 0.625 MATERIAL COIR (Husk of CoConut)GENERAL SPECIFICATION - 3 STRD CIR 2" DIA 0.625 MATERIAL COIR (Husk of CoConut)	
24	DGE97847	NIL	0476599430558 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OUNCES	
25	DGE102392	LETTER NO.E-1/4927/A/445DT050902	0461590003914 / CLOTH POLESHING		150 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DGE101981	NIL	0559794444898 / INSULATION SLEEVE ELECTRIC INT DIA 3MM THICK 0.500 MATER CERAMIC	GENERAL ELECTRIC USE	43 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
27	DGE105806	nil	0350595713121 / Rope Nylon, Hawser laid, White, 3-Strand, Cir. 1-Inch, Diameter: 8-MM		360 / FATHOM						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO.9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL- 120 FATHOM, 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
28	DGE105606		035059571312 8 / ROPE NYLON, HAWSERLAID, 3-STRAND, Z-LAY, NOM DIA: 20MM, (13/16") CIRC: 2.50 INCH, TYPE-1		780 / FATHOM						<u>TECHNICAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI <u>GENERAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTES	
29	DGE103 042		035059571312 8 / ROPE NYLON, HAWSERLAID, 3-STRAND, Z- LAY, NOM DIA: 20MM, (13/16") CIRC: 2.50 INCH, TYPE-1		400 / FATHO M						TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM, 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI	
30	DGE97706		043359924862 6 / KNIFE, DIVERS (SHEATH 7" & HANDLE 5)	OEM: USA, ITALY(SS MATERIAL, MAGNETIC TYPE)	1 / EACH/ NUMBER	RC 558000					TECHNICAL SPECIFICATION - Material Stainless Steel Blade Length: 17.8 cm/7.01 inch Overall Length: 30 cm/11.82 inch Blade Width: 32mm/1.25 inch Blade Thickness: 5.5mm/0.22 inch Knife Weight: 450gm/0.99 LB Weight with Seaboard: 600gm/1.32 LB GENERAL SPECIFICATION - Material Stainless Steel Blade Length: 17.8 cm/7.01 inch Overall Length: 30 cm/11.82 inch Blade Width: 32mm/1.25 inch Blade Thickness: 5.5mm/0.22 inch Knife Weight: 450gm/0.99 LB Weight with Seaboard: 600gm/1.32 LB	
31	DGE101	0415-2501	041559923144		10 /						TECHNICAL SPECIFICATION - DEF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN. SPECS	Dimension
	905		9 / CORK AND RUBBER SHEET SIZE. 36"X24"X1/16" THICK		SHEET						SPEC 22GENERAL SPECIFICATION - DEF SPEC 22	
32	DGB104 434	BS 1476	028359571122 9 / ANGLE-ALUMINIUM-ALLOY-2" EQUAL SIDED THK3/16" WT/FT 0.84 LB		2 / METER						TECHNICAL SPECIFICATION - BS 1476GENERAL SPECIFICATION - BS 1476	
33	DGB102 031		028359571143 3 / ROD NAVAL BRASS HEX SIZE A/F 1.10"WT PER FT 3.910(LB)		1 / METER						TECHNICAL SPECIFICATION - SPECS BSEN 12163, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet GENERAL SPECIFICATION - SPECS BSEN 12163, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet	
34	DGB102 451	NO DATA AVAILABLE	028359571115 5 / SHEET ALUMINIUM ALLOY ANNEALED		11 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN:573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).GENERAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN: 573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).	
35	DGB102 099		028359571147 4 / SHEET-NAVAL-BRASS-ANNEALED 48		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
36	DGE101 635	NO DATA AVAILABLE	043452000015 6 / LEAD WEIGHT IKG WITH CLAMP TYPE LOCK, T-40761	DIVING BREATHING APPARATUS T-9651 LARIII	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DGE101 988	0413-8553	041359923892 6 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		25 / KILOGRAMME						TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50" GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"	
38	DGE101 544	0413-8553	041359923892 6 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		87 / KILOGRAMME						TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50" GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"	
39	DGE105 686		035059571317 3 / ROPE SISAL, BOLT ROPE AND STAGE LASHING, 3-STRAND, CIR: 1", DIA: 0.3125" (8-MM)		240 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. 7. OEM: M/S COTESI GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. 7. OEM: M/S COTESI	
40	DGE101 955	NO DATA AVAILABLE	041359923969 2/ HOSERUBBER NATURALRUB BERINNERSU RFACECOTTO NBRANDEDRE INFORCEMEN TINTERNALDI A2: 00NOPLIES3" WALTHIK23/64		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DGB104 060		021259571028 3 / BAR STEEL CARBON HOT ROLLED FLAT 04"X3/8"WT. PER FT 5.10		30 / METER						TECHNICAL SPECIFICATION - RELEVANT SPECS i.e BS 970 EN 3A GENERAL SPECIFICATION - RELEVANT SPECS i.e BS 970 EN 3A	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LBS									
42	DGB103 263		026578423344 8 / PAD LOCK EACH SUPPLIED WITH 2 KEYS 2.500" STEEL 6LEVER CHUBB	MATERIAL IS STWOED WITH IN A LOCKED CAGE	12 / EACH/N UMBER						TECHNICAL SPECIFICATION - BATTLE SHIP FOR USE ON BUILDING. makes: KHAS, EHSAN, SIALKOT and POWER.GENERAL SPECIFICATION - BATTLE SHIP FOR USE ON BUILDING. makes: KHAS, EHSAN, SIALKOT and POWER.	
43	DGB101 888		026759521328 5 / Piping Steel Galv 3050x4. 0x0.250		240 / METER						TECHNICAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable.GENERAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable.	
44	SGB104 441		021450214058 6 / Bolt and Nut Steel Head Hexagonal		260 / EACH/N UMBER						TECHNICAL SPECIFICATION - MATERIAL: BS 1210 Length: 8.750 inch Dia: 0.625 inch Full threaded TPI 11 GENERAL SPECIFICATION - MATERIAL: BS 1210 Length: 8.750 inch Dia: 0.625 inch Full threaded TPI 11	
45	DGB103 982		026859000146 7 / WEIGHING- MACHINE- WITH-HOOK-1- TO-30-POUND		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE.GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	SGB104 440		026759923526 7 / COUPLING PIPE GALV. BORE 1.00 INCH		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - PIPE BORE 1'.00 INCH MATERIAL MS (GALVANIZE).GENERAL SPECIFICATION - PIPE BORE 1'.00 INCH MATERIAL MS (GALVANIZE)	
47	DGH104 059		021250212049 0 / BAR STEEL CHANNEL SIZE 3.50"X2"		2 / METER						TECHNICAL SPECIFICATION - Item Specification:BS EN OF 2004, GRADE S-275 JR.GENERAL SPECIFICATION - Item	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			X5/16"								Specification:BS EN OF 2004, GRADE S-275 JR	
48	DGB105 281	NO DATA AVAILABLE	027259272007 2 / DRILL-TWIST-TAPER-SHANK-HSS-9MM		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - size: 9 mm material: hss Hardness: HRC65-66; hss jobber drill-general purpose a100, 9.00mm GENERAL SPECIFICATION - size: 9 mm material: hss Hardness HRC65-66; hss jobber drill-general purpose a100, 9.00mm	
49	DGE105 964		033059571325 9 / TWINE NYLON MARLINE 3 STRD POLISHED MIN BKG STRENGTH 280 LBS		10 / KILOGRAMME						TECHNICAL SPECIFICATION - BKG STRENGTH 280 LBS TWINE NYLON MARLINE 3 STRD POLISHED (Dia 1.10 mm) PAKING: Standard available GENERAL SPECIFICATION - BKG STRENGTH 280 LBS TWINE NYLON MARLINE 3 STRD POLISHED (Dia 1.10 mm) PAKING: Standard available	
50	DGE105 685	NIL	035059923712 8 / ROPE NYLON, HAWSERLAID, Z-LAY, 3-STRANDS, NOM DIA: 20MM, CIRC: 2.50 INCH, TYPE: 1, MINIMUM BREAKING LOAD: 8.3 TONS	MIN BRKG STRENGTH UNIT OF AVAILABILITY	240 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM, 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1. TO BE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM, 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
51	DGE105 687	NIL	035059923713 1/ ROPE NYLON HAWSERLAID, 3-STRAND, Z- LAY TYPE-I, SIZE: CIRC 4", NOM.DIA: 32MM	BRKG STRENGTH UNIT OF AVAILABILITY 322LB	120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM, 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM, 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
52	DGE105 963	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, - NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 728	120 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
53.	DGE105 604	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	240 /- FATHO M						ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/BREAKING STRENGTH OF STORES.	
											<u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM, 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E</u> DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM, 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
54	DGB105 280		027250272004 0 / DRILL- PARALELL- SHANK-3MM CARBON STEEL		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Material HSS, Hardness HRC65-66. <u>GENERAL SPECIFICATION -</u> Material HSS, Hardness HRC65-66.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
55	DGB103 207	0257-13023	0257704195010 / NUT PLAIN HEXAGON BRASS BSW THD-SZ 0.500 IN HEIGHT0.437 IN		450 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DGB103 883		0263594149704 / SHACKLE STRAIGHT TO SCREW FOR RIGGING		25 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DGB103 962	BRAND (MADE IN WEST GERMANY)	0243702431004 / AGRICULTURAL SPRAYER MODEL GLORIA (172 RTG) CAPACITY 10 LITER		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DGB103 204	NO DATA AVAILABLE	0257709411508 / NUT-PLAIN-HEXAGON-THREAD-SIZE. 875LH.770 (brass)		8 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DGD105 630	NO DATA AVAILABLE	0035546001020 / COVERS FOR UTENSIL COOKING IT LARGE		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DGB102 630		0267595213278 / PIPING STEEL GALVANIZED SEAMLESS, L: 6.1 M, E/DIA 26.9MM, TH 2.6 MM, N/BORE:18.1 MM	UTS LENGTH. BULK SUPPLY	36 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS GENERAL SPECIFICATION - BSEN 10216-2 OF 2019, GRADE P265GH, FOR GALVANIZING BS EN ISO 10240 GALVANIZING THICKNESS: 40 MICRONS	
61	DGE102 019		2040PK5101052 / RUBBER SHEET SIZE	FENDER	20 / KILOGRAMME						TECHNICAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR/NO OF PR	MANUF ADO.	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WEIGHT: 10-KG, LENGTH: 7-ft, WIDTH: 1-FT, THICKNESS: 3/8-INCH								COMPOUND: NR DARDNESS (SHORE A): 50±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@LIVE.COM (2) LONGMAN KAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552 GENERAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@LIVE.COM (2) LONGMAN KAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552	
62	DGH103 803		056159000798 9 / Cable Elect 3 Core		44.5 / METER						TECHNICAL SPECIFICATION - Material: Copper Size: 7/44 Capacity: 30A oem: pak cable GENERAL SPECIFICATION - Material: Copper Size: 7/44 Capacity: 30A oem: pak cable	
63	DGH103		056159018066		200 /						TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN. SPECS	Dimension
	757		7 / CABLE ELECTRIC NO. OF CORES 2, SIZE OF COND. (IN) 182/0076,		METER						DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DGE99584	C-134	0851580000076 / DEFENCER EAR C-134 62TD		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DGE105492	C-134	0851580000076 / DEFENCER EAR C-134 62TD		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
66	DGB101951	C60	0474504481497 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	FOUNDRY USE OEM MORGANITE UK FAX NO	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
67	DGB103203	C60	0474504481497 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	FOUNDRY USE OEM MORGANITE UK FAX NO	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
68	DGB103595	C60	0474504481497 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	FOUNDRY USE OEM MORGANITE UK FAX NO	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
69	DGE101558	NO DATA AVAILABLE	0461546005683 / PAPER ABRASSIVE WATER PROOF 9" X11"		30 / SHEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DGE105887	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR-NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			X 26 FT								AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC. 1.25 INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN. NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH; LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
71	DGE101965	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT.	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4. ADJUSTABLE (DIA: 08 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONG WITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4. ADJUSTABLE (DIA: 08 INCH, LENGTH: 08 FT, QTY: 06 IN NOS	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO. OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WITH SEAMLESS OR WELDED.	
72	DGE105801	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
73	DGE100897	NO DATA AVAILABLE	424050508870 5/ CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	2/ EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(50854D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 08 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION:- 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D); (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD;	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUFACTO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
74	DGE101-129	NO DATA AVAILABLE	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						(DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4. ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (08 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50854D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
75	DGB101 841	CATLOG- NO.(USA) 42-059- 008WHITE	343971506689 2/ ELECTRODE (WHITE)TUFF COTE CUTTING UWATER DIA 5/16X18	FOR GENERAL USE	300 / PACKE T						<u>TECHNICAL SPECIFICATION -</u> Size: 3/8" x 18" Polarity: DC Electrode Negative (DCEN) Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration Material: Low Carbon Steels Technique: Use short Arc length with electrode angle 30° +15°, to the line of weld. UTILIZED DURING UNDERWATER WELDING OPERATION. MUST BE AS PER ISO 9000 STANDARD. MUST HAVE WATER PROOF COATING. <u>GENERAL SPECIFICATION - Size:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											3/8" x 18" Polarity: DC Electrode, Negative (DCEN) Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration Material: Low Carbon Steels Technique: Use short Arc length with electrode angle 30o.+15o, to the line of weld. UTILIZED DURING UNDERWATER WELDING OPERATION. MUST BE AS PER ISO 9000 STANDARD. MUST HAVE WATER PROOF COATING.	
76	DGE105 684	NIL	402099923712 1 / ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00", DIA 0.3125" (8MM)	NGTH 1.330 TONS UNIT OF AVAILABILITY	240 / FATHO M						<u>TECHNICAL SPECIFICATION - 1</u> 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. <u>GENERAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM	
77	DGE105 803	BS 2052	402099942504 2 / ROPE SISAL HAWSERLAID CIR 12MM 3 STRAND	MIN BKG LOAD 955 KG	120 / FATHO M						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
78	DGE103 919	8931290	381573100180 0 / HELMET PLASTIC P/N 8931290 COLES 16T	COLES CRANE 16 TON	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DGB103 963	SKF-6207 ZZ	311099119954 6 / BEARING BALL JOURNAL SKF-6207ZZ 035X072X17M M	GENERAL ITEM	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
80	DGB101 840	NO DATA AVAILABLE	343971504503 2 / WET WELDING ELECTRODE UW-CS-1 (1/8" OR 3.2 MM)	UNDERWATE R WELDING DURING SALVAGE OPS/TRAININ G	1000 / PACKE T						TECHNICAL SPECIFICATION - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration GENERAL SPECIFICATION - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration	
81	SGB104 140	0254-254009	473099420313 4 / TEE EQUAL	FOR GENERAL USE	30 / EACH/N UMBER						TECHNICAL SPECIFICATION - TEE EQUAL IS DN 1.5" AND MATERIAL IS EITHER BRASS, BRONZE OR GUN METAL DIMENSION: BORE 1 1/2" material: LEADED GUNMETAL-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LG2 tensile strength mpa: 270 material grade: BS-1400 GENERAL SPECIFICATION - TEE EQUAL IS DN 1.5" AND MATERIAL IS EITHER BRASS, BRONZE OR GUN METAL DIMENSION: BORE 1 1/2" material: LEADED GUNMETAL-LG2 tensile strength mpa: 270 material grade: BS-1400	
82	DGB103016		5306999418759 / BOLT PRECISION HEXAGON HEAD UNC SZ 1 1/2X1 1/4X1/2" TPI.13	FASTENINGS, BOLTS AND STUDS.	30 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	DGE103221	A-A-1201, P-P-121, ANSIB74-18	5350001868820 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE 110-A		70 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
84	DGE101586	A-A-1201, P-P-121, ANSIB74-18	5350001868820 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE 110-A		20 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DGE101581	GRADE 320	5350PK5104070 / WATER PROOF SAND PAPER GRADE 320	WOODEN & GRP BOATS,, AQUATIC CLUB D/YARD	50 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DGE101598	GRADE 400	5350PK5104071 / WATER PROOF SAND PAPER GRADE 400	WOODEN & GRP BOATS,, AQUATIC CLUB D/YARD	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
87	DGE104415	nil	5640008096312 / INSULATION		5 / SHEET						TECHNICAL SPECIFICATION - SPECIFICATION/SIZES: 1. MIL-I-742 TYPE-I, 2. OVERALL LENGTH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BLOCK, THERMAL FIBERGLASS (THICKNESS 1 INCH)								36 INCH NOMINAL, 3. OVERALL WIDTH: 24 INCH NOMINAL, 4. OVERALL THICKNESS: 01 INCH NOMINAL, 5. MATERIAL: GLASS FIBER, 6. DECORATIVE SIDE TYPE: FIBER GLASS CLOTH-COTATED, 7. PACKING LEVEL: A, AS PER SPECS MIL-I-742, TY-1, 8. ORIGIN: USA.GENERAL SPECIFICATION - SPECIFICATION/SIZES: 1. MIL-I-742 TYPE-I, 2. OVERALL LENGTH: 36 INCH NOMINAL, 3. OVERALL WIDTH: 24 INCH NOMINAL, 4. OVERALL THICKNESS: 01 INCH NOMINAL, 5. MATERIAL: GLASS FIBER, 6. DECORATIVE SIDE TYPE: FIBER GLASS CLOTH-COTATED, 7. PACKING LEVEL: A, AS PER SPECS MIL-I-742, TY-1, 8. ORIGIN: USA.	
88	DGE102 480	ECW0090 3-12	593572507749 2 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SIZE 48/16 LG 1 METER		5 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
89	DGE105 603	ECW0090 3-12	593572507749 2 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SIZE 48/16 LG 1 METER		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
90	DGE104 421	000W280	599999784543 2 / BRAID-BANDAGE (WIRE MES KNITTED)	GLASS WOOL (DC BOX)	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
91	DGE101 835	0413-2184	597099923966 4 / TAP INSULATION ELECT ADHESIVE	FOR RED PHASE	14 / EACH/N UMBER						TECHNICAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing GENERAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing	

S. No.	EPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PLASTIC RED W1								details: 10-12 in each packing	
92	DGE105490	SA9-27077PF.	6260011785560 / LIGHT, CHEMILUMINE SCENT 6inch BLUE	REPLENISHMENT LIGHT	315 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
93	DGE100813	NIL	5970705047303 / nomex paper-12		5 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DGB104646	NO DATA AVAILABLE	0266590033358 / SCREW MACHINE STEEL BSW HEX HD SZ 1.75X0.500 IN		350 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION: BS-970 MATERIAL GRADE: EN-07 GENERAL SPECIFICATION - SPECIFICATION: BS-970 MATERIAL GRADE: EN-07	
95	DGE105970	NO DATA AVAILABLE	0330500000018 / POPLIN CLOTH TARTAN GREEN WIDTH 36	GENERAL USE FOR BATTERIES OF S/MS	40 / YARD	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - material composition of 100% cotton WIDTH = 36" GENERAL SPECIFICATION - material composition of 100% cotton WIDTH = 36"	
96	DGD105962	LG-MP-9482 SR	7310735118939 / MICROWAVE OVEN-LG SHARP WAVES/DAWLANCE & TOSHIBA	MICROWAVE OVEN LG	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - capacity: 36 LITERS GENERAL SPECIFICATION - capacity: 36 LITERS	
97	DGB102165	NO DATA AVAILABLE	0268500000036 / AVERY-SCALE-PLATFORM-NO3205CAPACITY250KG SELF INDICATING	AND MOUNTED ON WHEEL SIZE OF PLATFORM24"	2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DGD69266	NO DATA AVAILABLE	7730705048053 / PLATE DINNER 26CM GOLDEN CRESTED		124 / EACH/NUMBER						TECHNICAL SPECIFICATION - 26CM GOLDEN CRESTED, MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) plate dinner o/a dia 26 cm golden	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											crestedGENERAL SPECIFICATION - 26CM GOLDEN CRESTED, MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) plate dinner o/a dia 26 cm golden crested	
99	DGD105446		7730705048075 / plate Dinner 23cm blue crested (as per stock sample)		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material: PORCELINGENERAL SPECIFICATION - Material: PORCELIN	
100	DGE105605	NO DATA AVAILABLE	0415780000093 / JARY. CANE, 729 MS. CAPACITY.		60 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - daimention: 14" x 6" x 18" capacity: 10 ltrsGENERAL SPECIFICATION - daimention: 14" x 6" x 18" capacity: 10 ltrs	
101	DGE100598	NO DATA AVAILABLE	0461500000024 / PAPER ABRASIVE 9" X11" WATERPROOF MATERIAL EMERY GRADE P-120D		20 / SHEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
102	DGE100798	NIL	8105011242645 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217-9451	STATIC SAFETY OF EQUIPMENT/COMPONENTS	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557GENERAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
103	DGE101722		8340PK5073827 / TENT 400 LBS DOUBLE PLY WITH		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COMPLETE ACCESSORIES								FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. GENERAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH). b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM $\pm$ 02 MM & THICKNESS 02 MM $\pm$ 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM $\pm$ 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
104	DGE101964		813570506488 2 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DGT96698	NO DATA AVAILABL E	010000000000 3 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	48 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DGE105820	NO DATA AVAILABL E	031050000000 6 / CANVAS COTTON NATURAL GREY (WD: 36 INCH)		100 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: Features: Water proof and Rot Proof Width & Length: 36" and 50 Meter roll Weight: 12 OZ per Sq. Yard Colour: Natural Grey. GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY. GENERAL SPECIFICATION - SPECIFICATION: Features: Water proof and Rot Proof Width & Length: 36" and 50 Meter roll Weight: 12 OZ per Sq. Yard Colour: Natural Grey GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY.	
107	DGE105 819	NO DATA AVAILABLE	0310500000009 / CANVAS COTTON NATURAL (WD: 24")		100 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - SPECIFICATIONS:</u> WIDTH: 24" WIGHT PER SQ YARD: 18 OZ COLOR: NATURAL WATER PROOF AND ROT PROOF, VARIETY NO 5 SHRINKING 3%, WARP: 3 X 59 (10S/3) WEFT: 4 X 59 (10S/4) MIN TESIL STRENGTH: 5 X 20 CM STRIP : 315 LBS GEN SPECS: PS - 319 OF 1986 ADVANCE SAMPLE TO BE APPROVED BY CINS <u>GENERAL SPECIFICATION - SPECIFICATIONS:</u> WIDTH: 24" WIGHT PER SQ YARD: 18 OZ COLOR: NATURAL WATER PROOF AND ROT PROOF, VARIETY NO 5 SHRINKING 3%, WARP: 3 X 59 (10S/3) WEFT: 4 X 59 (10S/4) MIN TESIL STRENGTH: 5 X 20 CM STRIP : 315 LBS GEN SPECS: PS - 319 OF 1986 ADVANCE SAMPLE TO BE APPROVED BY CINS	
108	DGE105 802	NO DATA AVAILABLE	834050503926 1 / SHAMIANA SIZE 18 X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare. 7. Hammer: 05 Lbs with handle. qty 01. 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length. 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN. SPECS	Dimension
											COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos <u>GENERAL SPECIFICATION - 1.</u>Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare. 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos	
109	DGE105 636	NO DATA AVAILAB E	834050503926 1 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare. 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos <u>GENERAL SPECIFICATION</u> :- 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White, (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare. 7. Hammer: 05 Lbs with handle. qty 01:8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length. 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos	
110	DGE99669	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	4 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					<u>TECHNICAL SPECIFICATION</u> :- 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
111	DGT105 496	NO DATA AVAILABL	010050000001		1052 / SQ	NO DATA AVAILAB					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR-NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	5 / PLY WOOD GRADE-1, 5 PLY		FEET	LE					SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) GENERAL SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
112	DGT105 611	NO DATA AVAILABL E	010050000001 5 / PLY WOOD GRADE-1, 5 PLY		996 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) GENERAL SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
113	DGB103 641	STEEL LARGE SZ W/KEY (K2575-1960)	846599411126 7 / HAND CUFFS STEEL ADJUSTABLE RATCHET TYPE CHROME PLATED BRIGHT	PNS NIGRAN	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
114	DGT103 956	BELFONT TRUWOOD TEAK	933099224609 7 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		4 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
115	DGH101 881	QQ-F-481	951500187395 5 / SHEET MILD STEEL	GENERAL USE	100 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
116	DGB104 544	SPEC: BS 1477/NP8-M	953599571114 3 / PLATE ALUMINIUM ALLOY 180X48X0.375 INCH.WT PER SQFT 5.180 LB (AL6082/AL5083 GRADE)		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Properties: a. Chemical COMPOSITION. AL 5083: ALLOY OF aluminum MAGNESIUM AND CHROMIUM. AL 6082: ALLOY OF ALUMINUM SILICON CHROMIUM. Remarks: 5083 grade is good choice for structural applications such as shipbuilding/ fabrication of structures etc. PROPERTIES: B. Strength. AL 5083: Higher Strength Than 6082, AL 6082: Lower strength than 5083. REMARKS: THE ADDITION OF CHROMIUM MAKES 5083 MORE RESISTANT TO CORROSION. (BEST FITTED FOR MARINE	

SR No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ENVIRONMENT) C. PROPERTIES: WELDABILITY BOTH CAN EASILY BE WELDED. PROPERTIES: D. MACHINABILITY. AL 5083: LOWER MACHNIABILITY THAN 6082. AL 6082: BETTER MACHNIABILITY THAN 5083. remarks: 1. BS EN 573-3Of 1995(Checal Composition) 2. BS EN 485-2 of(mechanical properties) gRade; al 5083 & al 6082 temper: "T" 2.bs-en-573-3 of 1995 material grade al 5083 and bs en-485-2 (mechincal properties) grades (i.e AL 5083 & AL 6082) <u>GENERAL SPECIFICATION -</u> Properties: a. Chemical COMPOSITION. AL 5083: ALLOY OF aluminum MAGNESIUM AND CHROMIUM. AL 6082: ALLOY OF ALUMINUM SILICON CHROMIUM. Remarks: 5083 grade is good choice for structural applications such as shipbuilding/ fabrication of structures etc. PROPERTIES: B. Strength. AL 5083: Higher Strength Than 6082, AL 6082: Lower strength than 5083. REMARKS: THE ADDITION OF CHROMIUM MAKES 5083 MORE RESISTANT TO CORROSION (BEST FITTED FOR MARINE ENVIRONMENT) C. PROPERTIES: WELDABILITY BOTH CAN EASILY BE WELDED. PROPERTIES: D. MACHINABILITY. AL 5083: LOWER MACHNIABILITY THAN 6082. AL 6082: BETTER MACHNIABILITY THAN 5083. remarks: 1. BS EN 573-3Of 1995(Checal Composition) 2. BS EN 485-2 of(mechanical properties) gRade; al 5083 & al 6082 temper: "T" 2.bs-en-573-3 of 1995 material grade al 5083 and bs en-485-2 (mechincal properties) grades (i.e AL 5083 & AL 6082)	
117	DGD105 624	FOR SALT SPACES	732070501242 7 / MACHINE		1 / EACH/N						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUFACTO	Availability	Tender Remarks	TECH/ GEN SPECS	Dimension
		CAP 100 KGS IN	GRINDING AUTOMATIC 440V 3 PHASE 50HZ 2HP SIZE 12INCH		UMBER						SPECIFICATION - NO DATA AVAILABLE	
118	DGD105 626		732070501321 4 / TOASTER TWO SLOT 220V 50HZ 01 PHASE 920W	FOR DOMASTIC USE	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Make/ Model / Brand/ Equivalent be endorsed: Panasonic/ Dawlance/ West point a. Make/ Model of item Moulinex LT 140827 Black & Decker ET 222 Philips HD 2637/90 b. OEM COC/ authorized dealer certificate/ mill test certificate (MTC): Not required GENERAL SPECIFICATION - a. Make/ Model / Brand/ Equivalent be endorsed: Panasonic/ Dawlance/ West point a. Make/ Model of item Moulinex LT 140827 Black & Decker ET 222 Philips HD 2637/90 b. OEM COC/ authorized dealer certificate/ mill test certificate (MTC): Not required	
119	DGD787 16		734070506081 3 / PASTRY FORK		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material S/S 304 FOOD GRADE NON Magnetic (LOCAL) GENERAL SPECIFICATION - Material S/S 304 FOOD GRADE NON Magnetic (LOCAL)	
120	DGD104 860	MS-563XD LG	734070511750 1 / MICROWAVE OVEN LG 56 LTRS		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
121	DGE105 494	IS8021	047654600478 5 / Coated Rigger Gloves with Rubberized Cuff		70 / PAIR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DGD105 437	NO DATA AVAILABL E	003550000045 2 / UTENSILS COOKINGALU M O/D 10" TO 10.5" "H 4" TO 5.5" TH 12		9 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd) DIMENSION: O/D 10" to 10.5" "H 4" to 5.5" TH 12 SWg ALUMINIUM GRADE 3003, 1100.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SWH WITH COVER								2024 AND 5052 GENERAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd) DIMENSION: O/D 10" to 10.5" "H 4" to 5.5" TH 12 SWG ALUMINIUM GRADE 3003, 1100, 2024 AND 5052	
123	DGD105440		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		5 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWGGENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
124	DGD93342		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		4 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWGGENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
125	DGD105619	NO DATA AVAILAB LE	0035500000507 / STRAINERSRICE FOR POTS ALU 20X10 INCH		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kgGENERAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kg	
126	DGD105439		0035500000520 / UTENSILS COOKING		5 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR-NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ALUMINUM O/D 24 TO 26" .H12 TO 14" TH 10 SWG WITH OUT COVER								FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER <u>GENERAL SPECIFICATION - SPECIFICATION:</u> FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
127	DGD99216	NO DATA AVAILABLE	0035500000318 / Aluminium covers for utensil cooking (Large) O/D. 25.50" TH 10 SWG.		14 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned. a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers. <u>GENERAL SPECIFICATION -</u> Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) alongwith Packing details. a. Galley utensil used to cove the cooking pots. b. Packed in cardboard and poly bags. Detailed Specifications/ Technical data/ Testing/ Acceptance Criteria be mentioned: a. Food grade stainless steel must be rust and lead free. b. Grade of 18/08 or 18/10 stainless steel recommended for cooking. c. Magnet test Magnet should not stick to the covers.	
128	DGD103214	NO DATA AVAILABLE	0035500000454 / UTENSIL COOKING ALUMINIUM WITH COVER O/D 16-17".		4 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) <u>GENERAL SPECIFICATION -</u> Aluminium Grade	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESS 10 SWG								1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD)	
129	DGD105 441	NO DATA AVAILABLE	003550000045 4 / UTENSIL COOKING ALUMINIUM WITH COVER O/D 16-17", INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESS 10 SWG		3 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) GENERAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD)	
130	DGD105 617		003554600061 4 / POT ALU 15/7" WITH COVER		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 200 TO 250 LBS GENERAL SPECIFICATION - 200 TO 250 LBS	
131	DGD105 615		003554600061 5 / Pot Aluminum 18/9" With COVER		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 18 Gauge Aluminum Pot having Capacity of 250 lbs Aluminum grade (as food grade and lead free) GENERAL SPECIFICATION - 18 Gauge Aluminum Pot having Capacity of 250 lbs Aluminum grade (as food grade and lead free)	
132	DGD105 623	NO DATA AVAILABLE	003550000036 5 / KNIFE BUTCHER (OVER ALL LENGTH 38 CM) BLADE WIDTH 4 CM		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
133	DGD105 621	NO DATA AVAILABLE	003550000038 0 / LADLE COOK 1/2 PINT		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Stainless Steel Grade 316, Handl material Hand wood (Length 8 inch Sisso, kahoo, walnut etc) GENERAL SPECIFICATION - Stainless Steel Grade 316 Handl material Hand wood (Length 8 inch Sisso, kahoo, walnut etc)	
134	DGE105 602	565665	534070524611 1 / leatherite for		2000 / SQ	565665					TECHNICAL SPECIFICATION - leatherite wallpaper	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			wallpaper		FEET						sheetsGENERAL SPECIFICATION - leatherite wallpaper: sheets	
135	DGE103 996	nil	663078532704 5 / OIL ONLY PILLOWS		20 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - DIMENSION: 40 X 50CM ABSORBING CAPACITY: 184 LITRES PACKAGING: 10/BAGGENERAL SPECIFICATION - DIMENSION: 40 X 50CM ABSORBING CAPACITY: 184 LITRES PACKAGING: 10/BAG	
136	DGE102 350	d000-004	844073527072 0 / cotton gloves (pack of 12 gloves)		5 / PAIR	na					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
137	DGP085 37	A360 PLUS	702571531623 4 / A3 SIZE FLATBED SCANNER		1 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
138	DGE103 994	nil	663078532704 8 / OIL ONLY SOCKS		24 / PAIR	N/A					TECHNICAL SPECIFICATION - DIMENSION: DIAMETER 76-CM, LENGHT 1.2M, ABSORBING CAPACITY: 43 LITERS, PACKAGING: 12/BOX, COLOUR: YELLOW, MATERIAL: SHREDDED POLYPROPYLENE, OTHER FEATURES: ABSORB VARIOUS STRONG ACID/ALKALI SOLUTIONS, ABSORB VARIOUS LIQUID SOLVENTS, SUCH AS HYDROCHLORIC ACID, SULFURIC ACID, PHOSPHORIC ACID, NITRIC ACID, SODIUM HYDROXIDE, HYDROFLUORIC ACID ETC, GENERAL SPECIFICATION - DIMENSION: DIAMETER 76-CM, LENGHT 1.2M, ABSORBING CAPACITY: 43 LITERS, PACKAGING: 12/BOX, COLOUR: YELLOW, MATERIAL: SHREDDED POLYPROPYLENE, OTHER FEATURES: ABSORB VARIOUS STRONG ACID/ALKALI SOLUTIONS, ABSORB VARIOUS LIQUID SOLVENTS, SUCH AS HYDROCHLORIC ACID, SULFURIC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
139	DGE101943	NOT KNOWN	792070518127 1 / BROOM SCRUBBING DECK (FOR DECONTAMIN ATION)	NIL	16 / EACH/N UMBER		NIL	LOCAL MARKET	NIL		ACID, PHOSPHORIC ACID, NITRIC ACID, SODIUM HYDROXIDE, HYDROFLUORIC ACID ETC, <u>TECHNICAL SPECIFICATION:-</u> REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21 <u>GENERAL SPECIFICATION -</u> REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) SIZE: Stock Length 12.5" inch, width 3.625 inch. Filling Bahia Bass. Stock wood Mango. Specification: DEFSTAN 79-6 Table I (A) UPDATED VIDE PN/CICP/01/3230989 DT 16 AUG 21	
140	DGB102448	sch-40 long radius	473070527416 0 / elbow dia 5 inch LONG RADIUS WITHOUT THREAD		6 / EACH/N UMBER	SCH-40					<u>TECHNICAL SPECIFICATION -</u> ELBOW BEND PIPE MILDSTEEL INNER DIA 5 INCH, OUTER DIA 5.25 INCH, THICKNESS 0.25 INCH (7 MM), MILD STEEL GRADE 40. Grade: ASTM 106 Grade B. Schedule 40 <u>GENERAL</u> <u>SPECIFICATION - ELBOW BEND</u> PIPE MILDSTEEL INNER DIA 5 INCH, OUTER DIA 5.25 INCH, THICKNESS 0.25 INCH (7 MM), MILD STEEL GRADE 40, Grade: ASTM 106 Grade B, Schedule 40	
141	DGH101282	GDHBMK4 092040	4010FT100791 8 / STEEL WIRE ROPE (20MM/40M/N ON- ROTATING/GA LVANIZED)	9M COMBINED BOAT CRANE	6.75 / EACH/N UMBER	GD.HBM. K.S-40/6- PG&40/9	N/A	GURDESAN GEMI MAK. SAN.TIC.A.S, DILOVASI ORGANIZE SAN.BOL 4 NCU KISIM, KOCAELI, TURKEY TEL # 9.02627E+11 FAX # 9.02627E+11 INFO@GURDESAN.COM. TR	GURDES AN GEMI MAK. SAN.TIC. A.S		<u>TECHNICAL SPECIFICATION - A.</u> Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<u>GENERAL SPECIFICATION - A.</u> Length : 40 Meter B. Thickness: Ø20mm C. No. of Wires: 1 D. Safe Working Load: 04 Tons E. Tensile Strength (Mpa): Not held in OEM technical manual F. Minimum Breaking Load: 220 KN G. DIA : 20mm H. Approx Weight (KG/100m): Not held in OEM technical manual	
142	DGE101526	828 653-H9020051	801079520819 8 / FABRIC 1300 GSM MILITARY GREY (HYPALONE)	RHIB BOAT	5 / METER		NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON, SOMERSET, BA9 9RX, TEL*01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHAW INFLATABLES LTD		<u>TECHNICAL SPECIFICATION - TDS</u> IS ENCLOSED WITH RWIMSGENERAL SPECIFICATION -TDS IS ENCLOSED WITH RWIMS	
143	DGE101372	828 653-H9020051	801079520819 8 / FABRIC 1300 GSM MILITARY GREY (HYPALONE)	RHIB BOAT	7 / METER		NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON, SOMERSET, BA9 9RX, TEL*01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHAW INFLATABLES LTD		<u>TECHNICAL SPECIFICATION - TDS</u> IS ENCLOSED WITH RWIMSGENERAL SPECIFICATION -TDS IS ENCLOSED WITH RWIMS	
144	DGE101567		561099200438 5 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	124 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCRETE UK LTD THE FLOORING TECHNOLOGIES CENTRE BOOTH LANE SANDBATCH CHESHIRE CW11 3QF UK PH:+44(0)1270 753000 & FAX :+44 (0)1270 753333		<u>TECHNICAL SPECIFICATION - IN</u> DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRAINING ME/251/544 DT 11 APRIL 2011.&(M) DC&FF.<u>GENERAL</u> SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRAINING ME/251/544 DT 11 APRIL 2011.&(M) DC&FF.	
145	DGB103456		028370000160		40 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u>	

Serial No	S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				8 / INGOT-BRASS		AMME						Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg <u>GENERAL SPECIFICATION</u> - Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg	
146	DGE101 545	NIL	0559794444901 / SLEEVING GLASS INSULATION CERAMIC VARNISHED GLASS FIBRE 6MM	GENERAL ELECTRIC USE	5 / METER							<u>TECHNICAL SPECIFICATION</u> - BS 2848 (5970994444901) <u>GENERAL SPECIFICATION</u> - BS 2848 (5970994444901)	
147	DGE101 977	NO DATA AVAILABLE	0559790200485 / INSULATION-TAPE-POLYETHYLENE TERAPHALATE (TERYLENE) W/O.75		10 / ROLL							<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
148	DGE101 979	NO DATA AVAILABLE	0559790020552 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	28 / ROLL							<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
149	DGE101 974	0.75X0.007INCH-50MTR	0559790015244 / INSULATION-TAPE-VARNISHED WOVEN GLASS-FIBRE (STRAIGHT CUT)		15 / ROLL							<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
150	DGB103346		0283595711440 / ROD NAVAL BRASS, RD DIA 0.25 inch, WT PER, FT 18LBS		1.5 / METER						TECHNICAL SPECIFICATION - specifications BSEN 12163 of 2011 material grade: CW712 MATERIAL CONDITION: M RUNNING LENGTH (MIN): 02 METER GENERAL SPECIFICATION - specifications BSEN 12163 of 2011 material grade: CW712 MATERIAL CONDITION: M RUNNING LENGTH (MIN): 02 METER	
151	DGB74640		0273709104476 / DIVIDERS SPRING LG OF LEG 06IN		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
152	DGH101847		0281502811680 / DIVIDER		138 / EACH/NUMBER						TECHNICAL SPECIFICATION - see attached file GENERAL SPECIFICATION - see attached file	
153	DGB101261	MATERIAL GRADE EN 4140	0214599416388 / BOLT MACHINE STEEL UNC HEX HD 0.75 X12X2 INCH TPI 10 (LOCAL)		116 / EACH/NUMBER						TECHNICAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED GENERAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
154	DGH99185		0281502811670 / BACK PLATE		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material : Metal Sheet Length : 10 Feet Width : 5.2 Feet Mounting Type : Back Mount Color : Gray Features : Quick in installation, Helpful in partitioning of storage pace, Robust & Durable, High grade Oil Paint. Construction GENERAL SPECIFICATION - Material : Metal Sheet Length : 10 Feet Width : 5.2 Feet Mounting Type : Back Mount Color : Gray Features : Quick in installation, Helpful in partitioning of storage pace, Robust & Durable, High grade Oil Paint Construction.	
155	DGB102007	NO DATA AVAILABLE	0243780001087 / CEASING WIRE 1MM 2185MB	S/M	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	UPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
156	DGE102823	NO DATA AVAILABLE	033054600448 4 / HEAVING LINE 06MM L50MM 466MS	MSI	60 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
157	DGE101761	NO DATA AVAILABLE	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25 INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN. SPECS	Dimension
											POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC. 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
158	DGE101 536	NO DATA AVAILABL E	424050508870 5/ CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	1/ EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC:	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN. SPECS	Dimension
											1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
159	DGE97109	NO DATA AVAILABLE	4220795055193 / WHISTLE PLASTIC FOR GENERAL SERVICE LIFE JACKET	LIFE JACKET MK-1, ORALLY INFLATED	45 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
160	DGB102081	NO DATA AVAILABLE	5120999105962 / SPANNER OPEN JAW ADJ 04 4 IN AF .05 INCH	TOOLS FOR ELECT EQUIPMENT NASR	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
161	DGE101823		8340705087915 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											STEEL), OUTER DIA 50 MM $\pm$ 02 MM & THICKNESS 02 MM $\pm$ 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM $\pm$ 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 23 X 15 FEET. ($\pm$ 3 INCH) b. HEIGHT OF TENT: 12 FEET ($\pm$ 2 INCH) c. HEIGHT OF WALL: 06 FEET ($\pm$ 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM. b. IRON PEGS: QTY 40 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS, WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
162	DGE95577	NO DATA AVAILABLE	834050503926 2 / QANAT COMPLETE SIZE 18.X 7. OUT SIDE		10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GREEN PRINTED CLOTH, 100% COTTON.								NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report: Sail and color shop PN Dockyard. ITEM SPECIFICATION: ROPE/CORD MADE OF COTTON, BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH) 100% COTTON NIWAR, BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED. GENERAL SPECIFICATION - Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report: Sail and color shop PN Dockyard. ITEM SPECIFICATION: ROPE/CORD MADE OF COTTON, BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH) 100% COTTON NIWAR, BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
163	DGE101 370	0413-8522	041399923891 3 / RUBBER SHEET SOLID		30 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
164	DGE101 068	BS 419/156	055954600536 2 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0		55 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO.	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MTR									
165	DGE101525	NO DATA AVAILABLE	055978000018 1 / SLEEVE PLASTIC RED 0.5X10 59P (NSD/TD/19/334 DT:15.05.93)		35 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
166	DGE101971	NO DATA AVAILABLE	055978000018 3 / SLEEVE PLASTIC GREEN 0.3X3 55P (DELETED NS/TD/32/611D T280989)		5 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
167	DGT102116	NO DATA AVAILABLE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		10 / CUBIC FOOT	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
168	DGE101441	NIL	351070518127 8 / TRAY BLEECH	NIL	1 / EACH/NUMBER	NIL		LOCAL MARKET	NOT KNOWN		TECHNICAL SPECIFICATION - GENERAL ITEM GENERAL SPECIFICATION - GENERAL ITEM	