

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 04-08-2026

- 1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)**
- 2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.**
- 3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.**
- 4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.**

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DSB104657	TAG-700 AIR ANGLE GRINDER/ NKS – NK2261G1	009908607296 7 / PNEUMATIC ANGLE GRINDER KL/12 OR 700NA		3 / EACH/N UMBER	tag-700 qjl/NK226 1G1					<u>TECHNICAL SPECIFICATION -</u> Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2" <u>GENERAL SPECIFICATION -</u> Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2"	
2	DSB104658	246343	254078517235 8 / PORTABLE BLOWER VENTILATOR 12 INCH		2 / EACH/N UMBER	pvf-12 / PVT-30					<u>TECHNICAL SPECIFICATION -</u> Structure : Aluminum Alloy Shell - Good heat dispersion and low weight Number of Blades: 7 blades Blade: Aluminum Alloy Drive Type: Motor Drive Bearing: Adopts High Quality bearing and durable using Motor: High Efficient and special made motor ducting Size: 300 mm material: steel Power (w): 380 watts: 305w rmp low: 2308 Cm3 rpm High: 2800-2900 rmp Voltage: 220v-240v phase: single phase Air Volume (m³/Hour): 3400 Pressure (Pa): 350 Noise dB (A): 80 decibels: 71 db fan diameter: portable blower ventilator 12 inch Safety Guard: Both front side and rear side is installed MAKE: Deton CHINA Brand Equipement: msm china <u>GENERAL SPECIFICATION -</u> Structure : Aluminum Alloy Shell - Good heat dispersion and low weight	

3. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Number of Blades: 7 blades Blade: Aluminum Alloy Drive Type: Motor Drive Bearing: Adopts High Quality bearing and durable using Motor: High Efficient and special made motor ducting Size: 300 mm material: steel Power (w): 380 watts: 305w rmp low: 2308 Cm3 rpm High: 2800-2900 rmp Voltage: 220v-240v phase: single phase Air Volume (m³/Hour): 3400 Pressure (Pa): 350 Noise dB (A): 80 decibels: 71 db fan diameter: portable blower ventilator 12 inch Safety Guard: Both front side and rear side is installed MAKE: Deton CHINA Brand Equipement: msm china	
3	DSB105361	CM7PS-D1-SEW	5935703399197 / 7PIN MALE DEUTSCH		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
4	DSB102357	CT105-3	6685144860574 / PRESSURE SENSOR		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
5	DSB102456	DRAWING NO.105-05-006-13-000 AND PART NO. 105-05-006-23-000	5340725343833 / CONICAL MOUNT T-90		16 / EACH/NUMBER	T-90					TECHNICAL SPECIFICATION - ENGINE MOUNTING GENERAL SPECIFICATION - ENGINE MOUNTING	
6	DSB104661	ORB-MO-003/90/V1/19/boxmo-003	5340505242048 / main box		1 / EACH/NUMBER	fatek					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
7	DGB101340	HME-AB-ADP-VLV-FERROL20-004	4730705351238 / ADAPTER 1/2"		30 / EACH/NUMBER	SS304 SURFACE					TECHNICAL SPECIFICATION - ADAPTER thread type size 1/2 inch 1ST SIDE VALVE THREAD AND SECOND SIDE DIA 20MM FERROL TYPE material stain less steel 316- GENERAL SPECIFICATION - ADAPTER thread type size 1/2 inch 1ST SIDE VALVE THREAD AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SECOND SIDE DIA 20MM FERROL TYPE material stain less steel 316-l	
8	DSB105509	pstn-11647316-vtx	4820705344317 / ball valve ported		5 / EACH/NUMBER	PSTN-11647316-VTX					<u>TECHNICAL SPECIFICATION - i</u> Length = 116mm & Dia = 47 mm i Material Stainless Steel grade 316 <u>GENERAL SPECIFICATION - j</u> Length = 116mm & Dia = 47 mm j Material Stainless Steel grade 316	
9	DSB105360	LW-PM-14-3KVTX/LW-PM-14-VTX (LOCAL)	5310705251577 / lock washer dn14 (LOCAL)		1460 / EACH/NUMBER	n/a					<u>TECHNICAL SPECIFICATION - a.</u> Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm <u>GENERAL SPECIFICATION - a.</u> Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm	
10	DSB103375	RT Seal/460/GIBSUN	5330545284632 / Regulating Tank Seal		6 / EACH/NUMBER	RT Seal/460/GIBSUN					<u>TECHNICAL SPECIFICATION - Seal</u> is composed of Polyc hhooprene material having Internarional Rubber Hardness Degree (iRHO) 65±5 as per Iso 481 NF T 46-o03. Dimen&on of the seal ls to be as per attached drawing. Pressure testing at 100 bars for 24 hours. a. Material : Neoprene Rubber. b. Shore Hardness : 73± shore A. c. Outer Diameter (Do) = : 460 mm. e. Inner Diameter (Di) = : 432mm. f. hTickndss : 14 mm. g. Height : 13mm. h. One Side Radius 12mm. j. Taper Degree (Both Sides): 10°. <u>GENERAL SPECIFICATION -</u> Seal is composed of Polyc hhooprene material having Internarional Rubber Hardness Degree (iRHO) 65±5 as per Iso 481 NF T 46-o03. Dimen&on of the seal ls to be as per attached drawing. Pressure testing at 100 bars for 24 hours. a. Material : Neoprene Rubber. b. Shore Hardness : 73± shore A. c. Outer Diameter (Do) = : 460 mm. e. Inner Diameter (Di) = : 432mm. f. hTickndss : 14 mm. g. Height : 13mm. h. One Side Radius 12mm. j. Taper Degree (Both Sides):	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											10°.	
11	DSB105354	99000/ HIL903-8501	662574521131 6 / FILTER CAPSULE		2 / EACH/N UMBER	MODEL IR-600					<u>TECHNICAL SPECIFICATION -</u> Make: a. Guardian NG U.K (Patt No. 99000) Parent equipment: b. CO2 Meter on board S/Ms HITOX Part No: HIL903-8501 OEM Pat No: 99000 FILTER CAPSULE 1.0 UM for CO2 Monitor HITOX-IR600. oem: uk Brand HITOX Equivalent Not Known <u>GENERAL SPECIFICATION - Make:</u> a. Guardian NG U.K (Patt No. 99000) Parent equipment: b. CO2 Meter on board S/Ms HITOX Part No: HIL903-8501 OEM Pat No: 99000 FILTER CAPSULE 1.0 UM for CO2 Monitor HITOX-IR600. oem: uk Brand HITOX Equivalent Not Known	
12	DSB104656	5330JA-BAGUERU CHDE17, 15 / (LOCAL) TR130RH- SEW/ (LOCAL) TR280RA- SEW	533014356877 9 / WATER TIGHTNESS RING TEFLON, S/STEEL & O-RING		170 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG) <u>GENERAL SPECIFICATION -</u> SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG)	
13	DSB102218	31851	592514482063 9 / CIRCUIT BREAKER (115V 60HZ BREAKER)		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> 115 Volt 60Hz AC Network (BF system) breaker NSX250F TP 200Amps Adjustable 160 to 200Amps Photo attached. <u>GENERAL SPECIFICATION -</u> 115 Volt 60Hz AC Network (BF system) breaker NSX250F TP 200Amps Adjustable 160 to 200Amps Photo attached.	
14	DSB104659	K20000L/ FG-3H-5F 1/4 N /K20000L	513014368011 9 / GRINDER PNEUMATIC HORIZONTAL (MEULEUSE PNEUMATIQUE)		2 / EACH/N UMBER	FG-3H-5, -5F					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
15	DNH105926	OWR-528 / NWD200/ic	731070517713 1 / HOT AND	WATER DISPENSER	6 / EACH/N	OWR-528/icon-2	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS/BROCHER OR	<u>TECHNICAL SPECIFICATION -</u> white colour only NASGAS WATER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		on-2 (ORIENT)	COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)		UMBER	(orient)				PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	DISPENSER <u>GENERAL SPECIFICATION</u> - white colour only NASGAS WATER DISPENSER	
16	DNH105073	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	2 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION</u> : white colour only NASGAS WATER DISPENSER <u>GENERAL SPECIFICATION</u> - white colour only NASGAS WATER DISPENSER	
17	DNH105532	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION</u> - white colour only NASGAS WATER DISPENSER <u>GENERAL SPECIFICATION</u> - white colour only NASGAS WATER DISPENSER	
18	DPC105712	1141674/ 22567233/ 22567259 (20 ltr)	615073514142 4 / COOLANT READY MIX (volvopenta)	VOLVOPANTA ENGINE	737 / LITER	NO DATA AVAILABLE		00	M/S AB VOLVOPANTA 40508 GOTEBO RG SWEEDN	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION</u> - PACKING: 05 LITER CAN /20 Liter can <u>GENERAL SPECIFICATION</u> - PACKING: 05 LITER CAN /20 Liter can	
19	DPC105449	Comp A= EPA001, Comp B = EPA740	801099740433 3 / PAINT INTERGARD 400 DARK GREY (Comp A = 17 Ltrs + Comp B = 03 Ltrs)	HULL PRESERVATION OF F-22P FRIGATES	820 / LITER	NO DATA AVAILABLE		UK	INTERNATIONAL PAINTSLTD.P.O. BOX: 20980, ORIEL HOUSE 16 CANNAUGHT PLACE,	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION</u> - SOURCE OF AVAILABILITY:M/S SEA TRADE COMPANY, KARACHIGENERAL <u>SPECIFICATION</u> - SOURCE OF AVAILABILITY:M/S SEA TRADE COMPANY,KARACHI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									LONDON, W22 2ZB, UNITED KINGDOM.			
20	DPC104 482	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
21	DPC105 656	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
22	DNM105 677	10000-02549/248 5C546	414079517192 2 / FAN	60 KVA PERKINS	1 / EACH/NUMBER	DK 51280	4ZK05396	PERKINS UK	PERKIN UK	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - RADIATOR COOLING GENERAL SPECIFICATION - RADIATOR COOLING	
23	DPC105 760	Comp A = PHB000 / Comp B = PHA 046	801079522137 7 / INTERTHANE	INSIDE HANGAR PHB000 UK	710 / LITER	PHB000		International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD, UK. Ph:01914696111	International Paints Pvt Ltd, UK	TDS/BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - TECHNICAL DETAILS INCLUDED IN DATA SHEET SHELF LIFE ;	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			990 (WHITE)							BE ENCLOSED WITH QUOTATION	COMP A 02 YEAR/COMP B-01 YEAR <u>GENERAL SPECIFICATION - TECHNICAL DETAILS INCLUDED IN DATA SHEET SHELF LIFE ;</u> COMP A 02 YEAR/COMP B-01 YEAR	
24	DNM104344	70MM2 4CORE	615070521857 6 / POWER CABLE 70MM2 4CORE	Power Cable 70mm2 4core	200 / FOOT	NA	NA	Head Office Arif Habib Centre, 1st Floor, 23 M.T. Khan Road, Karachi UAN : 111-CABLES (222-537) EMAIL : info@pakistancables.com sales@pakistancables.com export@pakistancables.com	PAKISTAN CABLES		<u>TECHNICAL SPECIFICATION -</u> No of core: 04 CSA of Conductor: 70MM2 Conductor Material: Copper Class 2 Standard: Standard as per IEC 60228 Shape & diameter of Conductor: Sectored-90 No of Strands: 19 Insulation Material: XLPE Thickness of Insulation: 1.1mm Steel Wire Armour Diameter (SWA): 2.5 mm Thickness of outer Sheath: 2.2 mm Diameter of Cable: 42.59mm Testing Voltage: 3.5KV <u>GENERAL SPECIFICATION -</u> No of core: 04 CSA of Conductor: 70MM2 Conductor Material: Copper Class 2 Standard: Standard as per IEC 60228 Shape & diameter of Conductor: Sectored-90 No of Strands: 19 Insulation Material: XLPE Thickness of Insulation: 1.1mm Steel Wire Armour Diameter (SWA): 2.5 mm Thickness of outer Sheath: 2.2 mm Diameter of Cable: 42.59mm Testing Voltage: 3.5KVA	
25	DPC103470	CC 2748M (5 liters packing) CC2750M (20 liters packing)	681071522985 7 / ES Complete EG premix coolant	MAIN ENGINE	1675 / LITER		22376716	CUMMINS FILTERATION FLEETGUARD DISTRIBUTORS	CUMMINS / FLEETGUARD	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol <u>GENERAL SPECIFICATION -</u> Fleetguard CC2825ES Compleat Ectended life antifreeze/ coolant. Ethylene glycol	
26	DPK101569	99000-22B55	915076522310 6 / ECSTAR OUT BOARD MOTOR GEAR OIL SUZUKI SAE-90 GL-5	SUZUKI OBM ENGINE	150 / MILLILITER	NIL		SHOWA SHELL SEQIYU K K. 3-2 DAIBA-2-CHOME, MINATO-KU, TOKYO, 135-8074, JAPAN	OBM SUZUKI	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED	<u>TECHNICAL SPECIFICATION -</u> ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION.	AUTOMOTIVE GEAR OIL <u>GENERAL SPECIFICATION -</u> ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE AUTOMOTIVE GEAR OIL	
27	DPK105812	OMALA 68	9150270001857 / SHELL OMALA OIL S2 GX 68 (PACKING 209 LTR DRUM)	MTP 750DD HUB OIL	1060 / LITER	NO DATA AVAILABLE		OC	TURKEY	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
28	SNM102997	CWCU-230-25	4130705214374 / ALUMINUM WASHABLE FILTER WITH FRAME (12	HVAC CWAHU-230	12 / EACH/NUMBER	CP-ALF-1	NIL	GUARD FILTERS PAKISTAN www.quadfilter.com.pk	GUARD FILTERS PAKISTAN www.quadfilter.com	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> ALUMINUM WASHABLE FILTER WITH FRAME (SIZE 12"X24" X1 <u>GENERAL SPECIFICATION -</u> ALUMINUM WASHABLE FILTER WITH FRAME (SIZE 12"X24"X1	
29	SNM102997	CWCU-230-25	4130705214374 / ALUMINUM WASHABLE FILTER WITH FRAME (12	HVAC CWAHU-230	12 / EACH/NUMBER	CP-ALF-1	NIL	GUARD FILTERS PAKISTAN www.quadfilter.com.pk	GUARD FILTERS PAKISTAN www.quadfilter.com	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> ALUMINUM WASHABLE FILTER WITH FRAME (SIZE 12"X24" X1 <u>GENERAL SPECIFICATION -</u> ALUMINUM WASHABLE FILTER WITH FRAME (SIZE 12"X24"X1	
30	DPC105448	LAZ684-Light Grey	8010795145259 / PAINT INTERSHEEN 579 LIGHT GREY (Packing = 20Ltrs)	HULL PRESERVATION OF F-22P FRIGATES	1080 / LITER	NO DATA AVAILABLE		UK	M/S INTERNATIONAL PAINT LTD P O BOX 20980 ORIAL HOUSE 16 CONNAU	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> WAR PAINT ISSUE 37 <u>GENERAL SPECIFICATION -</u> WAR PAINT ISSUE 37	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									GHT PLACE LONDON W2 2ZB UK			
31	DNH105 528	SPLIT TYPE A/C 01 TON MITSUBISHI / LG/GREE	596273514247 4 / SPLIT TYPE A/C 01 TON MITSUBISHI / LG/GREE 12000 BTU (INVERTIBLE/ REVERSIBLE)	SPLIT TYPE A/C 01 TON	2 / EACH/NUMBER	12PITH		00		TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
32	DPC105 729	NA	650870523178 5 / HAND SANITIZER	SELF	130 / LITER	NIL	NIL	PAKISTAN	PAKISTAN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - HAND SANITIZER GENERAL SPECIFICATION - HAND SANITIZER	
33	DPC105 673		047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	2334 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
34	DPC105 235		047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	72 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
35	DPC105 674		047450220173 8 / SOAP TOILET IN LIQUID FORM	SKF COUPLING	795 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY							ENCLOSED WITH QUOTATION		
36	DPC105 634	0461-3951, CS2879	046159224056 2 / WATER INDICATING PASTE FOR FUEL (03 OZ TUBE)		77 / TUBE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DPC105 645	SPEC. BS 3981	047350942925 1 / PIGMENT POWDER (DRY INGREDIENTS FOR PAINTS) RAW SIENNA POWDER (Packing 56 LB or 400 Gram) TIGER BRAND		2.5 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DPC105 706	G-1200	047550220561 3 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		52 / TUBE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
39	DPC105 219		044250442005 1 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd.	FINISHING INTERIOR	20 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTION PRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101 OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing							N	28 swg <u>GENERAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
40	DPC105 233		044250943448 3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	70 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996 <u>GENERAL SPECIFICATION</u> - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996	
41	DPC105 627		044279942354 2 / Paint Marking, Stenciling (Signal Red) flash point: 32 degree C (Min) method of application: brushing & stenciling type: Alkyed Packing: 04 liter tin gauge of tin 26 to 28 SWG		431 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - 1. DEFSTAN 80-68/4 2. NS/P/012 OF 2013 (REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996 <u>GENERAL SPECIFICATION</u> - 1. DEFSTAN 80-68/4 2. NS/P/012 OF 2013 (REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996	
42	DPC104 410		044250942937 4 / VARNISH	USE ONWOOD UNDER	52 / LITER					TDS/BROCHER OR	<u>TECHNICAL SPECIFICATION</u> - G/P-307/248 EXCEPT FLASH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	CONDITIONS OF MARINE EX						PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED <u>GENERAL SPECIFICATION - G/P-307/248</u> EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED	
43	DPC105 480	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		13685 / BOTTLE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u> <u>GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u>	
44	DPC105 608		0442509423543 / PAINT MARKING (WHITE)		641.5 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - a. Colour White b. Viscosity 100-200 cps (centipoise) c. Density 1.2-1.5 g/cm3 d. Fast Drying 15-30 minutes e. Thickness 50-100 microns (dry film) f. Adhesion Excellent on Metal, Wood, concrete g. Durability Resistant to weathering, UV and Chemicals h. Reflectivity High(85-90%)</u> <u>GENERAL SPECIFICATION - a. Colour White b. Viscosity 100-200 cps (centipoise) c. Density 1.2-1.5 g/cm3 d. Fast Drying 15-30 minutes e. Thickness 50-100 microns (dry film) f. Adhesion Excellent on Metal, Wood, concrete g. Durability Resistant to weathering, UV and Chemicals h. Reflectivity High(85-90%)</u>	
45	DNQ105 576	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		6 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.</u> <u>GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
46	DPC105688		0474502242463 / SOAP SCRUBBING		1392 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose.	
47	DNM104368	1055379	2910725091477 / FILTER (FOR SCHOTTEL HYDROLIC SYSTEM AGGREGATE UNIT)	SCHOTTEL SRP550FP AGGREGATE UNIT (GERMANY)	2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DNQ105579	PURIFIED LOCALLY DEVELOPED	4220795055188 / EMERGENCY PURIFIED DRINKING WATER CONTENT 500 ML (LIFE RAFT).	S/PACK USED IN 20MEN LIFE RAFT	246 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DNQ103511	LOCAL	4210705007917 / NOZZLE FOR HOSE CANVAS		2 / EACH/NUMBER	SL-13BP SHILA FIRE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Series: W2500 Model: Pwr 1 & 1p OEM/Brand: pwr control: manual output: 130-23- liter per minute at 6 bar pressure material: polyamide & light aluminium alloy GENERAL SPECIFICATION - Series: W2500 Model: Pwr 1 & 1p OEM/Brand: pwr control: manual output: 130-23- liter per minute at 6 bar pressure material: polyamide & light aluminium alloy	
50	DNM105578	EBH16 / TV16/tve-24	4130US5065504 / COOLING UNIT	MAIN A/C CRISAIR USA TYP.F48E-P.	2 / EACH/NUMBER	921047473				TDS/BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - Brand: Breeze Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22 GENERAL SPECIFICATION - Brand: Breeze	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										BE ENCLOSED WITH QUOTATION	Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22	
51	DNH105 577	UES-20 (SEE F8)	3510705099157 / INDUSTRIAL LAUNDRY WASHING MACHINE (CAPACITY 45LBS 20KG)		1 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
52	DNH105 915	EAC-70/WP-1302/ECM 6500	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	2 / EACH/NUMBER	EAC-70/WP-1302/ECM 6500				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE</u> <u>GENERAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE</u>	
53	DNH105 522	EAC-70/WP-1302/ECM 6500	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	5 / EACH/NUMBER	EAC-70/WP-1302/ECM 6500				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE</u> <u>GENERAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE</u>	
54	DNH105 715		4110705058486 / DEEP FREEZER 30 CUFT 220V 50HZ SINGLE	USER MRO LAHORE	2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
55	DNQ105 916	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	12 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION.		
56	DNM105918	70HFR20	596175506777 7 / METAL STUD DIODE 70HFR20 METAL DO-5 PACKAGE	DORMAN D/G 500KVA (UK)	3 / EACH/N UMBER	70HFR20				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE <u>GENERAL SPECIFICATION -</u> DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE	
57	DPC105640	NO DATA AVAILABLE	047350000011 1 / PASTE OIL RED OXIDE		50 / KILOGRAMME	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
58	DPC104054	R-5002	801070511103 7 / PIGMENT (BRILIANT WHITE)	GRP WORK, M/S ZAIN SONS. KARCHI.PH; 7731541	10 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
59	DPC105515	R-502	683070511056 9 / GAS REFRIGRENT R-502 (packing = 13.6kg)	COLD STORAGE & BLASTFREEZER	27 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
60	DNH105911	NO DATA AVAILABLE	130850053012 6 / DEEP FREEZER 12 CUFT 220 V AC WAVES		1 / EACH/N UMBER	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION.		
61	DSB96444	8.PWR. 57600	5998785239505 / NT-20KJ Power board BK-576		3 / EACH/NUMBER	BK-NT37K-J					<u>TECHNICAL SPECIFICATION -</u> Input: 320VDC Output: 115VAC <u>GENERAL SPECIFICATION -</u> Input: 320VDC Output: 115VAC	
62	DNQ104128	RADTARGE-H	6665785274041 / HIGH SENSITIVE PERSONAL DOSIMETER		6 / EACH/NUMBER	RADTARGE-H				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig <u>GENERAL SPECIFICATION -</u> electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig	
63	DNQ105519	RADTARGE-H	6665785274041 / HIGH SENSITIVE PERSONAL DOSIMETER		4 / EACH/NUMBER	RADTARGE-H				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig <u>GENERAL SPECIFICATION -</u> electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig	
64	DPC105731	QGF684/A (Part A + Part B)	8010785284945 / Interthane 870 Surf Gray (20 Ltrs Packing)		560 / LITER	N/A				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
65	DPC105649	407A	6830795293018 / REFRIGERANT GAS 407A (in non returnable cylinder of 40 kg net)		90 / KILOGRAMME	407A				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
66	DPK105829	s4 p 100	9150705270734 / compressor oil shell corena s4 p 100		10 / LITER	s4 p 100				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	TECHNICAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES GENERAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES	
67	DPC105 730	A020EEV2	801070533282 5 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		20 / LITER	HIGHLY PERFUMED				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION - PRODUCT INFORMATION:</u> APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation. <u>GENERAL SPECIFICATION -</u> PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.	
68	SRP105717	FC-577 (SOFT 99)	6850ZO6511199 / VINYL CLEANER FOAM SPRAY, 400ML		100 / BOTTLE	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> ABRO.CLEAN ALL FOAM CLEANERS FOR UPHOLSTERY. VINYL.CARPETS PART NO FC-577 (WWW.ABRO.COM).OEM: ABRO INDUSTRIES INC.PO BOX 1174.IN 46624 USA MAKE NET WT: 400ML/22 OZ/623 GMS <u>GENERAL SPECIFICATION -</u> ABRO.CLEAN ALL FOAM CLEANERS FOR UPHOLSTERY.VINYL.CARPETS PART NO FC-577 (WWW.ABRO.COM).OEM: ABRO INDUSTRIES INC.PO BOX 1174.IN 46624 USA MAKE NET WT:400ML/22 OZ/623 GMS	
69	DPC102884	H-300 HUX	8040735140710 / HARDNER (SET OF	AC COMPRESSOR KALMAT	14 / SET	NO DATA AVAILABLE		00		TDS\BROCHER OR PIC OF	<u>TECHNICAL SPECIFICATION - A.V</u> 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			2X1KG BOTTLE)	GWADER						ITEM MUST BE ENCLOSED WITH QUOTATION	Brown , Flash point, 200f>GENERAL SPECIFICATION - A.V 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown , Flash point, 200f>	
70	DPK97238	SHELL OMELA VISCOSITY-68	2590735165521 / HUB OIL	MJP	10 / LITER	MJP 750 SERIES		MJP OSTERBY GJUTERI AB SERVICE @ 'MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	MJP OSTERBY	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDENGENERAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	
71	DPC99751		0442504420064 / PAINT WEATHER WORK (LIGHT GREY)NHQ LTR NS/G/1303/C DT 270199	WEATHER WORK	972 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
72	DPC100028	M101021	9135PK5085413 / ALCOHOL FOR CLEANING	C-3 SYSTEM	5 / CAN					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DPC102539	NO DATA AVAILABLE	6840705057111 / INSECTICIDE K-OTHRINE ec 15 (01 LITER PACKING) (OEM M/S Bayer	TO CONTROL INSECT PASTS COCKROACHES BUGS	20 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label. GENERAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Environmental Sciences)								Packing: 01x Ltr sealed plastic packing with registered label.	
74	DPC100030	NO DATA AVAILABLE	6850785031104 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMENT FOR PNS NASR	6 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. GENERAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
75	DPC103549	LUSTRE EXPORT	0473504730132 / Electro polishing chemical LUSTRE EXPORT (OEM VANA Corporation Pakistan) (Packing = 650 Grams)		5 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	