

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 05-08-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGT105780	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
2	DGT105781	NO DATA AVAILABLE	0100500000043 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		20 / CUBIC FOOT	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% ($\pm 10\%$) <u>GENERAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% ($\pm 10\%$)	
3	DGE105691	SFF6 1	2590735175928 / POLYESTER BOAT LIFTING BELT 20000 KG LOAD	ENGINE	4 / EACH/NUMBER	NK	32568955	YONCA TURKEY LTD	YONCA		<u>TECHNICAL SPECIFICATION -</u> LENGTH 20 METER WLL 20000 KG BATCH NO YHTS-07-0105 TEMP -40 DEG C + 100 DEG C <u>GENERAL SPECIFICATION -</u> LENGTH 20 METER WLL 20000 KG BATCH NO YHTS-07-0105 TEMP -40 DEG C + 100 DEG C	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
4	DGT105701	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	60 / FOOT	NO DATA AVAILAB LE		PK	TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment : required <u>GENERAL SPECIFICATION</u> - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment :required	
5	DGB105900		0277799238164 / TOOL BOX PORTABLE		4 / EACH/N UMBER						TECHNICAL SPECIFICATION - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm <u>GENERAL SPECIFICATION</u> - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm	
6	DGB105664		0277799238164 / TOOL BOX PORTABLE		6 / EACH/N UMBER						TECHNICAL SPECIFICATION - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm <u>GENERAL SPECIFICATION</u> - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm	
7	DGE105693	DP3574	4220995228166 / HEAD STRAP	SWIM MASK (DIVING SET)	10 / EACH/N UMBER	NO DATA AVAILAB LE		UK	MINISTR Y OF DEFENC E (NAVY) EXPERIM ENTAL DIVING UNIT HMS VERNON PORT SMOOTH		<u>TECHNICAL SPECIFICATION</u> -- <u>GENERAL SPECIFICATION</u> --	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									HANTS UK			
8	DGB105647	NO DATA AVAILABLE	026850000006 1 / SCALE- SPRING- BALANCE-20- STONE-280- LBS		1 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow <u>GENERAL SPECIFICATION -</u> Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow	
9	DGT105703	NO DATA AVAILABLE	010050000001 0 / PLY WOOD GD 1, 11 PLY (CORE AND INNER PLIES OF POPLAR AND BOTH FACE AND BACK VENEER OF) TYPE OF BOND INT, TREATED WITH PRESERVATE D.		640 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 8 FEET WIDTH=4 FEET TH=22 MM Specification 1. Moisture Content BS EN 322 : 1993 2. Bonding Quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993 <u>GENERAL SPECIFICATION -</u> SIZE: LENGTH= 8 FEET WIDTH=4 FEET TH=22 MM Specification 1. Moisture Content BS EN 322 : 1993 2. Bonding Quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993	
10	DGE105692	NO DATA AVAILABLE	009159129245 5 / MATTING FLOOR COIR WIDTH 36".		20 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - a.</u> Per role length: 50 mtr b. Width: 36" (03 feet) c. Weight per square meter: 1.650 Kgs (1650 grams) <u>GENERAL</u> <u>SPECIFICATION - a.</u> Per role length: 50 mtr b. Width: 36" (03 feet) c. Weight per square meter: 1.650 Kgs (1650 grams)	
11	DGT105782	NO DATA AVAILABLE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	96 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8- FEET, Width=4- FEET & THickness= 19MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
12	DGT105705	NO DATA AVAILABLE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	880 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & Thickness= 19MM(±2MM) 4. <u>ACCEPTANCE CRITERIA:</u> Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
13	DGB105 981	Material Grade EN 4140	0214780001043 / NUT 1M80-405 213/MB SZ 8.00 MM, Bore 8mm, Dia 14 mm	BOOSTER ENGINE L12V-180	50 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - MATERIAL GRADE EN-4140 SZ 8.00 MM, BORE 8MM, DIA 14MM. <u>GENERAL SPECIFICATION - MATERIAL GRADE EN-4140 SZ 8.00 MM, BORE 8MM, DIA 14MM.</u></u>	
14	DGB105 985	NO DATA AVAILABLE	3439715045034 /		1000 / PACK						<u>TECHNICAL SPECIFICATION - a. Detailed Specifications : UW-CS-2</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	ELECTRODE SEA WELD 5/32X14 IN		T						Electrode Welding 5/32 Inches (4.0 mm) b. Technical data : AWS E70XX c. Polarity : DC Electrode Negative (DCEN) d. Position : Flat, Horizontal, Vertical, Overhead e. Type of Arc : Medium, Moderate, Penetration f. Material : Low Carbon Steels g. Technique : Use short Arc length with electrode angle 30 o + 15 o , to the line of weld. 2. Acceptance criteria : Item will be accepted upon technical rep inspection. <u>GENERAL SPECIFICATION</u> - a. Detailed Specifications : UW-CS-2 Electrode Welding 5/32 Inches (4.0 mm) b. Technical data : AWS E70XX c. Polarity : DC Electrode Negative (DCEN) d. Position : Flat, Horizontal, Vertical, Overhead e. Type of Arc : Medium, Moderate, Penetration f. Material : Low Carbon Steels g. Technique : Use short Arc length with electrode angle 30 o + 15 o , to the line of weld. 2. Acceptance criteria : Item will be accepted upon technical rep inspection.	
15	DGB105 710	66694	451099761024 5 / MIXER SHOWER UNIT 1/2" DUPLEX MIX FITTING TOP OUTLEY FOR 15MM	INLETS CHROME PLATED(COLD &WARM WATER)	15 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
16	DGB106 000	Material Grade EN 4140	025770941150 6 / NUT-PLAIN- HEXAGON- THREAD-SIZE. 625LH.550"		32 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - material specs AISI 4140(PD 970: 2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED <u>GENERAL SPECIFICATION</u> - material specs AISI 4140(PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
17	DGB105 702	1473	024879129614 8 / SAFE-STL	BODY 16 GAUGE, DOOR	1 / EACH/N						<u>TECHNICAL SPECIFICATION</u> -A. BODY: 16 GAUGE B. DOOR: NOT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	NOT LESS THAN 3/8" THK-	UMBER						LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03 <u>GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03</u>	
18	DGB105 670		025850258120 3 / COPPER-WIRE-2-MM-DIA		10 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm ² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm ² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER <u>GENERAL SPECIFICATION -</u> Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm ² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm ² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER	
19	DGB105 661	BS 1083	025770419500 8 / NUT-PLAIN-HEXAGON-THREAD-SIZE 0.750	BRASS TYPE	12 / DOZEN						<u>TECHNICAL SPECIFICATION -</u> material grade i.e SS347 bs 970, 60r7a <u>GENERAL SPECIFICATION -</u> material grade i.e SS347 bs 970, 60r7a	
20	DGE105 689		041559923141 2 / SHEET		50 / SHEET						<u>TECHNICAL SPECIFICATION -</u> Manfr/Tech.Sponcer Code reference:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PLASTIC METHYL METHACRYLATE PLAIN TRANSPARENT L X W X THIC 48"X48"X0.250"								DTD 5592GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference:DTD 5592	
21	DGE105694		0461592203678 / PAPER, ABRASIVE 9" X11" (OROCUS) MATERIAL EMERY GRADE 4/0		1001 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DGE105690	0413-8522	0413599238913 / RUBBER SHEET SOLID NATURAL (48 inch X 72 inch x 1/4 inch)	CONT OIL TANKS	80 / KILOGRAMME						TECHNICAL SPECIFICATION - ITEM SPECIFICATION: STANDARD BS 1154.GENERAL SPECIFICATION - ITEM SPECIFICATION: STANDARD BS 1154.	
23	DGB106002		0276700003634 / SEAL LEAD FOR SEALING COVER JOINT		19 / GROSS						TECHNICAL SPECIFICATION - diameter: 9mm thickness:4mm material: leadGENERAL SPECIFICATION - diameter: 9mm thickness:4mm material: lead	
24	DGB105991		0276709105937 / SHOVEL HAND ROUND MOUTH DIMENSIONS 10-1/2X12-1/2" LG OF H28"		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg. GENERAL SPECIFICATION - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg.	
25	DGE101349	NO DATA AVAILABLE	0413500000133 / EAR DEFENDER		120 / PAIR	PELTOR H10A/ OPTIME 105					TECHNICAL SPECIFICATION - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip) <u>GENERAL SPECIFICATION</u> - accaptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip)	
26	DGD94576		003554600066 5 / TAWA IRON (DLT VIDE LTR ST-V/1732 DT. 06-12-92		4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
27	DGE106062		035059923713 2 / ROPE NYLON, 3- STRD, CIR: 4.50", DIA 1.4375" (36- mm)		440 / METER						<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2019. <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
28	DGH105 968	070125648 4	028150281167 5 / GAS CUTTING TORCH(CUTTING) CAPACITY 250MM		1 / EACH/NUMBER	NM250 CUTTER					<u>TECHNICAL SPECIFICATION</u> - made: MUREX SAFFIRE <u>UKGENERAL SPECIFICATION</u> - made: MUREX SAFFIRE UK	
29	DGH105 921		023159571524 3 / WIRE ROPE STEEL EXTRA SPECIAL GALVA LAY OF ROPE RH CIRC 3/8"		100 / METER						<u>TECHNICAL SPECIFICATION</u> - Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39) <u>GENERAL SPECIFICATION</u> - Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39)	
30	DGH105 925	NO DATA AVAILABE	021159525927 7 / PLATE STEEL	EXPOSED DECKS	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - BSEN 10025 OF 2004, S 275JR <u>GENERAL SPECIFICATION</u> - BSEN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CARBON 2500X1250X04 MM W.P.SQ MTR 31.40KG								10025 OF 2004, S 275JR	
31	DGE106 061	ISO-1181 2004, BS- 2087	035059571323 2 / ROPE SISAL 3 STRAND CIRC 1.25 DIA 13/32 (0.40625) ROT PROOFED	GENERAL USE	600 / FATHO M						TECHNICAL SPECIFICATION - ISO-1181 2004, BS-2087, STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABEL & MARKING AS PER ISO 2307 & 9554 GENERAL SPECIFICATION - ISO-1181 2004, BS-2087, STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABEL & MARKING AS PER ISO 2307 & 9554	
32	DGE102 324	NO DATA AVAILABL E	424050508870 5/ CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
33	DGD91527	NO DATA AVAILABLE	0035500000324 / DISH BAKING ALUM		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DGB102	NO DATA	028359923680	BR 320D/76	2 /						TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	329	AVAILABLE	0 / SOLDER PASTE SELFLUX TYPE TCC SELF SOLDERING 1 LB TIN		KILOGRAMME						DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
35	DGE101333		0474504740126 / SHAMIANA COMPLETE, SIZE: 15X30- FEET		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES (GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03 KGS WITH WOODEN HANDLE 1.5 FEET LENGTH)GENERAL SPECIFICATION - 1. SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES (GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03 KGS WITH WOODEN HANDLE 1.5 FEET LENGTH)	
36	DGD991		773070504805		24 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	45		5 / PLATE PUDDING FLAT 19CM GOLDEN CRESTED		EACH/N UMBER						FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) <u>GENERAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u>	
37	DGD921 98	NO DATA AVAILABL E	773070504806 2 / COFFEE CUP 40 SAUCER 50 GOLDEN CRESTED		12 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
38	DGH105 929	751F00	343901056094 9 / CLEANER NOZZLE (CLEANER SET, WELDING)	GAS CUTTING AND WELDING NOZZLE	2 / SET						<u>TECHNICAL SPECIFICATION - L TEC WELDING & CUTTING SYSTEMS EBENEZER</u> <u>GENERAL SPECIFICATION - L TEC WELDING & CUTTING SYSTEMS EBENEZER</u>	
39	DGT101 280	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	55 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	<u>TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%</u> <u>GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%</u>	
40	DGT102 406	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	<u>TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%</u> <u>GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
41	DGB102885	10589	6525715175020 / ALUMINUM FILLER MATERIAL	WELDING EQUIPPAGE	10 / BOX			FREEDOM ALLOYS INC USA CAGE 5HMZ2 155 RAILROAD PLZ STE 1, ROYERSFORD, PA 19468, UNITED STATES	FREEDOM ALLOYS INC USA CAGE 5HMZ2 155 RAILROAD PLZ		TECHNICAL SPECIFICATION - IPC ATTACHED WITH LETTER GENERAL SPECIFICATION - IPC ATTACHED WITH LETTER	
42	DGE101949	2040	5330705131806 / RUBBER STRIP	DOOR&HATCHES SEAL	20 / METER	NO DATA AVAILABLE		PK	ABBASI TRADERS RUBBER STORE PH#2416152		TECHNICAL SPECIFICATION - 1 GENERAL SPECIFICATION - 1	
43	DGH102498	BS EN 10025 S 275 JR	9520705136052 / ANGLE STEEL BULB BAR 140MM X 09MM	DOCK,S HULL	40 / METER	NO DATA AVAILABLE		PK	M/S RUBY TRADERS IRON & STEEL SHERSHAH RD KARACHI -2573339		TECHNICAL SPECIFICATION - BS EN 10025 GRADE S 275 JR GENERAL SPECIFICATION - BS EN 10025 GRADE S 275 JR	
44	DGE101063	A-A-50162	7920006342408 / Towel, machinery wiping	0	1 / PACKET	0	0	1333 ISAAC HULL AVE SE, WASHINGTON NAVY YARD, DC	NAVAL SEA SYSTEMS COMMAND		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
45	DGE102351	P-295/2400	5970008166056 / Tape insulation electrical	NIL	24 / EACH/NUMBER	NA	NA	US Postal Code 08701-4537, 1990 RUTGERS BLVD, LAKEWOOD, USA	NITTO, INC, USA		TECHNICAL SPECIFICATION - PMS Item GENERAL SPECIFICATION - PMS Item	
46	DGE101831	7920-00-148-9666	7920001489666 / Rag wiping Cotton & cotton synthetic 50 lbs	NIL	250 / SET	NA	NA	ALFA LAVAL TUMBA AB, HANS STAHLES VAG 7 TUMBA SWEDEN	ALFA LAVAL TUMBA AB, SWEDEN		TECHNICAL SPECIFICATION - PMS Item GENERAL SPECIFICATION - PMS Item	
47	DGE101378	7920-00-148-9666	7920001489666 / Rag wiping Cotton & cotton synthetic 50 lbs	NIL	60 / SET	NA	NA	ALFA LAVAL TUMBA AB, HANS STAHLES VAG 7 TUMBA SWEDEN	ALFA LAVAL TUMBA AB, SWEDEN		TECHNICAL SPECIFICATION - PMS Item GENERAL SPECIFICATION - PMS Item	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
48	SGT106005	NO DATA AVAILABLE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB TO 850 KG/CUB. METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	60 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI. TEL/ FAX: +92-21-32776064. MOBILE 0322-2578654.		TECHNICAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB <u>GENERAL SPECIFICATION</u> - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	
49	DGB101854	F06DSS	4030795152993 / STAINLESS STEEL SHACKLE 06 MM DEE TYPE (S.W.L)	TAL SHIP SAILING RIG	20 / EACH/NUMBER			EURO PRODUCTS. INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL; EUROPRODUCTSINC. COM#SALES@	UK		TECHNICAL SPECIFICATION - EURO PRODUCTS. INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC. COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG. <u>GENERAL SPECIFICATION</u> - EURO PRODUCTS. INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC. COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG.	
50	DGB101857	F12DSS	4030795152992 / STAINLESS STEEL SHACKLE 12 MM DEE TYPE (S.W.L)	TAL SHIP SAILING RIG	20 / EACH/NUMBER			EURO PRODUCTS. INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL; EUROPRODUCTSINC. COM#SALES@	UK		TECHNICAL SPECIFICATION - EURO PRODUCTS. INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC. COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG. <u>GENERAL SPECIFICATION</u> - EURO PRODUCTS. INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG.	
51	DGE101591	H R 550	802000598408 0 / COVER PAINT ROLLER	PAINT ROLLER	15 / EACH/NUMBER	CAGE CODE ODRR8		FEDERAL SPECIFICATION USA CAGE CODE 81348ODRR8	FEDERAL SPECIFICATION S USA		TECHNICAL SPECIFICATION - MATERIAL FIBER , POLYESTER PILE HEIGHT 0.625 INCHES NOMINAL , NOMINAL LENGTH 7.000 INCHES GENERAL SPECIFICATION - MATERIAL FIBER , POLYESTER PILE HEIGHT 0.625 INCHES NOMINAL , NOMINAL LENGTH 7.000 INCHES	
52	DGE102299	EM 3061	593572512993 6 / RAYCHEM HEAT SHRINK	-	2 / EACH/NUMBER			GR	GMBH GERMANY		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
53	DGH106114	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	23 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM GENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
54	DGE101571	5557 SERIES	685071518046 0 / WATER CONTACT INDICATOR tape 5 X 5 MM	ADHESIVE TYPE INDICATION TAPE	10 / EACH/NUMBER	MSDS MATERIAL		3M	3M USA		TECHNICAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm) GENERAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm)	
55	DGE101894	5557 SERIES	685071518046 0 / WATER CONTACT INDICATOR tape 5 X 5 MM	ADHESIVE TYPE INDICATION TAPE	10 / EACH/NUMBER	MSDS MATERIAL		3M	3M USA		TECHNICAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm) GENERAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm)	
56	DGB74261		027678910587 6 / SCREWDRIVE		21 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			R F/POINT BLADE LG 6" TIP WIDTH 0.156 O/A LG 9.25"								AVAILABLE	
57	DGE105 889		041370506324 3 / ANTI SKID DOTTED RUBBER FLOORING COLOUR GREEN 15" X36"0.17"		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DGE101 373	NO DATA AVAILABL E	055979020048 5 / INSULATION- TAPE- POLYETHYLE NE TERAPHALAT E(TERYLENE) W/0.75		45 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DGE101 447	DGS 6971	041359923876 1 / HOSE RUBBER, LENGTH= 60- FEET, NOMINAL OVERALL INTERNAL DIA= 0.500 INCHES, OUTSIDE DIA= 0.875 INCHES		50 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DGE102 335	NO DATA AVAILABL E	055979444469 0 / RUBBER- TAP- INSULATION		35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DGE101 814	NO DATA AVAILABL E	055979444469 0 / RUBBER- TAP- INSULATION		35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
62	DGE102 304	0.75X0. 007INCH- 50MTR-	055979001524 4 / INSULATION-		15 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TAPE-VARNISHED WOVEN GLASS-FIBRE-(STRAIGHT CUT}								AVAILABLE	
63	DGE101 369	0414-7801	041459923090 2 / PACKING MATERIAL COTTON YARN FOR FRESH WATER PUMP SIZE 1/4"SQ		9 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DGE722 44		047659943042 2 / BRUSH ARTIST MET FER/SQU HAIR ST SPECT LG 0.750" WD 0.500"		32 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DGE967 28	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.		45 / EACH/N UMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
66	DGB102 331	NO DATA AVAILABL E	028370000162 4 / ROD WELDING MANGANESE BRONZE 1/8" 0.12"SPEC BS1453C2B (LOCAL)		5 / KILOGR AMME						TECHNICAL SPECIFICATION - length: 1 Meter thickness: 1/8 inch Packing: 5kg/ Packet GENERAL SPECIFICATION - length: 1 Meter thickness: 1/8 inch Packing: 5kg/ Packet	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
67	DGB101842	AWS S-8018-B2	0283700011838 / ELECTRODE WELDING 2.6 MM AWS S-8018-B2	WELDING SYSTEMS	120 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
68	DGB106116		0283502831521 / CADMIUM ANODE ROLLED LG 12 INCH WTH 8 INCH TH 3/8 INCH		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH GENERAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH	
69	DGB104432		0283595711474 / SHEET-NAVAL-BRASS-ANNEALED 48		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340 GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
70	DGE101991	BS 1154	0413599238921 / RUBBER SHEET SOLID NATURAL LG. 72 WD 48 INCH THICKNESS 01 INCH		20 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	DGE102500	NO DATA AVAILABLE	0451594510013 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	40 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS GENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	
72	DGE102395	NO DATA AVAILABLE	0451594510013 / OIL-CLOTH PAINTED FOR TABLE COVERS	GENERAL USED	20 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS GENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WHITE WIDTH 50 INCH									
73	DGE102320	BS-1145 HARDNES S 42-50	041359923890 0 / SHEET RUBBER SOLID NATURAL OFF WHITE SQ 05 LBS 0.625 X48X72IN	TENSILE STRENGTH 2500PSI	20 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DGH106118	DNC S-15	021159119997 3 / MS PLATE SIZE 2500X1250X5 MM		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025.STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. GENERAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025.STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010.	
75	DGH103328		021159119995 3 / PLATE STEEL CARBON MILD BLACK 5000X1500X10 MM		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - BSEN 10025-2 OF 2019, GRADE S275 JR, THICKNESS TOLERANCE LIMIT: "CLASS C" IN TABLE 1 OF BSEN 10029 GENERAL SPECIFICATION - BSEN 10025-2 OF 2019, GRADE S275 JR, THICKNESS TOLERANCE LIMIT: "CLASS C" IN TABLE 1 OF BSEN 10029	
76	DGH102038		023159571531 3 / WIRE ROPE GRIP STEEL DIA 0.398"		100 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
77	SGB102041		021459043020 6 / NUT-PLAIN- HEXAGON- BSW-0.56INCH THREAD SIZE 9/16"THICK 0.500		120 / TEN						TECHNICAL SPECIFICATION - AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) Spec: BS-970 material grade: EN4140 THICKNESS: 1/4" INNER DIA: 1/2" OUTER DIA: 7/8" THREAD SIZE: 9/16" Material Grade EN4140	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											coc/mtc required GENERAL SPECIFICATION - AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) Spec: BS-970 material grade: EN4140 THICKNESS: 1/4" INNER DIA: 1/2" OUTER DIA: 7/8" THREAD SIZE: 9/16" Material Grade EN4140 coc/mtc required	
78	DGE102005	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sSTRAND, Z-LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	120 / FATHOM						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
79	DGE102004	NIL	035059923712 9 / ROPE NYLON, HAWSERLAID, 3-STRANDS, CIRCI 3", NOM DIA: 24MM, Z- LAY, TYPE-1, MINIMUM BREAKING LOAD : 12 TONS	STRENGTH 11.800 TONS UNIT OF AVAILABILIT	120 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
80	DGE102003	NO DATA AVAILABLE	0350599237130 / ROPE NYLON HAWSERLAID, DIA: 28-MM, 3-STRAND	MIN BRKG STRENGTH 15.500 TONS UNIT OF	120 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
81	DGB101399		021459941000 8 / BOLT MACHINE STEEL UNC HEX HD SZ 0.500X3. 500X1.250 IN	BR 320 D/70	20 / TEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DGB101614	NO DATA AVAILABL E	026259419527 1 / SWIVEL- WITH- THIMBLE- LENGTH2.25"- DEP.50"		14 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	DGB101527	(SIM)	025770941150 4 / NUT-PLAIN- HEXAGON (BRASS) THREAD UNF SZ .375"LH . 350"		32 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
84	DGH102499		021259571098 1 / STEEL T-		60 / METER						TECHNICAL SPECIFICATION - BS EN 10025 / 2019 Material Grade S-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Section Carbon STEEL (FINISH BLACK) 04X3X3/8"								275 JR T-SECTION MANUFACTURED IN RADIUS ROOT & TOES FIGURE ATTACHED. SIZE : NOMINAL DEPTH OF SECTION: 03 INCH; NOMINAL WIDTH OF FLANGE:04 INCH; THICKNESS: 3/8 INCH (UNIFORM) WEIGHT PER SQ/FT : 8.49 LBS <u>GENERAL SPECIFICATION</u> - BS EN 10025 / 2019 Material Grade S-275 JR T-SECTION MANUFACTURED IN RADIUS ROOT & TOES FIGURE ATTACHED. SIZE : NOMINAL DEPTH OF SECTION: 03 INCH; NOMINAL WIDTH OF FLANGE:04 INCH; THICKNESS: 3/8 INCH (UNIFORM) WEIGHT PER SQ/FT : 8.49 LBS	
85	DGE101 963	947-430229	H94799560058 2 / RUBBER STRIP	GENERAL PURPOSE	26 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
86	DGE101 520	NO DATA AVAILABLE	033054600448 4 / HEAVING LINE 06MM L50MM 466MS	MSI	1620 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
87	DGE101 945	NO DATA AVAILABLE	046150000679 2 / CHALK WHITE SOFT	W/T DOORS & FIT	28 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
88	DGE101 820	NO DATA AVAILABLE	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
89	DGB101 869	NO DATA AVAILAB L E	343971504503 4 / ELECTRODE SEA WELD 5/32X14 IN		1000 / PACK E T						<u>TECHNICAL SPECIFICATION</u> - a. Detailed Specifications : UW-CS-2 Electrode Welding 5/32 Inches (4.0 mm) b. Technical data : AWS E70XX c. Polarity : DC Electrode Negative (DCEN) d. Position : Flat, Horizontal, Vertical, Overhead e. Type of Arc : Medium, Moderate, Penetration f. Material : Low Carbon Steels g. Technique : Use short Arc length with electrode angle 30 o + 15 o , to the line of weld. 2. Acceptance criteria : Item will be accepted upon technical rep inspection. <u>GENERAL SPECIFICATION</u> - a. Detailed Specifications : UW-CS-2 Electrode Welding 5/32 Inches (4.0 mm) b. Technical data : AWS E70XX c. Polarity : DC Electrode Negative (DCEN) d. Position : Flat, Horizontal, Vertical, Overhead e. Type of Arc : Medium, Moderate, Penetration f. Material : Low Carbon Steels g. Technique : Use short Arc length with electrode angle 30 o + 15 o , to the line of weld. 2. Acceptance criteria : Item will be accepted upon technical rep inspection.	
90	DGE101 572	A-A-1201	535000221088 2 / PAPER ABRASIVE	FIRE FIGHTING EQUIPMENT	20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
91	DGE101 723	MIL-P-15280	564000237482 8 /		40 / EACH/N						<u>TECHNICAL SPECIFICATION</u> - MIL-P-15280 SLEEVE SIZES: LENGTH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INSULATION SLEEVING THERMAL		UMBER						72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
92	DGE102 298	MWTM 95/29-1200	593572507749 1 / HEAT SHRINK SLEEVE		5 / METER						TECHNICAL SPECIFICATION - Dimensions: Size: 95/29 Expanded Diameter: 95mm Recovered Diameter: 29mm Cable Range Diameter: 32-86 mm Length: 1m GENERAL SPECIFICATION - Dimensions: Size: 95/29 Expanded Diameter: 95mm Recovered Diameter: 29mm Cable Range Diameter: 32-86 mm Length: 1m	
93	DGE102 297	ECW0090 3-12	593572507749 2 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SIZE 48/16 LG 1 METER		3 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DGE101 942	000W280	599999784543 2 / BRAID-BANDAGE (WIRE MES KNITTED)	GLASS WOOL (DC BOX)	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DGE105 893	9-27052	626001074423 0 / LIGHT CHEMILUMINE SC		600 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
96	DGE105894	SA9-27077PF.	6260011785560 / LIGHT, CHEMILUMINE SCENT 6inch BLUE	REPLENISHMENT LIGHT	50 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DGE101589	NIL	7920705101791 / BROOM NYLON SIZE:1. X2"(BRUSH NYLON)		6 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DGE101599	NO DATA AVAILABLE	0474500000307 / FENDER COIR ROUND		4 / EACH/NUMBER	600MM 24" ROUND COIR BOAT FENDER					TECHNICAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.GENERAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.	
99	DGE101366	NO DATA AVAILABLE	0474500000307 / FENDER COIR ROUND		5 / EACH/NUMBER	600MM 24" ROUND COIR BOAT FENDER					TECHNICAL SPECIFICATION - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY. <u>GENERAL SPECIFICATION -</u> CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY.	
100	DGE105 885	NO DATA AVAILABLE	0422500000027 / IMPROVED VERSION PVC TILES MAROON SIZE 300X300X3MM		50 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
101	DGE102 396	NO DATA AVAILABLE	0422500000027 / IMPROVED VERSION PVC TILES MAROON SIZE 300X300X3MM		50 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
102	DGE105 892	NO DATA AVAILABLE	0422500000003 / CARPET WOOLEN.		429.4 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm <u>GENERAL SPECIFICATION -</u> (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm	
103	DGE105	NO DATA	0422500000002		50 /	NO DATA					<u>TECHNICAL SPECIFICATION -</u> NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	884	AVAILABLE	6 / IMPROVED VERSION PVC TILES SKY BLUE SIZE 300X300X3MM		EACH/NUMBER	AVAILABLE					DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
104	DGT106001	NO DATA AVAILABLE	0100500000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	700 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
105	DGT106145	NO DATA AVAILAB LE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	96 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER. GENERAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
106	DGT105 977	NO DATA AVAILABL E	010050000001 5 / PLY WOOD GRADE-1, 5 PLY		996 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) GENERAL SPECIFICATION _ SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
107	DGT106 144	NO DATA AVAILABL E	010050000001 5 / PLY WOOD GRADE-1, 5 PLY		320 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) GENERAL SPECIFICATION _ SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
108	DGT103 050	NO DATA AVAILAB L E	010050000002 8 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLIES OF SHESHAM WOOD) 5-PLY	2.440X1. 220MTRX6. 35MM) SPECE/BS-1088	640 / SQ FEET	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, GENERAL SPECIFICATION - 1. SIZE= A. LENGTH: 8-FEET B. WIDTH: 4-FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,	
109	DGT100 197	NO DATA AVAILAB L E	010050000002 9 / Ply wood, Marine All Shesham, 13-Ply, GD-II, (WBP, Treated with Preservative) Size: L=8FT, W=4FT,		64 / SQ FEET	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METERGENERAL SPECIFICATION - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TH=25MM, (Core inner plies & veneer) (Wood Should be all Shesham)								PER CUBIC METER	
110	DGE105888	NO DATA AVAILABLE	0451500000005 / CLOTH FOR CURTAIN WIDTH 46 INCHES.		142 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
111	DGE101364	NO DATA AVAILABLE	7330701002289 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDUS/JOY0).		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - WITH FULLCOVER GENERAL SPECIFICATION - WITH FULLCOVER	
112	DGT101976	BELFONT TRUWOOD TEAK	9330992246097 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		7 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
113	DGE101983	BS 419/156	0559546005362 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		20 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
114	DGE98108	NO DATA AVAILABLE	0559780000187 / SLEEVE PLASTIC DIA 0.5CM		5 / ROLL	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S.NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black <u>GENERAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S, NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black</u>	
115	DGE100162	NO DATA AVAILABLE	0559780000187 / SLEEVE PLASTIC DIA 0.5CM		5 / ROLL	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S,NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black</u> <u>GENERAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S, NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black</u>	
116	DGE101972	NO DATA AVAILABLE	0559780000185 / SLEEVE PLASTIC		5 / ROLL	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
117	DGE101812	NO DATA AVAILABLE	0559790001985 / TAPE INSULATING BIAS WIDTH	GENERAL ELECTRIC USE	7 / ROLL	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			0.500IN TH 0.01IN LENGTH 50.0 MTR									
118	DGE102 347	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		19 / EACH/N UMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
119	DGT862 31	NO DATA AVAILABL E	010054600229 0 / BAMBOO SIZE 28FT- 30FT LONG	DEISEL GENERATOR	30 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10- 30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREEGENERAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10- 30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREE	
120	DGB914 66		024874512026 6 / CB SAFE SIZE LENTH X BRTH X HT 33" X19"X17"(INCH QUIB) IRON	FOR WARDROOM ON BOARD S/M	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Security safe Steel with combination lock size 48"X30"X29" inner body 16 Gauge outer body 18 gauge mild steel grade CRS S400, Door outer steel gauge 4mm complete door not less than 3/8" thickness (Front door nonmagnetic steel S S Steel, other body mild steel)GENERAL SPECIFICATION - Security safe Steel with combination lock size 48" X30"X29" inner body 16 Gauge outer body 18 gauge mild steel grade CRS S400, Door outer steel gauge 4mm complete door not less than 3/8" thickness (Front door nonmagnetic steel S S Steel, other body mild steel)	
121	DGE723 00	C-134	085158000007 6 / DEFENCER EAR C-134 62TD		57 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
122	DGH102580		021159204455 3 / SHEET STEEL STAINLESS SIZE 3050X1220X3 MM	DEEP FRYER 2PAN	8 / EACH/N UMBER						TECHNICAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MM GENERAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0. 25MM	
123	DGE88603	ALM7140A	841573513973 6 / DIVING GLOVES	DIVING.	15 / PAIR	ISF PROLINE		OC		TIWAN	TECHNICAL SPECIFICATION - SOFT,THICK RUBBER, SIZE: NORMAL SIZE GENERAL SPECIFICATION - SOFT,THICK RUBBER, SIZE: NORMAL SIZE	
124	DGD106099		731070534478 6 / SS HOT/ COLD BAIN MARIE WITH SS CUTLERY CABINET		1 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - SS HOT/ COLD BAIN MARIE WITH SS CUTLERY CABINET SIZE OF SS HOT/ COLD BAIN MARIE : 72" X 30" X 34" SIZE OF SS CUTLERY CABINET: 60" X 30" X 52" GENERAL SPECIFICATION - SS HOT/ COLD BAIN MARIE WITH SS CUTLERY CABINET SIZE OF SS HOT/ COLD BAIN MARIE : 72" X 30" X 34" SIZE OF SS CUTLERY CABINET: 60" X 30" X 52"	
125	DGE106140	5557 SERIES	685071518046 0 / WATER CONTACT INDICATOR tape 5 X 5 MM	ADHESIVE TYPE INDICATION TAPE	10 / EACH/N UMBER	MSDS MATERIA L		3M		3M USA	TECHNICAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm) GENERAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm)	
126	DGE106282	0413/8520	041359923891 1 / SHEET RUBBER SOLID NATURAL, OFF WHITE SQ 1/2 LBS, SIZE: 1830MM		10 / KILOGR AMME						TECHNICAL SPECIFICATION - 1. BS-1154 OF 1992 COMPOUND CLASSIFICATION, Y-40 2. HARDNESS RATING: 38-40 DEGREES 3. TENSILE STRENGTH: 2500 PSI GENERAL SPECIFICATION - 1. BS-1154 OF 1992 COMPOUND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			X 1220MM X 16.0MM (39.29 KILOS PER SHEET)								CLASSIFICATION, Y-40 2. HARDNESS RATING: 38-40 DEGREES 3. TENSILE STRENGTH: 2500 PSI	
127	DGE106 071	0413-8522	041359923891 3 / RUBBER SHEET SOLID NATURAL (48 inch X 72 inch x 1/4 inch)	CONT OIL TANKS	40 / KILOGRAMME						TECHNICAL SPECIFICATION - ITEM SPECIFICATION: STANDARD BS 1154. <u>GENERAL SPECIFICATION</u> - ITEM SPECIFICATION: STANDARD BS 1154.	
128	DGE106 186		047450474012 6 / SHAMIANA COMPLETE, SIZE: 15X30- FEET		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES (GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03 KGS WITH WOODEN HANDLE 1.5 FEET LENGTH) <u>GENERAL SPECIFICATION</u> - 1. SIZE= 15X30 FEET 2. MATERIAL= 100% COTTON, 3. SOUND REASONABLY STRAIGHT AND FREE FROM 100% BORER OR INSECT HOLES (GHOON) SPLIT AND RESERVED. 4. BAMBOO OF MATURE STEM, 5. COLOR= ITEM IS REQUIRED IN MULTICOLOR I E (YELLOW/ GREEN/ WHITE) 6. FOLLOWING ACCESSORIES= A. BAMBOO= 06 WITH COVER STANDARD SIZE, B. ROPES= 06 STANDARD SIZE, C. FRILL 02 (15 FEET) & 02 (30 FEET) D. KILLY 04 (IRON ROD), E. IRON HAMPER= 01 IN NOS (WEIGHT 03	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											KGS WITH WOODEN HANDLE 1.5 FEET LENGTH)	
129	DGE106 176		034059923619 8 / BAGS CANVAS SHIP DOCUMENTS FTD 3.50" POCKET SZ. 16.00X20.00IN		6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - A.</u> Color : Green, Gray, Navy Blue, Black B. Dimension : H: 18", W: 18", L: 36" C. Made from : Bag made with Waterproof Canvas/Fabric D. Shape : U shape for opening f. Appearance : 2 handles and shoulder strips E. Pockets Qty : 04 x pockets with Zipper F. Pocket Size : 08" x 12" <u>GENERAL SPECIFICATION - A.</u> Color : Green, Gray, Navy Blue, Black B. Dimension : H: 18", W: 18", L: 36" C. Made from : Bag made with Waterproof Canvas/Fabric D. Shape : U shape for opening f. Appearance : 2 handles and shoulder strips E. Pockets Qty : 04 x pockets with Zipper F. Pocket Size : 08" x 12"	
130	DGB954 41		021259923280 2 / BAR STEEL CORROSION RESISTING H/R RD 1.25" WT PER FT 4.209LBS		1 / METER						<u>TECHNICAL SPECIFICATION -</u> minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D) <u>GENERAL SPECIFICATION -</u> minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D)	
131	DGB963 63	SPEC BS 2874 C 107-0	028359961098 2 / ROD COPPER RD ANNEALED DIA 0.75 INCH (WEIGHT/ FOOT 1.710 LB		10 / METER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
132	DGB102 247		027379000411 4 / CUTTER INSULATION REMOVING DIAMETER CAPACITY 0.744IN	USE; PYROTEX CABLE	6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
133	DGE106 223		033059571326 6 / TWINE HEMP		10 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - (1)</u> 3 strand twin hemp packing medium and material consist of natural jute or	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PACKING MEDIUM 3STRD POLISHE MIN BKG STRGTH 100LB								hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses. <u>GENERAL SPECIFICATION</u> - (1) 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses.	
134	DGB101 549		021458000101 6 / BOLT WITH NUT STEEL 252TD SZ 15X14 AND 12X5MM	S/M	120 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
135	DGE101 547		005070000038 4 / CORRECTING TAPE-		5 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HERMESTOP-TRONIC-21									
136	DGH102668	BS EN 10025-2/2004, MATERIAL GRADE S 275 JR	0212595710718 / ANGLE STEEL CARBON E/S BLACK 1.25 X 1.25 X 0.25 INCH		32 / METER						<u>TECHNICAL SPECIFICATION -</u> RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr <u>GENERAL SPECIFICATION -</u> RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr	
137	DGB102748	0251-14505	0251704119737 / FERRULE-WIRE-ROPE 1.5 INCH (12mm)		63 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> MATERIAL aluminum alloy SHAPE ELLIPSE TYPE COLOR SILVER INTERNAL WIDTH 26 MM INTERNAL HEIGHT 13 MM OUTER DIA 36 MM OUTER LENGHT 42 MM BODY THICKNESS 05 MM <u>GENERAL SPECIFICATION -</u> MATERIAL aluminum alloy SHAPE ELLIPSE TYPE COLOR SILVER INTERNAL WIDTH 26 MM INTERNAL HEIGHT 13 MM OUTER DIA 36 MM OUTER LENGHT 42 MM BODY THICKNESS 05 MM	
138	DGE102259	NO DATA AVAILABE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO.	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
139	DGE974 85	NSN 1370-99-9629136	422072505519 8 / HAND FLARE RED P MK 3 (USE ONLY WHEN AIRCRAFT)	SURVIVAL PACK USED FOR 20MEN LIFERAFT	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
140	DGB102 281	NO DATA AVAILABLE	512073100065 4 / SCREW DRIVER FLAT PIONT 8PCS SET INTERCHANG EABLE(CHINA MADE)		1 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
141	DGE998 92		533000618322 1 / PACKING MATERIAL SIZE 3/16"		10 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
142	DGE106 254		533000244019 2 / SHEET RUBBER SOLID 0.125 X24X324 INCH		80 / FOOT						TECHNICAL SPECIFICATION - MILR900 GENERAL SPECIFICATION - MILR900	
143	DGE106 279	NO DATA AVAILABLE	593572507749 4 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 31/8 LG, 01 METER		40 / METER						TECHNICAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B. PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224 G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT AND ABRASION. GENERAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224 G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT AND ABRASION.	
144	DGE106083	SA9-27077PF.	6260011785560 / LIGHT, CHEMILUMINE SCENT 6inch BLUE	REPLENISHMENT LIGHT	50 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DGE106070	NIL	8105011242645 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217-9451	STATIC SAFETY OF EQUIPMENT/COMPONENTS	40 / EACH/NUMBER						TECHNICAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557 GENERAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
146	DGE105891	NIL	8105011242645 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217-9451	STATIC SAFETY OF EQUIPMENT/COMPONENTS	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557 GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
147	DGE98114		8135705064882 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	131 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
148	DGE105965	NO DATA AVAILABLE	0422500000026 / IMPROVED VERSION PVC TILES SKY BLUE SIZE 300X300X3MM		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
149	DGE103217	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	3 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAGE					TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. <u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
150	DGE103089	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	3 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					<u>TECHNICAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. <u>GENERAL SPECIFICATION - 1.</u> 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
151	DGE106281	NO DATA AVAILABLE	047650000006 1 / GLOVES LEATHER FOR WELDING, treated with preservative, standard quality		149 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag brochure uploaded as annex GENERAL SPECIFICATION - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL details: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex	
152	DGE101371	MIL-G-1149	9320002826624 / RUBBER SHEET LG 50 FT, WD 03 FT, TH 2.5 MM		15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
153	DGE95820	BS 419/156	0559546005362 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
154	DGD105615		0035546000615 / Pot Aluminum 18/9" With COVER		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 18 Gauge Aluminum Pot having Capacity of 250 lbs Aluminum grade (as food grade and lead free) GENERAL SPECIFICATION - 18 Gauge Aluminum Pot having Capacity of 250 lbs Aluminum grade (as food grade and lead free)	
155	DGE106280	B2315512	4710705177960 / FLEXIBLE PIPE 1 INCH DIA	CNA LAN NETWORK	500 / METER			ADAMJEE PAKISTAN		ADAMJEE PAKISTAN	TECHNICAL SPECIFICATION - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter GENERAL SPECIFICATION - ADAMJEE PAKISTAN M/S INBOX TECHNOLOGIES PVT LTD KARACHI POLYMER UPVC PIPE Item: PVC Flexible Pipe	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Specifications: Internal: Dia: 1" Thickness: 2mm Picture attached as Annex A Quantity 2600 Meter	
156	DGE106 225		042270515841 1 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	1800 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI & M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTIC S, SADDAR KARACHI		TECHNICAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
157	DGD102 303	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTME NT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	270 / EACH/N UMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 810+ GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX design: AS PER STOCK SAMPLE GENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 810+ GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX design: AS PER STOCK SAMPLE	
158	DGH106 153	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	23 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM GENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
159	DGH106 267	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	23 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM GENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
160	DGE105 607		033050942726 7 / FLANNELETTE CLOTH WHITE GROUND WITH RED STRIPT 4"X50	SMALL ARMS CLEANING	2060 / METER						TECHNICAL SPECIFICATION - BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural. GENERAL SPECIFICATION - BOOK REF DEF STAN 83 - 48/2	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			YARDS								1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural.	
161	DGE106 241	-	035059571323 5 / ROPE SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH (ROUNDED IN 9-MM)		240 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554. <u>GENERAL SPECIFICATION</u> - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554.	
162	DGE104 084	-	035059571323 5 / ROPE SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH (ROUNDED IN 9-MM)		120 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554. <u>GENERAL SPECIFICATION</u> - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554.	
163	DGE105 974		041370506324 3 / ANTI SKID DOTTED RUBBER FLOORING COLOUR GREEN 15" X36"0.17".		48 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
164	DGE104 081	NO DATA AVAILABL E	035059571313 2 / ROPE NYLON, 3- STRAND, CIRC: 4-INCH, DIA: 32MM		240 / FATHO M	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI <u>GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI</u>	
165	DGH106 268		021159923013 9 / PLATE STEEL CARBON SIZE 2500X1250X03 MM	HOUSE SIDE FTG	21 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> BSEN:10025/2 OF 2019, STEEL GRADE: S275 JR. special instructions: a. MILL TEST certificate (MTC) required alongwith supply. the certificate should have information on mechanical & chemical properties, steel grade, batch & heat number alongwith date. b. each plate shall have a suitable stamp at a corner indicationing batch number, garde and manufacturer for case identification. c. material should be freshly rolled & free steel all defects. <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BSEN:10025/2 OF 2019, STEEL GRADE: S275 JR. special instructions: a. MILL TEST certificate (MTC) required alongwith supply. the certificate should have information on mechanical & chemical properties, steel grade, batch & heat number alongwith date. b. each plate shall have a suitable stamp at a corner indicating batch number, grade and manufacturer for case identification. c. material should be freshly rolled & free steel all defects.	
166	DGE105 658	DEFSTAN 40-3	033059571325 3 / TWINE HEMP 3- STRAND, MIN BKG STRENGTH 810 LBS, DIA: 7mm		39 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> APPROX CIRC 7/8" DIA 7MM Materiel: Jute Process : Twist Colour Natural: Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE SPECIFICATION BS 2019 C-1557. CONSTRUCTION STYLE: 3 PLY/ 3 STRANDS <u>GENERAL SPECIFICATION -</u> APPROX CIRC 7/8" DIA 7MM Materiel: Jute Process : Twist Colour Natural: Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE SPECIFICATION BS 2019 C-1557. CONSTRUCTION STYLE: 3 PLY/ 3 STRANDS	
167	DGE105 659	BS2019	033059571325 7 / TWINE HEMP LOG PLAIED BKG 1000 LBS CIRC 1.125		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> BS 6125/1981 <u>GENERAL SPECIFICATION -</u> BS 6125/1981	
168	DGE106 224		033059571326 2 / TWINE NYLON ROPING 3 STRD		5 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NATURAL FINISH MIN BKG STRGT 50 LB								Min Breaking Strength: 23 KG h. General Specs: Rot Proofed. <u>GENERAL SPECIFICATION - a.</u> Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed.	
169	DGE105 680	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sSTRAND, Z-LAY, 120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	240 / FATHO M						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION -</u> SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
170	DGE104 802	NIL	035059923712 8 / ROPE NYLON, HAWSERLAID, Z-LAY, 3- STRANDS, NOM DIA: 20MM, CIRC: 2.50 INCH, TYPE: 1, MINIMUM BREAKING LOAD: 8.3 TONS	MIN BRKG STRENGTH UNIT OF AVAILABILITY	220 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
171	DGE104 874	NIL	035059923712 8 / ROPE NYLON, HAWSERLAID, Z-LAY, 3- STRANDS, NOM DIA: 20MM, CIRC: 2.50 INCH, TYPE: 1, MINIMUM BREAKING LOAD: 8.3 TONS	MIN BRKG STRENGTH UNIT OF AVAILABILITY	240 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
172	DGE104 678	NIL	035059923712 9 / ROPE NYLON, HAWSERLAID, 3-STRANDS, CIRCI 3", NOM DIA: 24MM, Z-LAY, TYPE-1, MINIMUM BREAKING LOAD : 12 TONS	STRENGTH 11.800 TONS UNIT OF AVAILABILIT	120 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
173	DGE104 031	NIL	035059923713 1 / ROPE NYLON HAWSERLAID, 3-STRAND, Z- LAY TYPE-I, SIZE: CIRC 4", NOM DIA: 32MM	BRKG STRENGTH UNIT OF AVAILABILITY 322LB	240 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
174	DGE104080	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	240 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
175	DGE106 238		047450474012 7 / QANAT COMPLETE SiZe. 18.00X7. 00 FT		20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - a. Size: Height 7 Feet, Length 18 Feet. b. Front Side: Golden/ Design. c. Back Side:.Simple / different color. d. Cloth Material:. Jersey two side heavy. e. Accessories:.Bamboos, sticks and ropes. f. Bamboos:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
176	DGE106187		0474504740127 / QANAT COMPLETE SiZe. 18.00X7.00 FT		30 / EACH/NUMBER						Quantity , 120, Length 10 ft each bamboo g. Rope: QUANTITY, 120, Length 12 ft each Rope h. Color of Design for Front/ Back. Olive Green, l. Multi-color (Yellow, Red and Green) are proposed for front/ back side design. <u>GENERAL SPECIFICATION</u> - a. Size: Height 7 Feet, Length 18 Feet. b. Front Side: Golden/ Design. c. Back Side: Simple / different color. d. Cloth Material: Jersey two side heavy. e. Accessories: Bamboos, sticks and ropes. f. Bamboos: Quantity , 120, Length 10 ft each bamboo g. Rope: QUANTITY, 120, Length 12 ft each Rope h. Color of Design for Front/ Back. Olive Green, l. Multi-color (Yellow, Red and Green) are proposed for front/ back side design.	
											<u>TECHNICAL SPECIFICATION</u> - a. Size: Height 7 Feet, Length 18 Feet. b. Front Side: Golden/ Design. c. Back Side: Simple / different color. d. Cloth Material: Jersey two side heavy. e. Accessories: Bamboos, sticks and ropes. f. Bamboos: Quantity , 120, Length 10 ft each bamboo g. Rope: QUANTITY, 120, Length 12 ft each Rope h. Color of Design for Front/ Back. Olive Green, l. Multi-color (Yellow, Red and Green) are proposed for front/ back side design. <u>GENERAL SPECIFICATION</u> - a. Size: Height 7 Feet, Length 18 Feet. b. Front Side: Golden/ Design. c. Back Side: Simple / different color. d. Cloth Material: Jersey two side heavy. e. Accessories: Bamboos, sticks and ropes. f. Bamboos: Quantity , 120, Length 10 ft each bamboo g. Rope: QUANTITY, 120, Length 12 ft each Rope h. Color of Design for Front/ Back. Olive Green, l. Multi-color	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(Yellow, Red and Green) are proposed for front/ back side design.	
177	DGE104 909	NIL	402099923712 1 / ROPE NYLON, HAWSERLAID, 3-STRD, CIR 1.00", DIA 0.3125" (8MM)	NGTH 1.330 TONS UNIT OF AVAILABILITY	720 / FATHO M						TECHNICAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. GENERAL SPECIFICATION - 1 TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM.	
178	DGE104 803	NIL	402099923713 3 / ROPE NYLON,		220 / METER						TECHNICAL SPECIFICATION - a. 3 stand 40mm in Color white Nylon rope length 220 Mtr. b. Material	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HAWSERLAID, CIRC: 5-INCH, DIA: 40MM, Z-LAY, 3-STRAND,								quality top nylon fibers. c. Thickness and diameter 40mm or 5 inch. d. Length 220 Mtr commercial bulk coil. e. 3-strand or 3-ply twisted rope. f. Breaking strength 28,000 kg to 30,000 kg g. High temperature resistance then polypropylene – working temperature up-to 100c (soften temperature 170c melting temperature 215c) h. A very strong and soft to touch synthetic fiber rope which has excellent shock absorption properties for use as a towing, mooring and as berthing hawser. j. High in strength and abrasion resistance, or elongation and absorbs moisture. 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 220 meter. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - a. 3 stand 40mm in Color white Nylon rope length 220 Mtr. b. Material quality top nylon fibers. c. Thickness and diameter 40mm or 5 inch. d. Length 220 Mtr	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											commercial bulk coil. e. 3-strand or 3-ply twisted rope. f. Breaking strength 28,000 kg to 30,000 kg g. High temperature resistance then polypropylene – working temperature up-to 100c (soften temperature 170c melting temperature 215c) h. A very strong and soft to touch synthetic fiber rope which has excellent shock absorption properties for use as a towing, mooring and as berthing hawser. j. High in strength and abrasion resistance, or elongation and absorbs moisture. 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 220 meter. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
179	DGE105 653		402099923713 7 / ROPE NYLON HAWSERLAID, 3-STRND, Z-LAY, TYPE-1, NOM DIA: 64-	NOR-SHIPS-USE-NASAR	240 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MM, CIRC: 08-INCH,								REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
180	DGH106264	ITD	4010705089994 / PVC	FOR GUARD RAIL PNS	140 / METER						<u>TECHNICAL SPECIFICATION</u> - DIA: 10 mm plastic coating type of core:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			COATED FLEX STEEL WIRE ROPE DIA10MM STRAND 6/26 300FM	JALALAT							hc lay length: right hand regular lay lay direction: nil unit weight: kg/m 0.180 tencel strength: (kg/mm2): 180 breaking load: (kgs): 3100 total mlength: (mtr): 1525 unit length: (mtr) 1525 x 1 reel/coil nos. which this certificate <u>GENERAL</u> SPECIFICATION - DIA: 10 mm plastic coating type of core: hc lay length: right hand regular lay lay direction: nil unit weight: kg/m 0.180 tencel strength: (kg/mm2): 180 breaking load: (kgs): 3100 total mlength: (mtr): 1525 unit length: (mtr) 1525 x 1 reel/coil nos. which this certificate	
181	DGE106 167		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIE S)	OLIVE GREEN WATERPROO F INNER LINNING OF,	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE/DIMENSION a.TENT SIZE (LENGTH & WIDTH):50 X 20 FEET (± 6 INCH) b.HEIGHT OF TENT:12 FEET (± 2 INCH) c.HEIGHT OF WALL:07 FEET (± 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850 GSM OR ABOVE WITH ROT- PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180- 200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 50 X 20 FEET (± 6 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 07 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 850 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 07 NOS (03 x	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5.PACKING REQUIRED:QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.	
182	DGE106239		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIES)	OLIVE GREEN WATERPROOF INNER LINNING OF,	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a.TENT SIZE (LENGTH & WIDTH):50 X 20 FEET (± 6 INCH) b.HEIGHT OF TENT:12 FEET (± 2 INCH) c.HEIGHT OF WALL:07 FEET (± 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5.PACKING REQUIRED:QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.<u>GENERAL SPECIFICATION - 1.</u> <u>SIZE/DIMENSION</u> a.TENT SIZE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(LENGTH & WIDTH):50 X 20 FEET (± 6 INCH) b.HEIGHT OF TENT:12 FEET (± 2 INCH) c.HEIGHT OF WALL:07 FEET (± 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4.VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5.PACKING REQUIRED:QTY 03 NOS BAGS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.	
183	DGT106303	NO DATA AVAILAB LE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	1500 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.GENERAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & Thickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
184	DGE104 843	NO DATA AVAILABL E	045150000001 6 / TAPE-WHITE-COTTON		150 / YARD	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
185	DGE104 461	NO DATA AVAILABL E	045150000001 6 / TAPE-WHITE-COTTON		150 / YARD	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
186	DGE104 910	NO DATA AVAILABL E	045150000001 6 / TAPE-WHITE-COTTON		150 / YARD	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
187	DGE106 255	NO DATA AVAILABL E	733070100228 9 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDUS/JOY0).		30 / EACH/N UMBER						TECHNICAL SPECIFICATION - WITH FULLCOVER GENERAL SPECIFICATION - WITH FULLCOVER	
188	DGE106 093		042270515841 1 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	2300 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTIC S, SADDAR KARACHI		TECHNICAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	