

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 12-08-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGD51838	NO DATA	7320705012426 / MACHINE ATTA KNEADING100 TO120KG CAPACITY 440V 50HZ 3PHS 5AMP		2 / EACH/NUMBER	GSA/23/A KM					<u>TECHNICAL SPECIFICATION -</u> Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade) <u>GENERAL SPECIFICATION</u> _Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)	
2	DGD78708		7320705013214 / TOASTER TWO SLOT 220V 50HZ 01 PHASE 920W	FOR DOMASTIC USE	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - a.</u> Make/ Model / Brand/ Equivalent be endorsed: Panasonic/ Dawlance/ West point a. Make/ Model of item Moulinex LT 140827 Black & Decker ET 222 Philips HD 2637/90 b. OEM COC/ authorized dealer certificate/ mill test certificate (MTC): Not required <u>GENERAL SPECIFICATION</u> - a. Make/ Model / Brand/ Equivalent be endorsed: Panasonic/ Dawlance/ West point a. Make/ Model of item Moulinex LT 140827 Black & Decker ET 222 Philips HD 2637/90 b. OEM COC/ authorized dealer certificate/ mill test certificate (MTC): Not required	
3	DGE96030	BS 419/156	0559546005362 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN		40 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH 50.0 MTR									
4	DGE98592		0413546003650 / PVC PIPE DIA 1.50"		3500 / METER						TECHNICAL SPECIFICATION - Size: DIA 1.50"GENERAL SPECIFICATION - Size: DIA 1.50"	
5	DGB75230	NO DATA AVAILABLE	5120731000593 / WRENCH PIPE CHAIN CAPICTY 6INCH		6 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
6	DGE102301	NO DATA AVAILABLE	0559780000187 / SLEEVE PLASTIC DIA 0.5CM		5 / ROLL	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S.NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black GENERAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S, NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black	
7	DGE98069		8305PK5124167 / FABRIC CURTAIN WITH FITTING (MOAWIN A&A)	SENIOR OFFICER CABIN	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
8	DGD99083	NO DATA AVAILABLE	0031500000054 / DISH FLAT RICE 33cm GOLDEN CRESTED (AS PER STOCK SAMPLE)		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - GOLDEN CRESTED ,MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) make/brand cera-e- noor material procelain size 12" (30cm) golden crested with pn logo (same standardised item is already	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											issue to various pn unit ref haibat/03/7762412 GENERAL SPECIFICATION - GOLDEN CRESTED ,MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) make/brand cera-e- noor material procelain size 12" (30cm) golden crested with pn logo (same standardised item is already issue to various pn unit ref haibat/03/7762412	
9	DGE100 235	NO DATA AVAILABL E	830570512795 0 / RUBBER FABRIC (PVC COATED) CLOTH IN SHIP SIDE GREY COLOUR	FOR PNS SHIFA	290 / METER						TECHNICAL SPECIFICATION - 1. APPLICATION= COVERAGE FOR SHIPS, ETC 2. TOTAL WEIGHT (DIN EN ISO 2286-2)= 500 g/m2 3. SUPPORT CLOTH (DIN 6000)= POLYESTER 4. TYPE OF COATING = PVC COATED ON BOTH SIDES 5. YARN (DIN EN ISO 2060)= 1000 X 1000D 6. SPECIFICATION (DIN EN 1049-2)= 18 X 18 PER INCH (PLAIN WEAVE) 7. DIMENSION (DIN EN ISO 2286-1)= WIDTH: 01 METER & ROLL 50 METER 8. TENSILE STRENGTH (DIN 53354)= 2500/2400 N/ 5CM 9. TEAR STRENGTH (DIN 53363)= 270/250 N 10. ADHESION STRENGTH (DIN 53357)= 100 N /5CM 11. TEMPERATURE RESISTANCE= -30 C° TO +70 C° 12. FEATURE= HIGH TENACITY POLYESTER YARN ENSURES SUPERIOR DURABILITY UV PROTECTION TREATED 13. PACKING= CRAFT PAPER OR PE 14. RUBBER FABRIC BASE MATERIAL= POLYESTER, 15. CHEMICAL RESISTANCE= 98% SULFURIC ACID, 38% HYDROCHLORIC ACID AND 40% SODIUM HYDROXIDE, 16. ABRASION RESISTANCE= >1000 ZYKLEN, 17. WATER RESISTANCE= >0.8 BAR, 18. COATING THICKNESS= 0.5 MM, 19. FLAME RETARDANCY AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CERTIFICATION= M2GENERAL SPECIFICATION - 1. APPLICATION= COVERAGE FOR SHIPS, ETC 2. TOTAL WEIGHT (DIN EN ISO 2286-2)= 500 g/m2 3. SUPPORT CLOTH (DIN 6000)= POLYESTER 4. TYPE OF COATING = PVC COATED ON BOTH SIDES 5. YARN (DIN EN ISO 2060)= 1000 X 1000D 6. SPECIFICATION (DIN EN 1049-2)= 18 X 18 PER INCH (PLAIN WEAVE) 7. DIMENSION (DIN EN ISO 2286-1)= WIDTH: 01 METER & ROLL 50 METER 8. TENSILE STRENGTH (DIN 53354)= 2500/2400 N/ 5CM 9. TEAR STRENGTH (DIN 53363)= 270/250 N 10. ADHESION STRENGTH (DIN 53357)= 100 N /5CM 11. TEMPERATURE RESISTANCE= -30 C° TO +70 C° 12. FEATURE= HIGH TENACITY POLYESTER YARN ENSURES SUPERIOR DURABILITY UV PROTECTION TREATED 13. PACKING= CRAFT PAPER OR PE 14. RUBBER FABRIC BASE MATERIAL= POLYESTER, 15. CHEMICAL RESISTANCE= 98% SULFURIC ACID, 38% HYDROCHLORIC ACID AND 40% SODIUM HYDROXIDE, 16. ABRASION RESISTANCE= >1000 ZYKLEN, 17. WATER RESISTANCE= >0.8 BAR, 18. COATING THICKNESS= 0.5 MM, 19. FLAME RETARDANCY AND CERTIFICATION= M2	
10	DGD91531	NO DATA AVAILAB LE	0032500000134 / FORK TABLE SMALL		25 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - PN Crest Stainless Steel Grade SS 316 (Food Grade)GENERAL SPECIFICATION - PN Crest Stainless Steel Grade SS 316 (Food Grade)	
11	DGD97402	NO DATA AVAILAB LE	0032500000138 / KNIFE	RADAR 1006	20 / EACH/N	LOCAL					TECHNICAL SPECIFICATION - Material Stainless steel non magnetic	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	BUTTER PN CRESTED (AS PER STOCK SAMPLE)		UMBER						& non reactive, food grade stainless stell (AS PER STOCK SAMPLE) <u>GENERAL SPECIFICATION -</u> Material Stainless steel non magnetic & non reactive, food grade stainless stell (AS PER STOCK SAMPLE)	
12	DGT103314	NO DATA AVAILAB E	0100500000043 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		28 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) <u>GENERAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
13	DGE101548		0476546004776 / BRUSH SABLE HAIR NO-3 FOR WRITING		20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
14	DGE96241	1900gsr-2usb	7025015913120 / honey well 1900 bar code scanner		2 / EACH/N UMBER	xeon 1900					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
15	DGE79864	havana	7110705247541 / master havana high back chair		3 / EACH/N UMBER	NIL					<u>TECHNICAL SPECIFICATION -</u> BACK: 24" ARM: 27 SEAT: 21.5" HEIGHT: 20" BACK HEIGHT: 47" A. CHROME BASE B. CHROME ARMS <u>GENERAL SPECIFICATION -</u> BACK: 24" ARM: 27 SEAT: 21.5" HEIGHT: 20" BACK HEIGHT: 47" A. CHROME BASE B. CHROME ARMS	
16	DGH100192		3990705331163 / MULTI-PURPOSE TROLLEY		4 / EACH/N UMBER	N/A					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
17	DGE85935	FEC 1735511	6532705172593 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	10 / EACH/N UMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4	GERMAN Y		<u>TECHNICAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% ($\pm$ 1%) COTTON + 3% ($\pm$ 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
18	DGE869 37	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	10 / EACH/N UMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4	GERMAN Y		<u>TECHNICAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% ($\pm$ 1%) COTTON + 3% ($\pm$ 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% ($\pm$ 1%) COTTON + 3% ($\pm$ 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
19	DGE958 34	NIL	651570518127 7 / TOWEL PAPER 24 ROLLS PER PACK	NIL	29 / CARTO N			LOCAL MARKET	NOT KNOWN		<u>TECHNICAL SPECIFICATION - No</u> of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 Inch <u>GENERAL SPECIFICATION -</u> No of Ply 02 , Color White, Length of Roll 25Mtr Width of Roll 08 Inch	
20	DGE997 09	GGG-H- 142	841500935190 6 / SAFETY	PERSONAL PROTECTION	30 / EACH/N			FEDERAL SPECIFICATIONS UNITED	FEDERAL SPECIFIC		<u>TECHNICAL SPECIFICATION -</u> GARMENT SIZE 6-3/4 TO 7-1/2;	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HELMET YELLOW		UMBER			STATES CAGE CODE 81348	ACTIONS		ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000 <u>GENERAL SPECIFICATION - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000</u>	
21	DGT103450	NO DATA AVAILABLE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB TO 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	14 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		<u>TECHNICAL SPECIFICATION - SIZE</u> Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB <u>GENERAL SPECIFICATION - SIZE</u> Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	
22	DGE101026	SNR29 DB	6525TY5202565 / 3M PRE MOULDED EARPLUGS ULTRA FIT WITH NATURAL COTTON CORD	BV	30 / EACH/NUMBER	NA		VHKMHMN			<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
23	DGE98101	0413/8568	0413599243503 / FIBER SHEET, VULCANISED, LG,54"WD,42" THICKNESS 0.031"	FOR AIR COMPRESSOR	50 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
24	DGE72202	NO DATA AVAILAB E	047654600595 5 / GLOVES LEATHER		50 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Item: Gloves LEather Materail : PVC Coated size: free make: china cuff length: 1-5 inch <u>GENERAL</u> SPECIFICATION - Item: Gloves LEather Materail : PVC Coated size: free make: china cuff length: 1-5 inch	
25	DGE101380	319- SIVLER- DE	047659000003 1 / BRUSH. STEEL WIRE SURFACE CLEANING SMALL		40 / EACH/N UMBER	319- SILVER- DE					<u>TECHNICAL SPECIFICATION - 1.</u> ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN BO7RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle, Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement <u>GENERAL</u> SPECIFICATION - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE : 06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN BO7RP9X98J 6. ITEM WEIGHT: 4.9 OUNCES 7.PRODUCT DIMENSION: L-200mm, W-25mm, T-8mm, Brush Dimension: L-78mm x W-22mm x 15mm 8. MODEL: Wooden handle, Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement	
26	DGE97671		047659000006 2 / GLOVES LEATHER LEFT HAND.		55 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable <u>GENERAL SPECIFICATION</u> - Size: Large a. Material leather b. Color Natural c. Good fit wing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
27	DGE98094	NIL	0559794444901 / SLEEVING GLASS INSULATION CERAMIC VARNISHED GLASS FIBRE 6MM	GENERAL ELECTIC USE	50 / METER						TECHNICAL SPECIFICATION - BS 2848 (5970994444901)GENERAL SPECIFICATION - BS 2848 (5970994444901)	
28	DGE100561		0414599230911 / PACKING MATERIAL HEMP FOR FURNACE FUEL, SIZE= 1/4" SQ		50 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DGE95817	BRUSH LEG 4.375"	0476599430411 / BRUSH PAINT SQUARE EDGE ONE KNOT GROUND WD. 2.500" TH. 0.625"		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
30	DGE80351	C-268	0476599430559 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		126 / EACH/NUMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
31	DGB101743	BS2874, CZ112M	0283595711429 / ROD NAVAL BRASS HEX SIZE ACROSS FLATS 0.71" WT PER FT1. 630 LB	SERVICE PUMP	6 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
32	DGB99576	NO DATA AVAILABLE	0283700001641 / SILVER SOLDER EASYFLO FOR STAINLESS STEEL IN ROD FORM		2700 / GRAM						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
33	DGB97045		028350283152 1 / CADMIUM ANODE ROLLED LG 12 INCH WTH 8 INCH TH 3/8 INCH		7.25 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH GENERAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH	
34	DGB96259	NO DATA AVAILABLE	027770000347 7 / SPANNER OPEN JAW ADJ 0.50" X 0.57"		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - Brand: Bahco Overall Length: 257 mm Wrench type: Adjustable Spanner Jaw Capacity: 33 mm Handle Type : Plastic/ Steel Material: Alloy Steel GENERAL SPECIFICATION - Brand: Bahco Overall Length: 257 mm Wrench type: Adjustable Spanner Jaw Capacity: 33 mm Handle Type : Plastic/ Steel Material: Alloy Steel	
35	DGB97873		028359571145 9 / ROD NAVAL BRASS RD DIA.2.50 INCH WT PER MTR 27.49 KG		0.6 / METER						TECHNICAL SPECIFICATION - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU ZN 39 SN GENERAL SPECIFICATION - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU ZN 39 SN	
36	DGB74774		028359571147 4 / SHEET- NAVAL- BRASS- ANNEALED 48		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340 GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
37	DGE99928	NO DATA AVAILABLE	041559923141 0 / SHEET PLASTIC TRASPARENT LG.48 WD 36TH 0.125 MATERIAL METHYL		4 / SHEET						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			METHACRYLATE PLAIN REF DTD 5592									
38	DGE99051		0415599231412 / SHEET PLASTIC METHYL METHACRYLATE PLAIN TRANSPARENT L X W X THIC 48"X48"X0.250"		12 / SHEET						TECHNICAL SPECIFICATION - Manfr/Tech. Sponcer Code reference: DTD 5592 GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference: DTD 5592	
39	DGT103449	NO DATA AVAILABLE	0100501000118 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE		320 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by one of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT, THICKNESS =12MM(±1MM) DENSITY= 700 TO 850 KILOGRAMS PER CUBIC METER. GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by one of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT, THICKNESS =12MM(±1MM) DENSITY= 700 TO 850 KILOGRAMS PER CUBIC METER.	
40	DGT102879	NO DATA AVAILABLE	0100501000118 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED		416 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by one of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT, THICKNESS =12MM(±1MM) DENSITY= 700 TO 850 KILOGRAMS PER CUBIC METER. GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WITH PRESERVATIVE								one of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM) DENSITY= 700 TO 850 KILOGRAMS PER CUBIC METER.	
41	DGB96385		021259923280 2 / BAR STEEL CORROSION RESISTING H/R RD 1.25" WT PER FT 4.209LBS		4 / METER						TECHNICAL SPECIFICATION - minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D) GENERAL SPECIFICATION - minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D)	
42	DGB96817	BS 1421	027570910547 4 / PICK HEAD DIGGING TYPE CHISEL AND POINT 07LBS EYE 3" X3"		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
43	DGB83874	BS 1421	027570910547 4 / PICK HEAD DIGGING TYPE CHISEL AND POINT 07LBS EYE 3" X3"		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DGH101783	DNC S15	021159119996 8 / STEEL PLATE CARBON SIZE 2500X1250X6 MM. **SIZE 2500X1220X6 MM (Only acceptable against demand based LPO).		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025.STEEL GRADE:5275 JR. ALL INFORMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr GENERAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025. STEEL GRADE:5275 JR. ALL INFORMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
45	SGB92807	9104923 (5110-99-910-4923)	0274709104923 / FILE ENGINEER ROUND D-CUT BASTARD LG 6.00IN DIA 6MM.		110 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DGB97389	BS949, 1G579 (5136-99-122-7414)	0271701227414 / TAP THREAD CUTTING I.S.O P/S12.00X01.75X29.00X07.50X89.00MM		72 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DGE98926		0330595713262 / TWINE NYLON ROPING 3 STRD NATURAL FINISH MIN BKG STRGT 50 LB		30 / KILOGRAMME						TECHNICAL SPECIFICATION - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed. GENERAL SPECIFICATION - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed.	
48	DGB104647		0214790130808 / BOLT, MACHINE, THREAD SERIES: BSF, HEX HD	BR 320 D/78	70 / TEN						TECHNICAL SPECIFICATION - THREAD SIZE: 1/2 INCH. NOMINAL LENGTH: 2 INCH. LENGTH OF THREAD: 1 INCH. MATERIAL SPECS PD970:2005 MATERIAL GRADE EN16(605 M36) or EN100 (945 M38), HEAT TREATMENT CONDITION: R as per BR-320D (Catalog of Naval Stores) OEM COC/MTC REQUIRED GENERAL SPECIFICATION - THREAD SIZE: 1/2 INCH. NOMINAL LENGTH: 2 INCH. LENGTH OF THREAD: 1 INCH. MATERIAL SPECS PD970:2005 MATERIAL GRADE EN16(605 M36) or EN100 (945 M38), HEAT TREATMENT CONDITION: R as per	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BR-320D (Catalog of Naval Stores) OEM COC/MTC REQUIRED	
49	DGB74679	SPEC-BS 2558 GRADE A	027779000243 8 / SPANNER BOX DOUBLE ENDED BA 09X10 LG 04" DRILLED BOR DIA 1/8"		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
50	SGB97119	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	25 / KILOGR AMME						TECHNICAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface GENERAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
51	DGB70955	NO DATA AVAILABL E	026559423325 5 / PAD-LOCK- BRASS-1.50 INCH WITH 02 KEYS		40 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
52	DGB74593		027179910198 1 / TAP THREAD CUTTING CS BSW B/S16. 0TPI0.375X1. 250X0.294X2. 937"		6 / EACH/N UMBER						TECHNICAL SPECIFICATION - thread type; iso metric thread m type material grade: (single) SIGH SPEED STEEL(HSS-M2 GRADE) THREAD LENGTH: 18 MM SHANK LENGTH: 50 MM THREAD ANGLE: 600 MAJOR DIAMETER: 10 MM+0.1 MM PITCH DIAMETER: AS PER DEFIN ISO STANDARD THREAD PITCH: 1.5 MM+ 0.05 MM MATERIAL IS TO BE HEAT TREATED TO ACHIEVE HARDNESS LEVEL OF 62-64 HRC. GENERAL SPECIFICATION - thread type; iso metric thread m type material grade: (single) SIGH SPEED STEEL(HSS-M2 GRADE) THREAD LENGTH: 18 MM SHANK LENGTH: 50 MM THREAD ANGLE: 600	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MAJOR DIAMETER: 10 MM+0.1 MM PITCH DIAMETER: AS PER DEFIN ISO STANDARD THREAD PITCH: 1.5 MM+ 0.05 MM MATERIAL IS TO BE HEAT TREATED TO ACHIEVE HARDNESS LEVEL OF 62-64 HRC.	
53	DGB63614	NO DATA AVAILABLE	024859129614 9 / STEEL SAFE FITTED WITH COMBINATION LOCK	NAL DIMENSIONS: 23-1/2	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Complete Item/ Store DESCRIPTION: Steel Safe fitted with Combination LOCK b. Gauge : Outer 16 SWG Inner 16 SWG c. Size/ dimension: Length/ Height 22 Inch Width 20 Inch Depth 18 Inch d. Door: Single e. No. of shelves: 02 f. No. of Levers: 01 g. Lock Type: Combination + Key/ Digital Lock h. Fire Retardant: Yes GENERAL SPECIFICATION - a. Complete Item/ Store DESCRIPTION: Steel Safe fitted with Combination LOCK b. Gauge : Outer 16 SWG Inner 16 SWG c. Size/ dimension: Length/ Height 22 Inch Width 20 Inch Depth 18 Inch d. Door: Single e. No. of shelves: 02 f. No. of Levers: 01 g. Lock Type: Combination + Key/ Digital Lock h. Fire Retardant: Yes	
54	DGB88581	AMARICAN(OR UNIFIND) NUMBER	026659000300 8 / WASHER FLAT ROUND BRASS 3 BA 0.177X0. 341X0.028IN	SPEC=BS 3410 MATERIAL BRASS	104 / TEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DGE100432	NO DATA AVAILABLE	033054600448 4 / HEAVING LINE 06MM L50MM 466MS	MSI	660 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DGB100106		132572335001 0 / BLADE POWER HACK SAW HSS 18X1-1/2X0. 075" 6TPI		5 / EACH/N UMBER	AISI M2 HSS (Super Hardened)					TECHNICAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 1/2 x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened) GENERAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 1/2 x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
57	DGE72173	0472-99-425-8913	0472UK511799 8 / HYDROSTATIC RELEASE		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DGB73861		513370504927 1 / DRILL BITS SETS 29 PCS	COMMON TOOLS GYRO REPAIR FACILITY JAPAN	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DGB72886		512073100058 5 / SPANNER RING DOUBLE END 6-TO-22MM 8 PIECES SET		14 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DGE99002		533000618322 1 / PACKING MATERIAL SIZE 3/16".		10 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DGE99264	MIL-P-15280	564000237482 7 / INSULATION SLEEVING THERMAL		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
62	DGE101725	MIL-P-15280	564000237482 7 / INSULATION SLEEVING THERMAL		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. <u>GENERAL SPECIFICATION</u> - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
63	DGE96024	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		13 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes <u>GENERAL SPECIFICATION</u> - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
64	DGD90076	NO DATA AVAILABL E	773070504806 6 / BOAT SAUCE 06 OZ GOLDEN CRESTED		70 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - 06 OZ GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) <u>GENERAL SPECIFICATION</u> - 06 OZ GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA- E-NOOR (LOCAL)	
65	DGE102349	NO DATA AVAILABL E	041350000013 3 / EAR DEFENDER		200 / PAIR	PELTOR H10A/ OPTIME 105					<u>TECHNICAL SPECIFICATION</u> - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model : pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip) <u>GENERAL SPECIFICATION</u> - accaptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB.	
66	DGD97234		7730705048058 / PLATE SOUP 9INCH GOLDEN CRESTED		100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) <u>GENERAL SPECIFICATION</u> - 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
67	DGE99743	DATA AVAILAB E	0461500000152 / POLISHING-FELT ROUND		4 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch <u>GENERAL SPECIFICATION</u> - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch	
68	DGE990	NO DATA	045150000009		40 /	NO DATA					<u>TECHNICAL SPECIFICATION</u> - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	58	AVAILABLE	3 / CLOTH VALVET COLOUR RED WIDTH 40 INCH		METER	AVAILABLE					DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
69	DGE96647	NO DATA AVAILABLE	031050000000 6 / CANVAS COTTON NATURAL GREY (WD: 36 INCH)		150 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION: 1. FEATURES: WATER PROOF AND ROT PROOF 2. WIDTH & LENGTH: 36" AND 50 METER ROLL 3. WEIGHT: 12 OZ PER SQ. YARD 4. COLOUR: NATURAL GREY GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY. GENERAL SPECIFICATION - SPECIFICATION: 1. FEATURES: WATER PROOF AND ROT PROOF 2. WIDTH & LENGTH: 36" AND 50 METER ROLL 3. WEIGHT: 12 OZ PER SQ. YARD 4. COLOUR: NATURAL GREY GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY.	
70	DGE72220	32B1296	813599220336 3 / TUBING PLASTIC POLYETHYLENE TYPE -1 LAY FLAT WD. 36 THICKNESS 0.010 INCH		707 / KILOGRAMME						TECHNICAL SPECIFICATION - AS AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll(no need of packing) locally available GENERAL SPECIFICATION - AS AS PER BR-320D LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2.DEF STAN 93-116 ISSUE 2 OF 2007 normal roll (no need of packing) locally available	
71	DGE102760	R	834570504262 9 / Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter)	ITEM REQUIRED FOR MAKING OF GIFT BOXES	100 / METER						TECHNICAL SPECIFICATION - Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes	
72	DGT101751	NO DATA AVAILABLE	010050000002 8 / PLY WOOD MARINE ALL SHESHAM DURABILITY REQUIRED STANDARD GD-I, (CORE, INNER AND OUTER PLIES OF SHESHAM WOOD) 5-PLY	2.440X1.220MTRX6.35MM) SPECE/BS-1088	520 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. SIZE= A. LENGTH: 8- FEET B. WIDTH: 4- FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM, GENERAL SPECIFICATION - 1. SIZE= A. LENGTH: 8- FEET B. WIDTH: 4- FEET, C. THICKNESS = 06 MM (± 0.50 MM), 2. TYPE OF BOND WBP CLASS III TREATED WITH PRESERVATIVE AS PER SPECS BS EN 314-2. 3. BS 1088 PART-I & II, 4. DENSITY OF TIMBER (SHESHAM)= 700-850 KG/M³. 5. PLYWOOD SHOULD BE MANUFACTURED FROM 100% SHESHAM, 6. SHESHAM VENIER BOTH SIDES THICKNESS= 0.70 MM,	
73	DGE97431	NO DATA AVAILABLE	045150000002 1 / CLOTH TICKEN BLUE STRIPS WIDTH 58 INCHES		1621 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. WIDTH:58 INCH(1,473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT;40 d.COUNT OF YARN WARP;2/206 WEFT2/206 e. SHRINKAGE- WARP; 2%(MAX) WEFT;2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS) GENERAL SPECIFICATION - a. WIDTH:58 INCH(1,473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT;40	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											d.COUNT OF YARN WARP;2/206 WEFT2/206 e. SHRINKAGE- WARP; 2%(MAX) WEFT;2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS)	
74	DGE72198	E-AE10000	0476500000068 / LEATHER CHROAME BLACK 24X24X1/16 INCH		56 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SIZE:24X24X1/16 INCH NATO Code: F3013 GENERAL SPECIFICATION - SIZE:24X24X1/16 INCH NATO Code: F3013	
75	DGT103219	BELFONT TRUWOOD TEAK	9330992246097 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		77 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
76	DGT99579	BELFONT TRUWOOD TEAK	9330992246097 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		5 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
77	DGT101832	BELFONT TRUWOOD TEAK	9330992246097 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK WOOD) (GRADE		12 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DESIGNATION (STAN)									
78	DGE100660	GGGH142	841500935313 7 / HELMET SAFTY		35 / EACH/N UMBER						TECHNICAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 broucher attached as document GENERAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 broucher attached as document	
79	DGE101443	60-501-001	615076502401 1 / TIE WRPA (CABLE TIE) P/N 60-501-001	GRADIOMETE R SYSTEM	360 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held GENERAL SPECIFICATION - a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held	
80	DGE101630		721070503053 7 / WATER COOLER PLASTIC 5 LTR (BRAND REHBAR/INDU STRY/JOY	WATER CONTAINER	50 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
81	DGE103445	N/A	933070518127 9 / PLASTIC SHEET	GENERAL ITEM	20 / ROLL			LOCAL MARKET		GENERA L ITEM	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
82	DGT103048	NO DATA AVAILABL E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE:	WOOD WORKS SHIPS&ESTAB LISHMENT	24 / SHEET	NO DATA AVAILAB LE		PK		SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ	TECHNICAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM GENERAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			L=8' W=4' TH=16MM						WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.			
83	DGT103 238	NO DATA AVAILAB E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTABLISHMENT	17 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		<u>TECHNICAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM <u>GENERAL SPECIFICATION -</u> BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	
84	DGB102 092		026759521328 5 / Piping Steel Galv 3050x4. 0x0.250		40 / METER						<u>TECHNICAL SPECIFICATION - BS 3602</u> , Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable. <u>GENERAL SPECIFICATION - BS 3602</u> , Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable.	
85	DGT101982	NO DATA AVAILABLE	0100501000118 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE		320 / SQ FEET						<u>TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by onE of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM) DENSITY= 700 TO 850 KILOGRAMS PER CUBIC METER.</u> <u>GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by onE of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM) DENSITY= 700 TO 850 KILOGRAMS PER CUBIC METER.</u>	
86	DGE105162	NIL	0350599237135 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHOM						<u>TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
87	DGB97386	(SIM)	0257709411504 / NUT-PLAIN-HEXAGON (BRASS) THREAD UNF SZ .375"LH . 350"		32 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
88	DGB74584		5136705010561 / TAP SET MACHINE SIZE 10X1.50 MM		5 / SET						<u>TECHNICAL SPECIFICATION</u> - Thread Size : M10 Thread Pitch : 1.5 mm Material : HSS Total Length : 70 mm OEM : Besly, OSG, Emuge, Balx, Guhring, Sandvik Acceptance Criteria: Physical inspection by concerned workshop rep. <u>GENERAL SPECIFICATION</u> - Thread Size : M10 Thread Pitch : 1.5mm Material : HSS Total Length : 70 mm OEM : Besly, OSG, Emuge, Balx, Guhring,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Sandvik Acceptance Criteria: Physical inspection by concerned workshop rep.	
89	DGE989 13	MIL-P- 15280	564000237482 7 / INSULATION SLEEVING THERMAL		105 / EACH/N UMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
90	DGD105 814	MS-3443-A/DW-136G	731070512190 4 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	3 / EACH/N UMBER	DW-136G					TECHNICAL SPECIFICATION - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI GENERAL SPECIFICATION - brand name: (i.e. WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLOW # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI	
91	DGT101 975	NO DATA AVAILAB LE	010000000000 3 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	217 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DGT967 76	BS 1088 & BS 6566 OF 1985	010054600144 3 / PLYWOOD 7PLY GDII SIZE		20 / SQ FEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			8X4FTX1/2INCH TYPE GRADE (INT)									
93	DGD105890	JE-01	732070526966 4 / STAINLESS STEEL JUICE EXTRACTOR		1 / EACH/NUMBER	UDZZ-A2000					TECHNICAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201 <u>GENERAL SPECIFICATION</u> - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201	
94	DGD105861	JE-01	732070526966 4 / STAINLESS STEEL JUICE EXTRACTOR		1 / EACH/NUMBER	UDZZ-A2000					TECHNICAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201 <u>GENERAL SPECIFICATION</u> - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201	
95	DGT105370	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	9 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
96	DGB105033	PN16DN100	024154600193 4 / GATE VALVE 1.5" PRESSURE 100PSI		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Gate Valve (Non-Rising Stem) with indicator, Flanged, 1.5", Pressure 100 PSI Testing/ Acceptance Criteria: Relevant ISO standards for sea water valves connection type: flange flange Standard: din 3202-f4 working	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											temperature: +180 c body material: g-cusn5znpb <u>GENERAL SPECIFICATION</u> - Gate Valve (Non-Rising Stem) with indicator, Flanged, 1.5", Pressure 100 PSI Testing/Acceptance Criteria: Relevant ISO standards for sea water valves connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb	
97	DGT99349	NO DATA AVAILABLE	934070514992 3 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB to 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	4 / SHEET	NO DATA AVAILABLE		PK		SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETANI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.	<u>TECHNICAL SPECIFICATION</u> - SIZE Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB <u>GENERAL SPECIFICATION</u> - SIZE Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	
98	DGT97893		934070514992 4 / MEDIUM DENSITY FIBER BOARD, (LASANI) WHITE COLOUR LAMINATION ONE SIDE DENSITY 750 KG cUB	WOOD WORKS SHIPS&ESTABLISHMENT	15 / SHEET	NO DATA AVAILABLE		PK		SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETANI HOUSE, SIDDIQ WAHAB	<u>TECHNICAL SPECIFICATION</u> - SIZE: Length: 8 feet Width: 4 feet Thickness: 3 MM colour: white SOURCE:M/S MEHRAN ART WOOD SHOP NO 9,PANJETANI HOUSE,SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI. TEL/ FAX: +92-21-32776064.MOBILE 0322- 2578654. PRICE:RS1350 APPOX PER SHEET,SIZE 8FEETX4FEETX1/8 INCHES.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			METER SIZE L:8' W: 4' TH: 3MM MOISTURE RESISTANT						ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92- 21- 32776064 .MOBILE 0322- 2578654.		GENERAL SPECIFICATION - SIZE: Length: 8 feet Width: 4 feet Thickness: 3 MM colour: white SOURCE:M/S MEHRAN ART WOOD SHOP NO 9,PANJETANI HOUSE,SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI. TEL/ FAX: +92-21-32776064.MOBILE 0322- 2578654. PRICE:RS1350 APPOX PER SHEET,SIZE 8FEETX4FEETX1/8 INCHES.	
99	DGB105 047	DEVS7866	473099525334 8 / FLANGE	-	3 / EACH/N UMBER	NO DATA AVAILAB LE		UK	MOD (NAVY) SHIP SUPPOR T AGENCY DME MC253 ROOM 19 BLOCK B FRAHILL BATH UK		TECHNICAL SPECIFICATION - BS 1400 Inner dia: 1 1/2 inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: 1/2 inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing GENERAL SPECIFICATION _BS 1400 Inner dia: 1 1/2 inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: 1/2 inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing	
100	DGH106 316	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	23 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MMGENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
101	DGH106 337	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	23 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MMGENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
102	DGH104 859	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	23 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MMGENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
103	DGE98303		4920725176054 / REGULATOR WITH OCTOPUS (COMPLETE SET)	DIVING	2 / EACH/NUMBER	PSS DIVE		GERMANY	GERMANY		<u>TECHNICAL SPECIFICATION - MAKE/ BRAND: AQUA LUNG (FRANCE/ TAIWAN/MEXICO) DETAILS OF COMPLETE SET: (A) AQUALUNG CALYPSO REGULATOR (PART NO 706006/ RG126113), (B) AQUALUNG CALYPSO OCTOPUS (PART NO 706032/ RS137111), (C) AQUALUNG ELEMENTS PG300BAR + DEPTH (PART NO 704003/ NS 114118), (D) AQUALUNG LP INFLATOR HOSE (PART NO BC911133) GENERAL SPECIFICATION - MAKE/ BRAND: AQUA LUNG (FRANCE/ TAIWAN/MEXICO) DETAILS OF COMPLETE SET: (A) AQUALUNG CALYPSO REGULATOR (PART NO 706006/ RG126113), (B) AQUALUNG CALYPSO OCTOPUS (PART NO 706032/ RS137111), (C) AQUALUNG ELEMENTS PG300BAR + DEPTH (PART NO 704003/ NS 114118), (D) AQUALUNG LP INFLATOR HOSE (PART NO BC911133)</u>	
104	DGE97151	NIL	0559794444901 / SLEEVING GLASS INSULATION CERAMIC VARNISHED GLASS FIBRE 6MM	GENERAL ELECTRIC USE	35 / METER						<u>TECHNICAL SPECIFICATION - BS 2848 (5970994444901)GENERAL SPECIFICATION - BS 2848 (5970994444901)</u>	
105	DGE100169	NIL	0559794444901 / SLEEVING GLASS INSULATION CERAMIC VARNISHED GLASS FIBRE 6MM	GENERAL ELECTRIC USE	50 / METER						<u>TECHNICAL SPECIFICATION - BS 2848 (5970994444901)GENERAL SPECIFICATION - BS 2848 (5970994444901)</u>	
106	DGE101449	NO DATA AVAILABLE	0559790020552 /	GENERAL ELECTRIC	35 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	USE							<u>SPECIFICATION - NO DATA AVAILABLE</u>	
107	DGB102 586		028359571143 2 / ROD NAVAL BRASS HEX A/F 1.01" WT PER FT 3.244 LB, (RUNNING LENGTH: MINIMUM 6 FT)	SERVICE PUMP	5 / METER						<u>TECHNICAL SPECIFICATION - BSEN 12163 OF 2016 GRADE CW 712 (R) M RUNNING LENGTH: minimum 6 ft</u> <u>GENERAL SPECIFICATION - BSEN 12163 OF 2016 GRADE CW 712 (R) M RUNNING LENGTH: minimum 6 ft</u>	
108	DGB102 631		028359571143 8 / ROD NAVAL BRASS HEX SIZE A/F 1.86 INCH	GENERAL PURPOSE (FOR SHIPS)	5 / METER						<u>TECHNICAL SPECIFICATION - BSEN 12163 OF 1998 GRADE CW 712 R(M)</u> <u>GENERAL SPECIFICATION - BSEN 12163 OF 1998 GRADE CW 712 R(M)</u>	
109	DGB106 263	NO DATA AVAILABLE	028359571115 5 / SHEET ALUMINIUM ALLOY ANNEALED		7 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN:573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).</u> <u>GENERAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN: 573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).</u>	
110	DGB106 220	NO DATA AVAILABLE	028359571115 5 / SHEET ALUMINIUM ALLOY ANNEALED		9 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN:573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF.ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN: 573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).	
111	DGB106097	NO DATA AVAILABL E	028359571115 5 / SHEET ALUMINIUM ALLOY ANNEALED		9 / EACH/N UMBER						TECHNICAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN:573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).GENERAL SPECIFICATION - SIZE LG 96" WD 48" TH 0.064" AS PER BR 320-D TABLE NO 98. BSEN: 485-2 OF 2016 (MECH PROPERTIES) MATERIAL CONDITION "O" & EN: 573-3 OF 2007 (CHEMICAL COMPOSITION), GRADE (EN-AW-5251).	
112	DGB96364		028359571145 7 / ROD NAVAL BRASS RD DIA 2.25" WT PER FT 14.73(LB)		6.35 / METER						TECHNICAL SPECIFICATION - Specifications: BSEN 12163 of 1998 Grade CW 712R (M), Running Length (Min): 02 meterGENERAL SPECIFICATION - Specifications: BSEN 12163 of 1998 Grade CW 712R (M), Running Length (Min): 02 meter	
113	DGE101662	0414-5160	041459923093 4 / SHEET, ASBESTOS, COMPRESSE D TH 1/16", WD 54"X63" IN WT PER SHEET 22LBS		3 / KILOGR AMME						TECHNICAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)GENERAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)	
114	DGE102831	0414-5162	041459923093 5 / ASBESTOS SHEET	GENERL PERPOSE	15 / KILOGR AMME						TECHNICAL SPECIFICATION - a. Standard/ Grade: BS 2815, Grade A b. Length = 60 Inch c. Width = 60-80	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COMPRESSE D,								INCH d. Thickness= 3-MM e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS-2815GENERAL SPECIFICATION - a. Standard/ Grade: BS 2815, Grade A b. Length = 60 Inch c. Width = 60-80 INCH d. Thickness= 3-MM e. Approx. Wt. per Sheet LBS. 44 F. COLOUR; RED, G. MATERIAL: ASBESTOS BS-2815	
115	DGE756 31	NO DATA AVAILABL E	045159910816 0 / TABLE-CLOTH- WOOLEN GREEN,100% WOOL,WIDTH 5FT-LETTER NO E- 1/4927/1496 DT 07 NOV 95		100 / YARD						TECHNICAL SPECIFICATION - em Specification TABLE CLOTH WOOLEN MATERIAL:100%WOOL- DIMENSIONS:WIDTH-5FT,LENGTH- AS PER WOS,COLOUR: GREEN , PRICE 300/-PER YARDGENERAL SPECIFICATION - em Specification TABLE CLOTH WOOLEN MATERIAL:100%WOOL- DIMENSIONS:WIDTH-5FT,LENGTH- AS PER WOS,COLOUR: GREEN , PRICE 300/-PER YARD	
116	DGE103 044	NIL	035059571323 1 / ROPE SISAL, HAWSERLAID, 3-STRD, CIRC: 1, 1/8 INCH DIA: 10-MM		1500 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
117	DGH103 531	DNC S15	021159119996 8 / STEEL PLATE CARBON SIZE 2500X1250X6 MM. **SIZE 2500X1220X6 MM (Only acceptable against demand based LPO).		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025. STEEL GRADE:5275 JR. ALL INFORMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr GENERAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025. STEEL GRADE:5275 JR. ALL INFORMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr	
118	DGB103 502		021859571185 7 / PIPING STEEL SEAMLESS OUTER DIA 219.710X8MM TH RAND LG4. 5-6.0M		18.3 / METER						TECHNICAL SPECIFICATION - 1. bs EN 10216-2 STEEL GRADE P 265 GH 2. INTERNAL DIA = 08 INCH cold finishing GENERAL SPECIFICATION - 1. bs EN 10216-2 STEEL GRADE P 265 GH 2. INTERNAL DIA = 08 INCH cold finishing	
119	DGB103 453		021859571185 7 / PIPING STEEL SEAMLESS OUTER DIA 219.710X8MM TH RAND LG4. 5-6.0M		18.3 / METER						TECHNICAL SPECIFICATION - 1. bs EN 10216-2 STEEL GRADE P 265 GH 2. INTERNAL DIA = 08 INCH cold finishing GENERAL SPECIFICATION - 1. bs EN 10216-2 STEEL GRADE P 265 GH 2. INTERNAL DIA = 08 INCH cold finishing	
120	DGE102 424	NIL	035059923713 5 / ROPE NYLON.	H 41.200 TONS UNIT OF AVAILABILITY	120 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	726							2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WORKING/ BREAKING STRENGTH OF STORES.	
121	DGB103 461		021259571002 7 / BAR STEEL CARBON HOT ROLLED RD DIA 3-1/2", WT PER FT 32.71 LBS		2 / METER						TECHNICAL SPECIFICATION - SPECS PD970:2005, Material Grade 070M20, Running Length: 6 meter GENERAL SPECIFICATION - SPECS PD970:2005, Material Grade 070M20, Running Length: 6 meter	
122	DGH103 955	BS EN 10025-2/2004, MATERIAL GRADE S 275 JR	021259571071 8 / ANGLE STEEL CARBON E/S BLACK 1.25 X 1.25 X 0.25 INCH		100 / METER						TECHNICAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, Material grade s 275 jr GENERAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, Material grade s 275 jr	
123	DGH103 964		021259571079 8 / Angle Steel Carbon Black 05X03-1/2X1/2" LG 40.3"		2 / METER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER FORECASTED QTY: 103 MTR MATERIAL TEST CERTIFICATE REQUIRED GENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER FORECASTED QTY: 103 MTR MATERIAL TEST CERTIFICATE REQUIRED	
124	DGH102 581	BSEN 10025 GRADE S275 JR	021259571072 3 / ANGLE STEEL CARBON BLACK 1-1/2X1-1/2X1/4"		10 / METER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED GENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED	
125	DGE103 540	C-134	085158000007 6 / DEFENCER EAR C-134 62TD		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
126	DGE106 369	NO DATA AVAILABLE	047659923891 9 / RUBBER SHEET (SIZE: L 2250 x W 2250 x THKNESS		200 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			12MM)									
127	DGE99286	81349, MIL-H-15217	472000203633 3 / HOSE RUBBER, NON-METTALIC, INTERNAL DIA 1", NO OF LAYERS= 4, (IMPREG. FAB), LENGTH= 50 FT		150 / FOOT						<u>TECHNICAL SPECIFICATION - tech specs:</u> Internal dia = 1 Inch, EQUILANT= 4-PLY, RUBBER TYPE/ FLEXIBLE, MINIMUM Working Pressure = 10 Bar, Maximum Working pressure = 30 Bar, Temp Range = -35 to 80 °C, Packing = Plastic Paper oem coc/DOCUMENTS /dealer cerificate= REQUIRED, PARENT EQUIP= CHIPPING MACHINE <u>GENERAL SPECIFICATION - tech specs:</u> Internal dia = 1 Inch, EQUILANT= 4-PLY, RUBBER TYPE/ FLEXIBLE, MINIMUM Working Pressure = 10 Bar, Maximum Working pressure = 30 Bar, Temp Range = -35 to 80 °C, Packing = Plastic Paper oem coc/DOCUMENTS /dealer cerificate= REQUIRED, PARENT EQUIP= CHIPPING MACHINE	
128	DGB104913	66694	451099761024 5 / MIXER SHOWER UNIT 1/2" DUPLEX MIX FITTING TOP OUTLEY FOR 15MM	INLETS CHROME PLATED(COLD &WARM WATER)	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
129	DGE101263	NO DATA AVAILABE	424050508870 5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
130	DGE102158	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
131	DGE102 862		422072501370 4 / O RING P/N R18694 SET OF 10		80 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
132	DGE101 130		402099923713 7 / ROPE NYLON HAWSERLAID, 3-STRND, Z- LAY, TYPE-1,	NOR-SHIPS- USE-NASAR	166.5 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			NOM DIA: 64-MM, CIRC: 08-INCH,								ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION -</u> 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
133	DGB104 956	ANT COUPLIN	472070505711	FOR FIRE FIGHTING	2 / EACH/N						TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		G-	2 / FIRE HOSE SIZE 2-1/2" X100 FEET DURLANE 500 LIGHT ALLOY INST-		UMBER						DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
134	DGE105 365	MIL-P-15280	564000237482 7 / INSULATION SLEEVING THERMAL		60 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. <u>GENERAL SPECIFICATION</u> - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
135	DGE105 364	MIL-P-15280	564000237482 8 / INSULATION SLEEVING THERMAL		60 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. <u>GENERAL SPECIFICATION</u> - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											UNICELLULAR PLASTIC FOAM.	
136	DGE106278	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		45 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
137	DGB98950	NO DATA AVAILAB LE	026350000127 6 / TURN BUCKLE HOOK & EYE		25 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Complete Dimensions: Length- 295 mm (11.61 Inches) Thread-12.7 mm (0.5 inch) Material grade: forged galvanized steel Testing/acceptance criteria: 1000lbs make, model, brand: Aashi Enterprises Suite # 48, 3rd, Floor Moosa Market / Shah rah Liaquat Karachi-74000. PH- +92-21- 32427508 +92-21-32465654 Fax- +92-21-32432083 E-mail: ashenterprises.gsel@gmail.co ma shienterprises@hotmail. com GENERAL SPECIFICATION - Complete Dimensions: Length- 295 mm (11.61 Inches) Thread-12.7 mm (0.5 inch) Material grade: forged galvanized steel Testing/acceptance criteria: 1000lbs make, model, brand: Aashi Enterprises Suite # 48, 3rd, Floor Moosa Market / Shah rah Liaquat Karachi-74000. PH- +92-21- 32427508 +92-21-32465654 Fax- +92-21-32432083 E-mail: ashenterprises.gsel@gmail.co ma shienterprises@hotmail.com	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
138	DGE106344	NO DATA AVAILABLE	0422500000033 / CARPET WOOLEN.		768 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm <u>GENERAL SPECIFICATION -</u> (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm	
139	DGE105363	NO DATA AVAILABLE	0432500000024 / HELMET PROTECTIVE WITH VISER COLOUR WHITE (HALF HEAD)		30 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Make: UK Brand / Company Name: JSP Safety <u>GENERAL SPECIFICATION -</u> Make: UK Brand / Company Name: JSP Safety	
140	DGT105346	NO DATA AVAILABLE	01005000000018 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFICATION.IM-2581 (E)	1088 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH: 8- FEET, WIDTH: 4 FEET, THICKNESS: 12 MM 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 9. DENSITY REQUIREMENT= 550-750 PER CUBIC METER, <u>GENERAL SPECIFICATION -</u> SIZE: LENGTH: 8- FEET, WIDTH: 4 FEET, THICKNESS: 12 MM 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
141	DGT102875	NO DATA AVAILABLE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	1440 / SQ FEET	NO DATA AVAILABLE					7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 9. DENSITY REQUIREMENT= 550-750 PER CUBIC METER,	
											<u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: Length= 8-FEET, Width=4-FEET & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.<u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: Length= 8-FEET, Width=4-FEET & Thickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
142	DGT106384	NO DATA AVAILABLE	0100500000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	800 / SQ FEET	NO DATA AVAILABLE					BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER. <u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											EN 323: 1993, MOISTURE: 6-14% DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
143	DGT103505	NO DATA AVAILABLE	0100500000015 / PLY WOOD GRADE-1, 5 PLY		672 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) <u>GENERAL SPECIFICATION</u> - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
144	DGT98652	NO DATA AVAILABLE	0100500000029 / Ply wood, Marine All Shesham, 13-Ply, GD-II, (WBP, Treated with Preservative) Size: L=8FT, W=4FT, TH=25MM, (Core inner plies & veneer) (Wood Should be all Shesham)		64 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER <u>GENERAL SPECIFICATION</u> - 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER	
145	DGT101	NO DATA	0100500000002		50 / SQ	NO DATA					<u>TECHNICAL SPECIFICATION -</u> 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	283	AVAILAB LE	9 / Ply wood, Marine All Shesham, 13-Ply, GD-II, (WBP, Treated with Preservative) Size: L=8FT, W=4FT, TH=25MM, (Core inner plies & veneer) (Wood Should be all Shesham)		FEET	AVAILAB LE					density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER <u>GENERAL SPECIFICATION</u> _ 1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER	
146	DGE106 346	10563	041370513921 3 / UPVC BAND 1 INCH	STANDBY ECHO SOUNDER	24 / EACH/N UMBER	NO DATA AVAILAB LE		PK	DIGI TECH, SHOP NO.2 NEW MEMON CHAMBERS, ALTAF HUSSAIN ROAD DENSO HALL KARACHI -74000. TEL:021-2639514		<u>TECHNICAL SPECIFICATION --</u> <u>GENERAL SPECIFICATION --</u>	
147	DGT102 876	NO DATA AVAILAB LE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		12 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) <u>GENERAL SPECIFICATION</u> _ SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
148	DGE105 421		711070504922 6 / STEEL	FOR MEDICAL-	2 / EACH/N						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CABINET SIZE AS PER DRAWING 7.6" X24"X18"	RECORD-OFFICERS-SAILORS	UMBER						SPECIFICATION - NO DATA AVAILABLE	
149	DGD106 288	ss-1000-ls	734070510187 3 / LUNCH TRAY STAINLESS STEEL 4 COMPARTMENT PLATES DINNER MESS PLATES	MESS UTENSILS, OFFICER WARD PNS SHIFA	250 / EACH/NUMBER						TECHNICAL SPECIFICATION - 280 X 220X40MM WEIGHT: 810+ GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX design: AS PER STOCK SAMPLE GENERAL SPECIFICATION - 280 X 220X40MM WEIGHT: 810+ GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX design: AS PER STOCK SAMPLE	
150	DGD106 290		003550000052 0 / UTENSILS COOKING ALUMINUM O/D 24 TO 26" , H12 TO 14" TH 10 SWG WITH OUT COVER		12 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER GENERAL SPECIFICATION - SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 99.99% FREE FROM LEAD (PB) AND CADMIUM (CD), DIMENSION: O/D 24 to 26" , H12 to 14" TH 10 SWG WITH out COVER	
151	DGE642 36	NO DATA AVAILABLE	933070505435 4 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PN CREST	32 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
152	DGE984 50	PD-87066	841501013738 4 / GLOVES CHEMICAL		58 / PAIR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	