

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 18-08-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DRG100 898	ZO655541 5	1560ZO655541 5 / ENGINE 14.95CC (OS91)		9 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - ECU:14.95CC(91FX)+TANK E-4020+A3 GLOW PLUG+BOOK LET, MAKE:OS JAPAN. GENERAL SPECIFICATION - ECU:14.95CC (91FX)+TANK E-4020+A3 GLOW PLUG+BOOK LET,MAKE:OS JAPAN.	
2	DPC106 497	OUW6032 SVA/ OUWCPB EVA (Comp A + B)	801078530068 2 / paint PEN GUARD FC green BASE 3 A (RAL 6032)		900 / LITER	PEN GUARD FC RAL 6032				TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
3	DNM102 841	100-3880	281501506715 5 / PUSHROD- VALVE	CATERPILLAR GENSET D3512B (YBB1) USA	24 / EACH/N UMBER	D3512B	CAT3512 BEYB800 583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPI LLAR USA	TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - CATERPILLAR GENSET D3512B (YBB1) USA METALLIC PUSHROD- VALVE MATERIAL STEEL MAIN ENGINE CUMMINSGENERAL SPECIFICATION - CATERPILLAR GENSET D3512B (YBB1) USA METALLIC PUSHROD-VALVE MATERIAL STEEL MAIN ENGINE CUMMINS	
4	DNH106 355	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour	WATER DISPENSER	1 / EACH/N UMBER	OWR- 528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS\BROC HER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			only (WITH 19 LTR BOTTLE)							ENCLOSED WITH QUOTATION		
5	DPC106524	Comp A= EPA001, Comp B = EPA740	8010997404333 / PAINT INTERGARD 400 DARK GREY (Comp A = 17 Ltrs + Comp B = 03 Ltrs)	HULL PRESERVATION OF F-22P FRIGATES	780 / LITER	NO DATA AVAILABLE		UK	INTERNATIONAL PAINTSLTD.P.O. BOX: 20980, ORIEL HOUSE 16 CANNAUGHT PLACE, LONDON, W22 2ZB, UNITED KINGDOM.	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY:M/S SEA TRADE COMPANY, KARACHIGENERAL SPECIFICATION - SOURCE OF AVAILABILITY:M/S SEA TRADE COMPANY,KARACHI	
6	DPC106516	BS381C	8010991689269 / PAINT BRUSHING GREY	F-22P FRIGATES	12 / LITER	NO DATA AVAILABLE		UK	INTERNATIONAL PAINTSLTD.P.O. BOX: 20980, ORIEL HOUSE 16 CANNAUGHT PLACE, LONDON, W22 2ZB, UNITED KINGDOM.	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OEM ADD:INTERNATIONAL PAINTS LTD. P.O.BOX 20980, ORIEL HOUSE 16,CANNAUGHT PLACE,LONDON,W22 2ZB,UK. GENERAL SPECIFICATION - OEM ADD:INTERNATIONAL PAINTS LTD. P.O.BOX 20980,ORIEL HOUSE 16,CANNAUGHT PLACE, LONDON,W22 2ZB,UK.	
7	DPC106517	CLK724	8010992355263 / PAINT INTERLAC 665 STORM GREY	Switchboard PNFT	400 / LITER	INTERLAC 665 INTERNATIONAL PAINT UK		AKZO NOBEL International Paint (Suzhou) Co.Ltd. No.129 Hongxi Road New District Suzhou, Jiangsu, 215151 China Telephone No. 86(512) 66167888	AKZO NOBEL International Paint (Suzhou) Co.Ltd.	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								Fax No. 86(512)66163911		N		
8	DPK106639	MOBILITH AW-2	915001514873 3 / GREASE GENERAL PURPOSE/ MOBILITH AW-2 (PACKING 18KG)	RHIB (DAVIT)	18 / CAN			MOBIL OIL CORP AVIATION & GOVERNMENT SALES DIV 3225 GALLOWS RD FAIRFAX VA UNITED STATES PSC: 22037-4872 TEL: 703-846-4090	MOBIL OIL CORP	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - HIGH PERFORMANCE LITHIUM COMPLES GREASE COLOUR GREEN ORDOR MILD NEGLIGIBLE SUITABLE FOR LUBRICATING CAMS WAYS AND OTHER SLIDING ELEMENTS</u> <u>GENERAL SPECIFICATION - HIGH PERFORMANCE LITHIUM COMPLES GREASE COLOUR GREEN ORDOR MILD NEGLIGIBLE SUITABLE FOR LUBRICATING CAMS WAYS AND OTHER SLIDING ELEMENTS</u>	
9	DPC106449	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL <u>SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
10	DPC105922	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL <u>SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
11	DPC105	SUVA	259071516019	TEMPERED	102.15 /	MTD 72	MTD 72	DOMESTIC MARINE REV-	DOMESTIC	TDS\BROCH	<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	984	410a /HFC-410a/R-410a//HONEYWELL R-410A	3 / DUPONT REFRIGERANT R410A	WATER SYS	KILOGRAMME	EC	EC	20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	C MARINE	HER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
12	DPC105 726	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
13	DPC106 503	PILOT-II	801079517183 9 / MAMMUT PRIMER WHITE	Tall ship	300 / LITER			Jotun Paints (Europe) Ltd. Stather Road Flixborough, Scunthorpe North Lincolnshire DN15 8RR England Tel: +44 17 24 40 00 00 Fax: +44 17 24 40 01 00 SDSJotun@jotun.com	JOTUN	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - undercoat primer whiteGENERAL SPECIFICATION - undercoat primer white	
14	DNQ106 332	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
15	DPC106 517	CLK724	801099235526 3 / PAINT INTERLAC 665 STORM GREY	Switchboard PNFT	400 / LITER	INTERLAC 665 INTERNATIONAL PAINT UK		"International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD, UK. Ph:0191 4696111	International Paint Pvt Ltd, uk	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
16	DPC106 500	LAZ684- Light Grey	801079514525 9 / PAINT INTERSHEEN 579 LIGHT GREY (Packing = 20Ltrs)	HULL PRESERVATION OF F-22P FRIGATES	780 / LITER	NO DATA AVAILABLE		UK	M/S INTERNATIONAL PAINT LTD P O BOX 20980 ORIAL HOUSE 16 CONNAUGHT PLACE LONDON W2 2ZB UK	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - WAR PAINT ISSUE 37 <u>GENERAL SPECIFICATION</u> - WAR PAINT ISSUE 37	
17	DPC106 143	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		11421 / BOTTLE					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	<u>TECHNICAL SPECIFICATION</u> - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL <u>GENERAL SPECIFICATION</u> - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATION	PACKING WITH REGISTERED LABEL	
18	DPC106090	NO DATA AVAILABLE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		85 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL</u> <u>SPECIFICATION - 1.</u> CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
19	DPC106450	NO DATA AVAILABLE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		250 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL</u> <u>SPECIFICATION - 1.</u> CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
20	DPC106342	NO DATA AVAILABLE	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		150 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
21	DNH106347	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DNQ106336	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	5 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DPC106	COMP A +	8010PK506484		26 /					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	606	Comp B = 580-3035-11	0 / HI-BUILD EPOXY ZINC PHOSPHATE PRIMER (PACKING 3.2 LTRS)		LITER					HER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
24	DPC106602	EPIGRIP 524	801099840098 8 / EPIGRIP L524-HIGH BUILD 2-PACK MODIFIED EPOXY COATING IN WHITE COLOR	BILGES PAINTING FRIGATES TYPE 24	100 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
25	DPK106703	XG-460	915099910052 4 / GREASE LUBRICATING XG-460 (Packing = 03 KG Tin)	MAINTENANCE, OILS, GREASES AND APPLICATION	18 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Technical Data (Typical Values) Appearance= Fibrous Grease Colour = Black NLGI Classification = 00 Unworked Penetration(IP50) = 400-430 Worked Penetration (IP50) = 400-430 Base oil Viscosity (IP71) @ 400C cSt = 600 @ 1000C cSt = 34 Four Ball (IP 239) Weld Load kgs = 315 Timken Ok Load IBS = 45 Operating Temperature Range = -25 to + 1000C GENERAL SPECIFICATION - Technical Data (Typical Values) Appearance= Fibrous Grease Colour = Black NLGI Classification = 00 Unworked Penetration(IP50) = 400-430 Worked Penetration (IP50) = 400-430 Base oil Viscosity (IP71) @ 400C cSt = 600 @ 1000C cSt = 34 Four Ball (IP 239) Weld Load kgs = 315 Timken Ok Load IBS = 45 Operating Temperature Range = -25 to + 1000C	
26	DPK106640	90790-BS455	915021877047 8 / OIL SAE 10W40 API SJ for	RADAR-DA08	621 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g: 6.9 D4739,mgKOH/g:6.0 part no 90790-bs455 updated against old	

3. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			YAMALUBE 4 STROKE MOTOR (01 Liter Packing)							ENCLOSE D WITH QUOTATIO N	part no FCW NMMA vide im direction on bases of oem quotation attached <u>GENERAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g:6.9 D4739, mgKOH/g:6.0</u> part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached	
27	DPK89706	IN105270/ MOBIL XHP222 146379	915079510274 1 / GREASE MOBIL XHP222 ,16 /180 KG PACKING	HOVERCRAFT ,GRIFFON HOVERCRAFT LTD,UK	36 / KILOGR AMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
28	DPK106690	1N70015/ NUTO H 32	915079510274 3 / OIL NUTO H 32 Elevators skirt shift (MOBIL NUTO tm H 32) 20 liter Drum)	HOVERCRAFT ,GRIFFON HOVERCRAFT LTD,UK	80 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
29	DNQ105444	NO DATA AVAILABL E	026250000136 5 / LADDER-ALUMINIUM-EXTENDING-28FEET CAPABLE OF WITH STANDING		5 / EACH/N UMBER	NO DATA AVAILAB LE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - 1. Closed height: 5 Meter 2. Extended height: 9 Meter 3. Approximately weight: 26 KG 4. Loading capacity: 150 KG 5. Warranty: Life time</u> <u>GENERAL SPECIFICATION - 1. Closed height: 5 Meter 2. Extended height: 9 Meter 3. Approximately weight: 26 KG 4. Loading capacity: 150 KG 5. Warranty: Life time</u>	
30	DNH106420	NO DATA AVAILABL E	130850053012 6 / DEEP FREEZER 12 CUFT 220 V AC WAVES		2 / EACH/N UMBER	NO DATA AVAILAB LE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
31	DPK106633	GB11120-2011 ISO VG 32	9140FP0010021 / ISO VG 32 GB11120-2011 TURBINE OIL		3 / LITER	GB11120-2011				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
32	DPK104526	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/ADDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	60 / LITER	JAPAN		JAPAN	SHELL	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
33	DPK104469	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/ADDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	500 / LITER	JAPAN		JAPAN	SHELL	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
34	DNM105382	CWCU-230-27	4130705214345 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 24	HVAC PLANT 02 CWAHU-24 PAKISTAN	8 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www. guardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20" GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20"	
35	DNM105386	CWCU-230-27 (12	4130705214346 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	1 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www. guardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20" GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
36	DNM105386	CWCU-230-27 (12	4130705214346 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	1 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www. guardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20" GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24" X20"	
37	DNQ105227	06973009	6140FT1019336 / Torch (Long Life) c/w Spares	Emergency Pack - 1	14 / EACH/NUMBER	583210B.0006	0	KINGSWAY DUNMURRY BELFAST BLANDA	SURVITE C GROUP	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
38	DPK102984	7101001002	9150735232473 / REFRIGERATION LUB OIL DHB-002 (19 Liters Packing)	HARD FORD AC COMPRESSOR	15 / LITER	DHB-002	17FA000 G5737A	DUNHAM-BUSH INDUSTRIES SNO.BHD. LOT 5755-6,KIDMAL INDUSTRIAL PARK,BUKIT ANGKAT,43000 KAJANG. SELANGOR PH:+603-89249000 FAX:+603-89395020	DUNHAM-BUSH INDUSTRIES	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - FLASH POINT (ASTM D-92,COC) 190C,MELTING POINT :(ASTM D-92,COC)-30 C GENERAL SPECIFICATION - FLASH POINT (ASTM D-92,COC)190C,MELTING POINT :(ASTM D-92,COC)-30 C	
39	DNM105306	A043Z558	2940715232077 / FILTER AIR	DG 138 KVA C150D5B	1 / EACH/NUMBER	C150D5B	78630284	M/S ORIENT ENERGY SYSTEM (PVT) LTD 52 WEST FIRST FLOOR WAHEED PLAZA BLUE AREA ISLAMABAD	CUMMINS/ORIENT ENERGY SYSTEM	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - FILTER AIR USED IN ENGINE(AIR) SYSTEM IN CUNMMINS 138 KVA DG AT RDS MIANWALI INSTALLED GENERAL SPECIFICATION - FILTER AIR USED IN ENGINE(AIR) SYSTEM IN CUNMMINS 138 KVA DG AT RDS MIANWALI INSTALLED	
40	DNM105382	CWCU-230-27	4130705214345 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 24	HVAC PLANT 02 CWAHU-24 PAKISTAN	8 / EACH/NUMBER	CP-F6-95-3	NIL	COL POINT PLOT : SHARAIZ AVENUE JATI UMERA ROAD LAHORE COOL POINT PVT LMTD LAHORE PAKISTAN GUARD FILTERS PAKISTAN www. guardfilters.com	GUARD FILTERS PAKISTAN www. guardfilters.com	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20" GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24" X20"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
41	DNM105386	CWCU-230-27 (12	4130705214346 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	1 / EACH/NUMBER	CP-F6-95-3	NIL	COOL POINT PLOT : SHARAIZ AVENUE JATIUMERA ROAD LAHORE COOL POINT PVT LMTD LAHORE PAKISTAN GUARD FILTERS PAKISTAN www.guardfilters.com	GUARD FILTERS PAKISTAN www.guardfilters.com	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"	
42	DPC105513	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
43	DPC105447	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
44	DPC105132	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension	
										QUOTATIO N	SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA		
45	DNM103564	SE123B	6680998980409 / DIPSTICK ASSEMBLY	PEKIN DIESEL GENERATOR 4006-23TAG3A	1 / EACH/NUMBER	4006-23TAG3A	1) DGF6116-U19638U 2) DGF6116-U19758U	PETER BOROUGH PE 15NA UNITED KINGDOM ENGLAND		PERKINS ENGINEERING COMPANY LIMITED	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - USED IN SUMP SYSTEM GENERAL SPECIFICATION - USED IN SUMP SYSTEM	
46	DPC105481	DEFSTAN 68-30/1 OF 1974	0474502204834 / CHLORINATED LIME, TECHNICAL 30% MIN available CHLORINE (25 KG Packing)		1500 / KILOGRAMME						TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 68-30/1 OF 1974 OEM . COC DATE OF MANUFACTURING & EXPIRY OEM TEST CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE GENERAL SPECIFICATION - DEFSTAN 68-30/1 OF 1974 OEM COC DATE OF MANUFACTURING & EXPIRY OEM TEST CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE	
47	DPC105612		0442509434479 / PAINT PRIMING, LIGHT ADMIRALTY GREY FLASH POINT 23 DEGREE C	PRIMER FOR FINISHING ACID AND ALKALI	60 / LITER						TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. DEFSTAN 80-72/3 OF 2006 2. COLOUR SHADE NO 697 OF BS: 381 OF 1996 GENERAL SPECIFICATION - 1. DEFSTAN 80-72/3 OF 2006 2. COLOUR SHADE NO 697 OF BS:381 OF 1996	
48	DPC105614		0442509434481 / PAINT ACID AND ALKALY RESISTANT A/R (BLACK) 05 LTR TIN Flash Point: 32	FINISHING	4 / LITER						TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - 1. NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED 3. DEFSTAN 80-72/3 OF 2006 GENERAL SPECIFICATION - 1. NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Degree C (min) Packing: standard oem 04 ltr tin non corrosive gauge of tin 26 to 28 swg							QUOTATION	3. DEFSTAN 80-72/3 OF 2006	
49	DPC105 224		044250442009 7 / VARNISH OIL EXTERIOR GARDE-II	AMPN	8 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
50	DPC105 229	DEFSTAN 80-37/2 OF 2006	044250442012 4 / Paint Cellulose White Finishing for vehicles principal component Nitro Cellulose Base Flash Point 23		25 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
51	DPC105 506	NO DATA AVAILABLE	044250220238 1 / PAINT PRIMING GRAPHITE BASIS (RED LEAD)	BUXLY/ICI/BE RGER/KOSAR GRP-E VIDE NHQ LT	243 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
52	DPC105 366	SPEC,DEF 1052 COLOURS TO BS 381C	044250910703 5 / PAINT FINISHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/5 66DT210902		30 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
53	DPC105 462	NO DATA AVAILABLE	027614505510	FOR GENERAL	45 / EACH/N					TDS\BROCHER OR	TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	0 / CONTACT CLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS) Packing = 200ml	USE	UMBER					PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
54	DNQ105128	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
55	DNM105465	B57121X513F075xx/P7800B3X/P425S-2373D-512-7.5T (340970)	4140715092410 / A/C SEA/CHILL WATER PUMP WITH MOTOR	A/C UNIT OEM:M/S TAYLOR MADE ENVIRONMENT	1 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OEM: DOMETIC ENVIRONMENTAL CORPORATION P.O BOX 15299 RICHMOND USA VA 23227-0699GENERAL SPECIFICATION - OEM: DOMETIC ENVIRONMENTAL CORPORATION P.O BOX 15299 RICHMOND USA VA 23227-0699	
56	DNM103689	525/50M	4730795066518 / CLIP (JUBLEE CLAMP) S/STEEL 60-80MM	DORMAN 6SETCW CONTINGENCY SPARES	12 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
57	DPC105517	NO DATA AVAILABLE	6830705041338 / GAS ARGON N56 HIGH PURITY 99.9996%	FOR MISTRAL AIR DEFENCE SYSTEM	6.8 / CUBIC METER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED	TECHNICAL SPECIFICATION - 1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes.GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION	1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes.	
58	DNM105098	MURPHY LTD PDS 100-007	668571504852 7 / OIL PRESSURE GAUGE 0-TO-100 PSI& 0-7 BAR MURPHY SWITCH GAUGE	CUMMINS DIESEL ENGINE 34.5 KVA (USA/UK)	6 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DIMENSION / SIZE: Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch Gauge GENERAL SPECIFICATION - DIMENSION / SIZE: Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch Gauge	
59	DPC105304	NIL-SHELF LIFE 3 MONTH	681070503926 3 / DECK COMPOUND FLASH POINT 89C SP-GR-1009 (ANTI SKID)	LOCAL PURCHASE	300 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DSX100377	3AG255	533075504379 0 / O-RING GASKET RUBBER DIA 288.8X300X7.0MM		30 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DRG98744	ZO6547932	2915ZO654793 2 / REGULATOR HIGH PRESSURE		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - S2500 GP SINGLE STAGE REG FOR OXY/INERT GAS SVCE EAX INLET PRESS:300BAR/4350PSI, OUTLET PRESS:172BAROR 2500 PSI GENERAL SPECIFICATION - S2500 GP SINGLE STAGE REG FOR OXY/INERT GAS SVCE EAX INLET PRESS:300BAR/4350PSI, OUTLET PRESS:172BAROR 2500 PSI	
62	DSB1065		424070524744		6 /	2020					TECHNICAL SPECIFICATION - As	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	81		1 / copper foils 0.22 MM		SHEET						per OEM document material of the disk is gold plated phosphor bronze. The diameter of disk is 20mm and ROUND IN SHAP THIKNESS 0.22 MM DIAMETER 19.96 MM The item can hold CO2 Gas pressure till 264 bar and required to puncture/ burst above 264 bar. Available sample dimensions: 20mm diameter and 0.30mm thickness The item is metal disc which can hold till CO2 Gas pressure till 264 Bar. It is required to puncture/ burst at pressure above 264 bar Packing REQUIRED to avoid physical damage to item Item is local substitute of item Disque Plein 19-8 X 0,24 Bronze (NSN 4210-14-254-0732) OEM COC/ Authorized Dealer Certificate/ Mil Test Certificate (MTC) Information not held with unit and may be acquired from local source Locally sourced sample is available Make: Item was originally received from NG France. Item locally available with M/s Star Engineering. Specification: Reference B refers <u>GENERAL SPECIFICATION</u> - As per OEM document material of the disk is gold plated phosphor bronze. The diameter of disk is 20mm and ROUND IN SHAP THIKNESS 0.22 MM DIAMETER 19.96 MM The item can hold CO2 Gas pressure till 264 bar and required to puncture/ burst above 264 bar. Available sample dimensions: 20mm diameter and 0.30mm thickness The item is metal disc which can hold till CO2 Gas pressure till 264 Bar. It is required to puncture/ burst at pressure above 264 bar Packing REQUIRED to avoid physical damage to item Item is local substitute of item Disque Plein 19-8 X 0,24 Bronze (NSN 4210-14-254-0732) OEM COC/ Authorized Dealer	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Certificate/ Mil Test Certificate (MTC) Information not held with unit and may be acquired from local source Locally sourced sample is available Make: Item was originally received from NG France. Item locally available with M/s Star Engineering. Specification: Reference B refers	
63	DSB74776	50TE000C0027	6685745194283 / THERMOMETER BDT 25 & 26 OA 200 DIAM93 SUTTE OM		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DSA101765		5340TY6720913 / CURTAIN RAILING		70 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum GENERAL SPECIFICATION - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum	
65	DSA99336	LOCAL Q1-52-10X100	5310745240197 / RACCORD DROIT (GREASING NUT UNION)		100 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - MARINE STANDARD ALUMINUM BRONZE SET: 03 X PIECES FERRULE LENGTH: 10MM NUT LENGTH: 16MM (14X1.5) PRESSURE: 200 BAR GENERAL SPECIFICATION - MARINE STANDARD ALUMINUM BRONZE SET: 03 X PIECES FERRULE LENGTH: 10MM NUT LENGTH: 16MM (14X1.5) PRESSURE: 200 BAR	
66	DNF102167	HME-AB-SLV-220AC-005	5975705351270 / electrical CONNECTION BOX		12 / EACH/NUMBER	SS304 SURFACE box					TECHNICAL SPECIFICATION - ELECTRICAL CONNECTION BOX material pvc no of glands 04 width 12 inches length 10 INCHES height 6 INCHES GENERAL SPECIFICATION - ELECTRICAL CONNECTION BOX material pvc no of glands 04 width 12 inches length 10 INCHES height 6 INCHES	
67	DSB106582	LOCAL ITEM	0000000500001 / GARBAGE		300 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Length: 36" Round width: 09"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BAG		UMBER	LE					Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag <u>GENERAL SPECIFICATION</u> - Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag	
68	DRG100068	A5476VLP	2915ZO6527525 / REGULATOR LP AIR		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN <u>GENERAL SPECIFICATION</u> - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN	
69	DRG100349	A5476VLP	2915ZO6527525 / REGULATOR LP AIR		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN GENERAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN	
70	DRG100280	A5476VLP	2915ZO6527525 / REGULATOR LP AIR		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN GENERAL SPECIFICATION - AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE),TANAKA JAPAN	
71	DRG79432	3916854	6110ZO6549107 / STARTER MOTOR(24V DC)		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - STARTER MOTOR WITH SOLONIDE SWITCH,24 V DC , MAKE: CUMMINS USA. GENERAL SPECIFICATION - STARTER MOTOR WITH SOLONIDE SWITCH, 24 V DC ,MAKE: CUMMINS USA.	
72	DSB93930	MAT820-0004F17	4510145022083 / MIXING TAP ON PANTRY SINK		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DPK105319	PYRATEX EP2	9150145784933 / FIRE PROOF GREASE / GREASE, HEAT DISSIPATION COMPOUND		2 / KILOGRAMME	EP2				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATION	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
74	DNH103409	058825A	4440013106604 / DRYER		2 / EACH/NUMBER	o 26-d dps				TDS\BROCHER OR	TECHNICAL SPECIFICATION - 0 26-D DPS MEDIUM AIR CHARGIN	

3. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CARTRIDGE/CARTRIDGE, DEHYDRATOR		NUMBER					PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	RATE 26.4 SCFM INLET PRESSURE ATMOSPHERIC OPERATING PRESSURE 5000 PSIG AMBIENT TEMPERATURE 40 TO 115 F WEIGHT 2000 IBS APPROX TECHNICAL SPEC ENCLOSED GENERAL SPECIFICATION - 0 26-D DPS MEDIUM AIR CHARGE RATE 26.4 SCFM INLET PRESSURE ATMOSPHERIC OPERATING PRESSURE 5000 PSIG AMBIENT TEMPERATURE 40 TO 115 F WEIGHT 2000 IBS APPROX TECHNICAL SPEC ENCLOSED	
75	DPK104477	SPIRAX S2 G 140	9150795293050 / shell SPIRAX S2 G 140		2 / LITER	EMPERO EM.09.P				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
76	DRG99887	I-6000T CC-6000 OR I-633MMTB	2915705150088 / COALESCER ELEMENT ASSY		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DRG100194	I-6000T CC-6000 OR I-633MMTB	2915705150088 / COALESCER ELEMENT ASSY		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
78	DSA101603	SC12SERI EWHA15-115V60HZ	4110143241805 / FONTAINE REFT SC12		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DPC103659	236543	2895715312132 / HAVOLINE XTENDED LIFE ANTIFREEZE/ COOLANT (Premixed 50/50)		40 / LITER	YANMAR, 6LPA-STP				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
80	DNQ105149	HAMMAR H 20	4220735199199 / HAMMAR H 20 R HYDROSTATIC RELEASER FOR LIFERAFTS	HAMMAR H 20 R HYDROSTATIC RELEASER FOR LIFE RAFT	12 / EACH/NUMBER	G91154/0902	NA	CM Hammar AB, August Barks gata 15, SE-421 32 Västra Frölunda (Göteborg), Sweden Phone: +46 31 709 65 50 Fax: +46 31 49 70 23 Email: info@cmhammar.com www.cmhammar.com	CM Hammar Sweden	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - The Hammar H20 hydrostatic release unit is designed for liferafts from 6 up to 150 persons. The Hammar H20 release unit consists of a double looped white rope sling, a release mechanism and a Red Weak Link? (breaking strength $2,2 \pm 0,4$ kN) <u>GENERAL SPECIFICATION</u> - The Hammar H20 hydrostatic release unit is designed for liferafts from 6 up to 150 persons. The Hammar H20 release unit consists of a double looped white rope sling, a release mechanism and a Red Weak Link? (breaking strength $2,2 \pm 0,4$ kN)	
81	DNM89356	0327-1617-01	5998715224447 / CARD, CONTROL	50 KVA CUMMINS DG S3.8-G6	1 / EACH/NUMBER	78740893 /CONTROL PANEL (A040S953)PC1.1 ELECTRONIC GOVERNOR	HUY831347	CUMMINS POWER GENERATION LIMITED 1400 73RD AVE NE MINNEAPOLIS MN 55432 COUNTRY USA	CUMMINS	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - PARENT EQUIPMENT: CUMMINS DG 220 KVA HIGHER ASSY: Engine Accessories <u>GENERAL SPECIFICATION</u> - PARENT EQUIPMENT: CUMMINS DG 220 KVA HIGHER ASSY: Engine Accessories	
82	DNM102777	352-9766	6105715225887 / MOTOR GP ELECTRICAL	GEN SET	1 / EACH/NUMBER	3512B	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR, USA	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - ITEM IS USED FOR STARTING SYSTEM OF CATERPILLAR GEN SET 1. Rating: 1088 KW 2. Brand: CATERPILLAR DG 3. Model No: 3512B 4. ESN: BS500559 5. Unit: NMG (O), DG No 3 <u>GENERAL SPECIFICATION</u> - ITEM IS USED FOR STARTING SYSTEM OF CATERPILLAR GEN SET 1. Rating: 1088 KW 2. Brand: CATERPILLAR DG 3. Model No: 3512B 4. ESN: BS500559 5. Unit: NMG (O), DG No 3	
83	DNM102843	358-0768	5305715202157 / SCREW-ADJUSTING (1/2-20X2.42-	CATERPILLAR GENSET D3512B (YBB1) USA	24 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA	TDS\BROCHER OR PIC OF ITEM MUST BE	<u>TECHNICAL SPECIFICATION</u> - <u>GENERAL SPECIFICATION</u> - 0	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			IN)							ENCLOSED WITH QUOTATION		
84	DNM102844	380-4843	5305715202158 / SCREW-ADJUSTING (5/8-18X2.375-IN)	CATERPILLAR GENSET D3512B (YBB1) USA	12 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	
85	DPC105384		0474502201738 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY	SKF COUPLING	750 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - BS 1545 : 1990</u> <u>GENERAL SPECIFICATION - BS 1545 : 1990</u>	
86	DPK104444	0474-7021 (0475-99-224-2137)	0474502242137 / TALLOW WHITE (GREASE) (200 KG DRUM)		200 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
87	DPC103658	G-1200	0475502205613 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		41 / TUBE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
88	DPC105461	SAME AS S NO 9 EXECPT	0442502201637 / PAINT FINISHING	USES FOR STEEL ALUMINUM	102 / LITER					TDS/BROCHER OR PIC OF	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		SHADE.	(GREEN)	OR WOOD ON GLASS						ITEM MUST BE ENCLOSED WITH QUOTATION	AVAILABLE	
89	DPC104 686		0442504420051 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	260 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
90	DPC105 508		0442504420051 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	319 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
91	DPC105		044250943448	FINISHING	160 /					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	622		3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg		LITER					HER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996 GENERAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996	
92	DPC105 373		044250943448 3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	72 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996 GENERAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996	
93	DPC104 663	SPECIFICATION BS 479 SECTION 5	044250942921 9 / NAPHTHA COALTAR (HEAVY) 90/190 (THINNER FOR BOTTOM COMPOSITION	THINNER FOR BOTTOM COMPOSITIONS	20 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DPC105 221	S NO 120 SIMILAR	044250442006 3 / PAINT WEATHER WORK(DARK GREY)	WEATHER WORK	100 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(NSSD/C01/0442/GEN/173DT060393)							ENCLOSED WITH QUOTATION		
95	DPC105564		0442509423538 / PAINT MARKING BRUSH STENCILLING (BLACK) type: alkyded, Flash Point: 32 Degreee C (Min) moethod of application brushing, Packing: 04 ltr tin gauge of drum 26 to 28 swg	N B C D MARKING ETC.	235 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed GENERAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed	
96	DPC105489.	SUPERSEDED BY DGS 1035	0442502202020 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	264 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
97	DPC105533	SPEC,DEF 1052 COLOURS TO BS 381C	0442509107035 / PAINT FNSHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/566DT210902		285 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DNQ103178	0121-924-0372	0121999240372 / LUMBER SOFT WOOD	NBCD DAMAGE CONTROL & FIRE	2 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			DIM SZ 100X100MM (LENGTH=07 FEETS)	FIGHTING EQUIP						BE ENCLOSE D WITH QUOTATIO N	AVAILABLE	
99	DNQ103812	DEVELOP ED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		8 / EACH/N UMBER					TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
100	DNM103943	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	1 / EACH/N UMBER	HD 8/18-4 M* KAR				TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control GENERAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
101	DPC103518	NO DATA AVAILABL E	4210705069936 / CYLINDER CO2 (72KG)	PNS GAWADAR	1 / EACH/N UMBER					TDS\BROC HER OR PIC OF	TECHNICAL SPECIFICATION - 01 Fire Extinguisher Cylinder CO2: 72 KG (Empty Weight) 02 Capacity :50	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CO2 FIXED FIRE FIGHTING SYSTEM BOAT WAIN (EMPTY)							ITEM MUST BE ENCLOSED WITH QUOTATION	KG 03 Total Weight: 122 KG 04 Operation Method: Store Pressure 05 Extinguishing Agent: Carbon Dioxide 06 Operating Temperature: 30c to 60c 07 Discharge Time: 7 Sec per KG 08 Discharge Distance: 4 Meter 09 Height: 1440 mm 10 Width: 650 mm 11 Depth :1400 mm 12 Working Pressure: 60 Bar 13 Testing Pressure: 250 Bar 14 Material: Iron Steel <u>GENERAL SPECIFICATION -</u> 01 Fire Extinguisher Cylinder.CO2: 72 KG (Empty Weight) 02 Capacity : 50 KG 03 Total Weight: 122 KG 04 Operation Method: Store Pressure 05 Extinguishing Agent: Carbon Dioxide 06 Operating Temperature: 30c to 60c 07 Discharge Time: 7 Sec per KG 08 Discharge Distance: 4 Meter 09 Height: 1440 mm 10 Width: 650 mm 11 Depth :1400 mm 12 Working Pressure: 60 Bar 13 Testing Pressure: 250 Bar 14 Material: Iron Steel	
102	DNQ103187	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL &FIRE FIGHTING EQUIOMENT	1 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
103	DNQ102012	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL &FIRE FIGHTING EQUIOMENT	2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
104	DNQ102214	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR-	DAMAGE CONTROL &FIRE FIGHTING	3 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			38-42MM LG 75MM	EQUIOMENT						BE ENCLOSED WITH QUOTATION	AVAILABLE	
105	DNM86351	2301JB	6125791005158 / ALTERNATOR 28V 20A NH220 ENGINE 2301JB	NH220 CUMMINS D/E	1 / EACH/NUMBER	NH220				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DPC103800	RESIN 60 TO 70% (DRIER 01.5)	8010705061107 / PAINT WEATHER WORK FINISHING DLT LTR NS/G/1303/C DT 270199		60 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DPK104328	Mobilux EP2	9611790170396 / Mobilux Grease EP2 (16 OR 18 Kg Packing)		5 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
108	DPC104058	HRC-407C (HFC-407C) GENETRON R-407C	6830705118136 / GAS FOR (A/CS) R-407C (packing = 11.3 kg) (Purity level 99% Min)	A/C SPLIT (02TONS)	102.15 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OEM: HONEYWELL (USA) GENERAL SPECIFICATION - OEM: HONEYWELL (USA)	
109	DPK104300	S-758/MIL-PRF-63460E/N YCOLUBE 127	9150010536688 / CLEANER, LUBRICANT AND PRESERVATIVE	USE FOR DIESEL ENGINE/12.7 MM GUN, MPAC,MRTPS	15 / GALLON					TDS/BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			E WEAPON OIL							ENCLOSE D WITH QUOTATIO N		
110	DNQ103819	RADTARG E-H	6665785274041 / HIGH SENSITIVE PERSONAL DOSIMETER		11 / EACH/N UMBER	RADTAR GE-H				TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settigGENERAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig	
111	DNQ105206	RADTARG E-H	6665785274041 / HIGH SENSITIVE PERSONAL DOSIMETER		10 / EACH/N UMBER	RADTAR GE-H				TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settigGENERAL SPECIFICATION - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management tresh hold time settig	
112	DPK104540	GB11120-2011 ISO VG 32	9140FP0010021 / ISO VG 32 GB11120-2011 TURBINE OIL		1 / LITER	GB11120-2011				TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
113	DNM102744	248-5513	5340715270350 /		4 / EACH/N	DE-660EO				TDS\BROC HER OR	TECHNICAL SPECIFICATION - TEMPRATURE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TEMPRATURE REGULATOR		UMBER	CATERPILLAR GENERATOR C18 600 KVA /480KW				PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	REGULATORGENERAL SPECIFICATION - TEMPRATURE REGULATOR	
114	DPC103805	S. No. 19 jotun anti-skid	8010785292318 /paint JOTUN ANTI-SKID (Dark)		50 / LITER	JOTUN ANTI SKID				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
115	DSB71176		4730TY6715002 / COPPER ELBOW 22MM MALE& FEMALE		12 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - MATERIAL: COPPER DIA: 22 MM DEGREE: 90 THICKNESS: 1 MM TYPE MALE & FEMALE: GENERAL SPECIFICATION - MATERIAL: COPPER DIA: 22 MM DEGREE: 90 THICKNESS: 1 MM TYPE MALE & FEMALE:	