

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 25-08-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF102168	HME-AB-LED-IND-20MM-GRNRD-006	6210705351274 / INDICATION LED LIGHT 230vac 20MM (GREEN & RED)		24 / EACH/NUMBER	led light					<u>TECHNICAL SPECIFICATION - INDICATION LED LIGHT 230VAC 20MM (GREEN & RED) head dia 29-30mm overhaul length 50mm panel thickness 6mm shape round</u> <u>GENERAL SPECIFICATION - INDICATION LED LIGHT 230VAC 20MM (GREEN & RED) head dia 29-30mm overhaul length 50mm panel thickness 6mm shape round</u>	
2	DSX100969	T0502	5999TY6712480 / H.LOCK SET		17 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
3	DSX101030	2CD059	5310755043683 / CONICAL WASHER S-STEEL-10X31X1.5MM		200 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
4	DSX101031	T011007	5340TY6720772 / PIANO HINGES S/STEEL (1200X70X2MM)		10 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
5	DSB96444	8.PWR.57600	5998785239505 / NT-20KJ Power board BK-576		3 / EACH/NUMBER	BK-NT37K-J				LOCAL SOURCE: MOHSIN ZAHIR JAMIL AEROSPACE	<u>TECHNICAL SPECIFICATION - Input: 320VDC Output: 115VAC</u> <u>GENERAL SPECIFICATION - Input: 320VDC Output: 115VAC</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										BAYKEE PAKISTAN (PVT) LTD ADD: 10L AL HASEEB INDUSTRIAL AREA DEFENCE ROAD LAHORE CONTACT: 0330-3588880 EMAIL: mohsin@baykee.com.pk		
6	DRG105083	SA10929 (287548)	294001484134 4 / AIR CLEANER ELEMENT HOBERT GPU		1 / EACH/NUMBER	0					TECHNICAL SPECIFICATION - AS PER PUBLICATION GENERAL SPECIFICATION - AS PER PUBLICATION	
7	DRG89965	TWNIG	2925ZO523849 3 / TWIN IGNITION		6 / EACH/NUMBER	GREAT POWER					TECHNICAL SPECIFICATION - MODEL: TWIN IGNITION GENERAL SPECIFICATION - MODEL: TWIN IGNITION	
8	DRG105086	NS100/N130P	6140ZO652918 3 / BATTERY LEAD		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE; 367MMX173X228(LXWXH)MADE IN PAKISTAN. GENERAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE;367MMX173X228(LXWXH)MADE IN PAKISTAN.	
9	DGB101340	HME-AB-ADP-VLV-FERROL20-004	473070535123 8 / ADOPTER 1/2"		30 / EACH/NUMBER	SS304 SURFACE					TECHNICAL SPECIFICATION - ADOPTER thread type size 1/2 inch 1ST SIDE VALVE THREAD AND SECOND SIDE DIA 20MM FERROL TYPE material stain less steel 316- GENERAL SPECIFICATION - ADOPTER thread type size 1/2 inch 1ST SIDE VALVE THREAD AND SECOND SIDE DIA 20MM FERROL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TYPE material stain less steel 316-l	
10	DSB102456	DRAWING NO.105-05-006-13-000 AND PART NO. 105-05-006-23-000	534072534383 3 / CONICAL MOUNT T-90		16 / EACH/NUMBER	T-90				MODEL: T9-ST OEM: VALKUN ORIGIN: GERMANY PARENT EQUIPMENT: MAIN ENGINE BD SYSTEM	TECHNICAL SPECIFICATION - ENGINE MOUNTING GENERAL SPECIFICATION - ENGINE MOUNTING	
11	DRG104525	SIZE 4.50-12	2610ZO653748 3 / TYRE WITH TUBE		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 4.50-12LT GENERAL TYRE GENERAL SPECIFICATION - 4.50-12LT GENERAL TYRE	
12	DRG88762	SINIG	2925ZO523848 8 / SINGLE IGNITION		4 / EACH/NUMBER	GREAT POWER					TECHNICAL SPECIFICATION - SINGLE IGNITION GENERAL SPECIFICATION - SINGLE IGNITION	
13	DPC105291		044250442004 3 / PAINT FINISHING MID BROWN GLOSS FLASH POINT 32C (04 LTR Packing)	MULTI COAT FINISH PRIMED SEEL ALUMINUM	90 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996 GENERAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996	
14	DPC105640	NO DATA AVAILABLE	047350000011 1 / PASTE OIL RED OXIDE		50 / KILOGRAMME	NO DATA AVAILABLE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
15	DPC104054	R-5002	801070511103 7 / PIGMENT (BRILIANT WHITE)	GRP WORK, M/S ZAIN SONS. KARCHI.PH; 7731541	10 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION		
16	DPC100030	NO DATA AVAILABLE	6850785031104 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLC LEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMENT FOR PNS NASR	6 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. <u>GENERAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
17	DPC105515	R-502	6830705110569 / GAS REFRIGRENT R-502 (packing = 13.6kg)	COLD STORAGE & BLASTFREEZER	27 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
18	DPC100028	M101021	9135PK5085413 / ALCOHOL FOR CLEANING	C-3 SYSTEM	5 / CAN					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
19	DNQ105519	RADTARG E-H	6665785274041 / HIGH		4 / EACH/NUMBER	RADTAR GE-H				TDS\BROCHER OR	<u>TECHNICAL SPECIFICATION -</u> electronics personnel dosimeter	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SENSITIVE PERSONAL DOSIMETER		UMBER					PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting <u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting	
20	DNQ104128	RADTARGE-H	6665785274041 / HIGH SENSITIVE PERSONAL DOSIMETER		6 / EACH/NUMBER	RADTARGE-H				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting <u>GENERAL SPECIFICATION</u> - electronics personnel dosimeter complete set. with dosimeter software and usb data transfer cable including annual, monthly, daily cumulative dose graph data log and export user device, management fresh hold time setting	
21	DPK105829	s4 p 100	9150705270734 / compressor oil shell corena s4 p 100		10 / LITER	s4 p 100				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES <u>GENERAL SPECIFICATION</u> - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TYPICAL REFRIGERATION TEMPERATURES	
22	DSM106540	M10	4130011976803 / FONTAINE REFRIGERANTE M10		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - non magnetic (ss) 220/110 v 60 hz single phase GENERAL SPECIFICATION - non magnetic (ss) 220/110 v 60 hz single phase	
23	DPC105649	407A	6830795293018 / REFRIGERANT GAS 407A (in non returnable cylinder of 40 kg net)		90 / KILOGRAMME	407A				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
24	DPC105730	A020EEV2	8010705332825 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		20 / LITER	HIGHLY PERFUMED				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation. GENERAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.	
25	DSX100234	61DB300	4710TY6715030 / SS PIPE 2"		224 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DNM105918	70HFR20	596175506777 / METAL STUD DIODE 70HFR20 METAL DO-5 PACKAGE	DORMAN D/G 500KVA (UK)	3 / EACH/NUMBER	70HFR20				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE GENERAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE	
27	DNQ105916	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	12 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
28	DNQ105579	PURIFIED LOCALLY DEVELOPED	4220795055188 / EMERGENCY PURIFIED DRINKING WATER CONTENT 500 ML (LIFE RAFT).	S/PACK USED IN 20MEN LIFE RAFT	246 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DPC103	LUSTRE	047350473013		5 /					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	549	EXPORT	2 / Electro polishing chemical LUSTRE EXPORT (OEM VANA Corporation Pakistan) (Packing = 650 Grams)		EACH/NUMBER					HER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	GENERAL SPECIFICATION - null	
30	DNQ105576	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		6 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
31	DPC104410		044250942937 4 / VARNISH MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	USE ONWOOD UNDER CONDITIONS OF MARINE EX	52 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED GENERAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED	
32	DPC99751		044250442006 4 / PAINT WEATHER WORK (LIGHT GREY)NHQ LTR NS/G/1303/C DT 270199	WEATHER WORK	972 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
33	DPC105233		044250943448 3 / PAINT FINISHING ACID AND	FINISHING	70 / LITER					TDS\BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg							BE ENCLOSED WITH QUOTATION	COLOUR SHADE NO 537 TO BS: 381-C Of 1996 <u>GENERAL SPECIFICATION</u> - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996	
34	DPC105 219		044250442005 1 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	20 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTION PRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101 OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTION PRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101 OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
35	DPC105 645	SPEC. BS 3981	047350942925 1 / PIGMENT POWDER (DRY INGREDIENTS FOR PAINTS) RAW SIENNA POWDER (Packing 56 LB or 400 Gram) TIGER BRAND		2.5 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
36	DNM104 344	70MM2 4CORE	615070521857 6 / POWER CABLE 70MM2	Power Cable 70mm2 4core	200 / FOOT	NA	NA	Head Office Arif Habib Centre, 1st Floor, 23 M.T. Khan Road,	PAKISTAN CABLES	TDS/BROCHER OR PIC OF	<u>TECHNICAL SPECIFICATION</u> - No of core: 04 CSA of Conductor: 70MM2 Conductor Material: Copper	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			4CORE					Karachi UAN : 111-CABLES (222-537) EMAIL : info@pakistancables.com sales@pakistancables.com export@pakistancables.com		ITEM MUST BE ENCLOSED WITH QUOTATION	Class 2 Standard: Standard as per IEC 60228 Shape & diameter of Conductor: Sectored-90 No of Strands: 19 Insulation Material: XLPE Thickness of Insulation: 1.1mm Steel Wire Armour Diameter (SWA): 2.5 mm Thickness of outer Sheath: 2.2 mm Diameter of Cable: 42.59mm Testing Voltage: 3.5KV <u>GENERAL SPECIFICATION</u> - No of core: 04 CSA of Conductor: 70MM2 Conductor Material: Copper Class 2 Standard: Standard as per IEC 60228 Shape & diameter of Conductor: Sectored-90 No of Strands: 19 Insulation Material: XLPE Thickness of Insulation: 1.1mm Steel Wire Armour Diameter (SWA): 2.5 mm Thickness of outer Sheath: 2.2 mm Diameter of Cable: 42.59mm Testing Voltage: 3.5KVA	
37	DNM105677	10000-02549/2485C546	4140795171922 / FAN	60 KVA PERKINS	1 / EACH/NUMBER	DK 51280	4ZK05396	PERKINS UK	PERKIN UK	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - RADIATOR COOLING</u> <u>GENERAL SPECIFICATION - RADIATOR COOLING</u>	
38	DPC105712	1141674/22567233/22567259 (20 ltr)	6150735141424 / COOLANT READY MIX (volvopenta)	VOLVOPANTA ENGINE	737 / LITER	NO DATA AVAILABLE		00	M/S AB VOLVOPANTA 40508 GOTEBO RG SWEEDN	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - PACKING: 05 LITER CAN /20 Liter can</u> <u>GENERAL SPECIFICATION - PACKING: 05 LITER CAN /20 Liter can</u>	
39	DPK97238	SHELL OMELA VISCOSITY-68	2590735165521 / HUB OIL	MJP	10 / LITER	MJP 750 SERIES		MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	MJP OSTERBY	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	<u>TECHNICAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATION	SWEDEN GENERAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	
40	DNM105093	SE1/12	403079517009 4 / SLEEVE	PERKINS DIESEL GENERATOR 4006-23TAG3A	6 / EACH/NUMBER	4006-23TAG3A	1) DGF6116-U19638U 2) DGF6116-U19758U	PETER BOROUGH PE 15NA UNITED KINGDOM ENGLAND	PERKINS ENGINEERING COMPANY LIMITED UK	TDS/BROCHURE OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - USED CYLINDER HEAD SYSTEM GENERAL SPECIFICATION - USED CYLINDER HEAD SYSTEM	
41	DNH106530	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	4 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS/BROCHURE OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
42	DNF104347	053300600059	662578514984 5 / LCD DISPLAY LANEVO 19 INCH	ENGINEERING MATERIAL	2 / EACH/NUMBER	NO DATA AVAILABLE		CH	M/S ZTE PAKISTAN (PVT) LTD PLOT NO. 36 ST. NO5 SECTOR NO. 1-9/3 ISLAMABAD.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
43	DNM104919	QSB 6.7	289571517906 8 / CUMMINS ENGINE MODEL QSB6.7 301BHP@2600 RPM	GRP UTILITY BOAT	1 / EACH/NUMBER	QSB6.7		CUMMINS ENGINE COMPANY INC COLUMBUS IN 47201 INDIANA	CUMMINS ENGINE COMPANY INC COLUMBUS INDIANA	TDS/BROCHURE OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ENGINE MODEL:QSB 6.7, DISPLACEMENT:6.7LTR,BORE 107MM,STROKE:124MM,FUEL SYSTEM:HPCR BOSCH CRIN 3.0, RATED: 224KW,RPM 2600, MEDIUM CONTINUOUS DUTY, ASPIRATION TURBOCHARGED/SEA WATER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AFTERCOOLED,CYLINDERS: 6 <u>GENERAL SPECIFICATION -</u> ENGINE MODEL:QSB 6.7, DISPLACEMENT:6.7LTR,BORE 107MM,STROKE:124MM,FUEL SYSTEM:HPCR BOSCH CRIN 3.0, RATED: 224KW,RPM 2600, MEDIUM CONTINUOUS DUTY, ASPIRATION TURBOCHARGED/SEA WATEER AFTERCOOLED,CYLINDERS:6	
44	DNM106 559	380-1882	662571522883 0 / SENSOR GP- PRESSURE (ENGINE OIL)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
45	DNM106 632	A043Z558	294071523207 7 / FILTER AIR	DG 138 KVA C150D5B	1 / EACH/NUMBER	C150D5B	78630284	M/S ORIENT ENERGY SYSTEM (PVT) LTD 52 WEST FIRST FLOOR WAHEED PLAZA BLUE AREA ISLAMABAD	CUMMINS/ORIENT ENERGY SYSTEM	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> FILTER AIR USED IN ENGINE(AIR) SYSTEM IN CUNMMINS 138 KVA DG AT RDS MIANWALI INSTALLED <u>GENERAL SPECIFICATION -</u> FILTER AIR USED IN ENGINE(AIR) SYSTEM IN CUNMMINS 138 KVA DG AT RDS MIANWALI INSTALLED	
46	DNQ103 811	PRM25/M ONIX REFILL	421070521224 2 / 25 KG DRUM OF MONEX POWDER FOR REFILLING.	DC &FF	60 / KILOGRAMME	PRM25	NIL	PRIME BUSINESS SYNDICATE SUITE NO 2, GROUND FLOOR, ABID CHAMBER, SHAHRA-E-LIAQUAT, KARACHI PAKISTAN PHONE: +92-21-32624690, 32213969 FAX: +92-21-32623828 E-MAIL: INFO@PRIME-FIRE.COM	PRIME BUSINESS SYNDICATE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION ATTACH <u>GENERAL SPECIFICATION -</u> SPECIFICATION ATTACH	
47	DNM104 921	imp/am200	301071522034 7 / ELASTIC SHAFT COUPLING	SHAFTING ARRANGEMENT	1 / EACH/NUMBER	Elastic shaft coupling for GR 2:		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON	CUMMINS	TDS\BROCHER OR PIC OF ITEM MUST	<u>TECHNICAL SPECIFICATION -</u> Elastic shaft coupling for GR 2:1, MAX SHAFT TORQUE 1620Nm, CENTAFLEX AM200 COUPLING,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FOR 50 MM SHAFT DIA			1, 1620Nm Torque		SC, USA TEL: 843-745-1483		BE ENCLOSED WITH QUOTATION	INCLUDING CLAMP FOR 50mm DIA AND MACHINED FOR FITTING ON GEAR BOX. OUTSIDE DIA OF AM200 IS 300mm. FIRM'S QUOTATION ALONGWITH TECHNICAL SPECIFICATIONS IS ENCLOSED. <u>GENERAL SPECIFICATION</u> - Elastic shaft coupling for GR 2:1, MAX SHAFT TORQUE 1620Nm, CENTAFLEX AM200 COUPLING, INCLUDING CLAMP FOR 50mm DIA AND MACHINED FOR FITTING ON GEAR BOX. OUTSIDE DIA OF AM200 IS 300mm. FIRM'S QUOTATION ALONGWITH TECHNICAL SPECIFICATIONS IS ENCLOSED.	
48	DPC106 660	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL <u>SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
49	DPC106 611	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL <u>SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FORAN USA	
50	DPC106 514	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
51	DPC106 565	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
52	DPC106 341	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
53	DNM106 554	LF3959	291001250192 2 / LUB OIL	CUMMINS ENGINE 5.9	2 / EACH/N	5.9 QSB	22066008	M/S CUMMINS INS CATENBERG STRAAT I-	CUMMINS UK	TDS/BROCHER OR	TECHNICAL SPECIFICATION - LUB OIL FILTER full flow lube oil filter	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FILTER	QSB USA	UMBER			2840 RUMST BELGIUM		PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	cummins qsb5.9 isb5.9 thread size 1-16 un-2b synthetic design <u>GENERAL SPECIFICATION - LUB OIL FILTER</u> full flow lube oil filter cummins qsb5.9 isb5.9 thread size 1-16 un-2b synthetic design	
54	DPK106976	SAE 90 (80W90)	9150251145135 / ENGINE GEAR OIL SAE 90 (80W90) (03 Ltr to 18 Ltr PACKING)	YAMAHA OUTBOARD ENGINE	18 / LITER	NO DATA AVAILABLE		US	SOCIETY OF AUTOMOTIVE ENGINEERS INC, COMMONWEALTH DRIVE, WARRENDALE, USA, PSC: 15096, TEL#724-776-4841	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - SAE 90 (80W90)</u> <u>GENERAL SPECIFICATION - SAE 90 (80W90)</u>	
55	DNM105986	247-1380	2940715207631 / FILTER ELEMENT AIR	DG CATERPILLAR C2-2 DE18E3/DE22E2 USA	16 / EACH/NUMBER	C2-2 DE18E3/DE22E2	NIL	CATERPILLAR USA CO 701 WATERFOLD WAY SUITE 200 MIAMI USA CONTACT NO 305-476-6800 FAX NO 305-476-6801	CATERPILLAR USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - AIR FILTER USE FOR PROVISION OF CLEAN COMBUSTION AIR TO DG FOR SMOOTH RUNNING OF ENGINE</u> <u>GENERAL SPECIFICATION - AIR FILTER USE FOR PROVISION OF CLEAN COMBUSTION AIR TO DG FOR SMOOTH RUNNING OF ENGINE</u>	
56	DNQ106527	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	22 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCR</u> <u>GENERAL SPECIFICATION - NMAGE:K4723</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
57	DPC105 299	COSMADEC-14	136573522800 0 / COSMADEC-14 EPOXY SEALER	DECK FLOOR	40 / KIT	COSMADEC-14		LABCO FINE CHEMICALS ADDRESS: D-200, SHAHRA-E-SILK, S.I.T.E., KARACHI PHONE: 021-32562622 EMAIL: labcod200@yahoo.com	LABCO FINE CHEMICALS	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MATERIAL TYPE: A BI-COMPONENT MEDIUM TO HIGH MOLECULAR WEIGHT EPOXY SEALER. COLOUR AVAILABILITY: CLEAR TRANSPARENT. FLASH POINT: COMP A: 130°C COMP B: > 180°C. THICKNESS: APPROXIMATELY 250 MICRONS PER COAT ON SMOOTH SURFACE. SHRINKAGE: MIN 0.0% MAX 0.001%. <u>GENERAL SPECIFICATION - MATERIAL TYPE: A BI-COMPONENT MEDIUM TO HIGH MOLECULAR WEIGHT EPOXY SEALER. COLOUR AVAILABILITY: CLEAR TRANSPARENT. FLASH POINT: COMP A: 130°C COMP B: > 180°C. THICKNESS: APPROXIMATELY 250 MICRONS PER COAT ON SMOOTH SURFACE. SHRINKAGE: MIN 0.0% MAX 0.001%.</u>	
58	DPK1069 63	TEXAMATIC 1888 SAE DEXRON-III	915001487853 0 / STEERING LUB OIL (PETROL/DIESEL ENGINE MT VEHICLES) (01 ltrs packing)	MT VEHICLE	56 / BOTTLE			GENERAL MOTORS CORP 3044 W GRAND BLVD DETROIT MI UNITED STATES PSC: 48202-3091 TEL: 248-857-2576	GENERAL MOTORS CORP	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
59	DPC105 303	COSMADEC-13 EPOXY	561070519749 8 / COSMADEC-	CHEMICAL	40 / KIT	-	-	M/S LABCO FINE CHEMICALS PH # 021-32562622	M/S LABCO FINE	TDS/BROCHER OR PIC OF	<u>TECHNICAL SPECIFICATION -</u> COSMADEC-13 EPOXY COMPOUND COMP A: Blend of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		COMPOUND	13 EPOXY COMPOUND (COMP A+ COMP B) (Packing = KIT) (Color = Grey)					EMAIL: labcod200@yahoo.com	CHEMICALS	ITEM MUST BE ENCLOSED WITH QUOTATION	epoxy polymer, fillers and pigments COMP B: Curing agent <u>GENERAL SPECIFICATION - COSMADEC-13</u> EPOXY COMPOUND COMP A: Blend of epoxy polymer, fillers and pigments COMP B: Curing agent	
60	DNM104 915	imp/gp/sh/01	201071522034 8 / PROPELLER SHAFT AQUAMET 17 DIA 50MM	MARINE GEAR BOX	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - PROPELLER SHAFT DIA 50MM, L 4.2M MATERIAL AQUAMET 1.7 OR EQUIVILANT, TYPE 23 PROPELLER SIDE WITH CONE 14 X 100 MM SS KEY AND BRONZE PROPELLER NUT M27 X 2, GEARBOX SIDE NUT MACHINED, FITS IN POS 7 QUOTATION ALONG WITH TECH SPECS ATTACHED</u> <u>GENERAL SPECIFICATION - PROPELLER SHAFT DIA 50MM, L 4.2M MATERIAL AQUAMET 1.7 OR EQUIVILANT, TYPE 23 PROPELLER SIDE WITH CONE 14 X 100 MM SS KEY AND BRONZE PROPELLER NUT M27 X 2, GEARBOX SIDE NUT MACHINED, FITS IN POS 7 QUOTATION ALONG WITH TECH SPECS ATTACHED</u>	
61	DNM104 916	imp/gp/stb/g01	201071522103 1 / STUFFING BOX FOR 50 MM SHAFT DIA	SHAFTING ARRANGEMENT	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONG WITH TECHNICAL SPECS IS ATTACHED</u> <u>GENERAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONG WITH TECHNICAL SPECS IS ATTACHED</u>	
62	DNM104 917	imp/gp/stb/t01	201071522103 3 / STERN TUBE FOR 50 MM SHAFT DIA	SHAFTING ARRANGEMENT	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N	MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHEDGENERAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED	
63	DPC106991		047350473004 0 / ZINC PHOSPHIDE (RAT POISON)		1 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER:1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)GENERAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)	
64	DPC107067		044250442004 6 / PAINT GOLDEN (YELLOW)	DECORATIVE/ FINISHING FOR MOTOR VEHICLES	1388 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - FLASH POINT 32C (min) COLOUR SHADE NO 356 OF BS 381-C OF 1996 defstan 80-72/3 of 2005 stage inspection prescribed PACKING 04 LTR gauge of tin 26 to 28 swg GENERAL SPECIFICATION - FLASH POINT 32C (min) COLOUR SHADE NO 356 OF BS 381-C OF 1996 defstan 80-72/3 of 2005 stage inspection prescribed PACKING 04 LTR gauge of tin 26 to 28 swg	
65	DPC107075		044250442005 1 / Paint, Interior Sky Blue fire	FINISHING INTERIOR	116 / LITER					TDS\BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing							BE ENCLOSED WITH QUOTATION	BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
66	DNQ106663	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		2 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" <u>GENERAL SPECIFICATION</u> - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
67	DNQ106519	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		11 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" <u>GENERAL SPECIFICATION</u> - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
68	DPC107055	NO DATA AVAILABLE	0442502202381 / PAINT PRIMING GRAPHITE BASIS (RED LEAD)	BUXLY/ICI/BERGER/KOSAR GRP-E VIDE NHQ LT	42 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION		
69	DPC107049	SUPERSEDED BY DGS 1035	0442502202020 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	531 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
70	DNQ104106	0121-924-0372	0121999240372 / LUMBER SOFT WOOD DIM SZ 100X100MM (LENGTH=07 FEETS)	NBCD DAMAGE CONTROL& FIRE FIGHTING EQUIP	2 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	DPC107056	NO DATA AVAILABLE	0276145055100 / CONTACT CLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS) Packing = 200ml	FOR GENERAL USE	44 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
72	DPC107014	NO DATA AVAILABLE	0276145055100 / CONTACT CLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS) Packing = 200ml	FOR GENERAL USE	36 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	SNQ106787	0265-12392/	0265594233534 / NAIL-		51 / KILOGR					TDS\BROCHER OR	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		SWG-8	STEEL-WIRE-5INCH (ROUND CHEQUERED HEAD SWG 5)		AMME					PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>SPECIFICATION - NO DATA AVAILABLE</u>	
74	DNQ106604	0254-254050	0254784203153 / CLAMP HOSE SZ 5.500 TO 6.250 BS 5315 71/226		45 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
75	DNQ106666	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		8 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.</u> <u>GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.</u>	
76	DPC105236	DSL 101/ SOFNOLIME 2050 (408)L Grade	0473504730050 / SODA LIME DSL 101 TYPE: INDICATOR (Packing 4.5 KG PLASTIC CAN) /SOFNOLIME CS2580 L Grade w/out Indica		150 / TIN/PKT					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - COLOUR WHITE, COLOUR ON SATURATION VIOLET, GRAINS SIZE 4-8 MESH (2.4-5MM) MOISTURE 13-15.5% ACTIVITY PERIOD 180 MINUTES CO2 ABSORPTION NOT LESS THAN 20% W/W DENSITY 6.06-1.00 G/CC</u> <u>GENERAL SPECIFICATION - COLOUR WHITE, COLOUR ON SATURATION VIOLET, GRAINS SIZE 4-8 MESH (2.4-5MM) MOISTURE 13-15.5% ACTIVITY PERIOD 180 MINUTES CO2 ABSORPTION NOT LESS THAN 20% W/W DENSITY 6.06-1.00G/CC</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
77	DNQ106 679	PURIFIED LOCALLY DEVELOPED	422079505518 / EMERGENCY PURIFIED DRINKING WATER CONTENT 500 ML (LIFE RAFT).	S/PACK USED IN 20MEN LIFE RAFT	246 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
78	DNM106 824	EBH 12 OR 215412400 /215612400/215613405	4130US5065503 / COOLING UNIT	MAIN A/C CRISAIR USA TYP.F48E-P.	2 / EACH/NUMBER	TVE12				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Make: USA Model: E58977 Brand: DOMETIC Equivalent: Nil 215612400 FOR 115V/1/60HZ, 215613405 FOR 230/1/60HZ GENERAL SPECIFICATION - Make: USA Model: E58977 Brand: DOMETIC Equivalent: Nil 215612400 FOR 115V/1/60HZ, 215613405 FOR 230/1/60HZ	
79	DNH106 799	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
80	DNH106 672		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	2 / EACH/NUMBER	WA60000 514				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W GENERAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W	
81	DNQ106 684	1-3-150 DEVELOPED BY DTD	4730992542747 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	7 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION		
82	DNQ105580	1-3-150 DEVELOPED BY DTD	4730992542747 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	7 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	DNQ105520	1-3-150 DEVELOPED BY DTD	4730992542747 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
84	DNQ106683	1-3-166 DEVELOPED BY DTD	4730992542748 / CLAMP REPAIR, PIPE	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	7 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DNQ106620	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DPK106941	20W-50	9150PK5079480 / LUB OIL 20W50 PKG 4LTR (FOR PETROL VEHICLES)	PETROL VEHICLES	3806 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
87	DNM106832	MURPHY LTD PDS 100-007	6685715048527 / OIL PRESSURE GAUGE 0-TO-100 PSI& 0-7 BAR MURPHY SWITCH GAUGE	CUMMINS DIESEL ENGINE 34.5 KVA (USA/UK)	5 / EACH/NUMBER					D WITH QUOTATION	TECHNICAL SPECIFICATION - DIMENSION / SIZE: Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch Gauge GENERAL SPECIFICATION - DIMENSION / SIZE: Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch Gauge	
88	DNM104695	NO DATA AVAILABLE	4720705120470 / HOSE PIPE FOR HP AIR CONTAIN BRAIDED TEFLON COVERED WITH FIBER GLASS (LENGTH 60 METERS) INTERNAL DIA 10MM W.P 4000PSI 275BAR (WITH BOTH END FITTING ADAPTOR OF SS)	HP AIR COMPRESSOR	4 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - HOSE PIPE FOR HP AIR CONTAIN BRAIDED TEFLON COVERED WITH FIBER GLASS (LENGTH 60 METERS) INTERNAL DIA 10MM W.P 4000PSI 275BAR (WITH BOTH END FITTING ADAPTOR OF SS) GENERAL SPECIFICATION - HOSE PIPE FOR HP AIR CONTAIN BRAIDED TEFLON COVERED WITH FIBER GLASS (LENGTH 60 METERS) INTERNAL DIA 10MM W.P 4000PSI 275BAR (WITH BOTH END FITTING ADAPTOR OF SS)	
89	DPK106945	TCW3 NMMA	0721500000013 / LUB OIL OMD-23 FOR TWO STROKE OUTBOARD GASOLINE ENGINE NMMA GRADE TCW3		1112 / LITER	NO DATA AVAILABLE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE GENERAL SPECIFICATION -ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
90	DPK106953	STM7610AB2L	6850142724978 / SOLVANT DEGRAISSANT DE SECURIT STM7610A (WD-40) (05 Liter Packing)		5 / LITER	NO DATA AVAILABLE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
91	DPK106951	10250	5970143407636 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	4 / KILOGRAMME	NO DATA AVAILABLE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DPK106755	Q/SY16055-85/7253	9150FP0020012 / AVIATION LUBRICATING GREASE 7253 (SINOPEC RIPP 7253)		10 / KILOGRAMME	NO DATA AVAILABLE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
93	DSB107181	CM7PS-D1-SEW	5935703399197 / 7PIN MALE DEUTSCH		12 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DSB107422	CM7PS-D1-SEW	5935703399197 / 7PIN MALE DEUTSCH		12 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DNM104143	2897133	5341735269954 / NO13 HOSE CLAMP		2 / EACH/NUMBER	CLASSIC V				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO13 HOSE CLAMP GENERAL SPECIFICATION - NO13 HOSE CLAMP	
96	DSA102648	GSM141-08F5MLEB	530614329937		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		ZCN17-03	4 / VIS-F90EV1-CARRE-B-ZISCN17-0 (SCREW)		UMBER	LE					DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DSA102570	E27311H60M22AET	530514235323 4 / VIS HM 6X18X18 A52		310 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DSA106575		5130TY673014 8 / disc CUTTING 4" 100X3X16MM		157 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - OEM: RHODIUS GERMANY Technical details: Series : FTK33 Diameter: 100mm Thickness: 2.0mm Center hole: 16mm with steel core out side Model No: 200840/ EN-12413 PRO LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROH/ GERMANY shelf life expiry date at least 03 years against manufacturing date GENERAL SPECIFICATION - OEM: RHODIUS GERMANY Technical details: Series : FTK33 Diameter: 100mm Thickness: 2.0mm Center hole: 16mm with steel core out side Model No: 200840/ EN-12413 PRO LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROH/ GERMANY shelf life expiry date at least 03 years against manufacturing date	
99	DNM104819	RAPID-S	534070524608 5 / LIGHT WEIGHT TRAFFIC BARRIER		2 / EACH/NUMBER	RAPID-S				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Boom Vehicle Barrier designed for fast movements . - Designed to blend into modern architectures, - Boom Vehicle Barrier is made of a sturdy steel structure for reliable operations and long lasting appearance. GENERAL SPECIFICATION - Boom Vehicle Barrier designed for fast movements . - Designed to blend	

Sl. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											into modern architectures, - Boom Vehicle Barrier is made of a sturdy steel structure for reliable operations and long lasting appearance.	
100	DSA105524	39-017/BFP-12-7213-VTX	0850886567213 / BATTERY FLEXIBLE HOSE		500 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
101	DPC105293	JOTAPRIME510 ALU. RED	8010785338806 / JOTAPRIME510 ALU.RED		250 / EACH/NUMBER	NA				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - JOTUN PAINT FOR SHIPSIDE ALUMINIUM RED 100DFT</u> <u>GENERAL SPECIFICATION - JOTUN PAINT FOR SHIPSIDE ALUMINIUM RED 100DFT</u>	
102	DNM104121	7653614	4730735269974 / HOSE BAND		2 / EACH/NUMBER	CLASSIC V				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - HOSE BAND</u> <u>GENERAL SPECIFICATION - HOSE BAND</u>	
103	DSA106081	D-18677	5130765157117 / disc CUTTING 5 inch		209 / EACH/NUMBER	200611/ EN-12413					<u>TECHNICAL SPECIFICATION - RHODIUS: FTK33 180X3.0X22.23MM DESPRESSED CENTER CUTTING DISCS SHAPE-42 MINIMUM SHELF LIFE - 18 MONTHS</u> Technical details: Series : FTK33 Diameter: 125mm Thickness: 3.0mm Center hole: 22.23mm with steel core out side Model No: 200611/ EN-12413 ALPHA LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWEKZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROH/ GERMANY SHELF LIFE OF DISC: 3 years from date of manufacturing <u>GENERAL SPECIFICATION - RHODIUS: FTK33 180X3.0X22.23MM</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DESPRESSED CENTER CUTTING DICS SHAPE-42 MINIMUM SHELF LIFE – 18 MONTHS Technical details: Series : FTK33 Diameter: 125mm Thickness: 3.0mm Center hole: 22.23mm with steel core out side Model No: 200611/ EN-12413 ALPHA LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROHI/ GERMANY SHELF LIFE OF DISC: 3 years from date of manufacturing	
104	DPC107013	S. No. 19 jotun anti-skid	8010785292318 / paint JOTUN ANTI-SKID (Dark)		100 / LITER	JOTUN ANTI SKID				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
105	DSA102651	GSM141-08F5MLEC Z15CN17-03/ 5306FBM0 DCINOX	5306143299375 / BOLT, INTERNALLY RELIEVED BODY/VIS CSM 141-08 INOX / BOLT, INTERNALLY RELIEVED BODY		100 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
106	DSA106576		5130TY6730149 / GRINDING DISC 4"		150 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - OEM: RHODIUS GERMANY</u> Technical details: Series : RS2 Diameter: 105mm Thickness: 7.0mm Center hole: 16mm with steel core out side Model No: 200167/EN-12413 PRO LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROHI/ GERMANY SHELF LIFE EXPIERY DATE AT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LEAST 03 YEARS AGAINST MANUFACTURING DATE <u>GENERAL SPECIFICATION</u> - OEM: RHODIUS GERMANY Technical details: Series : RS2 Diameter: 105mm Thickness: 7.0mm Center hole: 16mm with steel core out side Model No: 200167/EN-12413 PRO LINE STEEL Web: www.rhodium.abrasives.com OEM Address: SCHIEFWEKZEUGA GMBH & CO KG BROHTSLSTR 2 56659 BURGBROHI/ GERMANY SHELF LIFE EXPIERY DATE AT LEAST 03 YEARS AGAINST MANUFACTURING DATE	
107	DSB107548	ITD/2232018-ITD-VTX	295054534496 2 / Nut of Impeller		2 / EACH/NUMBER	MAIN ENGINE					<u>TECHNICAL SPECIFICATION</u> - The Impeller Nut is a precision-engineered fastener designed to securely lock the impeller onto the shaft. It ensures stable rotation, prevents loosening under vibration and maintains proper alignment during pump or engine operation. Typically made form high-strength, corrosion-resistant material for long-term reliability. <u>GENERAL SPECIFICATION</u> - The Impeller Nut is a precision-engineered fastener designed to securely lock the impeller onto the shaft. It ensures stable rotation, prevents loosening under vibration and maintains proper alignment during pump or engine operation. Typically made form high-strength, corrosion-resistant material for long-term reliability.	
108	DPC106997	739458	655022612651 6 / CHLORIDE TABLETS		6 / BOTTLE	CHLORIDE TABLETS				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - Manufacturer Address Wilhelmsen Ships Services AS P.O Box 33 NO-1324 LYSAKER, NORWAY Tel: +4767584550 Technical Specifications Bottle contains 250 tablets Used for measuring chloride contents in coolants (premix as well as water treated) General	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Specification Item is part of SPECTRAPACK 309 Cooling Water Test Kit (Part No 739466, NSN 6630735232429) <u>GENERAL SPECIFICATION</u> - Manufacturer Address Wilhelmsen Ships Services AS P.O Box 33 NO-1324 LYSAKER, NORWAY Tel: +4767584550 Technical Specifications Bottle contains 250 tablets Used for measuring chloride contents in coolants (premix as well as water treated) General Specification Item is part of SPECTRAPACK 309 Cooling Water Test Kit (Part No 739466, NSN 6630735232429)	