

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 26-08-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGB103 985	205426	345573522491 5 / disc CUTTING 5 INCH	CASINGS	4 / EACH/NUMBER	XT67	7*AH102	Rhodium Schleifwerkzeuge GmbH & co.KG GERMANY. www.rhodium-abrasives.com	RHODIUS		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
2	DGB104 083	205426	345573522491 5 / disc CUTTING 5 INCH	CASINGS	8 / EACH/NUMBER	XT67	7*AH102	Rhodium Schleifwerkzeuge GmbH & co.KG GERMANY. www.rhodium-abrasives.com	RHODIUS		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
3	DGH102 046	614599521 8490	614599521849 0 / CABLE POWER ELECTRICAL 3CORE 440V 34A	CABLES	300 / METER	DG SHIPS 212	NA	MINISTRY OF DEFENCE (NAVY) SHIPS SUPPORT AGENCY DME ME253, ROOM 19, BLOCK B FOXHILL, BATH, UK TEL: 01225 883293 FAX: 01225 883548	DG SHIPS 212 UK		TECHNICAL SPECIFICATION - AS PER NMCRL AND DG SHIPS 212 GENERAL SPECIFICATION - AS PER NMCRL AND DG SHIPS 212	
4	DGE105 600	SFF6 1	259073517592 8 / POLYESTER BOAT LIFTING BELT 20000 KG LOAD	ENGINE	3 / EACH/NUMBER	NK	32568955	YONCA TURKEY LTD	YONCA		TECHNICAL SPECIFICATION - LENGTH 20 METER WLL 20000 KG BATCH NO YHTS-07-0105 TEMP -40 DEG C + 100 DEG C GENERAL SPECIFICATION - LENGTH 20 METER WLL 20000 KG BATCH NO YHTS-07-0105 TEMP -40 DEG C + 100 DEG C	
5	DGE104 681	SCOTCH 88	597099664876 4 / Tape, insulation, Electrical	0	50 / EACH/NUMBER	0	0	3M CENTRE, CAIN ROAD, BRACKNELL	3M UNITED KINGDOM PLC		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
6	DGE100 420	-	561099200438 6 / BAG SAND	DC & FF	50 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCR ETE UK LTD THE		TECHNICAL SPECIFICATION - IN DESCRIPTION, LOCAL GOOD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(LOCAL GOOD QUALITY ACCEPTABLE)						FLOORING TECHNOLOGIES CENTRE BOOTH LANE SANDBATCH CHESHIRE CW11 3QF UK PH:+44(0)1270 753000 & FAX :+44 (0)1270 753333		QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRAINING ME/251/544 DT 11 APRIL 2011.&I(M) DC&FF. <u>GENERAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACCEPTABLE, ADDED VIDE FLAG OFFICER SEA TRAINING ME/251/544 DT 11 APRIL 2011.&I(M) DC&FF.</u>	
7	DGB103456		0283700001608 / INGOT-BRASS		40 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg <u>GENERAL SPECIFICATION -</u> Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg	
8	DGE101545	NIL	0559794444901 / SLEEVING GLASS INSULATION CERAMIC VARNISHED GLASS FIBRE 6MM	GENERAL ELECTRIC USE	5 / METER						<u>TECHNICAL SPECIFICATION - BS 2848 (5970994444901)</u> <u>GENERAL SPECIFICATION - BS 2848 (5970994444901)</u>	
9	DGE101977	NO DATA AVAILABLE	0559790200485 / INSULATION-TAPE-POLYETHYLENE TERAPHALATE(TERYLENE)		10 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			W/0.75									
10	DGE101979	NO DATA AVAILABLE	0559790020552 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	28 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
11	DGE104684	0.75X0.007INCH-50MTR-	0559790015244 / INSULATION-TAPE- VARNISHED WOVEN GLASS-FIBRE- (STRAIGHT CUT)		20 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
12	DGE101974	0.75X0.007INCH-50MTR-	0559790015244 / INSULATION-TAPE- VARNISHED WOVEN GLASS-FIBRE- (STRAIGHT CUT)		15 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
13	DGE101132		0350595713032 / ROPE COIR HAWSERLAID CIR 2"		400 / FATHOM						TECHNICAL SPECIFICATION - 3 STRD CIR 2" DIA 0.625 MATERIAL COIR (Husk of CoConut) GENERAL SPECIFICATION - 3 STRD CIR 2" DIA 0.625 MATERIAL COIR (Husk of CoConut)	
14	DGE100883	C-268	0476599430559 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
15	DGE102392	LETTER NO.E-1/4927/A/445DT050902	0461590003914 / CLOTH POLESHING		150 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
16	DGB103 346		028359571144 0 / ROD NAVAL BRASS, RD DIA 0.25 inch, WT PER, FT 18LBS		1.5 / METER						TECHNICAL SPECIFICATION - specifications BSEN 12163 of 2011 material grade: CW712 MATERIAL CONDITION: M RUNNING LENGTH (MIN): 02 METER GENERAL SPECIFICATION - specifications BSEN 12163 of 2011 material grade: CW712 MATERIAL CONDITION: M RUNNING LENGTH (MIN): 02 METER	
17	DGB104 434	BS 1476	028359571122 9 / ANGLE- ALUMINIUM- ALLOY-2" EQUAL SIDED THK3/16" WT/FT 0.84 LB		2 / METER						TECHNICAL SPECIFICATION - BS 1476 GENERAL SPECIFICATION - BS 1476	
18	DGB102 031		028359571143 3 / ROD NAVAL BRASS HEX SIZE A/F 1.10"WT PER FT 3.910(LB)		1 / METER						TECHNICAL SPECIFICATION - SPECS BSEN 12163, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet GENERAL SPECIFICATION - SPECS BSEN 12163, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet	
19	SGB104 440		026759923526 7 / COUPLING PIPE GALV BORE 1.00 INCH		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - PIPE BORE 1'.00 INCH MATERIAL MS (GALVANIZE) GENERAL SPECIFICATION - PIPE BORE 1'.00 INCH MATERIAL MS (GALVANIZE)	
20	DGB105 281	NO DATA AVAILABL E	027259272007 2 / DRILL- TWIST- TAPER- SHANK-HSS- 9MM		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - size: 9 mm material: hss Hardness HRC65-66. hss jobber drill-general purpose a100, 9.00mm GENERAL SPECIFICATION - size: 9 mm material: hss Hardness HRC65-66. hss jobber drill-general purpose a100, 9.00mm	
21	DGB103 061		021459941001 9 / BOLT MACHINE STEEL UNC class 2a HEX HD SZ 0.625	BR-320 D/78	100 / EACH/N UMBER						TECHNICAL SPECIFICATION - AISI PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED GENERAL SPECIFICATION - AISI PD 970:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			X3.000X1.500 IN								2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC REQUIRED	
22	DGB105 280		027250272004 0 / DRILL- PARALELL- SHANK-3MM CARBON STEEL		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Material HSS, Hardness HRC65-66. <u>GENERAL SPECIFICATION -</u> Material HSS, Hardness HRC65-66.	
23	DGB103 883		026359414970 4 / SHACKLE STRAIGHT TO SCREW FOR RIGGING		25 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
24	DGB103 204	NO DATA AVAILABL E	025770941150 8 / NUT-PLAIN- HEXAGON- THREAD-SIZE. 875LH.770 (brass)		8 / DOZEN						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
25	DGB102 007	NO DATA AVAILABL E	024378000108 7 / CEASING WIRE 1MM 2185MB	S/M	5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
26	DGH103 803		056159000798 9 / Cable Elect 3 Core		44.5 / METER						<u>TECHNICAL SPECIFICATION -</u> Material: Copper Size: 7/44 Capacity: 30A oem: pak cable <u>GENERAL SPECIFICATION -</u> Material: Copper Size: 7/44 Capacity: 30A oem: pak cable	
27	DGH103 757		056159018066 7 / CABLE ELECTRIC NO. OF CORES_2, SIZE OF COND. (IN) 162/0076,		200 / METER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
28	DGB103 203	C60	047450448149 7 / CRUCIBLE, METAL MELTING (60 LB BAG)-OEM MORGANITE UK K1461	FOUNDRY USE OEM MORGANITE UK FAX NO	3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
29	DGE105801	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
30	DGE105887	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
31	DGE103 760	G2951-38	424000926412 4 / BELT SAFETY INDUSTRIAL		-65 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Material= PLASTIC POLYAMIDE Nylon, 2. BODY BELT OVERALL LENGTH= 47.500 INCHES NOMINAL, 3. DISTANCE BETWEEN D RINGS= 21.00 INCHES NOMINAL, 4. BODY BELT WIDTH= 01.750 INCHES MINIMUM, 5. CUSHION PAD WIDTH= 04.000 INCHES MINIMUM, 6. CUSHION PAD LENGTH= 29.000 INCHES NOMINAL, 7. WAIST SIZE= 38 INCH, GENERAL SPECIFICATION - 1. Material= PLASTIC POLYAMIDE Nylon, 2. BODY BELT OVERALL LENGTH= 47.500 INCHES NOMINAL, 3. DISTANCE BETWEEN D RINGS= 21.00 INCHES NOMINAL, 4. BODY BELT WIDTH= 01.750 INCHES MINIMUM, 5. CUSHION PAD WIDTH= 04.000 INCHES MINIMUM, 6. CUSHION PAD LENGTH= 29.000 INCHES NOMINAL, 7. WAIST SIZE= 38 INCH,	
32	DGE103 919	8931290	381573100180 0 / HELMET PLASTIC P/N 8931290 COLES 16T	COLES CRANE 16 TON	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
33	DGB103 016		530699941875 9 / BOLT PRECISION HEXAGON HEAD UNC SZ 1 1/2X1 1/4X1/2" TPI.13	FASTENINGS, BOLTS AND STUDS.	30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DGE101 586	A-A-1201, P-P-121, ANSIB74-	535000186882 0 / PAPER ABRASIVE 9"		20 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		18	X11" WATER PROOF MATERIAL GLASS GRADE 110-A								AVAILABLE	
35	DGE104 415	nil	564000809631 2 / INSULATION BLOCK, THERMAL FIBERGLASS (THICKNESS 1 INCH)		5 / SHEET						TECHNICAL SPECIFICATION - SPECIFICATION/SIZES: 1. MIL-I-742 TYPE-I, 2. OVERALL LENGTH: 36 INCH NOMINAL, 3. OVERALL WIDTH: 24 INCH NOMINAL, 4. OVERALL THICKNESS: 01 INCH NOMINAL, 5. MATERIAL: GLASS FIBER, 6. DECORATIVE SIDE TYPE: FIBER GLASS CLOTH-COTATED, 7. PACKING LEVEL: A, AS PER SPECS MIL-I-742, TY-1, 8. ORIGIN: USA. GENERAL SPECIFICATION - SPECIFICATION/SIZES: 1. MIL-I-742 TYPE-I, 2. OVERALL LENGTH: 36 INCH NOMINAL, 3. OVERALL WIDTH: 24 INCH NOMINAL, 4. OVERALL THICKNESS: 01 INCH NOMINAL, 5. MATERIAL: GLASS FIBER, 6. DECORATIVE SIDE TYPE: FIBER GLASS CLOTH-COTATED, 7. PACKING LEVEL: A, AS PER SPECS MIL-I-742, TY-1, 8. ORIGIN: USA.	
36	DGE105 603	ECW0090 3-12	593572507749 2 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SIZE 48/16 LG 1 METER		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DGE104 421	000W280	599999784543 2 / BRAID-BANDAGE (WIRE MES KNITTED)	GLASS WOOL (DC BOX)	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DGB102 165	NO DATA AVAILAB LE	026850000003 6 / AVERY-SCALE-PLATFORM-	AND MOUNTED ON WHEEL.SIZE OF	2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NO3205CAPA CITY250KG SELF INDICATING	PLATFORM24"								
39	DGE105605	NO DATA AVAILABLE	0415780000093 / JARY CANE, 729 MS, CAPACITY.		60 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - daimention: 14" x 6" x 18" capacity: 10 ltrs GENERAL SPECIFICATION - daimention: 14" x 6" x 18" capacity: 10 ltrs	
40	DGT96698	NO DATA AVAILABLE	0100000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	48 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DGT103956	BELFONT TRUWOOD TEAK	9330992246097 / PLASTIC SHEET, LAMINATED, DECORATIVE (SIZE:8'X 4' X 1MM, SHADE TRU TEAK WOOD) (GRADE DESIGNATION :STAN)		4 / SHEET						TECHNICAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1 GENERAL SPECIFICATION - SIZE:8'X 4' X 1/25" resistant tested to bs 476pt 1class 1	
42	DGE101971	NO DATA AVAILABLE	0559780000183 / SLEEVE PLASTIC GREEN 0.3X3 55P(DELETED NS/TD/32/611DT280989)		5 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
43	DGE103996	nil	6630785327045 / OIL ONLY PILLOWS		20 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - DIMENSION: 40 X 50CM ABSORBING CAPACITY: 184 LITRES PACKAGING: 10/BAG GENERAL SPECIFICATION - DIMENSION: 40 X 50CM ABSORBING CAPACITY: 184 LITRES PACKAGING: 10/BAG	
44	DGB102448	sch-40 long radius	4730705274160 / elbow dia 5 inch LONG RADIUS WITHOUT		6 / EACH/NUMBER	SCH-40					TECHNICAL SPECIFICATION - ELBOW BEND PIPE MILDSTEEL INNER DIA 5 INCH, OUTER DIA 5.25 INCH, THICKNESS 0.25 INCH (7 MM), MILD STEEL GRADE 40.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			THREAD								Grade: ASTM 106 Grade B. Schedule.40 <u>GENERAL SPECIFICATION - ELBOW BEND PIPE MILDSTEEL INNER DIA 5 INCH, OUTER DIA 5.25 INCH, THICKNESS 0.25 INCH (7 MM), MILD STEEL GRADE 40. Grade: ASTM 106 Grade B. Schedule.40</u>	
45	DGP885 37	A360 PLUS	702571531623 4 / A3 SIZE FLATBED SCANNER		1 / EACH/N UMBER	N/A					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
46	DGE103 994	nil	663078532704 8 / OIL ONLY SOCKS		24 / PAIR	N/A					<u>TECHNICAL SPECIFICATION - DIMENSION: DIAMETER 76-CM, LENGHT 1.2M, ABSORBING CAPACITY: 43 LITERS, PACKAGING: 12/BOX, COLOUR: YELLOW, MATERIAL: SHREDDED POLYPROPYLENE, OTHER FEATURES: ABSORB VARIOUS STRONG ACID/ALKALI SOLUTIONS, ABSORB VARIOUS LIQUID SOLVENTS, SUCH AS HYDROCHLORIC ACID, SULFURIC ACID, PHOSPHORIC ACID, NITRIC ACID, SODIUM HYDROXIDE, HYDROFLUORIC ACID ETC, GENERAL SPECIFICATION - DIMENSION: DIAMETER 76-CM, LENGHT 1.2M, ABSORBING CAPACITY: 43 LITERS, PACKAGING: 12/BOX, COLOUR: YELLOW, MATERIAL: SHREDDED POLYPROPYLENE, OTHER FEATURES: ABSORB VARIOUS STRONG ACID/ALKALI SOLUTIONS, ABSORB VARIOUS LIQUID SOLVENTS, SUCH AS HYDROCHLORIC ACID, SULFURIC ACID, PHOSPHORIC ACID, NITRIC ACID, SODIUM HYDROXIDE, HYDROFLUORIC ACID ETC,</u>	
47	DGT106 970	NO DATA AVAILABL E	010000000000 3 / HARD BOARD SIZE	SPECE/BSS 1142/1971	150 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			12'X4'X1/4"								AVAILABLE	
48	DGT105343	NO DATA AVAILABLE	0100000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	30 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DGE107142	NO DATA AVAILABLE	8340505039260 / TENT 180 LBS MILITARY PATTERN MK-4 WITH ALL ACCESSORIES (COMPLETE SET)		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. LENGTH: 14 FEET (± 2 INCH) b. WIDTH: 14 FEET (± 2 INCH) c. CENTRAL HEIGHT: 07 FEET (± 2 INCH) 2. OTHER SPECIFICATION a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 05 NOS (02 x RIDGE POLES, LENGTH 07 FEET AND 03 x STANDING POLES, LENGTH: 07- FEET). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ± 02 MM & THICKNESS: 02 MM ± 0.50 MM. b. IRON PEGS: QTY 22 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2-MM AND MILD STEEL PIN QTY 12 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 22 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON & DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 03 KGS, WITH WOODEN HANDLE & LENGTH 1.5 FEET. e. FLAPPER FOR GROUND: MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FEATURE: WINDOW: 02 (SIZE: 1.5 x 1.5 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 02 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 01 x BAG FOR THE TENT AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. LENGTH: 14 FEET (± 2 INCH) b. WIDTH: 14 FEET (± 2 INCH) c. CENTRAL HEIGHT: 07 FEET (± 2 INCH) 2. OTHER SPECIFICATION a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 05 NOS (02 x RIDGE POLES, LENGTH 07 FEET AND 03 x STANDING POLES, LENGTH: 07- FEET). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ± 02 MM & THICKNESS: 02 MM ± 0.50 MM. b. IRON PEGS: QTY 22 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2-MM AND MILD STEEL PIN QTY 12 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 22 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NYLON/COTTON & DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 03 KGS, WITH WOODEN HANDLE & LENGTH 1.5 FEET. e. FLAPPER FOR GROUND: MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 1.5 x 1.5 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 02 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 01 x BAG FOR THE TENT AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
50	DGT107050	NO DATA AVAILABLE	010050000008 6 / PLY WOOD GD-I, 9PLY (CORE AND INNER PLIES OF POPLAR AND BOTH FACE & BACK VENEER OF GURJAN 0.6 MM) TYPE OF BOND INT		96 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> SIZE LENGTH 8FEET WIDTH 4FEET THICKNESS 19MM Specification 1. Moisture tent BS EN 322 : 1993 2. Bonding quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993 <u>GENERAL SPECIFICATION -</u> SIZE LENGTH 8FEET WIDTH 4FEET THICKNESS 19MM Specification 1. Moisture tent BS EN 322 : 1993 2. Bonding quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993	
51	DGT107045	NO DATA AVAILABLE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	96 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Width=4- FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER. GENERAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
52	DGT106 969	NO DATA AVAILAB L E	010050000001 5 / PLY WOOD GRADE-1, 5 PLY		96 / SQ FEET	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION -</u> SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) <u>GENERAL SPECIFICATION</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment.	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											- SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
53	DGT106 964	NO DATA AVAILAB E	010050000002 1 / Ply wood GD-II, 3 ply (core and inner plies of Popular SIZE: L=8' W=4' TH=03MM		1340 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - DESCRIPTION/ SIZES</u> Ply wood GD-II, 3 ply (core and inner plies of Popular and both face and back veneer of Mersawa (0.6MM) type of bond INT (phenolic/ aminoplastic), treated with preservative. Size: L = 8? W = 4? Th = 03 MM BS EN 322 : 1993 2. Bonding Quality: 1. BS 314-1 : 2004 2. BS EN 314-2: 1993 3. Glue: BS 1203 : 1979 4. Preservation: BS 4072 : 1999 5. Physical evaluation: BS 6566-6 : 1985 6. Density: BS EN 323 : 1993 <u>GENERAL SPECIFICATION - DESCRIPTION/ SIZES</u> Ply wood GD-II, 3 ply (core and inner plies of Popular and both face and back veneer of Mersawa (0.6MM) type of bond INT (phenolic/ aminoplastic), treated with preservative. Size: L = 8? W = 4? Th = 03 MM BS EN 322 : 1993 2. Bonding Quality: 1. BS 314-1 : 2004 2. BS EN 314-2: 1993 3. Glue: BS 1203 : 1979 4. Preservation: BS 4072 : 1999 5. Physical evaluation: BS 6566-6 : 1985 6. Density: BS EN 323 : 1993	
54	DGT105 609	NO DATA AVAILAB E	010050000002 9 / Ply wood, Marine All Shesham, 13- Ply, GD-II,		100 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(WBP, Treated with Preservative) Size: L=8FT, W=4FT, TH=25MM, (Core inner plies & veneer) (Wood Should be all Shesham)								METERGENERAL SPECIFICATION _1. density of plywood marine: may be 560 kgs per cubic meter 2. bs 1088 part i & ii. 3. DENSITY OF TIMBER SHEESHAM= 560 KGS PER CUBIC METER	
55	DGH105295		712599129769 4 / ANGLE POSTS STORAGE SHELVING 123		50 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material : Steel/ Aluminum Length: 6 feet to 24 feet Width: 02" to 6" Angle : 90 Degrees (standard) Thickness: ¼" to 1" Size: 2x2x ¼" (50.8 x50.8x6.35mm) 2x4x ¼" (50.8 x101.6.8 x 6.35 mm) 3x3x ½" (76.2 x76.2 x 12.7mm) MATERIAL GRADE SS 400 GENERAL SPECIFICATION - Material : Steel/ Aluminum Length: 6 feet to 24 feet Width: 02" to 6" Angle : 90 Degrees (standard) Thickness: ¼" to 1" Size: 2x2x ¼" (50.8 x50.8x6.35mm) 2x4x ¼" (50.8 x101.6.8 x 6.35 mm) 3x3x ½" (76.2 x76.2 x 12.7mm) MATERIAL GRADE SS 400	
56	DGD106884	NO DATA AVAILABLE	003550000045 2 / UTENSILS COOKINGALUM O/D 10" TO 10.5" "H 4" TO 5.5" TH 12 SWH WITH COVER		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd) DIMENSION: O/D 10" to 10.5" "H 4" to 5.5" TH 12 SWg ALUMINIUM GRADE 3003, 1100, 2024 AND 5052 GENERAL SPECIFICATION - Food Grade Aluminum Alloy 100% Free from Lead (Pb) and Cadmium (cd) DIMENSION: O/D 10" to 10.5" "H 4" to 5.5" TH 12 SWg ALUMINIUM GRADE 3003, 1100, 2024 AND 5052	
57	DGD106922	NO DATA AVAILABLE	003250000011 9 / BASIN SUGAR STAINLESS STEEL		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
58	DGD106880	NO DATA AVAILABLE	0035500000507 / STRAINERSRI CE FOR POTS ALU 20X10 INCH		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kg GENERAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kg	
59	DGD106757	NO DATA AVAILABLE	00355000000454 / UTENSIL COOKING ALUMINIUM WITH COVER O/D 16-17", INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESS 10 SWG		8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD) GENERAL SPECIFICATION - Aluminium Grade 1100, 3003, 2024 and 5052 Aluminium Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD)	
60	DGD106885		00315460000293 / PLATE SOUP DEEP 9" (22CM) GOLDEN CRESTED		15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
61	DGD98945		00355460000614 / POT ALU 15/7" WITH COVER		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 200 TO 250 LBS GENERAL SPECIFICATION - 200 TO 250 LBS	
62	DGD98956		00355460000616 / POT ALU 20X10" WITH COVER		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - 200 TO 250 LBS CAPACITY GENERAL SPECIFICATION - 200 TO 250 LBS CAPACITY	
63	DGD106918	NO DATA AVAILABLE	00325000000162 / SPOON DESSERT STAINLESS STEEL PN CRESTED		100 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - stainless steel grade 316 (used in marine environment and bio medical implants) GENERAL SPECIFICATION - stainless steel grade 316 (used in marine environment and bio medical implants)	
64	DGD106913	NO DATA AVAILABLE	00325000000171 / SPOON TABLE MEDIUM S/STEEL		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - pn crest is to be embossed. specs : stainless steel grade 316 GENERAL SPECIFICATION - pn crest is to be embossed. specs : stainless steel grade 316	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
65	DGD106927	NO DATA AVAILABLE	003450000023 9 / DISHES MEAT E W FLAT 16" BLUE CRESTED		5 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
66	DGT107044	NO DATA AVAILABLE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		8 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)</u> <u>GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)</u>	
67	DGT107121	NO DATA AVAILABLE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		20 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)</u> <u>GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)</u>	
68	DGT105783	MIL-L-2594D	010050000009 4 / TIMBER FIR DOUGLAS, WELL SEASONED & IMPORTED SAWN.		30 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SIZE: LENGTH=38 FEET, WIDTH=6-1/2 INCH, BREADTH=6-1/2 INCH SPECIFICATION MIL-L-2594D</u> TECH SPECIFICATION IS ATTACHED WITH DOCUMENTS <u>GENERAL SPECIFICATION - SIZE: LENGTH=38 FEET, WIDTH=6-1/2 INCH, BREADTH=6-1/2 INCH SPECIFICATION MIL-L-2594D</u> TECH SPECIFICATION IS ATTACHED WITH DOCUMENTS	
69	DGT106967		041554600431 2 / SHEET FORMICA WHITE 4.X4. X1/16"		2 / SHEET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
70	DGE97482	NO DATA AVAILABLE	0461546004602 / BOX FIRST AID 728 MS		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	DGE101762	1-401-47845	8305991252223 / COTTON CLOTH		50 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 100 % Cotton 100 % Color White 100 % Pieces 1 x 1 Feet 100 % Lint Free GENERAL SPECIFICATION - 100 % Cotton 100 % Color White 100 % Pieces 1 x 1 Feet 100 % Lint Free	
72	DGE106971	DEFSTAN 83-48	8305999427225 / CLOTH CALICO		20 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DGE107054	565665	5340705246111 / leatherite for wallpaper		3000 / SQ FEET	565665					TECHNICAL SPECIFICATION - leatherite wallpaper sheets GENERAL SPECIFICATION - leatherite wallpaper sheets	
74	DGH104472	SX 52-2-P	3610725344694 / POSITIVE PLATES FOR HEIDEBERG OFFSET PRINTING MACHINE SPEED MASTER SX 52-2-P SIZE 525 x 459 x 0.1mm		1000 / EACH/NUMBER	SX 52-2-P					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
75	DGT106966	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	15 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
76	DGT107047	NIL	5510705199134 / KAIL WOOD	KAIL WOOD (TIMBER)	5 / CUBIC	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SLEEPER GRADE-A (LOCAL)		FOOT						WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
77	DGH103 343	LNKCB151 520S	3020PK520265 0 / CROSS BRACING 20' X 20"	RACK	15 / UNIT	NIL	NIL	3RD FLOOR 83C, PHASE 2, EXTENSION, MAIN NATIONAL HIGHWAY DEFENCE KARACHI, 021538726		HABIB & SONS	<u>TECHNICAL SPECIFICATION</u> - Profile: Type-Square Size: 15mm x 15mm Surface Finish: RAL 5010/ Powder Coated Material: SS400 Yield Strength: 245 16mm Tensile Strength: 400-510 mpa Shim plate: 1 Anchor bolts: M12x110x2 <u>GENERAL SPECIFICATION</u> - Profile: Type-Square Size: 15mm x 15mm Surface Finish: RAL 5010/ Powder Coated Material: SS400 Yield Strength: 245 16mm Tensile Strength: 400-510 mpa Shim plate: 1 Anchor bolts: M12x110x2	
78	DGH105 296	LNKPN201 510	3020PK520265 1 / PINS	RACK	100 / UNIT			3RD FLOOR 83C, PHASE 2, EXTENSION, MAIN NATIONAL HIGHWAY DEFENCE KARACHI, 021538726		HABIB & SONS	<u>TECHNICAL SPECIFICATION</u> - YIELD STRENGTH: 245MPA 16MM MATERIAL: SS400 TENSILE STRENGTH: 400-510MPA THICKNESS: 1.3MM SURFACE FINISH: GALVANIZED/POWDER COATED HEXAGON NUT AND BOLT: M10*80*2 <u>GENERAL SPECIFICATION</u> - YIELD STRENGTH: 245MPA 16MM MATERIAL: SS400 TENSILE STRENGTH: 400-510MPA THICKNESS: 1.3MM SURFACE FINISH: GALVANIZED/POWDER COATED HEXAGON NUT AND BOLT: M10*80*2	
79	DGE101 638	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD	PCB FABRICATION	58 / EACH/NUMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K, 4th Floor, P.E.C.H.S Block-6, Shara-e-Faisal		GERMANY	<u>TECHNICAL SPECIFICATION</u> - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER +	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COMPLAINT LAB COATS.					Karachi Tele No.021-34302153-4			33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION</u> - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
80	DGH103014		952070513605 1 / ANGLE STEEL BULB BAR 200MM X 09MM	DOCK,S HULL	30 / METER	NO DATA AVAILABLE		PK	M/S RUBY TRADER S IRON & STEEL SHERSH AH RD KARACHI -2573339		<u>TECHNICAL SPECIFICATION</u> - BSEN:10025-2/2004, GD: S 275 JR <u>GENERAL SPECIFICATION</u> - BSEN:10025-2/2004, GD: S 275 JR	
81	DGE102290	10MM	597070513347 6 / GLASS SLEEVING 10MM	MOTOR WINDING FOR CABLE	12 / EACH/NUMBER	NO DATA AVAILABLE		PK	GREEN WAY ELECTRIC STORE SHOP NO.1-5 ARAMBA GH KARACHI		<u>TECHNICAL SPECIFICATION</u> -- <u>GENERAL SPECIFICATION</u> --	
82	DGE106848	LOCAL MADE	042270516014 7 / CARPET RUNNER JAI NAMAZ	JAI NAMAZ SUF	100 / FOOT			LOCAL SOURCE:BOLTON MARKET KARACHI.	LOCAL SOURCE: BOLTON MARKET KARACHI		<u>TECHNICAL SPECIFICATION</u> - LOCAL SOURCE:BOLTON MARKET KARACHI. Carpet Runner Jai Namaz (authorized quantity 200 running feet) 01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand. <u>GENERAL SPECIFICATION - LOCAL SOURCE:</u> BOLTON MARKET KARACHI. Carpet Runner Jai Namaz (authorized quantity 200 running feet) 01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand.	
83	DGB103950	DIA 32MM	6610785136660 / METALIC WIRE	2500M3 TRAILING SUCTION DREGER	45 / METER	NO DATA AVAILAB LE		CH	DANYAN G SHIP RUBBER FACTOR Y OF CHINA (0511) 6232016 0086-13706101 905		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
84	DGT105610	NO DATA AVAILAB LE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB to 850 KG/CUB . METER SIZE	WOOD WORKS SHIPS&ESTAB LISHMENT	30 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER		<u>TECHNICAL SPECIFICATION -</u> SIZE Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB <u>GENERAL SPECIFICATION -</u> SIZE Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			L:8' W: 4' TH: 6MM, MOISTURE RESISTANT						MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.			
85	DGT105700	NO DATA AVAILABLE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB TO 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	10 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		TECHNICAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB GENERAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	
86	DGT106968	NO DATA AVAILABLE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB TO 850 KG/CUB . METER SIZE L:8' W: 4' TH:	WOOD WORKS SHIPS&ESTABLISHMENT	2 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER		TECHNICAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB GENERAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6MM, MOISTURE RESISTANT						MARKET KARACHI . TEL/ FAX: +92- 21- 32776064 .MOBILE 0322- 2578654.			
87	DGH107 059		614570520821 8 / 3X95 CU/PVC/PVC FLEXIBLE 600/1000 VOLT NONARMOUR ED 233amp cable	ELECTRIC CABLE FOR SHORE SUPPLY	25 / METER	3X95 CU/PVC/ PVC	NIL	ARIF HABIB CENTRE 1ST FLOOR 23 M T KHAN ROAD KARCHI UAN: 111-CABLES(222- 537) EMAIL: info@pakistancables.com	PAKISTA N CABLE		TECHNICAL SPECIFICATION - a. Cores 3 Core 95MM b. Material Copper c. Coatings PVC/PVC Flexible d. Voltage rating 600/1000 Volts e. Ampere rating 233 Amp f. Type Non Armored g. Conductor cross sectional area 95 mm h. Number of conductor 03 j. Approximate overall diameter 55 mm to 65 mm 3X95 3 CORE 95MM COPPER/PVC/PVC FLEXIBLE 600/1000VOLT 233AMP NONARMOURED CABLE. conductor crass sectional Area: 95 mm2 (Brief detail are available in upload brusher) Number of conductor: 03 Conductor Cross sectional area/ Diameter: 11.7 mm Approximate overall diameter 55mm to 65mm Thickness of over sheet and thickness of Insulation: 3.2 mm to 3.5mm and 4.5mm to 5.5mm Specification Standard (BS, Def- Stan etc) : BS5467 GENERAL SPECIFICATION - a. Cores 3 Core 95MM b. Material Copper c. Coatings PVC/PVC Flexible d. Voltage rating 600/1000 Volts e. Ampere rating 233 Amp f. Type Non Armored g. Conductor cross sectional area 95 mm h. Number of conductor 03 j. Approximate overall diameter 55 mm to 65 mm 3X95 3 CORE 95MM COPPER/PVC/PVC FLEXIBLE 600/1000VOLT 233AMP NONARMOURED CABLE. conductor crass sectional Area: 95 mm2 (Brief	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											detail are available in upload brusher) Number of conductor: 03 Conductor Cross sectional area/ Diameter: 11.7 mm Approximate overall diameter 55mm to 65mm Thickness of over sheet and thickness of Insulation: 3.2 mm to 3.5mm and 4.5mm to 5.5mm Specification Standard (BS, Def-Stan etc) : BS5467	
88	DGH107 120		614570520821 8 / 3X95 CU/PVC/PVC FLEXIBLE 600/1000 VOLT NONARMOUR ED 233amp cable	ELECTRIC CABLE FOR SHORE SUPPLY	25 / METER	3X95 CU/PVC/ PVC	NIL	ARIF HABIB CENTRE IST FLOOR 23 M T KHAN ROAD KARCHI UAN: 111-CABLES(222- 537) EMAIL: info@pakistancables.com			<u>TECHNICAL SPECIFICATION - a.</u> Cores 3 Core 95MM b. Material Copper c. Coatings PVC/PVC Flexible d. Voltage rating 600/1000 Volts e. Ampere rating 233 Amp f. Type Non Armored g. Conductor cross sectional area 95 mm h. Number of conductor 03 j. Approximate overall diameter 55 mm to 65 mm 3X95 3 CORE 95MM COPPER/PVC/PVC FLEXIBLE 600/1000VOLT 233AMP NONARMOURED CABLE. conductor crass sectional Area: 95 mm2 (Brief detail are available in upload brusher) Number of conductor: 03 Conductor Cross sectional area/ Diameter: 11.7 mm Approximate overall diameter 55mm to 65mm Thickness of over sheet and thickness of Insulation: 3.2 mm to 3.5mm and 4.5mm to 5.5mm Specification Standard (BS, Def-Stan etc) : BS5467 <u>GENERAL SPECIFICATION - a.</u> Cores 3 Core 95MM b. Material Copper c. Coatings PVC/PVC Flexible d. Voltage rating 600/1000 Volts e. Ampere rating 233 Amp f. Type Non Armored g. Conductor cross sectional area 95 mm h. Number of conductor 03 j. Approximate overall diameter 55 mm to 65 mm 3X95 3 CORE 95MM COPPER/PVC/PVC FLEXIBLE 600/1000VOLT 233AMP NONARMOURED CABLE. conductor crass sectional Area: 95 mm2 (Brief	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											detail are available in upload brusher) Number of conductor: 03 Conductor Cross sectional area/ Diameter: 11.7 mm Approximate overall diameter 55mm to 65mm Thickness of over sheet and thickness of Insulation: 3.2 mm to 3.5mm and 4.5mm to 5.5mm Specification Standard (BS, Def-Stan etc) : BS5467	
89	DGH105 298	PPBNRD1 61184	302070520259 6 / BIN 410* 295 * 175 * 1000W	RACKING	40 / EACH/NUMBER			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI		HABIB & SONS STEEL MAN	<u>TECHNICAL SPECIFICATION -</u> SIZE: BIN L, 410 MM* DIA, 295 MM * H, 175 MM * 1000W MATERIAL/ GRADE: P.POLYMER / 2300N.C COLUR: RED, BLUE & YELLOW WEIGHT/CAPACITY: 1025 GRAM/ 70 KGS <u>GENERAL SPECIFICATION</u> _SIZE: BIN L, 410 MM* DIA, 295 MM * H, 175 MM * 1000W MATERIAL/ GRADE: P.POLYMER / 2300N.C COLUR: RED, BLUE & YELLOW WEIGHT/CAPACITY: 1025 GRAM/ 70 KGS	
90	DGB105 903		028259571212 9 / PIPING- COPPER- ALLOY EXT DIA MAX 4.184"MIN 4.178"INT DIA 4"		6 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
91	DGE106 961	NO DATA AVAILABLE	035059571324 4 / SPUN YARN SISAL "S" TWIST ROT PROOFED, 3/20 YARN, LENGTH PER COIL 811+-5% (FM)		10 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - BS-2052/65 TABLE 27</u> <u>GENERAL SPECIFICATION - BS-2052/65 TABLE 27</u>	
92	DGE106 965		035059571324 7 / SPUN YARN SISAL S TWIST R. FROOFED		10 / POUND						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6/20 YARN WT PER COIL 56LB									
93	DGE106 962		035059571324 8 / SPUN YARN SISAL S TWIST R. FROOFED 2/40 YARN WT 56LBLG 2430FM	YARN 2 , LENGTH PER COIL 2430 FM, RUNNAGE	10 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DGE106 995	NO DATA AVAILABLE	035059571311 8 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875") (5MM)		240 / FATHOM	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 120 FATHOMS. 8. REQUIREMENT OF VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/ RN/RELATED COUNTRY MOD. 10. VALID TEST CERTIFICATE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. OEM: M/S OCEAN SAFETY LTD UK AND M/S COTESI UK <u>GENERAL SPECIFICATION</u> - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554:2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 120 FATHOMS. 8. REQUIREMENT OF VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/ RN/RELATED COUNTRY MOD. 10. VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. OEM: M/S OCEAN SAFETY LTD UK AND M/S COTESI UK	
95	DGB104 429		028359571144 0 / ROD NAVAL BRASS, RD DIA 0.25 inch, WT PER, FT 18LBS		24 / METER						TECHNICAL SPECIFICATION - specifications BSEN 12163 of 2011 material grade: CW712 MATERIAL CONDITION: M RUNNING LENGTH (MIN): 02 METER GENERAL SPECIFICATION - specifications BSEN 12163 of 2011 material grade: CW712 MATERIAL CONDITION: M RUNNING LENGTH (MIN): 02 METER	
96	DGB104 768		028359571144 0 / ROD NAVAL BRASS, RD DIA 0.25 inch, WT PER, FT 18LBS		8 / METER						TECHNICAL SPECIFICATION - specifications BSEN 12163 of 2011 material grade: CW712 MATERIAL CONDITION: M RUNNING LENGTH (MIN): 02 METER GENERAL SPECIFICATION - specifications BSEN 12163 of 2011 material grade: CW712 MATERIAL CONDITION: M RUNNING LENGTH (MIN): 02 METER	
97	DGB978 57		028359571145 2 / ROD NAVAL BRASS RD DIA.1.62 INCH PT PER MTR 11.52 KG		1 / METER						TECHNICAL SPECIFICATION - SPEC.2874, CZ 112M DIA.1.62 INCH PT PER MTR 11.52 KG GENERAL SPECIFICATION - SPEC.2874, CZ 112M DIA.1.62 INCH PT PER MTR 11.52 KG	
98	DGB995 01	SPEC BS 2874 CZ 112M	028359571145 4 / ROD NAVAL BRASS RD DIA1-7/8" WT/FT 10.24LB SPEC BS2874 CZ112M	GENERAL USE	1 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
99	DGB963 66		028359571145 5 / ROD NAVAL BRASS DIA 2 INCH (WT PER FT 11.72 LB)		6 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance GENERAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.	
100	DGB104 804		028359571147 4 / SHEET- NAVAL- BRASS- ANNEALED 48		0.25 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340 <u>GENERAL SPECIFICATION -</u> Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
101	DGB104 545		021259571028 3 / BAR STEEL CARBON HOT ROLLED FLAT 04"X3/8"WT PER FT 5.10 LBS		10 / METER						<u>TECHNICAL SPECIFICATION -</u> RELEVANT SPECS i,e BS 970 EN 3A <u>GENERAL SPECIFICATION -</u> RELEVANT SPECS i,e BS 970 EN 3A	
102	DGB105 902		021259571028 3 / BAR STEEL CARBON HOT ROLLED FLAT 04"X3/8"WT PER FT 5.10 LBS		50 / METER						<u>TECHNICAL SPECIFICATION -</u> RELEVANT SPECS i,e BS 970 EN 3A <u>GENERAL SPECIFICATION -</u> RELEVANT SPECS i,e BS 970 EN 3A	
103	DGB103 083		021259571069 9 / BAR STEEL CORROSION RESISTING H/R RD 0.50		18 / METER						<u>TECHNICAL SPECIFICATION -</u> material grade: SS316L <u>GENERAL SPECIFICATION -</u> material grade: SS316L	
104	DGB103 311		021259571069 9 / BAR STEEL CORROSION RESISTING H/R RD 0.50		6 / METER						<u>TECHNICAL SPECIFICATION -</u> material grade: SS316L <u>GENERAL SPECIFICATION -</u> material grade: SS316L	
105	DGB103 262		026759521328 1 / PIPING STEEL GALV SEAMLESS, EXT DIA: 60.3 mm,WALL THKNESS: 3.6 mm,N/BORE: 50.8mm, running length	GENERAL USE	70 / METER						<u>TECHNICAL SPECIFICATION -</u> 1. BSEN:10216-2 OF 2019 2. BS EN ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships. <u>GENERAL SPECIFICATION -</u> 1. BSEN:10216-2 OF 2019 2. BS EN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6 meter								ISO 10240 FOR GALVANIZING STEEL GRADE: P265GH Galvanizing THICKNESS of 55 um on inside and outside of pipe is recommended. Pipe is utilized for fabrication of guard/ hand rails on PN Ships.	
106	DGH104 320		021159230669 5 / SHEET STEEL CARBON 2440X910X5M M		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DGE105 685	NIL	035059923712 8 / ROPE NYLON, HAWSERLAID, Z-LAY, 3- STRANDS, NOM DIA: 20MM, CIRC: 2.50 INCH, TYPE: 1, MINIMUM BREAKING LOAD: 8.3 TONS	MIN BRKG STRENGTH UNIT OF AVAILABILITY	240 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
108	DGB99110		0273790004114 / CUTTER INSULATION REMOVING DIAMETER CAPACITY 0.744IN	USE; PYROTENAX CABLE	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
109	DGH103240	SPEC:BS 826	0281594559636 / Panel storage & Display Shelving		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - GREY 63"H X 18.25" W 3XSIDES SHEET METALIC. SIZE 3,63"H X 18 1/4"NOMINAL BAY DEPTH GENERAL SPECIFICATION - GREY 63"H X 18.25" W 3XSIDES SHEET METALIC. SIZE 3,63"H X 18 1/4"NOMINAL BAY DEPTH	
110	DGE105687	NIL	0350599237131 / ROPE NYLON HAWSERLAID, 3-STRAND, Z-LAY TYPE-I, SIZE: CIRC 4", NOM DIA: 32MM	BRKG STRENGTH UNIT OF AVAILABILITY 322LB	120 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
111	DGE106 973		033059571326 6 / TWINE HEMP PACKING MEDIUM 3STRD POLISHE MIN		30 / KILOGR. AMME						<u>TECHNICAL SPECIFICATION - (1)</u> 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BKG STRGTH 100LB								3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses. <u>GENERAL SPECIFICATION</u> - (1) 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses.	
112	DGB105383		025770128378 3 / BOLT MACHINE BRASS BSW HEX HD SZ 1.000X1. 750X4.000 IN		8 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
113	DGB106003		026359414970 4 / SHACKLE STRAIGHT TO SCREW FOR RIGGING		65 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
114	DGB75451	NO DATA AVAILABL	024859129614 9 / STEEL	NAL DIMENSIONS:	4 / EACH/N						<u>TECHNICAL SPECIFICATION</u> - a. Complete Item/ Store	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	SAFE FITTED WITH COMBINATION LOCK	23-1/2	UMBER						DESCRIPTION: Steel Safe fitted with Combination LOCK b. Gauge : Outer 16 SWG Inner 16 SWG c. Size/ dimension: Length/ Height 22 Inch Width 20 Inch Depth 18 Inch d. Door: Single e. No. of shelves: 02 f. No. of Levers: 01 g. Lock Type: Combination + Key/ Digital Lock h. Fire Retardant: Yes <u>GENERAL SPECIFICATION</u> - a. Complete Item/ Store DESCRIPTION: Steel Safe fitted with Combination LOCK b. Gauge : Outer 16 SWG Inner 16 SWG c. Size/ dimension: Length/ Height 22 Inch Width 20 Inch Depth 18 Inch d. Door: Single e. No. of shelves: 02 f. No. of Levers: 01 g. Lock Type: Combination + Key/ Digital Lock h. Fire Retardant: Yes	
115	DGB100963	SKF 6208Z	0269599500114 / BEARING BALL JOURNAL SKF 6208Z 040X080X18MM	SUPPLY&EXH AUST FAN	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
116	DGD106921		0032500032017 / SPOON SALT FOR OCNS		4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Size: 2.5 to 3 ml Color: Silverware Length: 6.7" Diameter: 1.1" Width: 1" Made with stainless steel Material S/S 304/316 FOOD GRADE NON Magnetic (LOCAL) size and material grade: ss 304/316 (food grade) <u>GENERAL SPECIFICATION</u> - Size: 2.5 to 3 ml Color: Silverware Length: 6.7" Diameter: 1.1" Width: 1" Made with stainless steel Material S/S 304/316 FOOD GRADE NON Magnetic (LOCAL) size and material grade: ss 304/316 (food grade)	
117	DGB105997	(SIM)	0257709411504 / NUT-PLAIN-HEXAGON (BRASS) THREAD UNF		32 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SZ .375"LH . 350"									
118	DGH105 923		028150281166 0 / ANGLE STEEL DEXION SIZE 10-1/4.X1-1/2X2-1/2"X14 SWG		36 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
119	DGD106 883	NO DATA AVAILAB E	003550000045 1 / UTENSILS COOKINGALU M O/D5.35" H2.5" TH 18 SWG WITH COVER		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD) GENERAL SPECIFICATION - Material Aluminium Alloy Food Grade,100% Free from lead (PB) and Cadmium (CD)	
120	DGD106 928	NO DATA AVAILAB E	003154600077 1 / DISH VEGETABLE (DONGA) GOLDEN CRESTED		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - (Ceranic) with (lid) cover GENERAL SPECIFICATION - (Ceranic) with (lid) cover	
121	DGB103 017		021259571004 7 / BAR-STEEL-CARBON-COLD-FINISHED-1.37 INCH		60 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DGB955 62	NTER SUNK SLOT DRIVE SPEC BS1210	026659000022 6 / SCREW WOOD BRASS27 TONS/SQUAR E FALT CSK SLOT IN MTS DRIVE HD 7G LG 0.750 IN		1931 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
123	DGE107 053	NO DATA AVAILAB E	033054600448 4 / HEAVING LINE 06MM L50MM 466MS	MSI	1260 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
124	DGE985 72	NO DATA AVAILAB E	046150000679 2 / CHALK	W/T DOORS & FIT	20 / KILOGR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	WHITE SOFT		AMME						SPECIFICATION - NO DATA AVAILABLE	
125	DGE97089	NO DATA AVAILABLE	0461500006792 / CHALK WHITE SOFT	W/T DOORS & FIT	217 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
126	DGE74005	621100/3068.184	4220795229562 / FINS SWIM RUBBER BLACK	FOR DIVING	11 / PAIR						TECHNICAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES, COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95LBs(2.25Kg, MADE USA. GENERAL SPECIFICATION - Brand Name: Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium BRAND NAME: SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES, COLOUR-BLACK, MANUFACTURE-SCUBA-PRO, WEIGHT-4.95LBs(2.25Kg, MADE USA.	
127	SGB104142	BR3013-SHEET3.1.2	4730995311379 / FLANGE PIPE STEEL ROUND 2		45 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Specification: flange pipe steel round 2, bore 2 inch. b. Dimension: Inner Dia 2 inch (51 mm), c. Outer Dia: 5 inch (125 mm) and d. thickness: 13 mm. GENERAL SPECIFICATION - a. Specification: flange pipe steel round 2, bore 2 inch. b. Dimension: Inner Dia 2 inch (51 mm), c. Outer Dia: 5 inch (125 mm) and d. thickness: 13 mm.	
128	DGE97257		5350994616829 / STEEL WOOL 1 LB PER BALLS 50 BALLS PER CARTON GRADE-3	FOR GENERAL USE	16 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
129	DGE97115		5350994616829 / STEEL	FOR GENERAL	6 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WOOL 1 LB PER BALLS 50 BALLS PER CARTOON GRADE-3	USE	AMME						SPECIFICATION - NO DATA AVAILABLE	
130	DGT105 707	NO DATA AVAILABL E	553070504293 3 / PLY WOOD NATURAL TEAK FINISH ONE SIDE (NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W= 4' TH=03mm to 04mm	PRESENTATIO N BOXES FOR VVIPS	160 / SQ FEET						TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mmGENERAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm	
131	DGE901 52	NO DATA AVAILABL E	562050504233 5 / TILES CERAMIC GLAZED COLOUR WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")	DECK COVERING	400 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
132	DGE102 730	9-27052	626001074423 0 / LIGHT CHEMILUMINE SC		600 / EACH/N UMBER						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
133	DGD106 718		773070504806 1 / SAUCER TEA GOLDEN CRESTED		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
134	DGD106 925		773070504804 0 / DISH BUTTER BLUE CRESTED		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - Dish Butter (Round Shape) PN Crest and Shell on edge of dish. Material Porcelain, Size: dia 6.5CM, depth 2CM, Height: 3CMGENERAL SPECIFICATION - Dish Butter (Round Shape) PN Crest and Shell	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											on edge of dish. Material Porcelain, Size: dia 6.5CM, depth 2CM, Height: 3CM	
135	DGD106930		7730705048078 / CUP TEA BLUE CRESTED		13 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CM</u> <u>GENERAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CM</u>	
136	DGE107051	DATA AVAILABLE	0461500000152 / POLISHING-FELT ROUND		2 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch</u> <u>GENERAL SPECIFICATION - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch</u>	
137	DGE72407	NO DATA AVAILABLE	0433500000013 / FINS RUBBER FOR DIVERS.		14 / PAIR	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
138	DGE106794		8340PK5073827 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIES		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> <u>SIZE/DIMENSION</u> a. TENT SIZE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
139	DGT101 829	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	96 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
140	DGB105 498	41	203079527084 9 / 16 X 19 US FEDERAL SPECIFICATIO N DEE SHACKLE		4 / EACH/N UMBER	41					TECHNICAL SPECIFICATION - 16 X 19 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD: 6.5 TON GENERAL SPECIFICATION - 16 X 19 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD: 6.5 TON	
141	DGE105 348	30DB	8415TY520257 5 / 3M PELTOR OPTIME EARMUFFS 3M PELTER H 10A NRR 30DB		40 / EACH/N UMBER	-SAFETY		JUOOTG	PAK		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
142	DGB105 899		027779433464 4 / TOOL BOX PORTABLE 18X6X 1- 15/16IN STEEL ENAM		4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
143	DGE103 376		041459923091 1 / PACKING MATERIAL HEMP FOR		25 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FURNACE FUEL, SIZE= 1/4" SQ									
144	DGB104 676		021259571026 9 / BAR STEEL CARBON HOT ROLLED FLAT 03"X1/4"WT PER FT 2.55 LBS		125 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DGB105 648	1A2672	027579910547 3 / PICK HEAD, DIGGING TYPE, CHISEL&POINT SZ.4.50LBS EYE, UNIVERSAL NO2		15 / EACH/NUMBER						TECHNICAL SPECIFICATION - STANDARD/SPECIFICATION=BS14 21TABLE-2(AS PER BR320D) GENERAL SPECIFICATION - STANDARD/SPECIFICATION=BS14 21TABLE-2(AS PER BR320D)	
146	DGB105 898		027379000411 4 / CUTTER INSULATION REMOVING DIAMETER CAPACITY 0.744IN	USE; PYROTENAX CABLE	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
147	DGE102 562	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
148	DGB105 385		025770128378 2 / BOLT MACHINE BRASS BSW HEX HD TPI 8 SZ 1.000X3. 000X2.000 IN		12 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - material grade of brass is naval brass (c46400) 60 % copper, 39.2% zinc and 0.8% tin <u>GENERAL SPECIFICATION</u> - material grade of brass is naval brass (c46400) 60 % copper, 39.2% zinc and 0.8% tin	
149	DGB105 999		025770128378 3 / BOLT MACHINE BRASS BSW HEX HD SZ 1.000X1. 750X4.000 IN		8 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
150	DGB105882		0263594149704 / SHACKLE STRAIGHT TO SCREW FOR RIGGING		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
151	DGB105883	NO DATA AVAILABLE	0263590001108 / SCREW BOTTLE FOR AERIAL WT 1.06252 BS		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
152	DGB106191	NO DATA AVAILABLE	0262594195271 / SWIVEL-WITH-THIMBLE-LENGTH 2.25"-DEP. 50"		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
153	DGH105927		0281591297450 / SHELF STORAGE		150 / EACH/NUMBER						TECHNICAL SPECIFICATION - length 35.687 inches width 18 inches thickness 1.187 grade ss 400 material iron steel GENERAL SPECIFICATION - length 35.687 inches width 18 inches thickness 1.187 grade ss 400 material iron steel	
154	DGB105666	NO DATA AVAILABLE	0264594481524 / FUNNEL-OIL-FILLING	DUST BIN PASTIC 3.250 CU FT	38 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
155	DGE106982	CM6538-000	5970705044352 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		60 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Yes	
156	DGE106891	NIL	792070510179 1 / BROOM NYLON SIZE:1. X2"(BRUSH NYLON)		3 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
157	DGE105427	NIL	792070510179 1 / BROOM NYLON SIZE:1. X2"(BRUSH NYLON)		3 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
158	DGB106193	NO DATA AVAILABL E	026850000003 6 / AVERY- SCALE- PLATFORM- NO3205CAPA CITY250KG SELF INDICATING	AND MOUNTED ON WHEEL.SIZE OF PLATFORM24"	1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
159	DGD69267		773070504807 5 / plate Dinner 23cm blue crested (as per stock sample)		124 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material:PORCELING GENERAL SPECIFICATION - Material: PORCELIN	
160	DGE107143		8340PK507382 7 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIE S		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM $\pm$ 02 MM & THICKNESS 02 MM $\pm$ 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM $\pm$ 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET ($\pm$ 3 INCH) b. WALL HEIGHT: 06 FEET ($\pm$ 2 INCH) c. HEIGHT OF TENT: 12 FEET ($\pm$ 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
161	DGE98186	PD-87066	841501013738 4 / GLOVES CHEMICAL		20 / PAIR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
162	DGE107139	NO DATA AVAILABLE	045150000001 6 / TAPE- WHITE- COTTON		150 / YARD	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
163	DGE106904	NO DATA AVAILABLE	933070505435 4 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PN CREST	9 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
164	DGE105641	NIL	934073100099 5 / E-GLASS FIBER (POWDER) CHOPPED STRAND MAT	GRP BOATS	50 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2 GENERAL SPECIFICATION - BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2	
165	DGE101959		614579502372 4 / CABLE TIE 2.5 MM NYLON BLACK	TX/RX VRM	100 / PACKET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
166	DGE106801		711070511488 8 / master AURA LOW BACK REVOLVING CHAIR	MASTER OFFICE CHAIR	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240GENERAL <u>SPECIFICATION</u> - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240	
167	DGE106 905	565665	534070524611 1 / leatherite for wallpaper		3000 / SQ FEET	565665					TECHNICAL SPECIFICATION - leatherite wallpaper sheets GENERAL SPECIFICATION - leatherite wallpaper sheets	
168	DGE106 985	565665	534070524611 1 / leatherite for wallpaper		3000 / SQ FEET	565665					TECHNICAL SPECIFICATION - leatherite wallpaper sheets GENERAL SPECIFICATION - leatherite wallpaper sheets	
169	DGB105 500	B 34	204079527084 7 / 22 X 26 US FEDERAL SPECIFICATION DEE SHACKLE		4 / EACH/NUMBER	B 34					TECHNICAL SPECIFICATION - 22 X 26 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD: 13 TON GENERAL SPECIFICATION - 22 X 26 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD: 13 TON	
170	DGE106 898	RB10002 local	615070526408 5 / INSULATION RUBBER MAT		183 / FOOT	NA					TECHNICAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm. GENERAL SPECIFICATION - Size: 4 x 20 feet (WxL) THICKNESS: minimum 10mm.	
171	DGB105 502	D101 M 33	202079527084 2 / RIGGING SCREW M 33		6 / EACH/NUMBER	M 33					TECHNICAL SPECIFICATION - RIIGING SCREW M 33 1- MS GALAVANIZED MATERIAL 2- ONE END FITTED WITH JAW, SAFETY NUT & BOLT WITH LOCKING PIN 3- SECOND END FITTED WITH 26 MM EYE GENERAL SPECIFICATION - RIIGING SCREW M 33 1- MS GALAVANIZED MATERIAL 2- ONE END FITTED WITH JAW, SAFETY NUT & BOLT WITH LOCKING PIN 3- SECOND END FITTED WITH 26 MM EYE	
172	DGB105 499	IDENTIFICATION MARK: 16	532579526788 9 / 28 x 32 us FEDERAL dee shackle		17 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - 28 X 32 US FEDERAL SPECIFICATION D SHACKLE, proof load 189.3 kn (19.0 ton) GENERAL SPECIFICATION - 28 X 32 US FEDERAL SPECIFICATION D SHACKLE, proof load 189.3 kn (19.0 ton)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
173	DGB106 487	22 MM SHORT LINK (65 X 30)	532579526788 7 / 22 MM SHORT LINK (65 X 30) CHAIN I/D GALVANISED 2 X 14.6 METERS 28MM DIA END LINKS EACH END		75 / METER	NA					TECHNICAL SPECIFICATION - 22 MM SHORT LINK (65 X 30) CHAIN I/D GALVANISED 2 X 14.6 METERS 28MM DIA END LINKS EACH GENERAL SPECIFICATION - 22 MM SHORT LINK (65 X 30) CHAIN I/D GALVANISED 2 X 14.6 METERS 28MM DIA END LINKS EACH END	
174	DGB105 501	44	203079527084 6 / 26 X 28 US FEDERAL SPECIFICATION DEE SHACKLE		4 / EACH/NUMBER	44					TECHNICAL SPECIFICATION - 26 X 28 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD: 17 TON GENERAL SPECIFICATION - 26 X 28 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD: 17 TON	
175	DGE106 908		042270515841 1 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	612 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI & M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTICS, SADDAR KARACHI		TECHNICAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
176	DGE975 84	NO DATA AVAILABLE	8415PK506744 2 / CLOTH PARASHUTE GRAY		400 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
177	DGT983 92	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	10 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
178	DGE769 12		047659943045 3 / BRUSH ARTISTS CAMEL HAIR SWAN SMALL EXPOSED LG 1 3/16 INCH		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
179	DGE746 94	NO DATA AVAILABL E	834050503926 2 / QANAT COMPLETE SIZE 18.X 7. OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). 2 Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON,BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.GENERAL SPECIFICATION - Length: 18 feet. Width: 7 feet. COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS in EACH Qanat: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY I.E (01 & 05). 2 Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
180	DGB78423		0273599104463 / CALIPER INSIDE SPRING JOINT 06IN (LOCAL)		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
181	DGD94218	LG-MP-9482 SR	7310735118939 / MICROWAVE OVEN-LG SHARP WAVES/DAWLANCE & TOSHIBA	MICROWAVE OVEN LG	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - capacity: 36 LITTERs GENERAL SPECIFICATION - capacity: 36 LITTERs	
182	DGB94171	NO DATA AVAILABLE	0263599236987 / THIMBLE, ROPE STEEL BS 970-EN 3A GALVANISED PEAR SHAPED OPEN TYPE WT 1.75LBS SIZE 1.25	SPEC NO DGS 5031NO.40	350 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

INVITATION TO TENDER VSD I.T DATE 11-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 26-08-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.


<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 123/2026 DATED 03-08-2026 Mutton Dressed	200 KG	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "**Commander Local Purchase**" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II

INVITATION TO TENDER VSD I.T DATE 11-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 26-08-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.


<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 124/2026 DATED 03-08-2026 Beef Dressed	300 KG	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II