

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 02-09-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE88603	ALM7140A	8415735139736 / DIVING GLOVES	DIVING	15 / PAIR	ISF PROLINE		OC	TIWAN		<u>TECHNICAL SPECIFICATION</u> - SOFT, THICK RUBBER, SIZE: NORMAL SIZE <u>GENERAL SPECIFICATION</u> - SOFT, THICK RUBBER, SIZE: NORMAL SIZE	
2	DGH103503	HO7RN-F	6145270106347 / SINGLE CORE FLEXIBLE CABLE 185MM EI4 TYPE RUBBER (EPR) COMPUND 450/750V 341 AMPS		300 / METER	ho7rn-f					<u>TECHNICAL SPECIFICATION</u> - 185MM SINGLE CORE COPPER CONDUCTOR FLEXIBLE CABLE RUBBER INSULATED (EPR COMPUND). 450/750V MOBILE 341 AMPS, FIXED 475 AMPS <u>GENERAL SPECIFICATION</u> - 185MM SINGLE CORE COPPER CONDUCTOR FLEXIBLE CABLE RUBBER INSULATED (EPR COMPUND). 450/750V MOBILE 341 AMPS, FIXED 475 AMPS	
3	DGE106140	5557 SERIES	6850715180460 / WATER CONTACT INDICATOR tape 5 X 5 MM	ADHESIVE TYPE INDICATION TAPE	10 / EACH/NUMBER	MSDS MATERIAL		3M	3M USA		<u>TECHNICAL SPECIFICATION</u> - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm) <u>GENERAL SPECIFICATION</u> - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm)	
4	DGB74261		0276789105876 / SCREWDRIVER F/POINT BLADE LG 6"		21 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TIP WIDTH 0.156 O/A LG 9.25"									
5	DGE105 683		035059571323 5 / ROPE SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH (ROUNDED IN 9-MM)		120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554. <u>GENERAL SPECIFICATION - 1.</u> MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554.	
6	DGE722 44		047659943042 2 / BRUSH ARTIST MET FER/SQU HAIR ST SPECT LG 0.750" WD 0.500"		32 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
7	DGE967 28	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE		45 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - bs 2992</u> TABLE 8, MATERIAL: POLYESTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVER TAIL MAKE/BRAND:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			EDGE WD:3", STOCK THICKNESS 0.875 INCH, EXPOSED LENGTH 3 INCH.								CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES <u>GENERAL SPECIFICATION</u> - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
8	DGE102 347	C-268	0476599430559 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		19 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8 <u>GENERAL SPECIFICATION</u> - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
9	DGE103 042		0350595713128 / ROPE NYLON, HAWSERLAID, 3-STRAND, Z-LAY, NOM DIA: 20MM, (13/16") CIRC: 2.50 INCH, TYPE-1		400 / FATHOM						<u>TECHNICAL SPECIFICATION</u> - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 120 FATHOMS. 8. REQUIREMENT OF VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY IACS MEMBER CLASSIFICATION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/ RN/RELATED COUNTRY MOD. 10. VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. OEM: OCEAN SAFETY LTD, UK AND M/S COTESI UK <u>GENERAL SPECIFICATION</u> - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554:2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 120 FATHOMS. 8. REQUIREMENT OF VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/ RN/RELATED COUNTRY MOD. 10.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. OEM: OCEAN SAFETY LTD, UK AND M/S COTESI UK	
10	DGE104081	NO DATA AVAILABLE	035059571313 2 / ROPE NYLON, 3- STRAND, CIRC: 4-INCH, DIA: 32MM		240 / FATHOM	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI <u>GENERAL SPECIFICATION - 1</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2 TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5 OEM COC REQUIRED, 6 FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7 OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8 LENGTH PER COIL: 120 FATHOM. 9 VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. 10. OEM: M/S COTESI	
11	DGB104 432		028359571147 4 / SHEET- NAVAL- BRASS- ANNEALED 48		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION: CW719 R340 GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION: CW719 R340	
12	DGH103 328		021159119995 3 / PLATE STEEL CARBON MILD BLACK 5000X1500X10 MM		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - BSEN 10025-2 OF 2019, GRADE S275 JR, THICKNESS TOLERANCE LIMIT: "CLASS C" IN TABLE 1 OF BSEN 10029 GENERAL SPECIFICATION - BSEN 10025-2 OF 2019, GRADE S275 JR, THICKNESS TOLERANCE LIMIT: "CLASS C" IN TABLE 1 OF BSEN 10029	
13	DGH105 925	NO DATA AVAILABL E	021159525927 7 / PLATE STEEL CARBON 2500X1250X04 MM W.P.SQ MTR 31.40KG	EXPOSED DECKS	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004, S 275JR GENERAL SPECIFICATION - BSEN 10025 OF 2004, S 275JR	
14	DGH105 968	070125648 4	028150281167 5 / GAS CUTTING TORCH(CUTTING) CAPACITY		1 / EACH/N UMBER	NM250 CUTTER					TECHNICAL SPECIFICATION - made: MUREX SAFFIRE UK GENERAL SPECIFICATION - made: MUREX SAFFIRE UK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			250MM									
15	DGE104 802	NIL	035059923712 8 / ROPE NYLON, HAWSERLAID, Z-LAY, 3- STRANDS, NOM DIA: 20MM, CIRC: 2.50 INCH, TYPE: 1, MINIMUM BREAKING LOAD: 8.3 TONS	MIN BRKG STRENGTH UNIT OF AVAILABILITY	220 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
16	DGE104 874	NIL	035059923712 8 / ROPE NYLON, HAWSERLAID, Z-LAY, 3- STRANDS, NOM DIA: 20MM, CIRC: 2.50 INCH, TYPE: 1, MINIMUM BREAKING LOAD: 8.3 TONS	MIN BRKG STRENGTH UNIT OF AVAILABILITY	240 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
17	DGE104 678	NIL	035059923712 9 / ROPE NYLON, HAWSERLAID, 3-STRANDS, CIRCI 3", NOM DIA: 24MM, Z- LAY, TYPE-1, MINIMUM BREAKING LOAD : 12 TONS	STRENGTH 11.800 TONS UNIT OF AVAILABILIT	120 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL</u> SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
18	DGB102748	0251-14505	025170411973 7 / FERRULE- WIRE-ROPE 1.5 INCH (12mm)		63 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> MATERIAL aluminum alloy SHAPE ELLIPSE TYPE COLOR SILVER INTERNAL WIDTH 26 MM INTERNAL HEIGHT 13 MM OUTER DIA 36 MM OUTER LENGHT 42 MM BODY THICKNESS 05 MM <u>GENERAL SPECIFICATION -</u> MATERIAL aluminum alloy SHAPE ELLIPSE TYPE COLOR SILVER INTERNAL WIDTH 26 MM INTERNAL HEIGHT 13 MM OUTER DIA 36 MM OUTER LENGHT 42 MM BODY THICKNESS 05 MM	
19	DGE97485	NSN 1370-99-9629136	422072505519 8 / HAND FLARE RED P MK 3 (USE ONLY WHEN AIRCRAFT)	SURVIVAL PACK USED FOR 20MEN LIFERAFT	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
20	DGH105929	751F00	343901056094 9 / CLEANER NOZZLE (CLEANER SET, WELDING)	GAS CUTTING AND WELDING NOZZLE	2 / SET						<u>TECHNICAL SPECIFICATION - L</u> TEC WELDING & CUTTING SYSTEMS EBENEZER <u>GENERAL</u> <u>SPECIFICATION - L TEC WELDING</u> & CUTTING SYSTEMS EBENEZER	
21	DGE106254		533000244019 2 / SHEET RUBBER		80 / FOOT						<u>TECHNICAL SPECIFICATION -</u> MILR900 <u>GENERAL</u> <u>SPECIFICATION - MILR900</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SOLID 0.125 X24X324 INCH									
22	DGE101 572	A-A-1201	535000221088 2 / PAPER ABRASIVE	FIRE FIGHTING EQUIPMENT	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DGE102 298	MWTM 95/29-1200	593572507749 1 / HEAT SHRINK SLEEVE		5 / METER						TECHNICAL SPECIFICATION - Dimensions: Size: 95/29 Expanded Diameter: 95mm Recovered Diameter: 29mm Cable Range Diameter:32-86 mm Length: 1m GENERAL SPECIFICATION - Dimensions: Size: 95/29 Expanded Diameter: 95mm Recovered Diameter: 29mm Cable Range Diameter:32-86 mm Length: 1m	
24	DGE106 164	ECW0090 3-12	593572507749 2 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SIZE 48/16 LG 1 METER		5 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
25	DGE106 279	NO DATA AVAILABLE	593572507749 4 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE, SIZE 31/8 LG, 01 METER		40 / METER						TECHNICAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B. PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224 G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT AND ABRASION. GENERAL SPECIFICATION - A. PRODUCT CATEGORY :DUAL WALL B. PRODUCT NAME: TAT-25 C. OPERATING TEMPERATURE °C: -55 TO 110 D. MIN FULL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											RECOVERY TEMPERATURE °C: 121 E. COLOR: STANDARD BLACK F. SPECIFICATION: TAT-125 SCD; RW-3032; AS23053/4, CL. 2; UL 224 G. FLAMMABILITY RATING: ASTM D26714, PROCEDURE B H. TYPICAL APPLICATION: INSULATE AND PROTECT ELECTRICAL CONNECTIONS, WIRES AND CABLES FROM ENVIRONMENTAL FACTORS LIKE MOISTURE, HEAT AND ABRASION.	
26	DGB105981	Material Grade EN 4140	0214780001043 / NUT 1M80-405 213/MB SZ 8.00 MM, Bore 8mm, Dia 14 mm	BOOSTER ENGINE L12V-180	50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - MATERIAL GRADE EN-4140 SZ 8.00 MM, BORE 8MM, DIA 14MM. GENERAL SPECIFICATION - MATERIAL GRADE EN-4140 SZ 8.00 MM, BORE 8MM, DIA 14MM.	
27	DGE103217	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	3 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS.	
28	DGE103089	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	3 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAG					TECHNICAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. GENERAL SPECIFICATION - 1. 100% POLYESTER FABRIC, WITH: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, JUNGLE CAMOUFLAGE WITH IR FUNCTIONS PROVIDING DURABILITY, ROT RESISTANCE AND WATER PROOF. 2. COLOUR= NATO STANDARD MULTI-SPECTRAL CAMOUFLAGE NETS, 3. SIZE= 6.8 x 6.8 METERS, 4. PACKING= POLYTHENE / PARACHUTE BAG IN COTTON BOX AND ALONGWITH FOLLOWING ACCESSORIES= (a). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (b). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (c). HAMMER= 01 IN NUMBER. (d). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH GI COATED 300 G/SQ METER. 5. IR RANGE= SUPPRESS THERMAL SIGNATURES IN 3-5 UM & 8-14 UM (MICROMETER) BANDS. TECHNICAL SPECIFICATION -	
29	DGB103 641	STEEL LARGE SZ	846599411126	PNS NIGRAN	4 / EACH/N							

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		W/KEY (K2575-1960)	7 / HAND CUFFS STEEL ADJUSTABLE RATCHET TYPE CHROME PLATED BRIGHT		UMBER						nullGENERAL SPECIFICATION - null	
30	DGE95820	BS 419/156	055954600536 2 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		35 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
31	DGD94576		003554600068 5 / TAWA IRON (DLT VIDE LTR ST-V/1732 DT. 06-12-92		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
32	DGE101571	5557 SERIES	685071518046 0 / WATER CONTACT INDICATOR tape 5 X 5 MM	ADHESIVE TYPE INDICATION TAPE	10 / EACH/NUMBER	MSDS MATERIAL		3M		3M USA	TECHNICAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm) GENERAL SPECIFICATION - color : white (top) / red (bottom) top film : polyester adhesive : acrylic backing : film/ paper laminate thickness : 10.2 mils (0.259mm)	
33	DGE105693	DP3574	422099522816 6 / HEAD STRAP	SWIM MASK (DIVING SET)	10 / EACH/NUMBER	NO DATA AVAILABLE		UK		MINISTRY OF DEFENCE (NAVY) EXPERIMENTAL DIVING UNIT HMS VERNON PORTSMOUTH HANTS UK	TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
34	DGB102885	10589	6525715175020 / ALUMINUM FILLER MATERIAL	WELDING EQUIPPAGE	10 / BOX			FREEDOM ALLOYS INC USA CAGE 5HMZ2 155 RAILROAD PLZ STE 1, ROYERSFORD, PA 19468, UNITED STATES	FREEDOM ALLOYS INC USA CAGE 5HMZ2 155 RAILROAD PLZ		TECHNICAL SPECIFICATION - IPC ATTACHED WITH LETTER GENERAL SPECIFICATION - IPC ATTACHED WITH LETTER	
35	DGE105691	SFF6 1	2590735175928 / POLYESTER BOAT LIFTING BELT 20000 KG LOAD	ENGINE	4 / EACH/NUMBER	NK	32568955	YONCA TURKEY LTD	YONCA		TECHNICAL SPECIFICATION - LENGTH 20 METER WLL 20000 KG BATCH NO YHTS-07-0105 TEMP -40 DEG C + 100 DEG C GENERAL SPECIFICATION - LENGTH 20 METER WLL 20000 KG BATCH NO YHTS-07-0105 TEMP -40 DEG C + 100 DEG C	
36	DGT105701	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"		60 / FOOT	NO DATA AVAILABLE		PK	TAWAKAL BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
37	DGB101854	F06DSS	4030795152993 / STAINLESS STEEL SHACKLE 06 MM DEE TYPE (S.W.L)	TAL SHIP SAILING RIG	20 / EACH/NUMBER			EURO PRODUCTS. INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL; EUROPRODUCTSINC.COM#SALES@	UK		TECHNICAL SPECIFICATION - EURO PRODUCTS. INC,TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC.COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG. GENERAL SPECIFICATION - EURO PRODUCTS. INC,TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC.COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG.	
38	DGB101857	F12DSS	4030795152992 / STAINLESS STEEL	TAL SHIP SAILING RIG	20 / EACH/NUMBER			EURO PRODUCTS. INC, TELL;206 789 6468#800 577 5877 FAX;206 784 E	UK		TECHNICAL SPECIFICATION - EURO PRODUCTS. INC,TELL;206 789 6468#800 577 5877 FAX;206	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SHACKLE 12 MM DEETYPE (S.W.L)					MAIL; EUROPRODUCTSINC. COM#SALES@			784 E MAIL;EUROPRODUCTSINC. COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG.GENERAL SPECIFICATION - EURO PRODUCTS. INC,TELL;206 789 6468#800 577 5877 FAX;206 784 E MAIL;EUROPRODUCTSINC. COM#SALES@ PARENT/SYS;TALL SHIP SAILING RIG.	
39	DGE101 591	H R 550	802000598408 0 / COVER PAINT ROLLER	PAINT ROLLER	15 / EACH/NUMBER	CAGE CODE ODRR8		FEDERAL SPECIFICATION USA CAGE CODE 81348ODRR8	FEDERAL SPECIFICATION S USA		TECHNICAL SPECIFICATION - MATERIAL FIBER , POLYESTER PILE HEIGHT 0.625 INCHES NOMINAL , NOMINAL LENGTH 7.000 INCHESGENERAL SPECIFICATION - MATERIAL FIBER , POLYESTER PILE HEIGHT 0.625 INCHES NOMINAL , NOMINAL LENGTH 7.000 INCHES	
40	DGE102 299	EM 3061	593572512993 6 / RAYCHEM HEAT SHRINK	-	2 / EACH/NUMBER			GR	GMBH GERMAN Y		TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DGE977 12	-	561099200438 6 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	193 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCR ETE UK LTD THE FLOORING TECHNOLOGIES CENTRE BOOTH LANE SANDBATCH CHESHIRE CW11 3QF UK PH:+44(0) 1270 753000 & FAX :+44 (0)1270 753333		TECHNICAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&I(M) DC&FF.GENERAL SPECIFICATION - IN DESCRIPTION ,LOCAL GOOD QUALITY ACEPTABLE, ADDED VIDE FLAG OFFICER SEA TRANING ME/251/544 DT 11 APRIL 2011.&I(M) DC&FF.	
42	DGB106 116		028350283152 1 / CADMIUM		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ANODE ROLLED LG 12 INCH WTH 8 INCH TH 3/8 INCH		UMBER						contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH <u>GENERAL SPECIFICATION</u> - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH	
43	DGB106 002		027670000363 4 / SEAL LEAD FOR SEALING COVER JOINT		19 / GROSS						<u>TECHNICAL SPECIFICATION</u> - diameter: 9mm thickness:4mm material: lead <u>GENERAL SPECIFICATION</u> - diameter: 9mm thickness:4mm material: lead	
44	DGE102 500	NO DATA AVAILABL E	045159451001 3 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	40 / METER						<u>TECHNICAL SPECIFICATION</u> - AS PER STOCK SAMPLE HELD BY CINS <u>GENERAL SPECIFICATION</u> - AS PER STOCK SAMPLE HELD BY CINS	
45	DGE106 176		034059923619 8 / BAGS CANVAS SHIP DOCUMENTS FTD 3.50" POCKET SZ. 16.00X20.00IN		6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - A. Color : Green, Gray, Navy Blue, Black B. Dimension : H: 18", W: 18", L: 36" C. Made from : Bag made with Waterproof Canvas/Fabric D. Shape : U shape for opening f. Appearance : 2 handles and shoulder strips E. Pockets Qty : 04 x pockets with Zipper F. Pocket Size : 08" x 12" <u>GENERAL SPECIFICATION</u> - A. Color : Green, Gray, Navy Blue, Black B. Dimension : H: 18", W: 18", L: 36" C. Made from : Bag made with Waterproof Canvas/Fabric D. Shape : U shape for opening f. Appearance : 2 handles and shoulder strips E. Pockets Qty : 04 x pockets with Zipper F. Pocket Size : 08" x 12"	
46	DGE105 689		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN		50 / SHEET						<u>TECHNICAL SPECIFICATION</u> - Manfr/Tech.Sponcer Code reference: DTD 5592 <u>GENERAL SPECIFICATION</u> - Manfr/Tech. Sponcer Code reference:DTD 5592	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TRANSPAREN T L X W X THIC 48"X48"X0. 250"									
47	DGH106 118	DNC S-15	021159119997 3 / MS PLATE SIZE 2500X1250X5 MM		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025.STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010.GENERAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025.STEEL GRADE:5275 JR. ALL INFOMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010.	
48	DGT862 31	NO DATA AVAILABL E	010054600229 0 / BAMBOO SIZE 28FT- 30FT LONG	DEISEL GENERATOR	30 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10- 30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREE.GENERAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10- 30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREE	
49	DGT103 961	NO DATA AVAILABL E	010050100011 8 / PLY WOOD MARINE ALL SHESHAM GD- II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIV		64 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS- 4079 type: wbp preservation by onE of the following wb-1 mark w1/3 WB- 1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM) DENSITY= 700 TO 850 KILOGRAMS PER CUBIC METER.GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by onE of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			E								W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM(±1MM) DENSITY= 700 TO 850 KILOGRAMS PER CUBIC METER.	
50	DGH106 268		021159923013 9 / PLATE STEEL CARBON SIZE 2500X1250X03 MM	HOUSE SIDE FTG	21 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> BSEN:10025/2 OF 2019, STEEL GRADE: S275 JR. special instructions: a. MILL TEST certificate (MTC) required alongwith supply. the certificate should have information on mechanical & chemical properties, steel grade, batch & heat number alongwith date. b. each plate shall have a suitable stamp at a corner indicating batch number, grade and manufacturer for case identification. c. material should be freshly rolled & free steel all defects. <u>GENERAL SPECIFICATION -</u> BSEN:10025/2 OF 2019, STEEL GRADE: S275 JR. special instructions: a. MILL TEST certificate (MTC) required alongwith supply. the certificate should have information on mechanical & chemical properties, steel grade, batch & heat number alongwith date. b. each plate shall have a suitable stamp at a corner indicating batch number, grade and manufacturer for case identification. c. material should be freshly rolled & free steel all defects.	
51	DGB954 41		021259923280 2 / BAR STEEL CORROSION RESISTING H/R RD 1.25" WT PER FT 4.209LBS		1 / METER						<u>TECHNICAL SPECIFICATION -</u> minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D) <u>GENERAL SPECIFICATION -</u> minimum running length: 06 meter STANDARD/SPECIFICATION=BS 970/EN-58J(AS PER BR320D)	
52	DGH105 921		023159571524 3 / WIRE ROPE STEEL EXTRA		100 / METER						<u>TECHNICAL SPECIFICATION -</u> Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SPECIAL GALVA LAY OF ROPE RH CIRC 3/8"								(Reference NS 320D Table 39) <u>GENERAL SPECIFICATION</u> - Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39)	
53	DGE106 224		033059571326 2 / TWINE NYLON ROPING 3 STRD NATURAL FINISH MIN BKG STRGT 50 LB		5 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed. <u>GENERAL SPECIFICATION</u> - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed.	
54	DGE104 031	NIL	035059923713 1 / ROPE NYLON HAWSERLAID, 3-STRAND, Z- LAY TYPE-I, SIZE: CIRC 4", NOM DIA: 32MM	BRKG STRENGTH UNIT OF AVAILABILITY 322LB	240 / FATHOM						<u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3 ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4 OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
55	DGE106062		035059923713 2 / ROPE NYLON, 3- STRD, CIR: 4.50", DIA 1.4375" (36- mm)		440 / METER						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
56	DGE104 080	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	240 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
57	DGB105 661	BS 1083	025770419500 8 / NUT-PLAIN-HEXAGON-THREAD-SIZE 0.750	BRASS TYPE	12 / DOZEN						<u>TECHNICAL SPECIFICATION</u> - material grade i.e SS347 bs 970, 60r7a <u>GENERAL SPECIFICATION</u> - material grade i.e SS347 bs 970, 60r7a	
58	DGB105 670		025850258120 3 / COPPER-WIRE-2-MM-DIA		10 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm ² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm ² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER <u>GENERAL SPECIFICATION - Dimension/size:</u> Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm ² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm ² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER	
59	DGB101 527	(SIM)	025770941150 4 / NUT-PLAIN-HEXAGON (BRASS) THREAD UNF SZ .375"LH . 350"		32 / DOZEN						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
60	DGB106 000	Material Grade EN 4140	025770941150 6 / NUT-PLAIN-HEXAGON-THREAD-SIZE. 625LH.550"		32 / DOZEN						<u>TECHNICAL SPECIFICATION - material specs AISI 4140(PD 970: 2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED</u> <u>GENERAL SPECIFICATION - material specs AISI 4140(PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED</u>	
61	DGE104 803	NIL	402099923713 3 / ROPE NYLON,		220 / METER						<u>TECHNICAL SPECIFICATION - a. 3 stand 40mm in Color white Nylon rope length 220 Mtr. b. Material</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO.	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HAWSERLAID, CIRC: 5-INCH, DIA: 40MM, Z-LAY, 3-STRAND,								quality top nylon fibers. c. Thickness and diameter 40mm or 5 inch. d. Length 220 Mtr commercial bulk coil. e. 3-strand or 3-ply twisted rope. f. Breaking strength 28,000 kg to 30,000 kg g. High temperature resistance then polypropylene – working temperature up-to 100c (soften temperature 170c melting temperature 215c) h. A very strong and soft to touch synthetic fiber rope which has excellent shock absorption properties for use as a towing, mooring and as berthing hawser. j. High in strength and abrasion resistance, or elongation and absorbs moisture. 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 220 meter. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - a. 3 stand 40mm in Color white Nylon rope length 220 Mtr. b. Material quality top nylon fibers. c. Thickness and diameter 40mm or 5 inch. d. Length 220 Mtr	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											commercial bulk coil. e. 3-strand or 3-ply twisted rope. f. Breaking strength 28,000 kg to 30,000 kg g. High temperature resistance then polypropylene – working temperature up-to 100c (soften temperature 170c melting temperature 215c) h. A very strong and soft to touch synthetic fiber rope which has excellent shock absorption properties for use as a towing, mooring and as berthing hawser. j. High in strength and abrasion resistance, or elongation and absorbs moisture. 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 220 meter. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
62	DGB101840	NO DATA AVAILABLE	343971504503 2 / WET WELDING ELECTRODE UW-CS-1 (1/8" OR 3.2 MM)	UNDERWATER WELDING DURING SALVAGE OPS/TRAINING	1000 / PACKAGE						TECHNICAL SPECIFICATION - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Penetration <u>GENERAL SPECIFICATION</u> - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration	
63	DGE998 92		533000618322 1 / PACKING MATERIAL SIZE 3/16".		10 / FOOT						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
64	DGE102 297	ECW0090 3-12	593572507749 2 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SIZE 48/16 LG 1 METER		3 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
65	DGE101 599	NO DATA AVAILABL E	047450000030 7 / FENDER COIR ROUND		4 / EACH/NUMBER	600MM 24" ROUND COIR BOAT FENDER					<u>TECHNICAL SPECIFICATION</u> - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER DEGRADATION.STORAGE-WET AND DRY. <u>GENERAL SPECIFICATION</u> - CONSTRUCTION-MADE FROM COIR FIBROUS MATERIAL FROM OUTER COAT OF COCONUT. MATERIAL-NATURAL COIR ROPE. LOOK-ROUND OF OBLONG SHAPE.BIODEGRADABLE- YES, WILL DECOMPOSE AND CAN BE DISPOSED OFF NORMALLY. PERFORMANCE IN WATER- NATURALLY WATER PROOF AND RESISTANCE TO SALT WATER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DEGRADATION.STORAGE-WET AND DRY.	
66	DGE105891	NIL	810501124264 5 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217-9451	STATIC SAFETY OF EQUIPMENT/C OMPONENTS	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897- 1557 <u>GENERAL SPECIFICATION -</u> ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
67	DGE106239		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIE S)	OLIVE GREEN WATERPROO F INNER LINNING OF,	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE/DIMENSION a.TENT SIZE (LENGTH & WIDTH):50 X 20 FEET (± 6 INCH) b.HEIGHT OF TENT:12 FEET (± 2 INCH) c.HEIGHT OF WALL:07 FEET (± 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850 GSM OR ABOVE WITH ROT- PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180- 200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LENGTH: 18 INCHES, THICKNESS 20 MM $\pm$2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5.PACKING REQUIRED:QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.<u>GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a.TENT SIZE (LENGTH & WIDTH):50 X 20 FEET ($\pm$ 6 INCH) b.HEIGHT OF TENT:12 FEET ($\pm$ 2 INCH) c.HEIGHT OF WALL:07 FEET ($\pm$ 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3.	



S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4.VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5.PACKING REQUIRED:QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.	
68	DGE106 167		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIE S)	OLIVE GREEN WATERPROO F INNER LINNING OF,	1/ EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE/DIMENSION a.TENT SIZE (LENGTH & WIDTH):50 X 20 FEET (± 6 INCH) b.HEIGHT OF TENT:12 FEET (± 2 INCH) c.HEIGHT OF WALL:07 FEET (± 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5.PACKING REQUIRED:QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.GENERAL	

S. No	LPR-No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - 1. SIZE/DIMENSION a.TENT SIZE (LENGTH & WIDTH):50 X 20 FEET (± 6 INCH) b.HEIGHT OF TENT:12 FEET (± 2 INCH) c.HEIGHT OF WALL:07 FEET (± 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4.VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - 1. SIZE/DIMENSION a.TENT SIZE (LENGTH & WIDTH):50 X 20 FEET (± 6 INCH) b.HEIGHT OF TENT:12 FEET (± 2 INCH) c.HEIGHT OF WALL:07 FEET (± 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4.VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SIDES OF THE TENT. 5.PACKING REQUIRED:QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.	
69	DGE98114		813570506488 2 / TAPE TRANSPAREN T ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	131 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
70	DGT105782	NO DATA AVAILABL E	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	96 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.</u> <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
71	DGB105647	NO DATA AVAILAB E	026850000006 1 / SCALE- SPRING- BALANCE-20- STONE-280- LBS		1 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow <u>GENERAL SPECIFICATION -</u> Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow	
72	DGE98108	NO DATA AVAILAB E	055978000018 7 / SLEEVE PLASTIC DIA 0.5CM		5 / ROLL	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - 1.</u> FOLLOWING DIA SLEEVES DIMENSION ETC (S,NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black <u>GENERAL</u> <u>SPECIFICATION - 1.</u> FOLLOWING DIA SLEEVES DIMENSION ETC (S, NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black	
73	DGE101972	NO DATA AVAILAB E	055978000018 5 / SLEEVE PLASTIC		5 / ROLL	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
74	DGT107665	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	85 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
75	DGD101055	NIL	7320705332802 / ROTI DOUBLE WEDGE PRESS		1 / EACH/NUMBER	latest					<u>TECHNICAL SPECIFICATION - 1.</u> Production Capacity: 1000-1400 pcs PER hour 2. roti weight: 70-100 grms 3. roti size: dia 7-9 inch 4. thickness 2mm to 3mm 5. electric motors: 1hp with variable speed controller 6. electric heater: 4000 watts 220v/50hz 7. construction: heavy duty body frame made of ms angle iron and covered with stainless steel sheets 8. Parent equipment: electric roti plant <u>GENERAL SPECIFICATION -</u> 1. Production Capacity: 1000-1400 pcs PER hour 2. roti weight: 70-100 grms 3. roti size: dia 7-9 inch 4. thickness 2mm to 3mm 5. electric motors: 1hp with variable speed controller 6. electric heater: 4000 watts 220v/50hz 7. construction: heavy duty body frame made of ms angle iron and covered with stainless steel sheets 8. Parent equipment: electric roti plant	
76	DGT107765	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	82 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
77	DGE107 269	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	50 / EACH/N UMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021- 34302153-4	GERMAN Y		<u>TECHNICAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
78	DGE859 35	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	10 / EACH/N UMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021- 34302153-4	GERMAN Y		<u>TECHNICAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω <u>GENERAL SPECIFICATION - a.</u> Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	
79	DGE106346	10563	0413705139213 / UPVC BAND 1 INCH	STANDBY ECHO SOUNDER	24 / EACH/NUMBER	NO DATA AVAILABLE		PK	DIGI TECH, SHOP NO.2 NEW MEMON CHAMBERS, ALTAH HUSSAIN ROAD DENSO HALL KARACHI -74000. TEL:021-2639514		<u>TECHNICAL SPECIFICATION --</u> <u>GENERAL SPECIFICATION --</u>	
80	DGT107560	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"		3540 / FOOT	NO DATA AVAILABLE		PK	TAWAKAL BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		<u>TECHNICAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required <u>GENERAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
81	DGE107165	BS-6099	4710705174804 / PVC PIPE 1	SRE SYSTEM	3000 / FOOT			A-10/C MANGHOPIR ROAD SITE KARACHI, PAKISTAN PH-92 21 32570377-477,32562173-32550417 FAX:+92 21 32563038. CELL:0345-8289334 . E-MAIL:asim	pakistan		<u>TECHNICAL SPECIFICATION - A-</u> 10/C MANGHOPIR ROAD SITE KARACHI,PAKISTAN PH-92 21 32570377-477,32562173-32550417 FAX:+92 21 32563038. CELL:0345-8289334 . E-MAIL:asim @pakarab.net,info@pakarab.net Complete item/store description with packing details dimension size. PVC Pipe 2" width, 10' length. Detailed Specifications / Acceptance Criteria : PVC Pipe 2" inside diameter <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								@pakarab.net, info@pakarab.net			SPECIFICATION - A-10/C MANGHOPIR ROAD SITE KARACHI, PAKISTAN PH-92 21 32570377-477, 32562173-32550417 FAX: +92 21 32563038. CELL: 0345- 8289334. E-MAIL: asim @pakarab. net, info@pakarab.net Complete item/ store description with packing details dimension size. PVC Pipe 2" width, 10' length. Detailed Specifications / Acceptance Criteria : PVC Pipe 2" inside diameter	
82	DGT107 667	NO DATA AVAILABL E	934070514992 2 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTAB LISHMENT	20 / SHEET	NO DATA AVAILAB LE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92- 21- 32776064 .MOBILE 0322- 2578654.		TECHNICAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM GENERAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	
83	DGB105 047	DEVS7866	473099525334 8 / FLANGE		3 / EACH/N UMBER	NO DATA AVAILAB LE		UK	MOD (NAVY) SHIP SUPPOR T AGENCY DME MC253 ROOM 19 BLOCK B FRAHILL		TECHNICAL SPECIFICATION - BS 1400 Inner dia: 1 1/2 inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: 1/2 inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing GENERAL SPECIFICATION - BS 1400 Inner dia: 1 1/2 inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									BATH UK		Thickness: ½ inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing	
84	DGH106800	LCKUF901052OM	9340705202601 / FRAME 20' X 3.5'	UPRIGHT	9 / EACH/NUMBER			PAKISTAN	PAKISTAN		<u>TECHNICAL SPECIFICATION -</u> Profile type: Omega Upright size: 105mm x 90mm Surface Finish: Powder Coated Material: SS400 <u>GENERAL SPECIFICATION -</u> Profile type: Omega Upright size: 105mm x 90mm Surface Finish: Powder Coated Material: SS400	
85	DGH107062	LCKUF901052OM	9340705202601 / FRAME 20' X 3.5'	UPRIGHT	8 / EACH/NUMBER			PAKISTAN	PAKISTAN		<u>TECHNICAL SPECIFICATION -</u> Profile type: Omega Upright size: 105mm x 90mm Surface Finish: Powder Coated Material: SS400 <u>GENERAL SPECIFICATION -</u> Profile type: Omega Upright size: 105mm x 90mm Surface Finish: Powder Coated Material: SS400	
86	DGE101026	SNR29 DB	6525TY5202565 / 3M PRE MOULDED EARPLUGS ULTRA FIT WITH NATURAL COTTON CORD	BV	30 / EACH/NUMBER	NA		VHKMHMN			<u>TECHNICAL SPECIFICATION -</u> NIL <u>GENERAL SPECIFICATION -</u> NIL	
87	DGH106796	LCKHB1081182B	3020705202580 / BEAM PR 2740X240	RACKS	53 / EACH/NUMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726	HABIB & SONS		<u>TECHNICAL SPECIFICATION -</u> Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5 <u>GENERAL SPECIFICATION -</u> Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
88	DGH106797	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	23 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM GENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
89	DGH107063	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	21 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM GENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
90	DGH106881	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x9" (SET OF 09 TRAYS)	RACKS	21 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI	HABIB & SONS		TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM GENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
91	DGE107174	NO DATA AVAILABL E	035059571311 8 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875") (5MM)		120 / FATHO M	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 120 FATHOMS. 8. REQUIREMENT OF VALID TEST	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/ RN/RELATED COUNTRY MOD. 10. VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. OEM: M/S OCEAN SAFETY LTD UK AND M/S COTESI UK <u>GENERAL SPECIFICATION</u> - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554:2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 120 FATHOMS. 8. REQUIREMENT OF VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/ RN/RELATED COUNTRY MOD. 10. VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. OEM: M/S OCEAN SAFETY LTD UK AND M/S COTESI UK	
92	DGB101743	BS2874, CZ112M	0283595711429 / ROD NAVAL BRASS HEX SIZE ACROSS FLATS 0.71" WT PER FT1. 630 LB	SERVICE PUMP	6 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
93	DGB97856	ADSPEC1076D	0283595711217 / ROD ALUMINIUM BRONZE RD DIA 5 INCH		1 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DGB74774		0283595711474 / SHEET- NAVAL- BRASS- ANNEALED 48		1 / EACH/ NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340 GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
95	DGB102092		0267595213285 / Piping Steel Galv 3050x4. 0x0.250		40 / METER						TECHNICAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable. GENERAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable.	
96	DGB99410		026759521328 5 / Piping Steel Galv 3050x4.0x0.250		20 / METER						TECHNICAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable. <u>GENERAL SPECIFICATION</u> - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable.	
97	DGB107220	NO DATA AVAILABLE	021450214060 8 / BOLT AND NUTS STEEL FOUNDATION TYPE HEX HD SZ 12.000X0.500 INCH		450 / EACH/NUMBER						TECHNICAL SPECIFICATION - length 12 inch thickness ½ inch threaded area 3 inch head HEX PND/Timber Craft Shop (C No 107) specs: DGS 8060 – A, Class – I Material Grade: EN 16 (605 M36) <u>GENERAL SPECIFICATION</u> - length 12 inch thickness ½ inch threaded area 3 inch head HEX PND/Timber Craft Shop (C No 107) specs: DGS 8060 – A, Class – I Material Grade: EN 16 (605 M36)	
98	DGE107176	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-sTRAND, Z-LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	120 / FATHOM						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. <u>GENERAL SPECIFICATION -</u> SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
99	DGB104 647		021479013080 8 / BOLT, MACHINE, THREAD SERIES: BSF, HEX HD	BR 320 D/78	70 / TEN						<u>TECHNICAL SPECIFICATION -</u> THREAD SIZE: 1/2 INCH. NOMINAL LENGTH: 2 INCH. LENGTH OF THREAD: 1 INCH. MATERIAL SPECS PD970:2005 MATERIAL GRADE EN16(605 M36) or EN100 (945 M38), HEAT TREATMENT CONDITION: R as per BR-320D (Catalog of Naval Stores) OEM COC/MTC REQUIRED <u>GENERAL SPECIFICATION - THREAD SIZE:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											1/2 INCH. NOMINAL LENGTH: 2 INCH. LENGTH OF THREAD: 1 INCH. MATERIAL SPECS PD970: 2005 MATERIAL GRADE EN16(605 M36) or EN100 (945 M38), HEAT TREATMENT CONDITION: R as per BR-320D (Catalog of Naval Stores) OEM COC/MTC REQUIRED	
100	DGE105 162	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL</u> <u>SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
101	DGB785 93		027359910446 1 / CALIPER INSIDE 8IN		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
102	DGB745 81		027378923807 8 / BLADE POWER HACKSAW HIGH SPEED STEEL LG 14" WDTH 01" TEETH		18 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. Make: ECLIPSE 2. OEM/Country of origin: England 3. OEM COC/authorized dealer certificate: N/A GENERAL SPECIFICATION - 1. Make: ECLIPSE 2. OEM/Country of origin: England 3. OEM COC/authorized dealer certificate: N/A	
103	DGD107 562		003250003200 9 / KNIVES FISH EATING FOR OCNS		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - MATERIAL S/S 304 /316 FOOD GRADE NON MAGNETIC (LOCAL) PN CREST ENGRAVED ON KNIFE STAINLESS STEEL M/GRADE SS 304/316 (FOOD GRADE) LENGTH 21 TO 23 CM GENERAL SPECIFICATION - MATERIAL S/S 304 /316 FOOD GRADE NON MAGNETIC (LOCAL) PN CREST ENGRAVED ON KNIFE STAINLESS STEEL M/GRADE SS 304/316 (FOOD GRADE) LENGTH 21 TO 23 CM	
104	DGE103 540	C-134	085158000007 6 / DEFENCER EAR C-134 62TD		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
105	DGE107178	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		2000 / EACH/NUMBER						TECHNICAL SPECIFICATION - GUNNY BAGS a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM(gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF). GENERAL SPECIFICATION - GUNNY BAGS a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM(gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF).	
106	DGE105365	MIL-P-15280	5640002374827 / INSULATION SLEEVING THERMAL		60 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. <u>GENERAL SPECIFICATION - mil-p-15280</u> Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
107	DGE101725	MIL-P-15280	564000237482 7 / INSULATION SLEEVING THERMAL		30 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - mil-p-15280</u> Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. <u>GENERAL SPECIFICATION - mil-p-15280</u> Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
108	DGE105364	MIL-P-15280	564000237482 8 / INSULATION SLEEVING THERMAL		60 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - MIL-P-15280</u> SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL SPECIFICATION - MIL-P-15280 SLEEVE SIZES: LENGTH: 72-INCHES NOMINAL, INNER DIA: 3.500 INCHES NOMINAL, INSULATION THICKNESS: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
109	DGE107343	RT876-1/4-0	5970UK5072933 / TUBING (HEAT SHRINK SLEEVE) FOR MARNESS EQUIPMENT		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DGE106278	CM6538-000	5970705044352 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		45 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
111	DGD107538		7730705048055 / PLATE PUDDING FLAT 19CM GOLDEN CRESTED		18 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - FLAT 19CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
112	DGD107693		7730705048058 / PLATE SOUP 9INCH		60 / EACH/NUMBER						TECHNICAL SPECIFICATION - 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GOLDEN CRESTED								GRADE CERA-E-NOOR (LOCAL) GENERAL SPECIFICATION - 9INCH GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)	
113	DGD107 542		773070504807 5 / plate Dinner 23cm blue crested (as per stock sample)		18 / EACH/N UMBER						TECHNICAL SPECIFICATION - Material:PORCELINGENERAL SPECIFICATION - Material: PORCELIN	
114	DGD107 544		773070504807 8 / CUP TEA BLUE CRESTED		18 / EACH/N UMBER						TECHNICAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CMGENERAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CM	
115	DGD107 532		773070504888 3 / HALF PLATE 21 CM FOR CAKE PUDDING ETC GOLDEN CRESTED		6 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
116	DGE106 344	NO DATA AVAILABL E	042250000003 3 / CARPET WOOLEN.		768 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mmGENERAL SPECIFICATION - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm	
117	DGE107 523		8340PK507382 7 / TENT 400 LBS DOUBLE PLY WITH COMPLETE ACCESSORIE S		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. TENT SIZE (LENGTH & WIDTH): 20 X 16 FEET (± 3 INCH) b. WALL HEIGHT: 06 FEET (± 2 INCH) c. HEIGHT OF TENT: 12 FEET (± 3 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: OLIVE GREEN, COLOR CODE: RAL-6003. d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 10 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM & THICKNESS 02 MM ± 0.50 MM b. IRON PEGS: QTY 20 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 28 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 40 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 2 x 2 FEET) WITH MOSQUITO	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
118	DGT101975	NO DATA AVAILABLE	01000000000003 / HARD BOARD SIZE 12'X4'X1/4"	SPECE/BSS 1142/1971	217 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
119	DGE107425		8340705089249 / CAMOUFLAGE NET, SIZE: 30X25FT FOR COVER 12.7-MM GUNS	TO COVER COMOUFLAGE TE 12.7MM GUNS	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM : 1. 100% POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH G1 COATED 300 G/SQ	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438 <u>GENERAL SPECIFICATION</u> - SPECIFICATION OF ITEM : 1. 100% POLYESTER FABRIC, GRADE: 420D, GSM: 200 G/SQ METER AND SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. LOOP INTERVALS FOR JOINING MULTIPLE NETS= (06 INCHES DISTANCE LOOP TO LOOP). 3. COLOUR= GREEN JUNGLE, 4. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 5. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10-MM, CIRC: 1.25-INCH & LENGTH= 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER= 01 IN NUMBER. (D). IRON POLE= 01 X 4 ADJUSTABLE (DIA: 2.5-INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH G1 COATED 300 G/SQ METER. 6. SPECIFICATION FOR ROT/WATER PROOFING= BS-2087 7. SPECIFICATION FOR FIRE RESISTANT BS-5438	
120	DGE107521		834070511704 1 / MESS TENT COMPLETE WITH ACCESSORIES WALLS-		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - 02 x iron standing poles length 12 ft 01 x rich iron length 06 ft tent size (20 x 20ft) qanat size (18 x 18ft) rope straps 40 in no lenght 10ft iron pegs: 40 in no(lenght 2.5ft) hammer large 02 in no capacity 3.5 kg bambo 12	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			152CM								feet: 08 in noGENERAL SPECIFICATION - 02 x iron standing poles length 12 ft 01 x rich iron length 06 ft tent size (20 x 20ft) qanat size (18 x 18ft) rope strops 40 in no lenght 10ft iron pegs:40 in no(lenght 2.5ft) hammer large 02 in no capacity 3.5 kg bambo 12 feet: 08 in no	
121	DGT107664	NO DATA AVAILAB L E	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	768 / SQ FEET	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER. GENERAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN. SPECS	Dimension
122	DGE97390	NO DATA AVAILABLE	8415PK506744 2 / CLOTH PARASHUTE GRAY		100 / METER						<u>TECHNICAL SPECIFICATION -</u> Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery <u>GENERAL SPECIFICATION -</u> Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
123	DGE107161	NIL	934073100099 5 / E-GLASS FIBER (POWDER) CHOPPED STRAND MAT	GRP BOATS	400 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2 <u>GENERAL SPECIFICATION -</u> BS EN 14118 & DEFSTAN 02-166/2 gen a. LENGTH AS PER REQUIREMENT b. WIDTH 1860 MM c. NET WEIGHT 54 KG d. ORIGIN CHINA e. TYPE 450 G/M2	
124	DGE101443	60-501-001	615076502401 1 / TIE WRPA (CABLE TIE) P/N 60-501-001	GRADIOMETER SYSTEM	360 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held <u>GENERAL SPECIFICATION -</u> a. Length: 8 inches b. Material: Phenolic/ Plastic/ Nylon c. Picture: Enclosed d. Certificate of Conformity (COC): Not held	
125	DGH107065		953570504316 1 / SHEET STEEL CARBON 2500X1250X2 MM	FOR SHIPS STRUCTURE	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> BSEN 10025, Grade S-275 <u>GENERAL SPECIFICATION -</u> BSEN 10025, Grade S-275 JR	
126	DGE105421		711070504922 6 / STEEL CABINET SIZE AS PER DRAWING 7.6" X24"X18"	FOR MEDICAL-RECORD-OFFICERS-SAILORS	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
127	DGD106989	ss-1000-Is	734070510187 3 / LUNCH TRAY	MESS UTENSILS, OFFICER	250 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> 280 X 220X40MM WEIGHT: 810+ GRAM. PACKING: NORMAL. MATERIAL:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			STAINLESS STEEL 4 COMPARTMENT PLATES DINNER MESS PLATES	WARD PNS SHIFA							STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX design: AS PER STOCK SAMPLE <u>GENERAL SPECIFICATION</u> - 280 X 220X40MM WEIGHT: 810+ GRAM. PACKING: NORMAL. MATERIAL: STAINLESS STEEL NON MEGNATIC. BRAND/OEM: KT TRADE IMPLEX design: AS PER STOCK SAMPLE	
128	DGD107539	NO DATA AVAILABLE	0031500000096 / PLATE PUDDING 7" GOLDEN CRESTED		10 / EACH/NUMBER	Cera-e-noor					<u>TECHNICAL SPECIFICATION</u> - dia ; 7.48" material: porcelain golden crested with pn logo <u>GENERAL SPECIFICATION</u> - dia ; 7.48" material: porcelain golden crested with pn logo	
129	DGD107524		0034546000454 / Saucer Tea Blue Crested		18 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) As per existing Stock Make/Brand: CERA-E-NOOR with Blue Shell & PN Crest embossed on item <u>GENERAL SPECIFICATION</u> - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) As per existing Stock Make/Brand: CERA-E-NOOR with Blue Shell & PN Crest embossed on item	
130	DGE102301	NO DATA AVAILABLE	0559780000187 / SLEEVE PLASTIC DIA 0.5CM		5 / ROLL	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S, NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black <u>GENERAL SPECIFICATION</u> - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S, NO. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black	
131	DGD107565	NO DATA AVAILAB LE	003250000012 8 / FORKS FISH EATING STEEL PN CRESTED		15 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Material grade s/steel 304 (food grade) <u>GENERAL SPECIFICATION -</u> Material grade s/steel 304 (food grade)	
132	DGD107563	NO DATA AVAILAB LE	003250000013 4 / FORK TABLE SMALL		40 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> PN Crest Stainless Steel Grade SS 316 (Food Grade) <u>GENERAL SPECIFICATION -</u> PN Crest Stainless Steel Grade SS 316 (Food Grade)	
133	DGT107668	NO DATA AVAILAB LE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		10 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) <u>GENERAL SPECIFICATION</u> - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
134	DGT107266		041554600431 2 / SHEET FORMICA WHITE 4.X4. X1/16"		5 / SHEET						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
135	DGB105033	PN16DN100	024154600193 4 / GATE VALVE 1.5" PRESSURE 100PSI		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Gate Valve 1.5" (Non-Rising Stem) with indicator, Flanged, Pressure: 100 PSI Testing/ Acceptance Criteria: Relevant ISO standards for sea water valves connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb/ BRASS OEM: KITZ Japan <u>GENERAL SPECIFICATION -</u> Gate Valve 1.5" (Non-Rising Stem) with indicator, Flanged, Pressure: 100 PSI Testing/ Acceptance Criteria:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Relevant ISO standards for sea water valves connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb/ BRASS OEM: KITZ Japan	
136	DGD101058	NIL	732070533267 3 / DOUGH DIVEDER & ROUNDER WITH ACCESSORIES		1 / EACH/NUMBER	Latest					<u>TECHNICAL SPECIFICATION - 1.</u> CAPACITY 1000-2000 DOUGH BALL PER HOUSR, 2. ELECTRIC POWER 1.5HP/220V/50HZ VARIABLE SPEED CONTROL MOTOR, 3. DOUGH BALL WEIGHT RANGE 70-110 GRAMS AS PER REQUIRMENT, 4. ACCESSORIES: (A). 1 X SS SPECIAL WORKING TABLE (SIZE: 48X30X35), (MATERIAL STAINLESS STEEL 304), THICKNESS TOP: 1.2 MM/BOTTOM: 0.9MM/ LEGS: 1.5MM ADJUSTABLE FEET), (B). 2X SS TROLLEY, LEVEL 12 X TRAYS, (MATERIAL: STAINLESS STEEL: 202), THICKNESS: 1.2MM PORTABLE ON WHEELS, (C). 24 X SS TRAY FOR TROLLEY, MATERIAL: STAINLESS STEEL 304, <u>GENERAL SPECIFICATION -</u> 1. CAPACITY 1000-2000 DOUGH BALL PER HOUSR, 2. ELECTRIC POWER 1.5HP/220V/50HZ VARIABLE SPEED CONTROL MOTOR, 3. DOUGH BALL WEIGHT RANGE 70-110 GRAMS AS PER REQUIRMENT, 4. ACCESSORIES: (A). 1 X SS SPECIAL WORKING TABLE (SIZE: 48X30X35), (MATERIAL STAINLESS STEEL 304), THICKNESS TOP: 1.2 MM/BOTTOM: 0.9MM/ LEGS: 1.5MM ADJUSTABLE FEET), (B). 2X SS TROLLEY, LEVEL 12 X TRAYS, (MATERIAL: STAINLESS STEEL: 202), THICKNESS: 1.2MM PORTABLE ON WHEELS, (C). 24 X SS TRAY FOR TROLLEY,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIAL: STAINLESS STEEL 304.	
137	DGT107 170	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	80 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
138	DGE105 345	611-055	402079515314 3 / ROPE NYLON 16MM WHITE MULTIPLAIT (FLEXABLE AND HIGH	TAL SHIP SAILING RIG	440 / METER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT.		UK	<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG	
139	DGH987 80		614570533282 9 / electrical cable 30mm 4 core flexible cu/ pvc/ pvc.		50 / METER	4 CORE FLEXIBLE CABLE					<u>TECHNICAL SPECIFICATION -</u> ELECTRICAL CABLE 30MM 4 CORE FLEXIBLE CU/ PVC/ PVC <u>GENERAL SPECIFICATION -</u> ELECTRICAL CABLE 30MM 4 CORE FLEXIBLE CU/ PVC/ PVC	
140	DGE997 09	GGG-H- 142	841500935190 6 / SAFETY	PERSONAL PROTECTION	30 / EACH/N			FEDERAL SPECIFICATIONS UNITED	FEDERAL SPECIFIC		<u>TECHNICAL SPECIFICATION -</u> GARMENT SIZE 6-3/4 TO 7-1/2;	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension.
			HELMET YELLOW		UMBER			STATES CAGE CODE 81348	ATIONS		ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000 GENERAL SPECIFICATION - GARMENT SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000	
141	DGE98303		492072517605 4 / REGULATOR WITH OCTOPUS (COMPLETE SET)	DIVING	2 / EACH/NUMBER	PSS DIVE		GERMANY	GERMAN Y		TECHNICAL SPECIFICATION - MAKE/ BRAND: AQUA LUNG (FRANCE/ TAIWAN/MEXICO) DETAILS OF COMPLETE SET: (A) AQUALUNG CALYPSO REGULATOR (PART NO 706006/ RG126113), (B) AQUALUNG CALYPSO OCTOPUS (PART NO 706032/ RS137111), (C) AQUALUNG ELEMENTS PG300BAR + DEPTH (PART NO 704003/ NS 114118), (D) AQUALUNG LP INFLATOR HOSE (PART NO BC911133) GENERAL SPECIFICATION - MAKE/ BRAND: AQUA LUNG (FRANCE/ TAIWAN/MEXICO) DETAILS OF COMPLETE SET: (A) AQUALUNG CALYPSO REGULATOR (PART NO 706006/ RG126113), (B) AQUALUNG CALYPSO OCTOPUS (PART NO 706032/ RS137111), (C) AQUALUNG ELEMENTS PG300BAR + DEPTH (PART NO 704003/ NS 114118), (D) AQUALUNG LP INFLATOR HOSE (PART NO BC911133)	
142	DGB101049		027779923816 4 / TOOL BOX PORTABLE		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm GENERAL SPECIFICATION - A. multiple tool box for stowage of diff sizes tools. B. tool box may be of any color c. general material: hard plastic d. size: 29x3x8 cm	
143	DGE104084		035059571323 5 / ROPE		120 / FATHO						TECHNICAL SPECIFICATION - 1. MIN BREAKING STRENGTH= 5.66	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SISAL, HAWSERLAID, 3-STRND, (ROT PROOFED), CIR: 1-1/8 INCH, DIA: 11/32 INCH (ROUNDED IN 9-MM)		M						KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554. <u>GENERAL SPECIFICATION</u> - 1. MIN BREAKING STRENGTH= 5.66 KN 2. ANGLE OF LAY= 36°, 3. WEIGHT PER COIL= 26.5 LB, 4. UNIT OF AVAILABILITY= 120 FM PER COIL, 5. RELEVANT STANDARD= ISO 1181 OF 2004 (E) TABLE-1, 6. ROT PROOFING AGENT SHALL BE IN ACCORDANCE WITH BS 2087 OF 1992. 7. STORE TO BE SEALED AND STAMPED BY CERTIFYING AGENCY IN ADDITION TO LABELED AND MARKING AS PER ISO 2307 AND 9554.	
144	DGE98101	0413/8568	0413599243503 / FIBER SHEET, VULCANISED, LG, 54"WD. 42" THICKNESS 0.031"	FOR AIR COMPRESSOR	50 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
145	DGE105889		0413705063243 / ANTI SKID DOTTED RUBBER FLOORING COLOUR GREEN 15" X 36" 0.17"		12 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
146	DGE105974		0413705063243 / ANTI SKID DOTTED		48 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension.
			RUBBER FLOORING COLOUR GREEN 15" X36"0.17"								AVAILABLE	
147	DGE95817	BRUSH LEG 4.375"	0476599430411 / BRUSH PAINT SQUARE EDGE ONE KNOT GROUND WD. 2.500" TH. 0.625"		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
148	DGE102172	NO DATA AVAILABLE	0350595713118 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875") (5MM)		120 / FATHOM	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 120 FATHOMS. 8. REQUIREMENT OF VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension.
											RN/RELATED COUNTRY MOD. 10. VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. OEM: M/S OCEAN SAFETY LTD UK AND M/S COTESI UK <u>GENERAL SPECIFICATION</u> - 1. COMPLIED WITH THE SPECIFICATION OF ISO 1140:2021 (LATEST EDITION). 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554:2019(LATEST EDITION). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307: 2019. 4. OEM WILL PROVIDED TEST CERTIFICATE OF ROW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATION OF MATERIAL. 5. OEM/ MANUFACTURED COC. 6. FURNISH 'CALIBRATION CERTIFICATE' OF ALL THE MACHINERY/ EQUIPMENT INSTALLED AT OEM/ MANUFACTURE'S PREMISES FOR TESTING OF ROPES. 7. LENGTH PER COIL: 120 FATHOMS. 8. REQUIREMENT OF VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF ROPES FORM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/ DNV/ ABS/ BV ETC. 9. OEM OF ROPE MUST BE APPROVED BY MOD(UK)/ RN/RELATED COUNTRY MOD. 10. VALID TEST CERTIFICATE INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BREAKING STRENGTH OF ROPES FROM ANY IACS MEMBER CLASSIFICATION SOCIETY I.E LLOYDS/DNV/ABS/BV ETC. 11. OEM: M/S OCEAN SAFETY LTD UK AND M/S COTESI UK	
149	DGB99576	NO DATA AVAILABLE	028370000164 1 / SILVER SOLDER EASYFLO FOR STAINLESS STEEL IN ROD FORM		2700 / GRAM						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
150	DGE98520	0415-9061	041559923141 9 / SAFETY WALK TREAD NONMETALIC, NON-SKID, LENGTH= 2- FEET, WIDTH= 6-INCH,		800 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Make / Model / Brand / Equivalent be endorsed: Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated : Anti-Skid Safety Walk Used Over Stairs, 4. Detailed specifications / Technical data Testing : Safety Walk Thread Nonmetallic Nonskid SIZE: Length 2-feet, Width 6-INCH GENERAL SPECIFICATION - 1. Make / Model / Brand / Equivalent be endorsed: Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated : Anti-Skid Safety Walk Used Over Stairs, 4. Detailed specifications / Technical data Testing : Safety Walk Thread Nonmetallic Nonskid SIZE: Length 2-feet, Width 6-INCH	
151	DGB97045		028350283152 1 / CADMIUM ANODE ROLLED LG 12 INCH WTH 8 INCH TH 3/8 INCH		7.25 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH GENERAL SPECIFICATION - BS 2868 Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm SIZE: LG 12 WTH 8 TH 3/8 INCH	
152	DGB963		028359571145		6.35 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	64		7 / ROD NAVAL BRASS RD DIA 2.25" WT PER FT 14.73(LB)		METER						Specifications: BSEN 12163 of 1998 Grade CW 712R (M), Running Length (Min): 02 meter <u>GENERAL SPECIFICATION</u> - Specifications: BSEN 12163 of 1998 Grade CW 712R (M), Running Length (Min): 02 meter	
153	DGE99288	NO DATA AVAILABLE	041354600479 2 / EAR DENFENDER-SMALL SIZE		30 / PAIR	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
154	DGB97873		028359571145 9 / ROD NAVAL BRASS RD DIA.2.50 INCH WT PER MTR 27.49 KG		0.6 / METER						<u>TECHNICAL SPECIFICATION</u> - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU zN 39 SN 1 <u>GENERAL SPECIFICATION</u> - BS EN-12163 DESIGNATION: CW-719R, R-340 SYMBOL: CU zN 39 SN 1	
155	DGE98926		033059571326 2 / TWINE NYLON ROPING 3 STRD NATURAL FINISH MIN BKG STRGT 50 LB		30 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed. <u>GENERAL SPECIFICATION</u> - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed.	
156	DGE105680	NIL	035059923712 6 / ROPE NYLON ,CIRC 2", DIA: 16-MM, HAWSERLAID, 3-STRAND, Z-LAY,120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	240 / FATHOM						<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019. GENERAL SPECIFICATION - SPECIFICATION OF ITEM 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED TEST CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S/BSI TEST CERTIFICATE REQUIRED AS PER ISO 2307 OF 2019.	
157	SGB971 19	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	25 / KILOGRAMME						TECHNICAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface GENERAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
158	DGB963 63	SPEC BS 2874 C 107-0	028359961098 2 / ROD COPPER RD ANNEALED DIA 0.75 INCH (WEIGHT/ FOOT 1.710 LB		10 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
159	DGE105 234	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
160	DGE105344	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
161	DGB97386	(SIM)	0257709411504 / NUT-PLAIN-HEXAGON (BRASS) THREAD UNF SZ .375"LH . 350"		32 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
162	DGB79214		0251594119648 / HINGE-BUTT-BRASS-SINGLE		116 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
163	DGB88581	AMARICAN(OR UNIFIND) NUMBER	0266590003008 / WASHER FLAT ROUND BRASS 3 BA 0.177X0.341X0.028IN	SPEC=BS 3410 MATERIAL BRASS	104 / TEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
164	DGE100432	NO DATA AVAILABLE	0330546004484 / HEAVING LINE 06MM L50MM 466MS	MSI	660 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
165	DGE101130		4020999237137 / ROPE NYLON	NOR-SHIPS-USE-NASAR	133.2 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HAWSERLAID, 3-STRND, Z-LAY, TYPE-1, NOM DIA: 64-MM, CIRC: 08-INCH,								2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021,</u> 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND	

S. No	LPR No	PART. NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WORKING/ BREAKING STRENGTH OF STORES.	
166	DGB103963	SKF-6207ZZ	3110991199546 / BEARING BALL JOURNAL SKF-6207ZZ 035X072X17MM	GENERAL ITEM	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
167	DGE99002		5330006183221 / PACKING MATERIAL SIZE 3/16".		10 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
168	DGE98913	MIL-P-15280	5640002374827 / INSULATION SLEEVING THERMAL		105 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
169	DGE99264	MIL-P-15280	5640002374827 / INSULATION SLEEVING THERMAL		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. GENERAL SPECIFICATION - mil-p-15280 Sleeve Sizes: LENGTH: 72-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
170	DGE96024	CM6538-000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		13 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes <u>GENERAL SPECIFICATION -</u> Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
171	DGD99038		773070504805 4 / PLATE DESERT FLAT 19CM GOLDEN CRESTED WITH GOLDEN SHELL ON EDGE OF PLATE		24 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Material: porcelain Size: Width: 18CM, Height 2CM <u>2CM</u> <u>GENERAL SPECIFICATION -</u> Material: porcelain Size: Width: 18CM, Height 2CM 2CM	
172	DGE99743	DATA AVAILABL E	046150000015 2 / POLISHING- FELT ROUND		4 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10	

S. No	LPR No:	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Inch Thickness = 1.5 Inch <u>GENERAL SPECIFICATION</u> - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch	
173	DGE105892	NO DATA AVAILAB LE	042250000003 3 / CARPET WOOLEN.		429.4 / SQ FEET	NO DATA AVAILAB. LE					<u>TECHNICAL SPECIFICATION</u> - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm <u>GENERAL SPECIFICATION</u> - (Fire Retardant) Packing details if required: roll a. Width of Roll: 12 feet b. Length of Roll: 29.4 feet c. Color: AS PER SAMPLE d. Thickness: 1200 mm	
174	DGE106070	NIL	810501124264 5 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217-9451	STATIC SAFETY OF EQUIPMENT/C OMPONENTS	40 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557 <u>GENERAL SPECIFICATION</u> - ADD: Item name 1(ACODP3)2 NAVAIR AND NAVSEAMANGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES. 20376 215+897-1557	
175	DGE105164		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIE S)	OLIVE GREEN WATERPROO F INNER LINNING OF,	7 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - 1. SIZE/DIMENSION a.TENT SIZE (LENGTH & WIDTH):50 X 20 FEET (± 6 INCH) b.HEIGHT OF TENT:12 FEET (± 2 INCH) c.HEIGHT OF WALL:07 FEET (± 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4.VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5.PACKING REQUIRED:QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<u>PRODUCTION GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a.TENT SIZE (LENGTH & WIDTH):50 X 20 FEET (± 6 INCH) b.HEIGHT OF TENT:12 FEET (± 2 INCH) c.HEIGHT OF WALL:07 FEET (± 2 INCH) 2.OTHER SPECIFICATIONS a.100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.MATERIAL: 850 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d.INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: ROYAL BLUE. 3. LIST OF ACCESSORIES a.IRON POLES:TOTAL QTY 07 NOS (03 x RIDGE POLES, LENGTH 07 FEET & 04 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM. b.IRON PEGS: QTY 34 NOS, LENGTH: 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 34 NOS, LENGTH 06 INCHES. c.ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM 16 MM. d.HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. e. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 10 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DOOR 04 REQUIRED ON BOTH SIDES OF THE TENT. 5.PACKING REQUIRED:QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR BULK PRODUCTION.	
176	DGE105046	NO DATA AVAILABLE	834070501408 4 / TENT FOR CPOS/SAILOR S. WT= 120 LBS, ALONGWITH COMPLETE ACCESSORIES		6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - 1. SIZE/DIMENSION a. LENGTH: 10 FEET (± 2-INCH) b. WIDTH: 10 FEET (± 2-INCH) c. CENTRAL HEIGHT: 07 FEET (± 2-INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 05 NOS (02 x RIDGE POLES, LENGTH 05 FEET & 03 x STANDING POLES, LENGTH 07 FEET). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM, THICKNESS 02 MM ±0.50 MM. b. IRON PEGS: QTY 12 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2 MM AND MILD STEEL PIN QTY 18 NOS, LENGTH: 06 INCHES. c. ROPE: QTY: 12 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NOS, MATERIAL: MS (MILD STEEL),	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WEIGHT 03 KGS WITH WOODEN HANDLE, LENGTH 1.5 FEET. f. FLAPPER FOR GROUND: MATERIAL: POLYPROPYLENE OF 180-200 GSM. 4. VENTILATION FEATURE: WINDOW 02 (SIZE: 1.5 x 1.5 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 02 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 01 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. LENGTH: 10 FEET (± 2-INCH) b. WIDTH: 10 FEET (± 2-INCH) c. CENTRAL HEIGHT: 07 FEET (± 2-INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: QTY 05 NOS (02 x RIDGE POLES, LENGTH 05 FEET & 03 x STANDING POLES, LENGTH 07 FEET). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ± 02 MM, THICKNESS 02 MM ±0.50 MM. b. IRON PEGS: QTY 12 NOS, LENGTH 18 INCHES, THICKNESS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											20 MM ± 2 MM AND MILD STEEL PIN QTY 18 NOS, LENGTH: 06 INCHES. c. ROPE: QTY: 12 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON, DIA MINIMUM: 16-MM. d. HAMMER: QTY 01 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 03 KGS WITH WOODEN HANDLE, LENGTH 1.5 FEET. f. FLAPPER FOR GROUND: MATERIAL: POLYPROPYLENE OF 180-200 GSM. 4. VENTILATION FEATURE: WINDOW 02 (SIZE: 1.5 x 1.5 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 02 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 01 x BAG FOR THE TENT BODY AND 01 FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
177	DGT106303	NO DATA AVAILABLE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	1500 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<u>SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. <u>ACCEPTANCE CRITERIA:</u> Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. <u>SPECIFICATIONS/STANDARDS</u> BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. <u>MOISTURE:</u> 6-14% 7. <u>DENSITY RANGE</u> I.E 700 TO 850 KG PER CUBIC METER.	
178	DGT105705	NO DATA AVAILAB LE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	880 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. <u>ACCEPTANCE CRITERIA:</u> Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. <u>SPECIFICATIONS/STANDARDS</u> BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. <u>MOISTURE:</u> 6-14% 7. <u>DENSITY RANGE</u> I.E 700 TO 850 KG PER CUBIC METER.<u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM:</u> 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. <u>ACCEPTANCE CRITERIA:</u> Plywood, GD-I, 9-Ply, Both face and back	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
179	DGT106001	NO DATA AVAILABLE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	700 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: Length= 8-FEET, Width=4-FEET & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER. GENERAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: Length= 8-FEET, Width=4-FEET & Thickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
180	DGT106 144	NO DATA AVAILAB LE	010050000001 5 / PLY WOOD GRADE-1, 5 PLY		320 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) <u>GENERAL SPECIFICATION</u> _SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
181	DGT105 977	NO DATA AVAILAB LE	010050000001 5 / PLY WOOD GRADE-1, 5 PLY		996 / SQ FEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) <u>GENERAL SPECIFICATION</u> _SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
182	DGE100 660	GCGH142	841500935313 7 / HELMET SAFTY		35 / EACH/N UMBER						TECHNICAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 broucher attached as documentGENERAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 broucher attached as document	
183	DGE960 30	BS 419/156	055954600536 2 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR		40 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
184	DGE754 99		047654600478 6 / GLOVES LEATHER LEFT HAND LTR NO E- I4927/A/845 DT 28092000		35 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
185	DGE105 424		033054600356 2 / TWINE FLEX FINE 0.50 LBS.		100 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
186	DGD104 414		003550000045 7 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20 to 22", HEIGHT 10 to 12", THICKNESS 10 SWG		4 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWGGENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BREAKAGE/ BENT. O/D x 20 to 22", height x 10 to 12", thickness x 10 SWG	
187	DGD107381		003554600056 1 / MINCING MACHINE LARGE		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
188	DGD105615		003554600061 5 / Pot Aluminum 18/9" With COVER		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 18 Gauge Aluminum Pot having Capacity of 250 lbs Aluminum grade (as food grade and lead free) GENERAL SPECIFICATION - 18 Gauge Aluminum Pot having Capacity of 250 lbs Aluminum grade (as food grade and lead free)	
189	DGE96241	1900gsr-2usb	702501591312 0 / honey well 1900 bar code scanner		2 / EACH/NUMBER	xeon 1900					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
190	DGE86937	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION.	10 / EACH/NUMBER			M/sDF Technologies & Services (Pvt)Ltd Building No.2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4		GERMANY	TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω GENERAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 Ω to 108 Ω	

INVITATION TO TENDER VSD I.T DATE 013-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 02-09-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.

<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 125/2026 DATED 04-08-2026 WHOLE DAY MREs	125 PKT	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II

INVITATION TO TENDER VSD I.T DATE 013-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 02-09-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.

<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 126/2026 DATED 05-08-2026 WHOLE DAY MRES	125 PKT	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II

INVITATION TO TENDER VSD I.T DATE 013-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 02-09-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.


<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 127/2026 DATED 06-08-2026 WHOLE DAY MRES	125 PKT	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II

INVITATION TO TENDER VSD I.T DATE 013-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 02-09-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.


<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 128/2026 DATED 07-08-2026 WHOLE DAY MREs	125 PKT	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II

INVITATION TO TENDER VSD I.T DATE 013-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 02-09-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.


<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 129/2026 DATED 10-08-2026 WHOLE DAY MREs	125 PKT	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II

INVITATION TO TENDER VSD I.T DATE 013-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 02-09-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.


<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 130/2026 DATED 11-08-2026 WHOLE DAY MREs	125 PKT	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GO GSD II

INVITATION TO TENDER VSD I.T DATE 013-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 02-09-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.

<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 131/2026 DATED 12-08-2026 WHOLE DAY MREs	125 PKT	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II

CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II

INVITATION TO TENDER VSD I.T DATE 013-08-2026

The following item is required against local purchase. Suppliers are requested to quote by 02-09-2026 before 11:00 AM. Quotations are to be deposited in the quotation box.


<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 132/2026 DATED 13-08-2026 WHOLE DAY MRs	125 PKT	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


CH USMAN MUNAF
Lt Cdr Pakistan Navy
GSD-II