

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 08-09-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DSB105509	pstn-11647316-vtx	4820705344317 / ball valve ported		5 / EACH/NUMBER	PSTN-11647316-VTX					TECHNICAL SPECIFICATION - 2 Length = 116mm & Dia = 47 mm 2 Material Stainless Steel grade 316 GENERAL SPECIFICATION - 2 Length = 116mm & Dia = 47 mm 2 Material Stainless Steel grade 316	
2	DPK105818	TELLUS S2V-46	9150705041027 / Lub Oil HYDRALIC FLUID (20 LITER Packing)	PWR TXN IN STEERING SYSTEM	7496 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ISO VISCOSITY GRADE:46 GENERAL SPECIFICATION - ISO VISCOSITY GRADE:46	
3	DPC106793	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	105 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
4	DSA101765		5340TY6720913 / CURTAIN RAILING		70 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Aluminum <u>GENERAL SPECIFICATION</u> - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum	
5	DSB107182	DCPF4P-B1-SEW	5935703838625 / DETTCH CABLE PLUG 4 PIN FEMALE		5 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
6	DSA107781	536-415-17DET6	5985705233298 / SANDOW		10 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - Reference physical properties of Al. Alloy AA6061 Property Unit VALUE 1. Density Kg/m³ 2700 2. Elastic Modulus (TENSION/COMPRESSION) GPA 68.9 3. Coefficient of Linear Thermal EXPANSION (A)(20°C to 100°C) PPM/°C 23.6 4. Thermal Conductivity (at 20°C) W/mK 167 5. Specific Heat J/g°C 0.896 <u>CHEMICAL COMPOSITION</u> (AL. ALLOY AA6061) element (% by weight) 1. copper (cu) 0.15-0.4 2. magnesium (mg) 0.8-1.2 3. silicon (si) 0.4-0.8 4. iron (fe) 0.7 (max) 5. manganese (mn) 0.15 (MAX) 6. zinc (zn) 0.25 (MAX) 7. titanium (ti) 0.15 (MAX) 8. chromium (cr) 0.04-0.35 9. other each 0.05 (MAX) 10. other total 0.15 (MAX) 11. mg si ratio 1.6-1.8 12- aluminium (al) balance <u>GENERAL SPECIFICATION</u> - Reference physical properties of Al. Alloy AA6061 Property Unit VALUE 1. Density Kg/m³ 2700 2. Elastic Modulus (TENSION/COMPRESSION) GPA 68.9 3. Coefficient of Linear Thermal EXPANSION (A)(20°C to 100°C) PPM/°C 23.6 4. Thermal Conductivity (at 20°C) W/mK 167 5. Specific Heat J/g°C 0.896 <u>CHEMICAL COMPOSITION</u> (AL. ALLOY AA6061) element (% by weight) 1. copper (cu) 0.15-0.4 2. magnesium (mg) 0.8-1.2 3. silicon (si) 0.4-0.8 4.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Iron (fe) 0.7 (max) 5. manganese (mn) 0.15 (MAX) 6. zinc (zn) 0.25 (MAX) 7. titanium (ti) 0.15 (MAX) 8. chromium (cr) 0.04-0.35 9. other each 0.05 (MAX) 10. other total 0.15 (MAX) 11.mg si ratio 1.6-1.8 12-aluminium (al) balance	
7	DSB107200	LW-7235596-VTX /L23350-80CA	531014209559 6 / WASHER KEY/RONDELL E FREIN PLA 8 Z3CN18-10		30 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - PRESSURE TESTING / PHYSICALLY CHECKGENERAL SPECIFICATION - PRESSURE TESTING / PHYSICALLY CHECK	
8	DSB107183	EMBM4PS-D1-SEW	593570517462 1 / EMBASE 4PIN MALE		5 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DNM106627	219-3240	668501521831 1 / THERMOSTAT ,FLOW CONTROL	CATERPILLAR GENSET D3512B (YBB1) USA	4 / EACH/NUMBER	NA	CAT3512 BEYBB00 583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATION	TECHNICAL SPECIFICATION - 0GENERAL SPECIFICATION - 0	
10	DPK107829		915070512921 5 / LUB-OIL- SAE 20W-50 API SL (Packing 04 liters & 20 LTRS))	MT-VEHICALES FOR PETROL ENGINE	2000 / LITER			PK		CALTEX PAKISTAN	TECHNICAL SPECIFICATION - DEFSTAN 01-005 ISSUE 20. VISCOSITY TOLERANCE LIMIT ATTACHED IN WIMS PROFILE. GENERAL SPECIFICATION - DEFSTAN 01-005 ISSUE 20. VISCOSITY TOLERANCE LIMIT ATTACHED IN WIMS PROFILE.	
11	DNH107690	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENCER	5 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATION	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
12	DPK107861	GB491-1987#3	915070513981 7 / CALCIUM	GEARING OF MECHANISM	45 / KILOGR	NO DATA AVAILAB		UK	UK	TDS\BROCHER OR	TECHNICAL SPECIFICATION - . GENERAL SPECIFICATION - .	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BASE GREASE (KUN LUN) 15KG	TYPE	AMME	LE				PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION		
13	DPK106625	A-A-2702	8030001032868 / PRESERVATIVE COMPOUND	GENERAL PURPOSE	3 / LITER	NO DATA AVAILABLE		US	MILITARY SPECIFICATIONS PROMULGATED BY MILITARY DEPARTMENTS/AGENCIES UNDER AUTHORITY OF DEFENSE STANDARDIZATION MANUAL 4120 3-M UNITED STATES	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
14	DPK106673	90890-69920	9150765168799 / YAMAHA GREASE 50g/TUBE)	SFB (ENGINE)	25 / TUBE	F350A	102563X35	YAMAHA CORPORATION USA /JAPAN	YAMAHA	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> YAMAHA CORPORATION USA /JAPAN <u>GENERAL SPECIFICATION</u> - YAMAHA CORPORATION USA /JAPAN	
15	DNM107094	877072/861700	5330270363984 / VALVE STEM SEAT KIT	VOLVO ENGINE GRP BOAT	48 / EACH/NUMBER	NO DATA AVAILABLE		27	NCAGE: S3562	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
16	DPK106662	15W-40 DELO GOLD	9150705232057 / DELO GOLD ultra sae 15w-40	GEAR BOX	627 / LITER			SHEVRON PAKISTAN LUBRICANT PVT LTD	DELO GOLD ULTRA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - TYPICAL KEY PROPERTIES Delor Gold Ultra Test Test Methods Results Sae Grade ASTM 15W-40 Product Code 500574 Base no. Mg koh/g D2896 10.2 Sulfated Ash, m % D784 1.4 VISCOSITY, mm2/s @ 400C D445 115 mm2/s @ 1000C D445 15.1 Viscosity Index D2270 137 Packing 10 Ltr s Can GENERAL SPECIFICATION - TYPICAL KEY PROPERTIES Delor Gold Ultra Test Test Methods Results Sae Grade ASTM 15W-40 Product Code 500574 Base no. Mg koh/g D2896 10.2 Sulfated Ash, m % D784 1.4 VISCOSITY, mm2/s @ 400C D445 115 mm2/s @ 1000C D445 15.1 Viscosity Index D2270 137 Packing 10 Ltr s Can	
17	DNM107098	864722	5331190025476 / SEALING RING	MAIN ENGINE VOLVO PENTA AB 370	8 / EACH/NUMBER	AB 370 VOLVO PENTA	port 2006032390 STBD 2006032441	AB VOLVO PENTA, GROPEGARDSGTAN, 40508 GOTEVORG SWEDAN	AB VOLVO PENTA, GROPEGARDSGTAN, 40508 GOTEVORG	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
18	DPC107826	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
19	DPC107 674	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
20	DPC107 769	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
21	DPC107 768	Comp A = PHB000 / Comp B = PHA 046	801079522137 7 / INTERTHANE 990 (WHITE)	INSIDE HANGAR PHB000 UK	160 / LITER	PHB000		International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD, UK. Ph:01914696111	International Paints Pvt Ltd, UK	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - TECHNICAL DETAILS INCLUDED IN DATA SHEET SHELF LIFE ; COMP A 02 YEAR/COMP B-01 YEARGENERAL SPECIFICATION - TECHNICAL DETAILS INCLUDED IN DATA SHEET SHELF LIFE ; COMP A 02 YEAR/COMP B-01 YEAR	
22	DPC107 764	BOSTIK M501	801079520820 0 / BOSTIK THINNERS / CLEANER M501	RHIB BOAT	85 / LITER	BOSTIK M501	NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON, SOMERSET, BA9 9RX, TEL "01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHAW INFLATABLES LTD	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - M501 IS USED TO CLEAN, DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 240ADHESIVE. THINNING BOSTIK NE486, CLEANING GLUE BRUSHES. SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N	TOP.HIGHLY FLAMMABLE PRODUCT AND MUST BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA.GENERAL SPECIFICATION - M501 IS USED TO CLEAN,DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 2402ADHESIVE.THINNING BOSTIK NE486,CLEANING GLUE BRUSHES,SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW TOP.HIGHLY FLAMMABLE PRODUCT AND MUST BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA.	
23	DPC107009	TCA 994/TCA995 (GREY)	8010795207355 / INTERLINE 994 (GREY) EPOXY PHENOLIC TANK PAINT	INTERLINE994 INTERNATIONAL PAINT UK	400 / LITER	INTERLINE944		"International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD, UK. Ph:0191 4696111	International Paint Pvt Ltd, uk	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Technical Details included in Data Sheet GENERAL SPECIFICATION - Technical Details included in Data Sheet	
24	DNM107800	3593981	5340735134234 / ANODE KIT	PROPULSION AND STEERING SYSTEM	5 / EACH/NUMBER	NO DATA AVAILABLE		OC	VOLVO PENTA GOTEBURG SWEDEN	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BRAND: VOLVO PENTA ACTUAL WEIGHT: 1.78 MATERIAL: ZINC KIT INCLUDE ANODE BOLT GENERAL SPECIFICATION - BRAND: VOLVO PENTA ACTUAL WEIGHT: 1.78 MATERIAL: ZINC KIT INCLUDE ANODE BOLT	
25	DPC107009	TCA 994/TCA995 (GREY)	8010795207355 / INTERLINE 994 (GREY) EPOXY PHENOLIC TANK PAINT	INTERLINE994 INTERNATIONAL PAINT UK	400 / LITER	INTERLINE944		"International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD, UK. Ph:0191 4696111	International Paint Pvt Ltd, uk	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Technical Details included in Data Sheet GENERAL SPECIFICATION - Technical Details included in Data Sheet	
26	DPC107006	KBA406 INTERGARD403	8010795207354 /	INTERGARD 403 INTERNATIONAL	350 / LITER	INTERGARD 403		"International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD,	International Paint Pvt Ltd,	TDS/BROCHER OR PIC OF	TECHNICAL SPECIFICATION - Technical Details included in Data	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INTERGARD403 (LIGHT RED) EPOXY ANTICORROSIVE PAINT	AL PAINT UK				UK. Ph:0191 4696111	uk	ITEM MUST BE ENCLOSED WITH QUOTATION	SheetGENERAL SPECIFICATION - Technical Details included in Data Sheet	
27	DNM107707	703/41/u5mk7222	5930993868162 / SWITCH EMERGENCY STOP	D/G	20 / EACH/NUMBER	a22e-m-02-ems / a22e		UK	DORMAN DIESELS LTD CENTRAL SPARES DIVISION PO BOX 17 BEEVOR STREET LINCOLN LN6 7AD UK TELE: 0522-5212241 FAX #0522-511297	TDSIBROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 24VDC-GENERAL SPECIFICATION - 24VDC-	
28	DNM106687	3923060/3069053	5340795212330 / Clamp, V Band	Cummins DG	1 / EACH/NUMBER	QSN 11CM954	35339768	G & M TEX LTD MAGNET HOUSE 31 ANSON ROAD MARTLESHAM HEATH IP53RG SUFFOLK UK	UK	TDSIBROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NAGENERAL SPECIFICATION - NA	
29	DPC107721	LAZ684-Light Grey	8010795145259 / PAINT INTERSHEEN 579 LIGHT GREY (Packing = 20Ltrs)	HULL PRESERVATION OF F-22P FRIGATES	40 / LITER	NO DATA AVAILABLE		UK	M/S INTERNATIONAL PAINT LTD P O BOX 20980 ORIAL HOUSE 16 CONNAUGHT PLACE	TDSIBROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - WAR PAINT ISSUE 37GENERAL SPECIFICATION - WAR PAINT ISSUE 37	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									LONDON W2 2ZB UK			
30	DNQ106521	T-8802	0434720000005 / DIVING GOGGLES WITH SAFETY GLASS DOUBLE SEALING FRAME.	PL-70	3 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
31	DNH107776		2340705059829 / BICYCLE COMPLETE 22"/24" WITH STAND LOCK CARRIER BECO/SOHRAB/SHAHEEN/SUMAC DELUXE		6 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - SIZE: 22 INCHES GENERAL SPECIFICATION - SIZE: 22-INCHES	
32	DPC107972		1365997456895 / LIQUID FOR FOGGING		6 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
33	DNM107907	98262.1009	2945998275756 / OIL FILTER	COMPRESSOR 5415	2 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DNM103825	EBOH20/EBE18	4130US5065506 / COOLING UNIT	MAIN AIR CONDITION (CRUISAIR) USA	2 / EACH/NUMBER	EBE18				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED	TECHNICAL SPECIFICATION - UPDATION IN SPECIFICATION MADE VIDE DITD CONTRACT NO: TD-1/NSD/03/2004 DT 26/03/2008 MATERIAL TUBES :COPPER FINIS : ALUMINIUM BLOWER & CASING :M	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION	S (ANODIZED) CAPACITY :20000 BTU GENERAL SPECIFICATION - UPDATION IN SPECIFICATION MADE VIDE DITD CONTRACT NO: TD-1/NSD/03/2004 DT 26/03/2008 MATERIAL TUBES :COPPER FINES : ALUMINIUM BLOWER & CASING :M S (ANODIZED) CAPACITY :20000 BTU	
35	DNH107695	wdf-318	411073100120 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		3 / EACH/NUMBER	WDF-318				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CAPACITY: 18 CUBIC FEET ARE 509 LITERS DIMENSIONS : HEIGHT 168 CM X WIDTH 76 CM X DEPTH 81.6 CM. CURRENT: 1.3 TO 1.5 AMP.(SINGLE PHASE). COMPRESSOR: SIZE 1/4 RECIPROCATING 220 VOLTS. REFRIGERANT : R 134/R 600. DOOR : DOUBLE DOOR. GENERAL SPECIFICATION - CAPACITY: 18 CUBIC FEET ARE 509 LITERS DIMENSIONS : HEIGHT 168 CM X WIDTH 76 CM X DEPTH 81.6 CM. CURRENT: 1.3 TO 1.5 AMP. (SINGLE PHASE). COMPRESSOR: SIZE 1/4 RECIPROCATING 220 VOLTS. REFRIGERANT : R 134/R 600. DOOR : DOUBLE DOOR.	
36	DNH107777	NIL	4110705111991 / REFRIGGERATOR 18/22 CUFT (W=90KG, CAP=478LTRS, I/PUT220V,1.6 AMP)	REFRIGERATOR	1 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DNH107778		4110705058486 / DEEP FREEZER 30 CUFT 220V 50HZ SINGLE	USER MRO LAHORE	1 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
38	DNQ107701	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
39	DNM107706	70HFR20	596175506777 / METAL STUD DIODE 70HFR20 METAL DO-5 PACKAGE	DORMAN D/G 500KVA (UK)	30 / EACH/NUMBER	70HFR20				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE GENERAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE	
40	DNM104691	N18906	4310123587893 / air FILTER	HP COMP	2 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - O E M ADDRESS >.> BAUER KOMPRESSOREN Gsa traders GENERAL SPECIFICATION - O E M ADDRESS >.> BAUER KOMPRESSOREN Gsa traders	
41	DPC107771	850-761-04	8010PK5064841 / EPOXY THINNER 850-761-04 (04 Liter Packing)		60 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DPC107679	NO DATA AVAILABLE	8010705112537 / SOLIGNUM WOOD LACOUER	FOR WOOD WORK	80 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
43	DPC107807	BELZONA 1111	803099192429 2 / BELZONA SUPER METAL 1111 /1111 NF2, COMPRISING OF 833 GM SUPER METAL BASE AND 167 GM SOLIDIFIER 01KG PER SET (BASE+CURING AGENT)	FOR REPAIRING & REBILD MACHINERY EQUIP	131 / SET					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
44	DPC107810	NO DATA AVAILABLE	803099225168 7 / LOCTITE222	30MM GUN	1 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DPC106622	SCOTCH SEAL5200 (8030-01-187-8439	803070503763 5 / SEALING COMPOUND 3M MARINE Adhesive Sealant 5200 White) (295mL	HULL	107 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - REQUIREMENT OF SEALANT ARE AS UNDER GENERAL SPECIFICATION - REQUIREMENT OF SEALANT ARE AS UNDER	
46	DPC107666	NO DATA AVAILABLE	685078503110 4 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANER (UNIVERSAL DEGREASER) (OEM =	REQUIREMENT FOR PNS NASR	261 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PERFECTS								GENERAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B- 8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
47	DPK1078 11	NOSOL GBY2	915012322652 7 / GREASE NOSOL GBY2		3 / KILOGRAMME	NO DATA AVAILABLE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DPC107 686	PINAX	801070533282 4 / CLEANER ZEEPER liquid PINAX		3600 / LITER	PINAX-A				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. <u>GENERAL SPECIFICATION -</u> Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
49	DPC107709	ZEEPER114	8010705332849 / ZEEPER114 CLEANER		2400 / KILOGRAMME	ZEEPER.114				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - COMPOSITION:</u> Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years <u>GENERAL SPECIFICATION - COMPOSITION:</u> Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
50	DPC107719	JOTAPRIME510 ALU. RED	8010785338806 / JOTAPRIME510 ALU.RED		300 / EACH/NUMBER	NA				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - JOTUN PAINT FOR SHIPSIDE ALUMINIUM RED 100DFT</u> <u>GENERAL SPECIFICATION - JOTUN PAINT FOR SHIPSIDE ALUMINIUM RED 100DFT</u>	
51	DPK106954	GB2536-2011 10#	9140FP0010022 / Transformer oil		1 / KILOGRAMME	N/A				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
52	DNM106370	0147-0920	2910015738131 / pump injection (PUMP FUEL METERING AND DISTRIBUTING)		1 / EACH/NUMBER	C22 D5				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - PUMP INJECTION PUMP FUEL METERING AND DISTRIBUTING</u> <u>GENERAL SPECIFICATION - PUMP INJECTION PUMP FUEL METERING AND DISTRIBUTING</u>	
53	DPC107705	A020EEV2	8010705332825 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		455 / LITER	HIGHLY PERFUMED				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - PRODUCT INFORMATION:</u> APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation. <u>GENERAL SPECIFICATION -</u> PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.	
54	DPK107812	PYRATEX EP2	9150145784933 / FIRE PROOF GREASE / GREASE, HEAT DISSIPATION COMPOUND		2 / KILOGRAMME	EP2				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
55	DNH107780	MKF-1000	6670705284950 / WEIGHT MACHINE (UPTO 200 KG		1 / EACH/NUMBER	MKF 1000				TDS\BROCHER OR PIC OF ITEM MUST BE	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PLATFORM SIZE 14 X 18 INCHES)							ENCLOSED WITH QUOTATION		
56	DPC105456	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		1030 / LITER	PINAX-A				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> Daily mopping purpose concentrated Zeeper Pinax which Cleans S Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. <u>GENERAL SPECIFICATION -</u> Daily mopping purpose concentrated Zeeper Pinax which Cleans S Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
57	DSA99336	LOCAL Q1-52-10X100	5310745240197 / RACCORD DROIT (GREASING NUT UNION)		100 / EACH/NUMBER	N/A					<u>TECHNICAL SPECIFICATION -</u> MARINE STANDARD ALUMINUM BRONZE SET: 03 X PIECES FERRULE LENGTH: 10MM NUT LENGTH: 16MM (14X1.5) PRESSURE: 200 BAR <u>GENERAL SPECIFICATION -</u> MARINE STANDARD ALUMINUM BRONZE SET: 03 X PIECES FERRULE LENGTH: 10MM NUT LENGTH: 16MM (14X1.5) PRESSURE: 200 BAR	
58	DSB74776	50TE000C0027	6685745194283 / THERMOMETER BDT 25 &		2 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			26 0A 200 DIAM93 SUTTE OM									
59	DPC105460	ZEEPER114	8010705332849 / ZEEPER114 CLEANER		1520 / KILOGRAMME	ZEEPER.114				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years GENERAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
60	DPK105319	PYRATEX EP2	9150145784933 / FIRE PROOF GREASE / GREASE, HEAT DISSIPATION COMPOUND		2 / KILOGRAMME	EP2				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
61	DPK104526	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/A DDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	60 / LITER	JAPAN		JAPAN		SHELL	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
62	DPK104469	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/A DDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	500 / LITER	JAPAN		JAPAN		SHELL	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
63	DNM102841	100-3880	2815015067155 / PUSHROD-VALVE	CATERPILLAR GENSET D3512B (YBB1) USA	24 / EACH/NUMBER	D3512B	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA		CATERPILLAR USA	TECHNICAL SPECIFICATION - CATERPILLAR GENSET D3512B (YBB1) USA METALLIC PUSHROD-VALVE MATERIAL STEEL MAIN ENGINE CUMMINS GENERAL SPECIFICATION - CATERPILLAR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATION	GENSET D3512B (YBB1) USA METALLIC PUSHROD-VALVE MATERIAL STEEL MAIN ENGINE CUMMINS	
64	DNM105382	CWCU-230-27	4130705214345 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 24	HVAC PLANT 02 CWAHU-24 PAKISTAN	8 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www.quardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20" GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20"	
65	DNM105386	CWCU-230-27 (12	4130705214346 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	1 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www.quardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20" GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"	
66	DNM105386	CWCU-230-27 (12	4130705214346 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	1 / EACH/NUMBER	CP-F6-95-3	NIL	GUARD FILTERS PAKISTAN www.quardfilters.com COOL POINT Address: Adda Polt, Sharaiz Avenue, Jati Umra Road Raiwind Road Lahore.	COOL POINT PAKISTAN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20" GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"	
67	DNQ105149	HAMMAR H 20	4220735199199 / HAMMAR H 20 R HYDROSTATIC RELEASER FOR LIFERAFTS	HAMMAR H 20 R HYDROSTATIC RELEASER FOR LIFE RAFT	12 / EACH/NUMBER	G91154/0902	NA	CM Hammar AB, August Barks gata 15, SE-421 32 Västra Frölunda (Göteborg), Sweden Phone: +46 31 709 65 50 Fax: +46 31 49 70 23 Email: info@cmhammar.com www.cmhammar.com	CM Hammar Sweden	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - The Hammar H20 hydrostatic release unit is designed for liferafts from 6 up to 150 persons. The Hammar H20 release unit consists of a double looped white rope sling, a release mechanism and a Red Weak Link? (breaking strength 2,2 ± 0,4 kN) GENERAL SPECIFICATION - The Hammar H20 hydrostatic release unit is designed for liferafts from 6 up to 150 persons. The Hammar H20 release unit consists of a double looped white rope sling, a release	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											mechanism and a Red Weak Link? (breaking strength 2.2 ± 0.4 kN)	
68	DNQ105227	06973009	6140FT1019336 / Torch (Long Life) c/w Spares	Emergency Pack - 1	14 / EACH/NUMBER	583210B.0006	0	KINGSWAY DUNMURRY BELFAST RLANDA	SURVITE C GROUP	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
69	DNQ106158	CEN1000063E	5510FT1019834 / Wooden Plug 300 x 120 x 50 mm	Portable Firefighting and Damage Control Equipment System	30 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITE. 462 NCI GUZELBAHCE-IZMIR TÜRK YE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STL.	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
70	DPK102984	7101001002	9150735232473 / REFRIGERATION LUB OIL DHB-002 (19 Liters Packing)	HARD FORD AC COMPRESSOR	15 / LITER	DHB-002	17FA000G5737A	DUNHAM-BUSH INDUSTRIES SMD.BHD. LOT 5755-6,KIDMAL INDUSTRIAL PARK,BUKIT ANGKAT,43000 KAJANG. SELANGOR PH:+603-89249000 FAX:+603-89395020	DUNHAM-BUSH INDUSTRIES	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - FLASH POINT (ASTM D-92,COC) 190C,MELTING POINT : (ASTM D-92,COC)-30 CGENERAL SPECIFICATION - FLASH POINT (ASTM D-92,COC)190C,MELTING POINT : (ASTM D-92,COC)-30 C	
71	DPC106517	CLK724	8010992355263 / PAINT INTERLAC 665 STORM,GREY	Switchboard PNFT	400 / LITER	INTERLAC 665 INTERNATIONAL PAINT UK		AKZO NOBEL International Paint (Suzhou) Co.Ltd. No.129 Hongxi Road New District Suzhou, Jiangsu, 215151 China Telephone No. 86(512) 66167888 Fax No. 86(512)66163911	AKZO NOBEL International Paint (Suzhou) Co.Ltd.	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
72	DNM105382	CWCU-230-27	4130705214345 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 24	HVAC PLANT 02 CWAHU-24 PAKISTAN	8 / EACH/NUMBER	CP-F6-95-3	NIL	COL POIMT PLOT : SHARAIZ AVENUE JATI UMER A ROAD LAHORE COOL POINT PVT LMTD LAHORE PAKISTAN GUARD FILTERS PAKISTAN www.	GUARD FILTERS PAKISTAN www. guardfilters.com	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20" GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 24"X24"X20"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								quardfilters.com		QUOTATION		
73	DNM105386	CWCU-230-27 (12	4130705214346 / F-9 BAG FILTER (95% EFFICIENCY) SIZE 12	HVAC PLANT 02 CP-F6-95-3 PAKISTAN	1 / EACH/NUMBER	CP-F6-95-3	NIL	COOL POINT PLOT : SHARAIZ AVENUE JATI UMER ROAD LAHORE COOL POINT PVT LMTD LAHORE PAKISTAN GUARD FILTERS PAKISTAN www. quardfilters.com	GUARD FILTERS PAKISTAN www. quardfilters.com	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"GENERAL SPECIFICATION - F-9 BAG FILTER (95 % EFFICIENCY) SIZE 12"X24"X20"	
74	DPC105726	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
75	DPC105132	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
76	DPC105513	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATION	ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
77	DPC105 447	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
78	DPC105 984	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
79	DPC106 503	PILOT-II	801079517183 9 / MAMMUT PRIMER WHITE	Tall ship	300 / LITER			Jotun Paints (Europe) Ltd. Stather Road Flixborough, Scunthorpe North Lincolnshire DN15 8RR England Tel: +44 17 24 40 00 00 Fax: +44 17 24 40 01 00 SDSJotun@jotun.com	JOTUN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - undercoat primer whiteGENERAL SPECIFICATION - undercoat primer white	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
80	DNQ106 332	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
81	DPC106 517	CLK724	8010992355263 / PAINT INTERLAC 665 STORM GREY	Switchboard PNFT	400 / LITER	INTERLAC 665 INTERNATIONAL PAINT UK		"International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD, UK. Ph:0191 4696111	International Paint Pvt Ltd, uk	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null <u>GENERAL SPECIFICATION</u> - null	
82	DPC102 100		0473502247701 / GUM ACACIA TECHNICAL		20 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
83	DPC105 481	DEFSTAN 68-30/1 OF 1974	0474502204834 / CHLORINATED LIME,		1500 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - DEFSTAN 68-30/1 OF 1974 OEM COC DATE OF MANUFACTURING & EXPIRY OEM TEST	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TECHNICAL 30% MIN available CHLORINE (25 KG Packing)							ENCLOSED WITH QUOTATION	CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE <u>GENERAL SPECIFICATION</u> - DEFSTAN 68-30/1 OF 1974 OEM COC DATE OF MANUFACTURING & EXPIRY OEM TEST CERTIFICATE/ FATS/ CERTIFICATION/ APPROVAL AS APPLICABLE	
84	DPC105 461	SAME AS S NO 9 EXECPT SHADE.	044250220163 7 / PAINT FINISHING (GREEN)	USES FOR STEEL ALUMINUM OR WOOD ON GLASS	102 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
85	DPC106 084	WHO/SIF/ 13.R5	044250220120 1 / Lambda Cyhalothrin 2.5 or 25% EC. 01LTR PLASTIC PACKING WITH REGISTERED LABEL.	KEROCANE OIL.	120 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label. <u>GENERAL SPECIFICATION</u> - Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label.	
86	DPC105 508		044250442005 1 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT	FINISHING INTERIOR	319 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			/ Turpentine, Method of Application Brushing, Type of Coat: Finishing								80-78/2 OF 1995. 4. COLOUR SHADE NO 101 OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
87	DPC105 612		044250943447 9 / PAINT PRIMING, LIGHT ADMIRALTY GREY FLASH POINT 23 DEGREE C	PRIMER FOR FINISHING ACID AND ALKALI	60 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> DEFSTAN 80-72/3 OF 2006 2. COLOUR SHADE NO 697 OF BS: 381 OF 1996 <u>GENERAL SPECIFICATION - 1.</u> DEFSTAN 80-72/3 OF 2006 2. COLOUR SHADE NO 697 OF BS:381 OF 1996	
88	DPC105 614		044250943448 1 / PAINT ACID AND ALKALY RESISTANT A/R (BLACK) 05 LTR TIN Flash Point: 32 Degree C (min) Packing: standard oem 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	4 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED 3. DEFSTAN 80-72/3 OF 2006 <u>GENERAL SPECIFICATION - 1.</u> NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED 3. DEFSTAN 80-72/3 OF 2006	
89	DPC105 622		044250943448 3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	160 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996 <u>GENERAL SPECIFICATION -</u> DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
90	DPC106 188		044250943448 3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	141 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996 GENERAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996	
91	DPC105 373		044250943448 3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	72 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996 GENERAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996	
92	DPC106 120		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		344 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
93	DPC105 224		044250442009 7 / VARNISH OIL EXTERIOR GARDE-II	AMPN	8 / LITER					TDS/BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										BE ENCLOSED WITH QUOTATION		
94	DPC105 229	DEFSTAN 80-37/2 OF 2006	0442504420124 / Paint Cellulose White Finsihing for vehicles principal component Nitro Cellulose Base Flash Point 23		25 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DPC106 166	WHO/SIF/ 14 R-5 (6TH EDITION OF85)	0442504420136 / Insecticide Malathian 60		120 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Insecticide Malathion 57 to 60% EC, SPECIFICATION: Active Ingredience (A.1) Malathion 57 to 60% EC W/W PACKING: 01 Ltr Plastic Packing with registered label GENERAL SPECIFICATION - Insecticide Malathion 57 to 60% EC, SPECIFICATION: Active Ingredience (A.1) Malathion 57 to 60% EC W/W PACKING: 01 Ltr Plastic Packing with registered label	
96	DPC105 506	NO DATA AVAILABE	0442502202381 / PAINT PRIMING GRAPHITE BASIS (RED LEAD)	BUXLY/ICI/BERGER/KOSAR GRP-E VIDE NHQ LT	243 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DPC106 090	NO DATA AVAILABE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		85 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Dioxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
98	DPC106450	NO DATA AVAILABLE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		250 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Dioxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Dioxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
99	DPC106342	NO DATA AVAILABLE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		150 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Dioxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Avallability	Tender Remarks	TECH / GEN SPECS	Dimension
										N	Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
100	DPC105 489	SUPERSEDED BY DGS 1035	0442502202020 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	264 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed <u>GENERAL SPECIFICATION</u> - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
101	DNQ105 128	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. <u>GENERAL SPECIFICATION</u> - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
102	DNM983 65	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO.	1 / EACH/NUMBER	HD 8/18-4 M* KAR				TDS\BROCHER OR PIC OF ITEM MUST	<u>TECHNICAL SPECIFICATION</u> - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				GER						BE ENCLOSED WITH QUOTATION	Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control <u>GENERAL SPECIFICATION</u> - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
103	DNM104943	A/C 1-1/2 TON 03 YEAR GUARANTE	4310731001978 / A/C COMP 50HZ 220-240V 18000BTU 1-PH COPLAND USA 52-68 LRA	A/C 1-1/2 TON	1 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
104	DNM105465	B57121X5 13F075xx/ P7800B3X/ P425S-2373D-512-7.5T (340970)	4140715092410 / A/C SEA/CHILL WATER PUMP WITH MOTOR	A/C UNIT OEM:M/S TAYLOR MADE ENVIRONMENT	1 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - OEM: DOMETIC ENVIROMENTAL CORPORATION P.O BOX 15299 RICHMOND USA VA 23227-0699 <u>GENERAL SPECIFICATION</u> - OEM: DOMETIC ENVIROMENTAL CORPORATION P.O BOX 15299 RICHMOND USA VA 23227-0699	
105	DNQ105016	BS EN-3	4210705036007 / CO2 CYLINDER TROLLY MOUNTED 50KG WITH VALVE &HP	FIRE FIGHTING EQUIPMENT	3 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - DES:CO2 CYLINDER TROLLY MOUNTED 50KG <u>GENERAL SPECIFICATION</u> - DES:CO2 CYLINDER TROLLY MOUNTED 50KG	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HOSE DIA 0.75"							N		
106	DNH99329	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318				tds brochure / picture must be enclosed with quotation.	TECHNICAL SPECIFICATION - CAPACITY: 18 CUBIC FEET ARE 509 LITERS DIMENSIONS : HEIGHT 168 CM X WIDTH 76 CM X DEPTH 81.6 CM. CURRENT: 1.3 TO 1.5 AMP.(SINGLE PHASE). COMPRESSOR: SIZE 1/4 RECIPROCATING 220 VOLTS. REFRIGERANT : R 134/R 600. DOOR : DOUBLE DOOR. <u>GENERAL SPECIFICATION - CAPACITY: 18 CUBIC FEET ARE 509 LITERS DIMENSIONS : HEIGHT 168 CM X WIDTH 76 CM X DEPTH 81.6 CM. CURRENT: 1.3 TO 1.5 AMP. (SINGLE PHASE). COMPRESSOR: SIZE 1/4 RECIPROCATING 220 VOLTS. REFRIGERANT : R 134/R 600. DOOR : DOUBLE DOOR.</u>	
107	DNQ106336	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	5 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
108	DNM86351	2301JB	6125791005158 / ALTERNATOR 28V 20A NH220 ENGINE 2301JB	NH220 CUMMINS D/E	1 / EACH/NUMBER	NH220				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
109	DPC103756	BELZONA 9111	8010705040915 / BELZONA 9111 CLEANER/DEGREASER (0.5 liter packing)	FOR DEGREAS SURFACE & CLEANS APPLI TOOLS	6 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSE	TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION		
110	DPC106606	COMP A + Comp B = 580-3035-11	8010PK506484 0 / HI-BUILD EPOXY ZINC PHOSPHATE PRIMER (PACKING 3.2 LTRS)		26 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
111	DPC106602	EPIGRIP L524	801099840098 8 / EPIGRIP L524-HIGH BUILD 2-PACK MODIFIED EPOXY COATING IN WHITE COLOR	BILGES PAINTING FRIGATES TYPE 24	100 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
112	DPC105517	NO DATA AVAILABLE	683070504133 8 / GAS ARGON N56 HIGH PURITY 99.9996%	FOR MISTRAL AIR DEFENCE SYSTEM	6.8 / CUBIC METER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes. GENERAL SPECIFICATION - 1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes.	
113	DPK106703	XG-460	915099910052 4 / GREASE LUBRICATING XG-460 (Packing = 03 KG Tin)	MAINTENANCE, OILS, GREASES AND APPLICATORS	18 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Technical Data (Typical Values) Appearance= Fibrous Grease Colour = Black NLGI Classification = 00 Unworked Penetration(IP50) = 400- 430 Worked Penetration (IP50) = 400-430 Base oil Viscosity (IP71) @ 400C cSt = 600 @ 1000C cSt = 34 Four Ball (IP 239) Weld Load kgs = 315 Timken Ok Load IBS = 45 Operating Temperature Range = -25 to + 1000C GENERAL SPECIFICATION - Technical Data	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(Typical Values) Appearance= Fibrous Grease Colour = Black NLGI Classification = 00 Unworked Penetration(IP50) = 400-430 Worked Penetration (IP50) = 400-430 Base oil Viscosity (IP71) @ 400C cSt = 600 @ 1000C cSt = 34 Four Ball (IP 239) Weld Load kgs = 315 Timken Ok Load IBS = 45 Operating Temperature Range = -25 to + 1000C	
114	DNQ105444	NO DATA AVAILABLE	0262500001365 / LADDER-ALUMINIUM-EXTENDING-28FEET CAPABLE OF WITH STANDING		5 / EACH/NUMBER	NO DATA AVAILABLE				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. Closed height: 5 Meter 2. Extended height: 9 Meter 3. Approximately weight: 26 KG 4. Loading capacity: 150 KG 5. Warranty: Life time GENERAL SPECIFICATION - 1. Closed height: 5 Meter 2. Extended height: 9 Meter 3. Approximately weight: 26 KG 4. Loading capacity: 150 KG 5. Warranty: Life time	
115	DNM105098	MURPHY LTD PDS 100-007	6685715048527 / OIL PRESSURE GAUGE 0-TO-100 PSI& 0-7 BAR MURPHY SWITCH GAUGE	CUMMINS DIESEL ENGINE 34.5 KVA (USA/UK)	6 / EACH/NUMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DIMENSION / SIZE: Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch Gauge GENERAL SPECIFICATION - DIMENSION / SIZE: Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch Gauge	
116	DPC105304	NIL-SHELF LIFE 3 MONTH	6810705039263 / DECK COMPOUND FLASH POINT 89C SP-GR-1009 (ANTI SKID)	LOCAL PURCHASE	300 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
117	DPC105022	B71003, B71046	6810731001000 / COBALT		40 / KILOGRAMME					TDS\BROCHER OR	TECHNICAL SPECIFICATION - Accelerator Cobalt based, Preferably	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		OR ACCELRA TOR G (POLYACC P-A)	BASED ACCELERATOR / CRYSTIC ACCELRA TOR G / POLYACC P-A / LLOYD APPROVED EQUIVALENT PRODUCT		AMME					PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25 KG <u>GENERAL SPECIFICATION</u> - Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25 KG	
118	DPC106 324		047354600470 3 / SODA CAUSTIC (PACKING 25 KG)		300 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - Soda Caustic (chemical nomenclature SODIUM HYDROOXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments <u>GENERAL SPECIFICATION</u> - Soda Caustic (chemical nomenclature SODIUM HYDROOXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments	
119	DNH106 420	NO DATA AVAILABLE	130850053012 6 / DEEP FREEZER 12 CUFT 220 V AC WAVES		2 / EACH/NUMBER	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION		
120	DPK106633	GB11120-2011 ISO VG 32	9140FP001002 1 / ISO VG 32 GB11120-2011 TURBINE OIL		3 / LITER	GB11120-2011				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
121	DRG100898	ZO6555415	1560ZO655541 5 / ENGINE 14.95CC (OS91)		9 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - ECU:14.95CC(91FX)+TANK E-4020+A3 GLOW PLUG+BOOK LET, MAKE:OS JAPAN. GENERAL SPECIFICATION - ECU:14.95CC (91FX)+TANK E-4020+A3 GLOW PLUG+BOOK LET,MAKE:OS JAPAN.	
122	DPC106497	OUW6032 SVA/OUWCPB EVA (Comp A + B)	801078530068 2 / paint PEN GUARD FC green BASE 3 A (RAL 6032)		900 / LITER	PEN GUARD FC RAL 6032				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
123	DNM96766	2358051	530573524480 1 / m20x 60 8.8 zn di screw		8 / EACH/NUMBER	CLASSIC V WMAD				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - M20X 60 8.8ZN DI SCREW MS GRADE 8.8 GENERAL SPECIFICATION - M20X 60 8.8ZN DI SCREW MS GRADE 8.8	
124	DPC103805	S. No. 19 jotun anti-skid	801078529231 8 / PAINT JOTUN ANTI-SKID SNO 19 (Dark COLOR) PARTICLE SIZE FINE		50 / LITER	JOTUN ANTI SKID				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATIO N		