

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 17-09-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

DATE & TIME 01/03/2014 10:00:00

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPK107874	CORENA S2 P150	915070519669 9 / SHELL CORENA S2 P150 (PACKING = 20 LITERS)	HPAC PNFT	60 / LITER	NA	NA	M/S SHELL	M/S SHELL	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - SHELL CORENA S2 P150</u> <u>GENERAL SPECIFICATION - SHELL CORENA S2 P150</u>	
2	DPC108293		044250942937 4 / VARNISH MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	USE ONWOOD UNDER CONDITIONS OF MARINE EX	344 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED</u> <u>GENERAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED</u>	
3	DNM108104	3092608	482071532741 6 / Seal, Valve Stem		36 / EACH/NUMBER	N/A				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	
4	DPK107949	FLUGENE 113B0MBE AEROSOL/ UFI:PMU 1-ROPD- 8007-	685014344090 4 / CLEANING SOLVENT FOR ELECTRIC/ ELECTRONIC		34 / EACH/NUMBER	UFI:PMU 1-ROPD- 8007- P2DQ				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED	<u>TECHNICAL SPECIFICATION -</u> Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays,	

S. No.	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		P2DQ	EQUIPMENT							D WITH QUOTATION	telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c. Should have fast vaporization rate. <u>GENERAL SPECIFICATION</u> - Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c. Should have fast vaporization rate.	
5	DPK107948	TCW3 NMMA	0721500000013 / LUB OIL OMD-23 FOR TWO STROKE OUTBOARD GASOLINE ENGINE NMMA GRADE TCW3		70 / LITER	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY <u>GENERAL SPECIFICATION</u> - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE	
6	DPC108245	24137	6810002270410 / ISOPROPYL ALCOHOL (SIGMA ALDRICH 24137) (2.5 Liter Packing)		57.5 / GALLON					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
7	DPK108328	90790-BS802	9150705102424 / GEAR OIL (750CC X 1)	OBM ENGINE, GEAR, MOBILE ASHARI	480 / TUBE					TDS/BROCHER OR PIC OF	<u>TECHNICAL SPECIFICATION</u> - 750 ml Tube Packing <u>GENERAL SPECIFICATION</u> - 750 ml Tube	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FOR OBM ENGINE (GL4 OUTBOARD GEAR OIL SAE 90) OEM = YAMALUBE	PVTLTD.KAR						ITEM MUST BE ENCLOSED WITH QUOTATION	Packing	
8	DPK107943	20W-50	9150PK5079480 / LUB OIL 20W50 PKG 4LTR (FOR PETROL VEHICLES)	PETROL VEHICLES	68 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DPC108225	NO DATA AVAILABLE	6850785031104 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMENT FOR PNS NASR	5 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. GENERAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
10	DNH108102	EAC-70/WP-1302/ECM 6500	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	2 / EACH/NUMBER	EAC-70/WP-1302/ECM 6500				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE GENERAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
11	DNQ107958	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		10 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
12	DPC108318	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		2783 / BOTTLE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
13	DPC108284	NO DATA AVAILABLE	0442504420030 / DULAC HI-BUILD (Packing = 0.91 Liter)		48 / LITER	ICI				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - LACURE MAKE: ICI OEM GENERAL SPECIFICATION - LACURE MAKE: ICI OEM ICI	
14	DPK107916	SPIRAX S2 G 140	9150795293050 / shell SPIRAX S2 G 140		4 / LITER	EMPERO EM.09.P				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
15	DPC108243	NA	6508705231785 / HAND SANITIZER	SELF	80 / LITER	NIL	NIL	PAKISTAN	PAKISTAN	TDS/BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - HAND SANITIZER GENERAL SPECIFICATION - HAND SANITIZER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSE D WITH QUOTATIO N		
16	DPK108332	ZIC ATF 3	915073522136 9 / ZIC ATF 3 DEXRON SYNTHETIC TRANSMISSIO N FLUID	TILT & TRIM ASSEMBLY	40 / LITER	ZIC ATF 3	NIL	SK LUBRICANTS 26, JONG-RO-JONGNO-GU, SEOUL,KOREA www.skzic.com Made in Korea	SK LUBRICA NTS	TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly) <u>GENERAL</u> SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly)	
17	DNM108107	3094157/3 804866	676071519970 9 / VALVE INTAKE	CUMMINS DG QST30-G2 USA	18 / EACH/N UMBER	QST30- G2	37175632	CUMMINS ENGINE COMPANY INC USA COLUMBUS ,INDIANA, USA B.O BOX 3005	CUMMIN S USA	TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - 938 KVA DIESEL GENERATOR <u>GENERAL</u> SPECIFICATION - 938 KVA DIESEL GENERATOR	
18	DNM108106	3804713	312071516133 6 / SET, MAIN BEARING	ENGINE CRANK SHAFT	1 / EACH/N UMBER	QST 30 G2	37178798	CUMMINS INC. 500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 812-377-3920 812-377-1715 DUNS 006415160 STEVE.A. HEWITT@CUMMINS.COM	CUMMIN S INC.	TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - CUMMINS INC. 500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 812-377-3920 812-377- 1715 DUNS 006415160 STEVE.A. HEWITT@CUMMINS.COM <u>GENERAL SPECIFICATION -</u> CUMMINS INC. 500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 812-377-3920 812-377- 1715 DUNS 006415160 STEVE.A. HEWITT@CUMMINS.COM	
19	DNM108105	6314 2Z/C3	311015147712 8 / BALL BEARING	CUMMINS DG 650 KVA VTA- 28-G5 USA	1 / EACH/N UMBER	VTA - 28 - G5	25334882	CUMMINS POWER GENERATION 1400 73 RD AVE.NE MINNEAPOLIS MIN 55432 USA. PHONE: 17635745000 TOLL-FREE:18008886626 FAX: 17635745298. E-MAIL:ASK.POWER GEN@CUMMINS.COM	CUMMIN S ENERGY COMPAN Y INC USA	TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - OEM/ PERKINS COUNTRY OF ORIGIN: FRANCE, HOWEVER, SKF BRAND BEARING OF ANY OTHER ORIGIN ALSO ACCEPTABLE. <u>GENERAL SPECIFICATION - OEM/</u> PERKINS COUNTRY OF ORIGIN: FRANCE, HOWEVER, SKF BRAND BEARING OF ANY OTHER ORIGIN ALSO ACCEPTABLE.	
20	DNM107	6I-0645	530671522839	50KVA ALLIED	4 /	N/A	E3S01292	CATERPILLAR INC	ALLIED	TDS/BROC	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	983		0 / BOLT (M8X1.25X25-MM)	CAT DG 400 VOLTS 3 PHASE 50 HZ	EACH/NUMBER			MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	CAT	HER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	GENERAL SPECIFICATION -	
21	DPK107914	GL-95/GADUS S2 OG 40	9150735182950 / GREASE SHELL GADUS S2 OG 40/TUFGEAR UNIVERSAL Rocol (Packing 18kg)	MAIN SHAFT	4 / KILOGRAMME	GL-95		MJP MARINE JET POWER AB S-748 01 OSTERBYBRUK SWEDEN TEL +46 295 244 250 FAX +46 295 244 250	SHELL MALLEUS SWEDEN	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MJP MARINE JET POWER AB S-748 01 OSTERBYBRUK SWEDEN TEL +46 295 244 250 FAX +46 295 244 250 GENERAL SPECIFICATION - MJP MARINE JET POWER AB S-748 01 OSTERBYBRUK SWEDEN TEL +46 295 244 250 FAX +46 295 244 250	
22	DPC107968	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
23	DPC108096	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	220 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
24	DPK108335	99000-22B55	9150765223106 / ECSTAR OUT BOARD MOTOR GEAR OIL SUZUKI SAE-90 GL-5	SUZUKI OBM ENGINE	165 / MILLILITER	NIL		SHOWA SHELL SEQIYU K. 3-2 DAIBA-2-CHOME, MINATO-KU, TOKYO, 135-8074, JAPAN	OBM SUZUKI	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE AUTOMOTIVE GEAR OIL</u> <u>GENERAL SPECIFICATION - ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE AUTOMOTIVE GEAR OIL</u>	
25	DNM107957	HBC 139/HBC 52	5130735227950 / BRUSH CUTTER	Bush Cutter	2 / EACH/NUMBER	HBC 139/HBC 52	NIL	Hyundai Power products, Korea	Hyundai	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - BBC 139/HBC 52 Engine Cylinder Displacement 31cm3 Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of carburettor Diaphragm type</u> <u>GENERAL SPECIFICATION - BBC 139/HBC 52 Engine Cylinder Displacement 31cm3 Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of carburettor Diaphragm type</u>	
26	SPK92196	ARCTIC 32/146264	9150795170256 / MOBIL EAL ARCTIC 32 (1 LITRE PACKING)	COMPRESSOR	20 / LITER		65703502	Mobil Oil Company Limited Acting as Agent for Mobil Lubricants UK Limited ExxonMobil House, Emyrn Way Leatherhead, Surrey, KT22 8UX Telephone: 01372 22 2000	Mobil Oil Company Limited	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - MOBIL EAL ARCTIC 32</u> <u>GENERAL SPECIFICATION - MOBIL EAL ARCTIC 32</u>	
27	DNM107956	2890S	4240TY5202560 / 3M	BV	130 / EACH/NUMBER	NA		VHKMHMN		TDS/BROCHER OR	<u>TECHNICAL SPECIFICATION -</u> <u>NIL GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COMFORT LINE SAFETY GOGGLES 2890S SEALED VERSION		UMBER					PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	NIL	
28	DNM99014	dg-750	6685725022149 / GAUGE DEPTH FOR DIVING EQUIPMENT		35 / EACH/NUMBER	nd0000628				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GAUGE DEPTH (driver's) 0-70m (wrist) 600m (panel) analog dial wrist /console/ panel mounted GENERAL SPECIFICATION - GAUGE DEPTH (driver's) 0-70m (wrist) 600m (panel) analog dial wrist /console/ panel mounted	
29	DPC107602	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
30	DPC106496		6830PK5071580 / GAS MIXTURE 80% ARGON AND 20% CO2		115.6 / CUBIC METER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Packing Details: Cylinder PN/GM (HE SUR)/GENERAL/2569501 DT 20 JAN 2023 PACKING DETAILS - CYLINDER ORIGIN - LOCAL ACCEPTANCE CRITERIA - 80% ARGON & 20% CO2 (+ 2%) GENERAL SPECIFICATION - Packing Details: Cylinder PN/GM (HE SUR)/GENERAL/2569501 DT 20 JAN 2023 PACKING DETAILS - CYLINDER ORIGIN - LOCAL ACCEPTANCE CRITERIA - 80% ARGON & 20% CO2 (+ 2%)	
31	DPC106860	SUVA 410a	259071516019	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH	DOMESTIC MARINE	TDS/BROCHER OR	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		/HFC-410a/R-410a//HONEYWELL R-410A	3 / DUPONT REFRIGERANT R410A		AMME			PN:0880269 www.domesticusa.com	MARINE	PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
32	DNH107950	GUD140T/A-S/GUD140W/A-X	412070505910 1 / acson ceiling cassette 04 ton SPLIT air condition.	USER CNS HOUSE KARACHI	1 / EACH/NUMBER	GUD140T/A-S/GUD140W/A-X				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - brand: acson color: white capacity: 04 tons cooling capacity: 48000 btu ac type: ceiling cassette technology: conventional cooling type: cool/hot gas: r22GENERAL SPECIFICATION - brand: acson color: white capacity: 04 tons cooling capacity: 48000 btu ac type: ceiling cassette technology: conventional cooling type: cool/hot gas: r22	
33	DPC106960	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	245 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
34	DPC98597	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	18 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGINAL COLOR CHIPS,A DIVISION	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATION		
35	DNM102529	QP407PA A	4310765021898 / COMPRESSOR 2 TON BTU 24000 ROTARY 220V 50 HZT	A/C 02 TON WINDOW TYPE	1 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
36	DNM97930	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	2 / EACH/NUMBER	HD 8/18-4 M* KAR				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control GENERAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
37	DNH107708	NIL	4120735139117 / AIR CONDITIONER SPLIT 1.5 TONS	AIR CONDITIONING	1 / EACH/NUMBER	NO DATA AVAILABLE		OC		THILAND	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -
38	DPC108192	SUPERSEDED BY	0442502202020 / PAINT	DECK AND DADOES	56 / LITER						TDS/BROCHER OR	TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991

3. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimensio
		DGS 1035	FINISHING (RED)	PRIMER						PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed <u>GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed</u>	
39	DPC106 612	NO DATA AVAILABLE	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		45 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas</u> <u>GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas</u>	
40	DPC106 861	NO DATA AVAILABLE	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		100 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas</u> <u>GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Design Gas <u>GENERAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
41	DPC106780	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	56.75 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
42	DPC107540	LIQUID BE 380 & POWDER CS 381	5610705197496 / FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS381 (Packing = Kit) (Color = Light Grey)	CHEMICAL	29 / KIT	-	-	LABCO FINE CHEMICAL karachi PHONE 021-32562622 labcod2002yahoo.com	M/S LABCO FINE CHEMICAL	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS 381GENERAL SPECIFICATION - FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS 381	
43	DPC108487	LIQUID BE 380 & POWDER CS 381	5610705197496 / FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS381	CHEMICAL	6 / KIT	-	-	LABCO FINE CHEMICAL karachi PHONE 021-32562622 labcod2002yahoo.com	M/S LABCO FINE CHEMICAL	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS 381GENERAL SPECIFICATION - FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS 381	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(Packing = Kit) (Color = Light Grey)							N		
44	DPC108 540	COSMADEC-13 EPOXY COMPOUND	5610705197498 / COSMADEC-13 EPOXY COMPOUND (COMP A+ COMP B) (Packing = KIT) (Color = Grey)	CHEMICAL	47 / KIT			M/S LABCO FINE CHEMICALS PH # 021-32562622 EMAIL: labcod200@yahoo.com	M/S LABCO FINE CHEMICALS	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - COSMADEC-13 EPOXY COMPOUND</u> COMP A: Blend of epoxy polymer, fillers and pigments COMP B: Curing agent <u>GENERAL SPECIFICATION - COSMADEC-13 EPOXY COMPOUND</u> COMP A: Blend of epoxy polymer, fillers and pigments COMP B: Curing agent	
45	DPC107 522		0474500001889 / CLEANING POWDER, 1 CWT.DRUM (BR 320 D CLASS GROUP 0474 PG 2	BR320D REVISED 1965 CLASS GROUP 0474 PG2	150 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - a.</u> Type Cleaning Powder b. Age Group Any Age c. Brand Cesco Solutions d. Item weight 5 pounds or dependent upon market availability e. Packing material Woven Bag carton <u>GENERAL SPECIFICATION - a.</u> Type Cleaning Powder b. Age Group Any Age c. Brand Cesco Solutions d. Item weight 5 pounds or dependent upon market availability e. Packing material Woven Bag carton	
46	DPC108 414	0461-3951, CS2879	0461592240562 / WATER INDICATING PASTE FOR FUEL (03 OZ TUBE)		34 / TUBE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
47	DPC108 479	G-1200	0475502205613 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		10 / TUBE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
48	DPC108 410		0442509434481 / PAINT ACID AND ALKALY	FINISHING	48 / LITER					TDS/BROCHER OR PIC OF	<u>TECHNICAL SPECIFICATION - 1.</u> NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			RESISTANT A/R (BLACK) 05 LTR TIN. Flash Point: 32 Degree C (min) Packing: standard oem 04 ltr tin non corrosive gauge of tin.26 to 28 swg							ITEM MUST BE ENCLOSED WITH QUOTATION	3. DEFSTAN 80-72/3 OF 2006 <u>GENERAL SPECIFICATION -</u> 1. NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED 3. DEFSTAN 80-72/3 OF 2006	
49	DPC107 104		044250942119 5 / PAINT PRIMING ZINC PHOSPHATE WHITE FIRE RETARDANT FLASH POINT 32 OC (MIN)	SHADE 355 STAGE INSPECTION PRESCRIBED	120 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> 1. revised ns/p/009 of 2013 /SPECIFICATION NS/P/002 OF 2013 2. to be tested against defstan 80-77/2 of 1995 3. stage inspection prescribed 4. colour shade white 5. DEF1115A COLOUR TO BS 381-C 6 Fiash l"roint: 32 "C (Min) 7. Packirrq: 20 Ltr Drum, Gauge of Tin 24 to 26 <u>SWG GENERAL SPECIFICATION -</u> 1. revised ns/p/009 of 2013 /SPECIFICATION NS/P/002 OF 2013 2. to be tested against defstan 80-77/2 of 1995 3. stage inspection prescribed 4. colour shade white 5. DEF1115A COLOUR TO BS 381-C 6 Fiash l"roint: 32 "C (Min) 7. Packirrq: 20 Ltr Drum, Gauge of Tin 24 to 26 SWG	
50	DPC108 412		044279942354 2 / Paint Marking, Stenciling (Signal Red) flash point: 32 degree C (Min) method of application: brushing & stenciling type: Alkyed Packing: 04 liter tin gauge of tin 26 to 28		408 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> 1. DEFSTAN 80-68/4 2. NS/P/012 OF 2013 (REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996 <u>GENERAL SPECIFICATION -</u> 1. DEFSTAN 80-68/4 2. NS/P/012 OF 2013 (REVISED) 3. STAGE INSPECTION PRESCRIBED 4. COLOUR SHADE NO 537 OF BS: 381 COF 1996	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SWG									
51	DPC108500	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		3280 / BOTTLE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
52	DPC108760	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		4500 / BOTTLE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
53	DPC108444	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		3120 / BOTTLE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
54	DNH108246	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	2 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
55	DPK106644	90790-BS802	9150705102424 / GEAR OIL (750CC X 1) FOR OBM ENGINE (GL4	OBM ENGINE, GEAR, MOBILE ASHARI PVT LTD. KAR	451 / TUBE					TDS/BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - 750 ml Tube Packing GENERAL SPECIFICATION - 750 ml Tube Packing	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OUTBOARD GEAR OIL SAE 90) OEM = YAMALUBE							ENCLOSED WITH QUOTATION		
56	DPC108 604	NO DATA AVAILABLE	681073100099 9 / MARINE GRADE POLYESTER RESIN/ CRYSTIC 406E/ POLYPOL-1009/ LLOYD APPROVED EQUIVALENT PRODUCT	FOR GRP BOAT	1780 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - General purpose unsaturated, polyester resin unpromoted thixotropic, laminating type orthophthalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 °C mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25°C - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) j. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time, 30°C with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30°C accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25°C without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max) <u>GENERAL SPECIFICATION</u> - General purpose unsaturated, polyester resin unpromoted thixotropic, laminating type orthophthalic, suitable for hand and spray lay up of marine vessels in tropical conditions. USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register and of following specification: a Governing Reference/Specifications NES -167 CRYSTIC 406 E b. Viscosity, 25 °C	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											mean share at 50 rpm Poise 4-8 - c. Specific gravity at 25oC - 1.1-1.15 - d. Acid value mg KOH / gm 20 (Max) e. Volatile content - 46% (Max) f. Tensile strength (unfilled resin) Mpa 57 (Min) g. Tensile strength (filled resin) Mpa 150 (Min) h. Flexural strength (unfilled resin) Mpa 80 (Min) J. Flexural strength (filled resin) MPA 175 (Min) k. Typical gel time, 30oC with accelerator & MEKP Minutes 22 (Min) l. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) m. Stability in dark at 25oC without initiator Months 6-8 - n. Water absorption (24 hours) mg 30 (Max)	
57	DSX100969	T0502	5999TY6712480 / H.LOCK SET		17 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DSA102648	GSM141-008F5MLEBZ15CN17-03 / GSM141-08F5MLEBZCN17-03	5306143299374 / BOLT, INTERNALLY RELIEVED BODY (VIS-F90EV1-CARRE-B-ZISCN17-0)		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DSA102570	E27311H60M22AET	5305142353234 / VIS HM 6X18X18 A52		310 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
60	DRG89965	TWNIG	2925ZO5238493 / TWIN IGNITION		6 / EACH/NUMBER	GREAT POWER					TECHNICAL SPECIFICATION - MODEL: TWIN IGNITION GENERAL SPECIFICATION - MODEL: TWIN IGNITION	
61	DSX101030	2CD059	5310755043683 / CONICAL WASHER S-STEEL-10X31X1.5MM		200 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
62	DPC107606	X06-1	6810785277578 / Ethylene phosphide primer		5 / EACH/NUMBER	SKJ5-19				TDS/BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO.	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										BE ENCLOSED WITH QUOTATION		
63	DSM106540	M10	4130011976803 / FONTAINE REFRIGERANTE M10		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - non magnetic (ss) 220/110 v 60 hz single phase GENERAL SPECIFICATION - non magnetic (ss) 220/110 v 60 hz single phase	
64	DSX101031	T011007	5340TY6720772 / PIANO HINGES S/STEEL (1200X70X2MM)		10 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DSB102456	DRAWING NO.105-05-006-13-000 AND PART NO. 105-05-006-23-000	5340725343833 / CONICAL MOUNT T-90		16 / EACH/NUMBER	T-90					TECHNICAL SPECIFICATION - ENGINE MOUNTING GENERAL SPECIFICATION - ENGINE MOUNTING	
66	DSA102651	GSM141-008F5MLE CZ15CN17-03 / GSM141-08F5MLEC Z15CN17-03 / 5306FBM0 DCINOX	5306143299375 / BOLT, INTERNALLY RELIEVED BODY/VIS CSM 141-08 INOX / BOLT, INTERNALLY RELIEVED BODY		100 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
67	DGB101340	HME-AB-ADP-VLV-FERROL20-004	4730705351238 / ADOPTER 1/2"		30 / EACH/NUMBER	SS304 SURFACE					TECHNICAL SPECIFICATION - ADOPTER thread type size 1/2 inch 1ST SIDE VALVE THREAD AND SECOND SIDE DIA 20MM FERROL TYPE material stain less steel 316- GENERAL SPECIFICATION - ADOPTER thread type size 1/2 inch 1ST SIDE VALVE THREAD AND SECOND SIDE DIA 20MM FERROL TYPE material stain less steel 316-I	
68	DPC105	1141674/	615073514142	VOLVOPANTA	737 /	NO DATA		00		M/S AB	TDS/BROC	TECHNICAL SPECIFICATION -

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	712	22567233/ 22567259 (20 ltr)	4 / COOLANT READY MIX (volvopenta)	ENGINE	LITER	AVAILAB LE				VOLVOP ANTA 405 08 GOTEBO RG SWEEDN	HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	PACKING: 05 LITER CAN /20 Liter can GENERAL SPECIFICATION - PACKING: 05 LITER CAN /20 Liter can
69	DRG105 122	SO-436V5	291570515008 7 / SEPARATOR ELEMENT ASSY		3 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DNM104 921	imp/am200	301071522034 7 / ELASTIC SHAFT COUPLING FOR 50 MM SHAFT DIA	SHAFTING ARRANGEME NT	1 / EACH/N UMBER	Elastic shaft coupling for GR 2: 1, 1620Nm Torque		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMIN S	TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - Elastic shaft coupling for GR 2:1, MAX SHAFT TORQUE 1620Nm, CENTAFLEX AM200 COUPLING, INCLUDING CLAMP FOR 50mm DIA AND MACHINED FOR FITTING ON GEAR BOX. OUTSIDE DIA OF AM200 IS 300mm. FIRM'S QUOTATION ALONGWITH TECHNICAL SPECIFICATIONS IS ENCLOSED. <u>GENERAL SPECIFICATION</u> - Elastic shaft coupling for GR 2:1, MAX SHAFT TORQUE 1620Nm, CENTAFLEX AM200 COUPLING, INCLUDING CLAMP FOR 50mm DIA AND MACHINED FOR FITTING ON GEAR BOX. OUTSIDE DIA OF AM200 IS 300mm. FIRM'S QUOTATION ALONGWITH TECHNICAL SPECIFICATIONS IS ENCLOSED.	
71	DPK9723 8	SHELL OMELA VISCOSIT Y-68	259073516552 1 / HUB OIL	MJP	10 / LITER	MJP 750 SERIES		MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	MJP OSTERB Y	TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN GENERAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	
72	DPK105838	SHELL OMELA VISCOSITY-68	2590735165521 / HUB OIL	MJP	10 / LITER	MJP 750 SERIES		MJP.OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	MJP OSTERBY	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN GENERAL SPECIFICATION - MJP WATER JET SWEDEN MJP OSTERBY GJUTERI AB SERVICE @ MJP.SE e-MAIL ADD/MJP/OSTERBY GJUTERI AB SE-74801 OSTERBYBRUK SWEDEN	
73	DPC106611	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
74	DPC106565	SUVA 410a /HFC-410a/R-410a/HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
75	DPC106	SUVA	259071516019	TEMPERED	102.15 /	MTD 72	MTD 72	DOMESTIC MARINE REV-	DOMESTIC	TDS/BROCH	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	341	410a /HFC-410a/R-410a//HONEYWELL R-410A	3 / DUPONT REFRIGERANT R410A	WATER SYS	KILOGRAMME	EC	EC	20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	C MARINE	HER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
76	DPC106660	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
77	DPC106514	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
78	DPK106976	SAE 90 (80W90)	915025114513 5 / ENGINE GEAR OIL SAE 90 (80W90) (03	YAMAHA OUTBOARD ENGINE	18 / LITER	NO DATA AVAILABLE		US	SOCIETY OF AUTOMOTIVE	TDS/BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - SAE 90 (80W90)GENERAL SPECIFICATION - SAE 90 (80W90)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			Ltr to 18 Ltr PACKING)						ENGINEE RS INC, COMMAN WEALTH DRIVE, WARREN DALE, USA., PSC: 15096, TEL#724-776-4841	BE ENCLOSE D WITH QUOTATIO N		
79	DNM105 986	247-1380	294071520763 1 / FILTER ELEMENT AIR	DG CATTERPILLE R C2-2 DE18E3/DE22 E2 USA	16 / EACH/N UMBER	C2-2 DE18E3/ DE22E2	NIL	CATERPILLAR USA CO 701 WATERFOLD WAY SIUT 200 MIAMI USA CONTACT NO 305-476-6800 FAX NO 305-476-6801	CATERPI LLAR USA	TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - AIR FILTER USE FOR PROVISION OF CLEAN COMBUSTION AIR TO DG FOR SMOOTH RUNNING OF ENGINE <u>GENERAL SPECIFICATION - AIR FILTER USE FOR PROVISION OF CLEAN COMBUSTION AIR TO DG FOR SMOOTH RUNNING OF ENGINE</u>	
80	DNQ106 527	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	22 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D	TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL</u>	
81	DPC105	COSMADE	136573522800	DECK FLOOR	40 / KIT	COSMAD		LABCO FINE CHEMICALS	LABCO	TDS/BROC	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	Q.TY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	299	C-14	0 / COSMADEC-14 EPOXY SEALER			EC-14		ADDRESS: D-200, SHAHRA-E-SILK, S.I.T.E., KARACHI PHONE: 021-32562622 EMAIL: labcod200@yahoo.com	FINE CHEMICALS	HER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	MATERIAL TYPE: A BI-COMPONENT MEDIUM TO HIGH MOLECULAR WEIGHT EPOXY SEALER. COLOUR AVAILABILITY: CLEAR TRANSPARENT. FLASH POINT: COMP A: 130°C COMP B: > 180°C. THICKNESS: APPROXIMATELY 250 MICRONS PER COAT ON SMOOTH SURFACE. SHRINKAGE: MIN 0.0% MAX 0.001%. <u>GENERAL SPECIFICATION - MATERIAL TYPE: A BI-COMPONENT MEDIUM TO HIGH MOLECULAR WEIGHT EPOXY SEALER. COLOUR AVAILABILITY: CLEAR TRANSPARENT. FLASH POINT: COMP A: 130°C COMP B: > 180°C. THICKNESS: APPROXIMATELY 250 MICRONS PER COAT ON SMOOTH SURFACE. SHRINKAGE: MIN 0.0% MAX 0.001%.</u>	
82	DPC105303	COSMADEC-13 EPOXY COMPOUND	5610705197498 / COSMADEC-13 EPOXY COMPOUND (COMP A+ COMP B) (Packing = KIT) (Color = Grey)	CHEMICAL	40 / KIT			M/S LABCO FINE CHEMICALS PH # 021-32562622 EMAIL: labcod200@yahoo.com	M/S LABCO FINE CHEMICALS	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION.	<u>TECHNICAL SPECIFICATION - COSMADEC-13 EPOXY COMPOUND COMP A: Blend of epoxy polymer, fillers and pigments COMP B: Curing agent</u> <u>GENERAL SPECIFICATION - COSMADEC-13 EPOXY COMPOUND COMP A: Blend of epoxy polymer, fillers and pigments COMP B: Curing agent</u>	
83	DNM104915	imp/gp/sh/01	2010715220348 / PROPELLER SHAFT AQUAMET 17 DIA 50MM	MARINE GEAR BOX	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - PROPELLER SHAFT DIA 50MM, L 4.2M MATERIAL AQUAMET 1.7 OR EQUIVILANT, TYPE 23 PROPELLER SIDE WITH CONE 14 X 100 MM SS KEY AND BRONZE PROPELLER NUT M27 X 2, GEARBOX SIDE NUT MACHINED, FITS IN POS 7</u> <u>QUATATION ALONG WITH TECH SPECS ATTACHED</u> <u>GENERAL SPECIFICATION - PROPELLER SHAFT DIA 50MM, L 4.2M MATERIAL AQUAMET 1.7 OR EQUIVILANT, TYPE 23 PROPELLER</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SIDE WITH CONE 14 X 100 MM SS KEY AND BRONZE PROPELLER NUT M27 X 2, GEARBOX SIDE NUT MACHINED, FITS IN POS 7 QUATATION ALONG WITH TECH SPECS ATTACHED	
84	DNM104916	imp/gp/stb/g01	201071522103 1 / STUFFING BOX FOR 50 MM SHAFT DIA	SHAFTING ARRANGEMENT	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED <u>GENERAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED</u>	
85	DNM104917	imp/gp/stb/t01	201071522103 3 / STERN TUBE FOR 50 MM SHAFT DIA	SHAFTING ARRANGEMENT	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED <u>GENERAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED</u>	
86	DPC105645	SPEC. BS 3981	047350942925 1 / PIGMENT POWDER (DRY INGREDIENTS)		2.5 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE	TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FOR PAINTS) RAW SIENNA POWDER (Packing 56 LB or 400 Gram) TIGER BRAND							ENCLOSED WITH QUOTATION		
87	SPC108560	G-1200	0475502205613 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		400 / TUBE					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
88	DPC106991		0473504730040 / ZINC PHOSPHIDE (RAT POISON)		1 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MOLECULAR FORMULA: Zn3 P2 MOLECULAR WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET) GENERAL SPECIFICATION - MOLECULAR FORMULA: Zn3 P2 MOLECULAR WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)	
89	DPC107075		0442504420051 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application	FINISHING INTERIOR	116 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTION PRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101 OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg GENERAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTION PRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101 OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Brushing, Type of Coat: Finishing								28 swg	
90	DPC105 219		044250442005 1 / Paint, Interior Sky Blue fire retardant Flash Point: 32 Degree C (Min) Type: Alkyd, Principal Component Titanium THINNER WHITE SPIRIT / Turpentine, Method of Application Brushing, Type of Coat: Finishing	FINISHING INTERIOR	20 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED), EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg GENERAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED), EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
91	DPC105 233		044250943448 3 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min) Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	70 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C OF 1996 GENERAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C OF 1996	
92	DPC997 51		044250442006 4 / PAINT WEATHER WORK (LIGHT GREY)NHQ LTR NS/G/1303/C	WEATHER WORK	972 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DT 270199							QUOTATION		
93	DPC105291		0442504420043 / PAINT FINISHING MID BROWN GLOSS FLASH POINT 32C (04 LTR Packing)	MULTI COAT FINISH PRIMED SEEL ALUMINUM	90 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996 GENERAL SPECIFICATION - Flash point 32 C (Min) 04 LTR packing DEFSTAN 80-29/1 OF 1973 Stage Inspection Prescribed colour shade no 411 of bs 381 c of 1996	
94	DNQ106519	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		11 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
95	DNQ106663	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
96	DPC107055	NO DATA AVAILABLE	0442502202381 / PAINT PRIMING GRAPHITE BASIS (RED LEAD)	BUXLY/ICI/BERGER/KOSAR GRP-E VIDE NHQ LT	42 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
97	DPC107049	SUPERSEDED BY DGS 1035	0442502202020 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	531 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
98	DNQ104106	0121-924-0372	0121999240372 / LUMBER SOFT WOOD DIM SZ 100X100MM (LENGTH=07 FEETS)	NBCD DAMAGE CONTROL & FIRE FIGHTING EQUIP	2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
99	SNQ106787	0265-12392/ SWG-8	0265594233534 / NAIL-STEEL-WIRE-5INCH (ROUND CHEQUERED HEAD SWG 5)		51 / KILOGRAMME					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
100	DNQ105576	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		6 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
101	DNQ106	DEVELOP	204099787817		8 /					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION -	

3. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	666	ED BY DTD	3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		EACH/NUMBER					HER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. <u>GENERAL SPECIFICATION -</u> EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
102	DPC105236	DSL 101/ SOFNOLIME 2050 (408)L Grade	047350473005 0 / SODA LIME DSL 101 TYPE: INDICATOR (Packing 4.5 KG PLASTIC CAN) /SOFNOLIME CS2580 L Grade w/out Indica		150 / CAN					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> COLOUR WHITE, COLOUR ON SATURATION VIOLET, GRAINS SIZE 4-8 MESH (2.4-5MM) MOISTURE 13-15.5% ACTIVITY PERIOD 180 MINUTES CO2 ABSORPTION NOT LESS THAN 20% W/W DENSITY 6.06-1.00 G/CC <u>GENERAL SPECIFICATION -</u> COLOUR WHITE, COLOUR ON SATURATION VIOLET, GRAINS SIZE 4-8 MESH (2.4-5MM) MOISTURE 13-15.5% ACTIVITY PERIOD 180 MINUTES CO2 ABSORPTION NOT LESS THAN 20% W/W DENSITY 6.06-1.00G/CC	
103	DNH104489	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> CAPACITY: 18 CUBIC FEET ARE 509 LITERS DIMENSIONS : HEIGHT 168 CM X WIDTH 76 CM X DEPTH 81.6 CM. CURRENT: 1.3 TO 1.5 AMP.(SINGLE PHASE). COMPRESSOR: SIZE 1/4 RECIPROCATING 220 VOLTS. REFRIGERANT : R 134/R 600. DOOR : DOUBLE DOOR. <u>GENERAL SPECIFICATION -</u> CAPACITY: 18 CUBIC FEET ARE 509 LITERS DIMENSIONS : HEIGHT 168 CM X WIDTH 76 CM X DEPTH 81.6 CM. CURRENT: 1.3 TO 1.5 AMP. (SINGLE PHASE). COMPRESSOR: SIZE 1/4 RECIPROCATING 220	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											VOLTS. REFRIGERANT : R 134/R 600. DOOR : DOUBLE DOOR.	
104	DNQ106 684	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR- 38-42MM LG 75MM	DAMAGE CONTROL &FIRE FIGHTING EQUIPMENT	7 / EACH/N UMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DNQ105 520	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR- 38-42MM LG 75MM	DAMAGE CONTROL &FIRE FIGHTING EQUIPMENT	2 / EACH/N UMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DNQ105 580	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR- 38-42MM LG 75MM	DAMAGE CONTROL &FIRE FIGHTING EQUIPMENT	7 / EACH/N UMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DNQ106 683	1-3-166 DEVELOPED BY DTD	473099254274 8 / CLAMP REPAIR ,PIPE	DAMAGE CONTROL &FIRE FIGHTING EQUIPMENT	7 / EACH/N UMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
108	DNQ106 620	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/N UMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
109	DPC105640	NO DATA AVAILABLE	047350000011 / PASTE OIL RED OXIDE		50 / KILOGRAMME	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DNH102315	NO DATA AVAILABLE	4110500530125 / REFRIGE 12CU/FT DOUBLE DOOR 220V 50 HZ PHILCO/DAWLANCE/WAVES/PEL	DAWLANCE, WAVES, PHILICO (PAKISTAN), PEL (PAK)	1 / EACH/NUMBER	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
111	DPC100028	M101021	9135PK5085413 / ALCOHOL FOR CLEANING	C-3 SYSTEM	5 / CAN					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
112	DPK106941	20W-50	9150PK5079480 / LUB OIL 20W50 PKG 4LTR (FOR PETROL VEHICLES)	PETROL VEHICLES	3806 / LITER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
113	DPC102334	24137	6810002270410 / ISOPROPYL ALCOHOL (SIGMA ALDRICH 24137) (2.5 Liter Packing)		5 / GALLON					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
114	DPC103683	24137	6810002270410 / ISOPROPYL ALCOHOL (SIGMA ALDRICH 24137) (2.5 Liter Packing)		15 / GALLON					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
115	DNH98402	APPROVED MODEL	1308500530109 / REFRIGERATOR-4-CU-FT-ANY COMMERCIAL BRAND		1 / EACH/NUMBER	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
116	DNM104695	NO DATA AVAILABLE	4720705120470 / HOSE PIPE FOR HP AIR CONTAIN BRAIDED TEFLON COVERED WITH FIBER GLASS (LENGTH 60 METERS) INTERNAL DIA 10MM W.P 4000PSI 275BAR (WITH BOTH END FITTING ADAPTOR OF SS)	HP AIR COMPRESSOR	4 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - HOSE PIPE FOR HP AIR CONTAIN BRAIDED TEFLON COVERED WITH FIBER GLASS (LENGTH 60 METERS) INTERNAL DIA 10MM W.P 4000PSI 275BAR (WITH BOTH END FITTING ADAPTOR OF SS) GENERAL SPECIFICATION - HOSE PIPE FOR HP AIR CONTAIN BRAIDED TEFLON COVERED WITH FIBER GLASS (LENGTH 60 METERS) INTERNAL DIA 10MM W.P 4000PSI 275BAR (WITH BOTH END FITTING ADAPTOR OF SS)	
117	DPK106945	TCW3 NMMA	0721500000013 / LUB OIL OMD-23 FOR TWO STROKE OUTBOARD GASOLINE		1112 / LITER	NO DATA AVAILABLE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED	TECHNICAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY GENERAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ENGINE NMMA GRADE TCW3							D WITH QUOTATION		
118	DPK106953	STM7610A B2L	6850142724978 / SOLVANT DEGRAISSANT DE SECURIT STM7610A (WD-40) (05 Liter Packing)		5 / LITER	NO DATA AVAILAB LE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
119	DPK106951	10250	5970143407636 / VARNISH INSECT 10250 (DAMICOAT 2407-02 RED)	MAIN MOTOR SUBMARINES	4 / KILOGRAMME	NO DATA AVAILAB LE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
120	DPK106755	Q/SY16055-85/7253	9150FP0020012 / AVIATION LUBRICATING GREASE 7253 (SINOPEC RIPP 7253)		10 / KILOGRAMME	NO DATA AVAILAB LE				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
121	DNH101427		1308546011081 / REFRIGERATOR 10.CU FT-220V AC (NO FROST)		1 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DNM104143	2897133	5341735269954 / NO13 HOSE CLAMP		2 / EACH/NUMBER	CLASSIC V				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - NO13 HOSE CLAMP GENERAL SPECIFICATION - NO13 HOSE CLAMP	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
123	DPK105829	s4 p 100	915070527073 4 / compressor oil shell corena s4 p 100		10 / LITER	s4 p 100				QUOTATION TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991. FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A - FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A - REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES GENERAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C	

3. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A - FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A - REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES	
124	DNM103513	XNH542H A01	4310715293077 / COMPRESSOR DANFOSS 120000		1 / EACH/NUMBER	HRH054U LP6				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - COMPRESSOR DANFOSS MODEL HRH054U4LP6 GENERAL SPECIFICATION - COMPRESSOR DANFOSS MODEL HRH054U4LP6	
125	DPC105293	JOTAPRIME510 ALU. RED	8010785338806 / JOTAPRIME510 ALU. RED		250 / EACH/NUMBER	NA				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - JOTUN PAINT FOR SHIPSIDE ALUMINIUM RED 100DFT GENERAL SPECIFICATION - JOTUN PAINT FOR SHIPSIDE ALUMINIUM RED 100DFT	
126	DNM104121	7653614	4730735269974 / HOSE BAND		2 / EACH/NUMBER	CLASSIC V				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - HOSE BAND GENERAL SPECIFICATION - HOSE BAND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
127	DPC105649	407A	6830795293018 / REFRIGERANT GAS 407A (in non returnable cylinder of 40 kg net)		90 / KILOGRAMME	407A				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
128	DPC107013	S. No. 19 jotun anti-skid	8010785292318 / PAINT JOTUN ANTI-SKID SNO 19 (Dark COLOR) PARTICLE SIZE FINE		100 / LITER	JOTUN ANTI SKID				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
129	DPC105730	A020EEV2	8010705332825 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		20 / LITER	HIGHLY PERFUMED				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation. GENERAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.	
130	DNQ103811	PRM25/M ONIX REFILL	421070521224 2 / 25 KG DRUM OF MONEX POWDER FOR REFILLING.	DC &FF	60 / KILOGR AMME	PRM25	NIL	PRIME BUSINESS SYNDICATE SUITE NO 2, GROUND FLOOR, ABID CHAMBER, SHAHRA-E-LIAQUAT, KARACHI PAKISTAN PHONE: +92-21-32624690, 32213969 FAX: +92-21-32623828 E-MAIL: INFO@PRIME- FIRE.COM	PRIME BUSINES S SYNDICA TE	TDS/BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - SPECIFICATION ATTACH <u>GENERAL</u> SPECIFICATION - SPECIFICATION ATTACH	
131	DSB108527	CDCNPL4 7899/ MAT128- 0004F8/ (LOCAL) TR090RH- SEW	533014356877 8 / SEAL PLAIN FSP(JNB) (MESMA) TEFLON, S/STEEL & O- RING		351 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Make: NG France, Item locally available through M/s Star Engineering Specification: Item is combination of Teflon Seal, Rubberized O-ring & Metallic piece. Material inspection: Material inspection criteria not held Acceptance Criteria: Item can be accepted upon physical inspection <u>GENERAL</u> SPECIFICATION - Make: NG France, Item locally available through M/s Star Engineering Specification: Item is combination of Teflon Seal, Rubberized O-ring & Metallic piece. Material inspection: Material	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Inspection criteria not held Acceptance Criteria: Item can be accepted upon physical inspection	
132	DSB108526	(LOCAL) TR080RA- SEW/TR05 5RH-SEW	087003325533 O / SEALING RING DE-14 / TEFLON, BRASS & O- RING		70 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - COUNTRY NAME : USA SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG) GENERAL SPECIFICATION - COUNTRY NAME : USA SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG)	
133	DSB108525	5330JA- BAGUERU CHDE P20 / TR070RH- SEW	533014356877 7 / TEFLON SEAL FSP(JNB)		82 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
134	DSB108408	MAT 424- 0463	533174523326 3 / Seal for Regulation Tank		38 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Make/ Model (Local Source): Amir Enterprises (Ph # 0321-2030898 & 0333-3860521) SPECIFICATION: THE RUBBER SEAL USED IN REGULATING TANK COVERS. CHEMICAL COMPOSITION REPORT IS ATTACHED. STOCK SAMPLE: SAMPLE AVAILABLE (IF REQUIRED) Material: Polychloroprene Pressure Tested: Upto 100bar Dimension As per drawing (enclosed) Acceptance Criteria Physically inspection of rubber quality/ hardness by concerned rep. GENERAL SPECIFICATION - Make/ Model (Local Source): Amir Enterprises (Ph # 0321-2030898 & 0333-3860521) SPECIFICATION: THE RUBBER SEAL USED IN REGULATING TANK COVERS. CHEMICAL COMPOSITION REPORT IS ATTACHED. STOCK SAMPLE: SAMPLE AVAILABLE (IF REQUIRED) Material:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Polychloroprene Pressure Tested: Upto 100bar Dimension As per drawing (enclosed) Acceptance Criteria Physically inspection of rubber quality/ hardness by concerned rep.	
135	DSB108406	66795/841100	422014369684 / BRASSIERE-GONFLABLE-SC-ET-EVAC		17 / EACH/NUMBER	NF EN ISO 12402-3/A1 2010					TECHNICAL SPECIFICATION - Make: PLASTIMO Brand: 60-130cm 165N GENERAL SPECIFICATION - Make: PLASTIMO Brand: 60-130cm 165N	
136	DSB108409	LOCAL ITEM	0000000500001 / GARBAGE BAG		200 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag GENERAL SPECIFICATION - Length: 36" Round width: 09" Acceptance Criteria: As per sample • Garbage Bag used to stock garbage for onward throughway offboard • It must have enough seal (bottom) so that it doesn't leak • likely color blue • Having eyelets and a string/ sling (nylon or cotton) • Circular/ cylindrical shape • Bottom must be sealed/ punched so that it doesn't leak • Preferable if one piece (no joint/ seal) including bottom • Packing 20 per cotton/ bag	
137	DSB108310	LW-PM-14-3KV/TX/ LW-PM-14-VTX (LOCAL)	5310705251577 / lock washer dn14 (LOCAL)		1004 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm GENERAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Thickness - 1.5mm, 1.6mm d. Inner - 16mm	
138	DSB108303	RS-480 / RS-2	5130144018461 / GRINDING DISC 7 INCH		88 / EACH/NUMBER	RS2					TECHNICAL SPECIFICATION - Dimensions: 180x7,0x22, 23 GENERAL SPECIFICATION - Dimensions: 180x7,0x22,23	
139	DSB108528	SR20-7235330-VTX / (LOCAL) TR140RA-SEW/ (LOCAL) TR190RH-SEW	0870033265330 / SEALING RING DE-20 / TEFLON, BRASS & O-RING		126 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. ITEM IS COMBINATION OF TEFLON, METAL & O- RING WITH OUTER DIA 20MM 2. ITEM CAN BE TESTED IN WORKSHOP BY PLACING IN SYSTEM at 250 bar A. Service life of item (generally 06 x years for seals provided by different firms i.e. NG, Tripartite) be endorsed. b. Item is required to be properly preserved in packing to avoid moisture/environmental effects as the item pertains to rubberize O-rings nature. GENERAL SPECIFICATION - 1. ITEM IS COMBINATION OF TEFLON, METAL & O- RING WITH OUTER DIA 20MM 2. ITEM CAN BE TESTED IN WORKSHOP BY PLACING IN SYSTEM at 250 bar A. Service life of item (generally 06 x years for seals provided by different firms i.e. NG, Tripartite) be endorsed. b. Item is required to be properly preserved in packing to avoid moisture/environmental effects as the item pertains to rubberize O-rings nature.	
140	DSB108407	AV19990970045	0870131703439 / Aluminum Filter Metal AL-Mg 4.5 M		56 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 GENERAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183	
141	DSB108309	AV19990970045	0870131703439 / Aluminum		56 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Filter Metal AL-Mg 4.5 M		AMME	LE					Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 GENERAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183	
142	DSB108523	TEFLON O-RING, RUBBERIZED O-RING, METALLIC O-RING / (LOCAL) TR055RA-SEW	0870033245330 / SEALING RING DE-10, RUSH RING / TEFLON, BRASS & O-RING		53 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Part No. : Not Available Make: Unknown Supplier: DCN / Tripartite Sealing Ring also known as 'Rush Ring', comprises of 03 x parts described as follows: 1. Teflon O-Ring 2. Rubberized O-Ring 3. Metallic O-Ring Dimensions of Teflon part: Outer Dia: 18.30 mm Inner Dia: 12.30 mm Thickness: 1.5 mm Dimensions of Rubber part: Outer Dia: 12.60 mm Inner Dia: 9.0 mm Thickness: 1.80 mm Dimensions of Metallic part: Outer Dia: 9.30 mm Inner Dia: 5.5 mm Thickness: 1.4 mm Make: NG France, Item locally available through M/s Star Engineering.. Specification: Item is combination of Teflon Seal, Rubberized O-ring & Metallic piece Material inspection: Material inspection criteria not held Acceptance Criteria: Item can be accepted upon physical inspection. SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG) GENERAL SPECIFICATION - Part No. : Not Available Make: Unknown Supplier: DCN / Tripartite Sealing Ring also known as 'Rush Ring', comprises of 03 x parts described as follows: 1. Teflon O-Ring 2. Rubberized O-Ring 3. Metallic O-Ring Dimensions of Teflon part: Outer Dia: 18.30 mm Inner Dia: 12.30 mm Thickness: 1.5 mm Dimensions of Rubber part: Outer Dia: 12.60 mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Inner Dia: 9.0 mm Thickness: 1.80 mm Dimensions of Metallic part: Outer Dia: 9.30 mm Inner Dia: 5.5 mm Thickness: 1.4 mm Make: NG France, Item locally available through M/s Star Engineering.. Specification: Item is combination of Teflon Seal, Rubberized O-ring & Metallic piece Material inspection: Material inspection criteria not held Acceptance Criteria: Item can be accepted upon physical inspection. SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG)	
143	DSB108302	4011890052334	5130725155229 / FLAP GRINDING DISK (SIZE 125 X 22.23 MM)		570 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Size: 125 X 22.23MM 3 YEARS FROM DATE OF MANUFACTURE oem/made: RHODIUS GERMANY Acceptance Criteria: Concerned rep will inspect and practically test in workshop. GENERAL SPECIFICATION - Size: 125 X 22.23 MM 3 YEARS FROM DATE OF MANUFACTURE oem/made: RHODIUS GERMANY Acceptance Criteria: Concerned rep will inspect and practically test in workshop.	
144	DSB108301	ITD/221033-ITD-VTX	2990545344966 / Exhaust Bellow 6 Holes		2 / EACH/NUMBER	MAIN ENGINE					TECHNICAL SPECIFICATION - The Exhaust Bellow is a flexible, high-temperature-resistant connector designed to absorb vibration, thermal expansion, and movement in the exhaust system. It helps prevent leaks, reduces stress on pipes, and ensures smooth and reliable exhaust flow. GENERAL SPECIFICATION - The Exhaust Bellow is a flexible, high-temperature-resistant connector designed to absorb vibration, thermal expansion, and movement in the exhaust system. It helps prevent leaks, reduces stress on pipes, and ensures smooth and reliable exhaust flow.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
145	DSM108411	068N2103	4820144762791 / THERMO EXPANSION VALVE		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	