

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 05-10-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF108533	srt6krmxli	6130995556240 / apc smart ups srt 6000va		1 / EACH/NUMBER	SRT6KR MXLI					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
2	DNS107620	5294904/5473171	2930016421728 / PUMP COOLING SYSTEM ENGINE (Water Pump)	Water Pump	1 / EACH/NUMBER	OPTION WP97593	0	500 JACKSON ST COLUMBUS	CUMMINS INC.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
3	DNF108750	APC BRAND SMC2000I / GX9-2000	6130785166752 / UPS 2KVA 2H O/P 220V 2000VA	PSS (CCTV SYS)	2 / EACH/NUMBER	APC BRAND/GX9-2000		M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC International CO., LTD		TECHNICAL SPECIFICATION - OEM & SOA:M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China . GENERAL SPECIFICATION - OEM & SOA:M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China .	
4	DNS107618	5291050	2815016474845 / Lubricating Oil Pump	Lubricating Oil Pump	1 / EACH/NUMBER	OPTION LP9082	0	500 JACKSON ST COLUMBUS	CUMMINS INC.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
5	DNF108550	128-5739	5995795185150 / DATA CABLE 24 CORE 0.25MM	HF TX/RX XK2100L	125 / METER	XK-2100L	NOT	FARNELL UK WAREHOUSE PHONE NO+448701200208	FARNELL UK WAREHOUSE PHONE NO+448701200208		TECHNICAL SPECIFICATION - DATA CABLE 24 CORE 0.25 MM GENERAL SPECIFICATION - DATA CABLE 24 CORE 0.25MM	
6	DNG93941	803-1385714-8/0245 2IN	4820004830677 / VALVE-GATE UNTHREADED PIPE 2	FOR USE WITH WATER, OIL&GAS	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - VALUE 02 INCHES SOCKET, WELD PIPE THREAD SERIES UNS CLASS 3A STEAM NONRISING GENERAL SPECIFICATION - VALUE 02	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCHES SOCKET, WELD PIPE THREAD SERIES UNS CLASS 3A STEAM NONRISING	
7	DN0107434	ZR81KCE-TFD	431078528070 4 / Compressor (CLD-17, 17P)		1 / EACH/NUMBER	ZR81K3E-TFD					TECHNICAL SPECIFICATION - cooling capacity: 17kw power: 5.15 kw OEM : COPELAND FRANCE SA61 R EMILE ZOLA69150 DECINES CHARPIEUTEL72020357#FAX7849 7024#TLX305972# GENERAL SPECIFICATION - cooling capacity: 17kw power: 5.15kw OEM : COPELAND FRANCE SA61 R EMILE ZOLA69150 DECINES CHARPIEUTEL72020357#FAX7849 7024#TLX305972#	
8	DNG104123	MPN=P C 451	535000192504 7 / CLOTH ABRASIVE		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DNG103816	MPN=P C 451	535000192504 7 / CLOTH ABRASIVE		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
10	SNG107908	5000S4823F841499 REVG	473000926962 6 / STRAINER SEDIMENT SIZE 1/1/2 INCH BRONZE	HPAC	14 / EACH/NUMBER						TECHNICAL SPECIFICATION - bronze body size: 1/1/2 INCH threaded or flanged pipeline inline mouting naval ship piping system cast brinze corrosion-resistant housing removable perforated or mesh filter element threaded clean out cap sealing gasket GENERAL SPECIFICATION - bronze body size: 1/1/2 INCH threaded or flanged pipeline inline mouting naval ship piping system cast brinze corrosion-resistant housing removable perforated or mesh filter element threaded clean out cap sealing gasket	
11	DNG107980	576139/FS P-0008-12	432000368318 6 / PUMP UNIT CENTRIFUGAL	SELF	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Model: 777D - Bronze 777H - Aluminum b. Motor Rating: HP - 5 Phase - 3 Cycle - 60 RPM - 3450 Voltage - 115,220,440 Ac g.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Capacity: 140 GPM at 70 ft Total Head 200 GPM at 50 ft Total Head i. Cable: 45 feet of Conductor Type PHOF – 9 (9030 cm) j. Fresh Water Temperature: 1300 f k. Sea Water Temperature: 1300 f Specification: Maximum discharge flow rate: 180.0 GALLON Total Head:50 FEET gallons per minutes Operating speed at rated capacity: 50.000 feet/110. 000 FEET media for which designed: water, salt pumping element operating position: vertical centrifugal pump design: OEM/MANUFACTURERS/CODE: 83590/ STAR ENGINEERING WORKS radial flow cerntifugal pump impeller quantity: 1 centrifugal pump impeller suction type: single stage quantity: 1 pump quantity: 1 intake connection quantity: 1 intake connection type: threaded internal INTAKE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 nh DISCHARGE CONNECTION QUANTITY: 1 DISCHARGE CONNECTION TYPE: threaded internal/PIN LOCK SYSTEM DISCHARGE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 NH/2.5" PRIME MOVER TYPES: electric motor PRIME MOVER COOLING MEDIUM: air/WATER PRIME MOVER QUANTITY: 1 CURRENT TYPE: ac VOLTAGE IN VOLTS: 440 FREQUENCY IN HERTZ: 50/60 HZ PHASE: three CURRENT RATING IN AMPS: 7.5 INCLOSURE TYPE: fully inclosed ENVIRONMENTAL PROTECTION: submersible COOLING METHOD: self ventilated SPECIAL FEATURES: controller has magnetic casing, unit will operate in	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											horizontal or any midway position MAXIMUM DISCHARGE PRESSURE 180 GALLONS PER MINUTES AND ITS TOTAL HEAD IS 50. FEET. GENERAL SPECIFICATION - a. Model: 777D – Bronze 777H – Aluminum b. Motor Rating: HP – 5 Phase – 3 Cycle – 60 RPM – 3450 Voltage – 115,220,440 Ac g. Capacity: 140 GPM at 70 ft Total Head 200 GPM at 50 ft Total Head i. Cable: 45 feet of Conductor Type PHOF – 9 (9030 cm) j. Fresh Water Temperature: 1300 f k. Sea Water Temperature: 1300 f Specification: Maximum discharge flow rate: 180.0 GALLON Total Head: 50 FEET gallons per minutes Operating speed at rated capacity: 50.000 feet/110.000 FEET media for which designed: water, salt pumping element operating position: vertical centrifugal pump design: OEM/MANUFACTURERS/CODE: 83590/ STAR ENGINEERING WORKS radial flow centrifugal pump impeller quantity: 1 centrifugal pump impeller suction type: single stage quantity: 1 pump quantity: 1 intake connection quantity: 1 intake connection type: threaded internal INTAKE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 nh DISCHARGE CONNECTION QUANTITY: 1 DISCHARGE CONNECTION TYPE: threaded internal/PIN LOCK SYSTEM DISCHARGE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 NH/2.5" PRIME MOVER TYPES: electric motor PRIME MOVER COOLING MEDIUM: air/WATER PRIME MOVER QUANTITY: 1 CURRENT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TYPE: ac VOLTAGE IN VOLTS: 440 FREQUENCY IN HERTZ: 50/60 HZ PHASE: three CURRENT RATING IN AMPS: 7.5 INCLOSURE TYPE: fully inclosed ENVIRONMENTAL PROTECTION: submersible COOLING METHOD: self ventilated SPECIAL FEATURES: controller has magnetic casing, unit will operate in horizontal or any midway position MAXIMUM DISCHARGE PRESSURE 180 GALLONS PER MINUTES AND ITS TOTAL HEAD IS 50. FEET.	
12	DNG108098	576139/FS P-0008-12	432000368318 6 / PUMP UNIT CENTRIFUGAL	SELF	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - a.</u> Model: 777D – Bronze 777H – Aluminum b. Motor Rating: HP – 5 Phase – 3 Cycle – 60 RPM – 3450 Voltage – 115,220,440 Ac g. Capacity: 140 GPM at 70 ft Total Head 200 GPM at 50 ft Total Head i. Cable: 45 feet of Conductor Type PHOF – 9 (9030 cm) j. Fresh Water Temperature: 1300 f k. Sea Water Temperature: 1300 f Specification: Maximum discharge flow rate: 180.0 GALLON Total Head:50 FEET gallons per minutes Operating speed at rated capacity: 50.000 feet/110. 000 FEET media for which designed: water, salt pumping element operating position: vertical centrifugal pump design: OEM/MANUFACTURERS/CODE: 83590/ STAR ENGINEERING WORKS radial flow centrifugal pump impeller quantity: 1 centrifugal pump impeller suction type: single stage quantity: 1 pump quantity: 1 intake connection quantity: 1 intake connection type: threaded internal INTAKE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 nh DISCHARGE CONNECTION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											QUANTITY: 1 DISCHARGE CONNECTION TYPE: threaded internal/PIN LOCK SYSTEM DISCHARGE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 NH/2.5" PRIME MOVER TYPES: electric motor PRIME MOVER COOLING MEDIUM: air/WATER PRIME MOVER QUANTITY: 1 CURRENT TYPE: ac VOLTAGE IN VOLTS: 440 FREQUENCY IN HERTZ: 50/60 HZ PHASE: three CURRENT RATING IN AMPS: 7.5 INCLOSURE TYPE: fully inclosed ENVIRONMENTAL PROTECTION: submersible COOLING METHOD: self ventilated SPECIAL FEATURES: controller has magnetic casing, unit will operate in horizontal or any midway position MAXIMUM DISCHARGE PRESSURE 180 GALLONS PER MINUTES AND ITS TOTAL HEAD IS 50. FEET. <u>GENERAL SPECIFICATION</u> - a. Model: 777D - Bronze 777H - Aluminum b. Motor Rating: HP - 5 Phase - 3 Cycle - 60 RPM - 3450 Voltage - 115,220,440 Ac g. Capacity: 140 GPM at 70 ft Total Head 200 GPM at 50 ft Total Head i. Cable: 45 feet of Conductor Type PHOF - 9 (9030 cm) j. Fresh Water Temperature: 1300 f k. Sea Water Temperature: 1300 f Specification: Maximum discharge flow rate: 180.0 GALLON Total Head: 50 FEET gallons per minutes Operating speed at rated capacity: 50.000 feet/110.000 FEET media for which designed: water, salt pumping element operating position: vertical centrifugal pump design: OEM/MANUFACTURERS/CODE: 83590/ STAR ENGINEERING WORKS radial flow centrifugal pump	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											impeller quantity: 1 centrifugal pump impeller suction type: single stage quantity: 1 pump quantity: 1 intake connection quantity: 1 intake connection type: threaded internal INTAKE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 nh DISCHARGE CONNECTION QUANTITY: 1 DISCHARGE CONNECTION TYPE: threaded internal/PIN LOCK SYSTEM DISCHARGE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 NH/2.5" PRIME MOVER TYPES: electric motor PRIME MOVER COOLING MEDIUM: air/WATER PRIME MOVER QUANTITY: 1 CURRENT TYPE: ac VOLTAGE IN VOLTS: 440 FREQUENCY IN HERTZ: 50/60 HZ PHASE: three CURRENT RATING IN AMPS: 7.5 INCLOSURE TYPE: fully inclosed ENVIRONMENTAL PROTECTION: submersible COOLING METHOD: self ventilated SPECIAL FEATURES: controller has magnetic casing, unit will operate in horizontal or any midway position. MAXIMUM DISCHARGE PRESSURE 180 GALLONS PER MINUTES AND ITS TOTAL HEAD IS 50. FEET.	
13	DNJ1059 87	15643- 93J00	294076522180 2 / FILTER, FUEL (L)	SUZUKI DF300AP 300 HP OBM	4 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION -</u> <u>NIL</u> <u>GENERAL SPECIFICATION -</u> <u>NIL</u>	
14	DNF1059 89	30 PX	663576516844 0 / DENSITY METER	DENSITY METER	1 / EACH/N UMBER	30 PX	CAB 18146	METTLER-TOLEDO ANALYTICAL GMBH CH- 8603 SWITZERLAND	METTLER -TOLEDO ANALYTICAL GMBH CH-8603 SWITZER LAND		<u>TECHNICAL SPECIFICATION - M/S</u> <u>SPEEDY AUTOMATIC PLOT NO</u> <u>166-A GHULAM ALI MEMON ROAD</u> <u>SINDHI MUSLIM HOUSING</u> <u>SOCIETY KARACHI TEL: 021-</u> <u>34328859</u> <u>GENERAL</u> <u>SPECIFICATION - M/S SPEEDY</u> <u>AUTOMATIC PLOT NO 166-A</u> <u>GHULAM ALI MEMON ROAD</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SINDHI MUSLIM HOUSING SOCIETY KARACHI TEL: 021-34328859	
15	DNF106248	30 PX	6635765168440 / DENSITY METER	DENSITY METER	1 / EACH/NUMBER	30 PX	CAB 18146	METTLER-TOLEDO ANALYTICAL GMBH CH-8603 SWITZERLAND	METTLER-TOLEDO ANALYTICAL GMBH CH-8603 SWITZERLAND		TECHNICAL SPECIFICATION - M/S SPEEDY AUTOMATIC PLOT NO 166-A GHULAM ALI MEMON ROAD SINDHI MUSLIM HOUSING SOCIETY KARACHI TEL: 021-34328859 GENERAL SPECIFICATION - M/S SPEEDY AUTOMATIC PLOT NO 166-A GHULAM ALI MEMON ROAD SINDHI MUSLIM HOUSING SOCIETY KARACHI TEL: 021-34328859	
16	DNJ106907	8M0102482 / 8M0117247	3040715214971 / GEAR HOUSING ASSEMBLY Complete, Silver (Standard XX-Long)(1.75:1)	Mercury OBM Engine	1 / EACH/NUMBER	300 HP Mercury	2B469929	Murcery Marine W6250 Pioneer Road Fond du Lac Wisconsin USA	Murcery Marine USA		TECHNICAL SPECIFICATION - 12 teeth with corresponding spline connection gear ratio: 1.75:01 for verado height case: 8.75 (222 mmm) width: 31 (787 mm) length : 53 (1346) weight : 56-62 kg (123-136 lbs) GENERAL SPECIFICATION - 12 teeth with corresponding spline connection gear ratio: 1.75:01 for verado height case: 8.75 (222 mmm) width: 31 (787 mm) length : 53 (1346) weight : 56-62 kg (123-136 lbs)	
17	DNS109611	PAAE021257	2815FT1022608 / Flexible Element	Flexible Mounting	24 / EACH/NUMBER	PAAF253598	0	TARHAAJANTIE 2 VAASA	WARTSILA FINLAND OY	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
18	DNS109615	FIG. 103LK-PN10 DN200	4820FT1004847 / Globe Check Valve (S.D.N.R. Angle Type) PN10 DN200	Main Propulsion Sea Water Cooling System	3 / EACH/NUMBER	25600HI.0002	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATIO N		
19	DNS109 608	DBDH6K1 X/315	4820123216019 / Pressure Relief Valve	Hydraulic Power Unit	2 / EACH/N UMBER	08B14076 01000	0	ZUM EISENGIESSER 1 LOHR	BOSCH REXROT H AG - INDUSTRIAL HYDRAU LICS-	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
20	DNS109 599	FIG.5820-PN10 DN100	4820FT1004740 / Butterfly Valve (with Lever Actuated) PN10 DN100	Main Propulsion Fresh Water Cooling System	6 / EACH/N UMBER	25600HI. 0003	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
21	DNS109 606	FIG. 5820BR-PN16 DN150	4820FT1017128 / Butterfly Valve (with Lever Actuated) PN16 DN150	Piping Elements	11 / EACH/N UMBER	52100AE. 0002	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
22	DNS109 604	FIG. 103LK-PN16 DN150 S2. 2	4820FT1017138 / Globe Check Valve (S.D.N.R. Angle Type) PN16 DN150	Piping Elements	1 / EACH/N UMBER	52100AE. 0002	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
23	DNS109 616	FIG.4620-PN10 DN450 S2. 2	4820FT1018224 / Double Flanged Buterfly Valve	Main Propulsion Sea Water Cooling System	1 / EACH/N UMBER	25600HI. 0002	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE	TDS/BROCHURE OR PHOTOGRAPH OF	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									TICARET LTD.STI.	ITEM MUST BE ENCLOSED WITH QUOTATION		
24	DNS109598	FIG.1170-PN16 DN100	4730FT1017148 / Pipe Coupling PN16 DN100	Piping Elements	1 / EACH/NUMBER	52100AE.0002	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
25	DNS109609	4-HKE120-E-BV B ITEM12	4820FT1005090 / Relief Valve	Hydraulic Power Unit	2 / EACH/NUMBER	4-HKE120-E-BV B	0	VORWEIDE 4 BREMEN	BESI MARINE SYSTEMS GMBH	TDS/BROCHURE OR PHOTOGRAPH OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
26	DNJ108099	701-48320-70	5820765170579 / CABLE REMOTE CONTROL 20 FEET	OBM 90 HP YAMAHA	16 / EACH/NUMBER			JAPAN	JAPAN		<u>TECHNICAL SPECIFICATION - STANDARD SPECIFICATION - GENERAL SPECIFICATION - STANDARD SPECIFICATION</u>	
27	DNF106283	LDH 0615/00	6710PK5072899 / WIPER UNIT MODEL NO.LDH 0615/00		3 / EACH/NUMBER	LDH 0615/00					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
28	DNF106886	HU953UV	8040705009081 / ARALDITE AW 106 HARDNER	EM LOG	13 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Colour (visual) Neutral Pale yellow Specific gravity ca.1.15 ca. 0.95 ca. 1.05 Viscosity at 25 C 30-50 20-35 30-45 Pot Life (100 gm at 25 C) ca. 100 minutes <u>GENERAL SPECIFICATION -</u> Colour (visual) Neutral Pale yellow Specific gravity ca.1.15 ca. 0.95 ca.1.05 Viscosity at	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											25 C 30-50 20-35 30-45 Pot Life (100 gm at 25 C) ca.100 minutes	
29	DNJ103807	6P3-24563-01	294076523342 4 / FILTER		1 / EACH/N UMBER	300 HP Yamaha OBMs 4 stroke V6 (F300BET) /WS24A					TECHNICAL SPECIFICATION - A. Specification / Technical data /Testing /Acceptance criteria: Filter is the main component of fuel system. It provides 10 micron filtration to remove contaminates and water from fuel. Protects fuel injector & other sensitive fuel system components and maintains optimum engine performance. B. Technical parameters of store i.e Dimensions /sizes and etc: The element is a direct fit internal cartridge that installs into the OEM housing without modification and includes the sealing O-ring. GENERAL SPECIFICATION - A. Specification / Technical data /Testing /Acceptance criteria: Filter is the main component of fuel system. It provides 10 micron filtration to remove contaminates and water from fuel. Protects fuel injector & other sensitive fuel system components and maintains optimum engine performance. B. Technical parameters of store i.e Dimensions /sizes and etc: The element is a direct fit internal cartridge that installs into the OEM housing without modification and includes the sealing O-ring.	
30	DNT104879	3950140903	534073530851 0 / CHANNEL PLATE		4 / EACH/N UMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
31	DNT104882	323301424 6	533073530851 7 / END PLATE GASKET		2 / EACH/N UMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
32	DNZ97615	1B2242002	471072007005 0 / UPVC TEE DN 25		100 / EACH/N UMBER	HSRO-15B					TECHNICAL SPECIFICATION - UPVC TEE DN 25 GENERAL SPECIFICATION - UPVC TEE DN 25	
33	DNF91442	HID RP40	581071527971 1 / HID ICLASS		1 / EACH/N	hid					TECHNICAL SPECIFICATION - i RFID card reader i, HID iClass SE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			R40 SE reader		UMBER						reader & R40/ U90 GENERAL SPECIFICATION - & RFID card reader & HID iClass SE reader & R40/ U90	
34	DNF107819	ITD/VE/S. Sockets/F P.1012	593050523486 3 / Switch Socket TWO PIN		13 / EACH/N UMBER	VE/S. Sockets/F P.1012					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
35	DCD109233		845570144626 8 / BADGE ARM BLUE SINGLE ANCHOR-BASE CLOTH 100 % POLYSTER		4000 / EACH/N UMBER						TECHNICAL SPECIFICATION - BADGE ARM BLUE SINGLE ANCHOR-BASE CLOTH 100 % POLYSTER GENERAL SPECIFICATION - BADGE ARM BLUE SINGLE ANCHOR-BASE CLOTH 100 % POLYSTER	item required as per tender sample
36	DCD109235		845570300974 6 / SURFACE SHIP INSIGNIA CHROME CPO AND SAILOR		500 / EACH/N UMBER						TECHNICAL SPECIFICATION - SURFACE SHIP INSIGNIA CHROME CPO AND SAILOR GENERAL SPECIFICATION - SURFACE SHIP INSIGNIA CHROME CPO AND SAILOR	item required as per tender sample
37	DCD109234		845550130043 7 / PAK MARINE INSIGNIA CPOs / SAILORS		400 / EACH/N UMBER						TECHNICAL SPECIFICATION - PAK MARINE INSIGNIA CPOs / SAILORS GENERAL SPECIFICATION - PAK MARINE INSIGNIA CPOs / SAILORS	item required as per tender sample
38	DCD109239		845550503867 0 / BADGE CAP MINIATURE GOLDEN FOR CPOS		2400 / EACH/N UMBER						TECHNICAL SPECIFICATION - MATERIAL BLAZER FABRIC COLOUR PANTONE SHADE ANCHOR STAINLESS STEEL RING AROUND ANCHOR FIVE POINTED STAR GENERAL SPECIFICATION - MATERIAL BLAZER FABRIC COLOUR PANTONE SHADE ANCHOR STAINLESS STEEL RING AROUND ANCHOR FIVE POINTED STAR	item required as per tender sample
39	DNF107952	PFS4207-4GT-DP/DH-HS4208-4GT-90	702570524048 5 / 4 channel POE switch with complete accessories		1 / EACH/N UMBER	PFS4207-4GT-DP					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
40	DCD109236		845550080115 2 / BADGE CAP CPO GOLD		1300 / EACH/N UMBER						TECHNICAL SPECIFICATION - BADGE CAP CPO GOLD <u>GENERAL</u> SPECIFICATION - BADGE CAP CPO GOLD	item required as per tender sample
41	DCD109237		845550080115 3 / BADGE CAP POs GOLD		1300 / EACH/N UMBER						TECHNICAL SPECIFICATION - BADGE CAP POs GOLD <u>GENERAL</u> SPECIFICATION - BADGE CAP POs GOLD	item required as per tender sample
42	DGP105312	A360 PLUS	702571531623 4 / A3 SIZE FLATBED SCANNER		1 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - null <u>GENERAL SPECIFICATION -</u> null	
43	DCD109238		845550193866 9 / BADGE CAP MINIATURE GOLDEN FOR PETTY OFFICERS		2400 / EACH/N UMBER						TECHNICAL SPECIFICATION - material blazer fabric colour pantone shade Anchor Stainless Steel Ring around Anchor Five pointed Star <u>GENERAL SPECIFICATION -</u> material blazer fabric colour pantone shade Anchor Stainless Steel Ring around Anchor Five pointed Star	item required as per tender sample
44	DGP109922	NIL	773070529296 8 / LED TV 43 INCH		25 / EACH/N UMBER						TECHNICAL SPECIFICATION - null <u>GENERAL SPECIFICATION -</u> null	
45	SNG107910	ACB/MCC B 600A	000050000082 7 / AIR CIRCUIT BREAKER 600AMPS 500 VOLTS AC3PHASE 60HZ FUJIEA60		2 / EACH/N UMBER	EG603C					TECHNICAL SPECIFICATION - 600 AMP (03 PHASE) 500 VOLTS AC (50/60 HZ) OVERLAD SHORT CIRCUIT TRIP (AIR BREAKER) TRIP TYPE: THERMAL MAGNETIC OR ELECTRONIC TRIP UNIT PANEL OR SWITCHBOARD MOUNT IEC/UL TYPE PROTECTION <u>GENERAL</u> SPECIFICATION - 600 AMP (03 PHASE) 500 VOLTS AC (50/60 HZ) OVERLAD SHORT CIRCUIT TRIP (AIR BREAKER) TRIP TYPE: THERMAL MAGNETIC OR ELECTRONIC TRIP UNIT PANEL OR SWITCHBOARD MOUNT IEC/UL TYPE PROTECTION	
46	DGP110243	NO DATA AVAILABL E	005150000046 7 / F(MD)15 DISCHARGE SLIP		100500 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH 5.75" WIDTH 8" 60 GSM ± 5% White Color Paper printed With Black Ink Pad (100 Pages) <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											LENGTH 5.75" WIDTH 8" 60 GSM ± 5% White Color Paper printed With Black Ink Pad (100 Pages)	
47	DGP109 961		743570512703 1 / RACK 6U ALONGWITH ACCESSORIE S AND INSTALLATIO N	STANDALONG COMPONENT ROUTER CISCO 3825	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - make/brand: generic country of origen: local/china GENERAL SPECIFICATION - make/brand: generic country of origen: local/china	
48	DGP109 883	SONY/SAMSUNG/LG/TCL 20, 21,18, 32 INCH	773070505918 2 / LED 32 INCH		4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
49	DNG104 922	S3608S51 2 / 308SFFC	311000198241 9 / BEARING BALL ANNULAR SZ 40.00X90.00MMX1.4375IN	BRINE PUMP MOTOR	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
50	DGP110 005	CP1525N/ CP1515N/ HP COLOR LASER 150A PRINTER 4ZB94A	361070506112 0 / HP COLOR LASER JET CP1515N PRINTER	SELF/ANY COMPUTER OR LAPTOP	1 / EACH/N UMBER	CP1515N/ HP COLOR LASER 150A PRINTER 4ZB94A					TECHNICAL SPECIFICATION - SPECIFICATION: a. Model name & series number : HP Color Laser Jet Printer Pro M155a b. Print quality: 600 x 600 dpi c. Paper handling: 150 Sheet input tray 1. d. Paper sizes: A4, Letter, etc e. Toner Uses: HP 215A Series cartridges f. Size & weight: 392 x 435 x 244.2 mm & 13.3 kg g. Power supply: 220V-240V AC, 50/60 Hz (A)TYPE:COLOR. (B) PRINT TECHNOLOGY:COLOR LASER. (C)PROCESSOR SPEED: 450 MHZ. (D)STANDARD RAM:96 MB. (E)MAX RAM:352 MB. (F) RESOLUTION:600X600 dpi. (G) PRINT SPEED COLOR:8ppm. (H) PRINT SPEED B/W:12 PPM. PRICE OFLASER JET CP1515 RS:46,490/-. GENERAL SPECIFICATION - SPECIFICATION: a. Model name & series number : HP Color Laser Jet Printer Pro M155a b. Print quality:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											600 x 600 dpi c. Paper handling: 150 Sheet input tray 1. d. Paper sizes: A4, Letter, etc e. Toner Uses: HP 215A Series cartridges f. Size & weight: 392 x 435 x 244.2 mm & 13.3 kg g. Power supply: 220V-240V AC, 50/60 Hz (A)TYPE:COLOR. (B) PRINT TECHNOLOGY:COLOR LASER. (C)PROCESSOR SPEED: 450 MHZ. (D)STANDARD RAM:96 MB. (E)MAX RAM:352 MB. (F) RESOLUTION:600X600 dpi. (G) PRINT SPEED COLOR:8ppm. (H) PRINT SPEED B/W:12 PPM. PRICE OFLASER JET CP1515 RS:46,490/-.	
51	DGP110002	E2725HM/E2722H/M 27FW	743570521488 5 / LCD MONITOR 27 inch	Instructor Console	2 / EACH/NUMBER	E2725HM/E2417H (24") /e2722h/F 22P MCR Simulator	NOT KNOWN	PLOT NO.C-4/A, S.I.T.E., Karachi, Pakistan. Tel: +92921)32571111-2 Fax: +92(21)32553111		DELL	TECHNICAL SPECIFICATION - VX 2781 MH WITH: A) IPS PANEL AND THIN PROFILE. B) FRAMELESS BEZEL WITH UNIQUE TRIANGULAR STAND. C) 75 HZ REFRESH RATE. D) VGA AND HDMI INPUTS. RESOLUTION-1920X1080@60 HZ (FHD) DISPLAY SIZE -27 INCH (DIAGONAL) DISPLAY TYPE -IPS WITH LED LACK LIGHT ANTI-GLARE INPU27 T -1 VGA &2 HDMI WEIGHT -3.68 KGS (UNPACKED)GENERAL SPECIFICATION - VX 2781 MH WITH: A) IPS PANEL AND THIN PROFILE. B) FRAMELESS BEZEL WITH UNIQUE TRIANGULAR STAND. C) 75 HZ REFRESH RATE. D) VGA AND HDMI INPUTS. RESOLUTION-1920X1080@60 HZ (FHD) DISPLAY SIZE -27 INCH (DIAGONAL) DISPLAY TYPE -IPS WITH LED LACK LIGHT ANTI-GLARE INPU27 T -1 VGA &2 HDMI WEIGHT -3.68 KGS (UNPACKED)	
52	DGP103222	50AU7000	773070513217 9 / TV LCD 46/49/50 INCH	-	5 / EACH/NUMBER	50AU7000		PK		AUTHORITY LETTER # NS-5/9205/SS	TECHNICAL SPECIFICATION - S. No Technical Specification Technical Data a. View Angle 178" b. Brightness 500cd/m2 c. Size 46/49 Inch d. Response Time 5ms e. Brand	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN. SPECS	Dimension
									C/NHQ/07 DT 24/05/08		Samsung f. Screen Type LED g. Smart TV Yes h. HDMI 3 j. USB 2 k. Operating System Tizen l. Width x Height x Depth (With stand) 46"= 71.64cm x 26.13 cm 49"= 110.28cm x 63.78cm x 5.91cm m. Warranty 01 Year n. Model 46 Inch LED HD TV (UA46F6100AR) 49 Inch LED HD TV (949N5300) p. Resolution (Pixels) 1920 x 1080 q. Color Black <u>GENERAL SPECIFICATION -</u> S.No Technical Specification Technical Data a. View Angle 178" b. Brightness 500cd/m2 c. Size 46/49 Inch d. Response Time 5ms e. Brand Samsung f. Screen Type LED g. Smart TV Yes h. HDMI 3 j. USB 2 k. Operating System Tizen l. Width x Height x Depth (With stand) 46"= 71.64cm x 26.13 cm 49"= 110.28cm x 63.78cm x 5.91cm m. Warranty 01 Year n. Model 46 Inch LED HD TV (UA46F6100AR) 49 Inch LED HD TV (949N5300) p. Resolution (Pixels) 1920 x 1080 q. Color Black	
53	DNM106554	LF3959	291001250192 2 / LUB OIL FILTER	CUMMINS ENGINE 5.9 QSB USA	2 / EACH/NUMBER	5.9 QSB	22066008	M/S CUMMINS INS CATENBERG STRAAT 1-2840 RUMST BELGIUM	CUMMINS UK		<u>TECHNICAL SPECIFICATION - LUB OIL FILTER</u> full flow lube oil filter cummins qsb5.9 isb5.9 thread size 1-16 un-2b synthetic design <u>GENERAL SPECIFICATION - LUB OIL FILTER</u> full flow lube oil filter cummins qsb5.9 isb5.9 thread size 1-16 un-2b synthetic design	
54	DGP110010	4003DN	743570513863 2 / PRINTER HP LASER JET	COMPUTER	3 / EACH/NUMBER	NO DATA AVAILABLE		PK	PAKISTAN		<u>TECHNICAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port Both <u>GENERAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
55	DGP109 921	4003DN	743570513863 2 / PRINTER HP LASER JET	COMPUTER	2 / EACH/N UMBER	NO DATA AVAILAB LE		PK		PAKISTA N	<u>TECHNICAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
56	DNF8900 3	ST4000NM 0053/ST40 00VX000	702578520784 9 / 4TB SURVEILLANC E HARD DISK- SATA FOR NVR	CCTV System ST4000VX000 CHINA	1 / EACH/N UMBER	ST4000V X000	NA	Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888		CHINA	<u>TECHNICAL SPECIFICATION -</u> Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32 <u>GENERAL SPECIFICATION -</u> Marketing Name: Surveillance HDD Cache Multisegmented (MB): 64 Bytes per Sector : 4096 Cameras Supported : up to 32	
57	SNG107 906	00675	531571522001 3 / Pin, cotter	CIWS Vulcan Phalanx	50 / EACH/N UMBER	N/A	NA	100 PLASTICS AVE. PITTSFIELD, UNITED STATES Tele No. 413-494-2849 Fax No. 413-494-6413			<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
58	DGP109 546	HP colour Laser Jet Enterprise M751DN	702578514129 0 / HP Laserjet Color Printer A3	ILS SYSTEM	1 / EACH/N UMBER	HP COLOUR LASER JET ENTERP RISE M751DN		US		HAWLET PACKAR D,11445 COMPAQ CENTRE DRIVE WEST, HOUSTO N TAXAS 77070, USA	<u>TECHNICAL SPECIFICATION - 1.</u> Paper Loading Tray 3 X 500 2. Resolution 1200 x 1200 dpi 3: Print Speed Upto 40 PPM 4. Color 04 Colors 5. OEM Address HEWLETT PACKARD, 11445 Compaq Centre Drive West, Houston, Texas 77070, USA 6. Supplier Address UNI Computer Bank, 10 Aamir Trade Center, PECHS Block 2, Karachi- 75400 <u>GENERAL SPECIFICATION -</u> 1. Paper Loading Tray 3 X 500 2.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Resolution 1200 x 1200 dpi 3. Print Speed Upto 40 PPM 4. Color 04 Colors 5. OEM Address HEWLETT PACKARD, 11445 Compaq Centre Drive West, Houston, Texas 77070, USA 6. Supplier Address UNI Computer Bank, 10 Aamir Trade Center, PECHS Block 2, Karachi-75400	
59	DNF106998	DGS-008D/E/DF3709B1001785	5930715181162 / D-LINK 8 PORT NETWORK SWITCH	VIRDI AC-4000	4 / EACH/NUMBER	DGS 1008 D/E	NA	USA/CANADA		USA/CANADA	TECHNICAL SPECIFICATION - 8 PORT DESKTOP SWITCH SPORTING.803.3 ETHERNET, 80230FAST ETHERNET OR 8023ab GB ETHERNET CATS ETHERNT CABLEGENERAL SPECIFICATION - 8 PORT DESKTOP SWITCH SPORTING.803.3 ETHERNET, 80230FAST ETHERNET OR 8023ab GB ETHERNET CATS ETHERNT CABLE	
60	DCW109840		8430701241008 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 9		170 / PAIR						TECHNICAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 9 GENERAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 9	ITEM REQUIRED AS PER SPECIFICATION
61	DCW109842		8430701241010 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 11		170 / PAIR						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	ITEM REQUIRED AS PER SPECIFICATION
62	DCW109841		8430701241009 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 10		170 / PAIR						TECHNICAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 10 GENERAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 10	ITEM REQUIRED AS PER SPECIFICATION
63	DCW109838		8430701241006 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 7		170 / PAIR						TECHNICAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 7 GENERAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 7	item required as per specification

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
64	DCW109 843		843070124101 1 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 12		170 / PAIR						TECHNICAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 12 <u>GENERAL</u> SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 12	ITEM REQUIRED AS PER SPECIFICA TION
65	DCW109 839		843070124100 7 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 8		170 / PAIR						TECHNICAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 8 <u>GENERAL</u> SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 8	ITEM REQUIRED AS PER SPECIFICA TION
66	DCW109 837		843070124100 5 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 6		170 / PAIR						TECHNICAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 6 <u>GENERAL</u> SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 6	item required as per specification
67	DGP110 239		751070504225 9 / PLAIN PAPER (OFF SET)VRG SHEET 80GSM ± 5% SIZE 610X914MM OR 24X36 INCHES,VRG, COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE	STATIONERY NA10S	1 / REAM						TECHNICAL SPECIFICATION - PLAIN PAPER (OFF SET)VRG SHEET 80GSM ± 5% SIZE 610X914MM OR 24X36 INCHES, VRG,COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE <u>GENERAL SPECIFICATION - PLAIN</u> PAPER (OFF SET)VRG SHEET 80GSM ± 5% SIZE 610X914MM OR 24X36 INCHES,VRG,COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE	
68	DGP110 238		751070504225 6 / PLAIN PAPER (OFFSET) VRG SHEET 80 GSM ± 5% SIZE 914MMX1016M M OR 36X40 INCHES,VRG, COLOR WHITE (PRODUCTS PULP AND	STATIONERY NA10S	1 / REAM						TECHNICAL SPECIFICATION - PLAIN PAPER(OFFSET) VRG SHEET 80 GSM ± 5% SIZE 914MMX1016MM OR 36X40 INCHES,VRG,COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE <u>GENERAL</u> SPECIFICATION - PLAIN PAPER (OFFSET) VRG SHEET 80 GSM ± 5% SIZE 914MMX1016MM OR 36X40 INCHES,VRG,COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PAPER) WOOD FREE									
69	DGP110 241		753070500717 1 / WHITE OFFSET PAPER SIZE 58.42CMX91.44CM		18 / REAM						TECHNICAL SPECIFICATION - GM 80 (+-) 10 gm GENERAL SPECIFICATION - GM 80 (+-) 10 gm	
70	DGP109 882	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		4 / SET	CORE I5					TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. GENERAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.	
71	DGP110001	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		2 / SET	CORE I5					TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. GENERAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.	
72	DGP110 187	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		2 / SET	CORE I5					TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>GENERAL SPECIFICATION - 1. CPU</u> Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.	
73	DGP106333	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		3 / SET	CORE I5					TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>GENERAL SPECIFICATION</u> - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.	
74	DGP110106	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		2 / SET	CORE I5					TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. GENERAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.	
75	DGP109 931	CORE I5	702570524609 1 / PERSONAL COMPUTER CORE i5 12th GENERATION or above		2 / SET	CORE I5					TECHNICAL SPECIFICATION - 1. CPU Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>GENERAL SPECIFICATION - 1. CPU</u> Technology= Intel® Core i5 Processor 12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above). 2. System Memory= Minimum 8 GB DDR4 SDRAM. 3. Hard Disk= 512 GB ssd or NVME. 4. Keyboard= USB (3D Optical) . 5. Mouse= USB (Optical LED) 6. LED= 19" (Min) or higher (same brand) 7. LAN= Yes (Built in 1000) 8. Warranty= Minimum 01 Year or as provided by OEM, 9. OPERATING SYSTEM= MS - DOS ONLY (WITHOUT PRE-INSTALLED WINDOW). 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
76	DGP110007	NO DATA AVAILABLE	7435705114870 / PERSONAL COMPUTER DUAL CORE/i3/CORE I7 (AS PER NHQ APPROVED SPEC)	SELF	1 / SET						genuineness. d. Online PC verification. e. PC without modification/ upgradation. <u>TECHNICAL SPECIFICATION - SPECIFICATION OF PC:</u> 1. HP/DELL CORE I7 SYSTEM OR HIGHER EQUIVALENT. 2. CPU TECHNOLOGY: INTEL @ CORE I7 (12TH GENERATION OR ABOVE) (MINIMUM 2.4 TO 4.7 GHZ OR ABOVE), 3. SYSTEM MEMORY: 16 GB RAM DDR3/DDR4 4. HARD DISK: 01 TB SSD 5. OPTICAL DISK DRIVE: DVD RW 6. KEYBOARD: WIRED/USB 7. MOUSE: WIRED/USB 8. LED: 18.5" HDMI DISPLAY 9. LAN: ETHERNET CARD: 10/100/1000 MBPS 10. WARRANTY: 3 YEARS 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION WINDOW-10 OR ABOVE). 12. GRAPHICS: INTEL @ HD GRAPHICS 750, (MINIMUM 2 GB SHARED/ DEDICATED GRAPHIC CARD) 13. MISCELLANEOUS REQUIREMENTS: A. OEM SEALED GENUINE PC. B. AUTHORIZED DEALER/ OEM COC. C. CERTIFICATE OF GENUINENESS. D. ONLINE PC VERIFICATION. E. PC WITHOUT MODIFICATION/ UPGRADATION. F. PC WITHOUT WIFI & BLUETOOTH IS REQUIRED. <u>GENERAL SPECIFICATION - SPECIFICATION OF PC:</u> 1. HP/DELL CORE I7 SYSTEM OR HIGHER EQUIVALENT. 2. CPU TECHNOLOGY: INTEL @ CORE I7 (12TH GENERATION OR ABOVE) (MINIMUM 2.4 TO 4.7 GHZ OR ABOVE), 3. SYSTEM MEMORY: 16 GB RAM DDR3/DDR4 4. HARD DISK: 01 TB SSD 5. OPTICAL DISK DRIVE: DVD RW 6. KEYBOARD:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WIRED/USB 7. MOUSE: WIRED/USB 8. LED: 18.5" HDMI DISPLAY 9. LAN: ETHERNET CARD: 10/100/1000 MBPS 10. WARRANTY: 3 YEARS 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION WINDOW-10 OR ABOVE). 12. GRAPHICS: INTEL @ HD GRAPHICS 750, (MINIMUM 2 GB SHARED/ DEDICATED GRAPHIC CARD) 13. MISCELLANEOUS REQUIREMENTS: A. OEM SEALED GENUINE PC. B. AUTHORIZED DEALER/ OEM COC. C. CERTIFICATE OF GENUINENESS. D. ONLINE PC VERIFICATION. E. PC WITHOUT MODIFICATION/ UPGRADATION. F. PC WITHOUT WIFI & BLUETOOTH IS REQUIRED.	
77	SNF105287	FSP21660-40	621078521667 2 / LED LIGHTS 2x2 SUSPENDED LIGHTING PANEL WITH FIX BRAND:SE WORLD MODEL: 4014 SMD	LED Lights 2? x2? suspended lighting panel with fix	33 / SET	se-cl-2x2 panel	NA	FOSHAN Electrical & Lighting Co. Ltd. 64 North FengJiang Road, Foshan China.		FOSHAN Electrical & Lighting Co. Ltd.	TECHNICAL SPECIFICATION - shape ;square lamp power;48 w size ;600 mm pf ;> 0.95 LUMINOUS ;100 LM/W LAMP MATERIAL ; ALUMINUM IP GRADE ;IP 40 VOLTAGE ;AC 90-265 V Brand: SE WORLD Model: 4014 SMD GENERAL SPECIFICATION - shape ;square lamp power;48 w size ;600 mm pf ;> 0.95 LUMINOUS ;100 LM/W LAMP MATERIAL ; ALUMINUM IP GRADE ;IP 40 VOLTAGE ;AC 90-265 V Brand: SE WORLD Model: 4014 SMD	
78	DGP110231	NO DATA AVAILABL E	005150000046 2 / FORM F (MD)10 CLINICAL CHART		120500 SHEET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH: 8 INCH WIDTH: 11.5 INCH WEIGHT: 50 GSM + 5% PAPER COLOUR: WHITE PRINTING COLOUR: BLACK INK PRINT ON BOTH SIDES PACKING: 100 PAGES OF PAD, 100 PAD IN PER BOX GENERAL SPECIFICATION - SIZE: LENGTH: 8 INCH WIDTH: 11.5 INCH WEIGHT: 50 GSM + 5% PAPER COLOUR:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WHITE PRINTING COLOUR: BLACK INK PRINT ON BOTH SIDES PACKING: 100 PAGES OF PAD, 100 PAD IN PER BOX	
79	DGP110 240	F(MD)-67	753070504926 0 / F(MD)-67 LOCAL PURCHASE OF MEDICINES (COLOR "Y"," P","W","G") BOOK OF 400 PAGES		150 / PAD						TECHNICAL SPECIFICATION - PAPER COLOR= (YELLOW, PINK, WHITE, GREY), PAPER WEIGHT= GSM: 48 ± 5% BOOK OF 400 PAGES, REQUIRED IN PAD, GENERAL SPECIFICATION - PAPER COLOR= (YELLOW, PINK, WHITE, GREY), PAPER WEIGHT= GSM: 48 ± 5% BOOK OF 400 PAGES, REQUIRED IN PAD.	
80	DGP110 184	42u rack toten	743578524982 1 / 42u rack (toten 800 x 1000) k3 server cabinet		3 / UNIT	toten					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
81	DNF8998 6	SURTA150 0XL	613001653907 6 / POWER SUPPLY APC SMART -UPS ON-LINE , 1500VA 120V		1 / EACH/N UMBER	SRT1500 XLA/SUR TA1500X L					TECHNICAL SPECIFICATION - APC SMART -UPS ON-LINE , 1500VA 120V, 6X5-15R NEMA OUTLETS SMART SLOT EXTENDED RUN TIME GENERAL SPECIFICATION - APC SMART -UPS ON-LINE , 1500VA 120V, 6X5-15R NEMA OUTLETS SMART SLOT EXTENDED RUN TIME	
82	DNF1033 96	DS- 2TD6267- 100C4L/W / ds- 2td6266- 100c2l/v2	671078527309 3 / THERMAL & OPTICAL BI- SPECTRUM NETWORK POSITIONING SYSTEM		1 / EACH/N UMBER	2td6266					TECHNICAL SPECIFICATION - THERMAL MODULE IMAGE SENSOR (VOX UNCOOLED FOCAL PLANE ARRAYS RESOLUTION 640 X 512 PIXEL INTERVAL 17UM RESPONSE WAVEBAND 8UM TO 14 UM NETD LESS THAN 35MK (@25 C, F #+1.0) FOCAL LENGTH 100MM FOCUS MODE SEMI- AUTO MANUAL IFOV 0.17 M RAD APERTURE F1.0 FIELD OF VIEW 6.23 X 4.98 (H X V) MIN. FOCUSING DISTANCE 10M DIGITAL ZOOM X1, X2, X4, X8	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											TESTING CRITERIA ACCEPTANCE ¿ Perimeter protection ¿ function based on intelligence algorithm; intrusion, region entrance & exit ¿ Temperature exception alarm for fire prevention ¿ Fire detection smoke detection algorithm ¿ 640 x 512 resolution 17 um, VO x UFPA, NETD 35MK ¿ Image processing technology: liner, histogram, and self -adaptive thermal AGC mode, DDE, 3D DNR ¿ Thermal channel supports EIS, conflicted with intelligent function <u>GENERAL SPECIFICATION</u> - ¿ THERMAL MODULE ¿ IMAGE SENSOR (VOX UNCOOLED FOCAL PLANE ARRAYS ¿ RESOLUTION 640 X 512 PIXEL INTERVAL 17UM ¿ RESPONSE WAVEBAND 8UM TO 14 UM ¿ NETD LESS THAN 35MK (@25 C, F #+1.0) ¿ FOCAL LENGTH 100MM ¿ FOCUS MODE SEMI-AUTO MANUAL ¿ IFOV 0.17 M RAD ¿ APERTURE F1.0 ¿ FIELD OF VIEW 6.23 X 4.98 (H X V) ¿ MIN. FOCUSING DISTANCE 10M ¿ DIGITAL ZOOM X1, X2, X4, X8 TESTING CRITERIA ACCEPTANCE ¿ Perimeter protection ¿ function based on intelligence algorithm; intrusion, region entrance & exit ¿ Temperature exception alarm for fire prevention ¿ Fire detection smoke detection algorithm ¿ 640 x 512 resolution 17 um, VO x UFPA, NETD 35MK ¿ Image processing technology: liner, histogram, and self -adaptive thermal AGC mode, DDE, 3D DNR ¿ Thermal channel supports EIS, conflicted with intelligent function	
83	DNF109380	A-2060/P2240/VP-1240A	5835765013357 / Amplifier 30W/ 60W/ 120W/ 240W	P.A SYSTEM.	1 / EACH/NUMBER	A-2060/P2240				TDS/BROCHER OR PICS OF ITEM MUST	<u>TECHNICAL SPECIFICATION -</u> General Spec: RATED OUTPUT: 30W/ 60W/ 120W/ 240W, BASE AND TREBLE CONTROL POWER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			TOA JAPAN							BE ENCLSED WITH QUOTATIO N	CONSUMPTION: 72W/150W/4A, MIC INPUT: 3 ELECTRONICALLY BALANCED AUX INPUT: 2 OUTPUT: PHANTOM POWER FOR MIC 1 AC & DC OPERATION <u>GENERAL SPECIFICATION</u> - General Spec: RATED OUTPUT: 30W/ 60W/ 120W/ 240W, BASE AND TREBLE CONTROL POWER CONSUMPTION: 72W/150W/4A, MIC INPUT: 3 ELECTRONICALLY BALANCED AUX INPUT: 2 OUTPUT: PHANTOM POWER FOR MIC 1 AC & DC OPERATION	
84	DNS109 605	FIG.5820-DN150 PN10 or PN10 DN150 BR	4810FT100010 9 / Butterfly Valve (with Lever Actuated) PN10 DN150	Piping Elements	27 / EACH/N UMBER	52400PN FT.0008	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLSED WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
85	DNS109 613	FIG. 5820BR-PN16 DN200	4820FT101712 9 / Butterfly Valve (with Lever Actuated) PN16 DN200	Piping Elements	8 / EACH/N UMBER	52100AE. 0002	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLSED WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
86	DNS109 617	FIG.5830-PN10 DN450	4820FT101822 3 / Wafer Buterfly Valve	Main Propulsion Sea Water Cooling System	2 / EACH/N UMBER	25600HI. 0002	0	BUTTIM IS MERKEZI. B-5 NO.1416 ORHANGAZI	KURTEK VANA SANAYI VE TICARET LTD.STI.	TDS/BROCHER OR PICS OF ITEM MUST BE ENCLSED WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
87	DGP105 008	CP1525N/ CP1515N/ HP COLOR	361070506112 0 / HP COLOR LASER JET	SELF/ANY COMPUTER OR LAPTOP	1 / EACH/N UMBER	CP1515N/ HP COLOR LASER					<u>TECHNICAL SPECIFICATION - SPECIFICATION: a. Model name & series number : HP Color Laser Jet</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		LASER 150A PRINTER 4ZB94A	CP1515N PRINTER			150A PRINTER 4ZB94A					Printer Pro M155a b. Print quality: 600 x 600 dpi c. Paper handling: 150 Sheet input tray 1. d. Paper sizes: A4, Letter, etc e. Toner Uses: HP 215A Series cartridges f. Size & weight: 392 x 435 x 244.2 mm & 13.3 kg g. Power supply: 220V-240V AC, 50/60 Hz (A)TYPE:COLOR. (B) PRINT TECHNOLOGY:COLOR LASER. (C)PROCESSOR SPEED: 450 MHZ. (D)STANDARD RAM:96 MB. (E)MAX RAM:352 MB. (F) RESOLUTION:600X600 dpi. (G) PRINT SPEED COLOR:8ppm. (H) PRINT SPEED B/W:12 PPM. PRICE OFLASER JET CP1515 RS:46,490/-. <u>GENERAL SPECIFICATION -</u> SPECIFICATION: a. Model name & series number : HP Color Laser Jet Printer Pro M155a b. Print quality: 600 x 600 dpi c. Paper handling: 150 Sheet input tray 1. d. Paper sizes: A4, Letter, etc e. Toner Uses: HP 215A Series cartridges f. Size & weight: 392 x 435 x 244.2 mm & 13.3 kg g. Power supply: 220V-240V AC, 50/60 Hz (A)TYPE:COLOR. (B) PRINT TECHNOLOGY:COLOR LASER. (C)PROCESSOR SPEED: 450 MHZ. (D)STANDARD RAM:96 MB. (E)MAX RAM:352 MB. (F) RESOLUTION:600X600 dpi. (G) PRINT SPEED COLOR:8ppm. (H) PRINT SPEED B/W:12 PPM. PRICE OFLASER JET CP1515 RS:46,490/-.	
88	DGP106 986	SONY/SAMSUNG/LG/TCL 20, 21,18, 32 INCH	773070505918 2 / LED 32 INCH		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	