

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 20-10-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNM106 627	219-3240	668501521831 1 / THERMOSTAT FLOW CONTROL	CATERPILLAR GENSET D3512B (YBB1) USA	4 / EACH/NUMBER	NA	CAT3512 BEYBB00 583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	
2	DNM106 924	3905375	471001234288 8 / TUBE FUEL SUPPLY	CUMMINS STANDBY EMERGENCY GENERATOR 4BT3-9D UK	1 / EACH/NUMBER	4BT3-9D	MAD 46950895 RSD 46954407	CUMMINS LTD T/A CUMMINS UK RUTHERFORD DRIVE, PARK FARM INDUSTRIAL ESTATE, WELLINGBOROUGH, NORTHAMPTONSHIRE, UK Tel : 01933 672 200 Fax : 01933 403 200 Email/URL : www.cummins.com	CUMMINS LTD UK	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
3	DNM107 091	947975	530573515235 6 / HOLLOW SCREW	VOLVO PENTA ENGINE	4 / EACH/NUMBER	VOLVO PENTA D6-370AB	20060324 41	AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-417 15 +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA	AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
4	DPK1092 74		915070512921 5 / LUB-OIL-SAE 20W-50 API SL	MT-VEHICALES FOR PETROL ENGINE	500 / LITER			PK	CALTEX PAKISTAN	TDS/BROUCHER OR PIC MUST BE	<u>TECHNICAL SPECIFICATION -</u> DEFSTAN 01-005 ISSUE 20. VISCOSITY TOLERANCE LIMIT ATTACHED IN WIMS PROFILE.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(Packing 04 liters & 20 LTRS))							ENCLOSED WITH QUOTATION	GENERAL SPECIFICATION - DEFSTAN 01-005 ISSUE 20. VISCOSITY TOLERANCE LIMIT ATTACHED IN WIMS PROFILE.	
5	DNM107090	943479/994564	4230995332968 / HOSE CLAMP (HEAT EXCHANGER AND EXPANSION TANK)	VOLVO PENTA MAIN ENGINE D6 370-AB	10 / EACH/NUMBER	D6-370D-E		AB VALVO PENTA SE 405 08 GOTHENBURG SWEDEN	SWEDEN	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - HOSE CLAMP(HEAT EXCHANGER AND EXPANSION TANK) ZINC PLATED W12.8MM I/D 55MMX70MM SZ 70MM 68/226 GENERAL SPECIFICATION - HOSE CLAMP(HEAT EXCHANGER AND EXPANSION TANK) ZINC PLATED W12.8MM I/D 55MMX70MM SZ 70MM 68/226	
6	DNM107623	FF5488/3959612	4330015300044 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD	1 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s Cummins Inc	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
7	DPK82134	MOBILUBE LS 85W-90	9150SV1200032 / LUBRICATING OIL MOBILUBE LS 85W-90	BOW AND STERN THRUSTER	180 / LITER	MOBILUBE LS 85W-90		EXXON MOBIL FUELS AND LUBRICANTS CO CHINA	EXXON MOBIL	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - LUBRICATING OIL MOBILUBE LS 85W-90 GENERAL SPECIFICATION - LUBRICATING OIL MOBILUBE LS 85W-90	
8	DNM105220	3101872/FS1040	2910015203411 / FILTER FUEL	CUMMINS ENGINE 550KVA, FILTER	1 / EACH/NUMBER	Cummins 4331009	793038093	CUMMINS INC PO BOX 3005 COLOMBUS INDIANA USA 47202	CUMMINS INC.	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Filter Type: Fuel Water Separator Test Standard SAEJ1985 Overall Height: 293.98 mm (11.574 inch) Outer Diameter: 118.11mm (4.65 inch) Gasket outside Diameter: 118.87mm (4.68 inch) Gasket Inside Diameter: 101.60mm (4.00 inch) Thread Size M85 x 2.7H internal CUMMINS INC PO BOX 3005 COLOMBUS INDIANA USA 47202 GENERAL SPECIFICATION - Filter Type: Fuel Water Separator Test Standard SAEJ1985 Overall Height: 293.98 mm (11.574 inch)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO. OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Outer Diameter: 118.11mm (4.65 inch) Gasket outside Diameter: 118.87mm (4.68 inch) Gasket Inside Diameter: 101.60mm (4.00 inch) Thread Size M85 x 2.7H internal CUMMINS INC PO BOX 3005 COLOMBUS INDIANA USA 47202	
9	DPK105823	GB495-65	9150705139823 / CALCIUM BASE GREASE GREY (KUNLUN) 15KG	BOATBEARING OF ELECTRIC WINCH	15 / KILOGRAMME	NO DATA AVAILABLE		UK	UK	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
10	DPK107861	GB491-1987#3	9150705139817 / CALCIUM BASE GREASE (KUNLUN) 15KG	GEARING OF MECHANISM TYPE	45 / KILOGRAMME	NO DATA AVAILABLE		UK	UK	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
11	DNM107623	FF5488/3959612	4330015300044 / FILTER FUEL	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD	1 / EACH/NUMBER	QSB6.7-305MD	74126404	CUMMINS ENGINE COMPANY, INC PO BOX 3005 COLUMBUS IN 47202-9982	CUMMINS ENGINE COMPANY	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - M/s</u> Cummins Inc 500 Jackson Street Columbus IN, USA <u>GENERAL</u> <u>SPECIFICATION - M/s Cummins Inc</u> 500 Jackson Street Columbus IN, USA	
12	DPC102884	H-300 HUX	8040735140710 / HARDNER (SET OF 2X1KG BOTTLE)	AC COMPRESSOR KALMAT GWADER	14 / SET	NO DATA AVAILABLE		00		TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - A.V</u> 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown, Flash point, 200f> <u>GENERAL</u> <u>SPECIFICATION - A.V 330-360,</u> Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown, Flash point, 200f>	
13	DPC108618	ZISE-15	6850705199639 / SUPER INSULATION (LIQUID ELECTRICAL INSULATION)	PCB PROTECTOR SPRAY ESTONIA	15 / BOTTLE	150 ML	NA	NANO PROTECH OU, Uus Sadama 21, Tallinn 10120, Estonia Phone +3726683242	NANO PROTECH	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> Form: Liquid Colour: Green Ignition Point: 250 Degree C <u>GENERAL</u> <u>SPECIFICATION - Form: Liquid</u> Colour: Green Ignition Point: 250 Degree C	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			OEM = NANO PROTECH, Packing = 150ML bottle							N		
14	DPK82131	3809441	915073516976 1 / SYNTHETIC TRANSMISSION OIL SAE75W-90 (Packing 20 LITRE)	VOLVO PENTA ENGINES	70 / LITER	SAE75W-90		AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669	VOLVO PENTA	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669 AB VOLVO PENTA PAKISTAN VPL PLOT 6 SECT 24 KORANGI INDUSTRIAL AREA KARACHI 2811+4669GENERAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO.COM/VOLVOPENTA 2811+4669 AB VOLVO PENTA PAKISTAN VPL PLOT 6 SECT 24 KORANGI INDUSTRIAL AREA KARACHI 2811+4669	
15	DPC109139	Comp A= EPA001, Comp B = EPA740	801099740433 3 / PAINT INTERGARD 400 DARK GREY (Comp A = 17 Ltrs + Comp B = 03 Ltrs)	HULL PRESERVATION OF F-22P FRIGATES	260 / LITER	NO DATA AVAILABLE		UK	INTERNATIONAL PAINTSLTD.P.O. BOX: 20980, ORIEL HOUSE 16 CANNAUGHT PLACE, LONDON, W22 2ZB, UNITED KINGDOM.	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY:M/S SEA TRADE COMPANY, KARACHIGENERAL SPECIFICATION - SOURCE OF AVAILABILITY:M/S SEA TRADE COMPANY, KARACHI	
16	DPC106368	HTA002	801032068740 5 / PAINT INTERTHERM 891	HULL PRESERVATION OF F-22P FRIGATES	60 / LITER	NO DATA AVAILABLE		UK	INTERNATIONAL PAINTSLTD.P.O.	TDS/BROUCHER OR PIC MUST BE	TECHNICAL SPECIFICATION - OEM ADD:INTERNATIONAL PAINTS LTD. P.O.BOX 20980, ORIEL HOUSE 16,CANNAUGHT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ALUMINIUM						BOX: 20980, ORIEL HOUSE 16 CANNAUGHT PLACE, LONDON, W22 2ZB, UNITED KINGDOM.	ENCLOSED WITH QUOTATION	PLACE, LONDON, W22 2ZB, UK. GENERAL SPECIFICATION - OEM ADD: INTERNATIONAL PAINTS LTD. P.O.BOX 20980, ORIEL HOUSE 16, CANNAUGHT PLACE, LONDON, W22 2ZB, UK.	
17	DPC106516	BS381C	8010991689269 / PAINT BRUSHING GREY	F-22P FRIGATES	12 / LITER	NO DATA AVAILABLE		UK	INTERNATIONAL PAINTS LTD. P.O. BOX: 20980, ORIEL HOUSE 16 CANNAUGHT PLACE, LONDON, W22 2ZB, UNITED KINGDOM.	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OEM ADD: INTERNATIONAL PAINTS LTD. P.O.BOX 20980, ORIEL HOUSE 16, CANNAUGHT PLACE, LONDON, W22 2ZB, UK. GENERAL SPECIFICATION - OEM ADD: INTERNATIONAL PAINTS LTD. P.O.BOX 20980, ORIEL HOUSE 16, CANNAUGHT PLACE, LONDON, W22 2ZB, UK.	
18	DNM107086	949841-VOLVO	5330270363930 / O-RING	VOLVO PENTA ENGINE	2 / EACH/NUMBER	NO DATA AVAILABLE		27	M/S AB VOLVO PENTA. CITY: GOTEBO RG SWEDEN GOTEBO RG	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
19	DPK105320	BH125GS A28	9150715223034 / MOBIL 1 TWO STROKE FULLY SYNTHETIC ENGINE OIL	SELF	50 / LITER	BLACK HAWK 125 LITE 2 STROKE	BLACK HAWK 125 LITE 2 STROKE	M/S BLACK HAWK PARAMOTOR USA 8591 HOGAN ROAD VALLEY SPRINGS CA USA TEL 209-418-5990	USA	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - USE IN BLACK HAWK PARAMOTOR GENERAL SPECIFICATION - USE IN BLACK HAWK PARAMOTOR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
20	DPK106625	A-A-2702	8030001032868 / PRESERVATIVE COMPOUND	GENERAL PURPOSE	3 / LITER	NO DATA AVAILABLE		US	MILITARY SPECIFICATIONS PROMULGATED BY MILITARY DEPARTMENTS/AGENCIES UNDER AUTHORITY OF DEFENSE STANDARDIZATION MANUAL 4120 3-M UNITED STATES	N TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION --</u> <u>GENERAL SPECIFICATION --</u>	
21	DPK106673	90890-69920	9150765168799 / YAMAHA GREASE 50g/TUBE)	SFB (ENGINE)	25 / TUBE	F350A	102563X35	YAMAHA CORPORATION USA /JAPAN	YAMAHA	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> YAMAHA CORPORATION USA <u>GENERAL SPECIFICATION</u> -YAMAHA CORPORATION USA /JAPAN	
22	DNM107093	860105/20707685	5330145035650 / GASKET	VOLVO ENGINE GRP BOAT	2 / EACH/NUMBER	NO DATA AVAILABLE		27		NCAGE: S3562	<u>TECHNICAL SPECIFICATION --</u> <u>GENERAL SPECIFICATION --</u>	
23	DNM107094	877072/861700	5330270363984 / VALVE STEM SEAT KIT	VOLVO ENGINE GRP BOAT	48 / EACH/NUMBER	NO DATA AVAILABLE		27		NCAGE: S3562	<u>TECHNICAL SPECIFICATION --</u> <u>GENERAL SPECIFICATION --</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
24	DPK108355	R 141b	6810715225084 / OIL FLUSHING AGENT R 141B	MAIN AC	60 / KILOGRAMME	R 141b	NA	COMSTAR INTERNATIONAL INC 20-45 128TH STREET COLLEGE POINT, NY 11356 +1 (800) 328-0142 USA www.comstarproducts.com	COMSTAR INTERNATIONAL INC	QUOTATION TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Transport package: Disposable cylinder RS-141b oil flushing agent GENERAL SPECIFICATION - Transport package: Disposable cylinder RS-141b oil flushing agent	
25	DPC106381	665 ALUMINIUM / JOTAMASTIC 85 ALUMINIUM	8010705185002 / JOTUN JOTAMASTIC 85 ALUMINIUM (PART A 16 LITER + PART B 4 LITER)	EXPOSED STEEL DECKS	100 / LITER			Jotun Paints, Inc. 9203 Highway 23 Belle Chasse, LA 70037 Telephone: (800) 229-3538 or (504) 394-3538 SDSJotun@jotun.com	JOTUN	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. MANUFACTURE TECHNICAL DATA SHEET 2. MANUFACTURE SAFETY DATA SHEET GENERAL SPECIFICATION - 1. MANUFACTURE TECHNICAL DATA SHEET 2. MANUFACTURE SAFETY DATA SHEET	
26	DPC106381	665 ALUMINIUM / JOTAMASTIC 85 ALUMINIUM	8010705185002 / JOTUN JOTAMASTIC 85 ALUMINIUM (PART A 16 LITER + PART B 4 LITER)	EXPOSED STEEL DECKS	100 / LITER			Jotun Paints, Inc. 9203 Highway 23 Belle Chasse, LA 70037 Telephone: (800) 229-3538 or (504) 394-3538 SDSJotun@jotun.com	JOTUN	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. MANUFACTURE TECHNICAL DATA SHEET 2. MANUFACTURE SAFETY DATA SHEET GENERAL SPECIFICATION - 1. MANUFACTURE TECHNICAL DATA SHEET 2. MANUFACTURE SAFETY DATA SHEET	
27	DPC107764	BOSTIK M501	8010795208200 / BOSTIK THINNERS / CLEANER M501	RHIB BOAT	85 / LITER	BOSTIK M501	NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON, SOMERSET, BA9 9RX, TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHAW INFLATABLES LTD	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - M501 IS USED TO CLEAN, DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 2402ADHESIVE. THINNING BOSTIK NE486, CLEANING GLUE BRUSHES. SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW TOP. HIGHLY FLAMMABLE PRODUCT AND MUST BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA. GENERAL SPECIFICATION - M501 IS USED TO CLEAN, DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 2402ADHESIVE. THINNING BOSTIK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											NE486,CLEANING GLUE BRUSHES.SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW TOP.HIGHLY FLAMMABLE PRODUCT AND MUST-BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA.	
28	DPC107 568	BOSTIK 2402	651079520819 7 / BOSTIK 2402 ADHESIVE + HARDENER	RHIB BOAT	90 / LITER	BOSTIK2 402		HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX,TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHA W INFLATA BLES LTD	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - BOSTIK 2402 CREATES A STRONG BOND WHICH IS RESISTANT TO HEAT -40 DEG C -90 DEG C,UV, SALTWATER AND HUMIDITY COVERAGE IS APPROX 4 SQUARE METER PER LITRE(VARIES WITH SURFACE).SUPPLIED AS 1 L TIN OF ADHESIVE AND A 40 ML BOTTLE OF BOSTIKURE D HARDENER.STORE B/W 5 DEG AND 25 DEG IN A DRY FLAMPROOF AREA. GENERAL SPECIFICATION - BOSTIK 2402 CREATES A STRONG BOND WHICH IS RESISTANT TO HEAT -40 DEG C -90 DEG C,UV, SALTWATER AND HUMIDITY COVERAGE IS APPROX 4 SQUARE METER PER LITRE(VARIES WITH SURFACE).SUPPLIED AS 1 L TIN OF ADHESIVE AND A 40 ML BOTTLE OF BOSTIKURE D HARDENER.STORE B/W 5 DEG AND 25 DEG IN A DRY FLAMPROOF AREA.	
29	DNM107 800	3593981	534073513423 4 / ANODE KIT	PROPULSION AND STEERING SYSTEM	5 / EACH/N UMBER	NO DATA AVAILAB LE		OC	VOLVO PENTA GOTEBU RG SWEDEN	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - BRAND: VOLVO PENTA ACTUAL WEIGHT: 1.78 MATERIAL: ZINC KIT INCLUDE ANODE BOLT GENERAL SPECIFICATION - BRAND: VOLVO PENTA ACTUAL WEIGHT: 1.78 MATERIAL: ZINC KIT INCLUDE ANODE BOLT	
30	DNQ106 987	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D	TDS/BROU CHER OR PIC MUST BE	TECHNICAL SPECIFICATION- NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL,	

S. No	LPR No	PART NO.	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ENCLOSED WITH QUOTATION	SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
31	DNQ107081	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
32	DNQ107281	B1 PRENEC	597099522452 6 / TAPE INSULATING	TAPE INSULATING (FF)	1 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND	TDS/BROUCHER OR PIC MUST	<u>TECHNICAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO. OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			38MM							BE ENCLOSED WITH QUOTATION	LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
33	DPC108480	COSMADEC-14	136573522800 / COSMADEC-14 EPOXY SEALER	DECK FLOOR	134 / KIT	COSMAD EC-14		LABCO FINE CHEMICALS ADDRESS: D-200, SHAHRA-E-SILK, S.I.T.E., KARACHI PHONE: 021-32562622 EMAIL: labcod200@yahoo.com	LABCO FINE CHEMICALS	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - MATERIAL TYPE: A BI-COMPONENT MEDIUM TO HIGH MOLECULAR WEIGHT EPOXY SEALER. COLOUR AVAILABILITY: CLEAR TRANSPARENT. FLASH POINT: COMP A: 130°C COMP B: > 180°C. THICKNESS: APPROXIMATELY 250 MICRONS PER COAT ON SMOOTH SURFACE. SHRINKAGE: MIN 0.0% MAX 0.001%. <u>GENERAL SPECIFICATION</u> - MATERIAL TYPE: A BI-COMPONENT MEDIUM TO HIGH MOLECULAR WEIGHT EPOXY SEALER. COLOUR AVAILABILITY: CLEAR TRANSPARENT. FLASH POINT: COMP A: 130°C COMP B: > 180°C. THICKNESS: APPROXIMATELY 250 MICRONS PER COAT ON SMOOTH SURFACE. SHRINKAGE: MIN 0.0% MAX 0.001%.	
34	DNM108189	AF879M	2940011996725 / AIR FILTER	CUMMINS DG QST30-G2	2 / EACH/N	QST30-G2	3175632	CUMMINS ENGINE COMPANY, INC. BOX	CUMMINS	TDS/BROUCHER OR	<u>TECHNICAL SPECIFICATION</u> - 650 KVA CUMMINS DG VTA28-G5 USA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
				USA	UMBER			3005 COLUMBUS, INDIANA, USA 47202	ENGINE COMPAN Y, INC. USA	PIC MUST BE ENCLOSE D WITH QUOTATIO N	AIR FILTER <u>GENERAL SPECIFICATION - 650 KVA CUMMINS DG-VTA28-G5 USA AIR FILTER</u>	
35	DNM107 956	2890S	4240TY520256 0 / 3M COMFORT LINE SAFETY GOGGLES 2890S SEALED VERSION	BV	130 / EACH/N UMBER	NA		VHKMHMN	-	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
36	DPC107 564	COSMADEC-13 EPOXY COMPOU ND	561070519749 8 / COSMADEC-13 EPOXY COMPOUND (COMP A+ COMP B) (Packing = KIT) (Color = Grey)	CHEMICAL	87 / KIT			M/S LABCO FINE CHEMICALS PH # 021-32562622 EMAIL: labcod200@yahoo. com	M/S LABCO FINE CHEMICA LS	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - COSMADEC-13 EPOXY COMPOUND COMP A: Blend of epoxy polymer, fillers and pigments COMP B: Curing agent</u> <u>GENERAL SPECIFICATION - COSMADEC-13 EPOXY COMPOUND COMP A: Blend of epoxy polymer, fillers and pigments COMP B: Curing agent</u>	
37	DPK8242 5	3809442	915014529737 0 / SYNTHETIC TRANSMISSIO N OIL SAE 75W-90 (5L PACKING)	VOLVO PENTA ENGINES	20 / LITER	SAE75W-90	VOLVO PENTA ENGINES	AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO. COM/VOLVOPENTA 2811+4669	VOLVO PENTA	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW. VOLVO.COM/VOLVOPENTA 2811+4669</u> <u>GENERAL SPECIFICATION - AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN +46 31 23 54 60 +46 31 22 89 37 556034-1330 HTTPS://WWW.VOLVO. COM/VOLVOPENTA 2811+4669</u>	
38	DPK1043 69	GREATWALL HM 100	9150SV523160 7 / LUBRICATING OIL GREATWALL HM 100	STERN TUBE	2000 / LITER	GREATWALL HM 100		SINOPEC CO, CHINA	CHEVRO N MARINE	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - LUBRICATING OIL GREATWALL HM 100 technical spec attached as document</u> <u>GENERAL SPECIFICATION - LUBRICATING OIL GREATWALL HM 100 technical spec attached as document</u>	
39	DPC107	NO DATA	044350044306	A/C NO 5 AND	48 /					TDS/BROU	<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	320	AVAILABLE	7 / Gas Nitrogen Technical (99.998% Pure Nitrogen Gas With Less Water Content (i.e. 4 PPM), In Buyer's/ Supplier's Returnable Cylinder of Water Capacity 45 to 55 Liters With Protection Cap.	6	CUBIC METER					CHER OR PIC MUST BE ENCLOSED WITH QUOTATION	CGA G-10.1 OF 2023 QVLs GRADE 'L' Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder. <u>GENERAL SPECIFICATION - CGA G-10.1 OF 2023 QVLs GRADE 'L'</u> Cylinder Specifications: 1. ISO 9809 (Part 1, 2 & 3) for Design, construction and testing of refillable seamless steel gas cylinders and tubes. 2. ISO 10297 for cylinder valves specification and type testing. 3. ISO 11114 (Part 1 & 2) for compatibility of cylinder and valve material with gas contents. 4. Certificates of service life of cylinder. 5. Certificates and periodic inspection record i.e. inspection and test reports of each cylinder including last hydrostatic test date and corresponding certificates. 6. Name of firm/third party testing authority conduction inspection, testing and certification of each cylinder.	
40	DPC107522		0474500001889 / CLEANING POWDER, 1 CWT.DRUM (BR.320 D CLASS	BR320D REVISED 1965 CLASS GROUP 0474 PG2	150 / KILOGRAMME					TDS/BROU CHER OR PIC MUST BE ENCLOSED WITH	<u>TECHNICAL SPECIFICATION</u> :- a. Type Cleaning Powder b. Age Group Any Age c. Brand Cesco Solutions d. Item weight 5 pounds or dependent upon market availability e. Packing material Woven Bag carton	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GROUP 0474 PG 2							QUOTATION	GENERAL SPECIFICATION - a. Type Cleaning Powder b. Age Group Any Age c. Brand Cesco Solutions d. Item weight 5 pounds or dependent upon market availability e. Packing material Woven Bag carton	
41	SPC109462		0474504740082 / CUPREX 1 BLOCK (PACKING 1 KG)	4FI SSDG SEA WATER PUMP	50 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - packing 1 kgGENERAL SPECIFICATION - packing 1 kg	
42	DPC107529	NO DATA AVAILABLE	0474500007028 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		50 / BAG					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0	
43	DPC106991		0473504730040 / ZINC PHOSPHIDE (RAT POISON)		1 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER:1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)GENERAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)	
44	DPC107110		0442509434479 / PAINT	PRIMER FOR FINISHING	50 / LITER					TDS/BROUCHER OR	TECHNICAL SPECIFICATION - 1. DEFSTAN 80-72/3 OF 2006 2.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PRIMING, LIGHT ADMIRALTY GREY FLASH POINT 23 DEGREE C	ACID AND ALKALI						PIC MUST BE ENCLOSED WITH QUOTATION	COLOUR SHADE NO 697 OF BS: 381 OF 1996 <u>GENERAL SPECIFICATION - 1. DEFSTAN 80-72/3 OF 2006</u> 2. COLOUR SHADE NO 697 OF BS:381 OF 1996	
45	DPC107082	106 OF BS381-C OF 1996	0442504420061 / PAINT VEHICLE CELLULOSE (ROYAL NAVY BLUE)	VEHICLES, DECORATIVE FINISHING	30 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - DEFSTAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.</u> <u>GENERAL SPECIFICATION - DEFSTAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.</u>	
46	DPC107085	S NO 120 SIMILAR	0442504420063 / PAINT WEATHER WORK(DARK GREY) (NSSD/C01/0442/GEN/173DT 060393)	WEATHER WORK	979.4 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
47	SPC109464		0442504420069 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		416 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
48	DPC107092		0442504420069 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		40 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
49	DPC107099	DEFSTAN 80-37/2 OF 2006	0442504420124 / Paint Cellulose White Finsihing for vehicles principal component Nitro Cellulose		150 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR,NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Base Flash Point 23									
50	DNQ107958	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		10 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
51	DNQ106663	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		2 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
52	DNQ106519	NO DATA AVAILABLE	0340599236243 / BAG CANVAS TOOL SACHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5		11 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" GENERAL SPECIFICATION - CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
53	DNQ106521	T-8802	0434720000005 / DIVING GOGGLES WITH SAFETY GLASS DOUBLE SEALING	PL-70	3 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FRAME.							N		
54	DPC105533	SPEC,DEF 1052 COLOURS TO BS 381C	0442509107035 / PAINT FNSHING GLOSS (SIGNAL RED NO537). NS/C01/GEN/566DT210902		285 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DPC102636		0443514430010 / CYLINDER NITROGEN GAS(EMPTY) FITTED WITH BRAND NEW VALVE (CAPACITY 45 KG)		10 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Gas Capacity ~6.0 m3 Water Capacity 40-45 L Hydraulic Test Pressure 22.5 MPa/225 Bar Nominal Working Pressure 15MPa/150 Bar Material 37Mn GENERAL SPECIFICATION - Gas Capacity ~6.0 m3 Water Capacity 40-45 L Hydraulic Test Pressure 22.5 MPa/225 Bar Nominal Working Pressure 15MPa/150 Bar Material 37Mn	
56	DNQ108508	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		2 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
57	DNQ107460	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		6 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control,, General dimension of the clamp is 190mm x 403 mm used to	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											support shoring spar of 150 mm timber.	
58	DPC107972		1365997456895 / LIQUID FOR FOGGING		6 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
59	DPC100743		0474502242463 / SOAP SCRUBBING		10 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose.</u>	
60	DNM107907	98262.1009	2945998275756 / OIL FILTER	COMPRESSOR 5415	2 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
61	DNM109392	0140-3840	2940715051848 / AIR FILTER	C55 D5 (4BT 3.3 G2) SERIAL NO. 68048207	3 / EACH/NUMBER	C55 D5				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - OEM: CUMMINS POWER GENERATION SYSTEM UPDATED VIDE GMT ORMARA LETTER GNT/YSD/5285 DATED 03 FEB 14</u> <u>GENERAL SPECIFICATION - OEM: CUMMINS POWER GENERATION SYSTEM UPDATED VIDE GMT ORMARA LETTER GNT/YSD/5285 DATED 03 FEB 14</u>	
62	DNM106910	2654407	2940010803861 / OIL FILTER	PERKIN D/E 606/Y6-102 OEM: ADAMJEE D/ENGG	1 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
63	DNM97930	1.524-975.0/1.	4320725107612 / KARCHER	KARCHER MACHINE	2 / EACH/NUMBER	HD 8/18-4 M* KAR				TDS/BROUCHER OR	<u>TECHNICAL SPECIFICATION -</u> Technical Specifications: Make :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		524.972.0	MACHINE	ALFRED KARCHER CO. GER	UMBER					PIC MUST BE ENCLOSED WITH QUOTATION	Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control <u>GENERAL SPECIFICATION</u> - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
64	DNM109 137	R3600-F48/bt-48-cnt-21	4120US506550 1 / CONDENSER (SEA WATER)	DOMETIC CRUISAIR AC COND UNIT WFAH48E 48000BTU 4TON USA	1 / EACH/NUMBER	BT-60-CTT-20				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - Refrigerant R-22 Sea water cooled condenser (BT-60-CTT-20) Suction accumulator size 7/8" (design pressure 450PSIG) Liquid receiver (design pressure 500PSIG) Solenoid valve size 3/8" Solenoid coil 220V Stainless steel drain tray complete copper piping 04 in No Tube <u>GENERAL SPECIFICATION</u> - Refrigerant R-22 Sea water cooled condenser (BT-60-CTT-20) Suction accumulator size 7/8" (design pressure 450PSIG) Liquid receiver (design pressure 500PSIG) Solenoid valve size 3/8" Solenoid coil 220V Stainless steel drain tray complete copper piping 04 in No Tube	
65	DNQ108 819	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR- 38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	2 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
66	DNQ106988	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	1 / EACH/NUMBER					D WITH QUOTATION TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
67	DNQ107520	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	1 / EACH/NUMBER					D WITH QUOTATION TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
68	DNQ107300	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	1 / EACH/NUMBER					D WITH QUOTATION TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
69	DNQ108740	1-3-150 DEVELOPED BY DTD	473099254274 7 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	1 / EACH/NUMBER					D WITH QUOTATION TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DNQ108530	1-3-166 DEVELOPED BY DTD	473099254274 8 / CLAMP REPAIR PIPE	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	3 / EACH/NUMBER					D WITH QUOTATION TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	DNQ108818	1-3-166 DEVELOPED BY	473099254274 8 / CLAMP REPAIR PIPE	DAMAGE CONTROL & FIRE	3 / EACH/NUMBER					D WITH QUOTATION TDS/BROUCHER OR PIC MUST	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		DTD		FIGHTING EQUIPMENT						BE ENCLOSED WITH QUOTATION	AVAILABLE	
72	DNQ109 242	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DNQ107 701	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DNQ108 741	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	4 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
75	DNQ108 531	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	4 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
76	DNQ107 130	11/454/3/1 0/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	1 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
77	DPC108 873	BS 2451, DEFSTAN: 80-73/1 OF 1977	8010701004136 / PAINT NON SLIPING PREMIXED (LIGHT GREY) BS2451, DEFSTAN 80-73/1	FINISHING NON SLIP	232 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0mm Thickness Level = 2.0mm to 3.0 mm GENERAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0 mm Thickness Level = 2.0mm to 3.0 mm	
78	DPC107 810	NO DATA AVAILABLE	8030992251687 / LOCTITE222	30MM GUN	1 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DPC106 622	SCOTCH SEAL5200 (8030-01-187-8439	8030705037635 / SEALING COMPOUND 3M MARINE Adhesive Sealant 5200 White) (295mL	HULL	107 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - REQUIREMENT OF SEALANT ARE AS UNDER GENERAL SPECIFICATION - REQUIREMENT OF SEALANT ARE AS UNDER	
80	DPK1079 43	20W-50	9150PK5079480 / LUB OIL 20W50 PKG 4LTR (FOR PETROL VEHICLES)	PETROL VEHICLES	68 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
81	DPK8756 9	RIMULA R3+30	9150705052441 / SHELL RIMULA R3+30 HIGH PERFORMANCE DIESEL OIL	DIESEL ENGINES (TRANSPORT)	209 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DPK1083 28	90790-BS802	9150705102424 / GEAR OIL (750CC X 1) FOR OBM ENGINE (GL4 OUTBOARD	OBM ENGINE, GEAR,MOBILE ASHARI PVTLTD.KAR	480 / TUBE					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - 750 ml Tube Packing GENERAL SPECIFICATION - 750 ml Tube Packing	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GEAR OIL SAE 90) OEM = YAMALUBE							QUOTATION		
83	DNM106832	MURPHY LTD PDS 100-007	668571504852 7 / OIL PRESSURE GAUGE 0-TO-100 PSI & 0-7 BAR MURPHY SWITCH GAUGE	CUMMINS DIESEL ENGINE 34.5 KVA (USA/UK)	5 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - DIMENSION / SIZE:</u> Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch Gauge <u>GENERAL SPECIFICATION - DIMENSION / SIZE:</u> Gauge size 2 x 2 inches, Dial 2 ¼ inches with installation flayer bush and 6 points male/female connector and wire. 0 to 100 PSI & 0 to 7 Bar Murphy Switch Gauge	
84	DPC104846	NIL-SHELF LIFE 3 MONTH	681070503926 3 / DECK COMPOUND FLASH POINT 89C SP-GR-1009 (ANTI SKID)	LOCAL PURCHASE	20 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
85	DNF108827	SMT30001 C/SURTD3 000XLI/30 00VA APC	613071506382 3 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/NUMBER	MODEL ESP-808 (E) /SYSTEK PVT.				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL</u> <u>GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
86	DPK107948	TCW3 NMMA	072150000013 / LUB OIL OMD-23 FOR TWO STROKE OUTBOARD GASOLINE ENGINE NMMA GRADE TCW3		70 / LITER	NO DATA AVAILAB. LE				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL <u>TECHNICAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE</u> <u>GENERAL SPECIFICATION - ADDINOL NMMA TCW3 01 LTR PACKING LOCALLY AVBLE</u>	
87	DPK109314	MAGNAFLUX (A DIVISION OF ITW LTD) WCP-2	6850TY671534 1 / WCP-2 WHITE CONTRAST PAINT		5 / EACH/NUMBER	NO DATA AVAILAB. LE				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - A. WCP-2 IS A BRIGHT WHITE OPAQUE NDT CONTRAST PAINT. IT PROVIDES A HIGH CONTRAST BACKGROUND TO IMPROVE PROBABILITY OF DETECTION AND SENSIBILITY DURING INSPECTION. B. IT CAN BE USED AT A WIDE RANGE OF TEMPERATURE FROM 6°C TO 48°C. C. IT HAS THE ABILITY TO DRY EVENLY AND QUICKLY TO CREATE AN OPTIMAL SURFACE FOR FASTER INDICATION FORMATION D. IT IS A FAST-DRYING PAINT AEROSOL SPRAY WITHOUT FLAKING. E. IT IS IDEAL FOR FIELD TESTING, SPOT INSPECTIONS AND IN-SERVICES INSPECTIONS. F. IT CAN BE USED WITH ALL TYPES OF COLORED AND VISIBLE MAGNETIC PARTICLES. G. IT CAN BE USED WITH WET OR DRY METHOD MAGNETIC PARTICLES. H. IT HAS 360° AEROSOL SPRAYER, HIGH OPACITY, STRONG SURFACE</u> <u>GENERAL SPECIFICATION - A. WCP-2 IS A BRIGHT WHITE OPAQUE NDT CONTRAST PAINT. IT PROVIDES A HIGH CONTRAST BACKGROUND TO IMPROVE PROBABILITY OF DETECTION AND SENSIBILITY DURING</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INSPECTION. B. IT CAN BE USED AT A WIDE RANGE OF TEMPERATURE FROM 6°C TO 48°C. C. IT HAS THE ABILITY TO DRY EVENLY AND QUICKLY TO CREATE AN OPTIMAL SURFACE FOR FASTER INDICATION FORMATION D. IT IS A FAST- DRYING PAINT AEROSOL SPRAY WITHOUT FLAKING. E. IT IS IDEAL FOR FIELD TESTING, SPOT INSPECTIONS AND IN-SERVICES INSPECTIONS. F. IT CAN BE USED WITH ALL TYPES OF COLORED AND VISIBLE MAGNETIC PARTICLES. G. IT CAN BE USED WITH WET OR DRY METHOD MAGNETIC PARTICLES. H. IT HAS 360° AEROSOL SPRAYER, HIGH OPACITY, STRONG SURFACE	
88	DPK107811	NOSOL GBY2	9150123226527 / GREASE NOSOL GBY2		3 / KILOGRAMME	NO DATA AVAILABLE				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
89	DRG103745	SBA-145016380	4730ZO6573882 / WATER PUMP ASSY		3 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
90	DPC109133	KUA752/KUA759	8010785265948 / intergard 7500.aluminium		300 / LITER	INTERGARD7500 ALUMINIUM				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
91	DNM108754	0130-6297	2930795241434 / radiator		1 / EACH/NUMBER	c350 d5 (nta855g9)				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
92	DSB111004	AI-9 8C 7C 6C	603078528089 7 / FIBER OPTIC SPLICING MACHINE		1 / EACH/NUMBER	AI-9				QUOTATION	TECHNICAL SPECIFICATION - OEM: SOFTEL OPTIC CO. LTD ADDRESS: 708-709 HAIWEI BUILDING, NO.101 BINKANG ROAD, BINJIANG DISTRICT, HANGZHOU, ZHEJIANG CHINA PH# +86-13588723749 EMAIL: INFO@SOFTEL-OPTIC.COM GENERAL SPECIFICATION - OEM: SOFTEL OPTIC CO. LTD ADDRESS: 708-709 HAIWEI BUILDING, NO.101 BINKANG ROAD, BINJIANG DISTRICT, HANGZHOU, ZHEJIANG CHINA PH# +86-13588723749 EMAIL: INFO@SOFTEL-OPTIC.COM	
93	DSB107200	LW-7235596-VTX /L23350-80CA	531014209559 6 / WASHER KEY/RONDELL E FREIN PLA 8 Z3CN18-10		30 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - PRESSURE TESTING / PHYSICALLY CHECK GENERAL SPECIFICATION - PRESSURE TESTING / PHYSICALLY CHECK	
94	DNM109143	JL269	668570523837 9 / PORTABLE GAS DETECTOR		1 / EACH/NUMBER	JL269				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
95	DPC107570	ASTM D1193	681000356493 6 / Distilled-deionized water		30 / LITER	N/A				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A	
96	DSB97879	049-21-006	830514333588 5 / TISSU ENDUIT PVC NON FEU BROWN CIGP/MEE&G		115 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Rexene brown commonly used for seat covers. PVC coated fabric. Waterproof upper layer. No specific packing required, Rolls of Rexene can be packed in wooden box to	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			S/244 DT16. 4.08								avoid damaged while handling <u>GENERAL SPECIFICATION</u> - Rexene brown commonly used for seat covers. PVC coated fabric. Waterproof upper layer. No specific packing required, Rolls of Rexene can be packed in wooden box to avoid damaged while handling	
97	DSA101765		5340TY6720913 / CURTAIN RAILING		70 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum <u>GENERAL SPECIFICATION</u> - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum	
98	DSA99336	LOCAL Q1-52-10X100	5310745240197 / RACCORD DROIT (GREASING NUT UNION)		100 / EACH/NUMBER	N/A					<u>TECHNICAL SPECIFICATION</u> - MARINE STANDARD ALUMINUM BRONZE SET: 03 X PIECES FERRULE LENGTH: 10MM NUT LENGTH: 16MM (14X1.5) PRESSURE: 200 BAR <u>GENERAL SPECIFICATION</u> - MARINE STANDARD ALUMINUM BRONZE SET: 03 X PIECES FERRULE LENGTH: 10MM NUT LENGTH: 16MM (14X1.5) PRESSURE: 200 BAR	
99	DPC107719	JOTAPRIME510 ALU. RED	8010785338806 / JOTAPRIME510 ALU. RED		300 / EACH/NUMBER	N/A				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - JOTUN PAINT FOR SHIPSIDE ALUMINIUM RED 100DFT <u>GENERAL SPECIFICATION</u> - JOTUN PAINT FOR SHIPSIDE ALUMINIUM RED 100DFT	
100	DSB110479	ORB-BTPG/0-10/V1/F334	6685545327041 / Pressure Gauge (0-10 Bar)		3 / EACH/NUMBER	ORB-BTPG/0-10/V1/F334					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
101	DPC107705	A020EEV2	8010705332825 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		455 / LITER	HIGHLY PERFUMED				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH	<u>TECHNICAL SPECIFICATION</u> - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										QUOTATION	NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation. <u>GENERAL SPECIFICATION -</u> PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.	
102	DPK107812	PYRATX EP2	915014578493 3 / FIRE PROOF GREASE / GREASE, HEAT DISSIPATION COMPOUND		2 / KILOGRAMME	EP2				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
103	DRG106	BTT3-303	5845ZO655049		10 /	NO DATA					<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	206	000-376	4 / POWERBAND DUAL		EACH/NUMBER	AVAILABLE					SAMPLE ATTACHED <u>GENERAL SPECIFICATION</u> - SAMPLE ATTACHED	
104	DRG110802	315/70 R 15 TL (300 R 15)	261012400272 4 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		2 / EACH/NUMBER	CONTINENTAL					<u>TECHNICAL SPECIFICATION</u> - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR <u>GENERAL SPECIFICATION</u> - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
105	DRG110743	315/70 R 15 TL (300 R 15)	261012400272 4 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		2 / EACH/NUMBER	CONTINENTAL					<u>TECHNICAL SPECIFICATION</u> - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR <u>GENERAL SPECIFICATION</u> - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
106	DNM109280	290-1935	294001624389 9 / FILTER ELEMENT AS-AIR (PRIMARY)		12 / EACH/NUMBER	cat c18				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
107	DSA107781	536-415-17DET6	598570523329 8 / SANDOW		10 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - Reference physical properties of Al. Alloy AA6061 Property Unit VALUE 1. Density Kg/m ³ 2700 2. Elastic Modulus (TENSION/COMPRESSION) GPA 68.9 3. Coefficient of Linear Thermal EXPANSION (A)(20°C to 100°C) PPM/°C 23.6 4. Thermal Conductivity (at 20°C) W/mK 167 5. Specific Heat J/g°C 0.896 <u>CHEMICAL COMPOSITION</u> (AL. ALLOY AA6061) element (% by weight) 1. copper (cu) 0.15-0.4 2. magnesium (mg) 0.8-1.2 3. silicon (si) 0.4-0.8 4. iron (fe) 0.7 (max) 5. manganese (mn) 0.15 (MAX) 6. zinc (zn) 0.25 (MAX) 7. titanium (ti) 0.15 (MAX) 8. chromium (cr) 0.04-0.35 9. other each 0.05 (MAX) 10. other total 0.15 (MAX) 11.mg si ratio 1.6-1.8 12-aluminium (al) balance <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<u>SPECIFICATION</u> - Reference physical properties of Al. Alloy AA6061 Property Unit VALUE 1. Density Kg/m³ 2700 2. Elastic Modulus (TENSION/COMPRESSION) GPA 68.9 3. Coefficient of Linear Thermal EXPANSION (A)(20°C to 100°C) PPM/°C 23.6 4. Thermal Conductivity (at 20°C) W/mK 167 5. Specific Heat J/g°C 0.896 CHEMICAL COMPOSITION (AL. ALLOY AA6061) element (% by weight) 1. copper (cu) 0.15-0.4 2. magnesium (mg) 0.8-1.2 3. silicon (si) 0.4-0.8 4. iron (fe) 0.7 (max) 5. manganese (mn) 0.15 (MAX) 6. zinc (zn) 0.25 (MAX) 7. titanium (ti) 0.15 (MAX) 8. chromium (cr) 0.04-0.35 9. other each 0.05 (MAX) 10. other total 0.15 (MAX) 11.mg si ratio 1.6-1.8 12- aluminium (al) balance	
108	DNH110 676	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		<u>TECHNICAL SPECIFICATION</u> - white colour only NASGAS WATER DISPENSER <u>GENERAL SPECIFICATION</u> - white colour only NASGAS WATER DISPENSER	
109	DNM110 525	FS100/L FS 100	294073521568 7 / FILTER 1 MICRON	MEDICAL OXYGEN GENERATOR O-500 ECO	1 / EACH/NUMBER	LF S 100	2011118	OXYMATE A/S, FASANVEJ 18-20, DK-3200, HELSINGE DENMARK. TEL: +45 48797811 FAX: +45 48797813 E MAIL: service@oxymat.dk www.oxymat.dt	OXYMAT A/S	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - 1. FILTER 1 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE. <u>GENERAL SPECIFICATION</u> - 1. FILTER 1 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE.	
110	DPK1110 75	1N70015/ NUTO H 32	915079510274 3 / OIL NUTO H 32 Elevators skirt shift (MOBIL NUTO tm H 32) 20	HOVERCRAFT GRIFFON HOVERCRAFT LTD,UK	125 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			liter Drum)							QUOTATION		
111	DNQ110748	NO DATA AVAILABLE	0461500000280 / SAFETY GOGGLES WITH SUN GLASSES		23 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - MAKE/ BRAND/ EQUIVALENT:</u> CHINA Color: Black Lenses Material: Polycarbonate Frame Material: PVC/PC Scratch Resistance: Yes Fog Resistant: Yes Weight: 40-50 gm (approx) Built in side shields to provide An ever greater level of impact protection. Petersafe/any well reputed firm having import/export license. <u>GENERAL SPECIFICATION - MAKE/ BRAND/ EQUIVALENT:</u> CHINA Color: Black Lenses Material: Polycarbonate Frame Material: PVC/PC Scratch Resistance: Yes Fog Resistant: Yes Weight: 40-50 gm (approx) Built in side shields to provide An ever greater level of impact protection. Petersafe/any well reputed firm having import/export license.	
112	DNM110217	F48E-P/DEU48/BMCU-48	4130715089740 / CONDENSING UNIT CRUISAIR TYPE SELF A/C UNIT 4TON	MAIN A/C CRISAIR USA TYP.F48E-P.	1 / EACH/NUMBER	BMCU-48				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
113	DNH111022	EAC-70/WP-1302/ECM 6500	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	30 / EACH/NUMBER	EAC-70/WP-1302/ECM 6500				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE</u> <u>GENERAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE</u>	
114	DNH110699	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/	SELF	1 / EACH/NUMBER	GREE/RE L, MITSUBUSHI/ DAKEN/ GENERA					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY			L, GENERAL, LG,						
115	DNH110 605	NO DATA AVAILABE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1/ EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
116	DNH110 604	FVQN125/ GF-48TF/R125 FUYI	4130735133058 / AIR CONDITIONER 4 tons 48000 btu	AIR CONDITIONING SYSTEM	1/ EACH/NUMBER	FVQN125 /GF-48TF		JP	DAIKIN INDUSTRIES (THAILAND) LTD 700/11 BANGKONG INDUSTRIAL ESTATE BANGNA-TRAD RD KM57. TAMBOL KLONGTAMRU AMPHUR MUNAG CHONBURI 20000 THAILAND TEL038 213 032 FAX NO: 038 213 047	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - SPECIFICATION:CAPACITY 48000 BTU GAS & LIQUID CONNECTION 3/4" & 3/8" AND DRAIN LINE 3/4" ELECTRICAL POWER SUPPLY 380VOLT 50HZ 3N~PHASE RUNNING CURRENT 7.1A MAX CURRENT RUNNING 8.3A DESIGNED PRESS (HI/LO) 2.9/1.3 MPA POWER CONSUMPTION (COOLIN)4150W (HEATING) W MAX POWER CONP 4800W REFEG R22/2.8KG GENERAL SPECIFICATION - SPECIFICATION: CAPACITY 48000 BTU GAS & LIQUID CONNECTION 3/4" & 3/8" AND DRAIN LINE 3/4" ELECTRICAL POWER SUPPLY 380VOLT 50HZ 3N~PHASE RUNNING CURRENT 7.1A MAX CURRENT RUNNING 8.3 A DESIGNED PRESS (HI/LO) 2.9/1.3 MPA POWER CONSUMPTION (COOLIN)4150W (HEATING) W MAX POWER CONP 4800W REFEG R22/2.8KG	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
117	DNH110 664	FX100/LF X 100	294073521568 8 / FILTER 0.01 MICRON	MEDICAL OXYGEN GENERATOR	1 / EACH/NUMBER	LF X 100	2011118	OXYMATE A/S, FASANVEJ 18-20, DK-3200, HELSINGE DENMARK. TEL: +45 48797811 FAX: +45 48797813 E MAIL: service@oxymat.dk www.oxymat.dt	OXYMAT A/S		TECHNICAL SPECIFICATION - 1. FILTER 0.01 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE. GENERAL SPECIFICATION - 1. FILTER 0.01 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE.	
118	DNH110 528	FX100/LF X 100	294073521568 8 / FILTER 0.01 MICRON	MEDICAL OXYGEN GENERATOR	1 / EACH/NUMBER	LF X 100	2011118	OXYMATE A/S, FASANVEJ 18-20, DK-3200, HELSINGE DENMARK. TEL: +45 48797811 FAX: +45 48797813 E MAIL: service@oxymat.dk www.oxymat.dt	OXYMAT A/S		TECHNICAL SPECIFICATION - 1. FILTER 0.01 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE. GENERAL SPECIFICATION - 1. FILTER 0.01 MICRON FITTED AFTER DRYER AS A PRE FILTER. 2. FRIULAIR FILTER FS100 IS ALSO SAME AND ACCEPTABLE.	
119	DNM107-177	PW1700X / BXPW1700E	494073513792 2 / HIGH PRESSURE WATER JET WASHING MACHINE	JET WASHING	1 / EACH/NUMBER	NO DATA AVAILABLE		TY	BLACK AND DECKER		TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
120	DPC111 102	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	160 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
121	DPC106 960	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	249.7 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		EYWELL R-410A								D WITH QUOTATION	DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
122	DPC109 373	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
123	DPC110 036	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
124	DPC110 112	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
125	DPC107674	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		<u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA <u>GENERAL SPECIFICATION - AHRI</u> STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
126	DPC110844	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA <u>GENERAL SPECIFICATION - AHRI</u> STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
127	DPC108792	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019</u> Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA <u>GENERAL SPECIFICATION - AHRI</u> STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
128	DNM110 866	CH10930	291079516020 5 / PRIMARY FUEL FILTER	DIESEL GENERATOR	6 / EACH/N UMBER	2806- E14TAG3	TGDF203 8U14293T	PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 1 5NA ENGLAND	PERKINS ENGINE COMPAN Y LTD	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 1 5NA ENGLAND GENERAL SPECIFICATION - PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 1 5NA ENGLAND	
129	DNH110 865		168071520694 6 / AIR CONDITIONER (FLOOR STANDING) 2 TONS	UPGRADING OF MARITIME SAFETY INFORMATION MANAGMENT	1 / EACH/N UMBER	GF-24TF	AE0091M 0100MAG 961772	M/S Skill Orbit using ESIR GIS software orig USA	M/S Skill Orbit using ESIR GIS software orig USA	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix. GENERAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix.	
130	DNH110 867		168071520694 6 / AIR CONDITIONER (FLOOR STANDING) 2 TONS	UPGRADING OF MARITIME SAFETY INFORMATION MANAGMENT	2 / EACH/N UMBER	GF-24TF	AE0091M 0100MAG 961772	M/S Skill Orbit using ESIR GIS software orig USA	M/S Skill Orbit using ESIR GIS software orig USA	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix. GENERAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix.	
131	DNM110 213	3970911	668501530122 0 / TRANSMITTE R, TEMPERATUR E /SENSOR WATER	MARINE ENGINE CUMMINS(UT BOAT)	4 / EACH/N UMBER	QSB5.9- 225BHP		23, BRENTFORD ROAD, KINGSHEATH, BIRMINGHAM B14 4DQ, ENGLAND	M/S MECHANI CAL & ELECTRI CAL (UK) LTD	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
132	DNH110 803	NIL, LOCAL	732070516360 7 / ELECTRIC ROTI PLANT 1000 CHAPATI /HRS	ROTI PLANT	1 / EACH/N UMBER	Automatic Electric Roti Plant		M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN GUJRANWALA.	M/S SHARIF ENGINEE RING WORKS BAZAR KHARAD AN	TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									GUJRAN			
133	DPC111 244	-	0474500001889 / CLEANING POWDER, 1 CWT.DRUM (BR 320 D CLASS GROUP 0474 PG 2	BR320D REVISED 1965 CLASS GROUP 0474 PG2	1649 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - a. Type Cleaning Powder b. Age Group Any Age c. Brand Cesco Solutions d. Item weight 5 pounds or dependent upon market availability e. Packing material Woven Bag carton <u>GENERAL SPECIFICATION</u> - a. Type Cleaning Powder b. Age Group Any Age c. Brand Cesco Solutions d. Item weight 5 pounds or dependent upon market availability e. Packing material Woven Bag carton	
134	DPC111 263	S NO 120 SIMILAR	0442504420063 / PAINT WEATHER WORK(DARK GREY) (NSSD/C01/0442/GEN/173DT 060393)	WEATHER WORK	48 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
135	DPC111 272		0442504420064 / PAINT WEATHER WORK (LIGHT GREY)NHQ LTR NS/G/1303/C DT 270199	WEATHER WORK	40 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
136	DPC111 243		0442504420069 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		20 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
137	DPC110 037	NO DATA AVAILABLE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		300 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Di Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO.	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL SPECIFICATION - 1.</u> CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Dioxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
138	DNQ110752	0472-5580	047259425974 7 / LIFE JACKET GENERAL SERVICE ORALLY INFLATED WITH LAMP WITH SERVICE MANUAL		34 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - 1.</u> FACE SHIELD/HOOD IS ADDED MATERIAL/COMPONENTS:\ a. RUBBRISED FABRIC b. LIFTING BECKET c. ORAL INFLATION VALVE d. STORAGE POUCH e. WAIST BELT f. METAL COMPONENTS (BUCKLESS & BUTTONS) g. RETRO-REFLECTIVE COVER h. WHISTLE j. FACE SHIELD k. SEA WATER OPERATED BATTERY l. REFLECTIVE PANELS SPECIFICATIONS: ITEM TO BE PROVIDED AS PER PN SPEC NO. 11-008/06 ISSUE 03 OF 22 FEB 07 (PY ENCLOSED) RUBBER LIFEJACKET MUST BE WELL PACKED & PRES <u>GENERAL SPECIFICATION - 1.</u> FACE SHIELD/HOOD IS ADDED MATERIAL/COMPONENTS:\ a. RUBBRISED FABRIC b. LIFTING BECKET c. ORAL INFLATION VALVE d. STORAGE POUCH e. WAIST BELT f. METAL COMPONENTS (BUCKLESS & BUTTONS) g. RETRO-REFLECTIVE COVER h. WHISTLE j. FACE SHIELD k. SEA WATER OPERATED BATTERY l. REFLECTIVE PANELS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATIONS: ITEM TO BE PROVIDED AS PER PN SPEC NO. 11-008/06 ISSUE 03 OF 22 FEB 07. (PY ENCLOSED) RUBBER LIFEJACKET MUST BE WELL PACKED & PRES	
139	DNM110665	NR-20550/96	2920725089587 / FOG GENERATOR TF-35 FOR CONTROL OF MOSQUITOES	FOR GENERATOR TF35FOR CONTROL (GERMANY)	1 / EACH/NUMBER	TF-35				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - IGEBA GENERAL SPECIFICATION - IGEBA	
140	DNQ110698	LOCAL	4210705007917 / NOZZLE FOR HOSE CANVAS		12 / EACH/NUMBER	SL-13BP SHILA FIRE				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Series: W2500 Model: Pwr 1 & 1p OEM/Brand: pwr control: manual output: 130-23- liter per minute at 6 bar pressure material: polyamide & light aluminium alloy GENERAL SPECIFICATION - Series: W2500 Model: Pwr 1 & 1p OEM/Brand: pwr control: manual output: 130-23- liter per minute at 6 bar pressure material: polyamide & light aluminium alloy	
141	DNH110668		4120705051919 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	1 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
142	DPC111184	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		700 / LITER	PINAX-A				TDS/BROUCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans & Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing Room, House,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Hospitals and All Types of Commercial and Noncommercial Area. <u>GENERAL SPECIFICATION</u> - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
143	DNH88873	NIL, LOCAL	7320705163607 / ELECTRIC ROTI PLANT 1000 CHAPATI /HRS	ROTI PLANT	1 / EACH/NUMBER	Automatic Electric Roti Plant		M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN GUJRANWALA.	M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN GUJRAN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
144	DPC107087		0442504420064 / PAINT WEATHER WORK (LIGHT GREY)NHQ LTR NS/G/1303/C DT 270199	WEATHER WORK	841 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
145	DPC111169	0474-7041	0474502242642 / CEMENT PORTLAND (50 KG BAG)		9160 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
146	DNQ111129	BS EN-3	0243502431051 / FIRE EXTINGUISHER	FIRE FIGHTING EQUIPMENT	120 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - UL/FM, BSI/KITE MARK LPCB APPROVED SHOULD COMPLY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			R CO2, CAPACITY 05 KGS, RED								WITH PROVISIONS OF EN-3-7, 3-9 & 3-10 BS 5045-7:2000 PRODUCT NAME : CO2 EXTINGUISHER 5KG OUT DIAMETER (mm) 150~160mm CYLINDER HIGH (mm): 800~840mm CYLINDER WEIGHT (Kg) 6~8KG EXTINGUISHER WEIGHT(kg) 11~13kg <u>GENERAL SPECIFICATION</u> - UL/FM, BSI/KITE MARK LPCB APPROVED SHOULD COMPLY WITH PROVISIONS OF EN-3-7, 3-9 & 3-10 BS 5045-7:2000 PRODUCT NAME : CO2 EXTINGUISHER 5KG OUT DIAMETER (mm) 150~160mm CYLINDER HIGH (mm): 800~840mm CYLINDER WEIGHT (Kg) 6~8KG EXTINGUISHER WEIGHT(kg) 11~13kg	
147	DPC111196	ZEEPER114	8010705332849 / ZEEPER 114 CLEANER		700 / KILOGRAMME	ZEEPER. 114				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years <u>GENERAL SPECIFICATION</u> - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
148	DSB87729	TAG-700 AIR ANGLE GRINDER/ NKS – NK2261G1	0099086072967 / PNEUMATIC ANGLE GRINDER KL/12 OR 700NA		5 / EACH/NUMBER	tag-700 qjl/NK2261G1					<u>TECHNICAL SPECIFICATION</u> - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2" <u>GENERAL SPECIFICATION</u> - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2"	