

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 27-10-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DRG88762	SINIG	2925ZO523848 8 / SINGLE IGNITION		4 / EACH/NUMBER	GREAT POWER					<u>TECHNICAL SPECIFICATION - SINGLE IGNITION</u> <u>GENERAL SPECIFICATION - SINGLE IGNITION</u>	
2	DPK107874	CORENA S2 P150	915070519669 9 / SHELL CORENA S2 P150 (PACKING = 20 LITERS)	HPAC PNFT	60 / LITER	NA	NA	M/S SHELL	M/S SHELL	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - SHELL CORENA S2 P150</u> <u>GENERAL SPECIFICATION - SHELL CORENA S2 P150</u>	
3	DNH111148	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	50 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT	TDS/BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER</u> <u>GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER</u>	
4	DNM111061	4893693/5473331	312001502826 4 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER		22066008	CUMMINS MER CRUISER DIESEL WEBSITE (WWW.CMDMARINE.COM)	CUMMINS	TDS/BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7</u> <u>GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MODEL: QSB6.7	
5	DNM111066	5268423/5268424	2835715193140 / KIT RAW WATER PUMP-INTE	DIESEL ENGINE CUMMINS MODEL QSB6.7?305MD@2600RPM	2 / EACH/NUMBER	QSB6.7-305MD		M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565 USA CAGE 65KD2 USA	M/s IMPEX NINE INC	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565 USA CAGE 65KD2 USA GENERAL SPECIFICATION - OEM: M/s IMPEX NINE INC 412, DU PAHZE ST NAPERVILLE, IL 60565 USA CAGE 65KD2 USA	
6	DNM109376	PW1700X / BXPW1700E	4940735137922 / HIGH PRESSURE WATER JET WASHING MACHINE	JET WASHING	1 / EACH/NUMBER	NO DATA AVAILABLE		TY	BLACK AND DECKER	TDS/BROUCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
7	DPC108611	ZIIE-15	6850705199638 / PROTECTIVE COATING ELECTRIC , OEM NANO PROTECH, Packing = 150 ML bottle	PCB PROTECTOR SPRAY ESTONIA	15 / BOTTLE	150 ML	NA	NANO PROTECH OU, Uus Sadama 21, Tallinn 10120, Estonia Phone +3726683242	NANO PROTECH	TDS/BROUCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Form: Liquid Colour: Green Ignition Point: 250 Degree C. GENERAL SPECIFICATION - Form: Liquid Colour: Green Ignition Point: 250 Degree C	
8	DPK111783	7101001002	9150735232473 / REFRIGERATION LUB OIL DHB-002 (19 Liters Packing)	HARD FORD AC COMPRESSOR	91 / LITER	DHB-002	17FA000G5737A	DUNHAM-BUSH INDUSTRIES SMD.BHD. LOT 5755-6,KIDMAL INDUSTRIAL PARK,BUKIT ANGKAT,43000 KAJANG. SELANGOR PH:+603-89249000 FAX:+603-89395020	DUNHAM-BUSH INDUSTRIES	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - FLASH POINT (ASTM D-92,COC) 190C,MELTING POINT :(ASTM D-92,COC)-30 C GENERAL SPECIFICATION - FLASH POINT (ASTM D-92,COC)190C,MELTING POINT :(ASTM D-92,COC)-30 C	
9	DNM107987	1945390	5330014715740 / GASKET-MANIFOLD	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT	TDS/BROUCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
10	DNM107990	353-3477	533001642446 6 / GASKET-TURBOCHARGER	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
11	DNM107994	353-3478	533001642603 2 / GASKET-TURBOCHARGER	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
12	DNM107983	6I-0645	530671522839 0 / BOLT (M8X1.25X25-MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	4 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
13	DPK107914	GL-95/GADUS S2 OG 40	915073518295 0 / GREASE SHELL GADUS S2 OG 40/TUFGEAR UNIVERSAL Rocol (Packing 18kg)	MAIN SHAFT	4 / KILOGRAMME	GL-95		MJP MARINE JET POWER AB S-748 01 OSTERBYBRUK SWEDEN TEL +46 295 244 250 FAX +46 295 244 250	SHELL MALLEUS SWEDEN	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - MJP</u> MARINE JET POWER AB S-748 01 OSTERBYBRUK SWEDEN TEL +46 295 244 250 FAX +46 295 244 250 <u>GENERAL SPECIFICATION -</u> MJP MARINE JET POWER AB S-748 01 OSTERBYBRUK SWEDEN TEL +46 295 244 250 FAX +46 295 244 250	
14	DPK109302	828250	915073517562 4 / GREASE	IPS 500	4 / EACH/NUMBER	IPS 500	IPS-F3940012979	VOLVO PENTA	VPL SWEDEN VOLVO PENTA	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> VOLVO PENTAGENERAL <u>SPECIFICATION - VOLVO PENTA</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
15	DNM110537	CWAHU-224-18	6110705216699 / CONTACTOR FOR COMPRESSOR	HVAC CWCU-230 AHU-1	3 / EACH/NUMBER	HDC6-32	NIL	HIMEL ELECTRIC CO LTD www.himel-electric.com COOL POINT PAKISTAN LAHORE	HIMEL ELECTRIC CO LTD www.himel-electric.com	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NORMAL CURRENT 9 TO 630 A, RELATED POWER 4 KW TO 35 KW 24 VTO 440 VOLT AUXILIARY CONTACT 9-95 A THERMAL OVER LOAD HDC6 STANDRED IEC/EN 60947-4-1 GENERAL SPECIFICATION - NORMAL CURRENT 9 TO 630 A, RELATED POWER 4 KW TO 35 KW 24 VTO 440 VOLT AUXILIARY CONTACT 9- 95 A THERMAL OVER LOAD HDC6 STANDRED IEC/EN 60947-4-1	
16	DPC108705	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
17	DPC108186	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
18	DPC111050	SUVA 410a /HFC-410a/R-	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		410a//HONEYWELL R-410A								ENCLOSED WITH QUOTATION	purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
19	DPC111 382	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
20	DPC106 780	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	56.75 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
21	DPC111 423	SUVA 410a /HFC-410a/R-410a//HONEYWELL R-410A	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	136 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE	TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USAGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										ON	SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) OEM: DUPONT USA HONEYWELL USA ARKEMA FORAN USA	
22	DNM107986	0676135 / 067-6135	5315016503302 / KEY-WOODRUFF	DG CAT 7.1 USA	1 / EACH/NUMBER	CAT 7.1	NIL	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPILLAR USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs	
23	DNH111142	HPU-48CH03	4130785157034 / A/C 4 TON FLOOR STANDING	4 TON A/C HPU-48CH03	1 / EACH/NUMBER	GF-48TF		HAIER CHINA LOCAL MARKET (TUBA INTER FIRM)	HAIER CHINA	TDS/BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BRABDI GREE SOURCE OF AVAILABILITY:LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HRS SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM (OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, lg, mitsubishi, daikin, gree, package: GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH COPELAND, CARRIER, OR DAIKIN COMPRESSOR), LG, GREE GENERAL SPECIFICATION - BRABDI GREE SOURCE OF AVAILABILITY:LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HRS SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM (OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, lg, mitsubishi, daikin, gree, package:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH COPELAND, CARRIER, OR DAIKIN COMPRESSOR), LG, GREE	
24	DNM105986	247-1380/551-6183	294071520763 1 / FILTER ELEMENT AIR	DG CATERPILLER C2-2 DE18E3/DE22E2 USA	16 / EACH/NUMBER	C2-2 DE18E3/DE22E2	NIL	CATERPILLAR USA CO 701 WATERFOLD WAY SIUT 200 MIAMI USA CONTACT NO 305-476-6800 FAX NO 305-476-6801	CATERPILLAR USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - AIR FILTER USE FOR PROVISION OF CLEAN COMBUSTION AIR TO DG FOR SMOOTH RUNNING OF ENGINE GENERAL SPECIFICATION - AIR FILTER USE FOR PROVISION OF CLEAN COMBUSTION AIR TO DG FOR SMOOTH RUNNING OF ENGINE	
25	DPK108335	99000-22B55	915076522310 6 / ECSTAR OUT BOARD MOTOR GEAR OIL SUZUKI SAE-90 GL-5	SUZUKI OBM ENGINE	165 / MILLILITER	NIL		SHOWA SHELL SEKIYU K K. 3-2 DAIBA-2-CHOME, MINATO-KU, TOKYO, 135- 8074, JAPAN	OBM SUZUKI	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE AUTOMOTIVE GEAR OIL GENERAL SPECIFICATION - ECSATR OBM GEAR OIL DATA SHEET PHYSICAL AND CHEMICAL PROPERTIES MATERIAL NAME ECSTAR OBM GEAR OIL SAE-90 GL-5 RECOMMENDED USE AUTOMOTIVE GEAR OIL	
26	DNM107986	0676135 / 067-6135	531501650330 2 / KEY- WOODRUFF	DG CAT 7.1 USA	1 / EACH/NUMBER	CAT 7.1	ZRE01323	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-349-8400	CATERPILLAR USA	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs	
27	DNQ102508	SEFSTAN 84-2	844099978449 6 / STOCKING WOOL WHITE FOOT SIZE 27CM	STOCKING SHIPS (FF)	6 / PAIR	NO DATA AVAILABLE		UK	UK ENGLAND	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATIO N		
28	SPK92196	ARCTIC 32/146264	9150795170256 / MOBIL EAL ARCTIC 32 (1 LITRE PACKING)	COMPRESSOR	20 / LITER		65703502	Mobil Oil Company Limited Acting as Agent for Mobil Lubricants UK Limited ExxonMobil House, Ermyn Way Leatherhead, Surrey, KT22 8UX Telephone: 01372 22 2000	Mobil Oil Company Limited	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - MOBIL EAL ARCTIC 32 GENERAL SPECIFICATION - MOBIL EAL ARCTIC 32	
29	DNM105845	U5MK0669 PPL039632	6110795214545 / CONTROL KIT	100 KVA DG	1 / EACH/NUMBER	1104C-44TAG2	RJ51155	PILKINGTON PERKIN-ELMER LTD FOREST ROAD HAINAULT, ESSEX UK	PERKINS ENGINE	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A	
30	DNM111061	4893693/5473331	3120015028264 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA	CUMMINS	TDS/BROCHER OR PIC MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS. MODEL: QSB6.7 GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
31	DPC107540	LIQUID BE 380 & POWDER CS 381	5610705197496 / FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS381 (Packing = Kit) (Color = Light Grey)	CHEMICAL	29 / KIT			LABCO FINE CHEMICAL karachi PHONE 021-32562622 labcod2002yahoo.com	M/S LABCO FINE CHEMICAL	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS 381 GENERAL SPECIFICATION - FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS 381	
32	DPC108487	LIQUID BE 380 &	561070519749	CHEMICAL	6 / KIT			LABCO FINE CHEMICAL karachi	M/S LABCO	TDS\BROCHER OR	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6 / FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS381 (Packing = Kit) (Color = Light Grey)					PHONE 021-32562622 labcod2002yahoo.com	FINE CHEMICAL	PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS 381 <u>GENERAL SPECIFICATION - FLOORWELL DECK UNDERLAY LIQUID BE 380 POWDER CS 381</u>	
33	DPC108 518	COSMADEC-10 EPOXY PRIMER	561070519749 7 / COSMADEC-10 EPOXY PRIMER (COMP A + COMP B) (Packing = KIT) (Color = Clear Transparent)	CHEMICAL	32 / KIT	-	-	M/S LABCO FINE CHEMICALS KARACHI TEL: 021-32562622 EMAIL: labcod200@yahoo.com	M/S LABCO FINE CHEMICALS	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - COSMADEC-10 EPOXY PRIMER COMPONENT A: BASE COMPONENT COMPONENT B: CURING AGENT</u> <u>GENERAL SPECIFICATION - COSMADEC-10 EPOXY PRIMER COMPONENT A: BASE COMPONENT COMPONENT B: CURING AGENT</u>	
34	DPC108 540	COSMADEC-13 EPOXY COMPOUND	561070519749 8 / COSMADEC-13 EPOXY COMPOUND (COMP A+ COMP B) (Packing = KIT) (Color = Grey)	CHEMICAL	47 / KIT	-	-	M/S LABCO FINE CHEMICALS PH # 021-32562622 EMAIL: labcod200@yahoo.com	M/S LABCO FINE CHEMICALS	TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - COSMADEC-13 EPOXY COMPOUND COMP A: Blend of epoxy polymer, fillers and pigments COMP B: Curing agent</u> <u>GENERAL SPECIFICATION - COSMADEC-13 EPOXY COMPOUND COMP A: Blend of epoxy polymer, fillers and pigments COMP B: Curing agent</u>	
35	DNH111 153	NIL	412073513911 7 / AIR CONDITIONER SPLIT 1.5 TONS	AIR CONDITIONING	1 / EACH/NUMBER	NO DATA AVAILABLE		OC	THAILAND	TDS/BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
36	SPC1094 63	NO DATA AVAILABLE	047450000702 8 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		300 / BAG					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SiO: MORE THEN 93-96 Fe2O3: LESS THEN 1.5 AL2O3: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N	SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0	
37	DPK111600	0474-7021 (0475-99-224-2137)	047450224213 7 / TALLOW WHITE (GREASE) (200 KG DRUM)		200 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DPC110486		047350224762 4 / LIQUID AMMONIA (33% AMMONIA 67% WATER)		9 / BOTTLE					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
39	DPC111464	SAME AS S NO 9 EXECPT SHADE.	044250220163 7 / PAINT FINISHING (GREEN)	USES FOR STEEL ALUMINUM OR WOOD ON GLASS	74 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
40	DPC108410		044250943448 1 / PAINT ACID AND ALKALY RESISTANT A/R (BLACK) 05 LTR TIN Flash Point: 32 Degree.C (min) Packing: standard oem 04 ltr tin non corrosive gauge of tin 26 to 28 swg	FINISHING	48 / LITER					TDS/BROUCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED 3. DEFSTAN 80-72/3 OF 2006 GENERAL SPECIFICATION - 1. NS/P/010 OF 2013(REVISED) 2. STAGE INSPECTION PRESCRIBED 3. DEFSTAN 80-72/3 OF 2006	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
41	DPC110473	NO. NS/C01/GEN/566 DT 210902	0442509429120 / PAINT OIL FINISHING G. O.S.B. (GREEN)	FINISHING	513 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DPC109515	106 OF BS381-C OF 1996	0442504420061 / PAINT VEHICLE CELLULOSE (ROYAL NAVY BLUE)	VEHICLES, DECORATIVE FINISHING	40 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996. GENERAL SPECIFICATION - DEFSTAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.	
43	DPC107104		0442509421195 / PAINT PRIMING ZINC PHOSPHATE WHITE FIRE RETARDANT FLASH POINT 32 OC (MIN)	SHADE 355 STAGE INSPECTION PRESCRIBED	120 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. revised ns/p/009 of 2013 /SPECIFICATION NS/P/002 OF 2013 2. to be tested against defstan 80-77/2 of 1995 3. stage inspection prescribed 4. colour shade white 5. DEF1115A COLOUR TO BS 381-C 6 Flash Point: 32 °C (Min) 7. Packing: 20 Ltr Drum, Gauge of Tin 24 to 26 SWG GENERAL SPECIFICATION - 1. revised ns/p/009 of 2013 /SPECIFICATION NS/P/002 OF 2013 2. to be tested against defstan 80-77/2 of 1995 3. stage inspection prescribed 4. colour shade white 5. DEF1115A COLOUR TO BS 381-C 6 Flash Point: 32 °C (Min) 7. Packing: 20 Ltr Drum, Gauge of Tin 24 to 26 SWG	
44	DPC108284	NO DATA AVAILABLE	0442504420030 / DULAC HI-BUILD (Packing = 0.91 Liter)		48 / LITER	ICI				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - LACURE MAKE: ICI OEM GENERAL SPECIFICATION - LACURE MAKE: ICI OEM: ICI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
45	DPC109504	king MOSPEL	0442504420119 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		20 / BOTTLE					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL.n, n- diethyl-meta -toluamide (deet) <u>GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL.n, n- diethyl-meta -toluamide (deet)</u>	
46	DPC106612	NO DATA AVAILABLE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		45 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas</u>	
47	DPC106090	NO DATA AVAILABLE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		85 / KILOGRAMME					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
48	DPC106342	NO DATA AVAILABL E	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		150 / KILOGR AMME					TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
49	DPC106861	NO DATA AVAILABL E	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		100 / KILOGR AMME					TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Design Gas <u>GENERAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
50	DPC106450	NO DATA AVAILABL E	044350942222 6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		250 / KILOGR AMME					TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas <u>GENERAL SPECIFICATION</u> - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas	
51	DNQ109563	PN SPEC 11- 002 OF 2005	024359129584 2 / FIRE EXTINGUISHER, STORED PRESSURE TYPE WATER (09 LITRES) DEEP DRAWN STAINLESS STEEL BODY.	FIRE FIGHTING EQUIPMENT	12 / EACH/N UMBER					TDS\BROC HER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
52	DNQ102154	LOCALLY DEVELOPED	204099787817 2 / CLAMP DAMAGE REPAIR		16 / EACH/N UMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
53	DNQ110362	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/N UMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring durisng Damage Control,, General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
54	DNM109315		132579439003 3 / BIT TOOL STANDARD SIZE 5/8"X 8" (SQUARE) HSS		15 / EACH/N UMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DPC111306		136599745689 5 / LIQUID FOR FOGGING		2 / EACH/N UMBER					TDS\BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DPC110548		047450474001 2 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)		20 / EACH/N UMBER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
57	DPC110487	NO DATA AVAILABLE	0473504730033 / DISTILLED WATER (10 ltr packing)		50 / GALLON					QUOTATION TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DNQ110092	THE STANDARD ISO 11601	4210705036011 / EXTINGUISHER FIRE DCP 50KG TROLLY MOUNTED CO2 CARTRIDGE	FIRE FIGHTING EQUIPMENT	4 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - WITH 2 WHEEL TROLLY RUBBER GENERAL SPECIFICATION - WITH 2 WHEEL TROLLY RUBBER TYPE	
59	DNH111152		4120705051919 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	2 / EACH/NUMBER					TDS/BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE-ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
60	DNM111154	BMCU-60	4120PK5073944 / CONDENSING UNIT (05 TONS) 440V-3PH WITH ALL ACCESSORIES	A/C UNIT SPLIT TYPE	1 / EACH/NUMBER	BMCU-60				TDS/BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - ZR61KCE-TFD-522 Refrigerant R-22 Sea Water Cooled Condenser (Cu-Ni) (BT-60-CTT-20) Suction Accumulator Size 7/8" (Design Pressure 450PSIG) Liquid Receiver (Design Pressure 500PSIG) Solenoid Valve Size 3/8" Solenoid Coil 220V Dual Pressure Switch (Danfoss) KP-15 Low Pressure Switch (Danfoss) KP-01 Drier Shell Service Valve 3/4" Service Valve 3/8" Stainless Steel Drain Tray Complete Copper Piping Imported Foam Insulation GENERAL SPECIFICATION - ZR61KCE-TFD-522 Refrigerant R-22 Sea Water	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Cooled Condenser (Cu-Ni) (BT-60-CTT-20) Suction Accumulator Size 7/8" (Design Pressure 450PSIG) Liquid Receiver (Design Pressure 500PSIG) Solenoid Valve Size 3/8" Solenoid Coil 220V Dual Pressure Switch (Danfoss) KP-15 Low Pressure Switch (Danfoss) KP-01 Drier Shell Service Valve 3/4" Service Valve 3/8" Stainless Steel Drain Tray Complete Copper Piping Imported Foam Insulation	
61	DNH111151	9178 chrome	4110PK5067366 / REFRIGERATOR 14CUFT	REFRIGEERATOR 14CUFT (PAKISTAN)	2 / EACH/NUMBER	9178 CHROME				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
62	DNH111143	EAC-70/WP-1302/ECM 6500	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	2 / EACH/NUMBER	EAC-70/WP-1302/ECM 6500				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE GENERAL SPECIFICATION - 220/240V AC SINGLE PHASE FULL SIZE	
63	DNH111149	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		3 / EACH/NUMBER	WDF-318				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - CAPACITY: 18 CUBIC FEET ARE 509 LITERS DIMENSIONS : HEIGHT 168 CM X WIDTH 76 CM X DEPTH 81.6 CM. CURRENT: 1.3 TO 1.5 AMP.(SINGLE PHASE). COMPRESSOR: SIZE 1/4 RECIPROCATING 220 VOLTS. REFRIGERANT : R 134/R 600. DOOR : DOUBLE DOOR. GENERAL SPECIFICATION - CAPACITY: 18 CUBIC FEET ARE 509 LITERS DIMENSIONS : HEIGHT 168 CM X WIDTH 76 CM X DEPTH 81.6 CM. CURRENT: 1.3 TO 1.5 AMP. (SINGLE PHASE). COMPRESSOR: SIZE 1/4 RECIPROCATING 220 VOLTS. REFRIGERANT : R 134/R	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											600. DOOR : DOUBLE DOOR.	
64	DNH111060		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	2 / EACH/NUMBER	WA60000514				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W <u>GENERAL SPECIFICATION</u> - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W	
65	DNH111150		4110735060828 / REFRIGERATOR 18-CUFT DOUBLE DOOR PEL/DAWLANCE		2 / EACH/NUMBER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
66	DNM103691	N4067	4820725042380 / VALVE-INTAKE-24-R-STEEL-28X34MM	R C CHAMBER PNS IQBAL	2 / EACH/NUMBER					TDS/BROUCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - 24-R-STEEL-28X34MM <u>GENERAL SPECIFICATION</u> - 24-R-STEEL-28X34MM	
67	DNQ110534	1-3-150 DEVELOPED BY DTD	4730992542747 / CLAMP PIPE REPAIR-38-42MM LG 75MM	DAMAGE CONTROL & FIRE FIGHTING EQUIPMENT	5 / EACH/NUMBER					TDS/BROUCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
68	DNM104122	29M2-P1LX2/57009904	5330735096596 / O RING (29M2-P1LX2. ITEM:PF101)	PF 101,PRE-FILTER(PF101)	5 / EACH/NUMBER	29M2-P1LX2				TDS/BROUCHER OR PIC OF ITEM MUST BE ENCLOSED	<u>TECHNICAL SPECIFICATION</u> - 10 BAR/125C DIMENSIONS/SIZE: Dia 45.8 Inch <u>GENERAL SPECIFICATION</u> - 10 BAR/125C DIMENSIONS/SIZE: Dia 45.8 Inch	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION		
69	DNQ109470	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DNQ109623	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	DNQ110085	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	10 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
72	DNM108466	8C6099	594501287332 6 / SOLENIOD (SHUT OFF) 24VDC	SR4B, CONTROL SYSTEM, DIESEL GEN. C/PILLER	2 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DPC111448	BELZONA 9341	803070504091 6 / BELZONA RE-INFORCEMENT TAPE (BELZONA 9341) (Packing	FOR BRIDGING CRACKS & FOR BELZONA METALS	30 / ROLL					TDS/BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			10 Meters roll)							ON		
74	DPC108225	NO DATA AVAILABLE	6850785031104 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMENT FOR PNS NASR	5 / EACH/NUMBER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. <u>GENERAL SPECIFICATION -</u> MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
75	DPC106496		6830PK5071580 / GAS MIXTURE 80% ARGON AND 20% CO2		115.6 / CUBIC METER					TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> Packing Details: Cylinder PN/GM (HE SUR)/GENERAL/2569501 DT 20 JAN 2023 PACKING DETAILS - CYLINDER ORIGIN - LOCAL ACCEPTANCE CRITERIA - 80% ARGON & 20% CO2 (+ 2%) <u>GENERAL SPECIFICATION -</u> Packing Details: Cylinder PN/GM (HE SUR)/GENERAL/2569501 DT 20 JAN 2023 PACKING DETAILS - CYLINDER ORIGIN - LOCAL ACCEPTANCE CRITERIA - 80% ARGON & 20% CO2 (+ 2%)	
76	DPK111710	20W-50	9150PK5079480 / LUB OIL 20W50 PKG 4LTR (FOR PETROL VEHICLES)	PETROL VEHICLES	60 / LITER					TDS/BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
77	DPK111843	20W-50	9150PK5079480 / LUB OIL 20W50 PKG 4LTR (FOR PETROL VEHICLES)	PETROL VEHICLES	180 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
78	DPK111664	S-758/MIL-PRF-63460E/N YCOLUBE 127	9150010536688 / CLEANER, LUBRICANT AND PRESERVATIVE WEAPON OIL	USE FOR DIESEL ENGINE/12.7 MM GUN, MPAC,MRTPS	4 / GALLON					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DPK111782	90790-BS455	9150218770478 / OIL SAE 10W40 API SJ for YAMALUBE 4 STROKE MOTOR (01 Liter Packing)	RADAR-DA08	160 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g: 6.9 D4739,mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached GENERAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g:6.9 D4739, mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached	
80	DPK111759	90790-BS455	9150218770478 / OIL SAE 10W40 API SJ for YAMALUBE 4 STROKE MOTOR (01 Liter Packing)	RADAR-DA08	179 / LITER					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g: 6.9 D4739,mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached GENERAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g:6.9 D4739, mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached	
81	DPK111678	90790-BS455	9150218770478 / OIL SAE 10W40 API SJ	RADAR-DA08	160 / LITER					TDS/BROUCHER OR PIC MUST BE	TECHNICAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g: 6.9 D4739,mgKOH/g:6.0 part no	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			for YAMALUBE 4 STROKE MOTOR (01 Liter Packing)							ENCLOSE D WITH QUOATATI ON	90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached <u>GENERAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g:6.9 D4739, mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached</u>	
82	DPC111 347		681000281276 2 / METHYL ETHYL KETONE (Packing = 165 KG)		360 / KILOGR AMME					TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOATATI ON	<u>TECHNICAL SPECIFICATION -</u> Acetone preferably USA West Europe, japan suitable for cleaning polyester resin and conforming to Lloyds's rules or following specification: a. Grade Solvent 'A' b. Appearance Clear colorless and free from matter in suspension c. Specific Gravly at 25 "C - 0.786-0.788 - d. Distillation Range at 760mm Hg oC 55.5-56.5 - e. Residue on evaporation - 0.005% (Max) d. Miscibility with water Shall show no opalescence when mixed with distilled water e. Acidly - 0.002% (Max) f. Alkalinity Shall not show any alkalinity j. Permanganate test Shell not completely discharge permanent color with 120 minutes k. Moisture - 1.2% (Max) l. Acetone content - 98% (Min) OR Methyl ethyl Ketone (MEK) Preferably USA West Europe, Japan suitable for cleaning polyester resin and conforming to Lloyds's rules or following specification a. Specific gravity 25 "C - 0.801-0.803 - b. Color Clear and transparent c. Distillation range oC 78.5-81 - d. Non-volatile matter at 105OC Mg/100ml 5 (Max) e. Acidity - 0.005% (Max) f. ASTMD740-94 PART 29 OF 1997 <u>GENERAL SPECIFICATION -</u> Acetone preferably USA West Europe, japan suitable for cleaning polyester resin and conforming to	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Lloyds's rules or following specification: a. Grade Solvent 'A' b. Appearance Clear colorless and free from matter in suspension c. Specific Gravity at 25 °C - 0.786-0.788 - d. Distillation Range at 760mm Hg oC 55.5-56.5 - e. Residue on evaporation - 0.005% (Max) d. Miscibility with water Shall show no opalescence when mixed with distilled water e. Acidly - 0.002% (Max) f. Alkalinity Shall not show any alkalinity j. Permanganate test Shell not completely discharge permanent color with 120 minutes k. Moisture - 1.2% (Max) l. Acetone content - 98% (Min) OR Methyl ethyl Ketone (MEK) Preferably USA West Europe, Japan suitable for cleaning polyester resin and conforming to Lloyds's rules or following specification a. Specific gravity 25 °C - 0.801-0.803 - b. Color Clear and transparent c. Distillation range oC 78.5-81 - d. Non-volatile matter at 105OC Mg/100ml 5 (Max) e. Acidity - 0.005% (Max) f. ASTMD740-94 PART 29 OF 1997	
83	DPC111363	B71003, B71046 OR ACCELRA TOR G (POLYACC P-A)	6810731001000 / COBALT BASED ACCELERATO R/ CRYSTIC ACCELRA TOR G/ POLYACC P-A/ LLOYD APPROVED EQUIVALENT PRODUCT		18 / KILOGRAMME					TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red / Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25 KG <u>GENERAL SPECIFICATION -</u> Accelerator Cobalt based, Preferably USA West Europe, Japan make mixable and compatible with Resins and conforming to Lloyds's rules or following specification: a. Grade Cobalt Naphtharate 1% b. Flash point - 100 °C (Min) c. Appearance - Red /	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Violet - d. Stability in dark at 30 °C 12 Months (Min) E. PACKING: 15 OR 25 KG	
84	DNH110524	NO DATA AVAILABLE	1308750530106 / REFRIGERATOR 10.CU FT-220V AC (NO FROST)		10 / EACH/NUMBER	NO DATA AVAILABLE				TDS/BROCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DNM104692	N15839	4330123302113 / OIL FILTER	HP COMP KAP23-40E	2 / EACH/NUMBER	KAP23-40E				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Outer Diameter:2.99 to 3.7 mm Height/ Length:3.66 to 3.94 mm GENERAL SPECIFICATION - Outer Diameter:2.99 to 3.7 mm Height/ Length:3.66 to 3.94 mm	
86	DPK107949	FLUGENE 113B0MBE AEROSOL/ UFI:PMU 1-ROPD-8007-P2DQ	6850143440904 / CLEANING SOLVENT FOR ELECTRIC/ ELECTRONIC EQUIPMENT		34 / EACH/NUMBER	UFI:PMU 1-ROPD-8007-P2DQ				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c. Should have fast vaporization rate. GENERAL SPECIFICATION - Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c. Should have fast vaporization rate.	
87	DPK110108	DCSEA220AGRADE 80W90T20L	9150144025416 / LUBRICATION OF CRANE & WINCH 80W-90 (TRANS AXLE 7 80W-90) 20 Liters Packing OEM = M/s TOTAL		60 / LITER	NO DATA AVAILABLE				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
88	DPC111682	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		600 / LITER	PINAX-A				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION</u> - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. <u>GENERAL SPECIFICATION</u> - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
89	DNM107998	458-8495	5910715269298 / PUMP GP - FUEL INJECTION		1 / EACH/NUMBER	DE110E2				TDS/BROUCHER OR PIC OF ITEM MUST BE ENCLOSED	<u>TECHNICAL SPECIFICATION</u> - PUMP GP - FUEL INJECTION <u>GENERAL SPECIFICATION</u> - PUMP GP - FUEL INJECTION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										D WITH QUOTATION		
90	DPC111687	ZEEPER114	8010705332849 / ZEEPER 114 CLEANER		600 / KILOGRAMME	ZEEPER.114				TDS/BROUCHER OR PIC MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - COMPOSITION:</u> Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years <u>GENERAL SPECIFICATION - COMPOSITION:</u> Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
91	DPK107881	H 100	9150705237689 / MOBIL NUTO H 100		100 / LITER	MOBIL H SERIES				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - MOBIL NUTO H 100 HYDRAULIC OIL FOR STERN TUBE 208 Ltr Drum</u> <u>GENERAL SPECIFICATION - MOBIL NUTO H 100 HYDRAULIC OIL FOR STERN TUBE 208 Ltr Drum</u>	
92	DNM107871	232-9759	2910715268540 / LINE AS - FUEL INJECTION (LOW PRESSURE FEED)		1 / EACH/NUMBER	DE110E2				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - LINE AS - FUEL INJECTION (LOW PRESSURE FEED)</u> <u>GENERAL SPECIFICATION - LINE AS - FUEL INJECTION (LOW PRESSURE FEED)</u>	
93	DNM107997	326-4137	5340715269002 / CONNECTOR		1 / EACH/NUMBER	DE110E2				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - CONNECTOR</u> <u>GENERAL SPECIFICATION - CONNECTOR</u>	
94	DNM108000	1004841	5930006862940 / BOLT		4 / EACH/NUMBER	DE165E0				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N		
95	DNM107876	225-8525	471071526853 1 / TUBE AS		1 / EACH/N UMBER	DE110E2				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - TUBE AS</u> <u>GENERAL SPECIFICATION - TUBE AS</u>	
96	DPC107606	X06-1	681078527757 8 / Ethylene phosphide primer		5 / EACH/N UMBER	SKJ5-19				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
97	DNM107872	237-0284	291071526854 8 / LINE AS - FUEL (LOW PRESSURE RETURN)		1 / EACH/N UMBER	DE110E2				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - LINE AS - FUEL (LOW PRESSURE RETURN)</u> <u>GENERAL SPECIFICATION - LINE AS - FUEL (LOW PRESSURE RETURN)</u>	
98	DNM107995	2388288	533071527102 2 / SEAL		1 / EACH/N UMBER	DE165E0				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSE D WITH QUOTATIO N	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
99	DNM111096	ITD/WTSC U-48- FCDD	413050535055 9 / Air Conditioner (A/C) 04 Tons for		1 / EACH/N UMBER	WTSCU- 48-FCDD				TDS/BROU CHER OR PIC MUST BE ENCLOSE D WITH QUOTATI ON	<u>TECHNICAL SPECIFICATION - WEIGHT: 137.3 KG</u> <u>GENERAL SPECIFICATION - WEIGHT: 137.3 KG</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OPS Shelter of LLADR									
100	DNM107880	232-6189	4710715268538 / TUBE AS		1 / EACH/NUMBER	DE110E2				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - weight: 0.23 kg length: 22.86cm, height: 17.78cm, width 4.2 cm GENERAL SPECIFICATION - weight: 0.23 kg length: 22.86cm, height: 17.78cm, width 4.2cm	
101	DNQ109786	4015014-04	4720735289435 / mpu300 Suction Hose Kit - 8"/DN200 - 12mw/strainer		1 / EACH/NUMBER	NA				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MPU300 Suction Hose Kit/ 8"/DN200 - 12mw/strainer Dia: 8 Inch Length: 12 Meters GENERAL SPECIFICATION - MPU300 Suction Hose Kit/ 8"/DN200 - 12mw/strainer Dia: 8 Inch Length: 12 Meters	
102	DNQ107912	4015014-04	4720735289435 / mpu300 Suction Hose Kit - 8"/DN200 - 12mw/strainer		1 / EACH/NUMBER	NA				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - MPU300 Suction Hose Kit/ 8"/DN200 - 12mw/strainer Dia: 8 Inch Length: 12 Meters GENERAL SPECIFICATION - MPU300 Suction Hose Kit/ 8"/DN200 - 12mw/strainer Dia: 8 Inch Length: 12 Meters	
103	DPC110100	A020EEV2	8010705332825 / HIGHLY PERFUMED BACTERICIDAL WASHROOM CLEANER.		25 / LITER	HIGHLY PERFUMED				TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation. <u>GENERAL SPECIFICATION -</u> PRODUCT INFORMATION: APPEARANCE: GREEN CLEAR LIQUID PH 7.5 UNDILUTED ISO 9001 NO 09535 ISO 14001 NO 506072 CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS CONTAINS A BLEND O, NONIONIC SURFACTANT VISCOSITY STABILIZER, SEQUESTERING AGENT. QUATERNARY AMMONIUM COMPOUND. PERFUME AND DYE SHELF LIFE 3 YEARS highly perfumed bactericidal washroom cleaner clean disinfects and deodorises in one operation.	
104	DPK107916	SPIRAX S2 G 140	915079529305 0 / shell SPIRAX S2 G 140		4 / LITER	EMPERO EM.09.P				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
105	DNM107868	1989169	289571526816 5 / HOSE DISPOSA		1 / EACH/NUMBER	C4.4				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION -</u> HOSE DISPOSAGENERAL <u>SPECIFICATION - HOSE DISPOSAGENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
106	DNQ111744	HAMMAR H 20	4220735199199 / HAMMAR H 20 R HYDROSTATIC RELEASER FOR LIFERAFTS	HAMMAR H 20 R HYDROSTATIC RELEASER FOR LIFE RAFT	1 / EACH/NUMBER	G91154/0902	NA	CM Hammar AB, August Barks gata 15, SE-421 32 Västra Frölunda (Göteborg), Sweden Phone: +46 31 709 65 50 Fax: +46 31 49 70 23 Email: info@cmhammar.com www.cmhammar.com	CM Hammar Sweden	TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION</u> - The Hammar H20 hydrostatic release unit is designed for liferafts from 6 up to 150 persons. The Hammar H20 release unit consists of a double looped white rope sling, a release mechanism and a Red Weak Link? (breaking strength 2.2 ± 0.4 kN) <u>GENERAL SPECIFICATION</u> - The Hammar H20 hydrostatic release unit is designed for liferafts from 6 up to 150 persons. The Hammar H20 release unit consists of a double looped white rope sling, a release mechanism and a Red Weak Link? (breaking strength 2.2 ± 0.4 kN)	
107	DSB108301	ITD/221033-ITD-VTX	2990545344966 / Exhaust Bellow 6 Holes		2 / EACH/NUMBER	MAIN ENGINE					<u>TECHNICAL SPECIFICATION</u> - The Exhaust Bellow is a flexible, high-temperature-resistant connector designed to absorb vibration, thermal expansion, and movement in the exhaust system. It helps prevent leaks, reduces stress on pipes, and ensures smooth and reliable exhaust flow. <u>GENERAL SPECIFICATION</u> - The Exhaust Bellow is a flexible, high-temperature-resistant connector designed to absorb vibration, thermal expansion, and movement in the exhaust system. It helps prevent leaks, reduces stress on pipes, and ensures smooth and reliable exhaust flow.	
108	DNM111459	21344508/24077907/24542601	2920145655137 / BELT TENSIONER (ALTERNATOR)	AL TERNATOR	1 / EACH/NUMBER	D6-370D-E		AB VALVO PENTA SE 40508 GOTHENBURG SWEDEN	VALVO PENTA	TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION</u> - BELT TENSIONER (ALTERNATOR) <u>GENERAL SPECIFICATION</u> - BELT TENSIONER (ALTERNATOR)	
109	DNQ111577	CEN1000063A	5510FT1019830 / Wooden Plug, 200 x 30 x 8 mm	Portable Firefighting and Damage Control Equipment System	15 / EACH/NUMBER	55580MT.0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRKYE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD.	TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION</u> - <u>GENERAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									STI.			
110	DNQ111 575	CEN10000 63C	5510FT101983 2 / Wooden Plug 250 x 70 x 20 mm	Portable Firefighting and Damage Control Equipment System	15 / EACH/NUMBER	55580MT. 0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRKİYE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.	TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
111	DNQ111 557	CEN10000 63E	5510FT101983 4 / Wooden Plug 300 x 120 x 50 mm	Portable Firefighting and Damage Control Equipment System	100 / EACH/NUMBER	55580MT. 0001	0	SITELER MAH. OZZUMRUT SITESI. 462 NCI GUZELBAHCE-IZMIR TÜRKİYE	CENAK GIDA TUR.INS. MUH. MAK. SAN.LTD. STI.		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
112	DNM111 522	864722	533119002547 6 / SEALING RING	MAIN ENGINE VOLVO PENTA AB 370	10 / EACH/NUMBER	AB 370 VOLVO PENTA	port 20060323 90 STBD 20060324 41	AB VOLVO PENTA, GROPEGARDSGTAN, 405 08 GOTEVORG SWEDAN	AB VOLVO PENTA, GROPEG ARDSGTAN, 405 08 GOTEVORG	TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
113	DNM111 512	NO DATA AVAILABLE	513072514731 7 / DIAMOND CUTTING DISC 5" (AEG)		48 / EACH/NUMBER	NO DATA AVAILABLE			M. SHOAIB MANSOOR 13. 14 MUSA MARKEE T. SHARAH-E-LIAQUAT OPP. SINDHI MADARS A P.O BOX NO. 6726, KARACHI PHONES: 021-2428946.	TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION - a.</u> Diamond cutting disc having size of 5 inches and thickness 1.2-1.5 mm. b. Item is utilized onboard for tiles cutting work. In this regard, disc must be constructed from SS material. Moreover, disc should be circular and no cuts and gaps must be present inside the disc. <u>GENERAL SPECIFICATION - a.</u> Diamond cutting disc having size of 5 inches and thickness 1.2-1.5 mm. b. Item is utilized onboard for tiles cutting work. In this regard, disc must be constructed from SS material. Moreover, disc should be circular and no cuts and gaps must be present inside the disc.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									2421046. FAX,021- 2425060.			
114	DNQ112 005	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	5 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D	TDS / Broacher or pic must be enclosed with quotation	TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN- HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL</u> SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
115	DNQ112 003	464748 ABN.	473001435510 6 / REPAIR KIT,PIPE, EMERGENCY DAMAGE CONTROL	EMERGENCY CONTROL, PIPE REPAIR KIT.	3 / KIT			OEM: c IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT. COM	INDUMAR PRODUC TS INC DBA STOP ..	TDS / Broacher or pic must be enclosed with quotation	TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP: //WWW.STOPIT.COM <u>GENERAL</u> SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	
116	DSB1083 09	AV199909 70045	087013170343 9 / Aluminum		56 / KILOGR	NO DATA AVAILAB					TECHNICAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR.NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Filter Metal AL-Mg 4.5 M		AMME	LE					Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 <u>GENERAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183	
117	DSB108407	AV19990970045	0870131703439 / Aluminum Filter Metal AL-Mg 4.5 M		56 / KILOGRAMME	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 <u>GENERAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183	
118	DSB107548	ITD/2232018-ITD-VTX	2950545344962 / Nut of Impeller		2 / EACH/NUMBER	MAIN ENGINE					<u>TECHNICAL SPECIFICATION -</u> The Impeller Nut is a precision-engineered fastener designed to securely lock the impeller onto the shaft. It ensures stable rotation, prevents loosening under vibration and maintains proper alignment during pump or engine operation. Typically made from high-strength, corrosion-resistant material for long-term reliability. <u>GENERAL SPECIFICATION -</u> The Impeller Nut is a precision-engineered fastener designed to securely lock the impeller onto the shaft. It ensures stable rotation, prevents loosening under vibration and maintains proper alignment during pump or engine operation. Typically made from high-strength, corrosion-resistant material for long-term reliability.	
119	DSB104655	orb-pn-sm/20/v2/4.3/sk	5999505265931 / 4.3 inch human interface hmi		1 / EACH/NUMBER	P2043SA/ORB-PN-SM/20/V2/4.3/SK					<u>TECHNICAL SPECIFICATION -</u> Input power: 14-32VDC/ 0.42 A (24V) DC Resolution: 480x272 CPU: 32-bit processor Memory (flash): 128MB fATEK BRAND DETAILS ; ENCLOSED AS	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DOCUMENT <u>GENERAL SPECIFICATION</u> - Input power: 14-32VDC/ 0.42 A (24V) DC Resolution: 480x272 CPU: 32-bit processor Memory (flash): 128MB fATEK BRAND DETAILS ENCLOSED AS DOCUMENT	
120	DSA102651	GSM141-008F5MLE CZ15CN17-03 / GSM141-08F5MLEC Z15CN17-03/ 5306FBM0 DCIN0X	530614329937 5 / BOLT, INTERNALLY RELIEVED BODY/VIS CSM 141-08 INOX / BOLT, INTERNALLY RELIEVED BODY		100 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
121	DSB109886	049-21-009	830514344090 3 / SIMILI CUIR BLEU 3517		130 / METER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - b. Technical parameters of store i.e. dimension/ size and etc: Nomenclature: Rexine/ Leatherette, PVC Coated Fabric. Base Cloth: Cotton, polyester Mix. Color: Navy Blue. Width: 140 CM. Thickness: 0.9 mm to 1.1 mm Pattern: Plain/ Mat Finished (no grain) c. Specifications/ Technical Data/Testing/Acceptance Criteria/Applicable Standard: Fire retardant (M1 class non flame able) Water proof Anti-Fungus, anti-Mildew <u>GENERAL SPECIFICATION</u> - b. Technical parameters of store i.e. dimension/ size and etc: Nomenclature: Rexine/ Leatherette, PVC Coated Fabric. Base Cloth: Cotton, polyester Mix. Color: Navy Blue. Width: 140 CM. Thickness: 0.9 mm to 1.1 mm Pattern: Plain/ Mat Finished (no grain) c. Specifications/ Technical Data/Testing/Acceptance Criteria/Applicable Standard: Fire retardant (M1 class non flame able) Water proof Anti-Fungus, anti-Mildew	
122	DSB105358	ORB/RS	613070520040 4 / 24V STBD		3 / EACH/NUMBER	PRO-M					<u>TECHNICAL SPECIFICATION</u> - nput supply: 100- 240VAC 50/60 Hz	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			POWER SUPPLY 10 AMP		UMBER						Output supply: 24VDC Output voltage adjustment range: 22.5VDC-29.5VDC Output current: 10Amp Power rating: 250WGENERAL SPECIFICATION - nput supply: 100-240VAC 50/60 Hz Output supply: 24VDC Output voltage adjustment range: 22.5VDC-29.5VDC Output current: 10Amp Power rating: 250W	
123	DRG93715	BARREL JP	4320ZO6531217 / BARREL EMPTY FUEL JP1/JP4 EPOXY COATED REUSABLE		64 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - CAPICITY 210 LIT (40/45 IMPERIAL GALLON), SPECIAL PURPOSE EPOXIY COATED, TO BE USED FOR AVN FUEL GENERAL SPECIFICATION - CAPICITY 210 LIT (40/45 IMPERIAL GALLON), SPECIAL PURPOSE EPOXIY COATED, TO BE USED FOR AVN FUEL	
124	DSX101031	T011007	5340TY6720772 / PIANO HINGES S/STEEL (1200X70X2MM)		10 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
125	DSA107725	SCB-2000	6710735164082 / COLOR V-CAMERA D/N 600TV LINE/LENS2.8-10MM/68IP CASING+STAND		4 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
126	DSB102218	31851	5925144820639 / CIRCUIT BREAKER (115V 60HZ BREAKER)		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 115 Volt 60Hz AC Network (BF system) breaker NSX250F TP 200Amps Adjustable 160 to 200Amps Photo attached.GENERAL SPECIFICATION - 115 Volt 60Hz AC Network (BF system) breaker NSX250F TP 200Amps Adjustable 160 to 200Amps Photo attached.	
127	DSB109184	50TE000C0027	6685745194283 / THERMOMET		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			ER BDT 25 & 26 OA 200 DIAM93 SUTTE OM								AVAILABLE	
128	DSX101030	2CD059	5310755043683 / CONICAL WASHER S-STEEL-10X31X1.5MM		200 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
129	DSA103441	488821	5360142749717 / RESSORT COMPRESSION DISTO		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
130	DSA102570	E27311H60M22AET	5305142353234 / VIS HM 6X18X18 A52		310 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
131	DSA102648	GSM141-008F5MLEBZ15CN17-03 / GSM141-08F5MLEBZCN17-03	5306143299374 / BOLT, INTERNALLY RELIEVED BODY (VIS-F90EV1-CARRE-B-ZISCN17-0)		50 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
132	DSB109891	ITD/NRV-FUELSS-1.5-VTX	4820545289487 / Fuel Non Return Valve		2 / EACH/NUMBER	NRV-FUELSS-1.5-VTX					TECHNICAL SPECIFICATION - Fuel Non Return Valve. (1) Valve is fitted in fuel circuit and prevents reverse flow of fuel. (2) Strength test may be conducted with the following test conditions: (a). Fluid: Water (b). Pressure: 2.6 bar (c) Duration: 10 min Material Stainless Steel 316 GENERAL SPECIFICATION - Fuel Non Return Valve. (1) Valve is fitted in fuel circuit and prevents reverse flow of fuel. (2) Strength test may be conducted with the following test conditions: (a). Fluid: Water (b). Pressure: 2.6 bar (c) Duration: 10 min Material Stainless Steel 316	
133	DNH111461	1.030-911.0/HDS 10/204M/H DS 10/214	4320725113693 / KARCHER MACHINE (HOT WATER	KARCHER MACHINE FOR WASHING OF MAIN	1 / EACH/NUMBER	HDS 10/21-4M					TECHNICAL SPECIFICATION - as per attached brusher KARCHER MACHINE (HOT WATER HIGH PRESSURE WASHER WITH 30	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		CLASSIC	HIGH PRESSURE WASHER WITH 30 MTR HIGH PRESS HOSE ,400 bar 6.110-023.0).	MAST&RADAR							MTR HIGH PRESS HOSE ,400 BAR 6.110-023.0). <u>GENERAL SPECIFICATION</u> - as per attached brusher KARCHER MACHINE (HOT WATER HIGH PRESSURE WASHER WITH 30 MTR HIGH PRESS HOSE ,400 BAR 6.110-023.0).	
134	DNH111722	EAC-70/WP-1302/ECM 6500	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	12 / EACH/NUMBER	EAC-70/WP-1302/ECM 6500				TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION</u> - 220/240V AC SINGLE PHASE FULL SIZE <u>GENERAL SPECIFICATION</u> - 220/240V AC SINGLE PHASE FULL SIZE	
135	DNM111443	F48E-P/DEU48/BMCU-48	4130715089740 / CONDENSING UNIT CRUISAIR TYPE SELF A/C UNIT 4TON	MAIN A/C CRISAIR USA TYP.F48E-P.	1 / EACH/NUMBER	BMCU-48				TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
136	DNM111728	70HFR20	5961755067777 / METAL STUD DIODE 70HFR20 METAL DO-5 PACKAGE	DORMAN D/G 500KVA (UK)	3 / EACH/NUMBER	70HFR20				TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION</u> - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE <u>GENERAL SPECIFICATION</u> - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE	
137	DNQ111428	NO DATA AVAILABLE	0262500001365 / LADDER-ALUMINIUM-EXTENDING-28FEET CAPABLE OF WITH STANDING		1 / EACH/NUMBER	NO DATA AVAILABLE				TDS / Broacher or pic must be enclosed with quotation	<u>TECHNICAL SPECIFICATION</u> - 1. Closed height: 5 Meter 2. Extended height: 9 Meter 3. Approximately weight: 26 KG 4. Loading capacity: 150 KG 5. Warranty: Life time <u>GENERAL SPECIFICATION</u> - 1. Closed height: 5 Meter 2. Extended height: 9 Meter 3. Approximately weight: 26 KG 4. Loading capacity: 150 KG 5. Warranty: Life time	
138	DSX100969	T0502	5999TY6712480 / H.LOCK SET		17 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
139	DRG106240	CARBURATOR 17.83 CC	2590ZO6555427 / CARBURATOR 17.83 CC,OS-108(7L)		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE:17.83CC,OS-108,E/I:PERWAZ, MAKE:JR JAPAN GENERAL SPECIFICATION - SIZE:17.83CC, OS-108,E/I:PERWAZ,MAKE:JR JAPAN	
140	DNM110142	4302654	4420715198786 / HEAT EXCHANGER	CUMMINS DG HX956GW USA	1 / EACH/NUMBER		22068610	COMMINS USA NEWAGE LTD 4700 MAIN ST, N.E FRIDLEY MINNESOTA 55421 TEL: (1)800 367 2764 FAX: (1)800 863 9243	COMMINS USA	TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - HEAT EXCHANGER GENERAL SPECIFICATION - HEAT EXCHANGER	
141	DRG105881	MIL-G-43914 OR 43914 (PHOTO ENCLO	5820013288268 / GOGLESS SUN WIND DUST(P/AIR DEP/222 SQN/03/2693048		5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - BRAND: 3M MAXIM, CASE QUANTITY: 10, CLASS:PREMIUM, COLOR:CLEAR, COMFORT FEATURES:ELASTIC STRAP, FLEXIBLE FIT, SOFT RUBBER SEAL, FRAME COLOR: BLACK, FRAME STYLE:FULL FRAME, LENS:ANTI-FOG, LENS COLOR GENERAL SPECIFICATION - BRAND: 3M MAXIM, CASE QUANTITY: 10, CLASS:PREMIUM, COLOR:CLEAR, COMFORT FEATURES:ELASTIC STRAP, FLEXIBLE FIT, SOFT RUBBER SEAL, FRAME COLOR: BLACK, FRAME STYLE:FULL FRAME, LENS:ANTI-FOG, LENS COLOR	
142	DRG106203	BTT1-206-000-000	2630ZO6550515 / TUBE FUEL SILICON FOR BANSHEE AIRCRAFT(JR JAPAN)		50 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - LENHTH=13.5CM, OUTER DIA=5.5MM, INNER DIA=2MM, MATERIAL: SOFT RUBBER GENERAL SPECIFICATION - LENHTH=13.5CM, OUTER DIA=5.5MM, INNER DIA=2MM, MATERIAL: SOFT RUBBER	
143	DPK106644	90790-BS802	9150705102424 / GEAR OIL (750CC X 1) FOR OBM	OBM ENGINE, GEAR,MOBILE ASHARI PVT LTD.KAR	451 / TUBE					TDS\BROCHER OR PIC OF ITEM MUST	TECHNICAL SPECIFICATION - 750 ml Tube Packing GENERAL SPECIFICATION - 750 ml Tube Packing	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ENGINE (GL4 OUTBOARD GEAR OIL SAE 90) OEM = YAMALUBE							BE ENCLOSED WITH QUOTATION		
144	DRG106237	ZO6555426	2590ZO6555426 / CARBURETTOR (OS MAX-95 (MODEL/TYPE 61C))		7 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - MAKE: OS JAPAN CARBURATOR COMPLETE (7H/61) FOR 11.5CC READ 14.95CC O I/C H/M 191000 E JULY05 OS-91 IS QUOTED ON ITEM 7H 61 MAKE-OS JAPAN. OEM: OS ENGINE GENERAL SPECIFICATION - MAKE: OS JAPAN CARBURATOR COMPLETE (7H/61) FOR 11.5CC READ 14.95CC O I/C H/M 191000 E JULY05 OS-91 IS QUOTED ON ITEM 7H 61 MAKE-OS JAPAN. OEM: OS ENGINE	
145	DNM109534	70HFR20	5961755067777 / METAL STUD DIODE 70HFR20 METAL DO-5 PACKAGE	DORMAN D/G 500KVA (UK)	3 / EACH/NUMBER	70HFR20				TDS/BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE GENERAL SPECIFICATION - DORMAN D/G 500KVA (UK) 70HFR20 METAL DO-5 PACKAGE	
146	DRG106210	BTT1-320-100-000	1440ZO6551623 / Power Band Launcher (13 Feet Dual)		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Arms : 02 Arm Length: 13 Ft each Band Dia: 01 Inch 01 x Main Eye (1.5" Dia) 02 x Arm Eyes (1.5" Dia) OEM/ Country of Origin: Pakistan Parent Equipment: Parwaz Import Documents :Item is locally made and do not requires import documents GENERAL SPECIFICATION - Arms : 02 Arm Length: 13 Ft each Band Dia: 01 Inch 01 x Main Eye (1.5" Dia) 02 x Arm Eyes (1.5" Dia) OEM/ Country of Origin: Pakistan Parent Equipment: Parwaz Import Documents :Item is locally made and do not requires import documents	
147	DRG109	ZO657083	4710ZO657083		400 /	NO DATA					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	109	8	8 / PVC PIPE DIA 1"		FOOT	AVAILAB LE					PVC(HARD PLASTIC) WITH JOINTS,AVAILABLE IN 20 FEETLENGTH,ONE JOINT REQD FOR EACH 2 PIECES,FOR 4 PIECES 3 JOINTS REQD a. PVC PIPE DIA 1", b. MATERIAL HARD, ALONGWITH JOINT (SOCKET), c. PIPE LENTH 20 FEET, c. BRAND PAK ARAB OR STEELEX, d. CLOUR WHITE OR GREY. <u>GENERAL SPECIFICATION - PVC (HARD PLASTIC) WITH JOINTS, AVAILABLE IN 20 FEETLENGTH, ONE JOINT REQD FOR EACH 2 PIECES,FOR 4 PIECES 3 JOINTS REQD a. PVC PIPE DIA 1", b. MATERIAL HARD, ALONGWITH JOINT (SOCKET), c. PIPE LENTH 20 FEET, c. BRAND PAK ARAB OR STEELEX, d. CLOUR WHITE OR GREY.</u>	
148	DRG107-096	SMTCS08-02	7210ZO656201 1 / PVC MAT (VENYL FLOORING) - WIDTH : 2 MTR, THICK 2MM		50 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - W=2M,TH=2MM,LENGTH AS REQUIRED,COLOUR DARK GREY WITH 25MM CIRCLES DESIGN NO. SMTCS08-02) MAKE: LOCAL/IMPORTED SAMPLE HELD IN LIB. GENERAL SPECIFICATION - W=2M,TH=2MM,LENGTH AS REQUIRED,COLOUR DARK GREY WITH 25MM CIRCLES DESIGN NO. SMTCS08-02) MAKE: LOCAL/IMPORTED SAMPLE HELD IN LIB.</u>	
149	DPC107-049	SUPERSEDED BY: DGS 1035	044250220202 0 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	531 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	<u>TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed</u> <u>GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Packing Flash point 38c (min) stage inspection prescribed	
150	DPC108192	SUPERSEDED BY DGS 1035	0442502202020 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	56 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
151	DPC109505	SUPERSEDED BY DGS 1035	0442502202020 / PAINT FINISHING (RED)	DECK AND DADOES PRIMER	13 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed GENERAL SPECIFICATION - DEFSTAN 80-151/1 OF 1991 NS/P/006 OF 1976 SHADE NO BS 4800 OF 1981 SHADE RED 04-D-45 04 LTR Packing Flash point 38c (min) stage inspection prescribed	
152	DPC109514		0442504420041 / PAINT ENAMEL (WHITE), Brushing, Flash Point 32C(Min), ALKYED Type (04 LTR TIN)	3 INCH ROCK LAUNCH	823 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - DEFSTAN 80-59/1 OF 1976 Stage inspection prescribed 04 ltr tin Flash point: 32 C Type: ALKYED GENERAL SPECIFICATION - DEFSTAN 80-59/1 OF 1976 Stage inspection prescribed 04 ltr tin Flash point: 32 C Type: ALKYED	
153	DPC108293		0442509429374 / VARNISH MARINE SYNTHETIC, Flash Point 34C (04 Ltrs Packing)	USE ON WOOD UNDER CONDITIONS OF MARINE EX	344 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE INSPECTION PRESCRIBED GENERAL SPECIFICATION - G/P-307/248 EXCEPT FLASH POINT INDICATED AS 34 DEGREE C. 2. STAGE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										N	INSPECTION PRESCRIBED	
154	DPC109524		0442504420069 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		132 / LITER					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
155	DPC110503	NO DATA AVAILABLE	0474500007028 / SAND YORKSHIRE FOR STEEL MOULDING (50 KG BAG)		150 / BAG					TDS\BROCHER OR PIC OF ITEM MUST BE ENCLOSED WITH QUOTATION	TECHNICAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601 (1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0 GENERAL SPECIFICATION - JAPAN INTERNATIONAL STANDRED GUIDE(JIS-G)5601(1974) TABLE NO 5 SPECIFICATION/REF: SIO: MORE THEN 93-96 Fe203: LESS THEN 1.5 AL203: LESS THEN 4.5 Cao+Mgo: LESS THEN 2.0	
156	DRG107633	ZO6555421	1610ZO6555421 / PROPELLER (MASTER AIR SCREW 14" X6")		80 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Flight RC Wooden Beach Propeller Material: Beach Wooden Size: 14X6 Type: Clockwise ROTATION GENERAL SPECIFICATION - Flight RC Wooden Beach Propeller Material: Beach Wooden Size: 14X6 Type: Clockwise ROTATION	