

LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 11-11-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF “PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT” (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)
2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.
3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.
4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL: clp@paknavy.gov.pk, localpurchasedivision@gmail.com

PHONE: 021-48508524, 48508828,

WHATSAPP NO. 92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGT112 369	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	60 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
2	DGT113 038	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	72 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18% <u>GENERAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	
3	DGT112 509	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	64 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION -</u> size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06 % to 18%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture content: 06 % to 18%	
4	DGB111970	4992	4020795153120 / DOUBLE SIDED TAPE (SIZE 12MMX50M)	TALL SHIP SAILING RIG	6 / EACH/NUMBER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT.COM WWW. BASELINEHARDWARE.CO.UK	BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL E		<u>TECHNICAL SPECIFICATION</u> - LIGHT,NON YELLOWING ACRILIC TAPE WITH VERY HIGH ADHESION,SIZE: 12mmx50m <u>GENERAL SPECIFICATION</u> - LIGHT,NON YELLOWING ACRILIC TAPE WITH VERY HIGH ADHESION,SIZE: 12mmx50m	
5	DGE95100	NIL	5330705131806 / RUBBER STRIP,	DOOR&HATCHES SEAL	370 / METER	NO DATA AVAILABLE		PK	ABBASI TRADERS RUBBER STORE PH#2416152		<u>TECHNICAL SPECIFICATION</u> - SIZE= WIDTH= 40-MM, THICKNESS= 20-MM, LENGTH= 13 METER IN ROLL, MATERIAL= EPDM, <u>GENERAL SPECIFICATION</u> - SIZE= WIDTH= 40-MM, THICKNESS= 20-MM, LENGTH= 13 METER IN ROLL, MATERIAL= EPDM,	
6	DGE113054	YCR105 or 1260	8305785163090 / CERAMIC FIBER CLOTH	GENERAL USE	103 / METER	YCR105		OEM:CHINA MANUFACTURERS NINGBO RUIFENG SEALING MATERIAL COMPANY LTD KUANGVAN TOWN CIXI : 86-574-63531211.63531433.	PANASONIC SADDAR KARACHI. TECHNO POWER SYSTEM		<u>TECHNICAL SPECIFICATION</u> - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd, colour = white, temperature resistance= 700 °C (degree centigrade), max thermal conductivity= 0.16 w/m.K <u>GENERAL SPECIFICATION</u> - size= width= 60.00 inCH (1,524 MM), thickness= 48 mils (1.22 MM), length= 50.00 yards PER ROLL (45.72 METER PER ROLL), weight= 24.00 oz/ sq yd.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											colour = white, tempErature resistance= 700 °C (degree centigrade), max thermal conDuctivity= 0.16 w/m.K	
7	SGE112 916	10MM	5970705133476 / GLASS SLEEVING 10MM	MOTOR WINDING FOR CABLE	200 / EACH/NUMBER	NO DATA AVAILAB LE		PK	GREEN WAY ELECTRI C STORE SHOP NO.1-5 ARAMBA GH KARACHI		TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
8	DGE113 103	NIL	7210505155172 / FIRE RETARDANT SPRING MATTRESS (L6' X W2' X H6")	MATRESSES FOR BED	25 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL-KHAIR HOUSE-43-T		TECHNICAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413GENERAL SPECIFICATION - size: length: 6 Feet width: 2 Feet height: 6 inch COMPLIANCE TO STANDARD ASTM D 6413	
9	DGE112 053		0422705158411 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 1.5 MM)	SELF	1000 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTIC S, SADDAR KARACHI		TECHNICAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM GENERAL SPECIFICATION - SHEET LENGTH= 18.5 M, WIDTH= 1.5 m, THICKNESS= 1.5 MM	
10	DGE972 49	L10/11610	5340775168377 / FLAT POLYSTER WEBBING SLING, SF 6:1	POLICE BOAT LIFTING	2 / EACH/NUMBER			EUROTEX HOLLAND	EUROTE X HOLLAN D		TECHNICAL SPECIFICATION - 10 INCH WIDE 20M LONG PLY 3 VERTICAL LIFT 150000KG U-LIFT 30000KG PLOT 122-C KEMARI TOWNSHIP KEMARI KARACHI PH 0333-2114658GENERAL SPECIFICATION - 10 INCH WIDE 20M LONG PLY 3 VERTICAL LIFT 150000KG U-LIFT 30000KG PLOT 122-C KEMARI TOWNSHIP KEMARI KARACHI PH 0333-2114658	
11	DGB995 57	Morgan TPC 843	0474795208626 / Morgan Silicon Carbide Crucible, Top Dia: 420MM,	TILTING FURNACE NO 3006 TYPE CA F-23 (PLL) RECORD	1 / EACH/NUMBER	N/A	N/A	MOLTEN ADVANCED MATERIALS PLC REGISTERED IN ENGLAND AND WALES REGISTRATION NO	MORGAN ITE CRUCIBL E LTD		TECHNICAL SPECIFICATION - Morgan Silicon Carbide Crucible, Height: 675MM, Top Dia: 420MM, Bottom Dia: 295MM, Part No. TPC 843 (drawing enclosed)GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Bottom Dia: 295MM					286773 & INDIA MANUFACTURED			SPECIFICATION - Morgan Silicon Carbide Crucible, Height: 675MM, Top Dia: 420MM, Bottom Dia: 295MM, Part No. TPC 843 (drawing enclosed)	
12	DGT112349	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	500 / FOOT	NO DATA AVAILABLE		PK	TAWAKAL BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
13	DGT97546	NO DATA AVAILABLE	9340705149922 / MEDIUM DENSITY FIBER BOARD (LASANI) OAK COLOUR LAMINATION BOTH SIDE DENSITY 750kg/cubic meter SIZE: L=8' W=4' TH=16MM	WOOD WORKS SHIPS&ESTABLISHMENT	5 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		TECHNICAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM GENERAL SPECIFICATION - BSEN-622-1 LENGTH 08FEET WIDTH 04 FEET THICKNESS 16MM	
14	SGT112923		0100705149926 / LASANI PLY SHEET (SIZE8'x'	WOOD WORK SHIPS/ESTABLISHMENT.	40 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART		TECHNICAL SPECIFICATION - size: 8'x'4x16mm GENERAL SPECIFICATION - size: 8'x'4x16mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			4x16mm) SIMPLE.						WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.			
15	SGB65953	DEVS7866	473099525334 8 / FLANGE		8 / EACH/NUMBER	NO DATA AVAILABLE		UK	MOD (NAVY) SHIP SUPPORT AGENCY DME MC253 ROOM 19 BLOCK B FRAHILL BATH UK		TECHNICAL SPECIFICATION - BS 1400 Inner dia: 1 1/2 inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: 1/2 inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing GENERAL SPECIFICATION - BS 1400 Inner dia: 1 1/2 inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: 1/2 inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing	
16	DGE105350	4910-600	662578522549 2 / DIGITAL LEVEL AND SLOPE METER	LEVEL METER 4910-600 USA	1 / EACH/NUMBER	4910-600	NIL	INSIZE COMPANY LTD,80 XIANGYANG ROAD, SUZHOU NEW DISTRICT, CHINA TEL;05126809993 FAX051268085081	INSIZE COMPANY LTD,		TECHNICAL SPECIFICATION - RANGE 0-360 DEGREE(90X4), RESOLUTION = AT 0 DEGREE AND 90 DEGREE=0.8725mm/m at others 0.1 (=1.745mm/m), Accuracy= at 0 degree and 90 degree +/- 1, at 0 and 90 degree buzzer alarm, Length overall=600mm, Length internal=585mm, Breadth=60mm, thick=25mm GENERAL SPECIFICATION - RANGE 0-360 DEGREE(90X4), RESOLUTION = AT 0 DEGREE AND 90 DEGREE=0.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											8725mm/m at others 0.1 (=1.745mm/m), Accuracy= at 0 degree and 90 degree +- 1, at 0 and 90 degree buzzer alarm, Length overall=600mm, Length internal=585mm, Breadth=60mm, thick=25mm	
17	DGE113020	SA9-27017	6260010744229 / LIGHT, CHEMILUMINESCENT GREEN	REPLENISHMENT LIGHT	340 / EACH/NUMBER			CYALUME TECHNOLOGIES SA 295 R MAYOR DE MONTRICHER AIX EN PROVENCE FRANCE AIX EN PROVENCE CEDEX 3 04 42 37 17 80 04 42 37 17 99 325965622 XFARCY@CYALUME.COM WWW.CYALUME.COM	CYALUME TECHNOLOGIES		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
18	DGE112143	NIL	8415705228017 / PARACHUTE CLOTH FOR WEAPONS AND SENSORS	Cloth	200 / METER	NIL		AL MUSTAFA TRADERS F-41/F-42, Iqbal Center, M. A. Jinnah Road, Karachi-74200	AL MUSTAFA TRADERS		<u>TECHNICAL SPECIFICATION -</u> Type of cloth: Parachute Cloth Code: D-16-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof. with good quality gauge to withstand humid and hot environment. <u>GENERAL SPECIFICATION -</u> Type of cloth: Parachute Cloth Code: D-16-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof. with good quality gauge to withstand humid and hot environment.	
19	DGE106588	NIL	4020785142495 / MOORING ROPE, MIXED POLYESTER & POLYPROPYLENE, DIA 64-MM, 8-STRAND, Z-LAY, TYPE-1, CIRC 8-INCH,	DREDGER	440 / METER	NO DATA AVAILABLE		CH	CHINA SHIP BUILDING CO. LTD. CHINA.E-MAIL: XUJJ<XUJJ@MAIL.CHINASHIP.COM, TEL# +861		<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 10556-2009, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 220 METER. 6. VALID LLOYD'S/ DNV/ BSI/ CERTIFICATE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									0-88573502 FAX#+8610-88573692		OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 10556-2009, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 220 METER. 6. VALID LLOYD'S/ DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
20	DGE101128		0330509427267 / FLANNELETTE CLOTH WHITE GROUND WITH RED STRIPT 4"X50 YARDS	SMALL ARMS CLEANING	2200 / METER						<u>TECHNICAL SPECIFICATION</u> - BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural. <u>GENERAL SPECIFICATION</u> - BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural.	
21	DGE111905		0330509427267 / FLANNELETTE CLOTH WHITE GROUND WITH RED STRIPT 4"X50 YARDS	SMALL ARMS CLEANING	760 / METER						<u>TECHNICAL SPECIFICATION</u> - BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural. <u>GENERAL SPECIFICATION</u> - BOOK REF DEF STAN 83 - 48/2 1977 Size: 4" x 2". Width: 10 cm. Material:100% Softness Cotton and Gun Care Cleaning Products. Colour: Natural.	
22	DGB105		028259571212		6 /						<u>TECHNICAL SPECIFICATION</u> - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	903		9 / PIPING-COPPER-ALLOY EXT DIA MAX 4.184"MIN 4.178"INT DIA 4"		METER						DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DGB112852		0283700001608 / INGOT-BRASS		200 / KILOGRAMME						TECHNICAL SPECIFICATION - Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg GENERAL SPECIFICATION - Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg	
24	DGE106061	ISO-11812004, BS-2087	0350595713232 / ROPE SISAL 3 STRAND CIRC 1.25 DIA 13/32 (0.40625) ROT PROOFED	GENERAL USE	600 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM/MANUFACTURED COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OEM/MANUFACTURED COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
25	DGE112 550	BS2052 , DEF STAN 40-3	035059571324 6 / SPUN YARN SISAL S TWIST R. FROOFED 4/20 YARN LENGTH PER COIL 608-5% (FM)		90 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - 1.</u> Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor) <u>GENERAL SPECIFICATION - 1.</u> Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor)	
26	DGE110 682	NO DATA AVAILABL E	035059923357 5 / FENDER MARINE ROUND SISAL WT.32 LBS. OVERALL DIA 2",INTERNAL DIA 8" FOR HARBOUR LAUNCHES		8 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> MEDIUM SIZE: 1000 MM LENGHT 500 MM DIAMETER 1550 MM CIRCUMFERENCE 1 MATERIAL EVA FOAM AND NATURAL RUBBER 1 TYPE: FLANGE TYPE AND ROPE TYPE 1 ISO 9001 COMPLIANCE 1 ENERGY ABSORPTION 08 K NM 1 FORCE RECTION 71 KN <u>GENERAL</u> <u>SPECIFICATION - 1.</u> MEDIUM SIZE: 1000 MM LENGHT 500 MM DIAMETER 1550 MM CIRCUMFERENCE 1 MATERIAL EVA FOAM AND NATURAL RUBBER 1 TYPE: FLANGE TYPE AND ROPE TYPE 1 ISO 9001 COMPLIANCE 1 ENERGY ABSORPTION 08 K NM 1 FORCE RECTION 71 KN	
27	DGE112 024	14.02.0012	035059923357 7 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32- MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED. <u>GENERAL SPECIFICATION - 1.</u> SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED.	
28	DGE112 139		041370506324 3 / ANTI SKID DOTTED RUBBER FLOORING COLOUR GREEN 15" X36"0.17".		68 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
29	DGE112 022		046159220367 8 / PAPER, ABRASIVE 9" X11" (OROCUS) MATERIAL EMERY GRADE 4/0		260 / SHEET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
30	SGE112 911	NO DATA AVAILABLE	047659943474 3 / TUFF GRADE 1" PAINT BRUSH	HANGAR DOOR	450 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> Bristle material: China bristle 2. Bristle colour: White/BLACK 3. Bristle width: 25mm 4. Bristle thickness:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											10mm <u>GENERAL SPECIFICATION</u> - 1. Bristle material: China bristle 2. Bristle colour: White/BLACK 3. Bristle width: 25mm 4. Bristle thickness: 10mm	
31	DGE109073		041459923069 7 / PACKING ASSEMBLIES EXT.DIA 1- 23/32" I.DIA 1- 1/8"NO.PER SET 2		86 / SET						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
32	DGE89409	NO DATA AVAILABL E	041359923875 5 / MAT FLOOR RUBBER LG. 18. WD.(LTR NO E-I/4927- A/1082 DT221096)		10 / METER						<u>TECHNICAL SPECIFICATION</u> - Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4- 6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black. <u>GENERAL SPECIFICATION</u> - Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4- 6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black.	
33	DGE99009		041459923090 3 / PACKING GLAND MATERIAL COTTON BRAIDED SECTION NON SIZE 3/16"		16 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
34	SGE112		041459923091		240 /						<u>TECHNICAL SPECIFICATION</u> - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	927		1 / PACKING MATERIAL HEMP FOR FURNACE FUEL, SIZE= 1/4" SQ		METER						DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
35	DGE97669	NO DATA AVAILABLE	0462546005784 / TAPE-BROWN-PAPER-GUMMED (DTLD. NSD/TD/19/286 . DT.09		90 / ROLL	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
36	SGE112915		0476590009100 / GLASS FOR WELDING SIZE 4 1/4"X3 1/4"X1/16"	HULL ABOVE U/W	700 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DGE106615		0476599242508 / SHEET GLASS ALL EDGES AS CUT LG. 914MM WD. 600MM TH. 6.350MM.		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DGE76914		0476599430441 / BRUSH ARTISTS QUILL FERRULE;RED SABLE HAIR EXPOSED LG. 0.500"		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
39	SGE112925		0476599244519 / STRAPS LEATHER HYDRAULIC 4. -3"X4.-3" WEIGHT 5LB THICK 0.0625"		40 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
40	DGB112358	BS-1471-NT4	0282595711976 / TUBE, ALUMINIUM		30 / METER						TECHNICAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ALLOY,EXT DIA 2"TH 0.060"WIDG 60 SPE BS 1471								GENERAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades)	
41	DGB112 362		028359571143 3 / ROD NAVAL BRASS HEX SIZE A/F 1.10"WT PER FT 3.910(LB)		6 / METER						TECHNICAL SPECIFICATION - SPECS BSEN 12163 OF 2024, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet GENERAL SPECIFICATION - SPECS BSEN 12163 OF 2024, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet	
42	DGB112 170		028359571144 7 / ROD NAVAL BRASS RD DIA 01 INCH	GENERAL USE	20 / METER						TECHNICAL SPECIFICATION - BS EN 12163 OF 2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98LBS, R-LENGTH-03 METERS (EACH) GENERAL SPECIFICATION - BS EN 12163 OF 2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98 LBS, R-LENGTH-03 METERS (EACH)	
43	DGB112 179		028359571144 8 / ROD NAVAL BRASS RD DIA 1-1/8,	SERVICE PUMP	20 / METER						TECHNICAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft:3.70 lb authority: br320d BS EN/2163 OF1998 GRADE CW719R (M) GENERAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft:3.70 lb authority: br320d BS EN/2163 OF1998 GRADE CW719R (M)	
44	DGB112 381		028359571145 1 / ROD NAVAL BRASS RD DIA 1.50 INCH(38MM), L: 4 MTR, WT/FT: 6.05 LBS		8 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2024, CW712R, MATERIAL CONDITION: R-400. GENERAL SPECIFICATION - BSEN 12163 OF 2024, CW712R, MATERIAL CONDITION: R-400.	
45	DGB112 373		027670000363 4 / SEAL LEAD FOR SEALING COVER JOINT		25 / GROSS						TECHNICAL SPECIFICATION - diameter: 9mm thickness:4mm material: lead GENERAL SPECIFICATION - diameter: 9mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											thickness:4mm material: lead	
46	SGE112 913	0461-931-8996	0460599318996 / TAPE COTTON ADHASIVE COMPOUND WIDTH 3" THICK 0.038" LG.10 MTR.	30 MM GUN.	350 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DGB112 360		0283595711474 / SHEET-NAVAL-BRASS-ANNEALED 48		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340 GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
48	DGB104 432		0283595711474 / SHEET-NAVAL-BRASS-ANNEALED 48		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340 GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
49	DGE113 053	NO DATA AVAILABLE	0451594510013 / OIL-CLOTH PAINTED FOR TABLE COVERS WHITE WIDTH 50 INCH	GENERAL USED	490 / METER						TECHNICAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS GENERAL SPECIFICATION - AS PER STOCK SAMPLE HELD BY CINS	
50	DGE105 686		0350595713173 / ROPE SISAL, BOLT ROPE AND STAGE LASHING, 3-STRAND, CIR: 1", DIA: 0.3125" (8-MM)		240 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. 7. OEM: M/S COTESI <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. 7. OEM: M/S COTESI	
51	DGE106 665	NIL	035059571323 1 / ROPE SISAL, HAWSERLAID, 3-STRD, CIRC: 1,1/8 INCH DIA: 10-MM		1500 / FATHO M						<u>TECHNICAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
52	DGE113098		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN TRANSPAREN T L X W X THIC 48"X48"X0. 250"		50 / SHEET						TECHNICAL SPECIFICATION - Manfr/Tech.Sponcer Code reference: DTD 5592GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference:DTD 5592	
53	DGE113052		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN TRANSPAREN T L X W X THIC 48"X48"X0. 250"		34 / SHEET						TECHNICAL SPECIFICATION - Manfr/Tech.Sponcer Code reference: DTD 5592GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference:DTD 5592	
54	DGE99051		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN TRANSPAREN T L X W X THIC 48"X48"X0.		12 / SHEET						TECHNICAL SPECIFICATION - Manfr/Tech.Sponcer Code reference: DTD 5592GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference:DTD 5592	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimensior
			250"									
55	DGB105902		0212595710283 / BAR STEEL CARBON HOT ROLLED FLAT 04"X3/8"WT PER FT 5.10 LBS		50 / METER						TECHNICAL SPECIFICATION - RELEVANT SPECS i,e BS 970 EN 3A GENERAL SPECIFICATION - RELEVANT SPECS i,e BS 970 EN 3A	
56	DGT113086	NO DATA AVAILABL E	0100546002290 / BAMBOO SIZE 28FT-30FT LONG	DEISEL GENERATOR	250 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10-30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREE GENERAL SPECIFICATION - LENGTH: 30 FEET DIAMETER: 10-30 CM WALL THICKNESS; 1-8 CM WEIGHT: 2-10 LBS/FT MOISTURE CONTENT: 10-20% GRADE: HIGH QUALITY STRAIGHT AND DEFECT FREE	
57	DGB82813	HA-680	0268590012396 / Weighing Machine B/Roo		1 / EACH/N UMBER	HA-680/HA-622					TECHNICAL SPECIFICATION - 1. body weighing: 120 kg maximum weight ; 160 kg (sub- diviions of the weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO JAPAN GENERAL SPECIFICATION - 1. body weighing: 120 kg maximum weight ; 160 kg (sub- diviions of the weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO JAPAN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
58	DGH112855		021159923013 9 / PLATE STEEL CARBON SIZE 2440X1220X3. 2MM	HOUSE SIDE FTG	22 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> BSEN:10025/2 OF 2019, STEEL GRADE: S275 JR. TOLERANCE REQUIREMENT: BSEN10029 (CLASS C) WEIGHT PER SQ. FEET: 5 LBs special instructions: a. MILL TEST certificate (MTC) required alongwith supply. the certificate should have information on mechanical & chemical properties, steel grade, batch & heat number alongwith date. b. each plate shall have a suitable stamp at a corner indicating batch number, grade and manufacturer for case identification. c. material should be freshly rolled & free steel all defects. <u>GENERAL SPECIFICATION -</u> BSEN:10025/2 OF 2019, STEEL GRADE: S275 JR. TOLERANCE REQUIREMENT: BSEN10029 (CLASS C) WEIGHT PER SQ. FEET: 5 LBs special instructions: a. MILL TEST certificate (MTC) required alongwith supply. the certificate should have information on mechanical & chemical properties, steel grade, batch & heat number alongwith date. b. each plate shall have a suitable stamp at a corner indicating batch number, grade and manufacturer for case identification. c. material should be freshly rolled & free steel all defects.	
59	DGH108348		022259571850 7 / SHACKLE JOINING IRON SIZE 1-1/4X1. 750X4.250"		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> <u>DATA AVAILABLE</u> <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> <u>AVAILABLE</u>	
60	DGB112363	SPECIFICATION BS 887	027459910007 7 / CALIPER VERNIER ENG&MM COMB IN&EXT W/CASE 0-	MEASURING TOOL	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION BS 887 <u>GENERAL</u> <u>SPECIFICATION - SPECIFICATION</u> BS 887	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TO9"(0-TO-225MM)									
61	DGH112850	DNC S15	021159119996 8 / STEEL PLATE CARBON SIZE 2500X1250X6 MM. **SIZE 2500X1220X6 MM (Only acceptable against demand based LPO).		21 / EACH/N UMBER						TECHNICAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025. STEEL GRADE:5275 JR. ALL INFORMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr GENERAL SPECIFICATION - SPECIFICATION FOR ALL 17 ITEMS: BSEN:10025. STEEL GRADE:5275 JR. ALL INFORMATION AMENDED VIDE CINS LETTER INS/EM-8047/10/3895 DT 24 SEP 2010. 2. bsen-10025 part-2 of 2004 grade: s-275 jr	
62	DGB112352	ME-DIAL- GAU-10	027479274145 6 / DIAL INDICATOR GAUGE FROM 0 TO 10 MM	CHINA,JAPAN, GERMANY,UK MADE	3 / EACH/N UMBER						TECHNICAL SPECIFICATION - Range: 0-10mm Dial Diameter: 52mm Display type: Analogue Sub type: Plunger MAKE/MODEL: UK/USAGENERAL SPECIFICATION - Range: 0-10mm Dial Diameter: 52mm Display type: Analogue Sub type: Plunger MAKE/MODEL: UK/USA	
63	DGB98172		021459013101 0 / BOLT MACHINE HEAD HEXAGON (STEEL BSF MEDIUM CLASS)	BR 320 D/78	425 / EACH/N UMBER						TECHNICAL SPECIFICATION - material standard en-100(945 m38) minimum hardness 250 hb tpi 14 Thread Size 5/8 Inch Nominal Length 2.5 Inch Length of Thread 1.5 Inch tensile strength 10 tons/inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) MATERIAL: STEEL 45 TON/SQ.IN.MTS TENSILE STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC REQUIREDGENERAL SPECIFICATION - material standard en-100(945 m38) minimum hardness 250 hb tpi 14 Thread Size 5/8 Inch Nominal Length 2.5 Inch Length of Thread 1.5 Inch tensile strength 10	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											tons/inch Heat treatment condition R Material Grade EN16 (605 M36) OR EN100 (945 M38) MATERIAL: STEEL 45 TON/SQ.IN.MTS TENSILE STRENGTH OF FASTENER SIZE 5/8 INCHES WITH GRADE R IS 66 TON / INCH2 OEM COC/MTC REQUIRED	
64	DGH109 144	NO DATA AVAILABL E	022359423410 9 / CHAIN MOORING ANCHOR LENGTH 27.4 MTR DIAMETER 20.0MM		3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DGB100 114		027279910879 5 / DRILL TWIST HIGH SPEED STEEL DIA 1-5/16" (1.3125)FLUTE LG		5 / EACH/N UMBER	HSS-GP 10084					TECHNICAL SPECIFICATION - Material: HSS Dia: 1-5/16 Inch Flute Length: 8-5/8 Inch Overall Length: 14-1/4 Inch Point angle: 118 Degree Drill Type: Taper Shank, General Purpose GENERAL SPECIFICATION - Material: HSS Dia: 1-5/16 Inch Flute Length: 8-5/8 Inch Overall Length: 14-1/4 Inch Point angle: 118 Degree Drill Type: Taper Shank, General Purpose	
66	DGE111 973	C1560	033059571325 0 / TWINE HEMP WHITING LINE 40YDS STREND 3 MIN BREAKING 48 LBS, C1559	ALSO KNOWN AS FISHING LINE TO BS 2019	15 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019 GENERAL SPECIFICATION - a. Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019	
67	DGE112 546		033059571325 2 / TWINE NYLON MACKEREL LINE 3 STRD MIN BKG STRENGTH 140 LBS.		29 / EACH/N UMBER						TECHNICAL SPECIFICATION - Dimensions: 3 STRD 2mm x 218 yard BS 6125 OF 1981 TABLE 12 GENERAL SPECIFICATION - Dimensions: 3 STRD 2mm x 218 yard BS 6125 OF 1981 TABLE 12	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
68	DGE112 548	BS2019	033059571325 7 / TWINE HEMP LOG PLAITED BKG 1000 LBS CIRC 1.125		10 / EACH/N UMBER						TECHNICAL SPECIFICATION - BS 6125/1981 GENERAL SPECIFICATION - BS 6125/1981	
69	DGE112 549		033059571325 9 / TWINE NYLON MARLINE 3 STRD POLISHED MIN BKG STRENGTH 280 LBS		10 / KILOGR AMME						TECHNICAL SPECIFICATION - BKG STRENGTH 280 LBS TWINE NYLON MARLINE 3 STRD POLISHED (Dia 1.10 mm) PAKING: Standard available GENERAL SPECIFICATION - BKG STRENGTH 280 LBS TWINE NYLON MARLINE 3 STRD POLISHED (Dia 1.10 mm) PAKING: Standard available	
70	DGE112 553		033059571326 2 / TWINE NYLON ROPING 3 STRD NATURAL FINISH MIN BKG STRGT 50 LB		5 / KILOGR AMME						TECHNICAL SPECIFICATION - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed. GENERAL SPECIFICATION - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed.	
71	DGE110 655	0330-1225	035059923386 8 / FENDER MARINE LENGTH 9.0 INCHES WIDTH 5.0 INCHES		6 / EACH/N UMBER						TECHNICAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT. GENERAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT.	
72	DGE108 864	0330-1225	035059923386 8 / FENDER MARINE		8 / EACH/N UMBER						TECHNICAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH 9.0 INCHES WIDTH 5.0 INCHES								SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT. <u>GENERAL SPECIFICATION</u> - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT.	
73	DGB101 554	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	10 / KILOGR AMME						<u>TECHNICAL SPECIFICATION</u> - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface <u>GENERAL SPECIFICATION</u> - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
74	DGB963 61	BS 2870	028359961098 3 / ROD COPPER RD DIA 1 INCH WT PER FT 3.040 LB	SPEC. BS 2874 C107-O	10 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
75	DGB112 351		026659001603 0 / WASHER FLAT ROUND MILD STEEL 0.625X0. 687X1.375X0. 128IN	O/D 34.925 INCH THK 0.128 INCH SPEC=BS 1769	207 / KILOGR AMME						<u>TECHNICAL SPECIFICATION</u> - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER REQUIREMENT IS REQUIRED Size 5/8 (0.625) Inch Hole Distance= 11/16 (0.6875) Inch Outerside Dia= 13/8 (1.375) Inch Appro Weight per 100=4 Lbs <u>GENERAL SPECIFICATION</u> - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925 MM), THICKNESS 0.128" INCH (3.25	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MM), NO TEMPER REQUIREMENT IS REQUIRED Size 5/8 (0.625) Inch Hole Distance= 11/16 (0.6875) Inch Outsides Dia= 13/8 (1.375) Inch Appro Weight per 100=4 Lbs	
76	DGB111507		026659001603 O / WASHER FLAT ROUND MILD STEEL 0.625X0.687X1.375X0.128IN	O/D 34.925 INCH THK 0.128 INCH SPEC=BS 1769	34 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER REQUIREMENT IS REQUIRED Size 5/8 (0.625) Inch Hole Distance= 11/16 (0.6875) Inch Outsides Dia= 13/8 (1.375) Inch Appro Weight per 100=4 Lbs <u>GENERAL SPECIFICATION -</u> SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER REQUIREMENT IS REQUIRED Size 5/8 (0.625) Inch Hole Distance= 11/16 (0.6875) Inch Outsides Dia= 13/8 (1.375) Inch Appro Weight per 100=4 Lbs	
77	DGB102240	NO DATA AVAILABLE	026359923698 7 / THIMBLE, ROPE STEEL BS 970-EN 3A GALVANISED PEAR SHAPED OPEN TYPE WT 1.75LBS SIZE 1.25	SPEC NO DGS 5031NO.40	400 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Material specification: BS 970/ EN 3A material grade : 070M20. Galvanized thickness: 1.25mm. <u>GENERAL SPECIFICATION -</u> Material specification: BS 970/ EN 3A material grade : 070M20. Galvanized thickness: 1.25mm.	
78	DGB102746	NO DATA AVAILABLE	026359923698 7 / THIMBLE, ROPE STEEL BS 970-EN 3A GALVANISED PEAR SHAPED OPEN TYPE WT 1.75LBS	SPEC NO DGS 5031NO.40	80 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Material specification: BS 970/ EN 3A material grade : 070M20. Galvanized thickness: 1.25mm. <u>GENERAL SPECIFICATION -</u> Material specification: BS 970/ EN 3A material grade : 070M20. Galvanized thickness: 1.25mm.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE 1.25									
79	DGE106 590	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	50 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
80	DGE105 162	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
81	DGE103 325	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	240 / FATHO M						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION</u> - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
82	DGE103 457	NIL	035059923713 5 / ROPE NYLON, HAWSERLAID, 3-STRAND, NOM DIA: 48 MM, TYPE-1	H 41.200 TONS UNIT OF AVAILABILITY 726	240 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/	

S. No	LPR No.	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimensionior
											MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
83	DGE112545		033059571326 6 / TWINE HEMP PACKING MEDIUM 3STRD POLISHE MIN BKG STRGTH 100LB		10 / KILOGR AMME						TECHNICAL SPECIFICATION - (1) 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses. <u>GENERAL SPECIFICATION</u> - (1) 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses.	
84	DGB74593		027179910198 1 / TAP THREAD CUTTING CS BSW B/S16. 0TPI0.375X1. 250X0.294X2. 937"		6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> thread type; iso metric thread m type material grade: (single) SIGH SPEED STEEL(HSS-M2 GRADE) THREAD LENGTH: 18 MM SHANK LENGTH: 50 MM THREAD ANGLE: 600 MAJOR DIAMETER: 10 MM+0.1 MM PITCH DIAMETER: AS PER DEFIND ISO STANDARD THREAD PITCH: 1.5 MM+ 0.05 MM MATERIAL IS TO BE HEAT TREATED TO ACHIEVE HARDNESS LEVEL OF 62-64 HRC. <u>GENERAL SPECIFICATION -</u> thread type; iso metric thread m type material grade: (single) SIGH SPEED STEEL(HSS-M2 GRADE) THREAD LENGTH: 18 MM SHANK LENGTH: 50 MM THREAD ANGLE: 600 MAJOR DIAMETER: 10 MM+0.1 MM PITCH DIAMETER: AS PER DEFIND ISO STANDARD THREAD PITCH: 1.5 MM+ 0.05 MM MATERIAL IS TO BE HEAT TREATED TO ACHIEVE HARDNESS LEVEL OF 62-64 HRC.	
85	DGB105383		025770128378 3 / BOLT MACHINE BRASS BSW HEX HD SZ 1.000X1. 750X4.000 IN		8 / DOZEN						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
86	DGB72878		0273702731395 / AXE HAND 3.5 LBS		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
87	DGB111960	BS 1083	0257704195008 / NUT-PLAIN-HEXAGON-THREAD-SIZE 0.750	BRASS TYPE	4 / DOZEN						TECHNICAL SPECIFICATION - material grade i.e SS347 bs 970, 60r7a GENERAL SPECIFICATION - material grade i.e SS347 bs 970, 60r7a	
88	DGB112504		0258502581203 / COPPER-WIRE-2-MM-DIA		10 / KILOGRAMME						TECHNICAL SPECIFICATION - Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm ² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm ² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER GENERAL SPECIFICATION - Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm ² Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm ² Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER	
89	DGB111963		0258502581203 / COPPER-WIRE-2-MM-DIA		10 / KILOGRAMME						TECHNICAL SPECIFICATION - Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											> 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm2 Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm2 Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER <u>GENERAL SPECIFICATION</u> - Dimension/size: Diameter 2mm Specification: Conductivity > 98% Resistivity 0.047 (@20 C) Elongation > 10% Tensile strength > 180 mpa Purity: As per open source in general marine environment 100% purity of copper required 1. Acceptable diameter variation: 0/-0.04 Cross section: 3.0 mm2 Resistivity Max: 0.01739 Ω x332/m Conductivity Min: 57.5 m/ Ω xmm2 Length related weight: 26.5 kg/1000 m 2. Required minimum copper purity and wire diameter: 99.9 % COPPER PURITY WITH 2MM DIAMETER	
90	DGB105883	NO DATA AVAILABLE	0263590001108 / SCREW BOTTLE FOR AERIAL WT 1.06252 BS		10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
91	DGB111979	NO DATA AVAILABLE	0248591296149 / STEEL SAFE FITTED WITH COMBINATION LOCK	NAL DIMENSIONS: 23-1/2	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - a. Complete Item/ Store DESCRIPTION: Steel Safe fitted with Combination LOCK b. Gauge : Outer 16 SWG Inner 16 SWG c. Size/ dimension: Length/ Height 22 Inch Width 20 Inch Depth 18 Inch d. Door: Single e. No. of shelves: 02 f. No. of Levers: 01 g. Lock Type: Combination + Key/ Digital Lock h. Fire Retardant: Yes <u>GENERAL SPECIFICATION</u> - a. Complete Item/	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Store DESCRIPTION: Steel Safe fitted with Combination LOCK b. Gauge : Outer 16 SWG Inner 16 SWG c. Size/ dimension: Length/ Height 22 Inch Width 20 Inch Depth 18 Inch d. Door: Single e. No. of shelves: 02 f. No. of Levers: 01 g. Lock Type: Combination + Key/ Digital Lock h. Fire Retardant: Yes	
92	DGB109 098	0700 605 378	025176437195 8 / ELECTRODE HOLDER (MUREX HANDICOOL)	IN AIR INCLUDING SPRING MADE JAPAN/TAIWA	19 / EACH/NUMBER						TECHNICAL SPECIFICATION - DESCRIPTION: ELECTRODE HOLDER HANDICOOL 600A, COPPER JAWS, FULLY INSULATED, APPROVED TO EN-60974-11. GENERAL SPECIFICATION - DESCRIPTION: ELECTRODE HOLDER HANDICOOL 600A, COPPER JAWS, FULLY INSULATED, APPROVED TO EN-60974-11.	
93	DGB111 983	Material Grade EN 4140	025770941150 6 / NUT-PLAIN-HEXAGON-THREAD-SIZE. 625LH.550"		32 / DOZEN						TECHNICAL SPECIFICATION - material specs AISI 4140(PD 970: 2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED) GENERAL SPECIFICATION - material specs AISI 4140(PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
94	DGB108 539		021259571100 3 / STEEL-ROUND-CARBON-REFORGING-DIA-178MM		150 / KILOGRAMME						TECHNICAL SPECIFICATION - Dia: 178mm (7 inch) Length: 1 meter (at least) GENERAL SPECIFICATION - Dia: 178mm (7 inch) Length: 1 meter (at least)	
95	DGB108 538	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25"	NIL	100 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 μ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGHT: 06 MTR								BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
96	DGB108 802	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	129 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
97	DGB108 713	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	120 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	
98	DGB112 568	NIL	026759521327 9 / PIPING STEEL GALVANIZED (SEAMLESS) EXTERNAL Dia:1.688" wALL/thckness: 0.128" N/BORE:1.25" LENGHT: 06 MTR	NIL	200 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION : BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR GENERAL SPECIFICATION - BSEN 10216-2 : 2019 GRADE:P265 GH SPECS FOR GALVANIZATION :BSEN ISO 10240 BS EN ISO 10240 GALVANIZATION THICKNESS; 55 µ UM INSIDE AND OUTSIDE OF PIPE LENGHT: 06 MTR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MTR	
99	DGB108547	NO DATA AVAILABLE	0212595710623 / LATHE MACHINE CUTTING TOOL STEEL HIGH SPEED SQ HOT ROLLED	LATHE MACHINE	5 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Material: steel high speed square' hot rolled dimension : 3/4" x 3/4"x "6. <u>GENERAL SPECIFICATION</u> - Material: steel high speed square' hot rolled dimension : 3/4" x 3/4"x "6.	
100	DGB112133		1325723350010 / BLADE POWER HACK SAW HSS 18X1-1/2X0.075" 6TPI		14 / EACH/NUMBER	AISI M2 HSS (Super Hardened)					<u>TECHNICAL SPECIFICATION</u> - 450 x 38 x 2 (mm) 18 x 1 1/2 x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened) <u>GENERAL SPECIFICATION</u> - 450 x 38 x 2 (mm) 18 x 1 1/2 x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened)	
101	DGE109095	NO DATA AVAILABLE	0472595237744 / Life Bouy Ring (Orange) with SOLAS Reflective Tape	FOR SHIPS/BOATS	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM – Internal dia 44.5 CM Thickness 11.5CM Buoyancy Rating:181N. <u>GENERAL SPECIFICATION</u> - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM – Internal dia 44.5 CM Thickness 11.5 CM Buoyancy Rating:181N.	
102	SGP112920		0462599432395 / PAPER WRAPING WATER PROOF WD. 36"LG.100YD PER ROL 2PLY INTO 1		1400 / METER						<u>TECHNICAL SPECIFICATION</u> - a. GSM: 100-120 b. Width: 01 meter c. Length: 100 meter per roll d. Colour: Brown <u>GENERAL SPECIFICATION</u> - a. GSM: 100-120 b. Width: 01 meter c. Length: 100 meter per roll d. Colour: Brown	
103	DGE112999		4220505101929 / LIFE JACKETS (Orange/Camo uflage)	FOR PERSONNAL SAFETY,PNS QASIM,PRIZE ENT	68 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - (1) Buoyancy: 7.5kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											attached DRAWING NO TD-1688/2003 <u>GENERAL SPECIFICATION</u> - (1) Buoyancy: 7.5 kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003	
104	DGE112554	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		1200 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014. <u>GENERAL SPECIFICATION</u> - TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014.	
105	DGE111908	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		1000 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014. <u>GENERAL SPECIFICATION -</u> TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014.	
106	DGE99283		402099923713 7 / ROPE NYLON HAWSERLAID, 3-STRND, Z- LAY, TYPE-1, NOM DIA: 64- MM, CIRC: 08- INCH,	NOR-SHIPS- USE-NASAR	120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1.</u> 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CALIBRATION CERTIFICATE WILL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
107	DGE112146	NO DATA AVAILABLE	4220795055193 / WHISTLE PLASTIC FOR GENERAL SERVICE LIFE JACKET	LIFE JACKET MK-1, ORALLY INFLATED	15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
108	DGB111698	CH50-10	4030705039310 / CHAIN BLOCK 5TON CAPACITY WITH 45 FEET DRIFT LINE DIA 9MM-	FOR GENERAL PURPOSE-	1 / EACH/NUMBER	CH50-10					TECHNICAL SPECIFICATION - Make: ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 Inch Weight: 84 LBS Type: Manual Acceptance CRITERIA : lifting OF 5 Tons Load GENERAL SPECIFICATION - Make: ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 Inch Weight: 84 LBS Type: Manual Acceptance CRITERIA : lifting OF 5 Tons Load	
109	DGB79447		5120731000583 / SPANNER D/END OPENJAW 6-32MM 12 PCS SET		3 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DGE98120		5330002440192 / SHEET RUBBER SOLID 0.125 X24X324 INCH		80 / FOOT						TECHNICAL SPECIFICATION - MILR900 GENERAL SPECIFICATION - MILR900	
111	DGH99066	REPR0V3268B	5660992003094 / BARBED WIRE STEEL ZINC COATED		700 / KILOGRAMME	Concertina Razor Wire					TECHNICAL SPECIFICATION - 1. Coil outside diameter should be minimum 450 mm. 2. Barbed length minimum 10 mm. 3. Wire gauge 2.5	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			4 POINTS								mm. 4. Razor barbed type is cross. 5. Material is galvanized iron wire. 6. Barbed distance is to be minimum 26 mm. 7. Blade thickness is minimum 0.4 mm. 8. Blade width is minimum 15 mm. <u>GENERAL SPECIFICATION</u> - 1. Coil outside diameter should be minimum 450 mm. 2. Barbed length minimum 10 mm. 3. Wire gauge 2.5 mm. 4. Razor barbed type is cross. 5. Material is galvanized iron wire. 6. Barbed distance is to be minimum 26 mm. 7. Blade thickness is minimum 0.4 mm. 8. Blade width is minimum 15 mm.	
112	DGE112124	9-27052	6260010744230 / LIGHT CHEMILUMINESC		742 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
113	DGE113030	SA9-27054PF.	6260011785559 / LIGHT, CHEMILUMINESCENT 6inch RED		327 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
114	DGE110902	SA9-27077PF.	6260011785560 / LIGHT, CHEMILUMINESCENT 6inch BLUE	REPLENISHMENT LIGHT	30 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
115	DGB111601	NO DATA AVAILABLE	0246500001066 / BLOCK CHAIN 5 TON 10METER (ORIGINAL MANUFACTURE LENGTH)		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - Make: Elephant Chain Block Co. Ltd. Japan. Model: Manually operated chain Hoist Model C21. <u>GENERAL SPECIFICATION</u> - Make: Elephant Chain Block Co. Ltd. Japan. Model: Manually operated chain Hoist Model C21.	
116	DGE107790	DATA AVAILABLE	0461500000152 / POLISHING-FELT ROUND		8 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material : off white/white or grey sheep's wool Detailed Specification Diameter = 10	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Inch Thickness = 1.5 Inch <u>GENERAL SPECIFICATION</u> - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch	
117	DGE112 137	NO DATA AVAILABL E	041578000009 3 / JARY CANE, 729 MS, CAPACITY.		60 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - daimention: 14" x 6" x 18" capacity: 10 ltrs <u>GENERAL SPECIFICATION</u> - daimention: 14" x 6" x 18" capacity: 10 ltrs	
118	SGE112 926	NO DATA AVAILABL E	046150000008 6 / GOGGLE CHIPPING		615 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band. <u>GENERAL SPECIFICATION</u> - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors.Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.	
119	DGE112 230	NO DATA AVAILABL E	046150000008 6 / GOGGLE CHIPPING		89 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band. GENERAL SPECIFICATION - Concurrence to CSA Resistance to fogging for Resistance to fogging for use outdoors. Medium Energy Impact: Resists a 6mm; 0.86g at 120 m/s. Resistance to surface damage by fine particles. Liquid droplet protection. Protection against large dust particles at >5 microns Large enough to fit over prescription glasses. Shields the user against gas and fine dust particles of 5 microns in size. Resistant to molten metal and hot solids. Should be suitable for use around high speed particles at extreme temperatures One-size-fits - most along with fire- resistant head band.	
120	DGE112 709	-	834070508791 6 / TENT MARQUEE UNIVERSAL G. S (SIZE 27X19.	GENERAL PURPOSE	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 27 X 19.6 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			6FT) FOLD & FLY TWO (J/GREEN)								HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF, FIRE PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM b. IRON PEGS: QTY 24 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. WALL PIPE (LATHI): QTY 24 NOS OF MATERIAL: MS (MILD STEEL), LENGTH 06 FEET, THICKNESS 25 MM. d. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/ COTTON, DIA MINIMUM 16 MM. e. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. f. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. GROUND SHEET FIREPROOF 200 GSM. 4. VENTILATION FEATURE: WINDOW: 06 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION</u> - 1. SIZE/ DIMENSION a. TENT SIZE (LENGTH & WIDTH): 27 X 19.6 FEET (± 3 INCH) b. HEIGHT OF TENT: 12 FEET (± 2 INCH) c. HEIGHT OF WALL: 06 FEET (± 2 INCH) 2. OTHER SPECIFICATIONS a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 650 GSM OR ABOVE WITH ROT-PROOF, FIRE PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTHI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 03 NOS (01 x RIDGE POLES, LENGTH 07 FEET & 02 x STANDING POLES, LENGTH 12 FEET WITH JOINTED MALE/ FEMALE). MATERIAL: MS (MILD STEEL), OUTER DIA 50 MM ±02 MM & THICKNESS 02 MM ±0.50 MM b. IRON PEGS: QTY 24 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ±2 MM AND MILD STEEL PIN QTY 24 NOS, LENGTH 06 INCHES. c. WALL PIPE (LATHI): QTY 24 NOS OF MATERIAL: MS (MILD STEEL), LENGTH 06 FEET,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											THICKNESS 25 MM. d. ROPE: QTY: 48 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/ COTTON, DIA MINIMUM 16 MM. e. HAMMER: QTY 02 NOS, MATERIAL: MS (MILD STEEL), WEIGHT 05 KGS WITH WOODEN HANDLE LENGTH 1.5 FEET. f. FLAPPER FOR GROUND= MATERIAL: POLYPROPYLENE, 180-200 GSM. GROUND SHEET FIREPROOF 200 GSM. 4. VENTILATION FEATURE: WINDOW: 06 (SIZE: 2 x 2 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 03 NOS BAGS MADE OF CANVAS COTTON (475 GSM), 02 x BAGS FOR TENT BODY AND 01 x FOR ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION.	
121	DGE112729	NO DATA AVAILABLE	8340505039260 / TENT 180 LBS MILITARY PATTERN MK-4 WITH ALL ACCESSORIES (COMPLETE SET)		5 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. LENGTH: 14 FEET (± 2 INCH) b. WIDTH: 14 FEET (± 2 INCH) c. CENTRAL HEIGHT: 07 FEET (± 2 INCH) 2. OTHER SPECIFICATION a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b. MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ACCESSORIES a. IRON POLES: TOTAL QTY 05 NOS (02 x RIDGE POLES, LENGTH 07 FEET AND 03 x STANDING POLES, LENGTH: 07- FEET). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ± 02 MM & THICKNESS: 02 MM ± 0.50 MM. b. IRON PEGS: QTY 22 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2-MM AND MILD STEEL PIN QTY 12 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 22 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON & DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 03 KGS, WITH WOODEN HANDLE & LENGTH 1.5 FEET. e. FLAPPER FOR GROUND: MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 1.5 x 1.5 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 02 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 01 x BAG FOR THE TENT AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>GENERAL SPECIFICATION - 1.</u> SIZE/DIMENSION a. LENGTH: 14 FEET (± 2 INCH) b. WIDTH: 14 FEET (± 2 INCH) c. CENTRAL HEIGHT: 07 FEET (± 2 INCH) 2. OTHER SPECIFICATION a. 100% CANVAS COTTON: DOUBLE FLY WITH SINGLE FOLD (OUTER FLY WITH SINGLE FOLD & INNER FLY WITH DOUBLE FOLD). b.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIAL: 475 GSM OR ABOVE WITH ROT-PROOF AND WATERPROOF. c. COLOR FOR OUTER/ INNER FLY: JUNGLE GREEN (COLOR CODE: 3A5F31). d. INNER LINING: MATERIAL: DOSUTI CLOTH, 180-200 GSM, COLOR: PLAIN PARROT GREEN. 3. LIST OF ACCESSORIES a. IRON POLES: TOTAL QTY 05 NOS (02 x RIDGE POLES, LENGTH 07 FEET AND 03 x STANDING POLES, LENGTH: 07- FEET). MATERIAL: MS (MILD STEEL), OUTER DIA: 50 MM ± 02 MM & THICKNESS: 02 MM ± 0.50 MM. b. IRON PEGS: QTY 22 NOS, LENGTH 18 INCHES, THICKNESS 20 MM ± 2-MM AND MILD STEEL PIN QTY 12 NOS, LENGTH 06 INCHES. c. ROPE: QTY: 22 NOS MINIMUM OR AS RECOMMENDED BY MANUFACTURER, MATERIAL: NYLON/COTTON & DIA MINIMUM 16 MM. d. HAMMER: QTY 01 NO, MATERIAL: MS (MILD STEEL), WEIGHT 03 KGS, WITH WOODEN HANDLE & LENGTH 1.5 FEET. e. FLAPPER FOR GROUND: MATERIAL: POLYPROPYLENE, 180-200 GSM. 4. VENTILATION FEATURE: WINDOW: 02 (SIZE: 1.5 x 1.5 FEET) WITH MOSQUITO NETTING FOR AIRFLOW AND DOOR 02 REQUIRED ON BOTH SIDES OF THE TENT. 5. PACKING REQUIRED: QTY 02 TOTAL BAGS MADE OF CANVAS COTTON (475 GSM), 01 x BAG FOR THE TENT AND 01 x FOR THE ACCESSORIES. 6. ADVANCE SAMPLE TO BE APPROVED BY CINS/ SPECIALIST END USER PRIOR TO BULK PRODUCTION. <u>TECHNICAL SPECIFICATION - FOLD & FLY TWO COLOUR</u>	
122	DGE112 689		834070508791 7 / TENT	O/T FLY MADE OF	1 / EACH/N							

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BIVOUAC MOSQUITO PROOF SIZE 10.6X6 FT	COTT/CNVAS OLIVE GREEN	UMBER						JUNGLE GREEN / OLIVE GREEN OUTER FLY MADE OF COTTON CANVAS MOSQUITO NETTING COVER EACH END water proof (Inner Mosquito Net Fabrics) Accessories: Pole 7' standing 02 Pole 5' width 02 Nail 1' standing 10 Cotton rope 6'side 08 Cotton rope 10' front & back 02 <u>GENERAL SPECIFICATION - FOLD & FLY</u> TWO COLOUR JUNGLE GREEN / OLIVE GREEN OUTER FLY MADE OF COTTON CANVAS MOSQUITO NETTING COVER EACH END water proof (Inner Mosquito Net Fabrics) Accessories: Pole 7' standing 02 Pole 5' width 02 Nail 1' standing 10 Cotton rope 6'side 08 Cotton rope 10' front & back 02.	
123	DGT112368	NO DATA AVAILAB L E	010050000001 8 / Ply Wood GD-I, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATI ON.IM-2581 (E)	540 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH: 8- FEET, WIDTH: 4 FEET, THICKNESS: 12 MM 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 9. DENSITY REQUIREMENT= 550-750 PER CUBIC METER, <u>GENERAL SPECIFICATION -</u> SIZE: LENGTH: 8- FEET, WIDTH: 4 FEET, THICKNESS: 12 MM 1. BS-6566 OF 1985. PART 1-8. TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 2001, 6.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 9. DENSITY REQUIREMENT= 550-750 PER CUBIC METER,	
124	DGT112366	NO DATA AVAILABLE	0100500000015 / PLY WOOD GRADE-1, 5 PLY		736 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM($\pm$1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS EN 635 (PART 1, 2 & 3), 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) <u>GENERAL</u> <u>TECHNICAL SPECIFICATION</u> - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM($\pm$1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS EN 635 (PART 1, 2 & 3), 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
125	DGT109408	NO DATA AVAILABLE	0100500000015 / PLY WOOD GRADE-1, 5 PLY		32 / SQ FEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM($\pm$1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS EN 635 (PART 1, 2 & 3), 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC) <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 2001 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS EN 635 (PART 1, 2 & 3), 6. DENSITY: BS EN 323 : 1993 (550-750 KILOGRAM PER CUBIC)	
126	DGE110746	NO DATA AVAILABLE	045150000011 / MATTRESS FOAM LIGHT WEIGHT 72X36X4		25 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DGE113049	NO DATA AVAILABLE	8415PK506744 2 / CLOTH PARASHUTE GRAY		500 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
128	DGE111155	NO DATA AVAILABLE	8415PK506744 2 / CLOTH PARASHUTE GRAY		500 / METER						TECHNICAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery	
129	SGT112928	NO DATA AVAILABLE	041550000000 9 / FORMICA ENGRAVING WHITE FACE BLACK CORE (1220MMX1220MMX1.57MM		40 / SHEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness. GENERAL SPECIFICATION - 1220 mm x1220 mm x1.57 mm, tolerance of +/- 0.01 mm may in thickness.	
130	DGE113021	NO DATA AVAILABLE	045150000001 6 / TAPE-WHITE-COTTON		113 / YARD	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
131	DGE112 172	NO DATA AVAILABLE	733070100228 9 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDUS/JOY0).		25 / EACH/NUMBER						TECHNICAL SPECIFICATION - WITH FULLCOVER GENERAL SPECIFICATION - WITH FULLCOVER	
132	DGE112 023	NO DATA AVAILABLE	933070505435 4 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PN CREST	9 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
133	DGE112 998	NIL	934073100099 5 / E-GLASS FIBER (POWDER) CHOPPED STRAND MAT	GRP BOATS	366 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. DEF STAN-2-166/2 GEN, 2. WIDTH= 1,860 MM, 3. NET WEIGHT= 54 KG, 4. WEIGHT PER UNIT= 450 g/m ² (±10%). 5. A LABORATORY TEST REPORT/ CERTIFICATE IN ACCORDANCE WITH SPECIFICATIONS I.E DEF 2-166 ISSUED-2 TABLE E.1 AND E.2 OF ANNEX E, W.R.T PHYSICAL AND MECHANICAL PROPERTIES, ISSUED BY A THIRD PARTY LABORATORY (E.G SGS OR EQUIVALENT) FOR VERIFICATION OF COMPLIANCE IS REQUIRED. GENERAL SPECIFICATION - 1. DEF STAN-2-166/2 GEN, 2. WIDTH= 1,860 MM, 3. NET WEIGHT= 54 KG, 4. WEIGHT PER UNIT= 450 g/m ² (±10%). 5. A LABORATORY TEST REPORT/ CERTIFICATE IN ACCORDANCE WITH SPECIFICATIONS I.E DEF 2-166 ISSUED-2 TABLE E.1 AND E.2 OF ANNEX E, W.R.T PHYSICAL AND MECHANICAL PROPERTIES, ISSUED BY A THIRD PARTY LABORATORY (E.G SGS OR EQUIVALENT) FOR VERIFICATION OF COMPLIANCE IS REQUIRED.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO.	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
134	DGD109631		773070504806 5 / BOWL SALAD 23CM 06 OZ GOLDEN CRESTED		2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> 23CM 06 OZ GOLDEN CRESTED , MATERIAL PORCELAIN FOOD, GRADE CERA-E-NOOR (LOCAL) <u>GENERAL SPECIFICATION -</u> 23CM 06 OZ GOLDEN CRESTED , MATERIAL PORCELAIN FOOD, GRADE CERA-E-NOOR (LOCAL)	
135	DGB111663	NO DATA AVAILABL E	711070503606 7 / SAFE STEEL WITH KEYS AND COMB LOCK OF C/B 18" X18"X17"TH 1/8"	FOR GENERAL PERPOSE	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less than 3/8" d. No of levers: Minimum 02 <u>GENERAL SPECIFICATION -</u> Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less than 3/8" d. No of levers: Minimum 02	
136	DGB111967	NO DATA AVAILABL E	711070503606 7 / SAFE STEEL WITH KEYS AND COMB LOCK OF C/B 18" X18"X17"TH 1/8"	FOR GENERAL PERPOSE	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less than 3/8" d. No of levers: Minimum 02 <u>GENERAL SPECIFICATION -</u> Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less than 3/8" d. No of levers: Minimum 02	
137	DGD109629		734070510187 4 / Cruets Complete Small	MESS UTENSILS, OFFICER WARD PNS SHIFA	3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> As per existing Stock, Make/Brand is Regal China with Blue Shell & PN Crest embossed on item <u>GENERAL</u> <u>SPECIFICATION -</u> As per existing Stock, Make/Brand is Regal China with Blue Shell & PN Crest embossed on item	
138	DGD109639	NO DATA AVAILABL E	003550000027 4 / BOARD KNIFE		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952 <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - size; 10" material; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952	
139	DGD109 634		003454600043 4 / DISHES VEGETABLE ROUND E W W O COVER B/C		3 / EACH/N UMBER	cera-e- noor					TECHNICAL SPECIFICATION - dia; 6" material; porcelain blue crested with pn logo GENERAL SPECIFICATION - dia; 6" material; porcelain blue crested with pn logo	
140	DGD109 640	NO DATA AVAILABL E	003550000036 6 / KNIFE COOK 6 INCH		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Blade Length = 6 inch Total Length = 11-11.5 inch Blade Material = SS 420 Handle = Full Steel Thickness = 2.2 mm Weight = 140-160 g Finish = Mirror Polish, plain Usage = Kitchen/ Commercial GENERAL SPECIFICATION - Blade Length = 6 inch Total Length = 11-11.5 inch Blade Material = SS 420 Handle = Full Steel Thickness = 2.2 mm Weight = 140-160 g Finish = Mirror Polish, plain Usage = Kitchen/ Commercial	
141	DGE111 903	1-401- 47845	830599125222 3 / COTTON CLOTH		60 / KILOGR AMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 100 % Cotton 1 x 1 Feet 100 % Cotton 1 x 1 Feet Lint Free GENERAL SPECIFICATION - 100 % Cotton 1 x 1 Feet Lint Free	
142	DGE981 23		047654600477 6 / BRUSH SABLE HAIR NO-3 FOR WRITING		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
143	DGE112 123	565665	534070524611 1 / leatherite for wallpaper		300 / SQ FEET	565665					TECHNICAL SPECIFICATION - leatherite wallpaper sheets GENERAL SPECIFICATION - leatherite wallpaper sheets	
144	DGB105 500	B 34	204079527084 7 / 22 X 26 US FEDERAL SPECIFICATIO N DEE SHACKLE		4 / EACH/N UMBER	B 34					TECHNICAL SPECIFICATION - 22 X 26 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD: 13 TON GENERAL SPECIFICATION - 22 X 26 US FEDERAL SPECIFICATION DEE SHACKLE TENSILE PROOF LOAD:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											13 TON	
145	DGE64931	CTLCB10008025	5340735267410 / CANTILEVER BRACKET 3' (1000 X 80 X 2.5MM)		72 / EACH/NUMBER	CANTILEVER BARACKET 3' CTLCB10008025					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
146	DGB105499	IDENTIFICATION MARK: 16	5325795267889 / 28 x 32 us FEDERAL dee shackle		17 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - 28 X 32 US FEDERAL SPECIFICATION D SHACKLE, proof load 189.3 kn (19.0 ton) GENERAL SPECIFICATION - 28 X 32 US FEDERAL SPECIFICATION D SHACKLE, proof load 189.3 kn (19.0 ton)	
147	DGB113212	NO DATA AVAILABLE	5660705148476 / CONCERTINA WIRE BLADE SIZE: 22MML, 14MMW THICKNESS: 0.5MM	FOR BOUNDARY PROTECTION	25 / ROLL			SOURCE OF AVAILIBTY: PAKISTAN WIRE SITE AREA KARACHI .Mr WASEEM CONTRACT NO 0333-2112465.		PAKISTAN WIRE	TECHNICAL SPECIFICATION - BLADE SIZE: 22MML, 14MMW BLADE THICKNESS: 0.5MM LINE WIRE: 2.6/3MM 10-12 GAUGE SIZE: 36INCH DIA MATERIAL: (MILD STEEL&GALVANIZEDWEIGHT / ROLL: 25 KG PER ROLL COUNTRY OF ORIGIN PAKISTAN GENERAL SPECIFICATION - BLADE SIZE: 22MML, 14MMW BLADE THICKNESS: 0.5MM LINE WIRE: 2.6 /3MM 10-12 GAUGE SIZE: 36INCH DIA MATERIAL: (MILD STEEL&GALVANIZEDWEIGHT / ROLL: 25 KG PER ROLL COUNTRY OF ORIGIN PAKISTAN	
148	DGE79864	havana	7110705247541 / master havana high back chair		3 / EACH/NUMBER	NIL					TECHNICAL SPECIFICATION - BACK: 24" ARM: 27 SEAT: 21.5" HEIGHT: 20" BACK HEIGHT: 47" A. CHROME BASE B. CHROME ARMS GENERAL SPECIFICATION - BACK: 24" ARM: 27 SEAT: 21.5" HEIGHT: 20" BACK HEIGHT: 47" A. CHROME BASE B. CHROME ARMS	
149	DGE110873	LOCAL MADE	042270516014	JAI NAMAZ SUF	15 / FOOT			LOCAL SOURCE: BOLTON MARKET KARACHI.		LOCAL SOURCE:	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			7 / CARPET RUNNER JAI NAMAZ						BOLTON MARKET KARACHI		LOCAL SOURCE: BOLTON MARKET KARACHI. Carpet Runner Jai Namaz (authorized quantity 200 running feet) 01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand. <u>GENERAL SPECIFICATION - LOCAL SOURCE: BOLTON MARKET KARACHI.</u> Carpet Runner Jai Namaz (authorized quantity 200 running feet) 01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand.	
150	DGD110 047	NO DATA AVAILAB L E	003350000020 6 / Tumbler Glass for Drinking Water		10 / EACH/N UMBER	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION -</u> Material: Glass (Crystal Clear) Capacity: 280/300 ml Brand: Toya Nasic / Nova (LOCAL) <u>GENERAL SPECIFICATION -</u> Material: Glass (Crystal Clear) Capacity: 280/300 ml Brand: Toya Nasic / Nova (LOCAL)	
151	DGT109 913	NO DATA AVAILAB L E	010050000002 1 / Ply wood GD-II, 3 ply (core and inner plies of Popular SIZE: L=8' W=4' TH=03MM		300 / SQ FEET	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION -</u> DESCRIPTION/ SIZES Ply wood GD-II, 3 ply (core and inner plies of Popular and both face and back veneer of Mersawa (0.6MM) type of bond INT (phenolic/ aminoplastic), treated with preservative. Size: L = 8' W = 4' Th = 03 MM BS EN 322 : 1993 2. Bonding Quality: 1. BS 314-1	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											: 2004 2. BS EN 314-2: 1993 3. Glue: BS 1203 : 1979 4. Preservation: BS 4072 : 1999 5. Physical evaluation: BS 6566-6 : 1985 6. Density: BS EN 323 : 1993 <u>GENERAL SPECIFICATION - DESCRIPTION/ SIZES</u> Ply wood GD-II, 3 ply (core and inner plies of Popular and both face and back veneer of Mersawa (0.6MM) type of bond INT (phenolic/ aminoplastic), treated with preservative. Size: L = 8? W = 4? Th = 03 MM BS EN 322 : 1993 2. Bonding Quality: 1. BS 314-1 : 2004 2. BS EN 314-2: 1993 3. Glue: BS 1203 : 1979 4. Preservation: BS 4072 : 1999 5. Physical evaluation: BS 6566-6 : 1985 6. Density: BS EN 323 : 1993	
152	DGE110 876	MIL-P-15280	564000237482 7 / INSULATION SLEEVING THERMAL		165 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - mil-p-15280</u> Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM. <u>GENERAL SPECIFICATION - mil-p-15280</u> Sleeve Sizes: LENGTH: 72-INCHES NOMINAL, INNER DIA: 2.625 INCHES NOMINAL, INSULATION Thickness: 0.750 INCHES NOMINAL, COLOR: BLACK, DESIGN FORM: FULL ROUND, SUPPLEMENTARY FEATURES: EXPANDED UNICELLULAR PLASTIC FOAM.	
153	DGE110 881	NIL	533070505816 9 / INSULATION MATERIAL FOAM TYPE SUPERLON.	FOR AIR CONDITION	135 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS
			SIZE= 3/8 X 1-1/16 X 72 INCH								
154	DGE111278	nil	533000038292 2 / PACKING-MATERIAL	FUEL OIL SERVICE PMP	100 / METER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NI ASBESTOS, TEM UPTO: 400 °C <u>GENERAL SPECIFICATION -</u> SPECIFICATION: CROSS SECTIONAL SHAPE SQUARE, SIZE: 0.250 INCH, MATERIAL: NI ASBESTOS, TEM UPTO: 400 °C
155	DGE99002		533000618322 1 / PACKING MATERIAL SIZE 3/16".		10 / FOOT						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE
156	DGB113299	MAKITA 9556NB	513076501638 1 / ELECTRIC ANGLE GRINDER DISC TYPE I/P 840W, 11000RPM, LG 271MM		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: DEPRESSED CENTER WHEEL: 100MM(4"), W CUP BRUSH: 75MM(3"), ABRASI DISC: 100MM(4"), DIAMOND WHEEL: 100MM (4"), INPUT: 840 NO LOAD SPEED: 11,000 RPM, OVERLENGTH: 271MM (10-5/8") NET WEIGHT: 1.6KG (3.5 LBS), POWER SUPPLY CORD: 2.5M (8 FT) <u>GENERAL SPECIFICATION -</u> SPECIFICATION: DEPRESSED CENTER WHEEL: 100MM(4"), W CUP BRUSH: 75MM(3"), ABRASI DISC: 100MM(4"), DIAMOND WHEEL: 100MM (4"), INPUT: 840 NO LOAD SPEED: 11,000 RPM, OVERLENGTH: 271MM (10-5/8") NET WEIGHT: 1.6KG (3.5 LBS), POWER SUPPLY CORD: 2.5M (8 FT)
157	DGH106481		056159521849 2 / CABLE, power, ELECT ELASTOMER C LFH , 3 cores, cond276/0.40 440 v, 160		100 / METER						<u>TECHNICAL SPECIFICATION -</u> 3 CORES, COND276/0.40 440 V, 1 AMP, 100 LG. DEFSTAN 02-526 <u>GENERAL SPECIFICATION -</u> 3 CORES, COND276/0.40 440 V, 1 AMP, 100 LG. DEFSTAN 02-526

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			amp, 100 lg.									
158	DGE106 973		033059571326 6 / TWINE HEMP PACKING MEDIUM 3STRD POLISHE MIN BKG STRGTH 100LB		30 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - (1)</u> 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses. <u>GENERAL SPECIFICATION - (1)</u> 3 strand twin hemp packing medium and material consist of natural jute or hemp fibers. (2) Structure of 3 strands twisted or plied together. (3) Diameter of Twin Hemp is common size include 2mm (0.08 inches) and 3mm (0.12 inches), with some products reaching 4mm or more. (4) Length of Twin Hemp is 328 feet (100 Meter). (5) Color of Twin Hemp is typically a natural, brown, or green. (6) Properties of Twin Hemp are strong enough for bundling and binding, does not damage item being tied or held, Eco friendly and compostable and chemical free from harmful substances & making it safe for various uses.	
159	DGE109 665		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN		4 / SHEET						<u>TECHNICAL SPECIFICATION -</u> Manfr/Tech.Sponcer Code reference: DTD 5592 <u>GENERAL SPECIFICATION -</u> Manfr/Tech. Sponcer Code reference: DTD 5592	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TRANSPARENT L X W X THIC 48"X48"X0.250"									
160	DGE103451	NO DATA AVAILABLE	0432500000027 / HELMET PROTECTIVE DESPATCH RIDER WITH VISOR SIZE 6 3/4		10 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - Item</u> Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218) <u>GENERAL SPECIFICATION - Item</u> Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218)	
161	DGE109910	CM6538-000	5970705044352 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		31 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Material System:</u> Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes <u>GENERAL SPECIFICATION - Material System:</u> Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
162	DGE110471	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOUFLAGE THE 14.5MM GUNS	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. <u>GENERAL SPECIFICATION - 1.</u> SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
163	DGE111062	NO DATA AVAILAB LE	424050508870 5/ CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMO FLAGE THE 14.5MM GUNS	2/ EACH/N UMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
164	DGD106922	NO DATA AVAILABLE	0032500000119 / BASIN SUGAR STAINLESS STEEL		4 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
165	DGE107675		046279125518 8 / TUBING PLASTICS POLYETHYLENE (LOW DENSITY) FLIM LAY FLAT		15 / KILOGRAMME						TECHNICAL SPECIFICATION - DEFSTAN = 93-116/2 OF 2007 THICKNESS=.0.005" (Double Side) WIDTH = 24". WEIGHT OF ROLL = 48 LBS (APPROX 21.77 KG) LENGTH PER ROLL= 500 FT TYPE = 1 ADVANCE SAMPLE TO BE APPROVED BY CINS GENERAL SPECIFICATION - DEFSTAN = 93-116/2 OF 2007 THICKNESS=.0.005" (Double Side) WIDTH = 24". WEIGHT OF ROLL = 48 LBS (APPROX 21.77 KG) LENGTH PER ROLL= 500 FT TYPE = 1 ADVANCE SAMPLE TO BE APPROVED BY CINS	
166	DGB102163	NO DATA AVAILABLE	026850000006 1 / SCALE- SPRING- BALANCE-20- STONE-280- LBS		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Capacity :Maximum Usage/ Application : To hang load Material : Steel GENERAL SPECIFICATION - Capacity :Maximum Usage/ Application : To hang load Material : Steel	
167	DGB106751	SPEC BSS 2874 CZ 112 M	028370571144 9 / ROD NAVAL BRASS RD DIA 1.25" WT PER FT 4.58LB		20 / METER						TECHNICAL SPECIFICATION - sPECIFICATION:BSEN/2/63 OF 1998 MATERIAL gRADE: CW712R GENERAL SPECIFICATION - sPECIFICATION: BSEN/2/63 OF 1998 MATERIAL gRADE: CW712R	
168	DGD110045		003154600024 2 / CUPS TEA GOLDEN CRESTED		12 / EACH/NUMBER	CERA-A-NOOR					TECHNICAL SPECIFICATION - MESS TRAPS ITEM MADE IN PAKISTAN LOCAL MADE BY OEM: CERA-A-NOOR SIZE: STANDARD GENERAL SPECIFICATION - MESS TRAPS ITEM MADE IN PAKISTAN LOCAL MADE BY OEM: CERA-A-NOOR SIZE: STANDARD	
169	DGB106748	BS-1471-NT4	028259571197 6 / TUBE, ALUMINIUM ALLOY,EXT DIA 2"TH 0.060"W WDG 60		30 / METER						TECHNICAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades) GENERAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SPE BS 1471									
170	DGD110 048		003250003201 7 / SPOON SALT FOR OCNS		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Size: 2.5 to 3 ml Color: Silverware Length: 6.7" Diameter: 1.1" Width: 1" Made with stainless steel Material S/S 304/316 FOOD GRADE NON Magnetic (LOCAL) size and material grade: ss 304/316 (food grade) <u>GENERAL SPECIFICATION -</u> Size: 2.5 to 3 ml Color: Silverware Length: 6.7" Diameter: 1.1" Width: 1" Made with stainless steel Material S/S 304/316 FOOD GRADE NON Magnetic (LOCAL) size and material grade: ss 304/316 (food grade)	

INVITATION TO TENDER VSD I.T DATE 21-10-2026

The following item is required against local purchase. Suppliers are requested to quote by 11-11-2026 before 10:00 AM. Quotations are to be deposited in the quotation box.

<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 155/2026 DATED 07-10-2026 WHOLE DAY MREs	750 Pkt	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED


M DANIYAL KHAN
Lt Cdr/Pakistan Navy
GO LP VSD
Date: _____

INVITATION TO TENDER VSD I.T DATE 21-10-2026

The following item is required against local purchase. Suppliers are requested to quote by 11-11-2026 before 10:00 AM. Quotations are to be deposited in the quotation box.

<u>S.NO</u>	<u>LPR NO & DATE/ DESCRIPTION</u>	<u>QTY</u>	<u>DELIVERY</u>
01	VSD-LPR NO 156/2026 DATED 08-10-2026 WHOLE DAY MREs	485 Pkt	VSD AT KARACHI

NOTE:

1. Non-registered firms/suppliers are required to forward bank draft/pay order equal to 5% total value of quotation in favor of "Commander Local Purchase" division along with their bids.
2. For any amplified details interested firms may contact Local Purchase Division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED




M DANIYAL KHAN
Lt Cdr Pakistan Navy
GO LP VSD
Date: _____

MENU # 1

Specifications of whole day ration pack

<u>S.No</u>	<u>ITEM</u>	<u>QUANTITY</u>
1.	Break Fast:	
	a. Gram Masala	250 gm
	b. Naan	95 gm (02 in No)
2.	Morning Tea:	
	a. Sugar	10 gm
	b. Milk Powder	8 gm
	c. Tea Leaves	1.5 gm to 2 gm
3.	Stand Easy:	
	a. Biscuit	45 gm
4.	Lunch:	
	a. Chicken Biryani	500 gm
	b. Black Roasted Chana (Dry)	60 gm
	c. Dry Dates	7.5 gm x 08 In No
	d. Candies	3.625 gm x 04 In No
5.	Dinner:	
	a. Beef Haleem	300 gm
	b. Naan	95 gm (02 In Nos)
6.	Accessories:	
	a. Fork	01 x 05 gm
	b. Spoon	01 x 05 gm
	c. Tissue Paper	6.6 gm
7.	Energy Bars	01




M. SUBHAN JAVED
Lt Pakistan Navy
Group Officer (Dry)

MENU # 2

Specifications of whole day ration pack

S.No	Item	Quantity
1.	Breakfast	
	a. Gram Masala	250gm.
	b. Naan	95gm (02 in No)
2.	Morning Tea	
	a. Sugar	10gm
	b. Milk Powder	08gm
	c. Tea Leaves	1.5gm to 02 gm
3.	Stand Easy	
	a. Biscuits	45gm
4.	Lunch	
	a. Beef Biryani	500gm
	b. Black Roasted Channa Dry	60gm
	c. Dry dates	7.5gmX08 in No.
	d. Candies	3.625gmX04 in No.
5.	Dinner	
	a. Chicken Halæem	300gm
	b. Naan	95gm (02 in No)
6.	Accessories	
	a. Fork	01X05gm
	b. Spoon	01X05gm
	c. Tissue paper	6.6gm
7.	Energy Bars	01



M SUBHAN JAVED
Lt Pakistan Navy
Group Officer (Dry)

MENU # 03

Specifications of whole day ration pack

<u>S.No</u>	<u>ITEM</u>	<u>QUANTITY</u>
1.	Break Fast:	
	a. Gram Masala	250 gm
	b. Naan	95 gm (02 in No)
2.	Morning Tea:	
	a. Sugar	10 gm
	b. Milk Powder	8 gm
	c. Tea Leaves	1.5 gm to 2 gm
3.	Stand Easy:	
	a. Biscuit	45 gm
4.	Lunch:	
	a. Chicken Biryani (or equivalent)	500 gm
	b. Black Roasted Chana (Dry)	60 gm
	c. Dry Dates	7.5 gm x 08 In No
	d. Candies	3.625 gm x 04 In No
5.	Dinner:	
	a. Beef Haleem (or equivalent)	300 gm
	b. Naan	95 gm (02 in No)
6.	Accessories:	
	a. Fork	01 x 05 gm
	b. Spoon	01 x 05 gm
	c. Tissue Paper	6.6 gm
7.	Energy Bars	01



M. SUBHAN JAVED
Lt Pakistan Navy
Group Officer (Dry)

SPECIFICATIONS OF WHOLE DAY MRE PACK

1. Scope.

This specification covers the quality and quantity of the components and packing requirements of whole day per person MRE Pack Ration.

2. Quality:

- a. The pack shall consist of items described in Annex A to this Specification.
- b. All ingredients used in the manufacture of the item of the rations shall be fresh, clean, sound, wholesome, free from infestation, extraneous matter and any kind of deterioration. These shall be in satisfactory condition in all respects.
- c. The items included in the pack shall be well baked/cooked where applicable and be attractive in appearance, pleasant in taste, wholesome, palatable and free from unpleasant odor, infestation and deleterious substances.
- d. The total caloric value of one complete ration shall not be less than 3400.

3. Packing.

The aim shall be to provide a light, compact and sturdy packing, which allows minimum of oxygen to the contents and complete barrier to water vapors.

- a. Individual Items. Sugar shall be packed in sealed polyethylene bags. Skimmed Milk Powder and Tea Leaves shall be packed in heat scalable moisture proof cellophane paper. Other packing materials can be used provided they offer equal protection to Tea Leaves and Skimmed Milk Powder and do not impart any foreign odour to the product. Chicken Biryani and, Beef Biryani shall be packed in aluminum foil laminate. The laminate shall be a combination of polyethylene and aluminum foil.
- b. Complete Ration Pack. All the items constituting the ration shall be packed in a bag of polyethylene possesses light weight and of good quality. The instructions for reconstitution of the items where applicable shall be printed on each packet.
- c. All items included in the pack shall be free from pathogenic/ food spoiling micro-organisms.

4. Marking.

The following particulars shall be marked on at least one side of each pack.

- a. Item Name and Brand Name (if any)
- b. Batch or Code Number
- c. Date of Manufacturing
- d. Date of Expiry (at least 02 years)
- e. Net Weight
- f. Name and Address of the manufacturer/ supplier
- g. Accurate Nutrients (i.e Calories, Proteins, carbohydrates and Fats)
- h. Specially packed for VSD

5. Warranty.


The warranty shall be in accordance with the standard warranty clause. The minimum warranty period shall not be less than six months but the rations should remain fit for consumption for not less than **two years** under normal storage conditions.

6. Hygiene.

The item shall be prepared, packed and stored in good hygienic premises in accordance with Pakistan Standards – Good Manufacturing Practices (PS:1825) and Codex Alimentarius Commission's recommended international code of practices and general principles of food hygiene (CAC/RCP1-1969, rev.4-2003), which shall be opened to inspection at any time, by a competent authority approved by Pakistan Navy.

7. Inspection.

Inspection of supplies tendered shall be carried out by an officer acting on behalf of CO VSD. The decision of the officer shall be final. Deliveries shall be equal in all respects to the sample approved by the competent authority. In case any disparity is found between the original sample and the delivered stock, the purchaser shall have the right to demand replacement of the stock from the supplier and supplier shall be bound to do so within 05 x days.



M SUBHAN JAVED
Lt Pakistan Navy
Group Officer (Dry)