LOCAL PURCHASE DIVISION – PAKISTAN NAVY

TERMS & CONDITIONS FOR INVITATION TO TENDERS TO BE OPENED ON 26-11-2026

1. ALL FIRMS (REGISTERED / UN REGISTERED) REQUIRED TO PAY TENDER FEES @ RS 500/- PER QUOTATION IN SHAPE OF BANK DRAFT / PAY ORDER/ CROSS CHEQUE / ONLINE TRANSFER (NON REFUNDABLE) IN FAVOUR OF "PN NONPUBLIC FUND LP DIVISION IT FUND ACCOUNT" (ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586)

2. IN CASE OF ONLINE PAYMENT, PROOF OF ONLINE DEPOSIT IN ACCOUNT NO. PK04 MEZN 0001 7001 0321 0586 IS TO BE ATTACHED WITH RELEVANT QUOTATION.

3. FURTHERMORE, ALL NON REGISTERED FIRMS ARE TO PAY BG @ 5% OF THE PURCHASE ORDER VALUE, IN SHAPE OF PAY ORDER / BANK DRAFT VALID FOR SIX (6) MONTHS. THEREAFTER PURCHASE ORDER WILL BE ISSUED.

4. TO AVOID PAYMENT OF BG, ALL NON REGISTERED FIRMS ARE ENCOURAGED TO GET THEMSELF REGISTER WITH HQ COMLOG. FOR DETAILS PLEASE CONTACT SO CONTRACT ON 021-48506138.

5. STANDARD DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND IMPORTED ITEMS IS 45 DAYS.

6. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

7. FOR ANY QUERY FIRM MAY CONTACT LOCAL PURCHASE DIVISION, THROUGH TELEPHONE, VIA EMAIL OR WHATSAPP

EMAIL:	clp@paknavy.gov.pk, localpurchasedivision@gmail.com
PHONE:	021-48508524, 48508828,
WHATSAPP NO.	92-322-0188121 (Message Only)

TENDER BULLETIN

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGH112382	20' X 8'	5610705206956 / PORTA CABIN (OI/C OFFICE AND RETIRING ROOM	PORTA CABIN Star Engineering PAKISTAN	1 / EACH/NUMBER	2017	-	Star Engineering Works Plot # 29-C, 12 th Street Phase II, Ext, DHA Karachi, Pakistan Phone # 021-35888950 WF & Sons Plot # A-440, A Area, Kalaboard Malir Karachi Phone # 021 - 34510136	STAR ENGINEERING WORKS and WF & SONS		TECHNICAL SPECIFICATION - a. materiel GRADE : Steel or Aluminum Frame, Insulated Panels (EPS, PU or Rock Wool) b. Paint coating/ Colour: White/ Off white c. Accessories required in CABINS (1) Ceiling with LED lights and Fan. (2) Electrical System with Sockets and switches. (3) Air Conditioner. (4) Vinyl or laminate flooring (5) Painted or Laminated walls. (6) Fire Extinguisher. (7) 02 x Table, 04 x Chair and 02 x wooden racks d. Measurement Length: 20ft to 40ft Width: 09ft to 12ft Height: 08ft to 10ftGENERAL SPECIFICATION - a. materiel GRADE : Steel or Aluminum Frame, Insulated Panels (EPS, PU or Rock Wool) b. Paint coating/ Colour: White/ Off white c. Accessories required in CABINS (1) Ceiling with LED lights and Fan. (2) Electrical System with Sockets and switches. (3) Air Conditioner. (4) Vinyl or laminate flooring (5) Painted or Laminated walls. (6) Fire Extinguisher. (7) 02 x Table, 04 x Chair and 02 x wooden racks d. Measurement Length: 20ft to 40ft Width: 09ft to 12ft Height: 08ft to 10ft	
2	DRG96285	8814157000	6680ZO6529519 / TANK		3 / EACH/N	NO DATA AVAILAB					TECHNICAL SPECIFICATION - MATERIAL STRONG PLASTIC .	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PRESSURE GENERATOR.		UMBER	LE					CAPACITY 4.5 - 5.5 LTRS. PRESSURE 03 BAR WITH PRESSURE GAUGE,FILTER ETC. MODEL:229TS,MAKE GLORIA GERMANY/ANY COMPITABLE WITH BOOKLET a. OEM TURBOMECA (FRANCE)GENERAL SPECIFICATION - MATERIAL STRONG PLASTIC .CAPACITY 4.5 - 5.5 LTRS. PRESSURE 03 BAR WITH PRESSURE GAUGE,FILTER ETC. MODEL:229TS,MAKE GLORIA GERMANY/ANY COMPITABLE WITH BOOKLET a. OEM TURBOMECA (FRANCE)	
3	DGH110 204		9520705136051 / Angle Steel Bulb Bar	DOCK,S HULL	150 / METER	NO DATA AVAILABLE		PK	M/S RUBY TRADERS IRON & STEEL SHERSHAH RD KARACHI -2573339		TECHNICAL SPECIFICATION - Material specification is AH36. BS EN 10025-06 of 2019 + A1:2022. length/Height: 6 Meters, width: 200 mm, Flange/ web thickness: 09 mm. GENERAL SPECIFICATION - Material specification is AH36. BS EN 10025-06 of 2019 + A1:2022. length/Height: 6 Meters, width: 200 mm, Flange/ web thickness: 09 mm.	
4	DGH109 928		9520705136051 / Angle Steel Bulb Bar	DOCK,S HULL	80 / METER	NO DATA AVAILABLE		PK	M/S RUBY TRADERS IRON & STEEL SHERSHAH RD KARACHI -2573339		TECHNICAL SPECIFICATION - Material specification is AH36. BS EN 10025-06 of 2019 + A1:2022. length/Height: 6 Meters, width: 200 mm, Flange/ web thickness: 09 mm. GENERAL SPECIFICATION - Material specification is AH36. BS EN 10025-06 of 2019 + A1:2022. length/Height: 6 Meters, width: 200 mm, Flange/ web thickness: 09 mm.	
5	DGH109 630		9520705136052 / Angle Steel Bulb Bar	DOCK,S HULL	150 / METER	NO DATA AVAILABLE		PK	M/S RUBY TRADERS IRON & STEEL SHERSHAH RD KARACHI -2573339		TECHNICAL SPECIFICATION - Material Specifications are AH36. BS EN 10025-06 of 2019 + A1:2022. length/Height: 6 Meter, width: 140mm, Flange/ web thickness: 09 mm.GENERAL SPECIFICATION - Material Specifications are AH36. BS EN 10025-06 of 2019 + A1:2022. length/Height: 6 Meter, width: 140mm, Flange/ web thickness: 09	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											mm.	
6	DGT114593	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	2040 / FOOT	NO DATA AVAILABLE		PK	TAWAKAL BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment : required GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment :required	
7	DGE113090	-	5610992004386 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	50 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCRETE UK LTD THE FLOORING TECHNOLOGIES CENTRE BOOTH LANE SANDBATCH CHESHIRE CW11 3QF UK PH:+44(0)1270 753000 & FAX :+44 (0)1270 753333		TECHNICAL SPECIFICATION - BAG SAND(LOCAL GOOD QUALITY ACCEPTABLE) 25 kg unfilledGENERAL SPECIFICATION - BAG SAND(LOCAL GOOD QUALITY ACCEPTABLE) 25 kg unfilled	
8	DGE114226	-	5610992004386 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	8 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCRETE UK LTD THE FLOORING TECHNOLOGIES CENTRE BOOTH LANE		TECHNICAL SPECIFICATION - BAG SAND(LOCAL GOOD QUALITY ACCEPTABLE) 25 kg unfilledGENERAL SPECIFICATION - BAG SAND(LOCAL GOOD QUALITY ACCEPTABLE) 25 kg unfilled	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									SANDBATCH CHESHIRE CW11 3QF UK PH:+44(0)1270 753000 & FAX :+44(0)1270 753333			
9	DGE114147	-	5610992004386 / BAG SAND (LOCAL GOOD QUALITY ACCEPTABLE)	DC & FF	5 / KILOGRAMME	NO DATA AVAILABLE		UK	FLOWCRETE UK LTD THE FLOORING TECHNOLOGIES CENTRE BOOTH LANE SANDBATCH CHESHIRE CW11 3QF UK PH:+44(0)1270 753000 & FAX :+44(0)1270 753333		TECHNICAL SPECIFICATION - BAG SAND(LOCAL GOOD QUALITY ACCEPTABLE) 25 kg unfilledGENERAL SPECIFICATION - BAG SAND(LOCAL GOOD QUALITY ACCEPTABLE) 25 kg unfilled	
10	SGB113355	BS1476/NE 8-M	0283705711226 / ALUMINIUM ALLOYANGLE EQUALSIDED RT ANGLE LG 1.50"X1.50" X1/8"		100 / METER						TECHNICAL SPECIFICATION - Item Specification:BSEN-573-3 OF 1995 (CHEMICAL COMPOSITION)BSEN-485-2 OF 1995(MECHANICAL PROPERTIES) GRADE ENAW 5083GENERAL SPECIFICATION - Item Specification:BSEN-573-3 OF 1995(CHEMICAL COMPOSITION) BSEN-485-2 OF 1995(MECHANICAL PROPERTIES) GRADE ENAW 5083	
11	SGE112918	NIL	0461599104733 / HANDLE FOR		50 / EACH/NUMBER						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HAMMER-17INCH									
12	DGB109936		028370923350 4 / ZINC INGOT 99.995% PURITY LG 16",BREADTH 8",HT 1.75"		600 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005% GENERAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005%	
13	DGB109635		028370923350 4 / ZINC INGOT 99.995% PURITY LG 16",BREADTH 8",HT 1.75"		500 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005% GENERAL SPECIFICATION - BS EN 1179 GRADE CLASSIFICATION Z-1, COLOUR WHITE, PURITY 99.995%. LME (London Metal Exchange) registered brand and Special High Grade (SHG) Zinc (Min 99.995% Pure). PROVISION OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CERTIFICATE OF LME REGISTERED BRAND. 1. Dimensions : Length= 16" Breath= 8" Height= 1.75" 2. Composition: Zinc= 99.995% Remainder= 0.005%	
14	SGB114306	SPECS: DNC/S2A/BS 970/EN 3A	0212595710000 / MILDSTEEL CARBON RD HOT ROLLED 1/4"WT PER FT 0.167LBS		800 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
15	DGH108779		0211592044553 / SHEET STEEL STAINLESS SIZE 3050X1220X3MM	DEEP FRYER 2PAN	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MMGENERAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0. 25MM	
16	DGH109647		0211592044553 / SHEET STEEL STAINLESS SIZE 3050X1220X3MM	DEEP FRYER 2PAN	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0.25MMGENERAL SPECIFICATION - ASTM A240 GRADE : SS 304 SIZE: L X W XTH : 3050MM X 1220MM X 03MM THICKNESS TOLLERENCE: +0. 25MM	
17	SGH113357		0211599230173 / STAINLESS STEEL SHEET SIZE 2500X1250X1MM	COLD ROLLED TENSILE TESTED ZINC COATED	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC) GENERAL SPECIFICATION - SPECS: ASTM A240 GRADE 304 MIL TEST CERTIFICATE (MTC)	
18	SGB113359		0267599235343 / Tee pipe equal galvanized (three sides equal) black		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - INNER DIA: 45 MM, OUTSIDE DIA: 58 MM, THICKNESS: 6.5 MM, THREADS: 11, BS 1740/71 CORROSION RESISTING STEEL/FERROUS ALLOY, WITH LAYER OF MOLTEN ZINC MTC OF ITEM IS REQUIREDGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - INNER DIA: 45 MM, OUTSIDE DIA: 58 MM, THICKNESS: 6.5 MM, THREADS: 11, BS 1740/71 CORROSION RESISTING STEEL/FERROUS ALLOY, WITH LAYER OF MOLTEN ZINC MTC OF ITEM IS REQUIRED	
19	DGH109372		0231595715243 / WIRE ROPE STEEL EXTRA SPECIAL GALVA LAY OF ROPE RH CIRC 3/8"		50 / METER						TECHNICAL SPECIFICATION - bs en 12385-4/ iso2408 coil length: 1000 meter Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39) GENERAL SPECIFICATION - bs en 12385-4/ iso2408 coil length: 1000 meter Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands= 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 320D Table 39)	
20	SGB114307		0288790011747 / ELECTRODE WELDING Low hydrogen 3.2 MM	WELDING	3000 / METER						TECHNICAL SPECIFICATION - aws a5.1:2025 is supported. of 2004 e 7018 low hydrogen type 1. acceptable brands are fortrex(pak oxygen) & nihonweld (philippines); welding Pack should come in Vacuum packing. 2. IACS MEMBER SOCIETY APPROVED CERTIFICATION 3. tender SAMLE OF ELECTRODE WITH THEIR TECHNICAL BIDS. 4. SIZE: DIAMETER: 3.2 MM LENGHT: 350 MM SUITABLE FOR HIGH CRACK RESISTANT & TOUGH JOINTS, INCLUDING THOMAS GRADE & CARBON STEELS UP TO 0.4% CURRENT: 90-140 AMPS Vaccum Packing is required. a. Proposed description i.e. 'Electrode Welding, Low Hydrogen 3.2mm' is acceptable. b. Updated Standard i.e. AWS A5.1: 2025 is supported. c. Para 2 c is supported. d. Para 2 d is supported. e. Acceptable brands are FORTREX (Pak Oxygen) & NIHONWELD (Philippines); Welding Pack should	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											come in Vacuum packing.GENERAL SPECIFICATION - aws a5.1:2025 is supported. of 2004 e 7018 low hydrogen type 1. acceptable brands are fortrex(pak oxygen) & nihonweld (philippines); welding Pack should come in Vacuum packing. 2. IACS MEMBER SOCIETY APPROVED CERTIFICATION 3. tender SAMLE OF ELECTRODE WITH THEIR TECHNICAL BIDS. 4. SIZE: DIAMETER: 3.2 MM LENGHT: 350 MM SUITABLE FOR HIGH CRACK RESISTANT & TOUGH JOINTS, INCLUDING THOMAS GRADE & CARBON STEELS UP TO 0.4% CURRENT: 90-140 AMPS Vaccum Packing is required. a. Proposed description i.e. 'Electrode Welding, Low Hydrogen 3.2mm' is acceptable. b. Updated Standard i.e. AWS A5.1: 2025 is supported. c. Para 2 c is supported. d. Para 2 d is supported. e. Acceptable brands are FORTREX (Pak Oxygen) & NIHONWELD (Philippines); Welding Pack should come in Vacuum packing.	
21	DGB113691		0276799105870 / SCREW DRIVER RATCH, DOUBLE SPIRAL,AUTO RETURN, 250MM LG,3 BITS		28 / EACH/NUMBER						TECHNICAL SPECIFICATION - Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in ChinaGENERAL SPECIFICATION - Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in China	
22	SGB113350		0266590016030 / WASHER FLAT ROUND MILD STEEL 0.625X0.687X1.375X0.	O/D 34.925 INCH THK 0.128 INCH SPEC=BS 1769	260 / KILOGRAMME						TECHNICAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			128IN								REQUIREMENT IS REQUIRED Size 5/8 (0.625) Inch Hole Distance= 11/16 (0.6875) Inch Outerside Dia= 13/8 (1.375) Inch Appro Weight per 100=4 Lbs GENERAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925 MM), THICKNESS 0.128" INCH (3.25 MM), NO TEMPER REQUIREMENT IS REQUIRED Size 5/8 (0.625) Inch Hole Distance= 11/16 (0.6875) Inch Outerside Dia= 13/8 (1.375) Inch Appro Weight per 100=4 Lbs	
23	DGB113708		0266590016030 / WASHER FLAT ROUND MILD STEEL 0.625X0.687X1.375X0.128IN	O/D 34.925 INCH THK 0.128 INCH SPEC=BS 1769	300 / KILOGRAMME						TECHNICAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER REQUIREMENT IS REQUIRED Size 5/8 (0.625) Inch Hole Distance= 11/16 (0.6875) Inch Outerside Dia= 13/8 (1.375) Inch Appro Weight per 100=4 Lbs GENERAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925 MM), THICKNESS 0.128" INCH (3.25 MM), NO TEMPER REQUIREMENT IS REQUIRED Size 5/8 (0.625) Inch Hole Distance= 11/16 (0.6875) Inch Outerside Dia= 13/8 (1.375) Inch Appro Weight per 100=4 Lbs	
24	DGB114029	NO DATA AVAILABLE	0263599236987 / THIMBLE, ROPE STEEL BS 970-EN 3A GALVANISED PEAR SHAPED OPEN TYPE WT 1.75LBS	SPEC NO DGS 5031NO.40	280 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material specification: BS 970/ EN 3A material grade : 070M20. Galvanized thickness: 1.25mm.GENERAL SPECIFICATION - Material specification: BS 970/ EN 3A material grade : 070M20. Galvanized thickness: 1.25mm.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE 1.25									
25	DGB114 003	BS 1083	025770419500 8 / NUT-PLAIN-HEXAGON-THREAD-SIZE 0.750	BRASS TYPE	12 / DOZEN						TECHNICAL SPECIFICATION - material grade i.e SS347 bs 970, 60r7aGENERAL SPECIFICATION - material grade i.e SS347 bs 970, 60r7a	
26	DGB114 004		025770419501 3 / NUT PLAIN HEX BSW BRASS THD 0.250 O/A LG 0.200 (FULL BEARING)	0.250",O/A HEIGHT: 0.200",STYLE: FULL BEA.	12 / DOZEN						TECHNICAL SPECIFICATION - MATERIAL GRADE: MILD STEEL INNER DIA: 6.5MM OUTER DIA: 11MM WIDTH: 7MM BR 320-D/69GENERAL SPECIFICATION - MATERIAL GRADE: MILD STEEL INNER DIA: 6.5MM OUTER DIA: 11MM WIDTH: 7MM BR 320-D/69	
27	SGB113 354		026259001689 7 / CLIP IRON O/A LG 6" DIA 3/8"BOTH ANGLE 90 BOTH ARM 2" (LOCAL)	USE MARINE RAILWAY	750 / EACH/NUMBER						TECHNICAL SPECIFICATION - MILD STEEL BS 970 EN 3A superceeded by PD 970 (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local)GENERAL SPECIFICATION - MILD STEEL BS 970 EN 3A superceeded by PD 970 (070M20) Clip Iron O/A 6" dia 3/8" both angle 90° arm 2" (local)	
28	SGB113 356	0265-111	026559423319 5 / NAIL STEEL WIRE ROUND, CHEQUEReD HD,SWG 9 LG 3.0 IN (LOCAL)		100 / KILOGRAMME	local					TECHNICAL SPECIFICATION - nail steel wire round 3 inch GENERAL SPECIFICATION - nail steel wire round 3 inch	
29	DGB114 178	Material Grade EN 4140	025770941150 6 / NUT-PLAIN-HEXAGON-THREAD-SIZE. 625LH.550"		8 / DOZEN						TECHNICAL SPECIFICATION - material specs AISI 4140(PD 970: 2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIREDGENERAL SPECIFICATION - material specs AISI 4140(PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
30	DGB114 161	0251-14505	025170411973 7 / FERRULE-WIRE-ROPE 1.5 INCH (12mm)		200 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL aluminum alloy SHAPE ELLIPSE TYPE COLOR SILVER INTERNAL WIDTH 26 MM INTERNAL HEIGHT 13 MM OUTER DIA 36 MM OUTER LENGHT 42 MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BODY THICKNESS 05 MM GENERAL SPECIFICATION - MATERIAL aluminum alloy SHAPE ELLIPSE TYPE COLOR SILVER INTERNAL WIDTH 26 MM INTERNAL HEIGHT 13 MM OUTER DIA 36 MM OUTER LENGHT 42 MM BODY THICKNESS 05 MM	
31	SGB113358		1325723350010 / BLADE POWER HACK SAW HSS 18X1-1/2X0.075" 6TPI		60 / EACH/NUMBER	AISI M2 HSS (Super Hardened)					TECHNICAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 ½ x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened)GENERAL SPECIFICATION - 450 x 38 x 2 (mm) 18 x 1 ½ x 0.075 (inches) GRADE AISI M2 HSS (Super Hardened)	
32	SGB113360	NO DATA AVAILABLE	4730705038535 / band pipe m/s 2.5 inch	DUMP BARGE COUNSTRUCTION	185 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material: Mild Steel Grade JR275 Size: 2.5 inch x 4.775 mm thick Schedule: 40 OEM: Pakistan/China Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload) GENERAL SPECIFICATION - Material: Mild Steel Grade JR275 Size: 2.5 inch x 4.775 mm thick Schedule: 40 OEM: Pakistan/China Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload)	
33	SGE112910		5350002247201 / PAPER ABRASIVE P/N P-P-101		20 / PACKET						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DGT114487	NO DATA AVAILABLE	0100500000088 / Ply wood GD-I, 9 ply,	X 19.05 MM)	750 / SQ FEET	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.GENERAL SPECIFICATION - SPECIFICATION OF ITEM: 1. Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8-FEET, Width=4-FEET & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood and core and inner plies of poplar. Thickness of Face Back veneer 0.6mm. 5. SPECIFICATIONS/STANDARDS BS EN 322: 1993, BS 314-1: 2004 AND BS EN 314-2: 1993, BS 1203: 2001, BS 4072: 1999, BS 6566-6: 1985, BS EN 323: 1993, 6. MOISTURE: 6-14% 7. DENSITY RANGE I.E 700 TO 850 KG PER CUBIC METER.	
35	DGB113694		0275500000026 / MEASURING TAPE STEEL ½" x 300'		8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Crescent Lufkin ½" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure – Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working conditionGENERAL SPECIFICATION - Crescent Lufkin ½" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure – Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working condition	
36	DGB114069		7240505040724 / BUCKET		100 / EACH/N						TECHNICAL SPECIFICATION - Model No: WK S30, Metallic:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			KICK WITH FOUR RUBBER WHEEL, Capacity: 14L, MODEL NO WK530, Stainless Steel		UMBER						Stainless Steel, Size: 33x33x42cm, Castor: Dia 50mm, Capacity: 14LGENERAL SPECIFICATION - Model No: WK S30, Metallic: Stainless Steel, Size: 33x33x42cm, Castor: Dia 50mm, Capacity: 14L	
37	DGB109935		9535995711401 / PLATE FLOOR METAL (TREAD PLATE)	MATERIAL SPEC.BS 1477HP 30SPEC. ADSP1098A	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 2440 MM X WIDTH 1220 MM X 6 MM BASE THICKNESS CROSS - SECTION THICKNESS: 7.2MM British Specification 1474 along with Material Grade 6082 and heat treatment condition T6. Embossed pattern height: 1.2mm above the base metal. basic shape style: b2 pattern no 10 density: 18.95 KG/M2 DEFSTAN 02-840 (NES- 840) GENERAL SPECIFICATION - PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 2440 MM X WIDTH 1220 MM X 6 MM BASE THICKNESS CROSS - SECTION THICKNESS: 7.2MM British Specification 1474 along with Material Grade 6082 and heat treatment condition T6. Embossed pattern height: 1.2mm above the base metal. basic shape style: b2 pattern no 10 density: 18.95 KG/M2 DEFSTAN 02-840 (NES- 840)	
38	DGB112359		9535995711401 / PLATE FLOOR METAL (TREAD PLATE)	MATERIAL SPEC.BS 1477HP 30SPEC. ADSP1098A	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 2440 MM X WIDTH 1220 MM X 6 MM BASE THICKNESS CROSS - SECTION THICKNESS: 7.2MM British Specification 1474 along with Material Grade 6082 and heat treatment condition T6. Embossed pattern height: 1.2mm above the base metal. basic shape style: b2	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											pattern no 10 density: 18.95 KG/M2 DEFSTAN 02-840 (NES- 840) GENERAL SPECIFICATION - PLATE FLOOR METAL (TREAD PLATE) SIZE: LENGTH 2440 MM X WIDTH 1220 MM X 6 MM BASE THICKNESS CROSS - SECTION THICKNESS: 7.2MM British Specification 1474 along with Material Grade 6082 and heat treatment condition T6. Embossed pattern height: 1.2mm above the base metal. basic shape style: b2 pattern no 10 density: 18.95 KG/M2 DEFSTAN 02-840 (NES- 840)	
39	DGE113869		0330546003565 / FLANNELETTE CLOTH CREAM GRD W/RED WEFT BARS 4"X50 YARDS		400 / METER						TECHNICAL SPECIFICATION - ¿ Size: 4" x 2". ¿ Width: 10 cm. ¿ Material: 100% Softness Cotton and Gun Care Cleaning Products. ¿ Colour: Cream.GENERAL SPECIFICATION - ¿ Size: 4" x 2". ¿ Width: 10 cm. ¿ Material: 100% Softness Cotton and Gun Care Cleaning Products. ¿ Colour: Cream.	
40	SGE112921		9330PK5124256 / PLASTIC COVER TRANSPARENT FOR MODLES OF 18' (SEE COMD F8)	N	40 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DRG103745	SBA-145016380	4730ZO6573882 / WATER PUMP ASSY		3 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DSB100066	ITD/5250180	4320545344811 / Shaft Protective Liner 15x21x50 MONEL 500		2 / EACH/NUMBER	268969/5250180					TECHNICAL SPECIFICATION - (15X21X50 MONEL K 500 DIMENSIONAL CHEK REQUIRED LEAK HOLDING TEST PRESSURE 48bar) Shaft Protective Liner (Existing metallurgy 15 x 21 x 50 MONEL 500, metallurgy offered by KSB Duplex Steel)GENERAL SPECIFICATION - (15X21X50	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MONEL K 500 DIMENSIONAL CHEK REQUIRED LEAK HOLDING TEST PRESSURE 48bar) Shaft Protective Liner (Existing metallurgy 15 x 21 x 50 MONEL 500, metallurgy offered by KSB Duplex Steel)	
43	DSB113973	BLANC	8305143440441 / TISSU CORFEU 1000 AERE BLANC (REXINE) (WOVEN)		300 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - • Complete item/ store description be endorsed alongwith Packing details: white ragsine, having thickness 1.5 mm, Packing as per OEM Dual side rexine, Material: PVC coated rexine Base: Locasre cloth Colour: White Thickness 1.8mm Width: 54 inch Waterproof Heat resistant • Detailed Specification alongwith inspection/ Acceptance Criteria be mentioned: As per procedure in vogue GENERAL SPECIFICATION - • Complete item/ store description be endorsed alongwith Packing details: white ragsine, having thickness 1.5 mm, Packing as per OEM Dual side rexine, Material: PVC coated rexine Base: Locasre cloth Colour: White Thickness 1.8mm Width: 54 inch Waterproof Heat resistant • Detailed Specification alongwith inspection/ Acceptance Criteria be mentioned: As per procedure in vogue	
44	DSB100063	itd/5250128	4320545344808 / Wear Ring		3 / EACH/NUMBER	365191/5250128					TECHNICAL SPECIFICATION - (ALUMMINIUM BRONZE DIMENSIONAL CHEK REQUIRED LEAK HOLDING TEST PRESSURE 48bar) Centralized Cooling Pump (DK/ME) is used to circulate sea/ fresh water to fulfill cooling requirements of hydraulic circuit, HP air compressors, air conditioning units and main electric propulsion motor onboard.GENERAL SPECIFICATION - (ALUMMINIUM BRONZE DIMENSIONAL CHEK REQUIRED LEAK HOLDING TEST PRESSURE 48bar) Centralized	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Cooling Pump (DK/ME) is used to circulate sea/ fresh water to fulfill cooling requirements of hydraulic circuit, HP air compressors, air conditioning units and main electric propulsion motor onboard.	
45	DSB100067	itd/5250183	4320545344335 / Mechanical Packing Cover - Impeller WEar Ring		3 / EACH/NUMBER	365192/5250183					TECHNICAL SPECIFICATION - (ALUMMINIUM BRONZE DIMENSIONAL CHEK REQUIRED LEAK HOLDING TEST PRESSURE 48bar) Mechanical Packing Cover - Impeller Wear Ring (Metallurgy offered by KSB Duplex steel) GENERAL SPECIFICATION - (ALUMMINIUM BRONZE DIMENSIONAL CHEK REQUIRED LEAK HOLDING TEST PRESSURE 48bar) Mechanical Packing Cover - Impeller Wear Ring (Metallurgy offered by KSB Duplex steel)	
46	DSB113974	049-21-009	8305143440903 / SIMILI CUIR BLEU 3517		316 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - b. Technical parameters of store i.e. dimension/ size and etc: Nomenclature: Rexine/ Leatherette, PVC Coated Fabric. Base Cloth: Cotton, polyester Mix. Color: Navy Blue. Width: 140 CM. Thickness: 0.9 mm to 1.1 mm Pattern: Plain/ Mat Finished (no grain) c. Specifications/ Technical Data/Testing/Acceptance Criteria/Applicable Standard: Fire retardant (M1 class non flame able) Water proof Anti-Fungus, anti-Mildew GENERAL SPECIFICATION - b. Technical parameters of store i.e. dimension/ size and etc: Nomenclature: Rexine/ Leatherette, PVC Coated Fabric. Base Cloth: Cotton, polyester Mix. Color: Navy Blue. Width: 140 CM. Thickness: 0.9 mm to 1.1 mm Pattern: Plain/ Mat Finished (no grain) c. Specifications/ Technical Data/Testing/Acceptance Criteria/Applicable Standard: Fire retardant (M1 class non flame able)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Water proof Anti-Fungus, anti-Mildew	
47	DSB100069	ITD/5250184	4320545344336 / Shaft Protective Liner 22.3X39.7X130 CUAL9NI3FE2		3 / EACH/NUMBER	268958/5250184					TECHNICAL SPECIFICATION - (22.3X39.7X130 CUAL 9ni3fe2 DIMENSIONAL CHEK REQUIRED LEAK HOLDING TEST PRESSURE 48bar) Shaft Protective Liner (Existing metallurgy 22.3 x 39.7 x 130 CUAL9NI3FE2, (Metallurgy offered by KSB CC333G)GENERAL SPECIFICATION - (22.3X39.7X130 CUAL 9ni3fe2 DIMENSIONAL CHEK REQUIRED LEAK HOLDING TEST PRESSURE 48bar) Shaft Protective Liner (Existing metallurgy 22.3 x 39.7 x 130 CUAL9NI3FE2, (Metallurgy offered by KSB CC333G)	
48	DGH112135		9520705136050 / ANGLE STEEL BULB BAR	DOCK,S HULL	100 / METER	NO DATA AVAILABLE		PK	M/S RUBY TRADERS IRON & STEEL SHERSHAH RD KARACHI -2573339		TECHNICAL SPECIFICATION - MATERIAL GRADE: ASTM AH36 BS EN 10025-06 OF 2019 + A1: 2022 IENGTH/HEIGHT= 06 METERS WIDTH: 240MM FLANGE/WEB THICKNESS: 10MM GENERAL SPECIFICATION - MATERIAL GRADE: ASTM AH36 BS EN 10025-06 OF 2019 + A1: 2022 IENGTH/HEIGHT= 06 METERS WIDTH: 240MM FLANGE/WEB THICKNESS: 10MM	
49	DRG106206	BTT3-303-000-376	5845ZO6550494 / POWERBAND DUAL		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SAMPLE ATTACHED GENERAL SPECIFICATION - SAMPLE ATTACHED	
50	DRG107633	ZO6555421	1610ZO6555421 / PROPELLER (MASTER AIR SCREW 14" X6")		80 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Flight RC Wooden Beach Propeller Material: Beach Wooden Size: 14X6 Type: Clockwise ROTATIONGENERAL SPECIFICATION - Flight RC Wooden Beach Propeller Material: Beach Wooden Size: 14X6 Type: Clockwise ROTATION	
51	DGB111970	4992	4020795153120 / DOUBLE SIDED TAPE	TALL SHIP SAILING RIG	6 / EACH/NUMBER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE	BASELINE MARINE PRODUC		TECHNICAL SPECIFICATION - LIGHT,NON YELLOWING ACRLIC TAPE WITH VERY HIGH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(SIZE 12MMX50M)					AVENUE FAREHAM HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT. COM WWW. BASELINEHARDWARE. CO.UK	TS LTD 10 APPLE INDUSTRIAL E		ADHESION,SIZE: 12mmx50mGENERAL SPECIFICATION - LIGHT,NON YELLOWING ACRLIC TAPE WITH VERY HIGH ADHESION,SIZE: 12mmx50m	
52	DGE110873	LOCAL MADE	0422705160147 / CARPET RUNNER JAI NAMAZ	JAI NAMAZ SUF	15 / FOOT			LOCAL SOURCE:BOLTON MARKET KARACHI.	LOCAL SOURCE: BOLTON MARKET KARACHI		TECHNICAL SPECIFICATION - LOCAL SOURCE:BOLTON MARKET KARACHI. Carpet Runner Jai Namaz (authorized quantity 200 running feet) 01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand.GENERAL SPECIFICATION - LOCAL SOURCE:BOLTON MARKET KARACHI. Carpet Runner Jai Namaz (authorized quantity 200 running feet) 01 x Jai Namaz generally contain 02 x running feet and also available in Local Market due commercial item, likely supplier is HAVAL Carpet Center Sindhi Muslim Society Shahra-e-Faisal Karachi (Contact 0331-3924092). TSR check before LPO physically sample check for color, quality, sizing and cutting of Jai Namaz as per required length against demand.	
53	DGE97249	L10/11610	5340775168377 / FLAT POLYSTER WEBBING	POLICE BOAT LIFTING	2 / EACH/NUMBER			EUROTEX HOLLAND	EUROTEX HOLLAND		TECHNICAL SPECIFICATION - 10 INCH WIDE 20M LONG PLY 3 VERTICAL LIFT 150000KG U-LIFT 30000KG PLOT 122-C KEMARI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SLING, SF 6:1								TOWNSHIP KEMARI KARACHI PH 0333-2114658GENERAL SPECIFICATION - 10 INCH WIDE 20M LONG PLY 3 VERTICAL LIFT 150000KG U-LIFT 30000KG PLOT 122-C KEMARI TOWNSHIP KEMARI KARACHI PH 0333-2114658	
54	DGB99557	Morgan TPC 843	0474795208626 / Morgan Silicon Carbide Crucible, Top Dia: 420MM, Bottom Dia: 295MM	TILTING FURNACE NO 3006 TYPE CA F-23 (PLL) RECORD	1 / EACH/NUMBER	N/A	N/A	MOLTEN ADVANCED MATERIALS PLC REGISTERED IN ENGLAND AND WALES REGISTRATION NO 286773 & INDIA MANUFACTURED	MORGANITE CRUCIBLE LTD	-	TECHNICAL SPECIFICATION - Morgan Silicon Carbide Crucible, Height: 675MM, Top Dia: 420MM, Bottom Dia: 295MM, Part No. TPC 843 (drawing enclosed)GENERAL SPECIFICATION - Morgan Silicon Carbide Crucible, Height: 675MM, Top Dia: 420MM, Bottom Dia: 295MM, Part No. TPC 843 (drawing enclosed)	
55	DGT112349	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	500 / FOOT	NO DATA AVAILABLE		PK	TAWAKAL BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI	-	TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment : required GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feets termite treatment :required	
56	SGB65953	DEVS7866	4730995253348 / FLANGE	-	8 / EACH/NUMBER	NO DATA AVAILABLE		UK	MOD (NAVY) SHIP SUPPORT AGENCY DME MC253 ROOM 19 BLOCK B FRAHILL BATH UK	-	TECHNICAL SPECIFICATION - BS 1400 Inner dia: 1 ½ inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: ½ inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing GENERAL SPECIFICATION - BS 1400 Inner dia: 1 ½ inch Pitch circle dia: 3 7/8 inch Outer dia: 5 1/8 inch 04 x holes of 11/16 inch Thickness: ½ inch Material: COPPER ALLOY Leaded Gunmetal LG4 as per drawing	
57	DGE106061	ISO-1181 2004, BS-	0350595713232 / ROPE	GENERAL USE	600 / FATHO					-	TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		2087	SISAL 3 STRAND CIRC 1.25 DIA 13/32 (0.40625) ROT PROOFED		M						SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM/MANUFACTURED COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1181-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM/MANUFACTURED COC REQUIRED, 5. LENGTH PER COIL: 120 FATHOM. 6. VALID LLOYD'S DNV/ BSI/ CERTIFICATE OF ANY IACS MEMBER SOCIETY IS REQUIRED INDICATING BATCH/ LOT NUMBER FOR IDENTIFICATION AND BREAKING STRENGTH OF STORES.	
58	DGE112550	BS2052 , DEF STAN 40-3	0350595713246 / SPUN YARN SISAL S TWIST R. FROOFED 4/20 YARN LENGTH PER COIL 608-5% (FM)		90 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor) GENERAL SPECIFICATION - 1. Country of Origin 59- UK 2. End user Indicated Ops (for sea securing the items during sea and harbor)	
59	DGE110682	NO DATA AVAILABL	0350599233575 / FENDER		8 / EACH/N						TECHNICAL SPECIFICATION - ¿ MEDIUM SIZE: ¿ 1000 MM LENGHT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	MARINE ROUND SISAL WT.32 LBS. OVERALL DIA 2',INTERNAL DIA 8" FOR HARBOUR LAUNCHES		UMBER						¿ 500 MM DIAMETER ¿ 1550 MM CIRCUMFERENCE ¿ MATERIAL EVA FOAM AND NATURAL RUBBER ¿ tYPE: FLANGE TYPE AND ROPE TYPE ¿ ISO 9001 COMPLIANCE ¿ ENERGY ABSORPTION 08 K NM ¿ FORCE RECTION 71 KN GENERAL SPECIFICATION - ¿ MEDIUM SIZE: ¿ 1000 MM LENGHT ¿ 500 MM DIAMETER ¿ 1550 MM CIRCUMFERENCE ¿ MATERIAL EVA FOAM AND NATURAL RUBBER ¿ tYPE: FLANGE TYPE AND ROPE TYPE ¿ ISO 9001 COMPLIANCE ¿ ENERGY ABSORPTION 08 K NM ¿ FORCE RECTION 71 KN	
60	DGE112024	14.02.0012	0350599233577 / FENDER MARINE ROUND (HEAVY DUTY), FILLED WITH JUNK.		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8. MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED. GENERAL SPECIFICATION - 1. SIZE: DIAMETER= 800-MM, LENGTH: 2050-MM, EYE DIA: 32-MM, 2. TYPE: 3282 (F13) 3. GROSS BUOYANCY: 720-KG, 4. WEIGHT APPROX: 28-KG, 5. PACKING: 1 X PCS/ POLY BAG, 6. VALVE: HEAVY DUTY DUAL VALVE (AIR IN/OUT), 7. WATTANTY REQUIRED: 02 YEARS AGAINST MANUFACTURING FAULTS, 8.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MATERIAL: PVC 9. UV PROTECTION FOR TEMPERATURES BETWEEN -30 TO +60 DEGR CET 10. PICT/BROCHURE IS ATTACHED.	
61	DGE89409	NO DATA AVAILABLE	041359923875 5 / MAT FLOOR RUBBER LG. 18. WD.(LTR NO E-I/4927-A/1082 DT221096)		10 / METER						TECHNICAL SPECIFICATION - Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4-6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black. GENERAL SPECIFICATION - Size: Size 15" x 36" Thickness: 5mm Dotted Mat Material: Synthetic rubber Performance: Antiskid/ non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Diminutions: Width :1.5m, Length (as per roll), Thickness: 4-6mm Feature: Weather resistant, Impact resistant, Heat resistant, Corrosion resistant, nsulated, Cold resistant. Color: Blue/ Black.	
62	DGE97669	NO DATA AVAILABLE	046254600578 4 / TAPE-BROWN-PAPER-GUMMED (DTLD. NSD/TD/19/286 . DT.09		90 / ROLL	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
63	DGE107675		046279125518 8 / TUBING PLASTICS POLYETHYLENE (LOW DENSITY) FLIM LAY FLAT		15 / KILOGRAMME						TECHNICAL SPECIFICATION - DEFSTAN = 93-116/2 OF 2007 THICKNESS=.0.005" (Double Side) WIDTH = 24". WEIGHT OF ROLL = 48 LBS (APPROX 21.77 KG) LENGTH PER ROLL= 500 FT TYPE = 1 ADVANCE SAMPLE TO BE APPROVED BY CINS GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - DEFSTAN = 93-116/2 OF 2007 THICKNESS=.0.005" (Double Side) WIDTH = 24". WEIGHT OF ROLL = 48 LBS (APPROX 21.77 KG) LENGTH PER ROLL= 500 FT TYPE = 1 ADVANCE SAMPLE TO BE APPROVED BY CINS	
64	SGE112925		047659924451 9 / STRAPS LEATHER HYDRAULIC 4. -3"X4.-3" WEIGHT 5LB THICK 0.0625"		40 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DGB106748	BS-1471-NT4	028259571197 6 / TUBE, ALUMINIUM ALLOY,EXT DIA 2"TH 0.060"WDG 60 SPE BS 1471		30 / METER						TECHNICAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades) GENERAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades)	
66	DGB112358	BS-1471-NT4	028259571197 6 / TUBE, ALUMINIUM ALLOY,EXT DIA 2"TH 0.060"WDG 60 SPE BS 1471		30 / METER						TECHNICAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades) GENERAL SPECIFICATION - BS-1471, Material Grades: 6061, 6063, 5083 (all 03 are acceptable grades)	
67	DGB112362		028359571143 3 / ROD NAVAL BRASS HEX SIZE A/F 1.10"WT PER FT 3.910(LB)		6 / METER						TECHNICAL SPECIFICATION - SPECS BSEN 12163 OF 2024, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet GENERAL SPECIFICATION - SPECS BSEN 12163 OF 2024, Material Grade: CW712R, Material Condition: M, Minimum Running Length upto 06 feet	
68	DGB112170		028359571144 7 / ROD NAVAL BRASS RD DIA 01 INCH	GENERAL USE	20 / METER						TECHNICAL SPECIFICATION - BS EN 12163 OF 2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98LBS, R-LENGTH-03 METERS (EACH)GENERAL SPECIFICATION - BS EN 12163 OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2024, GRADE: CW712R (M) SIZE: RD DIA 01 INCH, WT PER FT 2.98 LBS, R-LENGTH-03 METERS (EACH)	
69	DGB112 179		028359571144 8 / ROD NAVAL BRASS RD DIA 1-1/8,	SERVICE PUMP	20 / METER						TECHNICAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft:3.70 lb authority: br320d BS EN/2163 OF 2024 GRADE CW712R (M) GENERAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft:3.70 lb authority: br320d BS EN/2163 OF 2024 GRADE CW712R (M)	
70	DGB112 381		028359571145 1 / ROD NAVAL BRASS RD DIA 1.50 INCH(38MM), L: 4 MTR, WT/FT: 6.05 LBS		8 / METER						TECHNICAL SPECIFICATION - BSEN 12163 OF 2024, CW712R, MATERIAL CONDITION: R-400. GENERAL SPECIFICATION - BSEN 12163 OF 2024, CW712R, MATERIAL CONDITION: R-400.	
71	DGB112 373		027670000363 4 / SEAL LEAD FOR SEALING COVER JOINT		25 / GROSS						TECHNICAL SPECIFICATION - diameter: 9mm thickness:4mm materiaL: leadGENERAL SPECIFICATION - diameter: 9mm thickness:4mm materiaL: lead	
72	DGB112 360		028359571147 4 / SHEET-NAVAL-BRASS-ANNEALED 48		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
73	DGB104 432		028359571147 4 / SHEET-NAVAL-BRASS-ANNEALED 48		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340GENERAL SPECIFICATION - Size: length: 48 inch width: 30 inch thickness: 0.060 inch BS EN;1653 DESIGNATION; CW719 R340	
74	DGB828 13	HA-680	026859001239 6 / Weighing Machine B/Roo		1 / EACH/NUMBER	HA-680/HA-622					TECHNICAL SPECIFICATION - 1. body weighing: 120 kg maximum weight ; 160 kg (sub- diviions of the	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO JAPANGENERAL SPECIFICATION - 1. body weighing: 120 kg maximum weight ; 160 kg (sub- diviions of the weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO JAPAN	
75	DGB112363	SPECIFICATION BS 887	027459910007 7 / CALIPER VERNIER ENG&MM COMB IN&EXT W/CASE 0-TO9"(0-TO-225MM)	MEASURING TOOL	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION BS 887GENERAL SPECIFICATION - SPECIFICATION BS 887	
76	DGB112352	ME-DIAL-GAU-10	027479274145 6 / DIAL INDICATOR GAUGE FROM 0 TO 10 MM	CHINA,JAPAN, GERMANY,UK MADE	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - Range: 0-10mm Dial Diameter: 52mm Display type: Analogue Sub type: Plunger MAKE/MODEL: UK/USAGENERAL SPECIFICATION - Range: 0-10mm Dial Diameter: 52mm Display type: Analogue Sub type: Plunger MAKE/MODEL: UK/USA	
77	DGB106751	SPEC BSS 2874 CZ 112 M	028370571144 9 / ROD NAVAL BRASS RD DIA 1.25" WT PER FT 4.58LB		20 / METER						TECHNICAL SPECIFICATION - sPECIFICATION:BSEN/2/63 OF 1998 mATERIAL gRADE: CW712RGENERAL SPECIFICATION - sPECIFICATION: BSEN/2/63 OF 1998 mATERIAL gRADE: CW712R	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
78	DGE111973	C1560	0330595713250 / TWINE HEMP WHITING LINE 40YDS STRENDS 3 MIN BREAKING 48 LBS, C1559	ALSO KNOWN AS FISHING LINE TO BS 2019	15 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019GENERAL SPECIFICATION - a. Description: Twine hemp white b. Dimensions: 3 STRD 1.5mm x 218 yard Specifications: BS-2019	
79	DGE112548	BS2019	0330595713257 / TWINE HEMP LOG PLAITED BKG 1000 LBS CIRC 1.125		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 6125/1981GENERAL SPECIFICATION - BS 6125/1981	
80	DGE112549		0330595713259 / TWINE NYLON MARLINE 3 STRD POLISHED MIN BKG STRENGTH 280 LBS		10 / KILOGRAMME						TECHNICAL SPECIFICATION - BKG STRENGTH 280 LBS TWINE NYLON MARLINE 3 STRD POLISHED (Dia 1.10 mm) PAKING: Standard availableGENERAL SPECIFICATION - BKG STRENGTH 280 LBS TWINE NYLON MARLINE 3 STRD POLISHED (Dia 1.10 mm) PAKING: Standard available	
81	DGE112553		0330595713262 / TWINE NYLON ROPING 3 STRD NATURAL FINISH MIN BKG STRGT 50 LB		5 / KILOGRAMME						TECHNICAL SPECIFICATION - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed. GENERAL SPECIFICATION - a. Material: Nylon b. Color: White, Red, Green, Blue c. Style: Twisted d. Line Weight: Light e. Item diameter: 1.5 mm f. Size: 1.5mm x 219 yards g. Min Breaking Strength: 23 KG h. General Specs: Rot Proofed.	
82	DGE110655	0330-1225	0350599233868 / FENDER MARINE LENGTH 9.0 INCHES WIDTH 5.0 INCHES		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT. GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WIDTH: 5.000 INCHES NOMINAL. LENGTH: 9.000 INCHES NOMINAL. SPECIAL FEATURES: CANVAS COVERING FILLED W/KAPOK:FLAT CIRCULAR W/TAB:2 IN NOM O/A HT.	
83	DGB101554	AWS E308-16	028370001185 3 / ELECTRODE WELDING LG 10	WELDING SYSTEMS (STAINLESS STEEL)	10 / KILOGRAMME						TECHNICAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surfaceGENERAL SPECIFICATION - a. Dia: 3.2mm b. Length: 350 mm~ 13.78 inches c. Material: Rutile (E6013) d. Shelf Life: 3-5 year e. Current: 120-180 Amperes f. Application: To weld Mild Steel on surface	
84	DGB72878		027370273139 5 / AXE HAND 3.5 LBS		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DGB111960	BS 1083	025770419500 8 / NUT-PLAIN-HEXAGON-THREAD-SIZE 0.750	BRASS TYPE	4 / DOZEN						TECHNICAL SPECIFICATION - material grade i.e SS347 bs 970, 60r7aGENERAL SPECIFICATION - material grade i.e SS347 bs 970, 60r7a	
86	DGD110048		003250003201 7 / SPOON SALT FOR OCNS		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size: 2.5 to 3 ml Color: Silverware Length:6.7" Diameter: 1.1" Width: 1" Made with stainless steel Material S/S 304/316 FOOD GRADE NON Magnetic (LOCAL) size and material grade: ss 304/316 (food grade) GENERAL SPECIFICATION - Size: 2.5 to 3 ml Color: Silverware Length: 6.7" Diameter: 1.1" Width: 1" Made with stainless steel Material S/S 304/316 FOOD GRADE NON Magnetic (LOCAL) size and material grade: ss 304/316 (food grade)	
87	DGB111983	Material Grade EN 4140	025770941150 6 / NUT-PLAIN-HEXAGON-		32 / DOZEN						TECHNICAL SPECIFICATION - material specs AISI 4140(PD 970: 2005 material GRADE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			THREAD-SIZE. 625LH.550"								708M40/42CRM04 OEM COC/mtc REQUIREDGENERAL SPECIFICATION - material specs AISI 4140(PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED	
88	DGH106 481		056159521849 2 / CABLE, power, ELECT ELASTOMERI C LFH , 3 cores, cond276/0.40 440 v, 160 amp, 100 lg.		100 / METER						TECHNICAL SPECIFICATION - 3 CORES, COND276/0.40 440 V, 160 AMP, 100 LG. DEFSTAN 02-526 GENERAL SPECIFICATION - 3 CORES, COND276/0.40 440 V, 160 AMP, 100 LG. DEFSTAN 02-526	
89	SGP112 920		046259943239 5 / PAPER WRAPING WATER PROOF WD. 36"LG.100YD PER ROL 2PLY INTO 1		1400 / METER						TECHNICAL SPECIFICATION - a. GSM: 100-120 b. Width: 01 meter c. Length: 100 meter per roll d. Colour: BrownGENERAL SPECIFICATION - a. GSM: 100-120 b. Width: 01 meter c. Length: 100 meter per roll d. Colour: Brown	
90	DGE112 554	NO DATA AVAILABL E	4240PK507817 7 / GUNNY BAGS		1200 / EACH/N UMBER						TECHNICAL SPECIFICATION - TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014. GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014.	
91	DGE111908	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		1000 / EACH/NUMBER						TECHNICAL SPECIFICATION - TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014. GENERAL SPECIFICATION - TECHNICAL SPECIFICATIONS= 1. MATERIAL= JUTE, 2. TYPE OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BAGS= HESSIAN BAG (1/1 PLAIN), 3. DIMENSION (INCHES/ CM) = 40X20/101X51 (TOLERANCE: ±1.5 INCH/ 04 CM), 4. PORTER X SHOTS/ENDS X PICKS PER DM= 11X12/47X47, 5. WEIGHT OF FABRIC (GSM) = (305 GSM), 6. WEIGHT OF BAG= 350 GM, 7. TENSILE STRENGTH= WARP X WEFT= 112 X 120 (KGF). 8. SEAM STRENGTH= WARP X WEFT 34X36 (KGF). 9. TEST STANDARD METHOD= TENSILE STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13934-1: 2013 AND SEAM STRENGTH SHALL BE DETERMINED IN ACCORDANCE WITH ISO 13935-1: 2014.	
92	DGE111062	NO DATA AVAILABLE	4240505088705 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	TO COVER/CAMOFLAGE THE 14.5MM GUNS	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
93	DGE110471	NO DATA AVAILABL	424050508870	TO COVER/CAMO	2 / EACH/N						TECHNICAL SPECIFICATION - 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	5 / CAMOUFLAGE NETS, SIZE 26 X 26 FT	FLAGE THE 14.5MM GUNS	UMBER						SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED. GENERAL SPECIFICATION - 1. SPECIFICATIONS= POLYESTER FABRIC: GRADE: 300D, SAFETY: FIRE RESISTANT, ROT PROOF AND WATER PROOF. 2. MATERIAL COMPOSITION= 100% POLYESTER. 3. LOOP INTERVALS, FOR JOINING MULTIPLE NETS (06 INCHES DISTANCE LOOP TO LOOP). 4. COLOR LIGHT/ DARK GREEN, ROT PROOF WITHOUT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											USE OF METALLIC OBJECT (WITH COLOR SHADE ARMY GREEN, BROWN AND GRAY COMBINATION). 5. COLOUR CODE FOR MATCHING OF CAMOUFLAGE AND NET SHOULD BE COMBINATION OF FOLLOWING COLOR CODE= (A). EBONY (50654D), (B). ARTICHOKE (9C9177), (C). QUINCY (655949), (D). DARK CHARCOAL (313831). 6. PACKING OF COMPLETE NET ALONGWITH FOLLOWING ACCESSORIES= (A). ROPE= (01 X BUNDLE= DIAMETER: 10MM, CIRC: 1.25-INCH & LENGTH: 50 FT WITH CAMOUFLAGE COLOUR. (B). IRON NAILS= 06 STANDARD, (DIAMETER: 01 INCH & LENGTH: 18 INCH) (C). HAMMER: 01 IN NUMBER. (D). IRON POLE: 01 X 4 ADJUSTABLE (DIA: 06 INCH, LENGTH: 08 FT, QTY: 06 IN NOS WITH SEAMLESS OR WELDED.	
94	DGE99283		4020999237137 / ROPE NYLON HAWSERLAID, 3-STRND, Z-LAY, TYPE-1, NOM DIA: 64-MM, CIRC: 08-INCH,	NOR-SHIPS-USE-NASAR	120 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2021, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2019, 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2019, 4. OEM WILL PROVIDED CERTIFICATE OF RAW MATERIALS I.E DESCRIPTION OF MATERIAL AND SPECIFICATIONS OF MATERIAL, 5. OEM COC REQUIRED, 6. FURNISH CALIBRATION CERTIFICATE WIL BE PROVIDED BY OEM, 7. OEM OF ROPE MUST BE APPROVED BY MOD (UK)/RN/ RELATED COUNTRY, 8. LENGTH PER COIL: 120 FATHOM. 9. VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/ LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
95	DGE99002		5330006183221 / PACKING MATERIAL SIZE 3/16".		10 / FOOT						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
96	DGE98120		5330002440192 / SHEET RUBBER SOLID 0.125 X24X324 INCH		80 / FOOT						TECHNICAL SPECIFICATION - MILR900 GENERAL SPECIFICATION - MILR900	
97	DGE109910	CM6538-000	5970705044352 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		31 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Temperature Range: -40 to 90 °C Low Halogen: YesGENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes	
98	DGE107790	DATA AVAILABLE	0461500000152 / POLISHING-FELT ROUND		8 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch GENERAL SPECIFICATION - DIA 250 MM THICKNESS 75 MM (15 TO 18 LAYERS) Thickness Range: 10 to 40 mm (One Piece) 40 to 120 mm (Two Piece Pasted) Center Hole : 10 mm or on Request Material :off white/white or grey sheep's wool Detailed Specification Diameter = 10 Inch Thickness = 1.5 Inch	
99	DGE103451	NO DATA AVAILABLE	0432500000027 / HELMET PROTECTIVE DESPATCH RIDER WITH VISOR SIZE 6 3/4		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218) GENERAL SPECIFICATION - Item Specification :MAKE-JEIKAI, MODEL-JK-312 with double Glass, OEM/COUNTRY MR Enterprises Pakistan. OEM Authorization dot certified approved (FMUSS NO 218)	
100	DGE112689		8340705087917 / TENT BIVOUAC MOSQUITO	O/T FLY MADE OF COTT/CNVAS OLIVE GREEN	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - FOLD & FLY TWO COLOUR JUNGLE GREEN / OLIVE GREEN OUTER FLY MADE OF COTTON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PROOF SIZE 10.6X6 FT								CANVAS MOSQUITO NETTING COVER EACH END water proof (Inner Mosquito Net Fabrics) Accessories: Pole 7' standing 02 Pole 5' width 02 Nail 1' standing 10 Cotton rope 6'side 08 Cotton rope 10' front & back 02GENERAL SPECIFICATION - FOLD & FLY TWO COLOUR JUNGLE GREEN / OLIVE GREEN OUTER FLY MADE OF COTTON CANVAS MOSQUITO NETTING COVER EACH END water proof (Inner Mosquito Net Fabrics) Accessories: Pole 7' standing 02 Pole 5' width 02 Nail 1' standing 10 Cotton rope 6'side 08 Cotton rope 10' front & back 02	
101	DGB102163	NO DATA AVAILABLE	0268500000061 / SCALE-SPRING-BALANCE-20-STONE-280-LBS		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Capacity :Maximum Usage/ Application : To hang load Material : Steel GENERAL SPECIFICATION - Capacity :Maximum Usage/ Application : To hang load Material : Steel	
102	DGD109629		7340705101874 / Cruests Complete Small	MESS UTENSILS, OFFICER WARD PNS SHIFA	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - As per existing Stock, Make/Brand is Regal China with Blue Shell & PN Crest embossed on itemGENERAL SPECIFICATION - As per existing Stock, Make/Brand is Regal China with Blue Shell & PN Crest embossed on item	
103	DGD109639	NO DATA AVAILABLE	0035500000274 / BOARD KNIFE		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952GENERAL SPECIFICATION - size; 10" material.; 100 % steel stainless make/brand kiwi country of origin pakistan ref haibat 03/7765952	
104	DGD109634		0034546000434 / DISHES VEGETABLE ROUND E W W		3 / EACH/NUMBER	cera-e-noor					TECHNICAL SPECIFICATION - dia; 6" material; porcelain blue crested with pn logoGENERAL SPECIFICATION - dia; 6" material;	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			O COVER B/C								porcelain blue crested with pn logo	
105	DGD109640	NO DATA AVAILABLE	0035500000366 / KNIFE COOK 6 INCH		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Blade Length = 6 inch Total Length = 11-11.5 inch Blade Material = SS 420 Handle = Full Steel Thickness = 2.2 mm Weight = 140-160 g Finish = Mirror Polish, plain Usage = Kitchen/ CommercialGENERAL SPECIFICATION - Blade Length = 6 inch Total Length = 11-11.5 inch Blade Material = SS 420 Handle = Full Steel Thickness = 2.2 mm Weight = 140-160 g Finish = Mirror Polish, plain Usage = Kitchen/ Commercial	
106	DGE98123		0476546004776 / BRUSH SABLE HAIR NO-3 FOR WRITING		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DGE64931	CTLCB10008025	5340735267410 / CANTILEVER BRACKET 3' (1000 X 80 X 2.5MM)		72 / EACH/NUMBER	CANTILEVER BARACKET 3' CTLCB10008025					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONSGENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	