Pakistan State Oil Company Limited
PSO House, Khayaban-e-Iqbal, Clifton, Karachi-75600, Pakistan
Telephone (021) 9203866-85 Fax (021) 9203796

REQUEST FOR QUOTATION

(THIS IS PRICE ENQUIRY-NOT AN ORDER)
SAP No.6100019077

RFQ No	LM-20210MS
DATE	19.11.2026

Company PSO Dummy Vendor
PAKISTAN

QUOTATION REQUIRED

ON (Date)	02.12.2026	BY (Time)	

Please quote your best price for all items of following specifications. Please read the instructions attached herewith EARNEST MONEY % Rs._____ PO/DD NO. _____

Title: Procurement of Stainless Steel Standard-Size 3 Bag Filter Housing and Cartridge Filter Housing, Including Filter Bags and Cartridges, for Drum Filling Line No. 2 at PSO LMT.

S.No.	Description/Specifications	Location	Unit	Qty	Unit Price Rs.	Amount Rs.
1	**FILTER ASSY.,** STAINLESS STEEL FILTER BAG HOUSINGS WITH ACCESSORIES (STANDARD SIZE-3) 1. Description: Supply of a Product Filter Bag assembly Housing Shell / Body Cylindrical pressure vessel made of Stainless Steel-304. Designed to accommodate a filter Bag in standard bag filter size #3 configuration. As defined below. 2. Filter Housing: Capacity: Single Bag Filter Housing (standard Ring Neck arrangement) (Stainless Steel Housing Height: 72"inch) (Stainless Steel Housing Shell Outer Dia: 13"inch) (Stainless Steel Housing Top Cover Dia: 16" inch) (Stainless Steel Perforated Bucket Dia: 10"inch) (Stainless Steel Perforated Bucket Height: 52"inch) (Stainless Steel Housing Plate and Bucket Thickness: 3mm) (Inlet and Outlet Connection Port Size: 4"inch) (Inlet and Outlet Connection Port Type: Socket Internal Threaded) (Design Pressure: 8 Bar) (Working Pressure: 3 Bar) (Design Temperature: 200 degrees Celsius) (Working Pressure: 100 degrees Celsius) Flow Direction: Upper Shell Side Inlet, Lower Shell Side Outlet (typical) -Material of Construction: Stainless Steel AISI-304 -Connections: Inlet and outlet as per system requirement (flanged/threaded) -Design: Single bag filter housing with easy arrangement for installation and removal of bag filter) -Housing Lid Sealing: Gasketed / O-ring cover for leak-free Operation -Perforated Basket Sealing: sealing ring, molded collar, or neck ring for leak-free operation -Pressure Rating: Suitable for the operating pressure of the process: Approx. 3 bar -Finish: Corrosion-resistant, polished / passivated surface	**LMT**	**EA**	1		

Pakistan State Oil Company Limited
PSO House, Khayaban-e-Iqbal, Clifton, Karachi-75600, Pakistan
Telephone (021) 9203866-85 Fax (021) 9203796

REQUEST FOR QUOTATION

(THIS IS PRICE ENQUIRY-NOT AN ORDER)
SAP No.6100019077

RFQ No	LM-20210MS
DATE	19.11.2026

Company PSO Dummy Vendor
PAKISTAN

QUOTATION REQUIRED

ON (Date)	02.12.2026	BY (Time)	

Please quote your best price for all items of following specifications. Please read the instructions attached herewith EARNEST MONEY % Rs._____ PO/DD NO. _____

Title: Procurement of Stainless Steel Standard-Size 3 Bag Filter Housing and Cartridge Filter Housing, Including Filter Bags and Cartridges, for Drum Filling Line No. 2 at PSO LMT.

S.No.	Description/Specifications	Location	Unit	Qty	Unit Price Rs.	Amount Rs.
	3. Operational Requirements: -Top Cover / Head: Removable top for Bag replacement and maintenance. -Perforated Basket Support Plate holds and aligns securely. -Perforated Basket molded collar or neck ring to hold down the basket collar. Ensures proper sealing and prevents basket/bag movement. -Fastening System Swing bolts/eye bolts/clamps for pressure sealing. -Equipped with two pressure gauges for measuring the pressure inside the housing in both compartments. -Compatible with finished lubricants -Designed for ease of maintenance and minimal downtime. - Air Vent should be installed with an S.S. ball valve - Drain Point should be available at the bottom of the housing with S.S 1"inch ball valve. - Heavy-duty support legs for floor-mounted type					
2	**FILTER ASSY.,**	**LMT**	**EA**	1		
	STAINLESS STEEL FILTER CARTRIDGE HOUSINGS WITH ACCESSORIES (STANDARD SIZE-3) 1. Description: Supply of a Product Filter cartridge assembly Housing Shell / Body Cylindrical pressure vessel made of Stainless Steel-304. Designed to accommodate a 14-filter cartridge configuration. As defined below. 2. Filter Housing: Capacity: 14-cartridge filter housing (standard top-to-bottom arrangement) (Stainless Steel Housing length: 40"inches) (Separate containers for inlet and outlet products) (Stainless Steel Housing Shell Outer Dia: 14"inch) (Stainless Steel Housing Plate and Bucket Thickness: 3mm) (Inlet and Outlet Connection Port Size: 3"inch) (Design Pressure: 8 Bar) (Working Pressure: 3 Bar) (Design Temperature: 200 degrees Celsius)					

Pakistan State Oil Company Limited
PSO House, Khayaban-e-Iqbal, Clifton, Karachi-75600, Pakistan
Telephone (021) 9203866-85 Fax (021) 9203796

REQUEST FOR QUOTATION

(THIS IS PRICE ENQUIRY-NOT AN ORDER)
SAP No.6100019077

RFQ No	LM-20210MS
DATE	19.11.2026

Company PSO Dummy Vendor
PAKISTAN

QUOTATION REQUIRED

ON (Date)	02.12.2026	BY (Time)	

Please quote your best price for all items of following specifications. Please read the instructions attached herewith EARNEST MONEY % Rs._____ PO/DD NO. _____

Title: Procurement of Stainless Steel Standard-Size 3 Bag Filter Housing and Cartridge Filter Housing, Including Filter Bags and Cartridges, for Drum Filling Line No. 2 at PSO LMT.

S.No.	Description/Specifications	Location	Unit	Qty	Unit Price Rs.	Amount Rs.
	(Working Pressure: 100 degrees Celsius) Flow Direction: Upper Shell Side Inlet, Lower Shell Side Outlet (typical) -Material of Construction: Stainless Steel AISI-304 -Connections: Inlet and outlet as per system requirement (flanged/threaded) -Design: 14 filter cartridge housing with easy arrangement of installation and removal of cartridges) -Housing Lid Sealing: Gasketed / O-ring cover for leak-free Operation -Perforated Basket Sealing: sealing ring, molded collar, or neck ring for leak-free operation -Pressure Rating: Suitable for the operating pressure of the process: Approx. 3 bar -Finish: Corrosion-resistant, polished / passivated surface 3. Operational Requirements: -Top Cover / Head Removable top for cartridge replacement and maintenance. Swing bolts/eye bolts/clamps for pressure sealing. -Equipped with two pressure gauges. For measuring the pressure inside the housing in both compartments. -Compatible with finished lubricants -Designed for ease of maintenance and minimal downtime. - Air Vent should be installed with an S.S. ball valve - Drain Point should be available at bottom of the housing with S.S 1"inch ball valve. - Heavy-duty support legs for floor-mounted type					
3	**Bucket type filter bag - 25 microns** Filter Bag (25 µm) Parameter: Specification Filter Type: Industrial Liquid Filter Bag Bag Size: Standard Size #3 Diameter: 14 inches Length / Height: 32 inches	**LMT**	**EA**	250		

Pakistan State Oil Company Limited
PSO House, Khayaban-e-Iqbal, Clifton, Karachi-75600, Pakistan
Telephone (021) 9203866-85 Fax (021) 9203796

REQUEST FOR QUOTATION

(THIS IS PRICE ENQUIRY-NOT AN ORDER)
SAP No.6100019077

RFQ No	LM-20210MS
DATE	19.11.2026

Company PSO Dummy Vendor
PAKISTAN

QUOTATION REQUIRED

ON (Date)	02.12.2026	BY (Time)	

Please quote your best price for all items of following specifications. Please read the instructions attached herewith EARNEST MONEY % Rs._____ PO/DD NO. _____

Title: Procurement of Stainless Steel Standard-Size 3 Bag Filter Housing and Cartridge Filter Housing, Including Filter Bags and Cartridges, for Drum Filling Line No. 2 at PSO LMT.

S.No.	Description/Specifications	Location	Unit	Qty	Unit Price Rs.	Amount Rs.
	Micron Rating: 25 µm nominal Filter Media: Polypropylene (PP) needle felt Construction: Seam-stitched (double-stitched) with overlock Neck Type: Embedded ring neck Ring Material: Stainless Steel Ring Diameter: Compatible with standard Size #3 housing Filtration Mechanism: Depth filtration Surface Finish: Mirror Polished Operating Temperature: Up to 90 °C (typical for PP) Recommended Differential Pressure: 0.5 # 1.5 bar Maximum Differential Pressure: 2.5 bar Chemical Compatibility: Suitable for mineral oils, lubricants<(>,<)> hydrocarbons					
4	**FILTER CARTRIDGE THREADED TYPE** Filter Cartridge (10 µm) Parameter: Typical Specification Filter Type: String Wound Filter Media: 100% Polypropylene Yarn Core Material: Polypropylene Cartridge Length: 40" inch Outside Diameter: 60 # 65 mm Micron Rating: 10 µm Filtration Mechanism: Depth Filtration Operating Temperature: Up to 100#120 °C End Connection: Double Open End (DOE) Typical Application: Lube oil, chemicals, solvents GENERAL TERMS & CONDITIONS . The scope of work includes the manufacturing and supply of the filter housings, complete with all necessary provisions, arrangements<(>,<)> and interfaces for proper installation and integration of the bag filter within the housing. ·,,The quoted price shall be deemed all-inclusive, complete cost of materials, transportation, loading, and satisfactory delivery of	**LMT**	**#**	250		

Pakistan State Oil Company Limited
PSO House, Khayaban-e-Iqbal, Clifton, Karachi-75600, Pakistan
Telephone (021) 9203866-85 Fax (021) 9203796

REQUEST FOR QUOTATION

(THIS IS PRICE ENQUIRY-NOT AN ORDER)
SAP No.6100019077

RFQ No	LM-20210MS
DATE	19.11.2026

Company PSO Dummy Vendor
PAKISTAN

QUOTATION REQUIRED

ON (Date)	02.12.2026	BY (Time)	

Please quote your best price for all items of following specifications. Please read the instructions attached herewith EARNEST MONEY % Rs._____ PO/DD NO. _____

Title: Procurement of Stainless Steel Standard-Size 3 Bag Filter Housing and Cartridge Filter Housing, Including Filter Bags and Cartridges, for Drum Filling Line No. 2 at PSO LMT.

S.No.	Description/Specifications	Location	Unit	Qty	Unit Price Rs.	Amount Rs.
	material at LMT. ·,,All applicable government taxes, duties, levies, and other statutory charges shall be clearly identified and included in the quoted rates. No additional payment shall be entertained under these heads. ·,,The Contractor shall be solely responsible for arranging and bearing the cost of transportation of the filter housing, equipment, and associated materials to LMT. ·,,All loading, unloading, transportation, site handling, lifting, and rigging activities shall be carried out by the Contractor using appropriate equipment, certified lifting accessories (where applicable), and competent manpower. ·,,The Contractor shall ensure that all transportation and handling activities are conducted safely and in accordance with applicable site safety requirements. ·,,Any damage to the supplied materials, equipment, or existing site facilities resulting from improper handling, transportation, or lifting shall be rectified by the Contractor at its own cost. ·,,All materials and components supplied shall be brand new, unused, and free from defects. ·,,The materials, fabrication, finishing, and overall workmanship shall comply with the applicable engineering specifications, relevant industry standards, and approved technical requirements of LMT. ·,,The Contractor shall ensure that all dimensions, interfaces<(>,<)> connections, and provisions are compatible with the intended installation and operation of the bag filter. ·,,Any defective materials, fabrication deficiencies, or substandard workmanship identified during inspection or execution shall be rectified or replaced by the Contractor at its own cost, without any additional financial liability to LMT. ·,,LMT reserves the right to inspect the materials and workmanship at any stage of fabrication or execution. Such inspection shall not relieve the Contractor of its contractual obligations. ·,,The Contractor shall complete the entire scope of work within the mutually agreed delivery and completion schedule, as specified in the Purchase Order (PO) or otherwise agreed in writing by LMT.					

Pakistan State Oil Company Limited
PSO House, Khayaban-e-Iqbal, Clifton, Karachi-75600, Pakistan
Telephone (021) 9203866-85 Fax (021) 9203796

REQUEST FOR QUOTATION

(THIS IS PRICE ENQUIRY-NOT AN ORDER)
SAP No.6100019077

RFQ No	LM-20210MS
DATE	19.11.2026

Company PSO Dummy Vendor
PAKISTAN

QUOTATION REQUIRED

ON (Date)	02.12.2026	BY (Time)	

Please quote your best price for all items of following specifications. Please read the instructions attached herewith EARNEST MONEY % Rs._____ PO/DD NO. _____

Title: Procurement of Stainless Steel Standard-Size 3 Bag Filter Housing and Cartridge Filter Housing, Including Filter Bags and Cartridges, for Drum Filling Line No. 2 at PSO LMT.

S.No.	Description/Specifications	Location	Unit	Qty	Unit Price Rs.	Amount Rs.
	·,,In the event of an unjustified delay attributable to the Contractor, Liquidated Damages (LD) shall be imposed at the rate of 0.1% of the total Purchase Order value per calendar day of delay, subject to a maximum of 10% of the total Purchase Order value. ·,,The Contractor shall ensure that the supplied filter housing is complete in all respects and suitable for the intended installation and operation of the bag filter and cartridge filter. ·,,The Contractor shall account for all necessary materials<(>,<)> accessories, structural provisions, connections, and fabrication requirements essential for the proper completion of the job.					